

Predict the duration of forestfires using machine learning methods

Constantina Kopitsa¹, Ioannis G. Tsoulos^{2*}, Vasileios Charilogis³, Athanassios Stavrakoudis⁴

¹ Department of Informatics and Telecommunications, University of Ioannina, Greece; k.kopitsa@uoi.gr

² Department of Informatics and Telecommunications, University of Ioannina, Greece; itsoulos@uoi.gr

³ Department of Informatics and Telecommunications, University of Ioannina, Greece; v.charilog@uoi.gr

⁴ Department of Economics, University of Ioannina, Ioannina, Greece; astavrak@uoi.gr

* Correspondence: itsoulos@uoi.gr

Abstract: Forest and urban fires are a major problem in the modern era that tests the endurance of governments to extinguish them. Fires can cause economic and ecological problems especially in the summer months. In modern times, the rapid development of Artificial Intelligence can be a weapon for predicting the evolution of fires or even for their prevention. Specifically, through Machine Learning, which is one part of Artificial Intelligence several methods have been incorporated to detect the duration of fires using data which are freely available from the Fire Service of Greece for a period of 10 years. For this purpose, a wide range of machine learning techniques were used on this data and the experimental results were more than encouraging.

Keywords: Forest fires; Machine learning; Neural networks; Decision trees

1. Introduction

Forests play an important role in the ecological balance [1] of our planet as well as in our everyday life [2]. However, these ecosystems are threatened by various risks, the most important of which are fires [3–5]. Forest fires destroy the forest ecosystem [6–8] and can have devastating effects on local economies [9,10], with a significant impact also on tourism development [11–13] as well as in human health [14–16].

Since the risks of fires are great, governments must take measures and review them in the direction of fire prevention by analyzing data collected from fires that have broken out in recent history [17–19]. Also, local authorities have used techniques for forest fire monitoring, such as small UAVs [20], usage of a monitoring system based on GPRS and ZigBee wireless network [21], the iForestFire system [22] etc. Merino et al. suggested an Unmanned Aircraft System (UAS) [23] for forest fire monitoring. Also, Aslan et al. proposed a system [24] of wireless sensor networks for forest fire detection and monitoring. Recently, Serna et al. suggested a distributed system for fire monitoring using wireless sensor networks [25].

During recent years, machine learning techniques have started to play an important role in the prevention and treatment of forest fires. For example, Dwiasnati and Devianto proposed the usage of various machine learning methods for the classification of forest fire areas [26]. Also, Pang et al. suggested the usage of a series of machine learning models to forest fire occurrence prediction in China [27]. Dampage et al. suggested a system of wireless sensor networks with data handled by machine learning models for the detection of forest fires [28]. Shao et al. proposed a mapping of China's forest fire risks using a series of machine learning models [31]. A parallel SVM model is also suggested by Singh et al. [29] for forest fire prediction on data collected from India and Portugal. A survey on machine learning models used for forest fire prediction can be found in the work of Abid [30].

In addition, image processing has been established as a fire detection method. In this direction, a multitude of techniques have been presented that also take advantage of

Citation: Kopitsa, C.; Tsoulos, I.G.; Charilogis V., Stavrakoudis A. Predict the duration of forestfires using machine learning methods. *Journal Not Specified* **2024**, *1*, 0. <https://doi.org/>

Received:

Revised:

Accepted:

Published:

Copyright: © 2024 by the authors. Submitted to *Journal Not Specified* for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

machine learning methods, such as the work of Vicente and Guillemant that presented a method for early smoke source detection [32]. Also, Yan et al. proposed a method [33] that combined image processing techniques and neural networks for forest fire recognition. Mubarak et al. suggested a rule - based image processing algorithm [34] for forest fire detection. Convolution neural networks were utilized in the work of Wang et al. [35] for forest fire image recognition. Also, wavelet analysis was used in the work of Jiao et al. [36] for forest fire detection.

This research work focuses on the use of machine learning techniques to predict the duration of forest fires, which occurred in Greece from 2014 until 2023. The data was collected by the Hellenic Fire Service and then, after clearing missing records, the data was digitized and one of three categories was assigned to every pattern: fires of short duration, fires of medium duration and fires of long duration. The prediction of the duration of a fire is important as in this way, on the one hand, an estimate can be made of the expected damage that will be caused in the area, and on the other, the human resources required to extinguish the fire can be calculated. Similar works in this area include the work of Liang et al. that used the duration of a wildfire and the burnt area to determine the scale of wildfires using neural networks [37]. Also, KC et al. proposed a Surrogate model [38] to model the size of a wildfire over time, using data collected from wildfires in Tasmania. Furthermore, Xi et al. proposed [39] the application of joint mixture models to model the duration and the size of wildfires.

The rest of this article is divided as follows: in section 2 the used dataset is described as well as the incorporated machine learning methods, in section 3 the experimental results are fully described and finally in section 4 some conclusions are discussed accompanied by some guidelines for future research.

2. Materials and Methods

This section presents the datasets that will be used in the experiments as well as the machine learning techniques that will be applied to these datasets.

2.1. The used datasets

In this research work, open data was used which is available from the Hellenic Fire Service at the relevant link https://www.fireservice.gr/en_US/synola-dedomenon (accessed on 14 September 2024). The data was obtained for the years 2014-2023 and data preprocessing techniques were applied before inputting the data into machine learning models.

The initial datasets contain information in both numerical and alphanumeric form, such as the area in which the forest fire occurred or the fire station that extinguished it. Therefore, the first step in preprocessing the data was to digitize the columns that contained numerical information and replace them with a discrete integer. The next important step in the preprocessing of the original data is to delete the records that contain empty values in various attributes. This could happen, for example, if a value was not available at the time of entry. Those records in which the duration of the fire was zero were also deleted. Then, to create the exit category, the duration of the forest fire was converted into minutes. In order to address highly skewed and non-normal distribution of the dependent variable (fire duration) we used the commonly applied method of natural log transformation for minutes. This allowed the variance stabilization of the dependent variable and transformed its distribution much closer to normal, allowing a better allowance for linear modeling and greatly reducing the impact of outliers [40]. Subsequently, three distinct values were created depending on the logarithmic value of the duration in minutes of the forest fire: one value is used for short duration forest fires, one distinct class for forest fires of medium duration and one class for the forest fires with long duration. This value will be used as the target value in running the experiments. The preprocessing steps are graphically illustrated in Figure 1.




Figure 1. The steps of the preprocessing that were applied on the original datasets.

Having performed the previously mentioned preprocessing steps, the final datasets contain 25 features and the following information about the forest fires:

1. Fire department.
2. Province.
3. Season.
4. Burnt area: forest area, grove, grasslands, reeds/swamps, agricultural lands, cover crop, garbage dumps.
5. Personnel: Firefighters, volunteers, army, etc.
6. Vehicles: firefighting, tanks, etc.
7. Aerial means: helicopters and other aircrafts.

2.2. The used machine learning methods

A number of machine learning techniques were used to efficiently find classes in the datasets of the previous subsection. These techniques cover a wide range of techniques available in the field of machine learning and are presented in more detail below.

2.2.1. Bayesian Networks

Bayesian networks are probabilistic models based on direct acyclic graphs [41,42] and they have been applied with success in various cases. For example, Friedman et al. used Bayesian Networks to analyze expression data [43]. Also, Cai et al. used Bayesian Networks in fault diagnosis [44] and Barton et al. proposed the use of Bayesian Networks to environmental problems [45]. In the case of forest fires, Bayesian Networks have been used in many cases, such as to predict and analyze possible fire causes [46]. The study was conducted in Mugla of Turkey. Also, Bayesian networks were used to model the cascading impacts of drought and forest fire in a recent study [47]. Also, Bayesian Networks were combined with deep learning for detection of fires from video frames [48].

2.2.2. Naïve Bayes

The Naïve Bayes is a supervised machine learning algorithm, used for classification tasks. This classifier, uses principles of probability in order to perform classification tasks [49,50]. This algorithm has been incorporated in many research areas, such as document classification [51], traffic risk management [52], network intrusion detection [53] etc. Also,

the Naive Bayes has been used in forest fire issues in a series of papers. For example, Nugroho et al. proposed a system for forest fire prevention using a combination of a wireless sensor network and a Naïve Bayes classifier [54]. A classification of hotspots causing forest fires using the Naive Bayes algorithm is proposed in the work of Zainul et al. [55]. Karo et al. proposed a methodology to classify wildfires using feature selection and the Naive Bayes among other machine learning methods [56]. Also, a variant of the Naïve Bayes Algorithm was suggested by Shu et al. for forest fire prediction [57].

2.2.3. Logistic Regression

Like the previously mentioned algorithms, Logistic Regression, works also with machine learning classification and it can be considered as a data analysis technique used to predict probabilities [58]. Cabrera proposed the Logistic Regression for higher school decisions [59]. Also, Lawson et al. proposed the usage of Logistic Regression method to analyze customer satisfaction data [60]. Hu and Lo used the Logistic Regression technique to model urban growth in their paper [61]. This method has been used also in a series of issues involving forest fires, such as human - caused wildfire risk estimation [62], prediction of wildfire vulnerability [63], probabilistic modeling of wildfire occurrence [64], analysis of wildfire danger [65] etc.

2.2.4. Artificial neural networks

Artificial neural networks (ANNs) are parametric models [66,67], where a set of parameters, commonly called weights, must be calculated to be adapted to classification or regression data. This machine learning model has been utilized in a variety of scientific and real - world problems, such as physics problems [68–70], solving differential equations [71,72], solar radiation prediction [73], agriculture problems [74,75], problems appeared in chemistry [76–78], wind speed forecasting [79], economics problems [80–82], problems related to medicine [83,84] etc.

In the area of forest fire prediction and observation, a number of works using artificial neural networks have been published. Hossain et al. used ANNs to detect flames and smoke from static image features [85]. Lall and Mathibela utilized neural networks to predict the risk of wildfires in the city of Cape Town [86]. Also, Sayad et al. used neural networks among other machine learning techniques for predictive modeling of wildfires from data collected from NASA's Land Processes Distributed Active Archive Center (LP DAAC) [87]. Artificial neural networks and meteorological data were used in the work of Liang et al. to predict the scale of wildfires [88]. Also, a case study for predicting wildfires for a Chinese province using neural networks was published recently by Gao et al. [89].

2.2.5. The J48 algorithm

The J48 algorithm [90] is one of the most used supervised machine learning algorithms, used to construct decision trees for classification data. This method was tested on a series of classification problems, such as prediction of diabetes [91], network intrusion detection [92], classification of criminal data [93], fingerprint gender classification [94], fake news classification [95] etc. Also, the J48 algorithm was used to predict forest fires using data from Slovenia in a recent work [97]. A similar study was performed in Algeria using the J48 algorithm among other machine learning models [97].

2.2.6. Random Forests

Random Forest [98,99] is a popular supervised machine learning algorithm, used to construct decision trees for classification problems. The method of Random Forests has proven its adaptability and effectiveness in a number of difficult problems, such as remote sensing classification [100], ecology issues [101], bionformatics [102], text categorization [103], network intrusion detection [104] etc. Moreover, random forest was incorporated for forest fire prediction, such as in the work of Latifah et al., where random forests were applied to predict forest fires in Borneo [105]. Also, Malik et al. proposed the usage of

Random Forests for wildfire risk prediction in Northern California [106]. Also, Gao et al. performed a forest fire risk prediction [107] in China using a combination of Random Forests and a neural network trained with the Back Propagation method [108].

3. Results

The experiments were conducted using the freely available programming tool of WEKA [109]. The software, which is written in the JAVA programming language to be portable, can be downloaded freely from <https://ml.cms.waikato.ac.nz/weka/> (accessed on 14 September 2024) or it can be found in the repositories of most Linux systems. The WEKA software is a collection of machine learning and data analysis tools and it contains also some visualization tools for modeling. The WEKA has been used with success in many cases, such as educational problems [110,111], medical problems [112,113] etc. The validation of the conducted experiments was performed using the ten - fold cross validation technique. The experiments were carried out on an AMD Ryzen 5950X with 128GB of RAM, running the Debian Linux operating system. The experimental results using the methods mentioned in the previous section and the 10 modified datasets from the Hellenic Fire Service are listed in Table 1. The following applies to the tables of experimental results:

1. The numbers in cells denote average classification error as calculated on the test set.
2. The column YEAR denotes the year where the machine learning methods were applied.
3. The column BAYESNET stands for the application of the Bayesian Network method.
4. The column NAIVEBAYES denotes the application of the Naïve Bayes algorithm.
5. The column LOGISTIC represents the application of the Logistic Regression algorithm.
6. The column MLP denotes the application of a neural network to the dataset.
7. The column J48 denotes the application of the J48 method to the forest fire data.
8. The column RANDOMFOREST denotes the usage of the Random Forest method to the data.
9. The row AVERAGE denotes the average classification error for all datasets.

Table 1. Experimental results using various machine learning models for 10 years of observations. The numbers in cells denote average classification error as measured on the test set.

YEAR	BAYESNET	NAIVEBAYES	LOGISTIC	MLP	J48	RANDOMFOREST
2014	11.44%	12.89%	9.81%	11.37%	10.04%	9.42%
2015	11.08%	11.26%	9.53%	10.65%	9.51%	8.95%
2016	25.71%	13.00%	3.41%	3.90%	3.65%	3.00%
2017	11.04%	11.51%	9.48%	10.08%	10.30%	9.29%
2018	11.20%	10.46%	9.09%	9.48%	9.27%	8.58%
2019	9.61%	9.25%	8.29%	8.53%	9.08%	8.01%
2020	18.00%	6.72%	5.54%	5.97%	6.09%	5.50%
2021	12.35%	14.15%	12.04%	13.59%	13.59%	11.92%
2022	10.25%	9.62%	9.01%	9.47%	9.04%	8.93%
2023	9.74%	9.19%	8.26%	8.77%	8.39%	7.66%
AVERAGE	13.04%	10.81%	8.45%	9.18%	8.90%	8.13%

Judging from the experimental results it is evident that the Random Forest technique excellently outweighs the others along with the Logistic Regression technique. This observations is reinforced from the box plot of Figure 2.




Figure 2. Box plot for the used machine learning techniques.

Also the precision and recall measures for every dataset and for each method are presented in Table 2.

	BAYESNET		NAIVEBAYES		LOGISTIC		MLP		J48		FOREST	
YEAR	PRECISION	RECALL	PRECISION	RECALL	PRECISION	RECALL	PRECISION	RECALL	PRECISION	RECALL	PRECISION	RECALL
2014	0.889	0.886	0.851	0.871	0.89	0.902	0.87	0.886	0.888	0.90	0.898	0.906
2015	0.892	0.889	0.87	0.887	0.891	0.905	0.876	0.893	0.892	0.905	0.901	0.91
2016	0.959	0.743	0.959	0.87	0.96	0.966	0.955	0.961	0.959	0.963	0.968	0.97
2017	0.897	0.89	0.869	0.885	0.893	0.905	0.886	0.889	0.886	0.897	0.899	0.907
2018	0.897	0.888	0.879	0.895	0.894	0.909	0.89	0.905	0.894	0.907	0.905	0.914
2019	0.914	0.904	0.894	0.907	0.903	0.917	0.903	0.915	0.898	0.909	0.912	0.92
2020	0.929	0.82	0.923	0.933	0.937	0.945	0.933	0.94	0.931	0.939	0.94	0.945
2021	0.879	0.876	0.835	0.858	0.865	0.88	0.846	0.864	0.849	0.864	0.871	0.881
2022	0.91	0.897	0.889	0.904	0.893	0.91	0.891	0.905	0.896	0.91	0.9	0.911
2023	0.912	0.903	0.894	0.908	0.905	0.917	0.899	0.912	0.906	0.916	0.916	0.923

Table 2. Precision and recall for every machine learning method.

The statistical comparison of the Random Forest with the other machine learning methods is depicted in Figure 3.




Figure 3. Statistical comparison between the Random Forest method and the other machine learning methods.

In the statistical visualization of Figure 3, Random Forest consistently emerges as the best model based on error rates, recording lower errors in most years compared to the other machine learning models. Although other models, such as Logistic Regression and MLP, show strong performance in certain years, Random Forest maintains a more stable and reliable performance with fewer fluctuations.

4. Conclusions

A series of machine learning methods was applied on datasets involving forest fires for the Greece. These datasets covered a period of ten years, starting from 2014. These methods were obtained from the WEKA machine learning tool, which is freely available for any operating system. These methods cover a wide range of machine learning techniques from different domains. The purpose of this study was to identify the duration of forest fires and three cases of forest fires were studied in this research work: forest fires of limited duration, forest fires of medium duration and forest fires of long duration. Estimating the duration of a fire is an important factor, as it can be used to estimate the size of the impending disaster as well as the resources required to extinguish it. Most of the machine learning techniques used achieved significantly low error values for each year of experimental data. On average, these classification error values are in the range of 8-13% with the Random Forest technique achieving the lowest value. The present work could be extended in the future in various research directions, such as:

1. Incorporation of more machine learning methods from the relevant literature.
2. Use feature selection or construction techniques from recent literature to identify the most important factors influencing the classification process.
3. Usage of methods that create classification rules, in order to discover any hidden relationships between the data and the classes of the datasets.

4. Usage of data that also includes meteorological data, in order to identify a possible correlation of the categories with the meteorological conditions that prevailed at the time of the fire.
5. Parallel programming techniques may be incorporated to speed up the optimization process, such as MPI [114] or the OpenMP library [115].

Author Contributions: C.K., V.C. and I.G.T. conceived of the idea and the methodology, and C.K. and V.C. implemented the corresponding software. C.K. conducted the experiments, employing objective functions as test cases, and provided the comparative experiments. A.S. performed the necessary statistical tests. All authors have read and agreed to the published version of the manuscript.

Funding: This research received no external funding.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Not applicable.

Acknowledgments: This research has been financed by the European Union: Next Generation EU through the Program Greece 2.0 National Recovery and Resilience Plan, under the call RESEARCH-CREATE-INNOVATE, project name “iCREW: Intelligent small craft simulator for advanced crew training using Virtual Reality techniques” (project code: TAEDK-06195).

Conflicts of Interest: The authors declare no conflicts of interest.

References

1. Z. Qiang, E.Z. Meka, R.C. Anderson, Y. Kakabadse, Forests nature at your service. UNEP report. The magazine of the United Nations Environment Program, 2011.
2. A.S. Mori, K.P. Lertzman, L. Gustafsson, Biodiversity and ecosystem services in forest ecosystems: a research agenda for applied forest ecology, *Journal of Applied Ecology* **54**, pp. 12-27, 2017.
3. B.J. Stocks, Mason, J. A., Todd, J. B., Bosch, E. M., Wotton, B. M., Amiro, B. D., ... & Skinner, W. R. (2002). Large forest fires in Canada, 1959–1997. *Journal of Geophysical Research: Atmospheres*, 107(D1), FFR-5.
4. M.D. Flannigan, B.D. Amiro, K.A. Logan, B.J. Stocks, B.M. Wotton, Forest fires and climate change in the 21 st century. *Mitigation and adaptation strategies for global change* **11**, pp. 847-859, 2006.
5. O. Sahar, Wildfires in Algeria: problems and challenges. *IFOREST* **8**, pp. 818–826, 2015.
6. G. Certini, Effects of fire on properties of forest soils: a review, *Oecologia* **143**, pp. 1–10, 2005.
7. G.R. Van Der Werf, J.T. Randerson, G.J. Collatz, L. GIGLIO, Carbon emissions from fires in tropical and subtropical ecosystems. *Global Change Biology*, 9: 547-562, 2003.
8. A.A. Agbeshie, S. Abugre, T. Atta-Darkwa et al, A review of the effects of forest fire on soil properties, *J. For. Res.* **33**, pp. 1419–1441, 2022.
9. P. Aleksić, M. Krstić, G. Jančić, Forest fire - ecological and economic problem in Serbia, *Botanica Serbia* **32**, pp. 169-176, 2009.
10. D. Wang, D. Guan, S. Zhu. et al, Economic footprint of California wildfires in 2018, *Nat Sustain* **4**, pp. 252–260, 2021.
11. P. W. Hystad, P.C. Keller, Towards a destination tourism disaster management framework: Long-term lessons from a forest fire disaster, *Tourism Management* **29**, pp. 151-162, 2008.
12. G. Boustras, N. Boukas, Forest fires’ impact on tourism development: a comparative study of Greece and Cyprus, *Management of Environmental Quality* **24**, pp. 498-511, 2013.
13. V. Otrachshenko, L.C. Nunes, Fire takes no vacation: impact of fires on tourism, *Environment and Development Economics* **27**, pp. 86-101, 2022.
14. N. Sastry, Forest fires, air pollution, and mortality in Southeast Asia, *Demography* **39**, pp. 1–23, 2002.
15. E. Frankenberg, D. McKee, D. Thomas, Health consequences of forest fires in Indonesia, *Demography* **42**, pp. 109–129, 2005.
16. D. Bowman, G. Williamson, J. Abatzoglou. et al, Human exposure and sensitivity to globally extreme wildfire events, *Nat Ecol Evol* **1**, 0058, 2017.
17. M. Zhong, W. Fan, T. Liu, P. Li, Statistical analysis on current status of China forest fire safety, *Fire Safety Journal* **38**, pp. 257-269, 2003.
18. D. Avila-Flores, M. Pompa-Garcia, X. Antonio-Nemiga. et al., Driving factors for forest fire occurrence in Durango State of Mexico: A geospatial perspective, *Chin. Geogr. Sci.* **20**, pp. 491–497, 2010.
19. R. Lovreglio, V. Leone, P. Giaquinto, A. Notarnicola, Wildfire cause analysis: four case-studies in southern Italy. *iForest* **3**, pp. 8-15, 2010.

20. D. W. Casbeer, R. W. Beard, T. W. McLain, Sai-Ming Li and R. K. Mehra, "Forest fire monitoring with multiple small UAVs," *Proceedings of the 2005, American Control Conference*, 2005., Portland, OR, USA, 2005, pp. 3530-3535 vol. 5, doi: 10.1109/ACC.2005.1470520. 276
21. Guozhu Wang, J. Zhang, Wenbin Li, Dongxu Cui and Ye Jing, "A forest fire monitoring system based on GPRS and ZigBee wireless sensor network," *2010 5th IEEE Conference on Industrial Electronics and Applications*, Taichung, 2010, pp. 1859-1862, doi: 10.1109/ICIEA.2010.5515417. 277
22. M. Stula, D. Krstinic, L. Seric, Intelligent forest fire monitoring system, *Inf Syst Front* **14**, pp. 725–739, 2012. 278
23. L. Merino, E. Caballero, J.R. Martínez-de-Dios al., An Unmanned Aircraft System for Automatic Forest Fire Monitoring and Measurement, *J Intell Robot Syst* **65**, pp. 533–548, 2012. 279
24. Y.E. Aslan, I. Korpeoglu, Ö. Ulusoy, A framework for use of wireless sensor networks in forest fire detection and monitoring, *Computers, Environment and Urban Systems* **36**, pp. 614-625, 2012. 280
25. M.Á. Serna, R. Casado, A. Bermúdez, N. Pereira, S. Tennina, Distributed Forest Fire Monitoring Using Wireless Sensor Networks, *International Journal of Distributed Sensor Networks* **11**, 10, 2015. 281
26. S. Dwiasnati, Y. Devianto, Classification of forest fire areas using machine learning algorithm, *World Journal of Advanced Engineering Technology and Sciences*, **3**, pp. 008-015, 2021. 282
27. Y. Pang, Y. Li, Z. Feng, Z. Feng, Z. Zhao, S. Chen, H. Zhang, Forest Fire Occurrence Prediction in China Based on Machine Learning Methods, *Remote Sensing* **14**, 5546, 2022. 283
28. U. Dampage, L. Bandaranayake, R. Wanasinghe et al, Forest fire detection system using wireless sensor networks and machine learning, *Sci Rep* **12**, 46, 2022. 284
29. K.R. Singh, K.P. Neethu, K. Madhurekaa, A. Harita, P. Mohan, Parallel SVM model for forest fire prediction, *Soft Computing Letters* **3**, 100014, 2021. 285
30. F. Abid, A survey of machine learning algorithms based forest fires prediction and detection systems, *Fire technology* **57**, pp. 559-590, 2021. 286
31. Y. Shao, Z. Feng, L. Sun, X. Yang, Y. Li, B. Xu, Y. Chen, Mapping China's Forest Fire Risks with Machine Learning, *Forests* **13**, 856, 2022. 287
32. J. Vicente, P. Guillemant, An image processing technique for automatically detecting forest fire, *International Journal of Thermal Sciences* **41**, pp. 1113-1120, 2002. 288
33. Q. Yan, P. Bo, Z. Juanjuan, Forest Fire Image Intelligent Recognition based on the Neural Network. *Journal of Multimedia* **9**, pp. 469-475, 2014. 289
34. Mahmoud, Mubarak A. I., Ren, Hongge, Forest Fire Detection Using a Rule-Based Image Processing Algorithm and Temporal Variation, *Mathematical Problems in Engineering*, 2018, 7612487, 8 pages, 2018. 290
35. Y. Wang, L. Dang, J. Ren, Forest fire image recognition based on convolutional neural network, *Journal of Algorithms & Computational Technology* **13**, 2019. 291
36. Z. Jiao, Y. Zhang, J. Xin, Y. Yi, D. Liu and H. Liu, "Forest Fire Detection with Color Features and Wavelet Analysis Based on Aerial Imagery," *2018 Chinese Automation Congress (CAC)*, Xi'an, China, 2018, pp. 2206-2211, doi: 10.1109/CAC.2018.8623473. 292
37. H. Liang, M. Zhang, H. Wang, A Neural Network Model for Wildfire Scale Prediction Using Meteorological Factors, *IEEE Access* **7**, pp. 176746-176755, 2019. 293
38. U. KC, J. Aryal, J. Hilton, S. Garg, A Surrogate Model for Rapidly Assessing the Size of a Wildfire over Time, *Fire* **4**, 20, 2021. 294
39. D.D. Xi, C.B. Dean, S.W. Taylor, Modeling the duration and size of wildfires using joint mixture models. *Environmetrics* **32**, e2685, 2021. 295
40. H.M. Hammouri, R.T. Sabo, R. Alsaadawi, K.A. Kheirallah, Handling Skewed Data: A Comparison of Two Popular Methods. *Applied Sciences* **10**, 6247, 2020. 296
41. Ben-Gal, I. (2008). Bayesian Networks. In *Encyclopedia of Statistics in Quality and Reliability* (eds F. Ruggeri, R.S. Kenett and F.W. Faltin). 297
42. Koski, T., & Noble, J. (2011). Bayesian networks: an introduction. John Wiley & Sons. 298
43. N. Friedman, M. Linial, I. Nachman, D. Pe'er, Using Bayesian networks to analyze expression data, In: *Proceedings of the fourth annual international conference on Computational molecular biology*, pp. 127-135, 2000. 299
44. B. Cai, L. Huang, M. Xie, Bayesian Networks in Fault Diagnosis, *IEEE Transactions on Industrial Informatics* **13**, pp. 2227-2240, 2017. 300
45. D.N. Barton, S. Kuikka, O. Varis, L. Uusitalo, H.J. Henriksen, M. Borsuk, A. de la Hera, R. Farmani, S. Johnson, J.D. Linnell, Bayesian networks in environmental and resource management. *Integr Environ Assess Manag*, **8**, pp. 418-429, 2012. 301
46. V. Sevinc, O. Kucuk, M. Goltas, A Bayesian network model for prediction and analysis of possible forest fire causes. *Forest Ecology and Management* **457**, 117723, 2020. 302
47. F. Chen, H. Jia, E. Du, Y. Chen, L. Wang, Modeling of the cascading impacts of drought and forest fire based on a Bayesian network, *International Journal of Disaster Risk Reduction* **111**, 104716, 2024. 303
48. B. Kim, J. Lee, A Bayesian network-based information fusion combined with DNNs for robust video fire detection. *Applied Sciences* **11**, 7624, 2021. 304
49. Bayes, T. (1968). Naive bayes classifier. *Article Sources and Contributors*, 1-9. 305
50. G.I. Webb, E. Keogh, R. Miikkulainen, Naïve Bayes, *Encyclopedia of machine learning* **15**, pp. 713-714, 2010. 306

51. S.L. Ting, W.H. Ip, A.H. Tsang, Is Naive Bayes a good classifier for document classification, *International Journal of Software Engineering and Its Applications* **5**, pp. 37-46, 2011. 335
52. H. Chen, S. Hu, R. Hua, et al, Improved naive Bayes classification algorithm for traffic risk management, *EURASIP J. Adv. Signal Process.* 2021, 30, 2021. 336
53. M. Panda, M.R. Patra, Network intrusion detection using naive bayes. *International journal of computer science and network security* **7**, pp. 258-263, 2007. 337
54. A. Andi Nugroho, I. Iwan, K. Iroh Nur Azizah, F. Hakim Raswa, Peatland Forest Fire Prevention Using Wireless Sensor Network Based on Naïve Bayes Classifier, *KnE Social Sciences* **3**, pp. 20-34, 2019. 338
55. M. Zainul, E. Minggu, Classification of Hotspots Causing Forest and Land Fires Using the Naive Bayes Algorithm, *Interdisciplinary Social Studies* **1**, pp. 555-567, 2022. 339
56. I.M.K. Karo, S.N. Amalia, D. Septiana, Wildfires Classification Using Feature Selection with K-NN, Naïve Bayes, and ID3 Algorithms, *Journal of Software Engineering, Information and Communication Technology (SEICT)* **3**, pp. 15-24, 2022. 340
57. L. Shu, H. Zhang, Y. You, Y. Cui, W. Chen, Towards fire prediction accuracy enhancements by leveraging an improved naïve bayes algorithm, *Symmetry* **13**, 530, 2021. 341
58. S. Sperandei, Understanding logistic regression analysis, *Biochemia medica* **24**, pp. 12-18, 2014. 342
59. A.F. Cabrera, Logistic regression analysis in higher education: An applied perspective, *Higher education: Handbook of theory and research* **10**, pp. 225-256, 1994. 343
60. C. Lawson, D.C. Montgomery, Logistic Regression Analysis of Customer Satisfaction Data, *Qual. Reliab. Engng. Int.* **22**, pp. 971-984, 2006. 344
61. Zhiyong Hu and C.P. Lo, Modeling urban growth in Atlanta using logistic regression, *Computers, Environment and Urban Systems* **31**, pp. 667-688, 2007. 345
62. L. Vilar del Hoyo, M.P. Martín Isabel, F.J. Martínez Vega, Logistic regression models for human-caused wildfire risk estimation: analysing the effect of the spatial accuracy in fire occurrence data, *Eur J Forest Res* **130**, pp. 983-996, 2011. 346
63. P.P. de Bem, O.A. de Carvalho Júnior, E.A.T. Matricardi, R.F. Guimarães, R.A.T. Gomes, Predicting wildfire vulnerability using logistic regression and artificial neural networks: a case study in Brazil's Federal District. *International journal of wildland fire* **28**, pp. 35-45, 2018. 347
64. Eufrásio João Sozinho Nhongo, Denise Cybis Fontana, Laurindo Antonio Guasselli and Carolina Bremm, Probabilistic modelling of wildfire occurrence based on logistic regression, Niassa Reserve, Mozambique, *Geomatics, Natural Hazards and Risk* **10**, pp. 1772-1792, 2019. 348
65. W. Peng, Y. Wei, G. Chen, G. Lu, Q. Ye, R. Ding, P. Hu, Z. Cheng, Analysis of Wildfire Danger Level Using Logistic Regression Model in Sichuan Province, China. *Forests* **14**, 2352, 2023. 349
66. C. Bishop, *Neural Networks for Pattern Recognition*, Oxford University Press, 1995. 350
67. G. Cybenko, Approximation by superpositions of a sigmoidal function, *Mathematics of Control Signals and Systems* **2**, pp. 303-314, 1989. 351
68. P. Baldi, K. Cranmer, T. Faucett et al, Parameterized neural networks for high-energy physics, *Eur. Phys. J. C* **76**, 2016. 352
69. J. J. Valdas and G. Bonham-Carter, Time dependent neural network models for detecting changes of state in complex processes: Applications in earth sciences and astronomy, *Neural Networks* **19**, pp. 196-207, 2006. 353
70. G. Carleo, M. Troyer, Solving the quantum many-body problem with artificial neural networks, *Science* **355**, pp. 602-606, 2017. 354
71. Y. Shirvany, M. Hayati, R. Moradian, Multilayer perceptron neural networks with novel unsupervised training method for numerical solution of the partial differential equations, *Applied Soft Computing* **9**, pp. 20-29, 2009. 355
72. A. Malek, R. Shekari Beidokhti, Numerical solution for high order differential equations using a hybrid neural network—Optimization method, *Applied Mathematics and Computation* **183**, pp. 260-271, 2006. 356
73. A. Kumar Yadav, S.S. Chandel, Solar radiation prediction using Artificial Neural Network techniques: A review, *Renewable and Sustainable Energy Reviews* **33**, pp. 772-781, 2014. 357
74. A. Topuz, Predicting moisture content of agricultural products using artificial neural networks, *Advances in Engineering Software* **41**, pp. 464-470, 2010. 358
75. A. Escamilla-García, G.M. Soto-Zarazúa, M. Toledano-Ayala, E. Rivas-Araiza, A. Gastélum-Barrios, Abraham, Applications of Artificial Neural Networks in Greenhouse Technology and Overview for Smart Agriculture Development, *Applied Sciences* **10**, Article number 3835, 2020. 359
76. Lin Shen, Jingheng Wu, and Weitao Yang, Multiscale Quantum Mechanics/Molecular Mechanics Simulations with Neural Networks, *Journal of Chemical Theory and Computation* **12**, pp. 4934-4946, 2016. 360
77. Sergei Manzhos, Richard Dawes, Tucker Carrington, Neural network-based approaches for building high dimensional and quantum dynamics-friendly potential energy surfaces, *Int. J. Quantum Chem.* **115**, pp. 1012-1020, 2015. 361
78. Jennifer N. Wei, David Duvenaud, and Alán Aspuru-Guzik, Neural Networks for the Prediction of Organic Chemistry Reactions, *ACS Central Science* **2**, pp. 725-732, 2016. 362
79. G. Li, J. Shi, On comparing three artificial neural networks for wind speed forecasting, *Applied Energy* **87**, pp. 2313-2320, 2010. 363
80. Lukas Falat and Lucia Pancikova, Quantitative Modelling in Economics with Advanced Artificial Neural Networks, *Procedia Economics and Finance* **34**, pp. 194-201, 2015. 364

81. Mohammad Namazi, Ahmad Shokrolahi, Mohammad Sadeghzadeh Maharluie, Detecting and ranking cash flow risk factors via artificial neural networks technique, *Journal of Business Research* **69**, pp. 1801-1806, 2016. 393
82. G. Tkacz, Neural network forecasting of Canadian GDP growth, *International Journal of Forecasting* **17**, pp. 57-69, 2001. 394
83. Igor I. Baskin, David Winkler and Igor V. Tetko, A renaissance of neural networks in drug discovery, *Expert Opinion on Drug Discovery* **11**, pp. 785-795, 2016. 395
84. Ronadl Bartzatt, Prediction of Novel Anti-Ebola Virus Compounds Utilizing Artificial Neural Network (ANN), *Chemistry Faculty Publications* **49**, pp. 16-34, 2018. 396
85. F. M. A. Hossain, Y. Zhang, C. Yuan and C. -Y. Su, "Wildfire Flame and Smoke Detection Using Static Image Features and Artificial Neural Network," 2019 1st International Conference on Industrial Artificial Intelligence (IAI), Shenyang, China, 2019, pp. 1-6, doi: 10.1109/ICIAI.2019.8850811. 397
86. S. Lall and B. Mathibela, "The application of artificial neural networks for wildfire risk prediction," 2016 International Conference on Robotics and Automation for Humanitarian Applications (RAHA), Amritapuri, India, 2016, pp. 1-6, doi: 10.1109/RAHA.2016.7931880. 398
87. Y. O. Sayad, H. Mousannif, H. Al Moatassime, Predictive modeling of wildfires: A new dataset and machine learning approach, *Fire Safety Journal* **104**, pp. 130-146, 2019. 399
88. H. Liang, M. Zhang, H. Wang, A Neural Network Model for Wildfire Scale Prediction Using Meteorological Factors, *IEEE Access* **7**, pp. 176746-176755, 2019. 400
89. K. Gao, Z. Feng, S. Wang, Using multilayer perceptron to predict forest fires in jiangxi province, southeast china, *Discrete Dynamics in Nature and Society* **1**, 6930812, 2022. 401
90. N. Bhargava, G. Sharma, R. Bhargava, M. Mathuria, Decision tree analysis on j48 algorithm for data mining. *Proceedings of international journal of advanced research in computer science and software engineering* **3**, 2013. 402
91. G. Kaur, A. Chhabra, Improved J48 classification algorithm for the prediction of diabetes, *International journal of computer applications* **98**, 22, 2014. 403
92. S. Sahu, B.M. Mehtre, Network intrusion detection system using J48 Decision Tree, In: 2015 International Conference on Advances in Computing, Communications and Informatics (ICACCI), pp. 2023-2026, 2015. 404
93. N.N. Sakhare, S.A. Joshi, Classification of criminal data using J48-Decision Tree algorithm. *Int. J. Data Warehous. Min* **4**, pp. 167-171, 2015. 405
94. S.F. Abdullah, A.F.N.A. Rahman, Z.A. Abas, W.H.M. Saad, Fingerprint gender classification using univariate decision tree (j48), *International Journal of Advanced Computer Science and Applications* **7**, 2016. 406
95. Jehad, R., & Yousif, S. A. (2020). Fake news classification using random forest and decision tree (j48). *Al-Nahrain Journal of Science*, 23(4), 49-55. 407
96. D. Stojanova, P. Panov, A. Kobler, S. Džeroski, K. Taškova, Learning to predict forest fires with different data mining techniques. In *Conference on data mining and data warehouses (SiKDD 2006)*, Ljubljana, Slovenia, pp. 255-258, 2006. 408
97. F. Abid, N. Izeboudjen, Predicting forest fire in algeria using data mining techniques: Case study of the decision tree algorithm. In *Advanced Intelligent Systems for Sustainable Development (AI2SD'2019) Volume 4-Advanced Intelligent Systems for Applied Computing Sciences* (pp. 363-370). Springer International Publishing, 2020. 409
98. Breiman, L. (2001). Random forests. *Machine learning*, 45, 5-32. 410
99. S.J. Rigatti, Random forest, *Journal of Insurance Medicine*, 47(1), 31-39, 2017. 411
100. M. Pal, Random forest classifier for remote sensing classification. *International Journal of Remote Sensing* **26**, pp. 217-222, 2005. 412
101. D.R. Cutler, T.C. Edwards, K.H. Beard, A. Cutler, K.T. Hess, J. Gibson, J.J. Lawler, random forests for classification in ecology. *Ecology* **88**, pp. 2783-2792, 2007. 413
102. Qi, Y. (2012). Random Forest for Bioinformatics. In: Zhang, C., Ma, Y. (eds) *Ensemble Machine Learning*. Springer, New York, NY. https://doi.org/10.1007/978-1-4419-9326-7_11 414
103. B. Xu, X. Guo, Y. Ye, J. Cheng, An improved random forest classifier for text categorization. *J. Comput.*, **7**, pp. 2913-2920, 2012. 415
104. N. Farnaaz, M.A. Jabbar, Random Forest Modeling for Network Intrusion Detection System, *Procedia Computer Science* **89**, pp. 213-217, 2016. 416
105. A. L. Latifah, A. Shabrina, I. N. Wahyuni, R. Sadikin, Evaluation of Random Forest model for forest fire prediction based on climatology over Borneo, In: 2019 International Conference on Computer, Control, Informatics and its Applications (IC3INA), Tangerang, Indonesia, pp. 4-8, 2019. 417
106. A. Malik, M.R. Rao, N. Puppala, P. Koouri, V.A.K. Thota, Q. Liu, S. Chiao, J. Gao, Data-Driven Wildfire Risk Prediction in Northern California. *Atmosphere*, **12**, 109, 2021. 418
107. C. Gao, H. Lin, H. Hu, Forest fire risk prediction based on random forest and backpropagation neural network of Heihe area in Heilongjiang province, China, *Forests* **14**, 170, 2023. 419
108. D.E. Rumelhart, G.E. Hinton and R.J. Williams, Learning representations by back-propagating errors, *Nature* **323**, pp. 533 - 536 , 1986. 420
109. M. Hall, F. Frank, G. Holmes, B. Pfahringer, P. Reutemann, I.H. Witten, The WEKA data mining software: an update. *ACM SIGKDD explorations newsletter* **11**, pp. 10-18, 2009. 421
110. S.B. Aher, L.M.R.J. Lobo, Data mining in educational system using weka. In *International conference on emerging technology trends*, Foundation of Computer Science **3**, pp. 20-25, 2011. 422

111. S. Hussain, N.A. Dahan, F.M. Ba-Alwib, N. Ribata, Educational data mining and analysis of students' academic performance using WEKA. *Indonesian Journal of Electrical Engineering and Computer Science* **9**, pp. 447-459, 2018. 452
112. A.K. Sigurdardottir, H. Jonsdottir, R. Benediktsson, Outcomes of educational interventions in type 2 diabetes: WEKA data-mining analysis. *Patient education and counseling* **67**, pp. 21-31, 2007. 453
113. M.N. Amin, A. Habib, Comparison of different classification techniques using WEKA for hematological data. *American Journal of Engineering Research* **4**, pp. 55-61, 2015. 454
114. Gropp, W.; Lusk, E.; Doss, N.; Skjellum, A. A high-performance, portable implementation of the MPI message passing interface standard. *Parallel Comput.* 1996, **22**, 789-828. 455
115. Chandra, R. *Parallel Programming in OpenMP*; Morgan Kaufmann: Cambridge, MA, USA, 2001. 456

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content. 457
458
459
460
461
462
463