When Does a Reader-Side Lifetime Fix Help? Admission Coupling in an LSM Engine (Extended Report)

V V Ramarathinam Iyer
Department of Database Systems, School of Computer Science and Engineering
Vellore Institute of Technology, Vellore, Tamil Nadu, India
Email: ram.iyer200722@gmail.com

This extended report accompanies the conference paper of the same title. It adds the full cells, protocols, and execution history that the paper omits.

***Abstract*—A read lock held across a lookup is an easy way to keep a storage file alive, yet a reader-side fix cannot shorten the writer's critical section. We ask when such a fix helps. In seven pre-registered campaigns on one LSM engine, with read cost controlled by injected delay, we compare a coarse read lock, per-table leases, and immutable reader sets across write load, compaction, and table count. Readers and writers are coupled through lock admission: each exclusive acquisition in a commit admits a round of readers, so the coarse lock's read gain at short injected delays depends on the redundant second acquisition. An intervention removing that acquisition supported this: with one acquisition the gain was absent at injected delays up to 20 μs. The writer also limits both replacements, which still take the manager lock to search memory: at a high write rate it held the lock across fsync for about three quarters of the time, and reads fell as that hold grew, though not in proportion as predicted. Leases and reader sets matched on throughput within a declared margin across publication and compaction, but read-only load separated them at high table counts, with leases completing 34% fewer reads at 256 tables and sixteen readers; their read equivalence was not established at high write rates. Practically, measure lock-held lookup time, write load, and table count before replacing a lock. Trials started immediately after another had a largest fsync near 55 ms; 30 s pauses removed that band, the cause is unknown, and rechecked throughput classes held. Results come from one engine on one Windows host, at most one writer, injected delay, and WAL fsync under the exclusive lock.**

***Index Terms*—LSM tree, reader-writer lock, descriptor leasing, immutable snapshots, controlled experiment.**

I. Introduction

A reader-side lifetime fix shortens the reader's lock hold but leaves the writer's own critical section in place. An LSM engine buffers updates in memory and writes sorted runs to disk [1], [2]; readers need stable file references while flushes and compactions replace those runs. Holding the manager's read lock across a lookup provides that protection but makes exclusive acquisitions wait for the lookup, including file I/O. We ask: when does a reader-side lifetime fix actually help, given the writer's own critical section?

Production engines separate lifetime protection from long read holds. LevelDB, RocksDB, and Pebble retain references after releasing a short coordination lock [3]–[5]. We compare CoarseLock, which retains the manager lock, with per-table leases (Lease) and immutable reader sets (Snapshot). Injected delay controls lookup cost while the writer's validation and WAL synchronization remain shared across designs.

The paper makes four contributions:

- **Admission coupling.** Under a saturated, continually waiting writer, CoarseLock's reads couple to writes as $R \simeq k\, r\, W$, where k is exclusive acquisitions per commit. A pre-registered intervention changing k supported this account, and the read gain depends on the redundant second acquisition (Section VI).
- **The writer's critical section limits the fix.** The cost of holding a read lock depends on how long it is held and on whether the writer is at capacity: below capacity, write throughput stays within the declared margin while median write response rises through two measured lock waits, and a follow-up campaign shows reads falling as the writer's hold share rises, though not in proportion as predicted (Sections V and VII).
- **Replacement designs are not interchangeable at the extremes.** Lease and Snapshot match on throughput within a declared margin across publication and compaction, and separate under read-only load at high table counts; their read equivalence was not established at high write rates (Section VII).
- **A methodology lesson.** Trials started immediately after another had a largest fsync near 55 ms that 30 s pauses removed; the cause is unknown, and rechecked throughput classes held (Section VIII).

II. Background

A. The lifetime problem and production designs

Stable references let a reader outlive a short coordination critical section. LevelDB takes references on memtables and the current version under its mutex, releases it while reading, and later releases the references; its writer also releases the mutex around log append and synchronization and batches queued writers [3]. RocksDB readers reference a SuperVersion, and Pebble readers reference a read state under a short `RLock` [4], [5]. These designs motivate the lifetime question; our implementations retain their engine's validation, file format, and publication path.

B. Reader-writer admission

Admission policy determines who proceeds after an exclusive hold. Reader-writer locks permit concurrent readers while excluding writers [12]; Go's `RWMutex` blocks new readers once a writer waits and releases queued readers on writer unlock [18]. A continually waiting writer can therefore alternate with admitted readers. Phase-fair synchronization frames this ordering [14], without implying that Go satisfies its formal properties.

Earlier measurements used a defective reader and supply no pooled evidence for this study; Appendix C records that history and the withdrawn claims.

III. The Engine and Three Designs

A. Storage and point reads

All designs share the storage and corrected point-read paths. A skip-list memtable [11] orders versioned internal keys and flushes frozen contents into SSTables. Data blocks use a 4 KiB threshold, a flat sparse index, and a footer locating the index. The point reader checks cached user-key ranges, binary-searches the index, and issues one `ReadAt` per visited block, stopping after finding a visible version or passing the key. Versions can straddle blocks. Open-time range-metadata reads bypass the delay, and there is no application block cache.

B. Three ways to keep readers alive

CoarseLock protects file lifetime by retaining the manager read lock through lookup and I/O. All designs first search active and frozen memory under `Mu.RLock`; CoarseLock keeps it until the SSTable search ends, excluding publication and retirement throughout.

Lease protects individual file readers after releasing the manager lock. Under the read lock it copies table-reader pointers into reusable scratch storage and takes an atomic lease on every active table. It searches outside `Mu` and releases the leases afterwards. Shutdown closes admission and drains active and retired leases; timeout preserves descriptors that remain leased. Each read leases all active tables even when only one range can match.

Snapshot pins one immutable reader-set descriptor under the manager read lock and `snapshotMu`. It searches outside both locks and reacquires `snapshotMu` to release the pin. Publication allocates and installs a new set under the mutexes and retires the old set; once it drains, eligible closure and unlinking run outside both mutexes. Table I summarizes the designs.

C. The commit path

The default commit path gives every design two exclusive acquisitions per successful commit, setting $k = 2$. `Transaction.Commit` first takes `Mu.Lock`, validates conflicts through `latestValueLocked`, appends and synchronizes the WAL, updates memory, and unlocks. It then calls `checkAndTriggerFlush`, which reacquires the exclusive lock even when no flush is needed. That second acquisition is unnecessary when no flush occurs; removing it below threshold changes k, as tested in Section VI-C. All designs share the default path. The first five campaigns time only the first acquisition's wait; the settled campaign times both.

TABLE I
LIFETIME DESIGNS WITH THE DEFAULT COMMIT PATH.

Property	CoarseLock	Lease	Snapshot
Memory-tier search under `Mu.RLock`	yes	yes	yes
Reader SSTable I/O under `Mu.RLock`	yes	no	no
Disk-reader lifetime	lock	table leases	set pin
Per-read lifetime synchronization	`Mu`	atomic leases	`snapshotMu`
New set descriptor on publication	no	no	yes
Conflict check and WAL sync under `Mu.Lock`	yes	yes	yes
Exclusive acquisitions per successful commit	2	2	2




Fig. 1. One commit cycle under CoarseLock and Lease (schematic, not a measured trace). Under CoarseLock the writer waits for each read and each reader completes one read per exclusive acquisition. Under Lease the reader's I/O is outside the lock and can outlast the short second acquisition. CoarseLock: approximately two reads per reader per commit; Lease: fewer.

Writer validation and fsync remain inside the exclusive hold after either reader-side fix. Conflict validation can read delayed SSTable blocks in every design. The delay therefore reaches the writer as well as readers, while the two acquisitions provide separate opportunities to admit queued readers (Fig. 1).

IV. Method

The campaigns fix the host and measurement conventions while varying read cost and write load. The host is an AMD Ryzen 7 7445HS with six cores, twelve logical CPUs, 15.2 GiB RAM, and a Samsung MZVL8512HFLU NVMe SSD, running Windows 11 Home build 26200 on NTFS with `GOMAXPROCS=12`. Every campaign recorded the Go toolchain as go1.26.3. Timing uses QueryPerformanceCounter. Except for table-count variants, fixtures have 10,000 keys in four disjoint tables, 128-byte values, and uniform lookups with target hit ratio 0.95. Trials use 2 s reader-only warmup, a 10 s measurement window, and 200 ms cooldown.

The workloads separate writer capacity, publication, and lifetime work. Mixed uses a free-running writer and a 1 MiB memtable; Publication releases twenty pre-frozen memtables every 0.5 s; Churn uses a 16 KiB memtable and frequent flushing; Paced fixes intended write arrivals at fractions f

TABLE II
PRE-REGISTERED RESULTS. H3 HAD NO DIRECTIONAL PREDICTION; ITS OUTCOME IS CI REPORTING. R-CHECK IS THE SENTINEL RULE, DISTINCT FROM COMPACTION H-C.

Campaign	Prediction in plain words	Outcome	Section
Initial H1	Write ratio falls as delay rises	Supported	V
Initial H2	Lease/Snapshot throughput and publication waits match the margin	Partly supported	VII
Initial H3	Churn: no directional prediction; report paired CIs	No directional prediction	VII
Intervention P1	CoarseLock reads per reader per commit follow acquisition count	Supported	VI
Intervention P2	Removing an acquisition lowers the relative read ratio	Supported	VI
Intervention P3	Cycle errors fit the band; higher-dose writes improve	Supported	VI
Compaction H-C	Lease/Snapshot throughput matches with compaction on	Supported	VII
Table count H-T1	Lease/Snapshot read ratio declines with table count	Partly supported	VII
Table count H-T2	Equivalence at small counts; read-only separation at the largest	Supported	VII
Paced H-P1	CoarseLock/Lease write response p99 ratio rises with delay	Failed	V
Paced H-P2	Below-capacity write throughput matches the margin	Supported	V
Paced H-P3	Higher-load writes match at zero delay and separate at higher doses	Partly supported; failed at 200 μs	V
Paced H-P4	Lease/Snapshot write and closed-reader throughput match	Partly supported	VII
Settled H-M1	Below-capacity write response median ratio rises with delay	Supported	V
Settled H-M2	Median ratio lies above the margin at higher doses	Supported	V
Settled H-M3	Both CoarseLock waits fit the delay band; Lease waits are short	Supported	V
Settled H-W	Higher offered rate separates write throughput	Supported	V
Settled H-R	Previously inconclusive Lease/Snapshot reads and writes match	Failed	VII
Settled H-S	Protocol check: below-capacity median largest fsync stays below the ceiling, raised from 25 to 40 ms before any campaign trial	Supported at the raised threshold	VIII
Settled R-check	Recheck prior metrics and classes; rerun if the rule triggers	No rerun triggered; five metrics inconclusive	VIII
Follow-up H-F1	Reads scale with free share across write rates, slope in $[0.80, 1.25]$	Failed	VII
Follow-up H-F2	Reads rise as write rate falls	Supported	VII
Follow-up H-F3	Lease/Snapshot reads match at 183, 366, and 549 writes/s	Partly supported; inconclusive at 549	VII
Follow-up H-F4	CoarseLock read latency has fast and blocked groups with a near-empty gap	Supported	VI

of earlier Lease capacity with closed or open readers. Compaction variants merge all active tables on a fixed timer, and table-count variants use disjoint ranges. Immediately before each point-read `ReadAt`, including writer validation, delay spins with CPU yielding below 1 ms or sleeps then spins at 2 ms. The legacy scan is excluded from the ordered dose test. Mixed and the intervention use $r \in \{4, 16\}$ and $d \in \{0, 20\,\mu\text{s}, 200\,\mu\text{s}, 2\,\text{ms}\}$. Publication uses $r = 16$ and $d \in \{0, 200\,\mu\text{s}, 2\,\text{ms}\}$; Churn uses $r \in \{1, 4, 16\}$ at zero delay. Compaction uses $r \in \{4, 16\}$ and $d \in \{0, 200\,\mu\text{s}, 2\,\text{ms}\}$. Table count uses $r \in \{4, 16\}$ at zero delay, with 4, 16, 64, or 256 tables. Paced uses $r = 16$, $d \in \{0, 200\,\mu\text{s}, 2\,\text{ms}\}$, and $f \in \{0.2, 0.8\}$: 183/732, 155/619, and 72/286 writes/s at the three delays, each pair ordered $f = 0.2/0.8$. The settled campaign adds 700 writes/s at 200 μs.

The follow-up fixes $r = 16$, one paced writer, closed readers, and zero delay at 183, 366, 549, and 732 writes/s with a 16 MiB memtable, so no flush falls in a window. It adds one 732 writes/s cell with fsync off, one with a 1 MiB memtable reported in Appendix B, and a rerun of one Mixed cell ($r = 4$, zero delay, all three designs) that stores full read-latency histograms. H-F4 uses that last cell. Appendix B gives full cells and coverage.

Pairing holds seeds and operation-index streams fixed within each cell-round unit, while randomized interleaving limits order effects. Faster designs may complete longer stream prefixes. Most campaigns use ten matched triplets per cell; the intervention uses five four-run units pairing two designs and two commit paths. Throughput counts in-window completions divided by the measured window, except the intervention's fixed 10 s denominator; latency histograms retain all in-window completions, while synchronization and flush counters include drain.

Service and response times distinguish execution from queueing. Service runs from issue to completion; response runs from intended arrival to completion. Below 0.95 completed/offered writes a trial is flagged saturated. Unissued ticks have no latency, so completion tails under overload are censored from below; a ratio with a censored component need not bound the true ratio. We use r for readers, d for delay, W, R for throughput, $S = W_{\text{CL}}/W_{\text{L}}$, $q = R/(rW)$, $T = 1/W$, and w for mean first-acquisition wait.

Equivalence uses paired log ratios and the declared margin $[0.90, 1/0.90]$, described as $\pm 10\%$ on the multiplicative scale. Holm-adjusted TOST establishes equivalence; a CI wholly beyond the margin is not equivalent, and remaining results are inconclusive. Trend tests use exact Page tests; Appendix A defines families, CIs, and sensitivity checks.

Seven protocols were frozen before campaign trials, separating predictions from exploratory interpretation (Table II) [28]. The first five campaigns ran back to back without a deliberate pause, with a paced-load median gap of 0.04 s; the settled campaign added a pause, fresh seeds, and sentinel comparisons, and the follow-up kept the pause. All 2,499 retained trials succeeded on the first attempt, with no retries or dropped paired units; Appendix C records pre-freeze exposure and execution history.

V. HOW MUCH DOES HOLDING THE LOCK COST?

A. A saturated writer pays for the read hold

CoarseLock's write penalty increased with measured read-lock hold (Fig. 2, Table III). At about 34 μs and four readers it completed 7.4% fewer writes than Lease, ratio 0.926 with 95% CI $[0.881, 0.974]$; around 163–173 μs losses were 24–30%, and around 1.9 ms they were 64–69%. H1 supported

a decreasing ratio across doses at both reader counts, with Page's $L = 294$, exact one-sided $p = 7.86 \times 10^{-9}$, and ten paired blocks each. The point estimates were not strictly monotonic: at sixteen readers S rose from 0.937 to 0.944 between zero and 20 μs, with mean ranks 3.4 and 3.6. Below about 40 μs the largest point loss, 7.4%, is not a confidence bound: the 20 μs intervals were $[0.881, 0.974]$ and $[0.887, 1.004]$, allowing larger losses and, for sixteen readers, no loss. The legacy scan lost above 99% of writes at mean holds of about 125 and 430 ms.

TABLE III
MIXED WORKLOAD: MEASURED COARSELOCK HOLD AND PERCENTAGE CHANGE RELATIVE TO LEASE, USING PAIRED GEOMETRIC RATIOS. THESE ARE POINT ESTIMATES; APPENDIX B GIVES CIS.

r	Delay	Hold (μs)	Writes	Reads
4	0	13.6	-1.2%	+19.3%
4	20 μs	33.6	-7.4%	+45.2%
4	200 μs	163	-24.2%	+18.7%
4	2 ms	1,885	-63.9%	-27.5%
4	legacy scan	124,853	-99.6%	-51.1%
16	0	21.2	-6.3%	+9.7%
16	20 μs	39.3	-5.6%	+43.2%
16	200 μs	173	-29.5%	+9.3%
16	2 ms	1,915	-68.9%	-37.5%
16	legacy scan	430,130	-99.8%	-47.8%

Lease and Snapshot also slowed as delay increased in the exploratory comparison. Conflict validation reads SSTable blocks under the exclusive lock in every design, so Lease's mean commit cycle at four readers rose from 1.07 ms at zero delay to 2.79 ms at 2 ms. A shorter reader hold leaves that exclusive work in place.

The penalty did not collapse onto one curve of hold relative to the writer's cycle, under criteria fixed before the test cells were computed. This exploratory check used $x = h/T_{\mathrm{L}}$, CoarseLock's mean read hold over Lease's commit cycle, with the parameter-free model $S = 1/(1 + kx)$ and the same model using p95 hold. On 39 test cells, the mean-hold model's median absolute log residual was 0.031, inside the 0.105 bound, and its reader-count difference over 19 pairs was -0.042, also inside. Its largest residual was 0.307, beyond the 0.211 bound, so it fails. It fell inside the margin in 32 cells, including 6 of 8 cells with $k = 1$, and missed most at 2 ms with sixteen readers, where writes fell further than it predicts. The p95 model failed two criteria, with median 0.106 and largest 0.448. We therefore offer no transferable rule; Appendix B plots the cells.

B. Below capacity, the cost appears in medians

Below capacity, write throughput matched Lease while median write response rose with delay. H-P2 established equivalence in 6/6 paced cells. The earlier exploratory, descriptive p50 ratios were 1.093, 1.484, 2.681 with closed readers and 1.007, 1.336, 2.453 with open readers across zero, 200 μs, and 2 ms; the settled campaign then tested the trend on fresh data. H-M1 held in both modes with maximum Page's $L = 140$, exact $p = 1.65 \times 10^{-8}$, Holm-adjusted $p = 3.31 \times 10^{-8}$, and every round in the predicted order. Its response p50 ratios were 1.080, 1.431, 2.663 and 1.015, 1.332, 2.414, respectively. H-M2 held in all four higher-dose tests (Table IV). At zero delay there was no prediction; ratios 1.080 [1.067, 1.092] and 1.015 [0.998, 1.032] had 90% CIs inside the margin.

Both lock waits behind the median penalty were measured directly, supporting H-M3. At 2 ms with closed readers, CoarseLock's first wait was 1.952 [1.911, 1.993] ms and its flush check 2.105 [2.099, 2.112] ms, with 95% CIs, against 0.0003 and 0.027 ms for Lease. The exploratory phase account assigns about 82–93% of the excess total commit p50 at 200 μs and 2 ms to the two waits; medians do not add. Commit-phase distributions show what the median leaves out: CoarseLock's flush-check wait at 2 ms falls in two steps, with 56% of samples below 3 ms and the rest near 4.1 ms (Appendix B), a pattern we did not predict or analyse further. Figure 3 separates achieved throughput from service medians; Appendix B retains both reader modes and full paced results.

C. Past capacity, the queue is unstable

H-P3 failed at 200 μs because its offered rate placed capacity next to the equivalence boundary. It met only 4/6 predictions: zero-delay cells were equivalent and 2 ms cells not equivalent, with ratios 0.390 and 0.405, but 200 μs was inconclusive in both modes, 0.896 [0.866, 0.927] and 0.920 [0.898, 0.942] with 90% CIs. CoarseLock fell below the completion flag in 19 of twenty trials there. The flaw was visible before freezing: earlier capacity divided by offered rate was $545.8/619 = 0.882$, already next to the 0.90 margin. H-W repaired the design at 700 writes/s: ratios 0.792 [0.775, 0.808] and 0.840 [0.818, 0.863], with 90% CIs, were both not equivalent.

Overload produced a window-dependent backlog in the exploratory paced comparison. At 2 ms and $f = 0.8$, mean completion p99 was about 6.05 s, close to $10(1 - 111.0/286) = 6.12$ s. This is an unstable queue, so its completion-only backlog percentile is not steady-state latency.

D. The pre-registered p99 trend failed

H-P1 did not support the predicted rise in the write response p99 ratio below capacity. At $f = 0.2$, closed readers gave Page's $L = 123$, $p = 0.291$, adjusted $p = 0.291$; open readers gave $L = 128$, $p = 0.047$, adjusted $p = 0.093$. At $f = 0.8$, the respective L values were 139 and 138, with adjusted $p = 1.4 \times 10^{-6}$ and 1.0×10^{-5}; every round had a censored component. Those tests detect increasing completion-only tails associated with backlog, not increasing true offered-work p99s.

A few stalls made p99 fragile in the exploratory diagnosis. Cell/design median maximum write service lay in 53–74 ms, with individual maxima 32–103 ms across doses and designs. At zero delay and $f = 0.2$, p99 concerns roughly the 18th-worst of about 1830 writes; a stall spans about 10–13 arrival ticks at 183 writes/s. Closed-reader zero-delay per-round p99 ratios ranged from 0.03–105.76. An engine-free append/fsync probe had maxima 12.8–36.5 ms over 6 ten-second runs,




Fig. 2. Mixed workload: paired CoarseLock/Lease ratios against CoarseLock's arithmetic mean trial read-lock hold. Bars are 95% paired log-t CIs. Lines connect the four injected doses; hollow legacy scan points are unconnected. Measured hold is descriptive, not a separately randomized treatment.

TABLE IV

SETTLED CAMPAIGN, TEN ROUNDS PER CELL. THE WRITE RESPONSE P50 RATIO IS THE PAIRED GEOMETRIC COARSELOCK/LEASE MEAN WITH ITS 90% CI; PHASES ARE ARITHMETIC MEANS OF PER-TRIAL P50 IN MS; THE LAST COLUMN IS THE CELL MEDIAN OF THE TRIAL LARGEST FSYNC IN MS. AT 700 WRITES/S COARSELOCK IS PAST CAPACITY, SO ITS RESPONSE P50 IS A COMPLETION-ONLY BACKLOG FIGURE AND THOSE RATIOS ARE CENSORED, NOT TRUE LATENCY RATIOS.

			CoarseLock/Lease	CoarseLock		Lease		Largest
Delay	Writes/s	Readers	Response p50 [90% CI]	Lock wait	Flush check	Lock wait	Flush check	fsync
0	183	closed	1.080 [1.067, 1.092]	0.075	0.074	0.001	0.047	21.8
0	183	open	1.015 [0.998, 1.032]	0.000	0.066	0.000	0.062	11.4
200 μs	155	closed	1.431 [1.398, 1.464]	0.229	0.296	0.000	0.033	9.8
200 μs	155	open	1.332 [1.325, 1.340]	0.137	0.264	0.000	0.028	8.9
2 ms	72	closed	2.663 [2.640, 2.687]	1.952	2.105	0.000	0.027	6.9
2 ms	72	open	2.414 [2.372, 2.456]	1.846	2.088	0.000	0.018	7.2
200 μs	700	closed	599.389 [195.644, 1836.337]	0.268	0.281	0.001	0.032	31.5
200 μs	700	open	206.265 [54.672, 778.187]	0.226	0.262	0.000	0.031	31.5
0	732	closed	1.114 [1.009, 1.231]	0.060	0.065	0.003	0.042	31.5

showing host stalls without accounting for the larger engine band. Section VIII diagnoses that band and reports the tails after pausing.

VI. ADMISSION COUPLING

A. Reads follow exclusive acquisitions

The exploratory read crossover appeared while CoarseLock wrote less. With a saturated writer it read more than Lease through the 200 μs dose and less at 2 ms: four-reader ratios ranged from 1.19 to 1.45 before falling to 0.725, and sixteen-reader ratios from 1.09 to 1.43 before falling to 0.625 (Fig. 2). This crossover was unpredicted.

Admission coupling accounts for the crossover under CoarseLock with a continually waiting writer. If each exclusive acquisition admits approximately one read per reader, then

$$R_{\mathrm{CL}} \simeq k\, r\, W_{\mathrm{CL}}, \qquad k = 2 \text{ on the default path.} \tag{1}$$

Individual trials in the eleven non-legacy Mixed and Churn cells had $q = 2.002$–2.015, despite changing delay and reader count. Legacy q ranged from 1.98 to 2.29 with only about 26 commits per trial at four readers and six at sixteen.

Lease and Snapshot can miss the second admission while doing I/O outside the manager lock. Their cell mean q fell from about 1.7 at zero delay to about 1.3 at 20 and 200 μs and about one at 2 ms (Table V). At four readers and zero delay, read p50 was 45 μs for CoarseLock and 808 μs for Lease, while p99 was 2.27 and 2.31 ms. Those trials stored only percentiles, so the follow-up campaign stored full histograms and tested the shape they implied. H-F4 held: in this cell CoarseLock reads split into a fast group below 200 μs (55.5 [55.2, 55.8]%, 95% CI) and a slow group at or above 500 μs (44.4 [44.1, 44.7]%), with 0.11 [0.09, 0.13]% between them. Lease and Snapshot show the same two groups, with 55.4% and 55.4% in the slow one (Fig. 12, Appendix B). The slow group's median, 854–877 μs, is a little below the roughly 1 ms commit hold we traced at paced rates. This cell carries no trace, so blocking behind a commit is inferred from that similarity and not measured.




Fig. 3. Paced workload, closed-reader cells only. Points are arithmetic means of trial summaries, with frozen 95% t CIs. Solid filled markers show $f = 0.2$ and dashed hollow markers $f = 0.8$. Panel (a) marks the 0.95 completion flag; panel (b) shows write service p50, excluding scheduling delay. Open-reader cells showed the same broad pattern and are reported in the tables.

A descriptive cycle check is consistent with two reader waits per commit:

$$\widehat{T}_{\mathrm{CL}} = T_{\mathrm{L}} + 2w_{\mathrm{CL}}. \tag{2}$$

Arithmetic means of per-trial cycles gave prediction errors from -13.8% to $+10.6\%$ across ten Mixed cells. The second wait was assumed equal to the measured first wait; the direct measurements in Section V are below capacity.

B. What the read gain depends on

By definition of q, $R_{\mathrm{CL}}/R_{\mathrm{L}} = (q_{\mathrm{CL}}/q_{\mathrm{L}})\,S$. For the stored cell summaries the product of the mean-q ratio and S reproduces the read ratio to within 0.0001 (Table VI). CoarseLock read more than Lease in six Mixed cells, at zero, 20, and 200 μs with four and sixteen readers. The gain comes from CoarseLock's higher q; its lower write throughput, S below one in all six cells as a point estimate, shrinks it. Lease readers, doing I/O outside the lock, can miss the short second admission, and CoarseLock readers do not.

In two of the six cells the write-loss CI includes one while the read gain's excludes it: at four readers and zero delay, S was 0.988 [0.896, 1.089] and reads 1.193 [1.089, 1.308]; at sixteen readers and 20 μs, S was 0.944 [0.887, 1.004] and reads 1.432 [1.350, 1.519]. In those cells we detected a read gain and no write loss at ten pairs.

C. Changing acquisition count tests the account

The pre-registered intervention supported coupling by changing k below the flush threshold. An experiment-only flag, false by default, checks the threshold inside the first exclusive hold and skips the second acquisition when no flush is needed. At or above threshold the default path reacquires and rechecks before rotation and flush. Validation and WAL work remain shared. Five paired four-run units per cell compare CoarseLock and Lease on both paths, with the default rerun in the same session.

All P1–P3 criteria held (Fig. 4). P1 required mean CoarseLock q near acquisition count: individual trial ranges were 2.002–2.013 for $k = 2$ and 1.001–1.006 for $k = 1$. P2's six applicable ratio-of-read-ratios CIs lay below one; at four readers and 20 μs the ratio was 0.659, 95% CI $[0.595, 0.730]$. P3's cycle errors were -3.7% to $+7.5\%$ with two acquisitions and -2.0% to $+8.4\%$ with one, within the declared band; all four higher-dose write-improvement CIs exceeded one. Appendix A gives the exact predictions and Appendix B the full estimates.

With one acquisition, the CoarseLock/Lease read ratios at zero and 20 μs were 0.963 [0.897, 1.033] and 0.975 [0.882, 1.077] at four readers and 0.987 [0.895, 1.089] and 0.983 [0.897, 1.077] at sixteen, all with 95% CIs including one (Table VII). With one acquisition CoarseLock's read ratio was below one as a point estimate at every dose and reader count (0.864, 0.848, 0.630, and 0.559 at 200 μs and 2 ms), with CIs below one at those two doses. The read gain at injected delays up to 20 μs therefore depended on the redundant second acquisition. Removing it raised CoarseLock writes, with CIs above one, at 200 μs and 2 ms at both reader counts and at sixteen readers with zero delay; the CIs included one at four readers with zero delay and 20 μs and at sixteen readers with 20 μs. For Lease, write ratios were 0.970–1.044, all with CIs including one, while its reads fell to 0.608–0.850 of the two-acquisition level; CoarseLock's reads fell to 0.507–0.763. These are exploratory comparisons of five pairs. Through

TABLE V
EXPLORATORY ADMISSION AND CYCLE CHECK: ARITHMETIC MEANS OVER TEN TRIALS PER CELL. CYCLES ARE MS; ERROR IS $100(\widehat{T}/T - 1)$. CHURN REPORTS ADMISSION RATIOS ONLY.

Workload	r	Delay	q_{CL}	q_{L}	q_{S}	T_{CL}	$\widehat{T}_{\mathrm{CL}}$	Error (%)
Mixed	4	0	2.009	1.664	1.657	1.077	1.130	4.9
Mixed	4	20 μs	2.003	1.278	1.277	1.140	1.175	3.1
Mixed	4	200 μs	2.004	1.280	1.280	1.627	1.738	6.8
Mixed	4	2 ms	2.003	0.998	1.001	7.712	7.432	-3.6
Mixed	4	legacy scan	2.032	0.018	0.018	384.3	363.6	-5.4
Mixed	16	0	2.010	1.717	1.718	1.169	1.249	6.8
Mixed	16	20 μs	2.008	1.323	1.318	1.206	1.334	10.6
Mixed	16	200 μs	2.006	1.295	1.294	1.835	1.978	7.8
Mixed	16	2 ms	2.003	0.995	0.996	9.008	8.726	-3.1
Mixed	16	legacy scan	2.209	0.007	0.007	1,666.7	1,437.3	-13.8
Churn	1	0	2.009	1.080	1.081	–	–	–
Churn	4	0	2.009	1.100	1.099	–	–	–
Churn	16	0	2.013	1.104	1.101	–	–	–

TABLE VI
THE SIX MIXED CELLS WHERE COARSELOCK READ MORE THAN LEASE AT THE DEFAULT COMMIT. q VALUES ARE ARITHMETIC MEANS; S AND THE READ RATIO ARE PAIRED GEOMETRIC RATIOS WITH 95% t CIS, AS IN TABLE X.

r	Delay	q_{CL}	q_{L}	$q_{\mathrm{CL}}/q_{\mathrm{L}}$	S [95% CI]	$R_{\mathrm{CL}}/R_{\mathrm{L}}$ [95% CI]
4	0	2.009	1.664	1.208	0.988 [0.896, 1.089]	1.193 [1.089, 1.308]
4	20 μs	2.003	1.278	1.568	0.926 [0.881, 0.974]	1.452 [1.380, 1.528]
4	200 μs	2.004	1.280	1.565	0.758 [0.725, 0.793]	1.187 [1.136, 1.241]
16	0	2.010	1.717	1.171	0.937 [0.884, 0.993]	1.097 [1.041, 1.156]
16	20 μs	2.008	1.323	1.518	0.944 [0.887, 1.004]	1.432 [1.350, 1.519]
16	200 μs	2.006	1.295	1.550	0.705 [0.676, 0.736]	1.093 [1.048, 1.140]

TABLE VII
ONE-ACQUISITION COMMITS: COARSELOCK/LEASE READ RATIO WITH 95% PAIRED t CI AT THE TWO LOWEST DOSES.

r	Delay	$R_{\mathrm{CL}}/R_{\mathrm{L}}$ [95% CI]
4	0	0.963 [0.897, 1.033]
4	20 μs	0.975 [0.882, 1.077]
16	0	0.987 [0.895, 1.089]
16	20 μs	0.983 [0.897, 1.077]

200 μs both designs then had $q \simeq 1$, making the read ratio close to S; CoarseLock's read-ratio CIs fell below one at 200 μs, a crossing that was not separately predicted. Lease's one-acquisition q fell to 0.857–0.858 at 2 ms. Paired trial-p99 ratios were 1.330–2.049 for CoarseLock and 1.578–2.125 for Lease, descriptive raw-percentile summaries without CIs. Thus the default path's second acquisition admits readers as well as delaying writes.

D. Replication and the equal-write-rate bound

The exploratory paced counts replicated the coupling out of sample under closed readers. At $f = 0.8$, CoarseLock completed 547.2 writes/s at 200 μs and 111.0 at 2 ms, against earlier means 545.8 and 111.0. Reads were 17,560 versus $2rW = 17{,}511$, and 3,557 versus 3,552. Open readers have paced arrivals, so Equation 1 does not apply to their rates.

At write rates we could match, the read gain was absent in a descriptive comparison. With closed readers, $r = 16$, $f = 0.2$, and no flushes, CoarseLock and Lease achieved matched write rates at zero delay, 200 μs, and 2 ms, and the CoarseLock/Lease read ratios were 0.967 [0.912, 1.025], 0.921 [0.889, 0.954], 0.720 [0.711, 0.730], with 95% CIs. At $f = 0.8$ only the zero-delay cell had near-equal writes, with read ratio 0.776 [0.666, 0.904]. The 200 μs and 2 ms cells at $f = 0.8$ do not have equal writes, since CoarseLock completed 0.884 and 0.388 of its offered writes there, so they are not equal-rate evidence. No paced cell used 20 μs, where the saturated gain peaked. Below capacity the writer is not continually waiting, so this compares regimes. The comparison remains descriptive.

The exploratory compaction comparison exposed an unpredicted limit to the earlier read-gain account. At 2 ms the CoarseLock/Lease read ratios with compaction were 0.912 [0.892, 0.933] and 0.820 [0.806, 0.835] at four and sixteen readers, with 95% CIs, versus 1.154 and 1.081 without compaction. A post hoc, untested contributor is table count: off-condition CoarseLock flushed less and ended with cell means 8.0 tables versus Lease's 12.0. Admission and table-count contributions were not separated.

VII. WHEN DO LEASE AND SNAPSHOT DIFFER?

A. Throughput matches across publication

Lease and Snapshot met H2's throughput equivalence criterion in every Mixed and Publication cell. All ten write and




Fig. 4. Intervention, five paired four-run units per cell. Top: arithmetic mean reads per reader per commit. Bottom: paired geometric CoarseLock/Lease read ratios with 95% log-t CIs. Solid filled markers denote two-acquisition commits; dashed hollow markers denote one-acquisition commits below threshold.

fourteen read tests passed after Holm correction (Fig. 5), and all corresponding bootstrap intervals lay inside the declared margin. Publication at zero delay still had read ratio 0.970, 90% CI $[0.962, 0.978]$, a detectable roughly 3% difference within the margin. The exploratory tighter-margin check found 6 of ten write and 11 of fourteen read CIs inside $[0.95, 1/0.95]$; all failures of containment occurred at $d \leq 20$ μs, without a new adjusted equivalence test.

Publication completion differed only under the legacy scan, while publication waits were not established as equivalent. All designs completed twenty scheduled publications at non-legacy doses; under the legacy scan CoarseLock completed median 10.5, range 9–11, while Lease and Snapshot completed twenty. Their cell geometric publication-wait p99s stayed below 42 μs, but the zero-delay Lease/Snapshot ratio was 3.11, 90% CI $[1.54, 6.30]$, not equivalent; the other three cells were inconclusive (Appendix B).

B. Churn corrects the lifecycle attribution

The Lease control does not support attributing Churn's read deficit to Snapshot's lifecycle, an exploratory earlier reading. CoarseLock/Snapshot read ratios were 1.66, 1.53, and 1.29 across reader counts, and Lease also showed the deficit despite allocating no reader-set descriptors. H3 had no directional prediction: all Lease/Snapshot 95% paired-t CIs included one, while bootstrap intervals at one and sixteen readers narrowly excluded it for both outcomes, including the one-reader read interval $[0.909, 0.997]$; these data do not establish that Lease avoids the deficit.

C. Compaction preserved throughput; commit tails differed

Compaction preserved throughput equivalence, and commit-wait tails differed in an exploratory comparison. All twelve primary on tests met H-C after separate write and read Holm corrections, as did the twelve off reference tests. The closest write comparison was 0.949, 90% CI $[0.909, 0.991]$, at sixteen readers and 200 μs.

The exploratory tail comparison gave Lease commit-wait p99 ratios of 1.43–7.69 times Snapshot's, with every 95% paired CI excluding one (Fig. 6). Absolute arithmetic means were 21–246 μs for Lease, 12–177 μs for Snapshot, and 306–9221 μs for CoarseLock. CoarseLock and Lease open compaction inputs under the exclusive lock, while Snapshot opens them outside all locks; this asymmetry is not an established




Fig. 5. Lease/Snapshot throughput, ten triplets per cell. Points are paired geometric ratios; bars are 90% paired log-t CIs for Mixed and Publication, and 95% for Churn. Shading shows the rounded $[0.90, 1.11]$ margin. Churn was not an equivalence test.

cause of the tail gap. The campaigns ran back to back, and after the settled campaign's pause the rechecked ratio moved from 1.43 to 2.40 and was classed inconclusive (Section VIII). The cause of the tail difference is untested.

Turning compaction on raised write throughput by 1.17–2.66 and reads by 1.31–2.86 in the exploratory on/off comparison, while reducing overlapping tables from a maximum cell mean 70.0 to means 1.0–2.8; the comparison includes relief from read amplification.

D. Table count exposes per-read work

Read-only load separated Lease and Snapshot as table count grew, while free-writer throughput remained equivalent. H-T1 detected declining read ratios in both read-only families, Page's $L = 295$ and 296 with Holm-adjusted $p = 5.88 \times 10^{-9}$ and 1.60×10^{-9}, but not with a writer. All H-T2 predictions held: equivalence at four tables and read-only non-equivalence at 256 for both reader counts. Across the four counts, read-only ratios were 0.975, 0.956, 0.918, 0.712 at four readers and 0.989, 0.962, 0.851, 0.663 at sixteen. At sixteen readers, 64 tables already gave 0.851, 90% CI $[0.837, 0.866]$, not equivalent. At 256 tables the read-only ratios were 0.712 at four readers and 0.663, 90% CI $[0.660, 0.666]$, at sixteen, both not equivalent; the roughly 34% fewer reads applies to sixteen readers only. Lease/Snapshot read equivalence was not established at high write rates (Section VII-E). All sixteen applicable free-writer tests were equivalent, with ratios 0.943–1.045 (Fig. 7).

The exploratory critical-section evidence locates growing work in Lease's read path. Read-only mean holds grew with table count, spanning 326–3370 ns at four readers and 393–8512 ns at sixteen, while Snapshot stayed below 1 μs. Separate capture/release microbenchmarks cost Lease 27–974 ns at one goroutine and 58–1767 ns at sixteen, against Snapshot's 21 and 88–89 ns. Publication cost Lease 104–128 ns with no allocations and Snapshot 654–3200 ns with three, moving table-proportional work from reads to publication (Appendix B).

E. A high write rate leaves little time for readers

H-P4 and H-R left the same read comparison inconclusive twice. H-P4 established Lease/Snapshot write equivalence in 12/12 cells and closed-reader read equivalence in 5/6. At zero delay and $f = 0.8$, reads were 1.072 [0.910, 1.264], 90% CI, adjusted $p = 0.35$, with log-ratio SD 0.284. On fresh settled data H-R failed: writes were equivalent, 1.001 [0.994, 1.008], but reads remained inconclusive, 0.995 [0.846, 1.171], adjusted $p = 0.142$, SD 0.280.

The exploratory fsync on/off check reduced read spread at the same frozen load specification. Pooled log-read SD fell




Fig. 6. Compaction-on cells, ten triplets each. Left: Lease/Snapshot read throughput with 90% paired log-t CIs and the equivalence band. Right: arithmetic mean trial commit-wait p99 with 95% t CIs, in μs on a log axis. Ratio intervals and absolute-duration intervals use different summaries.

from 0.142 to 0.018, a ratio of 0.128 [0.086, 0.191] with a 90% F interval assuming normality; the read comparison moved from inconclusive to equivalent (Appendix B). Fsync off removes ordinary holds as well as bursts, implicating fsync without isolating bursts.

The exploratory hold-share account relates reads to time outside the writer's exclusive hold (Fig. 16, Appendix B). At 732 writes/s, median hold shares were 74.7% in the campaign, range 67.4–79.2, and 72.3% in the check, range 67.6–78.8, versus 4.3% with fsync off. Log reads tracked log free share with $r = 0.905$, slope 1.11 in the campaign and $r = 0.965$, slope 1.16 in the check; bursts occupied median 4.9–8.3% of the window. Adjusting the paired campaign ratio for free share tightened 0.995 [0.846, 1.171] to 1.003 [0.956, 1.052] and reduced log-ratio SD from 0.280 to 0.082. This adjusted CI is not a test of H-R, which stays failed; hold time is an outcome of the same trial and direction is not established.

A follow-up campaign tested this account on new data, setting the hold share through the write rate. Hold share rose from about 20% at 183 writes/s to about 72% at 732, and reads fell from about 370,000 to about 166,000 per second. The hold per commit stayed near one millisecond, 0.98–1.11 ms across rates and designs, and WAL sync took 94.1–96.3% of the exclusive hold (Table XXV). H-F2 held, with Page's $L = 299$ and adjusted $p < 0.001$ for both designs. The primary prediction, H-F1, failed. Across the four rates, the slope of log reads on log free share was 0.768 [0.731, 0.806] for Lease and 0.779 [0.745, 0.813] for Snapshot, with 90% CIs reaching below the predicted band $[0.80, 1.25]$ and excluding 1 (Fig. 8). Reads fall as the hold grows but not in proportion to free share. One candidate, which we have not tested, is that read cost falls as write rate rises. Writes in these cells use the read keys and stay in the memtable, and a read found in memory skips the SSTable search. The share of reads served from memory rose from about 0.08 at 183 writes/s to about 0.29 at 732, and reads per unit of free share rose from about 460,000 to about 600,000 per second. Write rate and memory share move together here, so these cells cannot separate this from a rival in which fsync costs readers more than its hold at low write rates. A frozen protocol that would separate them has not been run. The slopes above came from one write rate and do not measure this response.

One exploratory comparison holds the write rate fixed. At 732 writes/s, turning fsync off raised reads 3.414 and 3.530 times for Lease and Snapshot and free share 3.470 and 3.600 times, so read gain over free-share gain was 0.984 [0.963, 1.005] and 0.981 [0.950, 1.012] (90% paired-t CIs). Fsync off gives up durability, so this does not estimate what a commit-path change would recover. Memory share was similar in those two cells, and read gain tracked free-share gain, which fits a factor tied to write rate without establishing one.

H-F3 was partly supported on the read comparison that H-P4 and H-R left open. Lease/Snapshot reads were equivalent at 183 and 366 writes/s, 0.992 [0.979, 1.006] and 0.992 [0.918, 1.073] (adjusted $p = 0.048$), and inconclusive at 549, 0.983 [0.871, 1.108], adjusted $p = 0.106$. They stayed inconclusive at 732, 1.023 [0.839, 1.246], where we made no prediction, and were equivalent with fsync off, 0.989 [0.981, 0.998] (all 90% CIs). The log-ratio SD grew from 0.023 at 183 writes/s to 0.341 at 732 and was 0.015 with fsync off. The estimates are close to 1, but the intervals at 549 and 732 writes/s neither establish nor exclude a difference larger than the margin; at high write rates the comparison lacks the precision to show equivalence.




Fig. 7. Table-count campaign and separate lifecycle microbenchmark. Left: Lease/Snapshot read ratios with 90% paired log-t CIs; solid lines are read-only and dashed lines have one free writer. Right: arithmetic means of three benchmark counts, with no campaign CI. The benchmark isolates capture/release and excludes search and I/O.




Fig. 8. Reads against the share of the window outside the writer's exclusive hold, every Lease and Snapshot trial at four write rates and with fsync off, zero delay, closed readers, log axes. The dashed line has slope 1 through median fsync-off capacity. H-F1 predicted a slope in $[0.80, 1.25]$ across the four rates and failed.

VIII. Trial Spacing: A Methodology Lesson

A. Pauses removed the band

The exploratory diagnosis located the large write stall inside WAL fsync and found it when a trial started immediately after another. All 27 fsync-on diagnostic runs placed the largest commit's time there. In 9/9 same-specification pairs, the largest fsync was higher back to back: median 54.9 ms, range 45.7–73.0, versus 8.0 ms, range 5.7–17.0, after 30 s pauses, with nonoverlapping ranges. Deleting a trial-shaped directory alone did not reproduce the effect. Calibration pauses of at least 15 s removed the band above about 45 ms in 18/18 trials; the settled protocol froze 20 s. The cause is unknown.

H-S is a protocol check, and it held at a threshold we raised from 25 to 40 ms after seeing the calibration trials and before any campaign trial. Three of 18 design-level medians (31.4–31.5 ms) exceed 25 ms, so H-S would have failed at the draft threshold. Realized pauses were 20.003–20.030 s, with design-level medians of the largest fsync at 6.9–31.5 ms. Cell medians of largest write service descriptively fell from 54–59 to 9.5–22 ms; one trial still reached 81.3 ms.

B. Rechecked classes held while tails moved

R-check triggered no rerun and contradicted no rechecked published class. Of 22 metrics, 17 were unchanged, 5 inconclusive, and 0 changed; none of 9 published classes was contradicted. The five inconclusive metrics were the Publication lock-wait p99 Lease/Snapshot ratio, the compaction commit-wait p99 Lease/Snapshot ratio, and three five-round intervention throughput ratios whose intervals extended beyond the margin; they do not rule out change. The compaction tail ratio moved from 1.43 to 2.40, as Snapshot's median trial p99 fell from 0.177 to 0.104 ms while Lease's remained near 0.245 and 0.232 ms.

The exploratory tail recheck showed substantial distortion at 2 ms and unusable zero-delay tails after pausing. CoarseLock cell-median response p99 fell from 25.95 to 11.17 ms with closed readers and 34.41 to 11.70 ms with open readers;

geometric CoarseLock/Lease ratios fell from 4.04 to 1.85 and 4.98 to 1.64. H-P1 stands as failed. Zero-delay p99 log-ratio SD remained 3.16 and 2.05.

C. The bare-loop prediction failed

The exploratory burst check failed to reproduce the engine pattern from rate alone. Fsyncs near 31 ms became more common with engine write rate: trials with an fsync of at least 25 ms rose from 6/60 at 72 writes/s to 88/90 at 650–730 writes/s (Appendix B). The engine-free append/fsync prediction, at least 8 of 10 runs with such an fsync at 700 writes/s, failed: only 5 of 10 did; rate/burst Spearman correlation was 0.40, unadjusted $p = 0.010$. In 5 bare runs across rates the only slow fsync was the first, at 47.4–51.8 ms. The 4 runs with real bursts were all among the first ten of forty despite shuffled rates. Flushes, readers, data volume, and run order, with bare runs first, were not separated, and the cause remains unknown. Pause between storage trials, report the gap, and check results against a paused sentinel.

IX. Discussion

A reader-side lifetime fix helps when writers wait on lock-held lookups at the intended write load or those waits limit capacity. Admission coupling makes the read/write balance part of that decision, and the writer's own exclusive work bounds either replacement.

As a worked example, consider a team whose engine holds a coarse read lock across lookups and that is considering Lease. The figures are this study's and show how to read each measurement; the team should take its own.

1) **Measure the hold and split the writer's time.** The team records lock-held lookup time and divides each commit into validation, synchronization, and lock waits. Only the lock waits can be recovered. With a saturated writer, our observed write losses stayed below about 8% at holds below about 40 μs, then reached 24–30% around 170 μs and 64–69% around 1.9 ms. Lease's own commit cycle at four readers still grew from 1.07 to 2.79 ms with delay, because validation reads delayed blocks under the exclusive lock.
2) **Compare at the intended write rate.** The team next asks whether its writer runs at capacity. Below capacity, Lease has little write throughput to recover, since CoarseLock already matched it within the margin; what it improves is median write response, where CoarseLock's ratio reached 1.33–1.43 at 200 μs and 2.41–2.66 at 2 ms. Past CoarseLock's capacity, Lease also recovers throughput and avoids a growing backlog: at 700 writes/s and 200 μs, CoarseLock completed 0.792 and 0.840 of Lease's writes with closed and open readers.
3) **Count acquisitions and judge reads at equal write rates.** A saturated-writer benchmark may show CoarseLock reading more than Lease at short holds and seem to argue against the change. In our data that gain depended on the redundant second acquisition and was absent at the matched write rates we measured, so the team compares reads at the rate it will run. It also counts exclusive acquisitions per commit, since that count sets k. Removing a second acquisition is a different fix with its own trade-off: in our intervention CoarseLock gained writes at 200 μs and 2 ms, while its reads fell to 0.507–0.763 of the two-acquisition level and read p99 rose.
4) **Test the intended table count and tails.** Lease does work per active table on every read. If the load is read-heavy with many tables, the team should test Snapshot too: with sixteen readers and no writer, Lease's read ratio to Snapshot was 0.851 at 64 tables and 0.663 at 256, while Snapshot moved that work to publication. With a free writer, all comparisons stayed equivalent. If commit tails matter under compaction, the team should test them directly: Lease's commit-wait p99 exceeded Snapshot's in one exploratory, back-to-back comparison, and the cause is untested.
5) **Measure the writer's hold share and space the trials.** At a high write rate our writer held the lock across fsync for about three quarters of the window, and reads fell as that hold grew. If the team sees this, neither replacement returns that time, and commit-path work such as group commit, which we did not test, is the next candidate. Finally, the team separates trials with a pause and checks results against a paused sentinel, since back-to-back runs here distorted p99 while rechecked throughput classes held.

The decision then follows from the measurements. A reader-side fix is worth testing when holds are long enough to cost writes at the intended rate. No throughput comparison favoured Lease over Snapshot beyond the declared margin: the two were equivalent at small table counts, and Snapshot read more under read-only load at high table counts. Complexity was not measured. Lease's cheaper publication appears in a microbenchmark and was not visible end to end; the zero-delay publication lock-wait p99 ratio was 3.11, 90% CI $[1.54, 6.30]$, not equivalent. When holds are short or the writer's own hold dominates, the team should look at the commit path first.

A. What we did not test

Further experiments must isolate overlapping-table search, independently queued writes, multiple writers, longer windows, burst and carry-over triggers, fsync outside the lock with group commit, other admission policies, real device reads on larger datasets, and other operating systems. Intervening on compaction input opening could test whether it explains the tail gap. The read-cost candidate in Section VII-E remains untested; the protocol to separate it from the fsync rival was frozen and has not been run.

X. Threats to Validity

A. Construct

Injected delay controls read cost rather than reproducing a device. The small dataset was likely page-cache resident, with no application block cache; every visited block incurs delay,

and the treatment changes from yielding spin to mostly sleep. Sixteen readers run on twelve logical CPUs. Closed-loop readers can understate latency relative to open arrivals [33]; paced readers add open load, but unissued write ticks still have no latency observation, including some trials above the completion flag. The overloaded queue and its censored tails depend on the measurement window. Synchronization and flush counters include drain, unlike throughput; publication p99 is near a maximum over twenty events, and full read histograms exist for one Mixed cell only.

Compaction and table-count variants isolate limited workload features. The first two campaigns had no compaction; the later merge-all timer differs from production level- or size-based policies, and on/off comparisons also change read amplification. Disjoint table ranges shrink under a fixed keyspace, while every design still does range comparisons. Synthetic lifecycle microbenchmarks exclude search, memory-tier lookup, and I/O, prime scratch storage, and use a Lease helper and spare publication slice capacity.

B. Internal

Host state remains a source of variation despite pairing and randomized order [30]. First-campaign drift was $D = 0.979$, $|\ln D| = 0.021$, below 0.10; CoarseLock and Snapshot end/start read ratios were about 1.09 with logs 0.087 and 0.090, each based on single anchors. Later campaigns had no anchors. Back-to-back running affected the first five campaigns, and settled sentinels cover only rechecked cells while confounding the pause with date, rebuilt binary, tracing, and seeds. Bursts near 31 ms were uncontrolled. Settled execution deviations included helper activity, an overlapping status check, and the running desktop application; Appendix C records them in full.

The untested read-cost candidate in Section VII-E remains confounded with write rate. The shared writer path constrains both mechanisms and attribution. WAL fsync remains under the exclusive lock without group commit; the separate exploratory fsync-off diagnostic reduced commit p50 from 1.114 to 0.083 ms for Lease, 1.106 to 0.080 ms for Snapshot, and 1.229 to 0.167 ms for CoarseLock, with three runs each. Delayed writer validation was noticed after collection, correcting the first protocol's reader-only statement. The default second acquisition remains common to all designs; the cycle check assumes its wait at saturation, while settled timing measures it below capacity. The compaction input-open asymmetry was disclosed before that campaign, is not intrinsic to leasing, and was not experimentally isolated. Smoke exposure, aborted starts, power-overlay history, and the race-detector context are in Appendix C.

C. External

One engine on one Windows host, at most one writer, injected delay, and fsync under the exclusive lock define the study's scope. Production engines may use group commit, block caches, different validation and publication, multiple writers, or different admission policies. These implementations do not reproduce LevelDB, RocksDB, or Pebble. The coupling equation describes this Go lock and workload rather than a general readers-writers law; the sole experimenter and analyst has no independent replication.

D. Statistical

The equivalence margin is the author's judgment rather than a production requirement. Holm adjustment applies within declared families, not across all outcomes. Churn has no equivalence prediction; CIs including one do not establish equality, and a missing writer-present trend does not establish absence of per-table cost. The intervention has five paired units, omits Snapshot, and has no multiplicity correction, including P2. Its rerun baseline reproduced admission but not identical ratios: sixteen-reader 20 μs S was 0.855 versus 0.944 earlier, and cohorts were not pooled. Tighter-margin containment uses the paired-t CIs and is post hoc and unadjusted; bootstrap sensitivity does not remove paired-inference assumptions.

New-data predictions preserve their exploratory origins. The admission account followed the first campaign, and settled hypotheses arose from earlier outcomes, as did the follow-up's, whose latency bounds drew on percentiles already seen. The fsync checks are unadjusted; post hoc hold-share adjustment cannot establish causal direction or repair H-R. Free-share capacity scaling undershot reads by mean 0.14–0.19 in log, and hold/burst correlations differed, 0.44 versus 0.94. In the follow-up, reads went from about 19% below that scaling at 183 writes/s to about 5% above it at 732, so free share gives a direction and not a calibrated model, and bursts do not explain all variation. The compaction-tail interpretation and the read-cost candidate remain untested; within-host repetition does not replicate machines or implementations. In the collapse check, x and S share Lease's measurements, and the development cells were seen before the criteria were written, so they do not count as evidence.

XI. Related Work

LSM concurrency work pursues scalability across more engine components than reader lifetime. The LSM-tree and subsequent survey frame the storage design [1], [2]; cLSM uses non-blocking structures with shared-exclusive coordination around merge pointer updates [7], FloDB scales the memory component [8], and RocksDB's development history describes broader production priorities [6]. SILK schedules internal I/O to prevent latency spikes [9], while performance-stability work studies write stalls [10]. Our fixed-timer on/off comparison includes read amplification and does not decompose background-work cost.

Reclamation and synchronization research explain different parts of the trade-off. Hazard pointers and comparisons with epoch and quiescent-state methods address lifetime protection without a globally optimal scheme [19], [20]. Scalable, phase-fair, NUMA-aware, passive, and biased reader-writer locks address admission and reader costs [13]–[17]. Our coupling result connects admission to completed storage reads and writes

through exclusive acquisitions per logical commit. Group commit and Aether's early lock release and flush pipelining address writer work that the reader-side replacements retain [21], [22].

Evaluation literature motivates separating throughput, latency, and workload construction. Benchmarking guidance identifies measurement and host-state pitfalls [29]–[32]; open versus closed load changes queueing interpretation [33]. Equivalence testing and pre-registration separate a declared tolerance from prediction and observation [27], [28]. The carry-over diagnosis adds a concrete reason to check storage-trial spacing against a paused sentinel.

XII. Conclusion

A reader-side lifetime fix helps when shortening the read hold relieves writer waiting at the intended load; the writer's own critical section bounds the gain. Admission coupling ties CoarseLock reads to exclusive acquisitions and writes, so its saturated-writer read gain depends on the redundant second acquisition and was absent at the matched write rates we measured. Below capacity the cost appears in median response through both lock waits, while reads fall as the writer's hold share rises, though not in proportion. Lease and Snapshot match throughput within the declared margin across publication and compaction, and read-only load at high table counts separates them; read equivalence was not established at high write rates. Trials started immediately after another had a largest fsync near 55 ms that pauses removed, the cause is unknown, and rechecked throughput classes held. These results cover one engine on one Windows host, at most one writer, injected delay, and WAL fsync under the exclusive lock.

Acknowledgment

Anthropic's Claude and OpenAI's Codex were used to assist with engineering, analysis scripts and drafting of text. The author reviewed the results and is responsible for the content.

Artifact Availability

The repository is https://github.com/itsramhere/selfdbms, with campaign records on branches `research/x-readcost` and `research/x-phase3`. Evidence is indexed by `paper/CLAIM_EVIDENCE_MAP_X.md`; the reproducibility appendix is `paper/REPRODUCIBILITY_APPENDIX.md`, and paper names map to repository identifiers in `paper/REPOSITORY_IDENTIFIERS.md`. Appendix A records protocols and provenance, Appendix B the full results, and Appendix C execution history.

References

[1] P. O'Neil, E. Cheng, D. Gawlick, and E. O'Neil, "The log-structured merge-tree (LSM-tree)," *Acta Informatica*, vol. 33, no. 4, pp. 351–385, 1996.

[2] C. Luo and M. J. Carey, "LSM-based storage techniques: a survey," *The VLDB Journal*, vol. 29, no. 1, pp. 393–418, 2020.

[3] S. Ghemawat and J. Dean, "LevelDB." [Online]. Available: https://github.com/google/leveldb

[4] Meta Platforms, "RocksDB." [Online]. Available: https://github.com/facebook/rocksdb

[5] Cockroach Labs, "Pebble." [Online]. Available: https://github.com/cockroachdb/pebble

[6] S. Dong, A. Kryczka, Y. Jin, and M. Stumm, "RocksDB: Evolution of development priorities in a key-value store serving large-scale applications," *ACM Trans. Storage*, vol. 17, no. 4, Art. 26, 2021.

[7] G. Golan-Gueta, E. Bortnikov, E. Hillel, and I. Keidar, "Scaling concurrent log-structured data stores," in *Proc. EuroSys*, 2015, Art. 32.

[8] O. Balmau, R. Guerraoui, V. Trigonakis, and I. Zablotchi, "FloDB: Unlocking memory in persistent key-value stores," in *Proc. EuroSys*, 2017, pp. 80–94.

[9] O. Balmau, F. Dinu, W. Zwaenepoel, K. Gupta, R. Chandhiramoorthi, and D. Didona, "SILK: Preventing latency spikes in log-structured merge key-value stores," in *Proc. USENIX ATC*, 2019, pp. 753–766.

[10] C. Luo and M. J. Carey, "On performance stability in LSM-based storage systems," *Proc. VLDB Endow.*, vol. 13, no. 4, pp. 449–462, 2019.

[11] W. Pugh, "Skip lists: A probabilistic alternative to balanced trees," *Commun. ACM*, vol. 33, no. 6, pp. 668–676, 1990.

[12] P. J. Courtois, F. Heymans, and D. L. Parnas, "Concurrent control with 'readers' and 'writers'," *Commun. ACM*, vol. 14, no. 10, pp. 667–668, 1971.

[13] J. M. Mellor-Crummey and M. L. Scott, "Scalable reader-writer synchronization for shared-memory multiprocessors," in *Proc. PPoPP*, 1991, pp. 106–113.

[14] B. B. Brandenburg and J. H. Anderson, "Reader-writer synchronization for shared-memory multiprocessor real-time systems," in *Proc. ECRTS*, 2009, pp. 184–193.

[15] I. Calciu, D. Dice, Y. Lev, V. Luchangco, V. J. Marathe, and N. Shavit, "NUMA-aware reader-writer locks," in *Proc. PPoPP*, 2013, pp. 157–166.

[16] R. Liu, H. Zhang, and H. Chen, "Scalable read-mostly synchronization using passive reader-writer locks," in *Proc. USENIX ATC*, 2014, pp. 219–230.

[17] D. Dice and A. Kogan, "BRAVO: Biased locking for reader-writer locks," in *Proc. USENIX ATC*, 2019, pp. 315–328.

[18] The Go Authors, "sync package: RWMutex." [Online]. Available: https://pkg.go.dev/sync#RWMutex

[19] M. M. Michael, "Hazard pointers: Safe memory reclamation for lock-free objects," *IEEE Trans. Parallel Distrib. Syst.*, vol. 15, no. 6, pp. 491–504, 2004.

[20] T. E. Hart, P. E. McKenney, A. D. Brown, and J. Walpole, "Performance of memory reclamation for lockless synchronization," *J. Parallel Distrib. Comput.*, vol. 67, no. 12, pp. 1270–1285, 2007.

[21] D. J. DeWitt, R. H. Katz, F. Olken, L. D. Shapiro, M. R. Stonebraker, and D. A. Wood, "Implementation techniques for main memory database systems," in *Proc. ACM SIGMOD*, 1984, pp. 1–8.

[22] R. Johnson, I. Pandis, R. Stoica, M. Athanassoulis, and A. Ailamaki, "Aether: A scalable approach to logging," *Proc. VLDB Endow.*, vol. 3, no. 1–2, pp. 681–692, 2010.

[23] E. B. Page, "Ordered hypotheses for multiple treatments: A significance test for linear ranks," *J. Amer. Statist. Assoc.*, vol. 58, no. 301, pp. 216–230, 1963.

[24] D. J. Schuirmann, "A comparison of the two one-sided tests procedure and the power approach for assessing the equivalence of average bioavailability," *J. Pharmacokinet. Biopharm.*, vol. 15, no. 6, pp. 657–680, 1987.

[25] S. Holm, "A simple sequentially rejective multiple test procedure," *Scand. J. Statist.*, vol. 6, no. 2, pp. 65–70, 1979.

[26] B. Efron, "Bootstrap methods: Another look at the jackknife," *Ann. Statist.*, vol. 7, no. 1, pp. 1–26, 1979.

[27] D. Lakens, "Equivalence tests: A practical primer for t tests, correlations, and meta-analyses," *Soc. Psychol. Personal. Sci.*, vol. 8, no. 4, pp. 355–362, 2017.

[28] B. A. Nosek, C. R. Ebersole, A. C. DeHaven, and D. T. Mellor, "The preregistration revolution," *Proc. Natl. Acad. Sci. USA*, vol. 115, no. 11, pp. 2600–2606, 2018.

[29] A. Georges, D. Buytaert, and L. Eeckhout, "Statistically rigorous Java performance evaluation," in *Proc. OOPSLA*, 2007, pp. 57–76.

[30] T. Mytkowicz, A. Diwan, M. Hauswirth, and P. F. Sweeney, "Producing wrong data without doing anything obviously wrong!," in *Proc. ASPLOS*, 2009, pp. 265–276.

[31] T. Hoefler and R. Belli, "Scientific benchmarking of parallel computing systems," in *Proc. SC*, 2015, pp. 1–12.

[32] A. Traeger, E. Zadok, N. Joukov, and C. P. Wright, "A nine year study of file system and storage benchmarking," *ACM Trans. Storage*, vol. 4, no. 2, Art. 5, 2008.
[33] B. Schroeder, A. Wierman, and M. Harchol-Balter, "Open versus closed: A cautionary tale," in *Proc. NSDI*, 2006.

APPENDIX A
PROTOCOLS

A. Hypotheses, margins, and statistical methods

The first campaign's H1 tests a decreasing S across the four non-legacy doses using the one-sided exact Page test [23], blocked by triplet. H2 uses two one-sided tests (TOST) [24], [27] on paired log Lease/Snapshot ratios. It reports exponentiated 90% paired-t CIs and applies Holm correction [25] separately to ten write, fourteen read, and four publication lock-wait p99 tests. An adjusted $p < 0.05$ establishes equivalence; a CI wholly beyond a margin is classified not equivalent, and other outcomes are inconclusive. H3 reports two-sided 95% paired-t CIs under Churn without a directional prediction. Descriptive ratios use 95% CIs. Percentile bootstrap sensitivity [26] uses 10,000 resamples and fixed seeds; it does not replace the planned tests. Cells are not pooled, and no planned write-zero adjustment was needed.

The margin is fixed before data at $\pm\ln(1/0.90)$, or ratios $[0.90, 1/0.90]$, described here as $\pm 10\%$ on the multiplicative scale. It is the author's judgment of a difference small relative to the complexity difference between designs, chosen so ten pairs could resolve it. It is not derived from a production requirement. The pre-registration used a pilot standard deviation of paired log ratio near 0.06, giving an expected 90% CI half-width near 0.035 at ten pairs. Full CIs let readers apply a tighter margin.

The new campaigns preserve this method while defining their own families. The compaction primary hypothesis (H-C) predicts equivalence in all six on cells for each of writes and reads, with separate six-test Holm families; off cells form separate reference families. The table-count trend hypothesis (H-T1) uses four Page tests, one per reader-count and writer-count combination, with Holm across those four. Its equivalence families (H-T2) contain sixteen read and eight applicable write tests. H-T2 predicts equivalence at four tables for each applicable outcome and non-equivalence for reads at 256 tables without a writer. The intervention has five paired units per cell and 95% CIs without multiplicity correction, as specified before data.

The paced-load primary hypothesis (H-P1) predicts an increasing CoarseLock/Lease write response p99 ratio with delay, using four Page tests and Holm across the load-fraction and reader-mode combinations. H-P2 predicts below-capacity write-throughput equivalence in six cells; H-P3 predicts equivalence at zero delay and a CoarseLock ratio below the margin at the two higher doses under the higher offered fraction, with separate six-test Holm families. H-P4 predicts Lease/Snapshot throughput equivalence in twelve write and six closed-reader tests, with separate Holm families and no open-reader read-throughput test. Median latency and Lease/Snapshot tails have no prediction. Censored components remain in the primary completion-tail test and are disclosed rather than treated as true p99s.

The settled primary hypothesis (H-M1) predicts a rising CoarseLock/Lease write response p50 ratio with delay at $f = 0.2$, using two Page tests with Holm across reader modes. H-M2 predicts non-equivalence, with CoarseLock higher, at 200 μs and 2 ms in both reader modes. H-M3 predicts that CoarseLock's lock-wait and flush-check p50s each lie in $[1, 3]$ ms at 2 ms with closed readers, and Lease's below 0.5 ms, with 95% t CIs wholly inside each band. H-W predicts CoarseLock/Lease write non-equivalence at 700 writes/s. H-R predicts Lease/Snapshot read and write equivalence in the previously inconclusive cell. H-S is a protocol check that the median largest fsync stays below 40 ms in every $f = 0.2$ cell and design. The threshold was raised from 25 to 40 ms after the calibration trials were seen and before any campaign trial; three of 18 design-level medians (31.4–31.5 ms) exceed 25 ms. The sentinel rule R-check compares 22 metrics with their originals using a 90% Welch interval on the change, with margin $\ln(1/0.90)$ for throughput and $\ln 1.5$ for tails, and classifies each as unchanged, changed, or inconclusive. A changed metric or a contradicted published class commits us to rerunning that campaign. These hypotheses were generated from earlier data and tested on fresh seeds.

The follow-up primary prediction H-F1 takes, per round and design, the OLS slope with intercept of log reads on log free share across the four F1 write rates. Each of Lease and Snapshot must have its arithmetic mean slope's two-sided 90% t CI wholly inside $[0.80, 1.25]$; both are required, with no multiplicity adjustment. Write rate is the treatment and free share is measured. The band was a judgment fixed before the campaign data: proportional reads give 1, and the earlier post hoc slopes lay inside it.

H-F2 predicts reads rising as write rate falls, separately for Lease and Snapshot: one-sided Page's L, 10 rounds as blocks, cells ordered 732, 549, 366, 183 writes/s, predicted ranks 1, 2, 3, 4, $\alpha = 0.05$, Holm across the 2 tests, using `page_trend_test(method='auto')`. H-F3 predicts Lease/Snapshot read equivalence at 183, 366, and 549 writes/s, with paired log-ratio TOST at $\alpha = 0.05$, margin $[0.90, 1/0.90]$, exponentiated 90% paired-t CIs, and one 3-test Holm family. The 732 writes/s comparison has no prediction because it was previously inconclusive twice; it is descriptive.

H-F4 predicts, for CoarseLock in the Mixed histogram cell, arithmetic mean trial shares, as fractions of the trial's reads, of at least 0.20 (20%) below 200 μs and at or above 500 μs, and at most 0.10 (10%) between those bounds. The result tables report the same shares as percentages, so a valley share of 0.11% lies far below the 10% ceiling. Each two-sided 95% t CI must lie wholly on the predicted side; all three must hold, with no Holm family. Lease and Snapshot's shares are descriptive. The region bounds and share thresholds were judgments fixed before the campaign data; the region bounds drew on first-campaign percentiles already seen. A bucket belongs to the region containing its lower bound, including buckets crossing a boundary. Protocol check H-X predicts no measured flush in any F1 or fsync-off F3 trial. Any flush is reported and the trial retained; H-F1 is then reported both with and without that round, with the inclusive analysis remaining the frozen one.

The five-round design pairs both conditions in Coarse-

Lock and Lease within each cell. P1 predicts CoarseLock's arithmetic mean q in $[1.90, 2.10]$ under two acquisitions and $[0.90, 1.10]$ under one, in all eight cells. P2 predicts that removing the acquisition lowers CoarseLock's read ratio relative to Lease at delays up to 200 μs: the 95% paired-t CI of the ratio of read ratios must lie wholly below one in six cells. These are unadjusted five-pair comparisons, of descriptive strength as specified in the protocol. P3 predicts cycle error within $\pm 15\%$ for both conditions, using two waits or one as appropriate, and a CoarseLock write improvement with its 95% CI above one at 200 μs and 2 ms.

R-check is the paper name for the settled sentinel rule stored under frozen JSON key `H_C` in `research/experiments/phase_i7/X_READCOST/analysis_settled/x_settled_results.json`. The frozen `research/experiments/phase_i7/X_SETTLED_PREREGISTRATION.md` calls it the sentinel rule H-C; that historical name maps to R-check here. Compaction H-C retains its hypothesis name and is a separate test. R-check's unchanged, changed, and inconclusive categories use the 90% Welch CI on the new minus original mean paired log ratio; a changed metric or a contradicted published class triggers a rerun, while inconclusive does not rule out change. Class contradiction means a previously equivalent outcome has a new unadjusted interval wholly outside the throughput margin, or a previously not-equivalent outcome has one wholly inside. These trigger checks are not Holm-adjusted and compare combined changes in pause, date, binary, and seeds.

The remaining measurements preserve their original descriptive status. Cells are not pooled. Median and tail trends outside the declared predictions, stall and backlog comparisons, and the earlier fsync and hold-share accounts remain exploratory; tracing outcomes are not covariates fixed before treatment.

B. Campaign cells and auxiliary measurements

The seven campaigns deliberately extend the lifetime activity covered by the initial measurements. Table IX counts diagnostics from trial envelopes, including drain. Mixed includes the nine anchor trials and had at most one flush per trial. Publication and Churn exercised reader-set publication, but the first campaign and the intervention ran no compactions because the compaction trigger was disabled. Since Lease and Snapshot differ most when reader sets change, throughput equivalence in a mostly stable set did not establish equivalence under file retirement. The compaction campaign was run to close that gap.

The intervention isolates acquisition count in eight Mixed-shaped cells: two reader counts and four non-legacy doses. It compares the default two-acquisition commit with a one-acquisition commit below the flush threshold in CoarseLock and Lease. Five rounds share a seed across each four-run cell-round unit, giving 160 trials. The default condition is rerun in the same session rather than borrowed from the first campaign. Snapshot is omitted. Section VI-C gives the predictions and exact change.

The compaction campaign uses Churn-shaped cells with $r \in \{4, 16\}$, $d \in \{0, 200, 2000\}$ μs, and compaction on or off. On uses a fixed 250 ms timer that merges all active tables into one; calls with at most one table do no work. Twelve cells, three designs, and ten rounds give 360 trials. On and off share seeds within the same reader-count, delay, and round. The implementation has a disclosed asymmetry: CoarseLock and Lease open compaction inputs under the exclusive lock, whereas Snapshot opens them outside all locks. This is not an inherent requirement of leasing.

The table-count campaign removes overlapping-table search as a factor by constructing disjoint ranges. It crosses $N \in \{4, 16, 64, 256\}$, $r \in \{4, 16\}$, and zero or one free-running writer. Sixteen cells, three designs, and ten rounds give 480 trials. The fixed 10,240-key space yields 2,560, 640, 160, or 40 keys per initial table. Delay is zero, the memtable threshold is 1 MiB, and no compaction is scheduled. A writer may still flush, so the analysis retains initial and final counts. All designs perform up to N in-memory range comparisons, under the manager lock only in CoarseLock.

Separate lifecycle microbenchmarks in the table-count results measure capture/release at one and sixteen goroutines and uncontended publication from N to $N+1$ tables. They exclude table search, memory-tier lookup, and disk I/O. Lease's test helper mirrors its scratch-copy and lease path; Snapshot uses its production pin/release path. The publication benchmark includes immediate retirement of an unpinned old Snapshot set; Lease models amortized append with spare slice capacity. Scratch is primed before timing. We report the arithmetic mean of three benchmark counts, separately from campaign throughput, without confirmatory tests.

The paced-load campaign tests whether the saturated-writer results persist at a fixed offered rate. It uses sixteen readers, one paced writer, three delay levels, two fractions of earlier Lease write capacity, and closed or open readers, with no compaction. Twelve cells over ten three-design rounds give 360 trials. The frozen rates are listed below; Section IV defines service time, response time, and censored completion tails.

The settled campaign repeats selected comparisons with a 20 s pause before every trial, after the diagnosis in Section VIII. It has nine paced cells: three delays at $f = 0.2$ with closed and open readers; 700 writes/s at 200 μs with closed and open readers, a rate chosen so earlier CoarseLock capacity was 0.78 of the offered rate; and the closed zero-delay $f = 0.8$ cell whose read comparison had been inconclusive. Ten three-design rounds give 270 trials, with commit-phase timing, a 1 ms heartbeat goroutine, and per-reader slowest-read tracking enabled. Sentinel cells copy specifications from each earlier campaign without that tracing and add 200 trials, for 470 in total, all on fresh seeds.

The follow-up campaign has 7 cells and 150 trials, with 10 paired rounds per cell. Its 6 paced cells use Lease and Snapshot, closed readers with $r = 16$, one writer, and zero delay. The four F1 cells vary intended writes over 183, 366,

549, and 732 writes/s. Their 16 MiB memtable keeps flushes out of the measured windows. F2 changes only that threshold to 1 MiB at 732 writes/s. F3 turns fsync off at 732 writes/s with the 16 MiB threshold. F4 copies the first campaign's four-reader, zero-delay Mixed cell for CoarseLock, Lease, and Snapshot, adding full read histograms. The paced cells retain commit-phase traces; F4 has no trace, so its hold share is unavailable.

The Paced workload fixes $r = 16$ and uses one paced writer, four initial tables, no compaction, and a 10 s measurement window. It crosses $d \in \{0, 200, 2000\}$ μs, offered write fractions $f \in \{0.2, 0.8\}$ of earlier Lease saturated capacity, and closed or open readers. Twelve cells, three designs, and ten rounds give 360 trials. The frozen write rates at the three doses are 183/732, 155/619, and 72/286 writes/s, respectively, with each pair ordered $f = 0.2/0.8$; open-reader rates are 12,500, 8,000, 2,850 reads/s. The higher write fraction is below CoarseLock's earlier capacity at zero delay and above it at 200 and 2000 μs.

The delay probe separates nominal dose from realized lookup time. The earlier single-goroutine probe measured approximately 9, 35, and 215 μs and 2.25 ms per read; concurrent lock holds are reported separately. The sub-millisecond dose yields while spinning; the 2 ms dose sleeps before a final 0.5 ms spin.

C. Revisions, plans, runners, and seeds

The first campaign used revision `c53ee5b`, plan SHA-256 prefix `68ad96f878c1`, and runner prefix `22060ffc4885`. The intervention used `4c2749b`, plan `2e44fcacb3e7`, and runner `5dc57e7d85d7`. The compaction campaign used `c342832`, plan `5330cbddf01b`, and runner `3a05470d307b`. The table-count campaign used `adf754b`, plan `0bc0042b8b8a`, and runner `050c3210e9e8`. Protocols are `research/experiments/phase_i7/X_PREREGISTRATION.md`, `research/experiments/phase_i7/X_INTERVENTION_PREREGISTRATION.md`, `research/experiments/phase_i7/X_COMPACTION_PREREGISTRATION.md`, and `research/experiments/phase_i7/X_TABLECOUNT_PREREGISTRATION.md`.

The paced-load campaign used revision `6833d7c`; its design was frozen in `54572b2`, and the later commit changed only notes. Its plan SHA-256 prefix is `384aace771c8`, runner prefix `00f97d04191b`, and protocol `research/experiments/phase_i7/X_PACED_PREREGISTRATION.md`. The separate non-campaign append/fsync probe is recorded in `research/experiments/phase_i7/X_READCOST/fsync_probe.py` and `research/experiments/phase_i7/X_READCOST/fsync_probe.txt`; it was not rerun for this paper update.

The settled campaign's design was frozen at revision `54b2c67`, with plan SHA-256 prefix `7c868047870d`, runner prefix `35b8ea6bbc3a`, and protocol `research/experiments/phase_i7/X_SETTLED_PREREGISTRATION.md`. Exploratory evidence, excluded from every campaign analysis, is in `research/experiments/phase_i7/X_READCOST/stall_diag/` and `research/experiments/phase_i7/X_READCOST/fsync_checks/`, with the narrative in `research/experiments/phase_i7/X_READCOST/OVERNIGHT_NOTES.md`. The diagnostic tool's results carry no git revision; the fsync checks used a binary built at `f71e7e2` with SHA-256 prefix `d0e7bb68b0a8`.

TABLE VIII
FIRST-CAMPAIGN CELLS. THE LEGACY SCAN HAS NO ADDED DELAY.

Workload	Readers	Injected delay	Cells
Mixed	4, 16	0, 20, 200 μs, 2 ms, legacy scan	10
Publication	16	0, 200 μs, 2 ms, legacy scan	4
Churn	1, 4, 16	0	3

The follow-up campaign used revision `fc7998c`, plan SHA-256 prefix `394675b73698`, runner prefix `6d065832f639`, a 20 s pause, and protocol `research/experiments/phase_i7/X_FOLLOWUP_PREREGISTRATION.md`. Results are regenerated from retained raw trials by `research/experiments/analysis/x_followup_analyze.py`; `research/experiments/analysis/x_followup_paper_outputs.py` reads that JSON and the raw trials to generate the manuscript macros and figures.

Master seeds were 20261030, 20261103, 20261104, 20261105, 20261106, 20261107, and 20261108, respectively. Paired seeds are the first eight SHA-256 bytes of decimal master, cell or shared base identifier, and round separated by vertical bars, interpreted as a big-endian signed 64-bit value; compaction on/off shares the base identifier. Plans and ledgers retain execution order, retry and approval bindings, and the excluded smoke runs; the first start stopped after 38 successful trials is disclosed in the protocol.

APPENDIX B
FULL RESULTS

Full cells, uncertainty intervals, and auxiliary results retain their original data captions. Earlier figures keep their original confidence intervals; follow-up descriptive comparisons below use the stated paired intervals. Table macros copy frozen results or the follow-up generator's descriptive calculations.

Retirement ran in all on cells in the exploratory lifecycle measurements. Mean retirement lags spanned 0.74–1.26 ms for CoarseLock, 0.86–6.21 ms for Lease, and 0.96–3.81 ms for Snapshot. Cell mean retired-table high-water marks were 4.0–5.9 across the designs (Table XVI). At low doses, counts were roughly timer-limited, with cell means of 32–36 compactions per trial. At 2 ms they were flush-limited: CoarseLock completed mean counts of 9–10 versus 22.0–22.8 in the alternatives because it produced fewer flushes. These observations do not establish compaction starvation.




Fig. 9. Mixed workload writes, ten triplets per cell. Points are per-design geometric means; bars are exponentiated 95% log-t CIs. Most intervals are smaller than the markers. The legacy scan is an isolated category.




Fig. 10. Mixed workload reads, ten triplets per cell. Points are geometric means; bars are exponentiated 95% log-t CIs. CoarseLock's low-dose read gain was unpredicted.

The exploratory per-table critical-section increase was roughly 12 ns at four readers and 32 ns at sixteen, compared with about 3.8 ns per table in the single-goroutine microbenchmark. Cold cache lines on real table objects spread through the heap are a possible explanation, not a tested one. The microbenchmark uses synthetic table objects and isolates lifecycle operations; it is not an end-to-end read measurement.

The higher offered fraction was not a comfortable operating point for any design in the exploratory descriptive comparison. For Lease and Snapshot, cell medians of trial write response p99 ranged from 65–453 ms, while cell medians of trial p50 were 1.0–3.0 ms. Even trials above the 0.95 completion flag left up to 360 ticks unissued, so the flag understates censoring. The descriptive Lease/Snapshot completion-p99 ratios and wide 95% CIs are reported in Table XX; no prediction or equivalence conclusion applies to them. Their write service p50 ratios stayed at 0.999–1.004. Similar service medians do not establish similar response tails.

At 732 writes/s, the 1 MiB against 16 MiB read ratios were 0.915 [0.794, 1.054] and 0.968 [0.830, 1.129] for Lease and Snapshot (90% paired-t CIs), with one flush per trial against none and similar hold share. This comparison is descriptive. Cell mean reads divided by the product of each design's fsync-off median reads and cell mean free share were 0.811/0.807 at 183 writes/s and 1.050/1.047 at 732 (Lease/Snapshot). The paired log-ratio SDs at the four F1 rates were 0.023, 0.134,




Fig. 11. Publication workload, ten triplets per cell. Left: arithmetic mean in-window count with min–max bars. Right: geometric mean trial publication lock-wait p99 and exponentiated 95% log-t CIs. Wait counters include drain.

TABLE IX
WHAT THE TRIALS EXERCISED IN THE FIRST SIX CAMPAIGNS. FLUSH COUNTS INCLUDE DRAIN; COMPACTIONS COUNT COMPLETED WORK, NOT NO-OP TIMER CALLS. THE FOLLOW-UP CAMPAIGN IS NOT IN THIS TABLE; TABLE XXIII GIVES ITS FLUSHES (NONE IN F1 AND F3, ONE PER TRIAL IN F2).

Workload/campaign	Trials	Flushes/trial Mean	Flushes/trial Max	Total compactions
Mixed	309	0.55	1	0
Publication	120	20.00	20	0
Churn	90	60.19	77	0
Intervention	160	0.66	1	0
Compaction	360	36.22	87	5364
Table-count	480	0.50	1	0
Paced	360	0.17	1	0
Settled	470	7.83	61	1090




Fig. 12. Follow-up Mixed read-latency CDFs, all three designs, 10 rounds pooled by summing histogram bucket counts, with mass at each bucket's lower bound. The log latency axis is in μs; dotted verticals mark 200 and 500 μs. H-F4's regions use these lower bounds; within-bucket timings are unavailable.

0.208, and 0.341, and 0.015 with fsync off. H-X held: no F1 or F3 trial flushed.

The fixed-rate fsync comparison pairs F3 and F1 at 732 writes/s within each round and design. It takes $\ln(R_{\mathrm{F3}}/R_{\mathrm{F1}})$ and $\ln(\mathrm{free}_{\mathrm{F3}}/\mathrm{free}_{\mathrm{F1}})$ and their difference, then exponentiates the mean difference and its two-sided 90% paired-t CI. Per-round logs and differences are retained in comments in the generated `paper/generated/followup.tex`. This exploratory comparison does not change the frozen H-F1 test. The fsync-off read comparison is descriptive, with its 90% interval inside the margin; it is outside the H-F3 Holm family.

A post hoc, untested fit of $1/(R/\mathrm{free})$ on memtable share has 2 parameters on 4 F1 cell means per design, Pearson $r = -0.995$ for Lease and $r = -0.995$ for Snapshot, and fsync-off capacity ratios of 0.962 and 0.962 (mean R/free divided by the reciprocal line prediction at its own share); the share is approximate because the two counters do not cover exactly the same interval.

The arithmetic means of per-trial slow-group medians were 877, 856, and 854 μs for CoarseLock, Lease, and Snapshot, respectively, assigning each sample to its bucket's lower bound. These are conditional on the slow group and are descriptive; the cell has no commit-phase trace.

APPENDIX C
PROJECT HISTORY AND EXECUTION NOTES

A. *Earlier measurements*

A defective reader motivated the present study but supplies no pooled evidence for it. That reader scanned from the target block toward the data end, used about four unbuffered

TABLE X

MIXED WORKLOAD, TEN TRIPLETS PER CELL. RATES ARE GEOMETRIC MEANS (OPERATIONS/S); HOLD IS THE ARITHMETIC MEAN OF COARSELOCK'S TRIAL MEAN READ CRITICAL SECTIONS. PAIRED RATIOS HAVE 95% t CIS.

r	Delay	Hold μs	Writes/s CoarseLock	Writes/s Lease	Writes/s Snapshot	S [95% CI]	Reads/s CoarseLock	Reads/s Lease	Reads/s Snapshot	$R_{\mathrm{CL}}/R_{\mathrm{L}}$ [95% CI]
4	0	13.6	929	940	978	0.988 [0.896, 1.089]	7,468	6,258	6,482	1.193 [1.089, 1.308]
4	20 μs	33.6	878	948	961	0.926 [0.881, 0.974]	7,035	4,844	4,909	1.452 [1.380, 1.528]
4	200 μs	163	615	811	813	0.758 [0.725, 0.793]	4,932	4,154	4,161	1.187 [1.136, 1.241]
4	2 ms	1,885	130	359	352	0.361 [0.354, 0.368]	1,039	1,434	1,408	0.725 [0.710, 0.739]
4	legacy scan	124,853	2.6	613	617	0.004250 [0.004049, 0.004461]	21.2	43.3	43.3	0.489 [0.468, 0.511]
16	0	21.2	856	914	909	0.937 [0.884, 0.993]	27,538	25,101	24,972	1.097 [1.041, 1.156]
16	20 μs	39.3	830	880	899	0.944 [0.887, 1.004]	26,668	18,620	18,966	1.432 [1.350, 1.519]
16	200 μs	173	545	773	785	0.705 [0.676, 0.736]	17,507	16,017	16,256	1.093 [1.048, 1.140]
16	2 ms	1,915	111	358	352	0.311 [0.305, 0.316]	3,557	5,693	5,617	0.625 [0.614, 0.636]
16	legacy scan	430,130	0.6	354	355	0.001696 [0.001661, 0.001732]	21.2	40.6	40.7	0.522 [0.501, 0.544]

TABLE XI

INTERVENTION. q IS ARITHMETIC; THROUGHPUT RATIOS ARE PAIRED GEOMETRIC MEANS, WITH 95% PAIRED LOG-t CIS WHERE SHOWN. COLUMN NUMBERS 2 AND 1 DENOTE TWO-ACQUISITION AND ONE-ACQUISITION COMMITS.

r	Delay	q_{CL} 2	q_{CL} 1	q_{L} 2	q_{L} 1	$W_{\mathrm{CL},1}/W_{\mathrm{CL},2}$ [95% CI]	S 2	S 1	$R_{\mathrm{CL}}/R_{\mathrm{L}}$ [95% CI] 2	$R_{\mathrm{CL}}/R_{\mathrm{L}}$ [95% CI] 1
4	0	2.008	1.004	1.655	1.004	1.014 [0.943, 1.091]	0.965	0.963	1.170 [1.066, 1.285]	0.963 [0.897, 1.033]
4	20 μs	2.003	1.002	1.281	1.002	1.032 [0.928, 1.147]	0.946	0.974	1.479 [1.363, 1.604]	0.975 [0.882, 1.077]
4	200 μs	2.003	1.002	1.281	1.002	1.191 [1.131, 1.253]	0.731	0.864	1.144 [1.062, 1.232]	0.864 [0.758, 0.985]
4	2 ms	2.003	1.001	0.998	0.857	1.468 [1.429, 1.508]	0.356	0.539	0.715 [0.706, 0.726]	0.630 [0.592, 0.671]
16	0	2.010	1.003	1.722	1.003	1.091 [1.050, 1.134]	0.945	0.987	1.103 [1.064, 1.142]	0.987 [0.895, 1.089]
16	20 μs	2.008	1.003	1.320	1.003	1.123 [0.992, 1.271]	0.855	0.983	1.301 [1.174, 1.443]	0.983 [0.897, 1.077]
16	200 μs	2.006	1.001	1.290	1.001	1.274 [1.175, 1.382]	0.662	0.848	1.030 [0.993, 1.068]	0.848 [0.822, 0.875]
16	2 ms	2.003	1.001	0.997	0.858	1.528 [1.507, 1.548]	0.310	0.479	0.623 [0.603, 0.643]	0.559 [0.553, 0.566]

TABLE XII

PUBLICATION WORKLOAD. RATES AND TRIAL LOCK-WAIT P99 (μS) ARE GEOMETRIC MEANS. PUBLICATION COUNTS ARE MEDIAN [MIN, MAX], OUT OF TWENTY.

Delay	Reads/s CoarseLock	Reads/s Lease	Reads/s Snapshot	In-window publications CoarseLock	In-window publications Lease	In-window publications Snapshot	Lock-wait p99 (μs) CoarseLock	Lock-wait p99 (μs) Lease	Lock-wait p99 (μs) Snapshot
0	318,567	304,721	314,201	20 [20, 20]	20 [20, 20]	20 [20, 20]	247	41.60	13.37
200 μs	75,018	74,678	74,844	20 [20, 20]	20 [20, 20]	20 [20, 20]	450	19.33	12.10
2 ms	8,437	8,445	8,450	20 [20, 20]	20 [20, 20]	20 [20, 20]	3,886	1.51	2.83
legacy scan	27.6	42.7	42.7	10.5 [9, 11]	20 [20, 20]	20 [20, 20]	1,054,655	1.88	1.74

TABLE XIII

PUBLICATION LOCK-WAIT P99: PAIRED LEASE/SNAPSHOT RATIO, 90% t CI, AND PLANNED CLASSIFICATION.

Delay	Ratio [90% CI]	Classification
0	3.11 [1.54, 6.30]	not equivalent
200 μs	1.60 [0.51, 4.98]	inconclusive
2 ms	0.53 [0.22, 1.29]	inconclusive
legacy scan	1.08 [0.64, 1.82]	inconclusive

syscalls per record, and did not stop after passing the target key. A 960-trial WSL2 campaign comparing CoarseLock and Snapshot and a Windows campaign stopped by its stopping rule at 60 of 330 planned trials, with 18 complete triplets, used this path. They reported Snapshot completing 3.3–18.5 times CoarseLock's writes and churn throughput ratios of 0.63–0.74 at $r \leq 4$. We retain the defective path only as the legacy scan operating point. The earlier campaigns motivated the controlled delay, were not pooled with these data, and carry no inference into this paper. This study supersedes their claims, including the withdrawn $\pm 5\%$ equivalence claim and any earlier claim about Lease under churn.

B. Smoke trials and aborted starts

The earlier campaigns' smoke trials preceded their freezes and were excluded. The first campaign had 21 smoke trials before analysis rules were fixed; the intervention had eight after predictions were written; compaction had fifteen; table count had six; paced load had six after predictions were written. The settled campaign had six mechanical smoke trials before its freeze, from a dirty tree with an earlier runner build, with outcomes unread, and 36 non-campaign calibration trials whose outcomes were seen. After seeing that calibration and before any campaign trial, we raised the H-S threshold from 25 to 40 ms. The table-count single-round smoke ratio near 0.66 at 256 tables and sixteen readers pointed in the predicted direction, although predictions were written first. No design value, margin, or prediction changed because of these runs. An operator also stopped the first start at 38 of 519 trials for

TABLE XIV
CHURN, TEN TRIPLETS PER CELL. RATES ARE GEOMETRIC MEANS (OPERATIONS/S). LEASE/SNAPSHOT HAS 95% PAIRED-t AND PERCENTILE BOOTSTRAP CIS. FLUSHES ARE ARITHMETIC MEANS INCLUDING DRAIN, ORDERED COARSELOCK/LEASE/SNAPSHOT.

r	Outcome	CoarseLock	Lease	Snapshot	Ratio [95% t CI]	Bootstrap CI	Flushes
1	W	697	747	781	0.957 [0.905, 1.012]	[0.910, 0.997]	65.3/70.1/73.2
1	R	1,400	807	844	0.956 [0.904, 1.011]	[0.909, 0.997]	–
4	W	585	702	699	1.004 [0.963, 1.047]	[0.970, 1.038]	54.6/65.9/65.5
4	R	4,703	3,089	3,074	1.005 [0.964, 1.048]	[0.970, 1.038]	–
16	W	415	569	588	0.968 [0.933, 1.004]	[0.938, 0.995]	38.8/53.2/55.1
16	R	13,351	10,050	10,357	0.970 [0.937, 1.005]	[0.941, 0.997]	–

TABLE XV
COMPACTION-ON THROUGHPUT. LEASE/SNAPSHOT RATIOS HAVE 90% CIS AND HOLM-ADJUSTED CLASSIFICATIONS; S AND COARSELOCK/LEASE READ RATIOS HAVE 95% CIS. ALL RATIOS ARE PAIRED GEOMETRIC MEANS.

		Lease/Snapshot writes		Lease/Snapshot reads		S	$R_{\mathrm{CL}}/R_{\mathrm{L}}$
r	Delay	Ratio [90% CI]	Class	Ratio [90% CI]	Class	[95% CI]	[95% CI]
4	0	0.989 [0.944, 1.035]	equivalent	0.996 [0.954, 1.040]	equivalent	0.919 [0.881, 0.958]	1.494 [1.433, 1.557]
4	200 μs	0.997 [0.949, 1.047]	equivalent	0.997 [0.949, 1.047]	equivalent	0.681 [0.651, 0.712]	1.301 [1.244, 1.361]
4	2 ms	0.995 [0.975, 1.015]	equivalent	0.987 [0.968, 1.008]	equivalent	0.439 [0.430, 0.448]	0.912 [0.892, 0.933]
16	0	1.030 [0.980, 1.083]	equivalent	1.038 [0.989, 1.090]	equivalent	0.851 [0.800, 0.904]	1.408 [1.326, 1.496]
16	200 μs	0.949 [0.909, 0.991]	equivalent	0.973 [0.933, 1.015]	equivalent	0.656 [0.636, 0.676]	1.239 [1.204, 1.276]
16	2 ms	0.998 [0.980, 1.016]	equivalent	0.990 [0.972, 1.007]	equivalent	0.393 [0.386, 0.400]	0.820 [0.806, 0.835]

TABLE XVI
COMPACTION-ON LIFECYCLE MEASUREMENTS. ARITHMETIC MEANS OF TRIAL COMMIT-WAIT P99 AND TRIAL MEAN RETIREMENT LAG, INCLUDING DRAIN.

		Commit-wait p99 (μs)			Mean retirement lag (ms)		
r	Delay	CoarseLock	Lease	Snapshot	CoarseLock	Lease	Snapshot
4	0	305.8	49.5	29.2	0.85	0.86	0.96
4	200 μs	1038.3	21.5	11.7	0.78	1.52	1.29
4	2 ms	7795.5	70.6	12.8	0.76	5.11	2.86
16	0	627.9	147.5	75.4	1.26	1.02	0.97
16	200 μs	1660.5	245.6	176.7	0.85	1.73	1.47
16	2 ms	9220.9	132.4	16.8	0.74	6.21	3.81

power-supply reasons unrelated to results. It was discarded without analysis; only status lines were seen. Fixtures were constructed without fsync.

The follow-up had 7 mechanical smoke trials after its freeze, excluded from analysis, with only status, trace and histogram presence, cleanup, and ledger checked. An aborted start stopped at the operator's request after a leftover process had to be closed during the run: 13 trials finished and the 14th was killed in flight. The records were set aside unread and excluded; only status lines were seen. The campaign restarted from trial 1 with the same plan, seeds, and runner in a fresh folder. All 150 of 150 retained trials succeeded on the first attempt, with no retries or dropped traces and gaps of 20.0 to 22.5 s. The host was on AC power at the start and end, and the machine was left alone during the restarted run.

Four later protocols were frozen and not run for this paper: X-locks, X-inputopen, X-realism, and X-memtable. The repository holds no campaign folder or trial for X-locks, X-inputopen, or X-realism. X-memtable had four mechanical smoke trials, excluded from analysis, and an aborted start stopped at the operator's request after one finished trial; that trial was kept unread and excluded, and the campaign has not been run.

C. Power record and settled execution deviations

`platform.json` records the Balanced base plan. The overnight campaigns ran on AC power with other user applications closed by the operator; the Best performance overlay on the Balanced base plan was read back from the registry after both had finished, not during them. This does not independently verify the overlay throughout execution. Defender and other host activity remain possible sources of variation. The first five campaigns ran back to back, so each trial could inherit host effects from the one before. The settled sentinels bound this only in the rechecked cells, and they confound the pause with date, binary, and seeds. Bursts near 31 ms were not controlled in any campaign. During the settled campaign a helper process held a power request to prevent idle standby and spawned about 50 short `tasklist` processes; one read-only status check overlapped one trial, which is the largest of its group and is retained under the no-exclusion rule, though no prediction depends on its tail; the desktop application was also

TABLE XVII

TABLE-COUNT CAMPAIGN, TEN TRIPLETS PER CELL. THROUGHPUT RATIOS ARE LEASE/SNAPSHOT WITH 90% PAIRED LOG-t CIS AND PLANNED HOLM-ADJUSTED CLASSES. CS IS ARITHMETIC MEAN READ CRITICAL SECTION (μS). A DASH MEANS NO WRITER AND NO APPLICABLE WRITE TEST.

			Reads		Writes		Mean read CS (μs)		
N	r	Writers	Ratio [90% CI]	Class	Ratio [90% CI]	Class	CoarseLock	Lease	Snapshot
4	4	0	0.975 [0.958, 0.993]	equivalent	–	–	13.520	0.326	0.256
4	4	1	0.989 [0.963, 1.016]	equivalent	0.988 [0.960, 1.018]	equivalent	13.546	2.274	2.109
4	16	0	0.989 [0.981, 0.997]	equivalent	–	–	40.980	0.393	0.327
4	16	1	0.982 [0.960, 1.005]	equivalent	0.980 [0.953, 1.007]	equivalent	21.682	1.708	1.542
16	4	0	0.956 [0.944, 0.969]	equivalent	–	–	10.524	0.494	0.294
16	4	1	0.947 [0.920, 0.976]	equivalent	0.943 [0.912, 0.974]	equivalent	13.792	2.304	2.095
16	16	0	0.962 [0.924, 1.002]	equivalent	–	–	26.098	0.914	0.610
16	16	1	0.981 [0.940, 1.024]	equivalent	0.977 [0.927, 1.031]	equivalent	19.559	1.768	1.556
64	4	0	0.918 [0.906, 0.929]	equivalent	–	–	10.250	1.016	0.291
64	4	1	1.037 [0.997, 1.078]	equivalent	1.045 [1.001, 1.092]	equivalent	14.962	2.558	2.117
64	16	0	0.851 [0.837, 0.866]	not equivalent	–	–	28.984	2.689	0.802
64	16	1	0.978 [0.943, 1.013]	equivalent	0.979 [0.936, 1.023]	equivalent	20.045	2.175	1.609
256	4	0	0.712 [0.699, 0.726]	not equivalent	–	–	12.157	3.370	0.269
256	4	1	0.994 [0.954, 1.036]	equivalent	1.011 [0.967, 1.057]	equivalent	17.045	3.528	2.184
256	16	0	0.663 [0.660, 0.666]	not equivalent	–	–	33.703	8.512	0.877
256	16	1	0.972 [0.933, 1.012]	equivalent	0.985 [0.938, 1.035]	equivalent	22.349	3.900	1.602

TABLE XVIII

SEPARATE LIFECYCLE MICROBENCHMARKS: ARITHMETIC MEAN OF THREE COUNTS, NS/OPERATION. READ-CYCLE BENCHMARKS ALLOCATE NO MEMORY. PUBLICATION ALLOCATION COUNTS ARE PER OPERATION.

	Read cycle, 1 goroutine		Read cycle, 16 goroutines		Publication		Publication allocations	
N	Lease	Snapshot	Lease	Snapshot	Lease	Snapshot	Lease	Snapshot
4	26.7	21.0	58.1	88.6	109.1	653.7	0	3
16	69.6	20.8	137.5	88.0	104.4	717.5	0	3
64	248.1	20.9	481.8	88.1	110.2	1035.3	0	3
256	974.4	20.9	1766.7	87.6	127.7	3200.3	0	3

TABLE XIX

PACED WORKLOAD, TEN TRIPLETS PER CELL. ACHIEVED FRACTIONS AND WRITE RESPONSE P50 ARE ARITHMETIC MEANS OF TRIAL SUMMARIES. SATURATED COUNTS ARE COARSELOCK TRIALS BELOW 0.95 COMPLETED/OFFERED. THROUGHPUT IS THE PAIRED GEOMETRIC COARSELOCK/LEASE RATIO WITH ITS FROZEN 90% CI AND HOLM-ADJUSTED H-P2 OR H-P3 CLASS. ROUNDED 1.000 INTERVALS ARE NOT EXACT EQUALITY.

			Offered	Achieved write fraction			Saturated	CoarseLock/Lease writes		Response p50 (ms)	
Delay	f	Readers	writes/s	CoarseLock	Lease	Snapshot	CoarseLock	Ratio [90% CI]	Class	CoarseLock	Lease
0	0.2	closed	183	0.999	0.999	0.999	0	1.000 [1.000, 1.000]	equivalent	1.232	1.126
0	0.2	open	183	0.999	0.999	0.999	0	1.000 [1.000, 1.000]	equivalent	1.127	1.119
0	0.8	closed	732	0.995	0.989	0.995	0	1.007 [0.995, 1.019]	equivalent	1.322	7.023
0	0.8	open	732	0.989	0.991	0.997	0	0.998 [0.982, 1.015]	equivalent	29.135	22.340
200 μs	0.2	closed	155	0.998	0.999	0.999	0	0.999 [0.997, 1.001]	equivalent	1.888	1.272
200 μs	0.2	open	155	0.998	0.999	0.999	0	0.999 [0.996, 1.001]	equivalent	1.663	1.244
200 μs	0.8	closed	619	0.884	0.986	0.994	10	0.896 [0.866, 0.927]	inconclusive	631.452	1.160
200 μs	0.8	open	619	0.912	0.991	0.999	9	0.920 [0.898, 0.942]	inconclusive	457.808	2.169
2 ms	0.2	closed	72	0.999	0.999	0.999	0	1.000 [1.000, 1.000]	equivalent	8.084	3.015
2 ms	0.2	open	72	0.998	0.999	0.999	0	0.999 [0.998, 1.001]	equivalent	7.504	3.057
2 ms	0.8	closed	286	0.388	0.995	0.999	10	0.390 [0.387, 0.392]	not equivalent	3085.330	2.966
2 ms	0.8	open	286	0.404	0.996	1.000	10	0.405 [0.401, 0.409]	not equivalent	3056.809	3.085

running, and the operator was away, so it cannot be confirmed that the machine stayed untouched.

The settled pause and H-S threshold were selected after non-campaign calibration. Its 36 seen trials were excluded from campaign inference, and its six mechanical smoke trials used a dirty tree and an earlier runner build with outcomes unread. No campaign trial preceded the change from the draft 25 ms H-S threshold to 40 ms. The overlapping status check, helper activity, and desktop application described above remain execution deviations, with the affected trial retained under the no-exclusion rule.

D. Race-detector context

The race detector reported no data races in the engine and campaign harness tests under Linux on WSL2, rerun after commit-phase tracing was added; one older overload test fails under the detector for a timing reason because the slowdown disturbs the overload it expects. The older timing-sensitive failure is the E4 overload test. This was not a Windows race-detector run.

The trial runner `i7trial`, which `xcampaign` takes through its `-runner` flag, builds for linux/amd64 from the Windows checkout (`GOOS=linux GOARCH=amd64 go build` completed without error, as did the `xcampaign`

TABLE XX

PACED DESCRIPTIVE RATIOS, WITH FROZEN 95% PAIRED LOG-t CIS. ALL COLUMNS EXCEPT THE LAST COMPARE COARSELOCK/LEASE. THE READ COLUMN IS THROUGHPUT FOR CLOSED READERS AND RESPONSE P99 FOR OPEN READERS. THE LAST COLUMN COMPARES LEASE/SNAPSHOT WRITE RESPONSE COMPLETION-P99, WITH NO PREDICTION; UNISSUED TICKS HAVE NO OBSERVED LATENCY, AND CENSORED RATIOS DO NOT BOUND TRUE RATIOS. NO MEDIAN OR TAIL TREND TEST IS ADDED.


			CoarseLock/Lease writes		CoarseLock/Lease	Lease/Snapshot
Delay	f	Readers	Response p50	Service p50	Read metric	Response p99
0	0.2	closed	1.093 [1.062, 1.124]	1.088 [1.064, 1.113]	0.967 [0.912, 1.025]	0.957 [0.658, 1.393]
0	0.2	open	1.007 [0.995, 1.020]	1.008 [0.994, 1.022]	1.975 [0.892, 4.372]	0.748 [0.326, 1.720]
0	0.8	closed	0.847 [0.319, 2.251]	1.068 [1.057, 1.080]	0.776 [0.666, 0.904]	0.761 [0.544, 1.067]
0	0.8	open	0.879 [0.135, 5.749]	1.009 [1.003, 1.015]	1.086 [0.521, 2.261]	0.880 [0.596, 1.300]
200 μs	0.2	closed	1.484 [1.473, 1.496]	1.472 [1.461, 1.482]	0.921 [0.889, 0.954]	0.868 [0.166, 4.551]
200 μs	0.2	open	1.336 [1.324, 1.349]	1.342 [1.330, 1.354]	1.151 [0.272, 4.862]	0.588 [0.167, 2.064]
200 μs	0.8	closed	510.629 [395.760, 658.837]	1.562 [1.552, 1.572]	0.550 [0.491, 0.616]	2.173 [0.941, 5.018]
200 μs	0.8	open	279.497 [155.636, 501.930]	1.416 [1.406, 1.427]	0.734 [0.288, 1.874]	1.141 [0.449, 2.897]
2 ms	0.2	closed	2.681 [2.659, 2.703]	2.677 [2.657, 2.697]	0.720 [0.711, 0.730]	1.386 [0.839, 2.288]
2 ms	0.2	open	2.453 [2.388, 2.520]	2.447 [2.385, 2.510]	4.712 [3.516, 6.315]	0.702 [0.402, 1.225]
2 ms	0.8	closed	1040.347 [1028.850, 1051.972]	3.104 [3.101, 3.108]	0.642 [0.632, 0.653]	0.914 [0.361, 2.317]
2 ms	0.8	open	992.262 [945.816, 1040.989]	3.035 [3.022, 3.048]	1.278 [0.626, 2.609]	1.129 [0.306, 4.170]

TABLE XXI

FSYNCS OF 25 MS OR LONGER, BY WRITE RATE. SETTLED TRIALS ARE ALL THREE DESIGNS. BARE RUNS ARE EXPLORATORY, WITH NO ENGINE. "NO FIRST" EXCLUDES EACH RUN'S FIRST FSYNC. THE LAST ROW'S BARE RUNS WERE AT 700 WRITES/S.

	Settled		Bare		
Writes/s	Trials	Fsyncs (%)	Runs	No first	Fsyncs (%)
72	6/60	0.044	0/10	0/10	0.000
155	16/60	0.140	2/10	0/10	0.013
183	28/60	0.229	2/10	1/10	0.093
650–730	88/90	0.283	5/10	3/10	0.053

build). We ran no trial on Linux, and no Linux result appears here.



Filled: k=2; hollow: k=1. Grey: development only.

Fig. 13. Exploratory collapse check: write ratio against CoarseLock's mean read hold over Lease's commit cycle, with $S = 1/(1+kx)$ drawn for $k = 1$ and $k = 2$. Filled markers have $k = 2$, hollow $k = 1$; grey cells were seen before the criteria were written and do not count. Neither model met the criteria.

TABLE XXII

EXPLORATORY FSYNC ON/OFF CHECK AT ZERO DELAY, 732 WRITES/S, CLOSED READERS, TEN ROUNDS. RATIOS ARE PAIRED GEOMETRIC LEASE/SNAPSHOT MEANS WITH 90% CIS. CLASSES USE THE DECLARED MARGIN WITH NO MULTIPLICITY CORRECTION. ROUNDED 1.000 INTERVALS ARE NOT EXACT EQUALITY.

	Reads/s		Trials with fsync	Hold	Lease/Snapshot reads		Lease/Snapshot writes	
Fsync	Lease	Snapshot	≥ 25 ms	(%)	Ratio [90% CI]	Class	Ratio [90% CI]	Class
fsync on	108,009–173,846	104,776–156,826	17/20	72.3	1.052 [0.906, 1.222]	inconclusive	1.011 [0.989, 1.034]	equivalent
fsync off	437,665–454,848	427,814–460,161	0/20	4.3	0.994 [0.987, 1.000]	equivalent	1.000 [1.000, 1.000]	equivalent

TABLE XXIII

FOLLOW-UP PACED CELLS, 10 PAIRED ROUNDS EACH. READS AND ACHIEVED WRITES ARE ARITHMETIC MEAN OPERATIONS/S; HOLD SHARE AND MEASURED FLUSHES ARE ARITHMETIC MEANS INCLUDING DRAIN. THE LEASE/SNAPSHOT READ RATIO REPEATS ON EACH DESIGN'S ROW AND HAS A DESCRIPTIVE 90% PAIRED LOG-t CI.

Offered writes/s	Fsync, memtable	Design	Reads/s	Writes/s	Hold share	Flushes	Lease/Snapshot [90% CI]
183	on, 16 MiB	Lease	368195	183.0	0.200	0	0.992 [0.979, 1.006]
183	on, 16 MiB	Snapshot	370938	183.0	0.203	0	0.992 [0.979, 1.006]
366	on, 16 MiB	Lease	310745	364.7	0.395	0	0.992 [0.918, 1.073]
366	on, 16 MiB	Snapshot	312896	365.7	0.399	0	0.992 [0.918, 1.073]
549	on, 16 MiB	Lease	238343	548.6	0.571	0	0.983 [0.871, 1.108]
549	on, 16 MiB	Snapshot	242780	548.6	0.563	0	0.983 [0.871, 1.108]
732	on, 16 MiB	Lease	168004	728.9	0.718	0	1.023 [0.839, 1.246]
732	on, 16 MiB	Snapshot	164336	729.3	0.728	0	1.023 [0.839, 1.246]
732	on, 1 MiB	Lease	151864	725.9	0.729	1	0.966 [0.869, 1.074]
732	on, 1 MiB	Snapshot	156635	725.1	0.723	1	0.966 [0.869, 1.074]
732	off, 16 MiB	Lease	563435	732.0	0.034	0	0.989 [0.981, 0.998]
732	off, 16 MiB	Snapshot	569640	732.0	0.034	0	0.989 [0.981, 0.998]

TABLE XXIV

FOLLOW-UP F1 AND F3 CELLS: ARITHMETIC MEANS OF PER-TRIAL MEMTABLE SHARE AND READS/S PER UNIT FREE SHARE, FOR LEASE AND SNAPSHOT. MEMTABLE SHARE DIVIDES THE WHOLE-TRIAL MEMORY-READ COUNTER BY COMPLETED WINDOW-ISSUED READS, INCLUDING DRAIN.

	Memtable share		R/free (reads/s)	
Offered writes/s	Lease	Snapshot	Lease	Snapshot
183	0.084	0.084	459,886	465,540
366	0.161	0.163	513,455	520,514
549	0.239	0.228	555,161	554,198
732	0.289	0.294	593,562	602,391
732 (fsync off)	0.302	0.303	583,223	589,713

TABLE XXV

FOLLOW-UP F1 CELLS: HOLD PER COMMIT (MEAN HOLD SHARE DIVIDED BY MEAN ACHIEVED WRITES PER SECOND, MS) AND THE SHARE OF THE EXCLUSIVE HOLD SPENT IN WAL SYNC (MEAN OF PER-TRIAL SHARES, %), FOR LEASE AND SNAPSHOT. THE HOLD IS VALIDATION, WAL WRITE, WAL SYNC, AND APPLY.

	Hold per commit (ms)		WAL sync share (%)	
Offered writes/s	Lease	Snapshot	Lease	Snapshot
183	1.09	1.11	94.1	94.1
366	1.08	1.09	95.6	95.7
549	1.04	1.03	96.0	96.0
732	0.98	1.00	96.2	96.3

TABLE XXVI

FOLLOW-UP MIXED READ-LATENCY REGION SHARES, ARITHMETIC MEAN TRIAL PERCENTAGES [95% t CI], USING BUCKET LOWER BOUNDS. H-F4 APPLIES TO COARSELOCK ONLY AND HELD: ITS THRESHOLDS ARE AT LEAST 20% IN THE FAST AND BLOCKED REGIONS AND AT MOST 10% IN THE VALLEY.

Design	Fast	Valley	Blocked
CoarseLock	55.5 [55.2, 55.8]	0.11 [0.09, 0.13]	44.4 [44.1, 44.7]
Lease	44.5 [44.2, 44.9]	0.11 [0.09, 0.13]	55.4 [55.0, 55.7]
Snapshot	44.5 [44.3, 44.8]	0.09 [0.08, 0.11]	55.4 [55.1, 55.6]





Fig. 14. Stored read-latency percentiles, Mixed, $r = 4$, zero delay, ten trials per design, with a median line. Trials stored percentiles and no histograms, so this cannot establish modes; Fig. 12 shows the full histograms from the follow-up campaign.



Ten rounds pooled by summing bucket counts; mass at recorded bucket lower bounds.

Fig. 15. Commit-phase empirical CDFs from the settled campaign, closed readers, ten rounds pooled by summing bucket counts, with mass at each bucket's lower bound. Exploratory.




Fig. 16. Reads against the share of the window outside the writer's exclusive hold, zero delay, 732 writes/s, closed readers, log axes. Post hoc, exploratory. The line is fsync-off median capacity scaled by free share.