

Lecture 34

Priority Queues

FIT 1008
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Objectives

- To understand the Priority Queue ADT.
- Consider different implementations (advantages/disadvantages)
- To understand the Heaps, and the Heap-based implementation of Priority Queues.



The doctor will see you now...

Probably should have seen the doctor earlier



The doctor will see you now...

Priority Queue


lowest in a dual
implementation

- Each element has a numeric priority.
- Element with highest priority is processed first.

Operations:

add(element)

get_max()



The following data structures can be used to support the implementation of a Priority Queue ADT...

- Array-based List (sorted and unsorted)
- Linked List (sorted and unsorted)
- Binary Search Trees


- Heaps (Binary Tree-based)
- Heaps (Array-based)

Implementing Priority Queues

- Standard operations:
`is_empty`, `__len__`, `__init__`
- Core operations:
 - `get_max()` :
returns the max element (and removes it from the queue)
 - `add(element)` : adds element to the priority queue

Complexity

(Priority Queue using Unsorted Lists)



get_max()

- Find max item.
- Remove and reshuffle.

$O(n)$


add()

- Add item at the back.

$O(1)$

Complexity

(Priority Queue using Unsorted Linked Lists)



`get_max()`

- Find max item.
- Remove.

$O(n)$

`add()`

- Add item at the head.

$O(1)$

Adding to an array-based sorted list


```
def add(self, new_item):  
    # easy if the list is empty  
    if self.is_empty():  
        self.the_array[self.count] = new_item  
        self.count += 1  
        return True  
    # if the list is not empty...  
    has_place_left = not self.is_full()  
    if has_place_left:  
        # find correct position  
        index = 0  
        while index < self.count and new_item > self.the_array[index]:  
            index += 1  
        # now index has the correct position  
        # we go backwards from count - 1 up to index  
        for i in range(self.count - 1, index - 1, -1):  
            # "moving" the item in position i to position i+1  
            self.the_array[i+1] = self.the_array[i]  
        # insert new item  
        self.the_array[index] = new_item  
        # increment counter  
        self.count += 1  
    return has_place_left
```

—————→ Find correct position

—————→ Move things to
make space

Complexity

(Priority Queue using Sorted Lists)



get_max()

- Find max item.
- Remove.

Position
count-1

$O(1)$

add()

- Add item.

$O(n)$

Complexity

(Priority Queue using Sorted Linked Lists)



get_max()

- Find max item.
- Remove.

at head

$O(1)$

add()

- Find correct position.

$O(n)$

Priority Queues using linear structures...

Implementation	<code>get_max()</code>	<code>add</code>
Unsorted array	$O(n)$	$O(1)$
Unsorted linked list	$O(n)$	$O(1)$
Sorted array	$O(1)$	$O(n)$
Sorted linked list	$O(1)$	$O(n)$

Consider
comparisons
complexity

Linear structure gives linear complexity



Let's try a non-linear structure!




```
class BinarySearchTreeNode:
    def __init__(self, key, item=None, left=None, right=None):
        self.key = key
        self.item = item
        self.left = left
        self.right = right
```

add() trivial.


```
class BinarySearchTree:
    def __init__(self):
        self.root = None

    def is_empty(self):
        return self.root is None
```

get_max() ?

BST:


`get_max()` ?




Right-most node: Go right until you can

Complexity depends on the height!

`get_max()`



get_max()




BST Deleting: Node with one child:
Point parent to child of deleted node

Simple version (without deleting)

```
def get_max(self):  
    if self.root is None:  
        raise ValueError("Empty Priority Queue")  
    else:  
        return self.get_max_aux(self.root)  
  
def get_max_aux(self, current):  
    if current.right is None: # base case: at max  
        return current.item  
    else:  
        return self.get_max_aux(current.right)
```

With delete?

[Remember the parent]



Node with no child:
Point parent to None


Node with one child:
Point parent to child of deleted node


```
def get_max(self):  
    if self.root is None:  
        raise ValueError("Priority Queue is empty")  
    elif self.root.right is None: # root has the max
```

We can only call the aux method if we have a parent!

```
def get_max_aux(self, current, parent):  
    if current.right is None: # base case: at max  
        parent.right = current.left  
        return current.item  
    else:  
        return self.get_max_aux(current.right, current)
```

```
def get_max(self):  
    if self.root is None:  
        raise ValueError("Priority Queue is empty")  
    elif self.root.right is None: # root has the max  
        temp = self.root.item  
        self.root = self.root.left # delete root  
        return temp  
    else:  
        return self.get_max_aux(self.root.right, self.root)
```



```
def get_max_aux(self, current, parent):  
    if current.right is None: # base case: at max  
        parent.right = current.left  
        return current.item  
    else:  
        return self.get_max_aux(current.right, current)
```

Alternative implementation

```
def get_max(self):  
    if self.root is None:  
        raise ValueError("Priority Queue is empty")  
    elif self.root.right is None: # root has the max  
        temp = self.root.item  
        self.root = self.root.left # delete root  
        return temp  
    else:  
        return self.get_max_aux(self.root)
```

```
def get_max_aux(self, parent):  
    if parent.right.right is None: # base case: at max  
        temp = parent.right.item  
        parent.right = parent.right.left  
        return temp  
    else:  
        return self.get_max_aux(parent.right)
```

only passing the parent, but “looking down” two levels

A better implementation

- Each of the previous choices has one $O(N)$ operation.
- $O(\text{Depth})$ for the binary tree with depth being $N-1$ if unbalanced.
- Can we do better? Use a (max) heap.
 - One could also use a min-heap
 - In FIT1008 we use max-heaps but the ideas are the same for a min-heap.




big bricks boss it up

Soil and silt sink through

Max Heaps!

Heap (Min-Heap)

How does it feel to know your children
Will be more successful in every way?




For **every** node:

- The values of the children are **greater or equal** to its value.
- **All the levels are filled**, except possibly the last one, which is filled left to right.

Note: The minimum is always at the root of the tree.

Everything was
Better back in
My day!

Heap (Max-Heap)




For **every** node:

- The values of the children are **smaller or equal** to its value.
- **All the levels are filled**, except possibly the last one, which is filled left to right.


Note: The **maximum** is always at the root of the tree.

Building a *binary* heap




Force the tree to be balanced...

Example




“Not a binary search tree”

Add 18




Add 18




all good now!

issue: swaps need a reference to parent

`get_max()`



“Sink” until the element is larger than or equal to children



Complexity?

Implementation?



<http://www.brainlazy.com/wp-content/uploads/Disgaea-3-Absence-of-Detention-14.jpg>

I don't know what this is... but we'll cover complexity and implementation next time

Summary

- Priority Queues:
 - **add**
 - **get_max**
- Possible implementations: Lists, BST.
- Heaps: binary trees that are
 - Complete
 - Heap ordered
- Heap operations for Priority Queues: Complexity and correctness