

Lecture 32

Binary Trees

FIT 1008
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA
Copyright Regulations 1969
WARNING


This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.


Do not remove this notice.

Objectives

- Revise Trees:
 - Concepts
 - Operations & Implementation
 - Complexity Ideas
 - Traversal

Trees






Trees

- Extremely useful.
- Natural way of modelling many things:
 - Family trees
 - Organisation structure charts
 - Structure of chapters and sections in a book
 - Execution/call tree (recall the one for fibonacci)
 - Object Oriented Class Hierarchies
- Particularly good for some operations (like search)
- Compact representation of data

Compact representation of data



Branches represent different strings.

Trees


- Graphs which are:

- Simple


no loops or multiple edges

- Connected


- No circuits.



Perfect Binary Trees




$N = 1$ Height = 0



$N = 3$ Height = 1




Each parent has two children

All leaves at same level



$N = 7$ Height = 2


Perfect Binary Trees



height	leaves	nodes
0	1	1
1	2	3
2	4	7
3	8	15
k	2^k	$2^{k+1}-1$

$$N = 2^{k+1} - 1$$

$$\text{Height} = k$$



Perfect Binary Trees

$$N = 2^{k+1} - 1$$

$$N+1 = 2^{k+1}$$

$$\log_2(N+1) = k+1$$


$$\log_2(N+1) - 1 = k$$

In a perfect binary tree with N nodes,
the height is $O(\log N)$


Balanced tree
the height is $O(\log N)$

Unbalanced tree
the height is $O(N)$


Representing a Binary Tree Node



Our implementation: Each link points to a **Node**



class TreeNode:



```
class TreeNode:
```

```
    def __init__(self, item=None, left=None, right=None):  
        self.item = item  
        self.left = left  
        self.right = right
```

```
    def __str__(self):  
        return str(self.item)
```

```
class TreeNode:
```

```
    def __init__(self, item=None, left=None, right=None):  
        self.item = item  
        self.left = left  
        self.right = right
```



```
    def __str__(self):  
        return str(self.item)
```

```
class BinaryTree:
```

```
    def __init__(self):  
        self.root = None
```


```
    def is_empty(self):  
        return self.root is None
```

Only instance variable is a reference to the
root




Add an item.

Add 3




where?


Add 3




bitstring = "10", item = 3

Examples


bitstring = "", item= 


bitstring = "01", item= 


bitstring = " ", item= 




Examples

bitstring = "", item= 

bitstring = "01", item= 

bitstring = " ", item= 



Recursively explore subtree
following “bitstring directions”




```
def add(self, item, position_bitstring):
    bitstring_iterator = iter(position_bitstring)
    self.root = self._add_aux(self.root, item, bitstring_iterator)

def _add_aux(self, current, item, bitstring_iterator):
    if current is None:
        current = TreeNode()
    try:
        bit = next(bitstring_iterator)
        if bit == "0":
            current.left = self._add_aux(current.left, item, bitstring_iterator)
        elif bit == "1":
            current.right = self._add_aux(current.right, item, bitstring_iterator)
    except StopIteration:
        current.item = item
    return current
```




Traversal

- Systematic way of visiting/processing all the nodes
- Methods: Preorder, Inorder, and Postorder
- They all traverse the left subtree before the right subtree. It's all about the position of the root.




Preorder



Inorder



Postorder



Print Preorder Traversal


- 1) Print the root node
- 2) Traverse the left subtree
- 3) Traverse the right subtree

```
def print_preorder(self):
```

Print Preorder Traversal


```
def print_preorder(self):  
    self._print_preorder_aux(self.root)  
  
def _print_preorder_aux(self, current):  
    if current is not None: # if not a base case  
        print(current)  
        self._print_preorder_aux(current.left)  
        self._print_preorder_aux(current.right)
```

Example: Preorder



43	31	20	28	40	33	64	56	47	59	89
----	----	----	----	----	----	----	----	----	----	----

Example: Inorder



20	28	31	33	40	43	47	56	59	64	89
----	----	----	----	----	----	----	----	----	----	----

Print In-order Traversal

- 1) Traverse the left subtree
- 2) Print the root node
- 3) Traverse the right subtree


```
def print_inorder(self):  
    self._print_inorder_aux(self.root)  
  
def _print_inorder_aux(self, current):  
    if current is not None: # if not a base case  
        self._print_inorder_aux(current.left)  
        print(current)  
        self._print_inorder_aux(current.right)
```

Print Post-order Traversal


- 1) Traverse the left subtree
- 2) Traverse the right subtree
- 3) Print the root node

```
def print_postorder(self):  
    self._print_postorder_aux(self.root)  
  
def _print_postorder_aux(self, current):  
    if current is not None: # if not a base case  
        self._print_postorder_aux(current.left)  
        self._print_postorder_aux(current.right)  
        print(current)
```

Example: Postorder



Example: Postorder



28	20	33	40	31	47	59	56	89	64	43
----	----	----	----	----	----	----	----	----	----	----


```

class ListIterator:
    def __init__(self, head):
        self.current = head


    def __iter__(self):
        return self

    def __next__(self):
        if self.current is None:
            raise StopIteration
        else:
            item_required = self.current.item
            self.current = self.current.next
            return item_required


```




?



State of the Iterator on creation



`self.stack`



StopIteration

—

a b d c

preorder!

```
self.current = self.stack.pop()  
self.stack.push(self.current.right)  
self.stack.push(self.current.left)  
return current
```

```
class PreOrderIteratorStack:
```

```
    def __init__(self, root):  
        self.current = root  
        self.stack = Stack()  
        self.stack.push(root)
```

```
    def __iter__(self):  
        return self
```

```
    def __next__(self):  
        if self.stack.is_empty():  
            raise StopIteration  
        current = self.stack.pop()  
        if current.right is not None:  
            self.stack.push(current.right)  
        if current.left is not None:  
            self.stack.push(current.left)  
        return current.item
```

```
my_tree.print_preorder()
```

```
2  
5  
3
```

```
for i in my_tree:  
    print(i)
```

```
2  
5  
3
```

In BinaryTree:


```
def __iter__(self):  
    return PreOrderIteratorStack(self.root)
```

What about without a stack?

hint: find out about python generators...
and yield

Computing the size of a tree

Returns the number of nodes in the tree (without modifying the tree)




```
size(self) = size(left) + 1 + size(right)
```

Computing the size of a tree

```
def __len__(self):  
    return self.len_aux(self.root)  
  
def len_aux(self, current):  
    if current is None:  
        return 0  
    else:  
        return 1 + self.len_aux(current.left) + self.len_aux(current.right)
```

Collecting the leaves of a tree

Returns the a list of the leaves (left to right)



[f, h, g, i, j]

traverse, when finding a leaf (no children) add to list...

[pass the list as an accumulator]

Collecting the leaves of a tree

```
def get_leaves(self):  
    a_list = []  
    self.get_leaves_aux(self.root, a_list)  
    return a_list
```

```
def get_leaves_aux(self, current, a_list):  
    if current is not None:  
        if self.is_leaf(current):  
            a_list.append(current.item)  
        else:  
            self.get_leaves_aux(current.left, a_list)  
            self.get_leaves_aux(current.right, a_list)
```

```
def is_leaf(self, current):  
    return current.left is None and current.right is None
```

```
>>> from lecture_31 import BinaryTree
>>> my_tree = BinaryTree()
>>> my_tree.add(1, '')
>>> my_tree.add(2, '1')
>>> my_tree.add(3, '0')
>>>
>>> my_tree.get_leaves()
[3, 2]
>>> my_tree.add(4, '01')
>>> my_tree.get_leaves()
[4, 2]
>>>
```

Summary

- Tree traversal: inorder, postorder, preorder
- Expression trees: prefix, infix, postfix