

Lecture 33

Binary Search Trees

FIT 1008
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA
Copyright Regulations 1969
WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.


Objectives

- To understand Binary Search Trees
- Implement Binary Search Trees:
 - search
 - insert
- Advantages and disadvantages of Binary Search Trees over sorted lists.


Binary Search Tree

A Binary Tree such that:

- Every node entry has a key
- All keys in the left subtree of a node are less than the key of the node
- All keys in the right subtree of a node are greater than the key of the node




key is an integer.



key is a string

(here not showing the associated items)



key is an key.

```
class BinarySearchTreeNode:
    def __init__(self, key, item=None, left=None, right=None):
        self.key = key
        self.item = item
        self.left = left
        self.right = right
```

```
class BinarySearchTree:
    def __init__(self):
        self.root = None

    def is_empty(self):
        return self.root is None
```

Search

Search algorithm

- If we reach an empty node, item is not there...
return **False**.
- Else, if target key is equal to the current node's key,
return **True**
- Else, if target key is less than current node's key,
search the left sub-tree
- Else, if target key is greater than current node's
key, search the right sub-tree

search can be implemented by
`__contains__`

__contains__

```
def __contains__(self, key):  
    return self._contains_aux(self.root, key)  
  
def contains_aux(self, current, key):
```

__contains__

```
def __contains__(self, key):  
    return self._contains_aux(self.root, key)  
  
def _contains_aux(self, current, key):  
    if current is None: # base case: empty  
        raise KeyError("Key not found")  
    elif key == current.key: # base case: found  
        return True  
    elif key < current.key:  
        return self._contains_aux(current.left, key)  
    else: # key > current.key  
        return self._contains_aux(current.right, key)
```

we want to get the item associated to a key...

`__getitem__`

Search for key and retrieve item associated with that key

__getitem__


```
def __getitem__(self, key):  
    return self._getitem_aux(self.root, key)  
  
def _getitem_aux(self, current, key):
```

__getitem__


```
def __getitem__(self, key):  
    return self._getitem_aux(self.root, key)  
  
def _getitem_aux(self, current, key):  
    if current is None: # base case: empty  
        raise KeyError("Key not found")  
    elif key == current.key: # base case: found  
        return current.item  
    elif key < current.key:  
        return self._getitem_aux(current.left, key)  
    else: # key > current.key  
        return self._getitem_aux(current.right, key)
```

Insert


Insert 2




Insert 2




Insert 2




Insert 7




Insert 7



Insert 7



Insert 7



Our BST does not allow for duplicates, so we need to do something if we find the key in the tree...

Insert algorithm


Input: key and associated item to insert.

Idea: Find the right spot (search) then create new node.

- Try to find the key...
 - Found? Raise an exception (insert expects no duplicates)
 - Not found? parent of **None** should be the parent of new node, which needs to be created.


```
def insert(self, key, item):  
    self.root = self._insert_aux(self.root, key, item)
```


```
def _insert_aux(self, current, key, item):  
    if current is None: # base case: at the leaf  
        current = BinarySearchTreeNode(key, item)  
    elif key < current.key:  
        self._insert_aux(current.left, key, item)  
    elif key > current.key:  
        self._insert_aux(current.right, key, item)  
    else: # key == current.key  
        raise ValueError("Duplicate Item")
```



`a_tree.insert(57, "Coco")`

```
def insert(self, key, item):  
    self.root = self._insert_aux(self.root, key, item)
```

```
def _insert_aux(self, current, key, item):  
    if current is None: # base case: at the leaf  
        current = BinarySearchTreeNode(key, item)  
    elif key < current.key:  
        self._insert_aux(current.left, key, item)  
    elif key > current.key:  
        self._insert_aux(current.right, key, item)  
    else: # key == current.key  
        raise ValueError("Duplicate Item")
```




key → 57

item → "Coco"

a_tree.insert(57, "Coco")

```
def insert(self, key, item):  
    self.root = self._insert_aux(self.root, key, item)
```

```
def _insert_aux(self, current, key, item):  
    if current is None: # base case: at the leaf  
        current = BinarySearchTreeNode(key, item)  
    elif key < current.key:  
        self._insert_aux(current.left, key, item)  
    elif key > current.key:  
        self._insert_aux(current.right, key, item)  
    else: # key == current.key  
        raise ValueError("Duplicate Item")
```




key → 57

item → "Coco"

a_tree.insert(57, "Coco")

```
def insert(self, key, item):
    self.root = self._insert_aux(self.root, key, item)
```


```
def _insert_aux(self, current, key, item):
    if current is None: # base case: at the leaf
        current = BinarySearchTreeNode(key, item)
    elif key < current.key:
        self._insert_aux(current.left, key, item)
    elif key > current.key:
        self._insert_aux(current.right, key, item)
    else: # key == current.key
        raise ValueError("Duplicate Item")
```



```
a_tree.insert(57, "Coco")
```

```
def insert(self, key, item):
    self.root = self._insert_aux(self.root, key, item)
```

```
def _insert_aux(self, current, key, item):
    if current is None: # base case: at the leaf
        current = BinarySearchTreeNode(key, item)
    elif key < current.key:
        self._insert_aux(current.left, key, item)
    elif key > current.key:
        self._insert_aux(current.right, key, item)
    else: # key == current.key
        raise ValueError("Duplicate Item")
```



current needs to be returned!

```
def insert(self, key, item):  
    self.root = self._insert_aux(self.root, key, item)
```

```
def _insert_aux(self, current, key, item):
```

```
def insert(self, key, item):  
    self.root = self._insert_aux(self.root, key, item)
```

```
def _insert_aux(self, current, key, item):  
    if current is None: # base case: at the leaf  
        current = BinarySearchTreeNode(key, item)  
    elif key < current.key:  
        current.left = self._insert_aux(current.left, key, item)  
    elif key > current.key:  
        current.right = self._insert_aux(current.right, key, item)  
    else: # key == current.key  
        raise ValueError("Duplicate Item")  
    return current
```

```
def insert(self, key, item):  
    self.root = self._insert_aux(self.root, key, item)
```


```
def _insert_aux(self, current, key, item):  
    if current is None: # base case: at the leaf  
        current = BinarySearchTreeNode(key, item)  
    elif key < current.key:  
        current.left = self._insert_aux(current.left, key, item)  
    elif key > current.key:  
        current.right = self._insert_aux(current.right, key, item)  
    else: # key == current.key  
        raise ValueError("Duplicate Item")  
    return current
```


__setitem__

```
def __setitem__(self, key, item):  
    self.root = self._setitem_aux_(self.root, key, item)  
  
def _setitem_aux_(self, current, key, item):  
    if current is None: # base case: at the leaf  
        current = BinarySearchTreeNode(key, item)  
    elif key < current.key:  
        current.left = self._setitem_aux_(current.left, key, item)  
    elif key > current.key:  
        current.right = self._setitem_aux_(current.right, key, item)  
    else: # key == current.key  
        current.item = item  
    return current
```


Delete

Delete 47




only showing key

Delete 47



only showing key


Delete 47



None


only showing key

Delete 47




Node with no child:
Find parent - point to None

Delete 20




only showing key

Delete 20




only showing key

Delete 20



only showing key


Delete 20



Node with one child:


Find parent - point to child of deleted node

Delete 31




only showing key

Delete 31





only showing key


Delete 31



Delete 31




Delete 31




Successor of a node: node with next larger key.



Delete 31



Delete 31




Delete 31




Node with two children:

Find parent and successor - successor is the new parent of the (orphan) children


Delete 43




Delete 43




Delete 43




Delete 43



Delete 43



Delete 43



Delete

Input: key of element to delete.

Idea: Find key and successor...

- Try to find the key...
 - If it is a leaf? Set parent's reference to None
 - It has one child? Parent's reference set to child ("bypass").
 - It has two children? Find **successor**. Successor takes position of deleted node. **If successor leaves an orphan child, it should be linked to the successor's parent.**

__delitem__

left as an exercise.

Summary

- Binary search trees: search, insertion and deletion