

Lecture 35

Heaps

FIT 1008

Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING


This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Objectives

- Revise basics of Heaps and Heap-based Priority Queue
- To understand a simple implementation of Heaps
- To be able to reason about the complexity of its operations
- Heap Sort

Heap (Max-Heap)




For **every** node:

- The values of the children are smaller or equal to its value.
- **All the levels are filled**, except possibly the last one, which is filled left to right.

Note: The **maximum** is always at the root of the tree.

Building a *binary* heap



Force the tree to be balanced...


add:

- put at the bottom
- while order is broken, rise.


get_max:

- swap root with last item
- remove last item
- while order is broken, sink.

Heap




Lets insert the numbers [5, -7, 10, -3, 13, 20, 25,1] into an empty heap




Lets insert the numbers [5, -7, 10, -3, 13, 20, 25,1] into an Binary Search Tree

Heap **vs** Binary Search Tree



Very different!



Implementation of Heaps?


Implementation

Alternative 1: Binary tree of linked nodes

- Downside: complex -- requires extra references to move up the tree (rise a node)
- Extra memory.

Alternative 2: With an array

- Possible due to completeness of the binary tree.
- Advantages: Very compact



1	2	3	4	5	6	7	8	9	10
0	1	2	3	4	5	6	7	8	9

Parent Position	Child Left	Child Right
0	1	2
1	3	4
2	5	6
3	7	8
4	9	
k	?	?


shift

1	2	3	4	5	6	7	8	9	10
---	---	---	---	---	---	---	---	---	----

0 1 2 3 4 5 6 7 8 9

	1	2	3	4	5	6	7	8	9	10
--	---	---	---	---	---	---	---	---	---	----

0 1 2 3 4 5 6 7 8 9 10




Parent Position	Child Left	Child Right

	1	2	3	4	5	6	7	8	9	10
0	1	2	3	4	5	6	7	8	9	10


Root at
position
1

Children of k:
 2^*k
 2^*k+1
(if they exist)

Parent of k:
position $k//2$
(except for root)



Parent Position	Child Left	Child Right
1	2	3
2	4	5
3	6	7
4	8	9
5	10	
k	2^*k	2^*k+1




A concrete implementation

Start with a None so that we have items from position 1 onwards

```
class Heap:
```

```
    def __init__(self):  
        self.count = 0  
        self.array = [None]
```



```
    def __len__(self):  
        return self.count
```

Operations

add:

- put at the bottom
- while order is broken, rise.

get_max:

- swap root with last item
- remove last item
- while order is broken, sink.


```
def add(self, item):  
    if self.count + 1 < len(self.array):  
        self.array[self.count+1] = item  
    else:  
        self.array.append(item)  
    self.count += 1  
    self.rise(self.count)
```

rise the last element -
swap with parent while order is broken

```
def swap(self, i, j):  
    self.array[i], self.array[j] = self.array[j], self.array[i]
```


Rise item at index k to its correct position

Precondition: $1 \leq k \leq \text{self.count}$

```
def rise(self, k):  
    while k > 1 and self.array[k] > self.array[k//2]:  
        self.swap(k, k//2)  
        k //= 2
```

```
def add(self, item):  
    if self.count + 1 < len(self.array):  
        self.array[self.count+1] = item  
    else:  
        self.array.append(item)  
    self.count += 1  
    self.rise(self.count)
```

Add 18




`self.array`

	20	15	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10

```
def rise(self, k):  
    while k > 1 and self.array[k] > self.array[k//2]:  
        self.swap(k, k//2)  
        k //= 2
```

```
def add(self, item):  
    if self.count + 1 < len(self.array):  
        self.array[self.count+1] = item  
    else:  
        self.array.append(item)  
    self.count += 1  
    self.rise(self.count)
```

Add 18



`item = 18` `self.count = 11`

`self.array`

	20	18	12	14	15	5	7	3	8	10	15
0	1	2	3	4	5	6	7	8	9	10	11

```
def rise(self, k):  
    while k > 1 and self.array[k] > self.array[k//2]:  
        self.swap(k, k//2)  
        k //= 2
```

```
def add(self, item):  
    if self.count + 1 < len(self.array):  
        self.array[self.count+1] = item  
    else:  
        self.array.append(item)  
    self.count += 1  
    self.rise(self.count)
```

best case: $O(1)$

worst case: $O(\log N)$

(may need to consider comparison operations)

Complexity of add

- Loop in `rise` can iterate at most depth times $\approx \log(N)$ (after depth iterations, the new item is at the root)
- **Best case:** $O(1) * O(\text{Compare})$ when the item is smaller or equal than its parent.
- **Worst case:** $O(\log N) * O(\text{Compare})$ when the item rises all the way to the top.

Why $\log(N)$? Heaps are always balanced
so there's only one path to explore

Operations

add:

- put at the bottom
- while order is broken, rise.

get_max:

- swap root with last item
- remove last item
- while order is broken, sink.

Summary

- A simple Heap implementation
 - rise
 - sink
 - largest_child
- Heap Sort