

Lecture 28

Iteration vs Recursion

FIT 1008
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA
Copyright Regulations 1969
WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.


Do not remove this notice.

Operation	Class Method
str(obj)	__str__(self)
len(obj)	__len__(self)
item in obj	__contains__(self,item)
y = obj[ndx]	__getitem__(self,ndx)
obj[ndx] = value	__setitem__(self,ndx,value)
obj == rhs	__eq__(self,rhs)
obj < rhs	__lt__(self,rhs)
...	
obj + rhs	__add__(self,rhs)
...	

```
class List:
    def __init__(self):
        self.head = None
        self.count = 0
```

```
def __len__(self):
    return self.count
```

?



↑ head




count from head to access elements

```
class List:
    def __init__(self):
        self.head = None

    def __len__(self):
        current = self.head
        count = 0
        while current is not None:
            current = current.next
            count += 1
        return count
```

What about recursively?



Convergence: Call recursion with $L-1$. Use variable *current*.

Base case: Empty? Size of empty list is 0.

Combining solutions: Add up result of recursive call +

```
def __len__(self):  
    if self.head is None:  
        return 0  
    else:  
        return 1 + self.__len__(self.head.next)
```



```
def __len__(self):  
    if self.head is None:  
        return 0  
    else:  
        return 1 + self.__len__(self.head.next)
```

TypeError: __len__() takes 1 positional argument but 2 were given


```
def _length(self, current):  
    if self.current is None: # base case  
        return 0  
    else:  
        return 1 + self._length(current.next)
```

Base case

Convergence


Combination

```
def __len__(self):  
    return self._length(self.head)
```

Auxiliary method sets up the initial
parameters

Recursion vs Iteration

- Can every **iterative function** be implemented using **recursion**?
Yes, it is **straightforward**.
- Can every **recursive function** be implemented using **iteration**?



you might also need to **store** past results.


Lovingly stolen from:

https://66.media.tumblr.com/3f1bb6a13c96f90cb332b385a6363b2e/tumblr_nkaavk9owg1qz6f4bo2_1280.jpg

Operation	Class Method
str(obj)	__str__(self)
len(obj)	__len__(self)
item in obj	__contains__(self,item)
y = obj[ndx]	__getitem__(self,ndx)
obj[ndx] = value	__setitem__(self,ndx,value)
obj == rhs	__eq__(self,rhs)
obj < rhs	__lt__(self,rhs)
...	
obj + rhs	__add__(self,rhs)
...	

___contains___

current



head

__contains__

```
def __contains__(self, item):  
    current = self.head  
    while current is not None:  
        if current.item == item:  
            return True  
        current = current.next  
    return False
```

Complexity: Worst case - $O(n)$ where n is the size of the list.


__contains__

```
def __contains__(self, item):  
    current = self.head  
    while current is not None:  
        if current.item == item:  
            return True  
        current = current.next  
    return False
```

- **Best case** complexity when found first: $O(1) \cdot \text{CompEq}$ where CompEq is the complexity of $==$ (or __eq__)
- **Worst case** when not found: $O(n) \cdot \text{CompEq}$ where n is the length of the list.

What about recursively?

__contains__(6) in L



$6 == \text{head.item}$ **or** __contains__(6) in L-1

Convergence: Call recursion with L-1. Use variable *current*.

Base case: Empty or Element Found. We need both.

Combining solutions: it's in the head **or** in the remaining list.

Auxiliary method sets up the initial parameters

```
def __contains__(self, item):  
    return self._contains_aux(self.head, item)
```

```
def _contains_aux(self, current, item):  
    if current is None:  
        return False  
    return current.head == item or self._contains_aux(current.next, item)
```


Base case

Convergence

Combination


Alternative coding

```
def __contains__(self, item):  
    return self._contains_aux(self.head, item)
```


```
def _contains_aux(self, current, item):  
    if current is None:  
        return False  
    elif current.head == item:   
        return True  
    else:  
        return self._contains_aux(current.next, item)
```

If complexity is the same, why bother with recursive implementations?

Copy Linked Lists




```
b_list = a_list.copy()
```



```
def copy(self):  
    new_list = List()  
    for item in self:  
        new_list.insert(len(new_list), item)  
    return new_list
```

What about recursively?

`_copy(self.head, new_list)`



`_copy(self.head.next, new_list)`

`new_list.insert(0, head.item)`

copy

Auxiliary method sets up the initial parameters

```
def copy(self):  
    new_list = List()  
    self._copy_aux(self.head, new_list)  
    return new_list
```

Convergence

```
def _copy_aux(self, node, new_list):  
    if node is not None:  
        self._copy_aux(node.next, new_list)  
        new_list.insert(0, node.item)
```

Base case

Combination



```

def copy(self):
    new_list = List()
    self._copy_aux(self.head, new_list)
    return new_list

def _copy_aux(self, node, new_list):
    if node is not None:
        self._copy_aux(node.next, new_list)
        new_list.insert(0, node.item)

```

$O(n)$




_copy_aux $O(1)$




_copy_aux $O(1)$



_copy_aux $O(1)$



_copy_aux $O(1)$



n times

Using iterators...

```
def copy(a_list):  
    new_list = List()  
    copy_aux(iter(a_list), new_list)  
    return new_list
```

```
def copy_aux(iter, new_list):  
    try:  
        item = next(iter)  
        copy_aux(iter, new_list)  
        new_list.insert(0, item)  
    except StopIteration:  
        pass
```

copy

```
def copy(self):  
    new_list = List()  
    for item in self:  
        new_list.insert(len(new_list), item)  
    return new_list
```


$O(n^2)$

```
def copy(self):  
    new_list = List()  
    self._copy_aux(self.head, new_list)  
    return new_list  
  
def _copy_aux(self, node, new_list):  
    if node is not None:  
        self._copy_aux(node.next, new_list)  
        new_list.insert(0, node.item)
```

$O(n)$

Or....

Have a tail attribute and you can have
 $O(1)$ append and hence $O(n)$ copy



Advantages/Disadvantages of Recursion

- Advantages:
 - More natural
 - Easier to prove correct
 - Easier to analyse
- Disadvantages:
 - Run-time overhead depending on the quality of the compiler
 - Memory overhead (fewer local variables versus stack space for function call)



what's easy to prove
Just keep doing 'you', and being who
~~you are~~ and doing what feels natural
to you.
balancing your time and memory use
— Taylor Swift —

AZ QUOTES

Summary

- Recursive algorithms are characterised by:
 1. Existence of base cases
 2. Decomposition into simpler subproblems
 3. Combination of solutions to subproblems
- Recursive methods require:
 1. One or more base cases
 2. One or more recursive calls
 3. Convergence in the recursive calls
 4. Combination of sub-solutions