

Lecture 23

Linked Structures

FIT 1008
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA
Copyright Regulations 1969
WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.
Do not remove this notice.

Container ADTs

- **Stores** and removes items **independent of contents**.
- **Examples** include:
 - List ADT ☒
 - Stack ADT ☒
 - Queue ADT. ☒
- **Core operations:**
 - add item
 - remove item



Implementation affects time complexity.

Unsorted List: Add

Adding an element


Recall: count indicates the first empty position (if any)

Example: add "Ada"

Add the item at position *count*

Increment *count*


count: 2



```
def add(self, new_item):  
    has_space_left = not self.is_full()  
    if has_space_left:  
        self.the_array[self.count] = new_item  
        self.count += 1  
    return has_space_left
```

Sorted List: Add

Example: add "Alan"
to the sorted list.



If there is space, find the correct position

Make room by moving all to the right.

Put item in position.

Update count

then **return True**

Recall how we add into a sortedList?

```
def add(self, new_item):  
    # easy if the list is empty  
    if self.is_empty():  
        self.the_array[self.count] = new_item  
        self.count += 1  
        return True  
    # if the lis is not empty...  
    has_place_left = not self.is_full()  
    if has_place_left:  
        # find correct position  
        index = 0  
        while index < self.count and new_item > self.the_array[index]:  
            index+=1  
        # now index has the correct position  
        # we go backwards from count -1 up to index  
        for i in range(self.count-1, index-1, -1):  
            # "moving" the item in position i to position i+1  
            self.the_array[i+1] = self.the_array[i]  
        # insert new item  
        self.the_array[index] = new_item  
        # increment counter  
        self.count+=1  
    return has_place_left
```

```

def add(self, new_item):
    # easy if the list is empty
    if self.is_empty():
        self.the_array[self.count] = new_item
        self.count += 1
        return True
    # if the list is not empty...
    has_place_left = not self.is_full()
    if has_place_left:
        # find correct position
        index = 0
        while index < self.count and new_item > self.the_array[index]:
            index += 1
        # now index has the correct position
        # we go backwards from count - 1 up to index
        for i in range(self.count - 1, index - 1, -1):
            # "moving" the item in position i to position i+1
            self.the_array[i+1] = self.the_array[i]
        # insert new item
        self.the_array[index] = new_item
        # increment counter
        self.count += 1
    return has_place_left

```

Adding to a Sorted List is **$O(N)$** in the worst-case

Can we improve this by changing the representation?

Welcome to the world of

ed structures




Legend of zelda

<https://upload.wikimedia.org/wikipedia/en/3/39/Wakerlink.jpg>

Array Linked List: Add

Example: add "Alan"
to the sorted list.


count: 5



the_array					
Ada	Charles	Grace	Konrad	Alan	???
4	2	3	-1	1	???
0	1	2	3	4	5

No shifting around!

If there is space, add it
then fix indexes...increment count



Why not use a **memory address** instead?

Location of the **next** item

count: 5


the_array

Ada	Charles	Grace	Konrad	Alan	???
0x3110	0x3100	0x3108	None	0x30F8	???
0x30F0	0x30F8	0x3100	0x3108	0x3110	0x3118

count: 5


the_array

Ada	Charles	Grace	Konrad	Alan
0x3110	0x3100	0x3108	None	0x30F8




count: 5

A node




Node



```
class Node:
    def __init__(self, item, link):
        self.item = item
        self.next = link
```

Node




default values, if not supplied

```
class Node:
    def __init__(self, item = None, link= None):
        self.item = item
        self.next = link
```


An orange dashed line connects the text "default values" to the default values "None" in the code.


```
n1 = Node()
n2 = Node("Coco")
n3 = Node("Coco", n1)
n4 = Node(n2)
```




```
class Node:
    def __init__(self, item = None, link= None):
        self.item = item
        self.next = link
```


```
>>> n1 = Node("Konrad")
>>> n2 = Node("Grace", n1)
>>> n3 = Node("Charles", n2)
>>> n4 = Node("Ada", n3)
>>> n5 = Node("Alan")
>>> n5.next = n3
>>> n4.next = n5
```







Node



```
class Node:
    def __init__(self, item = None, link= None):
        self.item = item
        self.next = link
```

Nodes

- Basic building blocks for simple **linked structures**.
- Allow easy addition of items
- Allow easy deletion of items
- Allow dynamic structures

Print Node

```
def __str__(self):  
    return str(self.item)
```

Print Linked Structure

a is b, True if variables a and b point to the same object

```
def print_structure(node):  
    while node is not None:  
        print(node, end=" ")  
        node = node.next  
    print()
```

by default end of **print** is a new line, we just want a space here

a == b, true if the objects referred to by variables a and b are equal.

```
print(*objects, sep=' ', end='\n', file=sys.stdout, flush=False)
```

Print *objects* to the text stream *file*, separated by *sep* and followed by *end*. *sep*, *end* and *file*, if present, must be given as keyword arguments.

All non-keyword arguments are converted to strings like `str()` does and written to the stream, separated by *sep* and followed by *end*. Both *sep* and *end* must be strings; they can also be `None`, which means to use the default values. If no *objects* are given, `print()` will just write *end*.

The *file* argument must be an object with a `write(string)` method; if it is not present or `None`, `sys.stdout` will be used. Since printed arguments are converted to text strings, `print()` cannot be used with binary mode file objects. For these, use `file.write(...)` instead.

Whether output is buffered is usually determined by *file*, but if the *flush* keyword argument is true, the stream is forcibly flushed.

<https://docs.python.org/3/library/functions.html#print>

```
class Node:
    def __init__(self, item = None, link= None):
        self.item = item
        self.next = link

    def __str__(self):
        return str(self.item)

def print_structure(node):
    while node is not None:
        print(node, end=" ")
        node = node.next
    print()

if __name__ == "__main__":
    n1 = Node("Konrad")
    n2 = Node("Grace", n1)
    n3 = Node("Charles", n2)
    print_structure(n3)
```

Summary

- Linked Structures
- Nodes