



FIT2093 INTRODUCTION TO CYBER SECURITY

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the *Copyright Act 1968* (the Act).

The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.



FIT2093 INTRODUCTION TO CYBER SECURITY

Digital Signature & Integrity Management

Unit Structure

- Introduction to security of
- Authentication
- Access Control Fundamental
- Fundamental concepts of cryptography
- Symmetric encryption techniques
- Introduction to number theory
- Public key cryptography
- **Integrity management**
- Practical aspects of cyber security
- Hacking and countermeasures
- Database security
- IT risk management & Ethics and privacy



Previous Lecture

- **Why public key cryptography ?**
- **General principles of public key cryptography**
- **Diffie-Hellman public key exchange**
 - g, p known to Alice & Bob and select private keys a, b
 - Exchange public keys $A = g^a \bmod p$; $B = g^b \bmod p$;
 - Calculate shared secret key, $K = B^a \bmod p = A^b \bmod p$
- **RSA public key cryptosystem**
 - Primes $p, q \Rightarrow n=pq$; e =public key; d = private key;
 - $ed \bmod \Phi(n)=1$; $C=m^e \bmod n$; $m = C^d \bmod n$;
- **RSA Security**

Outline

- **Why do we need digital signatures?**
- **Another look at the Public Key Cryptography**
- **How are the required properties satisfied by digital signatures?**
- **How to generate a digital signature?**
- **Integrity Management**
 - Verification of modification

The Need for a Digital Signature


- **Social & business activities and their associated documents are becoming digital**
 - digital conferences
 - digital contract signing
 - digital cash payments,
- **Hand-written signatures are not applicable to digital data**

Digital Signatures


- **Signatures are used for non-repudiation**
 - Authenticate/verify the source/issuer
- **Non-repudiation is the property where an entity cannot deceive another by falsely denying responsibility for an act**
- **Can also be used for integrity of data, if the signature contains non-forgeable information about the data.**
 - Detect forgery or tampering




RSA Public Key Cryptosystem



Digital Signature (based on Public Key Cryptography)



Digital Signature (based on RSA)



Digital Signature --- an example(1)

- **Bob:**

- chooses 2 primes: $p=5, q=11$
multiplies p and q : $n = p * q = 55$;
$$\phi(n) = (p-1) * (q-1) = 4 * 10 = 40$$
- finds out two numbers $e=3$ & $d=27$ which satisfy
$$e * d \bmod \phi(n) = 1;$$

$$(3 * 27) \bmod 40 = 1 ;$$
- Bob's public key
 - > 2 numbers: $(3, 55)$
 - > encryption alg: modular exponentiation
- secret key: $(27, 55)$

Digital Signature --- an example(2)

- **Bob has a document $m=19$ to sign:**
 - uses his secret key $d=27$ to calculate the digital signature of $m=19$:
$$\begin{aligned}s &= m^d \pmod n \\&= 19^{27} \pmod{55} = (19^3)^9 \pmod{55} = (31 \times 19)^9 \pmod{55} \\&= (39^3)^3 \pmod{55} = (36 \times 39)^3 \pmod{55} = 29^3 \pmod{55} \\&= (16 \times 29) \pmod{55} \\&= 24\end{aligned}$$
 - appends 24 to 19. Now $(m, s) = (19, 24)$ indicates that the doc is 19, and Bob's signature on the doc is 24.



Digital Signature --- an example(3)

- **Cathy, a verifier:**


- receives a pair $(m,s)=(19, 24)$
- looks up the phone book and finds out Bob's public key $(e, n)=(3, 55)$
- calculates
$$\begin{aligned} t &= s^e \pmod n \\ &= 24^3 \pmod{55} = 26 \times 24 \pmod{55} \\ &= 19 \end{aligned}$$
- checks whether $t=m$
- confirms that $(19,24)$ is a genuinely signed document of Bob if $t=m$.



Signing Long Documents!

- In the previous example, a document has to be an integer in $[0, \dots, (n-1)]$
- To sign a very long document, we need a so called **one-way hash algorithm**
- Instead of signing directly on a doc, we hash the doc first, and sign the hashed data which is normally short.

Digital Signature (for long doc)



One-Way Hash Algorithm

- **A one-way hash algorithm hashes an input document into a condensed short output (say of 100 bits)**
 - Denoting a one-way hash algorithm by $H(.)$, we have:
 - > Input: m - a binary string of any length
 - > Output: $H(m)$ - a binary string of L bits, called the “hash of m under H ”.
 - > The output length parameter L is fixed for a given one-way hash function H ,
 - > eg
 - The one-way hash function “MD5” has $L = 128$ bits
 - The one-way hash function “SHA-1” has $L = 160$ bits



One-Way Hash Algorithm

Message (of any length)



H

Hash of the message

A condensed short output, say of 100 bits



Properties of One-Way Hash Algorithm

- A good one-way hash algorithm H needs to have these properties:

1. **For any size of data**

Can be applied to a block of data of any size

2. **Output size:**

produces a fixed-length output



Properties of One-Way Hash Algorithm

3. Easy to Evaluate

The hashing algorithm should be fast

i.e. given any document m , the hashed value $h = H(m)$ can be computed quickly.

4. Hard to Reverse


There is no feasible algorithm to “reverse” a hashed value,

i.e. given any hashed value h , it is computationally infeasible to find any document m such that $H(m) = h$.

- **NOTE: An algorithm is called ‘One-Way’ if it has BOTH properties 3 and 4.**



The One-way Property




Properties of One-Way Hash Algorithm

5. Hard to find Collisions


- > There is no feasible algorithm to find two or more input documents which are hashed into the same condensed output,
- > i.e., it is computationally infeasible to find any two documents m_1 , m_2 such that $H(m_1) = H(m_2)$.



Finding Collision is Infeasible



Digital Signature (for long doc)



Why Digital Signature ?

- **Unforgeable**
 - takes long, long time to forge !
- **Un-deniable by the signatory**
 - Because secret key of the signatory was used
- **Universally verifiable**
 - Signature is verified using the public key of the signatory which should be available to everyone!
- **Differs from doc to doc**
- **Easily implementable by**
 - Software, hardware or software + hardware




Unforgeable Digital Signature

I, Bob,
will pay
\$1,000
to Alice.

101001010

a valid signature



I, Bob,
will pay
\$10,000
to Alice.

001001101

also a valid signature



Digital Signature Properties

- **A digital signature is analogous to the handwritten signature**
 - Provides a set of security capabilities that would be difficult to implement in any other way.
- **Properties**
 - It must verify the author and the date and time of the signature
 - It must authenticate the contents at the time of the signature
 - It must be verifiable by third parties, to resolve disputes
- **the digital signature function includes the authentication function.**

Digital Signature Requirements

- **Must depend on the message signed**
- **Must use information unique to the originator (sender)**
 - to prevent both forgery and denial
- **Must be relatively easy to produce**
- **Must be relatively easy to recognize & verify**
- **Be computationally infeasible to forge**
 - with new message for existing digital signature
 - with fraudulent digital signature for given message
- **Be practical to save digital signature in storage**



Digital Signature -- Summary

- **Three (3) steps are involved in digital signature**
 - Setting up public and secret keys
 - Signing a document
 - Verifying a signature



Setting up Public & Secret Keys

- **Bob does the following**
 - prepares a pair of public and secret keys
 - publishes his public key in the public key file (such as an on-line phone book)
 - keeps the secret key to himself
- **Note:**
 - Setting up needs only to be done once !



Signing a Document

- **Once setting up is completed, Bob can sign a document (such as a contract, a cheque, a certificate, ...) using the secret key**
- **The pair of document & signature is a proof that Bob has signed the document.**



Verifying a Signature

- **Any party, say Cathy, can verify the pair of document and signature, by using Bob's public key from the public key file.**
- **Important !**
 - Cathy does NOT need to have her own public or secret key !





Integrity → Verification of
modification

Message (file contents) Authentication

- **Message authentication is generally concerned with:**
 - protecting the integrity of a message
 - validating identity of originator
 - > non-repudiation of the origin (dispute resolution)
- **Possible methods that can be used to produce an authenticator**
 - message encryption
 - message authentication code (MAC)
 - hash function

Security Requirements

- **In the context of communications across a network, the attacks can be:**

- Disclosure
- traffic analysis
- masquerade
- content modification
- sequence modification
- timing modification
- source repudiation
- destination repudiation

Message confidentiality

The diagram shows a list of eight attacks on the left. A bracket groups the first two attacks (Disclosure and traffic analysis) and points to a speech bubble labeled 'Message confidentiality'. Another bracket groups the remaining six attacks (masquerade, content modification, sequence modification, timing modification, source repudiation, and destination repudiation) and points to a speech bubble labeled 'Message authentication'.

Message authentication




Message Authentication using Encryption (1)

- **message encryption by itself also provides a measure of authentication**
- **if symmetric encryption is used then:**
 - receiver knows sender must have created it
 - since only sender and receiver know key used
 - know content cannot be altered
 - if message has suitable structure, redundancy or a checksum to detect any changes



Symmetric Message Encryption



Message Authentication using Encryption (2)

- **if public-key encryption is used:**
 - encryption provides no confidence of sender
 - since anyone potentially knows public-key
 - however if
 - > senders **sign** the message using their private-key
 - > then encrypt with recipients public key
 - > have both secrecy and authentication
 - again need to recognize corrupted messages
 - but at the cost of two public-key uses on the message

Public-Key Message Encryption



(d) Public-key encryption: confidentiality, authentication, and signature




Message Authentication Code (MAC)

- **Generated by an algorithm that creates a small fixed-sized block → like check sum in data transmission**
 - depending on both **message** and some **key**
 - like encryption though need not be reversible
- **Appended to message as a **signature****
- **Receiver performs same computation on message and checks if it matches with the MAC**
- **Provides assurance that message is unaltered and comes from sender**



Message Authentication using a Message Authentication Code (MAC)



Message Authentication Codes

- **MAC is an approach to message authentication**
- **Can also use encryption for secrecy**
 - generally use separate keys for each
 - can compute MAC either before or after encryption
 - is generally regarded as better done before
- **Why use a MAC?**
 - sometimes only authentication is needed
 - sometimes need authentication to persist longer than the encryption (eg. archival use)
- **note that a MAC does not satisfy non-repudiation**



MAC Properties

- **MAC can be viewed as a cryptographic checksum**
 - $\text{MAC} = C_K(M)$
 - condenses a variable-length message M
 - using a secret key K
 - to a fixed-sized authenticator
- **is a many-to-one function**
 - potentially many messages can generate the same MAC
 - but finding those messages should be difficult

Requirements for MACs

- **Need the MAC to satisfy the following:**
 1. knowing a message and MAC, is infeasible to find another message with same MAC
 - deals with **message replacement attacks**
 2. MACs should be uniformly distributed across the messages
 - deals with the need to **thwart a brute-force attack based on chosen plaintext**
 3. MAC should depend equally on all bits of the message
 - dictates that the **authentication algorithm should not be weaker with respect to certain parts or bits of the message than others.**




Message Authentication Using Symmetric Ciphers for MACs

- Can use any block cipher chaining mode and use the final block as a MAC
- **Data Authentication Algorithm (DAA)** is a widely used MAC based on DES-CBC
 - using IV=0 and zero-pad of final block
 - encrypt message using DES in CBC mode
 - and send just the final block as the MAC
 - > or the leftmost M bits ($16 \leq M \leq 64$) of final block
- **But final MAC now may be too small for security**



Data Authentication Algorithm



Review :

- **Digital Signatures**

- Unforgeable, non-repudiation, universally verifiable, message dependent, easily implementable
- Short documents
- Long documents
 - > Properties of Hash functions
 - Any size input, fixed size o/p, one-way, strong collision resistance

- **Message Authentication**

- Integrity, validate identity of originator
- Encryption, MAC, Hash function
- Requirements and properties of MAC
 - > Data Authentication algorithm with DES-CBC, IV=0




Hash Function

- **Like MAC, hash function is a one way function that accepts a message M and produces a fixed-size message digest $H(M)$**
- **Unlike MAC, hash function takes only the message (not the key) as input to generate the message digest**
- **Hash is used to detect changes to message**
- **Can be used with both symmetric and asymmetric encryption**
 - used in various ways with message
 - Most often to create a digital signature




Message Authentication using Hash Function (1)



Message Authentication using Hash Function (2)

- Secret value K is known to A & B
- A calculates hash function of secret value + Message, i.e., $MD = H(K \parallel M \parallel K)$
- $M \parallel MD$ is sent
- B recalculates $H(K \parallel M \parallel K)$ and verifies



Simple Hash Functions

- a one-way or secure hash function used in message authentication, digital signatures
- all hash functions process an input block at a time in an iterative fashion
- one of simplest n -bit hash functions is the bit-by-bit exclusive-OR (XOR) of each block

$$C_i = b_{i1} \oplus b_{i2} \oplus \dots \oplus b_{im}$$

- C_i is i th bit of the hash code
- m is the number of n -bit blocks in the input
- b_{ij} is i th bit in the j th block
- effective data integrity check on random data
- less effective on more predictable data
- virtually useless for data security



Hash Functions: Attacks

- **two attack approaches**
 - cryptanalysis
 - > exploit logical weakness in alg
 - brute-force attack
 - > trial many inputs
 - > strength proportional to size of hash code ($2^{n/2}$)
- **Secure Hash Algorithm (SHA) most widely used hash algorithm**
 - SHA-1 gives 160-bit hash
 - more recent SHA-256, SHA-384, SHA-512 provide improved size and security

Keyed Hash Functions as MACs

- **want a MAC based on a hash function**
 - because hash functions are generally faster
 - crypto hash function code is widely available
- **hash includes a key along with message**
- **original proposal:**
 - $\text{KeyedHash} = \text{Hash}(\text{Key}||\text{Message})$
 - some weaknesses were found with this
- **eventually led to development of HMAC**

HMAC Design Objectives


- **use, without modifications, hash functions**
- **allow for easy replaceability of embedded hash function**
- **preserve original performance of hash function without significant degradation**
- **use and handle keys in a simple way.**
- **have well understood cryptographic analysis of authentication mechanism strength**

HMAC

- **specified as Internet standard RFC2104**
- **uses hash function on the message:**
 - $\text{HMAC}(K, M) = \text{Hash}[(K + \text{XOR opad}) \parallel \text{Hash}[(K + \text{XOR ipad}) \parallel M]]$
 - where $K +$ is the key padded out to size
 - opad, ipad are specified padding constants
- **overhead is just hash calculations on 3 more blocks than hashing the message alone**
- **any hash function can be used**
 - eg. MD5, SHA-1, RIPEMD-160, Whirlpool

- **HMAC**

Overview



HMAC Security

- **proved security of HMAC relates to that of the underlying hash algorithm**
- **attacking HMAC requires either:**
 - brute force attack on key used (2^n)
 - birthday attack (but since keyed would need to observe a very large number of messages)
 - > Collision resistant attacks, an adversary wishes to find 2 messages that yield the same hash ($2^{n/2}$)
- **choose hash function used based on speed verses security constraints**

Summary

- **Non-repudiation**
- **Digital Signatures**
 - > Properties
 - > Short document
 - > Long document
- **Message Authentication**
 - Message encryption
 - Message Authentication code
 - > Properties & DAA
 - Hash Algorithms
 - > Properties
 - > Simple Hash Function & HMAC



Further Reading

- **Chapters 2 & 21 of the textbook: *Computer Security: Principles and Practice*” by William Stallings & Lawrie Brown, Prentice Hall, 2015**
- **Acknowledgement: part of the materials presented in the slides was developed with the help of Instructor’s Manual and other resources made available by the author of the textbook.**