

# Lecture 7

## Functions in MIPS

### (preliminaries)

FIT 1008  
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

# What we know...

- MIPS **architecture** and **instruction set** (the subset we will use)
- Storing and accessing variables
- Understand what happens at compilation.
- Compiling **basic arithmetic, selection, loops and array access** into assembler
- Everything **EXCEPT** for how to compile **function call/return**

# Objectives

- To understand how **functions** are **implemented** in MIPS.
- In particular:
  - Use of the **jal** and **jr** instructions
  - Use of the **system stack** to satisfy function properties
- To understand the reasons behind the decisions taken by the **function calling convention**
- To understand what a **stack frame** is, and its purpose

# Accessing local variables


I can use **\$sp** since variables are located relative to top of stack

```
def a():  
    x = 5  
    y = 10  
    ...
```

**\$sp** **0x7FFFB3110** →

Store  $x = 5$  at  
address **\$sp + 0**  
(0x7FFFB3110)

Store  $y = 10$  at  
address **\$sp + 4**  
(0x7FFFB3114)



lower addresses

0x7FFF310C

0x7FFF3110

0x7FFF3114

0x7FFF3118

0x7FFF311C

higher addresses

# Reminder: addressing modes

**const** may be a label,  
signed number or  
expression at run time

**\$reg** is any GPR

**sw \$src, **const**(\$reg)**

**\$reg + const**  
Add const to the  
value of \$reg

# Examples of addressing modes

sw \$t0, 4(\$sp)

address is ( $\$sp + 4$ )

---

sw \$t0, -4(\$fp)

address is ( $\$fp - 4$ )

---

lw \$a0, 0(\$sp)

lw \$a0, (\$sp)



address is ( $\$sp + 0$ )

---

lw \$a0, var(\$zero)

lw \$a0, var



address is  
( $\$zero + \text{address of var}$ )

# ?

- Can access local variables relative to stack pointer (**\$sp**).
- However, this may be problematic when passing arguments to functions:
  - Stack pointer moves to accommodate other function info
  - Relative locations of local variables change

# Frame pointer

- Can access local variables relative to stack pointer (**\$sp**).
- However, this may be problematic when passing arguments to functions:
  - Stack pointer moves to accommodate other function info
  - Relative locations of local variables change
- Better to access local variables relative to **saved copy of stack pointer**: Copy made before subtracting from **\$sp** to allocate local variables
- Saved copy stored in register **\$fp** (**frame pointer**): Local variables accessed relative to **\$fp**.



# Example

```
def a():  
    x = 5  
    y = 10  
    ...
```

**\$sp** **0x7FFFB3118** → x

x

5

y

10

**\$fp** **0x7FFFB3118**

access **y** at address  $(\$fp - 4) = 0x7FFF3114$

access **x** at address  $(\$fp - 8) = 0x7FFF3110$

lower addresses

0x7FFF310C

0x7FFF3110

0x7FFF3114

0x7FFF3118

0x7FFF311C

higher addresses

- Local variables are referred to without names in MIPS.
- Therefore, remembering their address is vital:  
**diagrams help**

```
// A global variable  
g = 123
```

```
def main():
```

```
// Three local variables  
a = -5  
b = 0  
c = 230
```

```
// Do some arithmetic  
b = g + a
```

```
// Do some more arithmetic  
print(c - a)
```

```
.data  
# g is global, allocate  
# in data segment
```

```
g: .word 123
```

```
.text
```

```
main: # Copy $sp into $fp.  
      addi $fp, $sp, 0
```

```
# Allocate 12 bytes of  
# memory for local variables.  
addi $sp, $sp, -12
```

```
# Initialize local  
# variables.
```

```
addi $t0, $0, -5      # a  
sw $t0, -12($fp)
```

```
sw $0, -8($fp)        # b
```

```
addi $t0, $0, 230     # c  
sw $t0, -4($fp)
```

```
# ... rest of program  
# follows next slide ...
```

**Faithful translation:** regs for **g** and **a**  
are not re-used, they are reloaded

```
// A global variable
g = 123
```

```
def main():
```

```
    // Three local variables
```

```
    a = -5
```

```
    b = 0
```

```
    c = 230
```

```
    // Do some arithmetic
```

```
    b = g + a
```

```
    // Do some more arithmetic
```

```
    print(c - a)
```

... here is the rest  
# of the MIPS code ...

```
# b = g + a.
```

```
lw $t0, g
```

```
# g
```

```
lw $t1, -12($fp)
```

```
# a
```

```
add $t0, $t0, $t1
```

```
# g+a
```

```
sw $t0, -8($fp)
```

```
# store in b
```

```
# print(c-a)
```

```
addi $v0, $0, 1
```

```
# Print int
```

```
lw $t0, -4($fp)
```

```
# c
```

```
lw $t1, -12($fp)
```

```
# a
```

```
sub $a0, $t0, $t1
```

```
# c-a
```

```
syscall
```

```
# Do print.
```

```
# Now exit.
```

```
addi $v0, $0, 10
```

```
# Exit.
```

```
syscall
```

```

.data
# g is global, allocate
# in data segment
g:      .word 123

.text
main:   # Copy $sp into $fp.
        addi $fp, $sp, 0

        # Allocate 12 bytes of
        # memory for local variable
        addi $sp, $sp, -12

        # Initialize local
        # variables.

        addi $t0, $0, -5      # a
        sw $t0, -12($fp)

        sw $0, -8($fp)       # b

        addi $t0, $0, 230    # c
        sw $t0, -4($fp)

        # ... rest of program
        # follows next slide ...

```

... here is the rest  
# of the MIPS code ...

```

# b = g + a.
lw $t0, g          # g
lw $t1, -12($fp)   # a
add $t0, $t0, $t1  # g+a
sw $t0, -8($fp)    # store in b

# print(c-a)
addi $v0, $0, 1    # Print int
lw $t0, -4($fp)    # c
lw $t1, -12($fp)   # a
sub $a0, $t0, $t1  # c-a
syscall            # Do print.

# Now exit.
addi $v0, $0, 10   # Exit.
syscall

```

```

// A global variable
g = 123

def main():

    // Three local variables
    a = -5
    b = 0
    c = 230

    // Do some arithmetic
    b = g + a

    // Do some more arithmetic
    print(c - a)


```

- System stack:
  - ➔ Pushing and popping
  - ➔ **\$sp** and **\$fp**
- Local variables:
  - ➔ Stored on stack
  - ➔ Accessed with negative offset from **\$fp**
- Addressing: register + constant

# Reminder: why using functions?

- As **encapsulation** of a sequence of instructions:
  - ➔ Can be called repeatedly (**reuse**)
  - ➔ Can call other functions
  - ➔ Are self-contained
  - ➔ Can have their own private (local) variables/data
- As **abstractions**:
  - ➔ Can be generalised by taking parameters.
  - ➔ Can inform through return values.
- As **hiders** of information: make sure caller cannot access/modify internal data

# Function calling: return where?





# Jump Instructions

- jump (go) to label, e.g.,  
`j foo`      `# set PC = foo`  
              `# so, go to foo`
- jump to label and link (remember origin), e.g.,  
`jal foo`      `# $ra = PC+4; PC = foo, so same`  
              `# but setting a return address`
- jump to address contained in register, e.g.,  
`jr $t0`      `# set PC=$t0, so go to the`  
              `# address contained in $t0`
- jump to register and link (remember origin), e.g.,  
`jalr $t0`      `# $ra = PC+4; PC = $t0, same`  
              `# but setting a return address`

*sqr.py*

```
def sqr(n):  
    return n*n
```

```
print(sqr(int(input())))
```

Simple convention

```
def sqr(n):  
    return n*n  
  
print(sqr(int(input())))
```

.text

addi \$v0, \$0, 5 # read integer

syscall

add \$a0, \$0, \$v0 # \$a0 = \$v0

jal sqr # \$v0 = sqr(\$a0)

add \$a0, \$0, \$v0 # \$a0 = \$v0

addi \$v0, \$0, 1 # print \$a0

syscall

addi \$v0, \$0, 10 # exit

syscall

sqr:


mult \$a0, \$a0 # LO = \$a0\*\$a0

mflo \$v0 # \$v0 = LO

jr \$ra # return \$v0

Recall:

jal stores  
PC + 4 in \$ra



# Function calling in MIPS

To **write** a function

- ➔ Put **label** at the **start** of the function
- ➔ Write body of the function
- ➔ **End** function with **jr \$ra**

To **call** a function

- ➔ Write **jal label**
- ➔ When the function returns, program will continue from the next instruction

# Passing data

- Some functions take **parameters**. We need a way of passing parameters from caller to function.
- Some functions **return values**. We need a way of getting the return value safely back to caller.
- Reserve some **registers** for these tasks
  - We can use the “**syscall**” data passing method.
  - Pass function **parameters** in **\$a0, \$a1, \$a2, \$a3**.
  - **Return** values in **\$v0, \$v1**

# *sqr.py*

```
def sqr(n):  
    return n*n
```

```
print(sqr(int(input())))
```

Only one argument

No other local  
variables

No function calls

Single value returned

# Limitations


This simple function-calling convention works, but **has limits**

- Function must not call other functions
- Function call is limited to four arguments (**\$a0-\$a3**)
- Function must only write to “safe” registers **\$v0-\$v1, \$a0-\$a3, \$t0-\$t9**
- Function must not use local variables, only arguments
- Function can only return two values **\$v0** and **\$v1**



Original **\$ra** is lost!

**Solution:** Save and restore **\$ra** register on the stack upon function entry/exit.



# Too many arguments

```
addi $a0, $0, 1
lw $a1, x
addi $a2, $0, 0
lw $a3, -4($fp)
addi $??, $0, 2
jal five
...
```

```
five: # takes 5
      # parameters
      ...
      # examine
      # $a0, etc
      ...
      jr $ra
```


No such register **\$a4**

Not enough registers to use as function arguments

Not enough registers to use as function arguments

## **Solution:** Save arguments on the stack

```
# push 2
# push global y
# push 0
# push local x
# push 1
jal five
# pop
# pop
# pop
# pop
# pop
```



```
five: # takes 5
      # parameters
      ...
      # examine
      # stack
      ...
      jr $ra
```

**FIT1008:**

For simplicity we will use the stack to pass **all** arguments

# Saving registers

```
...  
lw $t0, a  
...  
...  
jal func  
...  
...  
# $t0 has been  
# changed!  
add $t0, $t0, $v0  
...
```

```
func: ...  
    # trashes  
    # $t0  
    lw $t0, x  
    ...  
    jr $ra
```

Function may use registers which hold important values.

**Solution:** save/restore registers on stack.

# Function calling convention

These **steps** must be performed **every time** a function starts:

1. Save temporary registers
2. Save arguments
3. Call function with **jal** instruction
4. Save **\$ra** register
5. Save **\$fp** register
6. Update **\$fp**
7. Allocate local variables