

Faculty of Information Technology, Monash University

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act. Do not remove this notice

FIT2004, S2/2016

Week 11: Topological Sort and Numerical Algorithms

Lecturer: Muhammad Aamir Cheema

ACKNOWLEDGMENTS

The slides are based on the material developed by [Arun Konagurthu](#) and [Lloyd Allison](#).

Announcements

- Last assessment released
 - Due: 17-Oct-2016 10:00:00
- Programming Competition round 3 closes on Saturday 22-Oct-2016 23:59:00
 - Trophy and Certificates to be given next week
- Start preparing for the final exam earlier
 - Listen to the lectures (or read slides)
 - Attempt tutorial questions
 - Attempt lab questions
 - Attempt past paper - released
 - Most importantly, do not hesitate to seek help

Overview

- Directed Acyclic Graph (DAG)
- Topological Sort on DAG
- Numerical Algorithms
 - Finding root of a function
 - Numerical Integration

Recommended reading


- Cormen et al. Introduction to Algorithms.
 - Chapter 23, Pages 624-638
- <http://www.csse.monash.edu.au/~lloyd/tildeAlgDS/Graph/DAG/>
- <http://www.csse.monash.edu.au/~lloyd/tildeAlgDS/Numerical/Integration/>

Directed Acyclic Graph (DAG)


A Directed Acyclic Graph (DAG) is

- **D**irected
- **A**cyclic – has no cycles
- **G**raph

Which of the two graphs is a DAG?





Graph 1



Graph 2

DAG: Examples

- sub-tasks of a project and “must finish before”
 - $A \rightarrow B$ means task A must finish before task B
 - so, DAGs useful in project management
- relationships between subjects for your degree -- “is prerequisite for”
 - $A \rightarrow B$ means subject A must be completed before enrolling in subject B
- people genealogy – “is an ancestor of”
 - $A \rightarrow B$ means A is an ancestor of B
- power sets and “is a subset of”
 - $A \rightarrow B$ means A is a subset of B



Source: wikipedia


Topological Sort of a DAG

Partial order of vertices in a DAG

- $A < B$ if $A \rightarrow B$.
 - Note that if $A \rightarrow B$ and $B \rightarrow D$, we have $A < B$ and $B < D$ which implies that $A < D$ (i.e., transitivity).
- Some vertices may be incomparable (e.g., B and C are incomparable), i.e. $A < B$ and $A < C$ but we do not know whether $C < B$ or $B < C$.

A topological Sort

- is a permutation of the vertices in the original DAG
- such that for every directed edge $u \rightarrow v$ of the DAG
- u appears before v in the permutation



Example: A, B, C, E, D


- Topological sort of a DAG of “is prerequisite of” example gives an ordering of the subjects for studying your degree, one at a time, while obeying prerequisite rules.

Topological Sort of a DAG

- A DAG can have many valid topological sorts, e.g., let u and v be two incomparable vertices, u may appear before or after v .

Which of these is not a valid topological sort of the DAG

1. A, B, C, E, D
2. A, C, B, E, D
3. A, C, E, B, D
4. A, B, C, E, D
5. A, B, E, C, D



Kahn's Algorithm

```
initialize Sorted to be empty # Sorted will contain the topological sort  
initialize a list L with vertices that do not have any incoming edge ?
```

```
while L is not empty:
```

```
    remove any vertex v from L
```

```
    S = S + {v}
```

```
    for each outgoing edge <v,u> of v:
```

```
        remove edge <v,u> from the graph
```

```
        if u has no other incoming edge: ?
```

```
            insert u in L # all the vertices that must appear before u has already  
            been added to S
```

```
if graph still has some edges:
```

```
    return error # graph has a cycle
```

```
else:
```

```
    return Sorted
```


L:

A	C
--------------	---

Sorted:

A	B	C	E	D
---	---	---	---	---

Time Complexity?




Kahn's Algorithm: Complexity

```
initialize Sorted to be empty # Sorted will contain the topological sort
initialize an array IncomingEdges[] with all values initialized to 0
for each edge <u,v>:
    IncomingEdge[v] += 1
initialize a list L with vertices for which IncomingEdges[v] = 0
while L is not empty:
    remove any vertex v from L
    S = S + {v}
    for each outgoing edge <v,u> of v:
        remove edge <v,u> from the graph
        IncomingEdges[u] = IncomingEdges[u] - 1
        if IncomingEdges[u] == 0: # u has no incoming edge
            insert u in L
if graph still has some edges:
    return error # graph has a cycle
else:
    return Sorted
```

$O(E+V)$

$O(E+V)$



Time Complexity: $O(V+E)$

Space Complexity: $O(V+E)$

Depth First Search

Initialization

Sorted = null # stores sorted list of vertices

Color all vertices yellow # yellow indicates not touched

while there are yellow vertices:

 select a yellow vertex x # any vertex can be selected

 DFS(x)

function DFS(vertex x):

if x is colored green: # green indicates it was accessed during a DFS

return ERROR #graph has a cycle

if x is colored yellow:

 color x green

for each neighbor y of x: # i.e., an edge $x \rightarrow y$


 DFS(y)

 color x red # red means added to Sorted

 add x to the head of Sorted


Note that a vertex is added to Sorted only after all
its neighboring vertices have been added

Sorted:



Time Complexity: $O(V+E)$


Space Complexity: $O(V+E)$



Algorithms to solve $f(x) = 0$

Problem

- For what value(s) of x does the function $f(x)$ take on the value 0.
 - E.g., Solve $x^2 - 4 \sin(x) = 0$
 - The solution(s) of x such that $f(x) = 0$ is called:
 - ✦ the root of the equation or
 - ✦ the zero of the function f



Algorithms to Solve $f(x) = 0$

Stopping Criteria

- When $f(x) = 0$ is a **nonlinear** equation, it **CANNOT** be solved in a **finite number of steps**.
- One resorts to **iterative methods** that produces increasingly accurate **approximations** to a solution.
- The process terminates once the result is “sufficiently” accurate.

Issues to consider

- In **finite precision** computing, there may be **NO** machine representable number x^* such that $f(x^*)$ is **exactly** zero.
- The function might have **multiple roots**.
- The function can be **discontinuous**.


We will study two approaches

- Interval Bisection Method
- Newton's Method

Interval Bisection Method

Binary Searching on a Continuous Domain

- Start with an initial range $[lo, hi]$ under the constraint that the root falls between lo and hi . This is called **bracketing** the root.
 - In other words, the **bracket** $[lo, hi]$ is chosen, such that $f(lo)$ has a value with an opposite sign compared to $f(hi)$.
- At each iteration, evaluate the function at the **midpoint of the bracketed interval** and **discard half of the interval**
- Repeat this process until we converge to the true solution up to some tolerance/precision.



Interval Bisection Method

#INPUT: Root bracket [lo,hi]

#PRECONDITION: requires $f(x)$ to be continuous

#PRECONDITION: $\text{computeSign}(f(\text{lo})) \neq \text{computeSign}(f(\text{hi}))$

loSign = computeSign($f(\text{lo})$)

while $(\text{hi}-\text{lo})/2 > \text{threshold}$: # limit iterations to prevent infinite loop

 mid = $(\text{lo} + \text{hi})/2$ # new midpoint

 midSign = computeSign($f(\text{mid})$)

if midSign == 0: # when mid is the root

 lo = hi = mid

else if midSign == loSign:


 lo = mid

else:

 hi = mid

return lo

$$f(x) = x^3 - x - 2$$



What is $f(\text{lo})$?
What is $f(\text{hi})$?
What is $f(\text{mid})$?

This graph is not a true representation and is just for illustration

Newton's Method

- Requires computing the derivative $f'(x)$ of the function $f(x)$
 - Iteratively formula $x_{n+1} = x_n - f(x_n) / f'(x_n)$
1. Set $n = 0$ and make an initial guess x_0
 2. Compute $x_{n+1} = x_n - f(x_n) / f'(x_n)$
 3. If $|x_{n+1} / x_n| < \text{threshold}$
 - Return x_{n+1}
 4. Else go to step 2

What is x_1 ?

What is x_2 ?

Example: compute square root of 300, i.e., $f(x) = x^2 - 300$
Or solve for x where $x^2 = 300$

$$f'(x) = 2x$$

Initial guess $\rightarrow x_0 = 10$

$$x_1 = x_0 - f(x_0)/f'(x_0) = 10 - (-200/20) = 20$$


$$x_2 = x_1 - f(x_1)/f'(x_1) = 20 - (100/40) = 17.5$$

$$x_3 = x_2 - f(x_2)/f'(x_2) = 17.5 - (6.25/35) = 17.321428571$$

...

Intuition behind Newton's Method

- $h = x_0 - x_1$
- $\tan(\theta) = f(x_0)/h$
- Tangent of a curve $f(x)$ at a point x_0 is $f'(x_0)$
- $f'(x_0) = f(x_0)/h$
- $h = f(x_0)/f'(x_0) = x_0 - x_1$
- Hence, $x_1 = x_0 - f(x_0)/f'(x_0)$



Limitations of Newton's Method


Although Newton's method is a very powerful technique and it usually converges on the root much faster than Interval Bisection Method, it has the following limitations:

- Calculating the derivative may be difficult or expensive
- The derivative may be zero and the procedure may halt due to division by zero
- May fail to converge
 - E.g., if $f(x) = 1 - x^2$ and initial guess is 0
- Hence, although Newton's method is faster, interval bisection method is applicable to more scenarios

Calculating Integral


How to solve the numerical integral of the form

$$\int_a^b f(x)$$



Calculating Integral: Rectangle Rule

- Divide the range $[a,b]$ in N equal width rectangles
- Let m be the mid point along the width of a rectangle
- Its height is then $f(m)$
 - The height can be negative (resulting in a negative area)
- Add the areas of all rectangles
- Larger N results in better approximation



Calculating Integral: Rectangle Rule

width = $(b-a)/N$; # divide into N rectangles of equal width

area = 0


for i=0 to N-1:

mid = $a + (i+0.5)*width$ #mid point of the rectangle

height = $f(\text{mid})$

area += height*width

return area



Calculating Integral: Trapezoidal Rule



- Use trapezoids instead of rectangles

Area of a trapezoid with width w and side lengths u and v

$$= wv + 0.5w(u-v)$$

$$= wv + 0.5wu - 0.5wv$$

$$= 0.5wv + 0.5wu = 0.5w(u+v)$$



Calculating Integral: Trapezoidal Rule

width = (b-a)/N

area = 0

for i=0 to N-1:


start = a + i*width # start is the x value of the lower left corner of the rectangle

u = f(start)

v = f(start + width) # start is the x value of the lower right corner

area += 0.5*w*(u+v)

return area



Calculating Integral: Trapezoidal Rule

width = $(b-a)/N$

area = 0

for $i=0$ to $N-1$:

start = $a + i \cdot \text{width}$ # start is the x value of the lower left corner of the rectangle

$u = f(\text{start})$


$v = f(\text{start} + \text{width})$ # start is the x value of the lower right corner

area += $0.5 \cdot w \cdot (u+v)$

return area

What if the root lies between a trapezoid?

- Ignore – will add more error (if N is sufficiently large, the error is small)
- Create one trapezoid for negative area and another for positive area! (requires the root of the function)



Summary

Content covered

- Directed Acyclic Graphs and algorithms for topological sort
- Numerical algorithms for computing root and integrals

Things to do (this list is not exhaustive)

- Make sure you understand topological sort and numerical algorithms
- Write programs for the numerical algorithms – these are very easy to implement and will significantly increase your understanding

Coming Up Next

- Primality Testing
- Recursion and Design Principles
- Format of the Final Exam and how/what to prepare