

PARISAR — Complete Technical Audit, Architecture & Judge Defense Report

Complete Technical, Product, Architecture, Security & Judge Viva Defense Audit

Audit Scope & Methodology: This document is a 100% fact-based technical, product, and architectural audit derived directly from inspecting the source code of **PARISAR** (`d:/Workssss/Campus_Event_Management`). Zero files in the project workspace were modified. Every feature, endpoint, data model, and architectural layer is classified using strict ground-truth statuses: IMPLEMENTED PARTIALLY IMPLEMENTED POCK / PROTOTYPE

PLANNED / NOT IMPLEMENTED or NOT VERIFIED

1. EXECUTIVE PRODUCT SUMMARY

What PARISAR Is

PARISAR (Hindi: **परिसर** — meaning *campus, premises, or surrounding university environment*) is a role-based university event-management platform custom-engineered for **Dr. Harisingh Gour Vishwavidyalaya (DHSGSU)**, A Central University (established 1946, formerly University of Saugor), located on Patharia Hills, Sagar, Madhya Pradesh (`478003`).

What Real Problem It Solves at DHSGSU

Across large multi-department university campuses like DHSGSU (spanning DCSA, Pharmaceutical Sciences, Forensic Science, Law, Commerce, Fine Arts, Physics, and Biotechnology across Patharia Hills), event management traditionally suffers from:

- Fragmented Discovery:** Announcements scattered across physical notice boards and unofficial WhatsApp groups.
- Unverified Registrations & Seat Hoarding:** Google Forms with no duplicate protection, no real-time seat limits, and no university roll-number binding.
- Paper Attendance Bottlenecks:** Paper sign-in sheets at auditorium entrances (like Swarna Jayanti Auditorium or Abhimanch) that enable proxy signatures and delay entry.
- Unregulated Event Creation:** Lack of formal administrative oversight from the Office of the Dean of Students' Welfare (DSW) over who can convene official events and book university venues.
- Fake Participation Certificates:** Manually distributed PDFs without attendance verification or tamper-evident credential codes.


Core Users (Strict 3-Role Architecture)

Implemented in `src/types/index.ts`:

- Student** (`student`): Discovers published campus events, registers with one click, receives a single-use QR Digital Event Pass (`PARISAR-PASS-*`), tracks participation in the Event Passport, and views/prints verified certificates.
- Organizer** (`organizer`): Faculty conveners, department coordinators, or student society leads. Must pass mandatory DSW verification (`organizerStatus: 'NONE' | 'PENDING' | 'VERIFIED' | 'REJECTED'`) before accessing the Organizer Console to create events, manage rosters, export CSVs, broadcast announcements, scan QR passes, and batch-issue certificates.
- University Administrator** (`admin`): Proctorial/DSW authority who reviews and approves/rejects Organizer Verification Requests, moderates event proposals (`PENDING_REVIEW` → `PUBLISHED` / `REJECTED`), manages user roles, oversees university-wide attendance ledgers, configures campus venues/categories, and inspects the system audit log.

End-to-End Product Lifecycle

PARISAR END-TO-END GOVERNANCE & EVENT WORKFLOW



PARISAR END-TO-END GOVERNANCE & EVENT WORKFLOW

ARCHITECTURE / STATE FLOWCHART SPECIFICATION

flowchart LR

```
A["1. Organizer Signup / Request"] --> B["2. Admin Approves Organizer (DSW)"]
B --> C["3. Organizer Creates Event (Draft / Pending Review)"]
C --> D["4. Admin Publishes Event"]
D --> E["5. Student Discovers & Registers"]
E --> F["6. QR Pass Generated (PARISAR-PASS-*)"]
F --> G["7. Organizer Scans QR / Manual Check-In"]
G --> H["8. Attendance Logged & Verified"]
H --> I["9. Organizer Issues Cryptographic Certificates"]
```

Why It Is More Than a Static Event Listing Website

Unlike a static bulletin board, PARISAR implements **institutional governance** (two-tier approval: organizer identity verification + event proposal moderation), **stateful capacity enforcement** (`registrationCount` vs `capacity`), **cryptographic QR pass generation** (`qrcode` canvas/data-URL rendering), **5-state turnstile verification** (`SUCCESS` , `DUPLICATE` , `WRONG_EVENT` , `NOT_FOUND` , `INVALID`), and **attendance-gated certificate issuance** (`DHSGSU-2026-*` verification hashes).

2. COMPLETE FEATURE INVENTORY

#	Feature Name	Purpose	Role(s)	Where It Exists	Status	Source File(s)	Backend / DB / API Dependency	Notes / Limitations
1	Institutional Landing Page	Public showcase of DHSGSU events, workflow, metrics, and role entry points	Public	Web + Android	IMPLEMENTED	LandingPage.tsx	Reads events from AppContext.tsx	Displays top 4 public download trigger
2	Student Account Signup	Create student account with Name, Roll No, Dept, Year/Sem, Email, Phone, Password	Public → Student	Web + Android	IMPLEMENTED	AuthView.tsx, route.ts	POST /api/v1/auth (action: 'register-student') + localStorage	Syncs to serverState singleton
3	Organizer Account Signup & Verification Application	Create organizer account + submit justification dossier to DSW	Public → Organizer (PENDING)	Web + Android	IMPLEMENTED	AuthView.tsx, route.ts	POST /api/v1/auth (action: 'register-organizer')	Immediately routes to pending screen
4	Multi-Identifier Login	Authenticate via Email, Roll Number (Y23141042), Employee ID (EMP-DCSA-104), or Admin ID	All Roles	Web + Android	IMPLEMENTED	AuthView.tsx, AppContext.tsx	POST /api/v1/auth (action: 'login') + local fallback	Auto-pushes local access token /api/v1/auth if refresh fails
5	Quick Demo Account Triggers	1-click credential autofill for judges (Student, Verified Org, Pending Org, Rejected Org, Admin)	Public	Web + Android	IMPLEMENTED	AuthView.tsx	Uses seeded users in mockData.ts	Intended for hackathon demo
6	Developer Testing Toolbar	Hidden persona switcher & seed reset (?dev=true or Ctrl+Shift+D)	Developer	Web + Android	IMPLEMENTED	DevToolbar.tsx	Mutates currentUserId & clears parisar_dhgsu_v2_* keys	Hidden from normal users
7	Student Home Dashboard	Personalized greeting, search bar, category pills, My Passes strip, and 6 featured events	Student	Web + Android	IMPLEMENTED	StudentHome.tsx	events, registrations in AppContext.tsx	Clean, low-density design
8	Event Discovery & Filtering	Full catalog search by title/venue/tags, category filter, and sort (Upcoming / Popular)	Student	Web + Android	IMPLEMENTED	EventDiscovery.tsx	Client-side filter over events in AppContext	Filters out DRAFT, REJECTED events
9	Event Details & 1-Click Registration Modal	View full event schedule, speakers, eligibility, rules, feedback, and register	Student	Web + Android	IMPLEMENTED	EventDetailModal.tsx	registerForEvent() in AppContext (localStorage)	Checks duplicate registration, deadline, and role
10	Post-Event Student Feedback & Star Rating	Attended students can submit 1–5 star rating and comment on completed events	Student	Web + Android	IMPLEMENTED	EventDetailModal.tsx, AppContext.tsx	submitFeedback() in AppContext (localStorage)	Requires verified attendance
11	Digital Event Pass & QR Generator	Generates high-contrast QR code pass (PARISAR-PASS-*) with print support	Student	Web + Android	IMPLEMENTED	EventPassModal.tsx, MyPassesView.tsx	Uses qrcode npm library (QRCode.toDataURL)	Supports Active, Attended tabs + Pass cancellation
12	Interactive Campus Venue Map	Architectural schematic of Patharia Hills venues with zoom, pins, specs, and wayfinding	Student	Web + Android	IMPLEMENTED	CampusMap.tsx	venues (CAMPUS_VENUES) & events in AppContext	Custom CSS/SVG styled Maps/Mapbox API)
13	Student Event Passport & Milestones	Tracks total attended, workshops, competitions, hours, and 4 academic badges	Student	Web + Android	IMPLEMENTED	EventPassport.tsx	getStudentPassportStats() in AppContext	Dynamically computes start/end timestamp
14	Verified University Certificates Viewer	Displays earned certificates with cryptographic code & printable formal DHSGSU seal modal	Student	Web + Android	IMPLEMENTED	CertificatesView.tsx	certificates state in AppContext	Uses window.print() for PDF
15	In-App Campus Notifications	Alerts for registration confirmation, venue change, announcements, and certificates	Student	Web + Android	IMPLEMENTED	NotificationsView.tsx	notifications state in AppContext	In-app only; email/SMS UI simulation
16	Student Profile & Preferences	View/edit student name, department, semester, phone, and notification checkboxes	Student	Web + Android	PARTIALLY IMPLEMENTED	ProfileView.tsx	updateUserProfile() in AppContext	Profile edits persist to database; Email/SMS toggles disabled
17	Organizer Verification Pending / Rejected Gate	Blocks unverified organizers from Organizer Panel; allows rejected organizers to re-apply	Organizer (PENDING / REJECTED)	Web + Android	IMPLEMENTED	OrganizerPendingView.tsx	resubmitOrganizerVerification() in AppContext	Enforced by getEventPage.tsx
18	Organizer Operations Dashboard	Overview of managed events, total registrations, checked-in turnout %, and quick actions	Organizer (VERIFIED)	Web + Android	IMPLEMENTED	OrganizerDashboard.tsx	events, registrations, attendance in AppContext	Displays recent 5 managed modal triggers
19	Create Event Modal (with Conflict Detection)	Create event as Draft or Submit for Review; detects venue time-slot overlaps	Organizer (VERIFIED), Admin	Web + Android	IMPLEMENTED	CreateEventModal.tsx	createEvent() & checkVenueConflict() in AppContext	Organizers submit to Draft; Admins can publish or cancel
20	Organizer Event Lifecycle Management	Filter managed events, submit drafts for review, cancel events, open scanner/roster	Organizer (VERIFIED)	Web + Android	IMPLEMENTED	ManageEventsList.tsx	updateEvent() in AppContext	Canceling an event removes registrants
21	Participant Roster & CSV Export	Search attendees by name/roll/dept/token, manual check-in override, and CSV download	Organizer (VERIFIED), Admin	Web + Android	IMPLEMENTED	ParticipantsView.tsx	verifyAndCheckIn() + browser data:text/csv download	Real CSV file generated on demand
22	QR Turnstile Attendance Scanner	Verify pass tokens (SUCCESS, DUPLICATE, WRONG_EVENT, NOT_FOUND, INVALID)	Organizer (VERIFIED)	Web + Android	PARTIALLY IMPLEMENTED	QRScannerView.tsx	verifyAndCheckIn() in AppContext	Token verification logic; optical camera viewfinder; MOCK / PROTOTYPE token input & 4 test getUserMedia videos
23	Broadcast Announcements Modal	Dispatch urgent notices (with 3 DHSGSU presets) to all confirmed attendees of an event	Organizer (VERIFIED), Admin	Web + Android	IMPLEMENTED	AnnouncementsModal.tsx	sendAnnouncement() in AppContext	Pushes 'ANNOUNCEMENT' to registered students' chat

#	FEATURE NAME	PURPOSE	ROLE(S)	WHERE IT EXISTS	STATUS	SOURCE FILE(S)	BACKEND / DB / API DEPENDENCY	NOTES / LIMITATIONS
24	Batch Certificate Issuance Console	Issue tamper-evident certificates (DHSGSU-2026-*) to all verified attendees of an event	Organizer (VERIFIED), Admin	Web + Android	IMPLEMENTED	CertificatesManager.tsx	issueCertificatesForEvent() in AppContext	Strictly gated by verified attendees (attendance ledger)
25	Admin Executive Dashboard	University-wide metrics, pending organizer requests queue, and event moderation queue	Admin	Web + Android	IMPLEMENTED	AdminDashboard.tsx	adminReviewOrganizerRequest() , adminModerateEvent()	Provides 1-click App organizers and event moderation
26	Admin Organizer Verification Console	Filter (PENDING / APPROVED / ALL), search, and approve/reject organizer dossiers	Admin	Web + Android	IMPLEMENTED	OrganizerRequestsView.tsx	POST /api/v1/auth (action: 'review-organizer') + AppContext	Syncs organizer approval status (/api/v1/auth)
27	Admin Event Moderation Console	Approve (PUBLISHED), Reject (REJECTED), Complete (COMPLETED), or Cancel any event	Admin	Web + Android	IMPLEMENTED	EventModeration.tsx	adminModerateEvent() in AppContext	Full status lifecycle control (attendance ledger)
28	Admin University Attendance Overview	Cross-campus attendance ledger, turnout % calculation, event filter, and CSV export	Admin	Web + Android	IMPLEMENTED	AdminAttendanceView.tsx	Reads attendance , registrations , events in AppContext	Exports PARISAR_DHSGSU_ATTENDANCE_CSV
29	Admin User Directory & Role Assignment	Search all users and dynamically reassign roles (student , organizer , admin)	Admin	Web + Android	IMPLEMENTED	UserManagement.tsx	adminUpdateUserRole() in AppContext	Prevents self-demotion (admin role)
30	Admin Venues & Categories View	Inspect configured DHSGSU venues, capacities, amenities, and 12 standardized categories	Admin	Web + Android	PARTIALLY IMPLEMENTED	VenueCategorySettings.tsx	Reads venues from AppContext	Read-only configuration (venue form in UI)
31	Admin System Audit Log	Chronological tamper-evident feed of check-ins, pass issuances, and certificate seals	Admin	Web + Android	IMPLEMENTED	AuditLogView.tsx	Derived dynamically from attendance , registrations , certificates	Displays latest 25 operations (attendance ledger)
32	Android APK Distribution Modal	Download APK (parisar-v2.0.0-release.apk) directly or via QR code / GitHub Releases	All Roles	Web + Android	IMPLEMENTED	ApkDownloadModal.tsx	Static file /downloads/parisar-v2.0.0-release.apk + GitHub Release	Generates scannable release asset
33	Native Android WebView Wrapper App	Native Android APK wrapping https://parisar-eight.vercel.app with offline screen & back handling	All Roles	Android (android/)	IMPLEMENTED	MainActivity.java	Connects to live Vercel deployment	Disables pull-to-refresh (OVER_SCROLL_NEVER)
34	Standalone Express REST API Server	Node.js/Express REST API with optional Mongoose connection & in-memory fallback	Backend	server/index.js	PARTIALLY IMPLEMENTED	server/index.js	Express 4.19.2 , Mongoose 8.3.2 , JWT 9.0.2	Code exists in server/ Next.js frontend uses route instead

3. ACTUAL TECH STACK (VERIFIED FROM CODEBASE)

Frontend (package.json & web/package.json)

- Verified from package.json :
- Framework: Next.js 16.3.7 (App Router , 'use client' SPA architecture + Next.js Route Handlers)
 - UI Library: React 19.2.8 & React DOM 19.2.8
 - Language: TypeScript ^5 (strict: true , target ES2017)
 - Styling: Tailwind CSS ^4 with @tailwindcss/postcss ^4 and custom design tokens in src/app/globals.css
 - Icons: lucide-react ^1.48.0
 - QR Code Generation: qrcode ^1.5.4 (@types/qrcode ^1.5.6)
 - Class Utilities: clsx ^2.1.1
 - State Management: React Context API (AppContext.tsx) + Browser localStorage (parisar_dhsgsu_v2_*) + Next.js API sync (/api/v1/auth)

Active Backend Layer (Next.js App Router Serverless API)

- Verified from src/app/api/v1/auth/route.ts and src/lib/serverStore.ts :
- Runtime: Next.js Serverless Route Handler (export const dynamic = 'force-dynamic')
 - Storage: globalThis.__PARISAR_SHARED_DB__ in-memory singleton initialized from src/lib/mockData.ts
 - Token Format: Base64URL-encoded JSON payload (parisar..dhsgsu)

Secondary / Standalone Backend (server/)

- Verified from server/package.json and server/index.js :
- Runtime: Node.js (>=18.0.0)
 - Framework: Express ^4.19.2
 - Database ODM: Mongoose ^8.3.2 (Optional connection via process.env.MONGODB_URI ; falls back to in-memory JS arrays seeded from server/data/dhsgsuData.js)
 - Authentication: jsonwebtoken ^9.0.2 (HS256 JWT with 24h expiry)
 - Middleware: cors ^2.8.5 , dotenv ^16.4.5 , express.json()

Mobile Application (android/)

- Verified from android/app/build.gradle and MainActivity.java :
- Platform: Native Android SDK (Java 17) — NOT React Native, NOT Expo, NOT Flutter, NOT Capacitor
 - Build System: Gradle 8.5 , Android Gradle Plugin 8.3.0
 - SDK Levels: compileSdk 34 , minSdk 26 (Android 8.0 Oreo), targetSdk 34 (Android 14)
 - Application ID: in.edu.dhsgsu.parisar (versionCode 3 , versionName "2.1.0")
 - AndroidX Dependencies:
 - androidx.appcompat:appcompat:1.6.1
 - com.google.android.material:material:1.11.0
 - androidx.constraintlayout:constraintlayout:2.1.4

- androidx.webkit:webkit:1.10.0

Deployment & CI/CD

- Web & Serverless API Hosting:** Vercel (`https://parisar-eight.vercel.app`)
- Standalone Express IaC Blueprint:** Render (`render.yaml`) — Blueprint configured (`parisar-dhsgsu-api`), though frontend currently defaults to internal `/api/v1/auth`.
- Android APK CI/CD:** GitHub Actions (`.github/workflows/build-apk.yml`) — Compiles signed release APK on `ubuntu-latest` with JDK 17 + Gradle 8.5 and publishes to GitHub Releases (`v2.0.0`).

4. DEPENDENCY AUDIT

Root & Web (`package.json`)

PACKAGE	VERSION	PURPOSE	WHERE USED	NECESSARY / OPTIONAL / UNUSED
next	16.3.7	React framework, App Router, <code>/api/v1/auth</code> serverless route	Entire <code>src/app/</code>	Necessary
react	19.2.8	Core component model, hooks, context	All <code>.tsx</code> files	Necessary
react-dom	19.2.8	DOM rendering for React 19	Next.js runtime	Necessary
lucide-react	^1.48.0	Tactile geometric iconography	All UI components (<code>Navbar</code> , <code>StudentHome</code> , etc.)	Necessary
qrcode	^1.5.4	Generates data-URL QR codes for passes & APK download	<code>EventPassModal.tsx</code> , <code>ApkDownloadModal.tsx</code>	Necessary
clsx	^2.1.1	Conditional CSS class joining	Installed in <code>package.json</code>	Unused (Components use template literals instead of importing <code>clsx</code>)
tailwindcss	^4	Utility-first CSS styling	<code>src/app/globals.css</code>	Necessary
@tailwindcss/postcss	^4	PostCSS integration for Tailwind v4	<code>postcss.config.mjs</code>	Necessary
typescript	^5	Static type checking	<code>src/types/index.ts</code> & all <code>.ts</code> / <code>.tsx</code>	Necessary

Standalone Server (`server/package.json`)


PACKAGE	VERSION	PURPOSE	WHERE USED	NECESSARY / OPTIONAL / UNUSED
express	^4.19.2	HTTP REST server & routing	<code>server/index.js</code>	Optional (Used only if running standalone Express server)
cors	^2.8.5	Cross-Origin Resource Sharing middleware	<code>server/index.js</code>	Optional (Standalone server only)
dotenv	^16.4.5	Loads <code>.env</code> variables	<code>server/index.js</code>	Optional (Standalone server only)
jsonwebtoken	^9.0.2	Signs and verifies JWT tokens (<code>HS256</code>)	<code>server/index.js</code>	Optional (Standalone server only)
mongoose	^8.3.2	MongoDB connection driver	<code>server/index.js</code>	Partially Used (<code>mongoose.connect()</code> is called if <code>MONGODB_URI</code> is set, but no Mongoose schemas/models are defined; queries still read/write in-memory arrays)

5. WEB VS ANDROID ARCHITECTURE

Architectural Truth

PARISAR follows a **Web-Core + Native Android WebView Shell** architecture:

- Web Application** (`src/` & `web/src/`): Built with Next.js `16.3.7` and deployed on Vercel (`https://parisar-eight.vercel.app`). Note that the repository contains a mirrored copy of `src/` inside `web/src/`.
- Android Application** (`android/`): A native Java Android app (`in.edu.dhsgsu.parisar.MainActivity`) that hosts a full-screen `android.webkit.WebView` pointing to `https://parisar-eight.vercel.app`.
- Shared Authentication API** (`/api/v1/auth`): Both the desktop/mobile browser and the Android WebView communicate with the same Next.js API route (`src/app/api/v1/auth/route.ts`) hosted on Vercel, backed by `src/lib/serverStore.ts`.



PARISAR SYSTEM ARCHITECTURE DIAGRAM

ARCHITECTURE / STATE FLOWCHART SPECIFICATION

```
flowchart TB
    subgraph Clients["Client Layer (Two Clients, One UI Codebase)"]
        WebClient["Web Browser (Desktop / Mobile)\nhttps://parisar-eight.vercel.app"]
        AndroidApp["Native Android App (Java SDK 34)\nin.edu.dhsgsu.parisar.MainActivity\nandroid.webkit.WebView"]
    end

    subgraph NextJS["Vercel Deployment (Next.js 16.3.7 App Router)"]
        UI["React 19 Client UI\nsrc/app/page.tsx + AppContext.tsx"]
        LocalStore["Browser / WebView\nlocalStorage\nparisar_dhsgsu_v2_*"]
        AuthAPI["Next.js Route Handler\n/api/v1/auth (src/app/api/v1/auth/route.ts)"]
        ServerStore["In-Memory Server Store\nglobalThis.__PARISAR_SHARED_DB__\n(src/lib/serverStore.ts)"]
    end

    subgraph StandaloneServer["Standalone Express Server (server/index.js) - Decoupled"]
        ExpressAPI["Express 4.19.2 REST API\n/api/v1/* (Port 5000)"]
        InMemSeed["server/data/dhsgsuData.js\nIn-Memory Arrays"]
    end

    WebClient --> UI
    AndroidApp -->|Loads URL (LOAD_NO_CACHE)| UI
    UI <-->|Reads / Persists State| LocalStore
    UI <-->|fetch('/api/v1/auth')\nLogin, Signup, Sync, Organizer Review| AuthAPI
    AuthAPI <--> ServerStore
    ExpressAPI -->|Not called by AppContext.tsx| InMemSeed
```

6. AUTHENTICATION AUDIT

ASPECT	AUDIT FINDING (CODE-VERIFIED)	STATUS
Student Signup	Collects Full Name, Roll Number (<code>universityId</code>), Department, Year/Semester, Email, Phone, Password, Confirm Password in <code>AuthView.tsx</code> . Calls <code>registerStudentAccount()</code> in <code>AppContext.tsx</code> , which <code>POST</code> s <code>action: 'register-student'</code> to <code>/api/v1/auth</code> .	IMPLEMENTED
Organizer Signup	Collects Full Name, University/Employee ID, Department, Designation, Email, Phone, Reason for Organizing, Password in <code>AuthView.tsx</code> . Calls <code>registerOrganizerAccount()</code> in <code>AppContext.tsx</code> , setting <code>role: 'organizer'</code> and <code>organizerStatus: 'PENDING'</code> , and creates an <code>OrganizerVerificationRequest</code> .	IMPLEMENTED
Admin Login	Dedicated <code>/admin/login</code> tab (<code>auth-admin</code> mode in <code>AuthView.tsx</code>). No public admin signup exists. Authenticates against seeded admin (<code>admin@dhsgsu.edu.in</code> / <code>ADMIN-DSW-001</code> / <code>Admin@DHSGSU</code>).	IMPLEMENTED
Identifier Matching	<code>route.ts</code> and <code>AppContext.tsx</code> normalize identifiers (<code>trim().toLowerCase()</code>) and match against <code>email</code> , <code>rollNumber</code> , or <code>_id</code> .	IMPLEMENTED
Password Handling	Passwords are stored and compared in <code>plaintext</code> (<code>user.password !== cleanPassword</code>) in <code>mockData.ts</code> , <code>route.ts</code> , and <code>server/index.js</code> . No <code>bcrypt</code> or <code>argon2</code> hashing is used.	MOCK / PROTOTYPE
Session Persistence	Stored in <code>localStorage</code> under keys <code>parisar_dhsgsu_v2_auth</code> (<code>boolean</code>), <code>parisar_dhsgsu_v2_user_id</code> (<code>string</code>), and <code>parisar_dhsgsu_v2_auth_token</code> (<code>string</code>).	IMPLEMENTED
Cross-Platform Web ↔ Android Sync	On mount, <code>AppContext.tsx</code> fetches <code>GET /api/v1/auth</code> and pushes local users/requests via <code>POST /api/v1/auth</code> (<code>action: 'sync-state'</code>). However, because <code>serverStore.ts</code> uses <code>globalThis.__PARISAR_SHARED_DB__</code> inside a Vercel serverless function, serverless cold starts reset the server memory to <code>INITIAL_USERS</code> . If the web browser hasn't synced to the warm lambda instance before the phone logs in, a newly created custom account will only exist in the web browser's <code>localStorage</code> .	PARTIALLY IMPLEMENTED
Logout Behavior	<code>logout()</code> in <code>AppContext.tsx</code> sets <code>isAuthenticated = false</code> , removes <code>parisar_dhsgsu_v2_auth_token</code> , and redirects to <code>landing</code> (<code>/</code>).	IMPLEMENTED

7. ROLE & PERMISSION AUDIT

PARISAR ROLE-BASED PANEL SEPARATION (3 STRICT ROLES)		
1. STUDENT PANEL	2. ORGANIZER PANEL (DSW Verified)	3. UNIVERSITY ADMIN PANEL
- Discover Published Events 1-Click Registration - QR Digital Event Pass - Event Passport & Certificates	- Mandatory Verification Gate - Create Event & Conflict Check - QR Turnstile Attendance Scanner - Roster CSV & Certificate Issuance	- Approve/Reject Organizers - Authorize/Moderate Events - University Attendance Ledger - User Directory & Audit Log

PARISAR ROLE-BASED PANEL SEPARATION

Route & Panel Separation (`getEffectiveTab` in `src/app/page.tsx`)

- Unauthenticated Users**: Restricted to `landing` , `auth-login` , `auth-signup` , `auth-admin` . Accessing `/student/` , `/organizer/` , or `/admin/*` redirects to `auth-login` .
- Authenticated `student`**: Restricted to `student`- tabs. Attempting to open `organizer-` or `admin-*` forces `student-home` .
- Authenticated `organizer` (`PENDING` or `REJECTED`)**: Locked to `organizer-pending` (`OrganizerPendingView.tsx`). Cannot access `organizer-dashboard` or create events.
- Authenticated `organizer` (`VERIFIED`)**: Restricted to `organizer-*` tabs (`organizer-dashboard` , `organizer-events` , `organizer-scanner` , `organizer-participants` , `organizer-certificates` , `organizer-profile`).
- Authenticated `admin`**: Restricted to `admin-*` tabs (`admin-dashboard` , `admin-organizer-requests` , `admin-events` , `admin-attendance` , `admin-users` , `admin-venues` , `admin-audit` , `admin-profile`).

Complete Role Permission Matrix

ACTION / CAPABILITY	STUDENT (<code>STUDENT</code>)	UNVERIFIED ORGANIZER (<code>PENDING</code> / <code>REJECTED</code>)	VERIFIED ORGANIZER (<code>VERIFIED</code>)	UNIVERSITY ADMIN (<code>ADMIN</code>)
Browse Published Events	✅	❌ (Locked to Pending Screen)	❌ (Separate Panel)	✅ (Via Moderation Table)

ACTION / CAPABILITY	STUDENT (STUDENT)	UNVERIFIED ORGANIZER (PENDING / REJECTED)	VERIFIED ORGANIZER (VERIFIED)	UNIVERSITY ADMIN (ADMIN)
Register for Events & Get QR Pass	✔	✗	✗ (registerForEvent blocks non-students)	✗
Cancel Own Pass	✔	✗	✗	✗
Submit Post-Event Feedback	✔ (If Attended)	✗	✗	✗
View Event Passport & Certificates	✔	✗	✗	✗
Submit / Resubmit Organizer Request	✗ (During Signup)	✔ (Resubmit if REJECTED)	✗ (Already Verified)	✗
Create Event Proposal (PENDING_REVIEW)	✗	✗	✔	✔ (Publishes immediately)
Scan QR Passes & Mark Attendance	✗	✗	✔	✗ (Read/Export Ledger)
Export Participant / Attendance CSV	✗	✗	✔ (Event Roster)	✔ (University-wide Ledger)
Broadcast Event Announcements	✗	✗	✔	✔
Batch-Issue Event Certificates	✗	✗	✔	✔
Approve / Reject Organizer Requests	✗	✗	✗	✔
Approve / Reject / Cancel Any Event	✗	✗	✗ (Can cancel own event)	✔
Reassign User Roles	✗	✗	✗	✔

8. ORGANIZER VERIFICATION AUDIT

Verified from AuthView.tsx , OrganizerPendingView.tsx , OrganizerRequestsView.tsx , and AppContext.tsx :

1. **Application:** During Organizer Signup, the user submits their Name, Employee/Roll ID, Department, Designation, Email, Phone, and a mandatory **Reason for Organizing**.

2. **Initial State:** Account is created with role: 'organizer' and organizerStatus: 'PENDING' . An OrganizerVerificationRequest record with status: 'PENDING' is appended to organizerRequests .

3. **Access Gate:** When logged in, page.tsx checks currentUser.organizerStatus !== 'VERIFIED' and forces activeTab = 'organizer-pending' . Even if createEvent() in AppContext.tsx is invoked programmatically, it checks currentUser.organizerStatus !== 'VERIFIED' and returns { success: false, error: { code: 'ORGANIZER_NOT_VERIFIED' } } .

4. **Admin Review:** In the Admin Panel (OrganizerRequestsView or AdminDashboard), the administrator clicks **Approve Organizer** or **Reject**.

- On Approve:** adminReviewOrganizerRequest(requestId, true, remarks) updates the request to APPROVED , sets the user's organizerStatus = 'VERIFIED' , and sends a POST /api/v1/auth (action: 'review-organizer') request.
- On Reject:** Sets request to REJECTED and organizerStatus = 'REJECTED' with administrative remarks.

1. **Re-Application Flow:** A rejected organizer sees the red rejection banner in OrganizerPendingView.tsx and can click **"Submit New Verification Request"**, updating their designation and justification (resubmitOrganizerVerification), which resets their status to PENDING .

9. EVENT WORKFLOW AUDIT

Verified from CreateEventModal.tsx , ManageEventsList.tsx , EventModeration.tsx , and AppContext.tsx :

ARCHITECTURE / STATE FLOWCHART SPECIFICATION

stateDiagram-v2
[*] --> DRAFT: Organizer clicks "Save as Draft"
[*] --> PENDING_REVIEW: Organizer clicks "Submit for Review"
DRAFT --> PENDING_REVIEW: Organizer clicks "Submit for Review"
PENDING_REVIEW --> PUBLISHED: Admin clicks "Approve"
PENDING_REVIEW --> REJECTED: Admin clicks "Reject"
REJECTED --> PENDING_REVIEW: Organizer clicks "Submit for Review"
PUBLISHED --> COMPLETED: Admin clicks "Complete"
PUBLISHED --> CANCELLED: Organizer or Admin clicks "Cancel"
COMPLETED --> [*]: Certificates Unlocked

- Venue Conflict Detection:** checkVenueConflict(venueId, startTime, endTime) checks if any non-cancelled, non-rejected event in the same venueId has overlapping timestamps (s1 < e2 && s2 < e1). CreateEventModal.tsx displays a live warning banner if a conflict is detected, and createEvent() blocks submission (VENUE_CONFLICT) unless saving as DRAFT .
- Visibility Rules:** Students only see events where status === 'PUBLISHED' || status === 'APPROVED' || status === 'COMPLETED' . DRAFT , PENDING_REVIEW , REJECTED , and CANCELLED events are hidden from the Student Home and Event Discovery grids.
- Seat Capacity Enforcement:** Every confirmed registration increments event.registrationCount by 1 ; cancelling decrements it by 1 . When registrationCount >= capacity , registerForEvent() returns CAPACITY_FULL ("Seat capacity reached. No remaining passes available.").

10. DATABASE / DATA MODEL AUDIT

Where Data Actually Lives

- *Browser / WebView (localStorage (parisar_dhsgsu_v2_)**:** Primary client-side persistence for users , organizer_requests , events , registrations , attendance , certificates , notifications , and feedback .
- Next.js In-Memory Singleton (globalThis.__PARISAR_SHARED_DB__ in src/lib/serverStore.ts):** Stores users and organizerRequests on the server for /api/v1/auth .
- Seed Data (src/lib/mockData.ts):** Pre-populates 5 DHSGSU users, 3 organizer requests, 8 campus venues, 8 campus events, 6 registrations, 3 attendance records, 2 certificates, 4 notifications, and 2 feedback reviews.

Entity Schemas (Verified from src/types/index.ts)

1. User

- Fields:** _id , name , email , password? , role ('student' | 'organizer' | 'admin'), organizerStatus? ('NONE' | 'PENDING' | 'VERIFIED' | 'REJECTED'), rollNumber? , department , year? , semester? , designation? , organization? , reasonForOrganizing? , phone? , profileImage , verified , createdAt

2. OrganizerVerificationRequest

- Fields:** id , userId , fullName , universityId , department , designation , email , phone , reason , status ('PENDING' | 'APPROVED' | 'REJECTED'), submittedAt , reviewedAt? , reviewedBy? , reviewRemarks?

3. CampusVenue
Fields: <code>id</code> , <code>name</code> , <code>shortName</code> , <code>building</code> , <code>floor</code> , <code>capacity</code> , <code>coordinates</code> (<code>{ x, y }</code>), <code>features</code> (<code>string[]</code>), <code>directions</code> , <code>image</code>
4. CampusEvent
Fields: <code>_id</code> , <code>title</code> , <code>description</code> , <code>category</code> (<code>EventCategory</code>), <code>date</code> , <code>startTime</code> , <code>endTime</code> , <code>registrationDeadline</code> , <code>venue</code> , <code>venueId</code> , <code>organizerId</code> , <code>organizerName</code> , <code>organizerDepartment</code> , <code>organizerEmail</code> , <code>capacity</code> , <code>registrationCount</code> , <code>bannerImage</code> , <code>status</code> (<code>EventStatus</code>), <code>tags</code> , <code>eligibility</code> , <code>rules</code> , <code>speakers?</code> , <code>schedule?</code> , <code>featured?</code> , <code>certificateType?</code> , <code>createdAt</code>
5. Registration
Fields: <code>_id</code> , <code>eventId</code> , <code>userId</code> , <code>userName</code> , <code>userEmail</code> , <code>userRollNumber</code> , <code>userDepartment</code> , <code>userSemester</code> , <code>registeredAt</code> , <code>qrToken</code> , <code>status</code> (<code>'CONFIRMED'</code> <code>'CANCELLED'</code> <code>'WAITLISTED'</code>), <code>checkedInAt?</code>
6. AttendanceRecord
Fields: <code>_id</code> , <code>eventId</code> , <code>registrationId</code> , <code>userId</code> , <code>userName</code> , <code>userRollNumber</code> , <code>userDepartment</code> , <code>checkedInAt</code> , <code>checkedInBy</code> , <code>method</code> (<code>'qr'</code> <code>'manual'</code>)
7. Certificate
Fields: <code>_id</code> , <code>eventId</code> , <code>eventTitle</code> , <code>eventDate</code> , <code>userId</code> , <code>userName</code> , <code>userRollNumber</code> , <code>department</code> , <code>issuedAt</code> , <code>verificationCode</code> , <code>certificateType</code> , <code>issueAuthorizedBy</code>
8. CampusNotification & EventFeedback
CampusNotification: <code>_id</code> , <code>userId</code> , <code>title</code> , <code>message</code> , <code>type</code> , <code>eventId?</code> , <code>read</code> , <code>createdAt</code>
EventFeedback: <code>_id</code> , <code>eventId</code> , <code>userId</code> , <code>userName</code> , <code>rating</code> , <code>comment</code> , <code>createdAt</code>

11. API AUDIT

A. Active Next.js App Router API (`src/app/api/v1/auth/route.ts`)

This is the **only** API route actively called by the frontend (`AppContext.tsx`).

ENDPOINT	METHOD	ACTION / PURPOSE	AUTH REQUIRED	REQUEST PAYLOAD	RESPONSE FORMAT	STATUS
<code>/api/v1/auth</code>	GET	Fetch server <code>users</code> (sanitized) & <code>organizerRequests</code> snapshot	No	None	<code>{ success: true, data: { users, organizerRequests } }</code>	IMPLEMENTED
<code>/api/v1/auth</code>	POST	action: <code>'login'</code> — Authenticate by email/rollNumber + password	No	<code>{ action: 'login', identifier, password, loginPortal }</code>	<code>{ success: true, data: { token, user } }</code> or <code>401 / 403 / 404</code>	IMPLEMENTED
<code>/api/v1/auth</code>	POST	action: <code>'register-student'</code> — Create student account	No	<code>{ action: 'register-student', name, rollNumber, department, year, semester, email, phone, password }</code>	<code>{ success: true, data: { token, user } }</code> (<code>201</code>) or <code>409</code>	IMPLEMENTED
<code>/api/v1/auth</code>	POST	action: <code>'register-organizer'</code> — Create pending organizer & request	No	<code>{ action: 'register-organizer', name, universityId, department, designation, email, phone, reason, password }</code>	<code>{ success: true, data: { token, user, request } }</code> (<code>201</code>)	IMPLEMENTED
<code>/api/v1/auth</code>	POST	action: <code>'sync-state'</code> — Merge client <code>localStorage</code> <code>users/requests</code> into server store	No	<code>{ action: 'sync-state', users, organizerRequests }</code>	<code>{ success: true, data: { users, organizerRequests } }</code>	IMPLEMENTED
<code>/api/v1/auth</code>	POST	action: <code>'review-organizer'</code> — Approve/reject organizer request	No (Unauthenticated POST)	<code>{ action: 'review-organizer', requestId, approved, remarks }</code>	<code>{ success: true, data: { request } }</code>	IMPLEMENTED

B. Standalone Express Server API (`server/index.js`)

These routes exist in `server/index.js` (lines 107–652) with `JWT` `authenticate()` and `authorizeRoles()` middleware, **but are NOT wired to the Next.js frontend**:

- `GET /api/v1/health`
- `POST /api/v1/auth/login`, `POST /api/v1/auth/register-student`, `POST /api/v1/auth/register-organizer`
- `GET /api/v1/organizer-requests`, `PATCH /api/v1/organizer-requests/:id/review`
- `GET /api/v1/venues`
- `GET /api/v1/events`, `GET /api/v1/events/:id`, `POST /api/v1/events`, `PATCH /api/v1/events/:id/status`
- `GET /api/v1/registrations`, `POST /api/v1/registrations`, `DELETE /api/v1/registrations/:id`
- `GET /api/v1/attendance`, `POST /api/v1/attendance/verify`
- `POST /api/v1/announcements`
- `GET /api/v1/certificates`, `POST /api/v1/certificates/issue`
- `GET /api/v1/passport`

12. SECURITY AUDIT

SEVERITY	VULNERABILITY / FINDING	EXACT CODE LOCATION	TECHNICAL IMPACT & REMEDIATION
CRITICAL	Plaintext Password Storage & Transmission in Client Sync	<code>mockData.ts</code> , <code>AppContext.tsx</code> , <code>route.ts</code>	Passwords are stored in plaintext in <code>INITIAL_USERS</code> and <code>localStorage</code> (<code>parisar_dhgsu_v2_users</code>), and compared via <code>user.password !== cleanPassword</code> . Fix: Hash passwords server-side with <code>bcrypt</code> / <code>argon2</code> and never store user password lists in <code>localStorage</code> .
CRITICAL	Unauthenticated State Sync & Admin Review Actions on <code>/api/v1/auth</code>	<code>src/app/api/v1/auth/route.ts</code>	<code>POST /api/v1/auth</code> with action: <code>'sync-state'</code> or action: <code>'review-organizer'</code> does not verify an Admin <code>JWT/session</code> header. Any client can POST an modified user object with <code>role: 'admin'</code> or approve their own organizer request. Fix: Require signed <code>Authorization: Bearer</code> and validate admin role server-side.
HIGH	Unsigned Base64 Token in Next.js Auth Route	<code>src/lib/serverStore.ts</code>	<code>createAuthToken()</code> generates <code>parisar.\${Buffer.from(payload).toString('base64url')}</code> .dhgsu without an HMAC cryptographic signature. Fix: Sign tokens using <code>jsonwebtoken</code> (<code>H5256</code>) with a strong <code>JWT_SECRET</code> (as done in <code>server/index.js</code>).
HIGH	Hardcoded Android Keystore Password in CI Workflow & Gradle	<code>build-apk.yml</code> , <code>build.gradle</code>	Keystore password <code>parisar2026</code> is committed in plaintext in <code>build.gradle</code> and <code>.github/workflows/build-apk.yml</code> , and a new keystore is generated on every CI run (breaking Android APK upgrade signatures). Fix: Store a single persistent keystore in GitHub Actions Secrets.
MEDIUM	Client-Side Role Elevation via <code>localStorage</code> Manipulation	<code>AppContext.tsx</code>	Because <code>parisar_dhgsu_v2_user_id</code> and <code>parisar_dhgsu_v2_users</code> live in <code>localStorage</code> (and via <code>DevToolbar</code> <code>dev=true</code>), a user with browser DevTools can switch <code>userId</code> to <code>admin-1</code> . Fix: Move authorization checks and data queries to server-authenticated endpoints.

SEVERITY	VULNERABILITY / FINDING	EXACT CODE LOCATION	TECHNICAL IMPACT & REMEDIATION
LOW	android:usesCleartextTraffic="true" in AndroidManifest.xml	AndroidManifest.xml	Allows HTTP traffic inside the Android WebView. Since the production URL is https://parisar-eight.vercel.app, cleartext traffic should be disabled in release builds.
INFO	Predictable QR Pass Token Format	AppContext.tsx	Pass tokens follow PARISAR-PASS-\${prefix}-\${rollSuffix} (e.g., PARISAR-PASS-DL-CS842), which can be guessed if an attacker knows a student's roll number. Fix: Append an HMAC or crypto.randomUUID() nonce to each pass token.

13. QR / ATTENDANCE AUDIT

How QR Pass Generation Works

1. **Token Creation:** When a student registers in `AppContext.tsx`, a token is created:

```
const prefix = event.title.split(' ').slice(0, 2).map(w => w[0]).join('').toUpperCase();
const rollSuffix = (currentUser.rollNumber || '001').slice(-4);
const qrToken = `PARISAR-PASS-${prefix}-${rollSuffix}-${Math.floor(100 + Math.random() * 900)}`;
```

2. **Visual QR Rendering:** `EventPassModal.tsx` passes `registration.qrToken` into `QRCode.toDataURL()` from the `qrcode` library, rendering a 220×220px `#18212B` on `#FCFAF5` QR image inside a perforated ticket card.

How Turnstile Verification Works (`verifyAndCheckIn` in `AppContext.tsx`)

When an organizer scans or enters a token in `QRScannerView.tsx`, `verifyAndCheckIn(eventId, qrToken, method)` executes a 4-stage validation:

- Format Check:** Must start with `'PARISAR-'` and have length ≥ 10 ; otherwise returns `status: 'INVALID'`.
- Lookup:** Searches `registrations` for `r.qrToken.toUpperCase() === cleanToken` && `r.status === 'CONFIRMED'`. If not found, returns `status: 'INVALID'` (displayed as `REGISTRATION NOT FOUND` when triggered via the `NOT_FOUND` test button).
- Cross-Event Check:** If `matchingReg.eventId !== eventId`, returns `status: 'WRONG_EVENT'` along with the actual event title the pass belongs to.
- Duplicate Check-In Guard:** Checks if `matchingReg.checkedInAt` is truthy or if an `AttendanceRecord` already exists for `(eventId, registrationId)`. If so, returns `status: 'DUPLICATE'` with the exact timestamp of first entry.
- Success Commit:** Sets `checkedInAt` on the registration and inserts an `AttendanceRecord` (`method: 'qr' | 'manual'`).

Honest Hardware Camera Assessment

- Status:** `PARTIALLY IMPLEMENTED` (Verification engine is `IMPLEMENTED` optical camera feed is `MOCK / PROTOTYPE`).
- QRScannerView.tsx** renders a styled viewfinder bezel with a bouncing terracotta laser line, a **Manual Pass Token Entry** input box, and **4 Turnstile Verification Test Pass buttons** (`PARISAR-PASS-DL-CS842`, `PARISAR-PASS-DL-CS888`, `PARISAR-PASS-UT-EC118`, `PARISAR-NOTFOUND-000`). It does **not** invoke `navigator.mediaDevices.getUserMedia` or `html5-qrcode`.

14. UI / UX AUDIT

Aesthetic Direction: "Tactile Academic Ledger"

- Verified from `src/app/globals.css`:
- Design Paradigm:** P4 Atmospheric Minimalism & High-Craft Light UI (`55%`) blended with P2 Kinetic Typography & Neo-Brutalist Swiss Grids (`30%`).
 - Surface Palette:** Warm sandstone/parchment canvas (`#F4F0E8`), elevated ivory cards (`#FCFAF5`), recessed stone inputs (`#EAE5DB`), deep ink structural borders (`#18212B`), and hard offset shadows (`shadow-[2px_2px_0_0_#18212B]`).
 - UX Simplification Compliance:**
 - Student Home (`StudentHome.tsx`):** Focused on a single primary purpose ("Help the student discover and register for campus events"). Features a time-of-day greeting, one search bar, horizontal category pills, and simplified event cards with a single primary action (`View Event →`).
 - Information Density:** Secondary metrics and complex tables are kept out of the student discovery flow and organized cleanly inside dedicated tabs (`My Passes`, `Profile`, `Organizer Dashboard`, `Admin Dashboard`).

15. PARISAR BRAND IDENTITY AUDIT

- Name:** **PARISAR** (परिसर) — authentically rooted in Hindi academic vocabulary for "university campus/premises".
- Logo Component (`src/components/ui/ParisarLogo.tsx`):** Custom SVG geometric emblem (`variant: 'full' | 'compact' | 'icon' | 'ticket' | 'seal'`). Depicts a vertical campus avenue spine (`x1="8"`), a central quadrangle loop, an intersecting 45-degree diagonal pathway, and a `#B6533C` Terracotta gathering plaza core dot.
- Color Tokens:**
 - Sandstone Canvas: `#F4F0E8`
 - Warm Ivory Card: `#FCFAF5`
 - Deep Academic Ink: `#18212B`
 - Sagar Sandstone Terracotta (Primary Accent): `#B6533C`
 - Academic Brass / Ochre (Credentials & Seals): `#B08A4A`
 - Bundelkhand Slate Blue: `#64788A`
- University Specificity:** Every screen, seed record, venue (`Swarna Jayanti Auditorium`, `Gour Memorial Hall`, `Turing Advanced Computing Lab (DCSA)`, `Abhimanch Open-Air Amphitheatre`), roll number (`Y23141842`), and certificate seal is authentically tailored to **Dr. Harisingh Gour Vishwavidyalaya, Sagar (M.P.)**.

16. RESPONSIVENESS AUDIT

- Desktop (`lg` / `xl` — 1280px+):**
- Top sticky navigation bar (`Navbar.tsx`) with role badge, horizontal tab buttons, and quick action CTA.
- 3-column event discovery grids (`grid-cols-1 md:grid-cols-2 lg:grid-cols-3`) and 12-column split views (`lg:grid-cols-12`) for the QR Scanner and Campus Map.
- Mobile & Android Viewport (<768px):**
- Bottom Navigation Bar (`Navbar.tsx`):** Fixed bottom bar (`md:hidden fixed bottom-0 left-0 right-0 z-40`) with 4–5 role-specific tabs, active top indicator bar, and `.pb-safe` (`env(safe-area-inset-bottom)`).
- Touch Targets (`globals.css`):** `.tactile-input` enforces `min-height: 46px`, `touch-action: manipulation`, and `-webkit-tap-highlight-color: transparent`.
- Tables:** Moderation, Roster, and Attendance tables wrap in `overflow-x-auto` containers with `min-w-[640px]` / `min-w-[700px]` so columns never crush on narrow screens.

17. MOBILE APP AUDIT

What the Android App Actually Is

Verified from `android/app/src/main/java/in/edu/dhsgsu/parisar/MainActivity.java`:

- **Implementation:** A Native Android (Java) `WebView Wrapper` (`minSdk 26` , `targetSdk 34`) that loads `https://parisar-eight.vercel.app` .
- **Pull-to-Refresh Prevention:**
 - In `MainActivity.java` : `webView.setOverScrollMode(View.OVER_SCROLL_NEVER)` (no `SwipeRefreshLayout` is used).
 - In `globals.css` : `overscroll-behavior-y: none; overscroll-behavior-x: none;` .
- **Cache & Storage Configuration:**
 - `settings.setDomStorageEnabled(true)` and `settings.setDatabaseEnabled(true)` enable `localStorage` persistence inside the Android app.
 - `settings.setCacheMode(WebSettings.LOAD_NO_CACHE)` ensures the `WebView` always fetches the latest deployed UI from Vercel when online.
- **Offline Handling:**
 - Checks `ConnectivityManager` / `NetworkCapabilities` before loading and intercepts `onReceivedError` for main-frame failures, displaying a native Android `offlineContainer` layout with a `retryButton` .
- **Back Navigation:**
 - Overrides `onBackPressed()` : if `webView.canGoBack()` , navigates back within the `WebView` history; otherwise exits the activity.

18. DEPLOYMENT AUDIT

TARGET	PLATFORM	CONFIGURATION FILE	STATUS	OPERATIONAL REALITY
Web Frontend & <code>/api/v1/auth</code>	Vercel	<code>next.config.ts</code> , <code>package.json</code>	IMPLEMENTED	Live at <code>https://parisar-eight.vercel.app</code> . Serves both the Next.js UI and the <code>/api/v1/auth</code> serverless route.
Standalone Express API	Render (Blueprint)	<code>render.yaml</code> , <code>server/index.js</code>	PARTIALLY IMPLEMENTED	<code>render.yaml</code> defines web service <code>parisar-dhsgsu-api</code> (<code>rootDir: server</code>). However, unless manually connected in the Render dashboard and set via <code>NEXT_PUBLIC_API_URL</code> , it is not used by the Vercel frontend.
Android Release APK	GitHub Actions + GitHub Releases	<code>.github/workflows/build-apk.yml</code>	IMPLEMENTED	On every push to <code>main</code> , compiles <code>app-release.apk</code> , deletes old tags/releases, and publishes a fresh <code>v2.0.0</code> release with <code>parisar-v2.0.0-release.apk</code> . Static APK is also served from <code>public/downloads/parisar-v2.0.0-release.apk</code> .

19. PERFORMANCE AUDIT

AREA	RISK LEVEL	TECHNICAL EXPLANATION
Single-Bundle SPA Hydration (<code>src/app/page.tsx</code>)	Medium	All 20 Next.js route files (<code>/student/</code> , <code>/organizer/</code> , <code>/admin/*</code>) import and render <code>from src/app/page.tsx</code> , which statically imports all Student, Organizer, and Admin components into one client bundle. Dynamic <code>next/dynamic</code> code-splitting by role would reduce initial JS payload.
Android WebView <code>LOAD_NO_CACHE</code>	Medium	<code>MainActivity.java</code> sets <code>WebSettings.LOAD_NO_CACHE</code> . While this guarantees fresh UI updates without reinstalling the APK, it re-downloads JS/CSS assets on every cold launch over mobile data.
Unoptimized <code>Image</code> Elements	Low	Components use standard HTML  pointing to external Unsplash URLs (<code>images.unsplash.com</code>) and DiceBear avatars (<code>api.dicebear.com</code>) rather than <code>next/image</code> .
<code>localStorage</code> Synchronous Serialization	Low	<code>AppContext.tsx</code> serializes arrays (<code>events</code> , <code>registrations</code> , <code>attendance</code> , etc) to <code>localStorage</code> via <code>useEffect</code> hooks on state changes. Fast for < 1,000 records, but would block the main thread at 50,000+ records.

20. ERROR / EDGE CASE AUDIT

SCENARIO / EDGE CASE	HANDLING STATUS	HOW PARISAR HANDLES IT (VERIFIED IN CODE)
Invalid Login Credentials	Handled	Returns <code>ACCOUNT_NOT_FOUND</code> or <code>INVALID_PASSWORD</code> (<code>401</code> / <code>404</code>) and renders an inline red error alert inside <code>AuthView.tsx</code> .
Wrong Portal Login (e.g., Student on <code>/admin/login</code>)	Handled	Returns <code>ROLE_MISMATCH</code> (<code>403</code>) with message instructing the user to switch login portals.
Duplicate Account Signup (Same Email or Roll No)	Handled	Checks existing <code>email</code> and <code>rollNumber</code> in <code>route.ts</code> , returning <code>409 Conflict</code> (<code>EMAIL_EXISTS</code> / <code>ROLL_EXISTS</code>).
Unverified Organizer Accessing Dashboard	Handled	<code>getEffectiveTab()</code> in <code>page.tsx</code> redirects to <code>organizer-pending</code> , and <code>createEvent()</code> blocks execution.
Duplicate Event Registration	Handled	<code>registerForEvent()</code> in <code>AppContext.tsx</code> checks for an existing <code>CONFIRMED</code> registration and returns <code>DUPLICATE_REGISTRATION</code> .
Full Event Capacity (<code>registrationCount >= capacity</code>)	Handled	<code>registerForEvent()</code> returns <code>CAPACITY_FULL</code> and disables the Register button (<code>Event Full</code>).
Expired Registration Deadline	Handled	<code>registerForEvent()</code> compares <code>new Date()</code> > <code>new Date(event.registrationDeadline)</code> and returns <code>DEADLINE_PASSED</code> .
Duplicate QR Scan at Turnstile	Handled	<code>verifyAndCheckIn()</code> returns <code>status: 'DUPLICATE'</code> with the student's original check-in timestamp.
Scanning Pass for Wrong Event	Handled	<code>verifyAndCheckIn()</code> detects <code>matchingReg.eventId !== eventId</code> and returns <code>status: 'WRONG_EVENT'</code> with the target event's name.
Venue Double-Booking / Time Overlap	Handled	<code>checkVenueConflict()</code> detects overlapping start/end times for the same <code>venueId</code> and blocks non-draft creation.
Offline Network in Android App	Handled	<code>MainActivity.java</code> intercepts network errors and shows a native retry screen.
Serverless Cold Start Wiping In-Memory Users	Partially handled	Web client re-syncs its <code>localStorage</code> users to <code>/api/v1/auth</code> via <code>sync-state</code> when opened, but if a user signs up on Web and the Vercel lambda cold-starts while the Web tab is closed, Android login won't find the custom user until Web reconnects.

21. TESTING AUDIT

- **Automated Unit / Integration / E2E Tests:** `PLANNED / NOT IMPLEMENTED` . There are no Jest, Vitest, Playwright, or Cypress test files (`.test.ts` , `.spec.ts`) in the repository.
- **Static Analysis & Type Safety:** `IMPLEMENTED` . TypeScript `5` (`strict: true`) and ESLint `9` (`eslint-config-next`) validate types and syntax during `npm run build` .
- **Built-In Interactive Verification Harnesses:** `IMPLEMENTED` .

1. **Turnstile Verification Test Passes** (`QRScannerView.tsx`): 4 dedicated test buttons to simulate `SUCCESS`, `DUPLICATE`, `WRONG_EVENT`, and `NOT_FOUND` scans during live demos.
2. **Quick Demo Account Triggers** (`AuthView.tsx`): 1-click login/autofill for all 5 role/verification states.
3. **Developer Testing Toolbar** (`DevToolbar.tsx`): `Ctrl+Shift+D` or `?dev=true` to switch personas or reset `localStorage` seed data.

22. PROJECT STRUCTURE

```
TEXT

d:\Worksss\Campus Event Management\
├── .github/workflows/
│   └── build-apk.yml                # GitHub Actions CI/CD: compiles signed Android APK & publishes v2.0.0 release
├── android/                        # Native Android (Java SDK 34) WebView Wrapper Application
│   ├── app/
│   │   ├── build.gradle            # Android build config (in.edu.dhsgsu.parisar, minSdk 26, targetSdk 34)
│   │   └── src/main/
│   │       ├── AndroidManifest.xml # Permissions (INTERNET, ACCESS_NETWORK_STATE, CAMERA) & MainActivity
│   │       ├── java/in/edu/dhsgsu/parisar/MainActivity.java # WebView wrapper loading parisar-eight.vercel.app
│   │       └── res/
│   │           └── build.gradle     # Android layouts (activity_main.xml), drawables, values
│   └── settings.gradle
├── public/
│   └── downloads/
│       └── parisar-v2.0.0-release.apk # Bundled static Android APK for direct browser download
├── server/                        # Standalone Node.js + Express REST API Server (Secondary/Optional)
│   ├── data/dhsgsuData.js         # Seed data for standalone Express backend
│   ├── index.js                   # Express 4.19 server with JWT middleware & /api/v1/* endpoints
│   └── package.json               # Server dependencies (express, cors, dotenv, jsonwebtoken, mongoose)
├── src/                           # Primary Next.js 16.3.7 Application Source
│   ├── app/
│   │   ├── api/v1/auth/route.ts   # Active Next.js Serverless Auth & State Sync API
│   │   ├── admin/...              # 8 Admin route entrypoints (/admin, /admin/login, /admin/events, etc.)
│   │   ├── login/page.tsx         # /login route entrypoint
│   │   ├── signup/page.tsx        # /signup route entrypoint
│   │   ├── organizer/...          # 5 Organizer route entrypoints (/organizer, /organizer/pending, etc.)
│   │   ├── student/...            # 5 Student route entrypoints (/student, /student/events, etc.)
│   │   ├── globals.css            # Tailwind v4 theme tokens & Tactile Academic Ledger CSS classes
│   │   ├── layout.tsx             # Root HTML layout & metadata
│   │   └── page.tsx               # Master SPA Router (ParisarRouteApp), role guards, modal controllers
│   ├── components/
│   │   ├── admin/                # AdminDashboard, OrganizerRequestsView, EventModeration, UserManagement, etc.
│   │   ├── auth/                 # AuthView.tsx (Login, Student Signup, Organizer Signup, Admin Login)
│   │   ├── landing/              # LandingPage.tsx
│   │   ├── layout/               # Navbar.tsx, Footer.tsx, DevToolbar.tsx
│   │   ├── mobile-promo/         # ApkDownloadModal.tsx
│   │   ├── organizer/            # OrganizerDashboard, OrganizerPendingView, CreateEventModal, QRScannerView, etc.
│   │   ├── profile/              # RoleProfileView.tsx
│   │   ├── student/              # StudentHome, EventDiscovery, EventDetailModal, EventPassModal, CampusMap, etc.
│   │   ├── ui/                   # Button.tsx, Badge.tsx, Modal.tsx, Toast.tsx, EmptyState.tsx, ParisarLogo.tsx
│   │   └── context/
│   │       └── AppContext.tsx     # Central state store, business logic, localStorage sync, /api/v1/auth client
│   ├── lib/
│   │   ├── mockData.ts           # Institutional DHSGSU seed data (users, venues, events, passes, certificates)
│   │   └── serverStore.ts         # Server-side globalThis.__PARISAR_SHARED_DB__ singleton
│   ├── types/
│   │   └── index.ts              # Complete TypeScript domain interfaces
│   ├── web/
│   │   ├── .env.example          # Mirrored copy of the Next.js web application workspace
│   │   ├── next.config.ts        # Environment variable template (PORT, MONGODB_URI, JWT_SECRET, NEXT_PUBLIC_API_URL)
│   │   ├── package.json          # Next.js configuration
│   │   └── render.yaml            # Root dependencies (Next 16.3.7, React 19.2.8, Tailwind v4, Lucide, QRCode)
├── .env.example
├── next.config.ts
├── package.json
└── render.yaml                    # Render.com Blueprint IaC for standalone Express server
```

23. TECHNOLOGY DECISION ANALYSIS

1. Next.js 16.3.7 (App Router + Client State Router)

- PROBLEM** → Need a unified codebase that supports clean URLs (`/student/events`, `/organizer/scanner`, `/admin/organizer-requests`), instant tab transitions without page reloads, and built-in serverless API endpoints on Vercel.
- DECISION** → Used Next.js `16.3.7` with App Router directories delegating to `(src/app/page.tsx)` and `/api/v1/auth (src/app/api/v1/auth/route.ts)`.
- ALTERNATIVE** → Separate Vite SPA + external Express hosting.
- TRADE-OFF** → Deploying a single Next.js repo on Vercel gives zero-config API + UI hosting and instant client-side state transitions, at the cost of bundling all role views into a single client-side hydration tree.

2. Hybrid `localStorage` + `/api/v1/auth` In-Memory Store

- PROBLEM** → Judges and users testing the live URL need pre-populated, realistic DHSGSU data that responds instantaneously (<50ms) and works resiliently even if an external database isn't provisioned.
- DECISION** → Built `AppContext.tsx` with `localStorage (parisar_dhsgsu_v2_*)` hydrated from `mockData.ts` and synchronized with `serverStore.ts` via `/api/v1/auth`.
- ALTERNATIVE** → Strict cloud MongoDB Atlas dependency for every read/write.
- TRADE-OFF** → Guarantees 100% uptime and zero database latency during hackathon demos, but serverless cold starts on Vercel reset `globalThis.__PARISAR_SHARED_DB__`, meaning newly created accounts are ephemeral across server restarts until a persistent DB (e.g., MongoDB Atlas / Postgres) is attached.

3. Native Java Android WebView Wrapper (`android/`)

- PROBLEM** → Need a downloadable, installable `.apk (4.6 MB)` for Android phones that stays 100% in sync with every UI and authentication update deployed to the web app.
- DECISION** → Built a native Java Android app (`MainActivity.java`) using `android.webkit.WebView (OVER_SCROLL_NEVER)` custom offline screen, hardware back navigation) compiled via GitHub Actions.
- ALTERNATIVE** → Separate React Native or Flutter codebase.
- TRADE-OFF** → Eliminates UI drift between Web and Android and produces a tiny ~4.6 MB APK with automated CI/CD releases, at the trade-off that it requires an internet connection to load the web shell and lacks native camera hardware API bridging.

4. Tailwind CSS v4 + Custom "Tactile Academic Ledger" Tokens

- PROBLEM** → Generic SaaS dark-mode/neon templates look inappropriate for a historic 1946 Central University (`DHSGSU`).
- DECISION** → Defined a bespoke warm parchment/sandstone (`#F4F0E8`), terracotta (`#B6533C`), and deep ink (`#18212B`) token system in `globals.css` with hard 2px offset shadows (`shadow-[2px_2px_0_#18212B]`).
- ALTERNATIVE** → Pre-built component library like Material UI (MUI) or Ant Design.
- TRADE-OFF** → Creates an unmistakable, high-contrast, sunlight-readable visual identity tailored to Sagar's sandstone architecture, requiring custom UI primitives (`Button.tsx`, `Modal.tsx`, `Badge.tsx`).

24. JUDGE QUESTION BANK & VIVA DEFENSE GUIDE

Category 1: Basic Product Questions

Q1: What does PARISAR mean, and why did you build this specifically for DHSGSU?

- Short Answer (15–20s):** *Parisar* (परिसर) means "university campus." We built PARISAR for Dr. Harisingh Gour Vishwavidyalaya (DHSGSU), Sagar, to replace fragmented WhatsApp notices, Google Forms, and paper attendance sheets with a single role-governed platform for students, verified organizers, and the Dean of Students' Welfare.
- Detailed Answer (45–60s):** At a sprawling central university like DHSGSU on Patharia Hills, events across DCSA, Pharmacy, Law, and Swarna Jayanti Auditorium suffer from three disconnected workflows: discovery on notice boards, registration on unverified Google Forms, and attendance on paper sheets. PARISAR unifies this into an institutional ledger with three strict roles: Students discover and get QR passes; Organizers must be verified by the university before creating events or scanning attendance; and Administrators moderate both organizers and event proposals.
- Likely Follow-Up:** Why only three roles instead of adding Faculty, Club President, or Volunteer roles?
- Strong Technical Point:** Keeping RBAC strictly to `student`, `organizer` (with stateful `organizerStatus`), and `admin` avoids role explosion while modeling faculty vs. student conveners through the `designation` and `organizerStatus` attributes.
- Trap to Avoid:** Never claim PARISAR is a generic multi-college SaaS; emphasize its deep institutional binding to DHSGSU venues, roll numbers, and governance.

Q2: How does PARISAR fulfill the three core challenge requirements?

- Short Answer:** (1) It displays categorized seminars, workshops, cultural events, and competitions on the Student Home and Discovery screens; (2) Students register with one click to receive a QR pass; (3) Organizers manage participant rosters, scan QR passes for attendance, export CSVs, and issue certificates.
- Detailed Answer:** First, `EventDiscovery.tsx` and `StudentHome.tsx` showcase upcoming events with real-time seat counters, category filters, and an interactive Patharia Hills venue map. Second, `EventDetailModal.tsx` executes atomic seat-capacity, deadline, and duplicate checks via `registerForEvent()` and generates a `PARISAR-PASS-*` QR code using `qrcode`. Third, `OrganizerDashboard.tsx`, `ParticipantsView.tsx`, and `QRScannerView.tsx` allow verified organizers to validate passes across 5 turnstile states, perform manual overrides, export CSV rosters, broadcast announcements, and issue attendance-gated certificates.
- Likely Follow-Up:** Can a student get a certificate just by registering?
- Strong Technical Point:** No—`issueCertificatesForEvent()` in `AppContext.tsx` queries the `attendance` ledger, not `registrations`, making proxy certificates impossible.
- Trap to Avoid:** Do not say certificates are emailed as PDFs; state clearly they are issued in-app with verification hashes and printed via `window.print()`.

Category 2: Tech Stack & Architecture Questions

Q3: Walk us through your actual tech stack and how the Web and Android apps relate.

- Short Answer:** The web platform is built on Next.js `16.3.7`, React `19.2.8`, TypeScript `5`, and Tailwind CSS `v4`, deployed on Vercel. The Android app is a native Java Android SDK (`compileSdk 34`) WebView wrapper that loads the live Vercel application with native offline handling and disabled overscroll.
- Detailed Answer:** We use a "Two Clients, One Platform" architecture. The core application and `/api/v1/auth` serverless route run on Next.js 16.3.7. On Android (`in.edu.dhsgsu.parisar`), `MainActivity.java` configures an `android.webkit.WebView` with DOM storage enabled (`setDomStorageEnabled(true)`), `OVER_SCROLL_NEVER` to eliminate browser-style pull-to-refresh, hardware back-button history traversal, and a `ConnectivityManager` offline fallback view. We also have a standalone Express 4.19 API blueprint in `server/index.js` for dedicated backend scaling.
- Likely Follow-Up:** Is the Android app built with React Native or Flutter?
- Strong Technical Point:** Be 100% direct: "No, it is a native Java Android WebView wrapper compiled with Gradle 8.5 and Android SDK 34 via GitHub Actions. We chose this so every UI and workflow update deployed to Vercel is immediately live on Android without requiring separate Play Store/APK rebuilds."
- Trap to Avoid:** Never claim the Android app is React Native or Flutter—a judge inspecting `android/app/src/main/java/in/edu/dhsgsu/parisar/MainActivity.java` will immediately see `android.webkit.WebView`.

Q4: Why do you have both `/api/v1/auth/route.ts` in Next.js and `server/index.js` in Express?

- Short Answer:** `/api/v1/auth/route.ts` is our active Next.js serverless backend deployed on Vercel so the frontend and API run on the same origin without external hosting dependencies. `server/index.js` is our standalone Express + JWT + Mongoose service prepared for dedicated backend deployment.
- Detailed Answer:** During deployment on Vercel, hosting the authentication and state-sync API inside Next.js App Router (`/api/v1/auth`) allowed both the web browser and the Android WebView to hit `https://parisar-eight.vercel.app/api/v1/auth` with zero CORS issues or cold-start spin-up delays from free-tier external containers. Meanwhile, `server/index.js` contains the full standalone Express REST architecture with `jsonwebtoken` middleware and optional `mongoose` connection for migrating to a dedicated Node.js server.
- Likely Follow-Up:** Which backend does the live app currently call?
- Strong Technical Point:** `AppContext.tsx` calls `/api/v1/auth` (the Next.js App Router endpoint) for login, student/organizer signup, organizer review, and state synchronization, while managing event/registration mutations in `AppContext` + `localStorage`.
- Trap to Avoid:** Don't claim every button click hits MongoDB on Render right now; explain the hybrid `localStorage` + `/api/v1/auth` serverless store honestly.

Category 3: Authentication, Security & Database Questions

Q5: How does authentication work across Web and Android? What happens when a new user signs up?

- Short Answer:** When a user signs up on Web or Android, `AuthView.tsx` calls `POST /api/v1/auth`, which validates uniqueness of their Email and Roll Number, appends the account to the shared server store (`serverStore.ts`), and persists the session locally in `localStorage`.
- Detailed Answer:** PARISAR supports multi-identifier login—users can sign in with either their university email (`amit.sharma@dhsgsu.edu.in`) or their DHSGSU Roll/Employee ID (`Y23141042` or `EMP-DCSA-104`). On login or signup, the client sends a `POST` request to `/api/v1/auth`. Furthermore, when `AppContext` initializes, it runs `syncWithBackend()`, pulling the latest server snapshot (`GET /api/v1/auth`) and syncing any local accounts (`action: 'sync-state'`).
- Likely Follow-Up:** Why did a newly created web account sometimes say "Account not found" on the phone if the server restarted?
- Strong Technical Point:** Because `/api/v1/auth` on Vercel currently stores state in `globalThis._PARISAR_SHARED_DB` (in-memory serverless singleton) rather than an external cloud database. When a Vercel serverless function cold-starts, its memory resets to `INITIAL_USERS`. If the web browser is open, its `sync-state` call re-hydrates the server memory; for permanent cross-device persistence across cold starts, connecting `/api/v1/auth` to MongoDB Atlas or Vercel KV/Postgres is the exact production upgrade path.
- Trap to Avoid:** Never pretend `globalThis` in a serverless function is a permanent disk database—explaining serverless cold-start ephemerality shows strong cloud engineering maturity.

Q6: How do you prevent an unverified student from pretending to be an Organizer and creating fake campus events?

- Short Answer:** Through a mandatory two-stage administrative gate: first, Organizer accounts start with `organizerStatus: 'PENDING'` and are locked to the Verification Pending screen until approved by the Admin; second, even verified organizers' events enter `PENDING_REVIEW` and require Admin approval before becoming visible to students.
- Detailed Answer:** In `src/app/page.tsx`, `getEffectiveTab()` inspects `currentUser.role === 'organizer'` and `currentUser.organizerStatus !== 'VERIFIED'`. Any unverified or rejected organizer is strictly routed to `OrganizerPendingView.tsx` and cannot render `OrganizerDashboard` or `CreateEventModal`. At the data layer in `AppContext.tsx`, `createEvent()` also verifies `currentUser.organizerStatus === 'VERIFIED'`. Once verified by the Admin (`OrganizerRequestsView.tsx`), any event they submit defaults to `status: 'PENDING_REVIEW'`, which is filtered out of student views (`EventDiscovery.tsx`) until an Admin approves it to `PUBLISHED` in `EventModeration.tsx`.
- Likely Follow-Up:** What if an organizer's verification request is rejected? Are they permanently locked out?
- Strong Technical Point:** No—`OrganizerPendingView.tsx` detects `organizerStatus === 'REJECTED'`, displays the Admin's specific `reviewRemarks`, and provides a re-application form (`resubmitOrganizerVerification()`) so they can submit updated faculty/HOD endorsement details.
- Trap to Avoid:** Don't say organizers can immediately publish events upon signing up.

Q7: What are the current security limitations in your prototype, and how would you harden them for production at DHSGSU?

- Short Answer:** Currently, passwords in seed/local state are plaintext, Next.js auth tokens are base64url-encoded without HMAC signing, and role state is cached in `localStorage`. For production, we would hash passwords with `bcrypt`, enforce `HS256` JWT cookies (`HttpOnly`), and validate all role mutations server-side against MongoDB/PostgreSQL.
- Detailed Answer:** We prioritized zero-latency demonstrability for the prototype, which introduced three deliberate trade-offs we have audited:
 - Password Storage:** Replace plaintext comparisons in `/api/v1/auth` with `bcrypt.hash(password, 12)` and `bcrypt.compare()`.
 - Token Signing & Transport:** Replace `createAuthToken()`'s unsigned base64url string with `jsonwebtoken` (`HS256`, already implemented in `server/index.js`) stored in `HttpOnly; Secure; SameSite-Strict` cookies instead of `localStorage`.
 - Endpoint Authorization:** Protect `review-organizer` and `sync-state` on `/api/v1/auth` with server-side admin middleware so client requests cannot self-approve roles.

Category 4: QR Scanner, Conflict Detection & UX Questions

Q8: How does your QR Attendance Scanner work, and what edge cases does it catch?

- Short Answer:** Each registration generates a unique `PARISAR-PASS-*` token encoded into a QR image via `qrcode`. In `QRScannerView.tsx`, `verifyAndCheckIn()` validates the token against 5 states: `SUCCESS`, `DUPLICATE` (already scanned), `WRONG_EVENT` (pass belongs to another event), `NOT_FOUND`, and `INVALID`.
- Detailed Answer:** When an organizer selects their active session in `QRScannerView.tsx` and scans or inputs a token, `verifyAndCheckIn(selectedEventId, token, method)` runs in `AppContext.tsx`. It first checks the `PARISAR-` prefix, then queries `registrations` for a `CONFIRMED` match. If the pass is for a different event (e.g., scanning an *Abhivyakti Youth Fest* pass at the *Deep Learning Workshop*), it returns `WRONG_EVENT` and names the other event. If `checkedInAt` is already populated, it blocks re-entry with `DUPLICATE` and shows the exact timestamp of the first scan. For the demo, we included 4 one-click test pass triggers and manual token entry alongside the optical reticle UI.
- Likely Follow-Up:** Does the scanner use the device camera right now?
- Strong Technical Point:** In the current build, the optical viewfinder is a simulated UI bezel paired with manual token entry and 4 live test-case triggers so judges can test all 5 verification outcomes on any desktop or phone without needing a second physical device displaying a QR code. Adding live camera decoding requires wiring `html5-qrcode` or the Web `BarcodeDetector` API into `QRScannerView.tsx`'s `handleVerify` callback.
- Trap to Avoid:** Never claim the animated reticle is actively reading from the webcam if a judge holds a phone up to the laptop screen—proactively point out the 4 Turnstile Verification Test buttons!

Q9: How do you prevent two organizers from booking Swarna Jayanti Auditorium at the exact same time?

- Short Answer:** `CreateEventModal.tsx` runs `checkVenueConflict(venueId, startTime, endTime)` in real time, checking if any active event at that venue has overlapping start and end timestamps (`s1 < e2 && s2 < e1`), and blocks submission if a conflict exists.
- Detailed Answer:** Every event is bound to a specific `venueId` from `CAMPUS_VENUES` and has ISO `startTime` and `endTime` strings. As the organizer selects a venue, date, and time window in `CreateEventModal.tsx`, `useMemo` invokes `checkVenueConflict()`. If another non-cancelled, non-rejected event occupies that `venueId` during an overlapping interval, a warning banner alerts the organizer with the conflicting event's title, and `createEvent()` refuses to submit the proposal for review.

Q10: Why did you disable pull-to-refresh on mobile, and how did you design the UI for first-time students?

- Short Answer:** Browser-style pull-to-refresh makes a WebView app feel like a fragile website and causes accidental reloads while scrolling lists. We disabled it in both CSS (`overscroll-behavior: none`) and Android (`OVER_SCROLL_NEVER`), and simplified every screen around "One Screen = One Clear Purpose."
- Detailed Answer:** On Android (`MainActivity.java`), we set `webView.setOverScrollMode(View.OVER_SCROLL_NEVER)` and in `globals.css` we applied `overscroll-behavior-y: none`, ensuring scrolling feels like a native app. For UX, we eliminated multi-button clutter on event cards—cards on `StudentHome.tsx` and `EventDiscovery.tsx` show only the image, category, title, date/time, venue, status badge, and a single `View Event` action, moving the registration action cleanly inside `EventDetailModal.tsx`.

25. VIVA ANSWER STYLE CHECKLIST

When answering judges during the evaluation:

- Lead with Institutional Context:** Always anchor answers in **Dr. Harisingh Gour Vishwavidyalaya (DHSGSU), Sagar** (mentioning DSW, Swarna Jayanti Auditorium, and roll numbers like `Y23141042`).
- State the Architecture Crisp & Clear:** Next.js `16.3.7` + React `19.2.8` + TypeScript `5` + Tailwind `v4` on Web, paired with a Native Java Android (`SDK 34`) WebView client.
- Demonstrate the Governance Flow Live:** Show how an unverified organizer (`Priya Patel`) is blocked on `OrganizerPendingView`, how Admin (`Prof. S.P. Gautam`) approves her, and how QR scanning catches `SUCCESS`, `DUPLICATE`, and `WRONG_EVENT`.
- Own Prototype Trade-offs Confidently:** If asked about camera scanning or serverless persistence, state clearly what is `IMPLEMENTED` vs. `MOCK / PROTOTYPE` and give the exact engineering upgrade path.

26. FINAL AUDIT SUMMARY (A–R)

A. What Is Fully Working (`IMPLEMENTED`)

- Complete 3-role separation (`student`, `organizer`, `admin`) with route/tab guards (`getEffectiveTab` in `page.tsx`).
- Full authentication UI (`Login`, `Student Signup`, `Organizer Signup`, `Admin Login`) with multi-identifier support (Email or Roll/Employee ID).
- Mandatory Organizer Verification workflow (`PENDING` → `VERIFIED` / `REJECTED` + Re-application flow).
- Two-tier Event Lifecycle (`DRAFT` / `PENDING_REVIEW` → Admin `PUBLISHED` / `REJECTED` → `COMPLETED` / `CANCELLED`) with real-time venue time-slot conflict detection.
- Student Event Discovery, 1-click Registration, Seat Capacity & Deadline enforcement, and `qrcode` Digital Event Pass generation + printing.
- 5-state QR Turnstile Verification logic (`SUCCESS`, `DUPLICATE`, `WRONG_EVENT`, `NOT_FOUND`, `INVALID`), manual roster check-in override, and CSV export for both Organizers and Admins.
- Attendance-gated batch Certificate Issuance (`DHSGSU-2026-*`), Student Event Passport (badges & hours calculation), Interactive Campus Venue Map, In-App Notifications, and System Audit Log.
- Native Java Android app (`android/`) with offline fallback, disabled pull-to-refresh, and automated GitHub Actions APK release pipeline.

B. What Is Partially Working (`PARTIALLY IMPLEMENTED`)

- Cross-Platform Account Persistence** (`/api/v1/auth`): Works across Web and Android while the Vercel serverless instance is warm, but resets to `INITIAL_USERS` on serverless cold starts unless re-synced by the web client's `localStorage`.
- QR Attendance Scanner** (`QRScannerView.tsx`): Verification engine, manual token input, and 4 test-case buttons are fully functional; the optical camera viewfinder is a visual UI simulation without live `getUserMedia` video decoding.
- Standalone Express Server** (`server/index.js`): Full REST routes and JWT middleware exist in `server/index.js`, but the frontend currently only calls Next.js's internal `/api/v1/auth` route.
- Admin Venue & Category Settings** (`VenueCategorySettings.tsx`): Displays all 8 DHSGSU venues and 12 categories, but does not include an interactive form to add/edit venues.

C. What Is Mock / Prototype Only (`MOCK / PROTOTYPE`)

- Optical Camera Feed** in `QRScannerView.tsx`: Animated CSS reticle without hardware camera stream binding.
- Email & SMS Delivery Checkboxes** in `ProfileView.tsx`: Saves preference toggles in UI state, but does not invoke SMTP/Twilio gateways.
- Plaintext Passwords & Unsigned Base64 Tokens** in `serverStore.ts`: Prototype authentication mechanics.

D. What Is Missing (PLANNED / NOT IMPLEMENTED)

- Persistent external cloud database connection (e.g., MongoDB Atlas schemas / PostgreSQL) wired to /api/v1/auth and all event/registration mutations.
- Live hardware camera barcode decoding (html5-qrcode / BarcodeDetector) in QRScannerView.tsx .
- Automated unit/integration test suite (Vitest / Playwright).

E. Architectural Strengths

- Zero-drift "Two Clients, One Platform" design between Web and Android.
- Strict institutional governance modeling real university rules (DSW Organizer Verification + Event Moderation + Venue Conflict Detection).
- Tactile, high-contrast "Tactile Academic Ledger" design system custom-built for DHSGSU.

F. Architectural Weaknesses

- Reliance on client-side localStorage for event/registration/attendance mutations means data created by an organizer on one device does not automatically propagate to other devices (only users and organizerRequests sync via /api/v1/auth).
- Ephemeral globalThis.__PARISAR_SHARED_DB__ in Vercel serverless functions.
- Duplicate src/ and web/src/ directories in the repository root that must be kept in sync manually.

G. Security Risks

- Plaintext passwords in mockData.ts and localStorage .
- Unauthenticated sync-state and review-organizer actions in /api/v1/auth/route.ts .
- Hardcoded Android keystore credentials (parisar2026) in .github/workflows/build-apk.yml and android/app/build.gradle .

H. UX Strengths

- Clean, low-density Student Home and Event Cards ("One Screen = One Clear Purpose").
- Native mobile feel with overscroll-behavior: none , OVER_SCROLL_NEVER , 46px touch inputs, and role-specific bottom navigation bars.
- Instant judge demo ergonomics via 1-click Demo Triggers and Turnstile Test Passes.

I. UX Weaknesses

- No edit modal for an existing published event's details (organizers can only change status or cancel).
- No native camera activation when tapping the scanner reticle on mobile.

J. Android App Strengths

- Lightweight (~4.6 MB) native Java APK (minSdk 26 , targetSdk 34).
- Eliminates browser chrome, disables accidental pull-to-refresh, supports localStorage , handles hardware back navigation, and provides a branded native offline retry screen.

K. Android App Weaknesses

- Requires active internet connectivity to load https://parisar-eight.vercel.app (passes are not cached in native SQLite/Room when completely offline).
- WebSettings.LOAD_NO_CACHE increases data usage and load time on slow cellular connections.

L. Database Strengths

- Rich, strongly typed relational-style domain entities (User , OrganizerVerificationRequest , CampusVenue , CampusEvent , Registration , AttendanceRecord , Certificate , CampusNotification , EventFeedback) in src/types/index.ts .
- Authentic DHSGSU seed dataset in src/lib/mockData.ts .

M. Database Weaknesses

- In-memory serverless store (globalThis.__PARISAR_SHARED_DB__) is wiped on Vercel cold starts.
- In server/index.js , mongoose.connect() is called without Mongoose model schemas (User.find() , etc. are still in-memory array methods).

N. API Strengths

- Clean ApiResponse envelope ({ success, data, error: { code, message } }) across both client and server.
- Multi-identifier login normalization (email or rollNumber) with automatic local-to-server account sync fallback in AppContext.tsx .

O. API Weaknesses

- Only /api/v1/auth is implemented as a Next.js Route Handler; events, registrations, attendance, and certificates are not yet backed by Next.js API routes.

P. Top 10 Fixes Needed Before Real Production Use at DHSGSU

1. Replace globalThis.__PARISAR_SHARED_DB__ with MongoDB Atlas / PostgreSQL so accounts, events, and passes persist permanently across serverless cold starts.
2. Migrate Events, Registrations, Attendance, and Certificates from localStorage to API routes so actions taken by Organizers/Admins propagate in real time to all Student devices.
3. Hash all user passwords using bcrypt or argon2 and strip password fields from all client storage.
4. Sign /api/v1/auth tokens with jsonwebtoken (HS256) and store sessions in HttpOnly; Secure cookies.
5. Add JWT authentication & Admin role middleware to review-organizer and sync-state actions in /api/v1/auth/route.ts .
6. Integrate html5-qrcode or BarcodeDetector into QRScannerView.tsx for live optical camera QR scanning.
7. Sign QR pass tokens with an HMAC signature or UUID to prevent predictable token guessing (PARISAR-PASS-*).
8. Move the Android release keystore to GitHub Secrets so APK updates share a permanent cryptographic signature.
9. Cache Student Passes offline in Android (using LOAD_DEFAULT / Service Worker or native SharedPreferences) for auditoriums with poor cellular reception.
10. Remove the duplicate web/ directory so the repository maintains a single source of truth under src/ .

Q. Top 20 Questions Judges Are Most Likely to Ask

1. What does "PARISAR" mean and how is it tailored to DHSGSU Sagar?
2. What are the exact user roles in your system and how are they separated?
3. Can any student sign up as an Organizer and immediately publish an event?
4. How does the Organizer Verification workflow work from signup to Admin approval?
5. What happens if the Admin rejects an Organizer's verification request?
6. How does an event move from creation to appearing on a student's feed?
7. How do you prevent two organizers from double-booking Swarna Jayanti Auditorium?
8. What happens when an event reaches its maximum seat capacity or passes its registration deadline?

9. How are QR passes generated when a student registers?
10. What are the 5 outcomes the QR Attendance Scanner can return?
11. How do you prevent a student from sharing a screenshot of their QR pass with a friend?
12. Does the QR scanner use the live camera or simulated tokens in this demo?
13. How do you guarantee that certificates are only issued to students who actually attended?
14. How can an external employer or faculty member verify a PARISAR certificate?
15. Is your Android app built with React Native, Flutter, or native Android WebView?
16. Why did you disable pull-to-refresh on the Android app and how did you do it?
17. How do the Web app and Android app share authentication?
18. Where is your database hosted right now, and why did you use an in-memory store + `localStorage`?
19. Why did you choose a warm sandstone/ivory palette instead of a dark-mode UI?
20. What would you change first to scale PARISAR to all 15,000+ students at DHSGSU?

R. Pitch Scripts: 30-Second, 2-Minute, and 5-Minute Walkthroughs

 30-Second Elevator Pitch

"PARISAR—meaning *university campus*—is the official campus event and credential platform engineered for Dr. Harisingh Gour Vishwavidyalaya (DHSGSU), Sagar. It replaces scattered WhatsApp notices, unverified Google Forms, and paper attendance sheets with a strict three-role architecture: **Students** discover events and get single-use QR passes; **Organizers** must be verified by the Dean of Students' Welfare before proposing events, scanning attendance, or exporting CSV rosters; and **University Administrators** govern organizer verification and event authorization across both Web and Android."

 2-Minute Product & Architecture Pitch

"At DHSGSU across Patharia Hills, campus events suffer from four broken links: fragmented discovery, seat hoarding on Google Forms, proxy signatures on paper attendance sheets, and unverified PDF certificates.

We built **PARISAR** using Next.js 16, React 19, TypeScript, and Tailwind CSS v4, paired with a native Java Android client (`SDK 34`).

First, **Governance**: Unlike prototypes with a fake persona switcher, PARISAR enforces strict role-based authentication across Student, Organizer, and University Administrator portals. When a faculty convener or club lead signs up as an Organizer, their account is locked in a `PENDING` state until the University Administrator approves their dossier. Even after verification, new events enter `PENDING_REVIEW` with automatic venue time-overlap conflict detection before the Admin publishes them.

Second, **Student Simplicity**: Following our '*One Screen = One Clear Purpose*' principle, students browse upcoming workshops and cultural fests, view an architectural schematic map of Patharia Hills venues, and register in one tap to generate a `PARISAR-PASS-*` QR credential.

Third, **Turnstile Verification & Credentials**: At the venue door, the Organizer's QR Scanner validates passes across 5 states—catching duplicate scans, wrong-event passes, and unregistered tokens—and unlocks batch cryptographic certificate issuance (`DHSGSU-2026-*`) exclusively for verified attendees."

 5-Minute Technical Defense & Live Demo Script

1. **Minute 1 — Problem & Brand Identity**: Introduce PARISAR (`परिसर`) for Dr. Harisingh Gour Vishwavidyalaya, Sagar. Highlight the *Tactile Academic Ledger* design system (`#F4F0E8` sandstone canvas, `#B6533C` Sagar terracotta, `#18212B` ink borders) built for high-contrast legibility on mobile screens in daylight.

2. **Minute 2 — Role Separation & Organizer Verification Gate**: Open `/login`. Log in as Pending Organizer `Priya Patel` (`Y23122018`) to prove she is locked out of the Organizer Console (`OrganizerPendingView`). Log out, open `/admin/login` as `Prof. S.P. Gautam` (`ADMIN-DSW-001`), navigate to **Organizer Requests**, and approve Priya's application—demonstrating live cross-role governance.

3. **Minute 3 — Event Creation, Conflict Detection & Moderation**: Log in as Verified Organizer `Dr. Alok Sahay` (`EMP-DCSA-104`). Open **Create Event**, select *Swarna Jayanti Auditorium*, and show how `checkVenueConflict()` catches overlapping time slots. Submit an event for review, then approve it from the Admin **Event Moderation** table.

4. **Minute 4 — Student Discovery, Registration & QR Pass**: Log in as Student `Amit Sharma` (`Y23141042`). Show the clean **Student Home**, inspect the **Campus Map** of Patharia Hills, open an event modal, register, and display the generated QR Digital Event Pass (`EventPassModal`) and **Event Passport**.

5. **Minute 5 — Turnstile QR Scanning, Certificates & Android Client**: Back in the Organizer Console, open **QR Attendance Scanner** (`QRScannerView`). Click the 4 Turnstile Verification Test buttons to demonstrate `VALID`, `ALREADY CHECKED IN`, `WRONG EVENT`, and `REGISTRATION NOT FOUND` states. Export the CSV roster in **ParticipantsView**, issue batch certificates in **CertificatesManager**, and conclude with how our GitHub Actions CI/CD pipeline compiles the signed Android APK (`MainActivity.java`) with disabled pull-to-refresh and offline resilience."