KF04 project report

Group 12:
Jakob Melnyk
Niklas Hansen
Emil Juul Jacobsen
Filip Hjermind Jensen
Jens Dahl Møllerhøj

May 3, 2011

Indhold

1 Features

This chapter describes the features and functions, we have included in our Map of Denmark project, part 2, Spring 2011.

- Find shortest path

- Display path using blue highlighting

- Multiple pins

- Total distance

- Estimated travel time

- Bike or car route

- Remove a single pin by clicking

- Remove all pins by using GUI button

1.1 Find shortest route

Our map is able to calculate the shortest route between two points. This is done by clicking the map. Clicking the map places a pin at the clicked location. If the user clicks on another part of the map, our map will show the shortest route between those two locations, if possible.

1.2 Display path using blue highlighting

When the user has selected two or more locations, the map will show the shortest route highlighted in blue. The algorithm we use for finding this route is pretty fast, so a user will not feel annoyed by how long it takes.

1.3 Multiple pins

It is possible for a user to place multiple pins on the map. This is done in similarly to finding the shortest route between two points. When any number of pins are placed, the user can add additional ones. This will calculate the route between the latest two pins placed. The route shown will be from pin 1-¿2-¿3-¿4..

1.4 Total distance

Our Map of Denmark program calculates the total distance of the route found, a functionality that assists the end-user in planning their trip. This was relatively simple to implement, but adds a big functionality.

1.5 Estimated travel time

As with the total travel distance, our Map of Denmark calculates the estimated time it will take to travel the route found by our algorithm. This was relatively easy to calculate and is a huge benefit for the end user.

1.6 Bike or car route

It is possible for the user to choose between a car route and a bike route. The different options will make our algorithm consider what is possible to traverse for both cars and bikes. It will make sure not to show small paths for cars and not show highways for bikes.

1.7 Remove a single pin

To make it easier to use our Map of Denmark, we have it possible to remove a pin by clicking on the location it was placed. This makes it possible for the end user to clear up a tiny missclick without having to shut down the entire Map or clearing all the pins the user has placed.

1.8 Remove all pins

In addition to enabling the user to remove a single pin by clicking on it, we have also made it possible to remove all the pins currently placed. This can be done by either pressing the "c" key on the keyboard or by clicking the button on the graphical interface. This avoids the chore of clicking every single point in order to start a new route planning.

2 Implementation

This chapter describes our implementation of interesting methods and functions in our Map of Denmark project, part 2, Spring 2011.

2.1 Model

In order to implement the mentioned pathfinding the **Model** has been extended to include a list of **Edges**. These correspond to all the roads that are in the current route. Whenever it recieves a new request to find a path from one **Node** to another it uses the static method in the Dijkstra class and adds the result to the list. When **Control** needs to draw the route it uses a method that returns the entire route as Line objects relative to the view. This approach is identical to what we use when the **Control** requests all roads that should be drawn as the map for a given view.

We have also included some statistics of the current route. These are calculated by the **Model** since it's the object that primarliy handles the data. This information can be calculated in linear time relative to the length of the current route since the route is saved in memory when first found.

2.2 Dijkstra

1. Skrevet ud fra implementationen fra Algorithms men modificeret meget til vores benyttelse. IndexMinPQ er svagt modificeret fra Algorithms. 2. Beskrivelse generelt af Dijkstra. 2. Ændringer: KrakNode istedet for integers (dog bliver index stadig brugt i PQ), Statisk metode istedet for Objekt, Evaluator så man kan benytte forskellige prioriteringer, Tjek for ensrettet.

2.3 Control

A lot has changed in **Control** since our last version. We have changed a lot of methods to work as static methods in a seperate **Tools** class, so **Control** will feel less cluttered in this version. New logic has taken the place of the old logic however. Route calculation, pin placement, pin removal and route display all goes through **Control**.

When a user clicks on the map, **Control** uses our **Tools** class to convert the screen coordinates to UTM coordinates. It then stores these in a **List**. If the list holds two or more elements, it asks the **Model** to calculate the shortest path between the first and second element, the second and third element

and so on, if any additional elements exist beyond the first two. Every time Control calls it's internal repaint method, it clears all the pins currently in the View. It then recalculates the pin position(s) according to the new size and postion of the View.

When a user takes advantage of one of the options to clear all the pins currently on the Map of Denmark, Control empties the collection holding all the pin points, asks Model to clear the route and asks View to repaint.

If a user removes a single pin by clicking on the location of the pin, we run through our collection and remove one of the pins within a specific range of pixels. It then makes Model recalculate the route for all the pins. This is not an effective implementation - if there are a lot of pins, then removing one might make the recalculating take a while. We decided to use this implementation, for now at least, because we wanted a working functionality that we could later improve upon if nessecary.

2.4   Car/Bike routes

Another useful feature we have included is the ability to switch between multiple modes of pathfinding. We have named these two modes Car and Bike. In the Car mode the pathfinding will priorize lower travel times, since we believe this to be most important when driving. Additionally the Car mode will exclude small paths and pedestrian zones. The Bike mode prioritizes lower distances highest since intersections and speed-limits are of relatively low importance here. When using Bike mode the route will not include highways.

As described earlier these different ways of prioritizing the roads are achieved by using the Evalutator that is provided when asking the pathfinding method for a best path. We have written these two evaluators as static objects on the Evaluator class for easy use in the code, but the use of a seperate object for the evaluations open up for later variation with little impact on the original code.

2.5   View

When looking at the changes in View relatively little has happened since most of the new code is located "behind the curtain". The Canvas has been extended to allow adding and drawing of the route. This is however, as mentioned earlier, done in exactly the same way as with the roads in the map itself. The Canvas also includes some points that is positions where the

pins are placed. These are drawn on top of the map and (like the map) needs provided again if the map moves.

When looking at the menu to the left there are a few more options to the user. There is a new button to remove all pins from the map and two RadioButtons to toggle between Car mode and Bike mode in the pathfinding.

Beneath the tools for pathfinding there are displayed two pieces of information (and spare space for more). This information is changed by a simple public method in the View and the units will adjust will be adjusted accordingly.