

Big-O Notation

Recap

- We want to analyse the runtime and performance of our code
- Logarithmic, linear, quadratic, cubic and exponential times

Objectives

- To understand why algorithm analysis is important.
- To be able to use "Big-O" to describe execution time.
- To understand the "Big-O" execution time of common operations on Python lists and dictionaries.
- To understand how the implementation of Python data impacts algorithm analysis.
- To understand how to benchmark simple Python programs.

General Scope

- In general, we are interested in *the performance* of the programs that we write
 - That is, how many seconds/minutes/hours/days is the code going to run?
- This is very dependent on the computer we run the program on
 - Can we find something more independent of the actual computer?U

Finding the position of the smallest number in a list

Let's solve the following problem:

We want to find a certain element in a list and return it's position.

- Input: Given a list of numbers in ascending order.
- That is, write a function `find_element_in_a_list(data, element)` with the following behavior:

```
>>> find_element_in_a_list([1, 3, 5], 3)
1
>>> find_element_in_a_list([2 * x for x in range(1000)], 550)
275
```

Defining the data

In [1]:

```
1 data_list = list(range(1000))
2 element_to_find = 999
```

In [2]:

```
1 def find_element_in_a_list(data_list, element):
2     for idx, el in enumerate(data_list):
3         if el == element:
4             return idx
```

In [3]:

```
1 %time find_element_in_a_list(data_list, element_to_find)
```

CPU times: user 30 μ s, sys: 4 μ s, total: 34 μ s
Wall time: 35.8 μ s

Out[3]:

999

How much is a microsecond?

$$1 \mu s = 0.000001 s = \frac{\frac{1s}{1000}}{1000} = \frac{1s}{1000^2}$$

Big-O Notation

Describes the **the limiting behaviour of a function** (Wikipedia)

Big-O ignores everything except the **limiting** part of a piece of code. Examples from math:

$$f(x) = 2x \quad (x)$$
$$f(x) = x^{1000} + 1000000000 \quad (x^{1000})$$
$$f(x) = x^4 + \frac{x}{9} + 2005 * \frac{x^9}{1000} \quad (\frac{x^9}{1000} \approx x^9)$$

Big-O in code

- What is the running time of this?

```
statement 1
```

- 1 (constant!)
 - $O(1)$

- What is the running time of this?

```
if (cond):  
    block 1 #sequence of statements  
else:  
    block 2 #sequence of statements
```

- 1 (constant!)
 - $O(1)$

- What is the running time of this?

```
statement 1  
statement 2  
...  
statement n
```

total_time = statement 1 + statement 2 + ... + statement n

- 1 (constant!)
 - It does **not** depend on the input size. The amount of statements is constant
 - $O(1)$

- What is the running time of this?

```
for x in range(0, n):  
    block 1
```

- Linear
 - The runtime depends on exactly the input (once for each element)
 - $O(n)$

- What is the running time of this?

```
for x in range(0, n):  
    for y in range(0, n):  
        block 1
```

- Quadratic
 - Everytime we have one n we need to go through all other n
 - $O(n^2)$ or $(n * n)$

- What is the running time of this?

```
for x in range(0, n):  
    for y in range(0, m):  
        block 1
```

- Quadratic
 - But no longer only depending on n
 - $O(n * m)$

- Is the runtime complexity of `find_element_in_a_list` and `find_element_double_loop` different?

```
def find_element_in_a_list(data_list, element):  
    for idx, el in enumerate(data_list):  
        if el == element:  
            return idx  
  
def find_element_double_loop(data_list, element):  
    for idx, el in enumerate(data_list):  
        if el == element:  
            first_result_idx = idx  
            break  
    for idx, el in enumerate(data_list):  
        if el == element and idx == first_result_idx:  
            return idx, el
```

Why do we not say $O(2n)$?

- Because only n matters when the size grows very big in $2n$, the 2 does not matter anymore:
 - $10 \approx 20$
 - $1'000'000 \approx 2'000'000$

Let's say one elementary operation takes 10 nanoseconds, then we get

	n							
$t_{\mathcal{A}}(n)$	10	100	1000	10^4	10^5	10^6	10^7	10^8
$\log n$	33ns	66ns	$0.1\mu s$	$0.1\mu s$	$0.2\mu s$	$0.2\mu s$	$0.2\mu s$	$0.3\mu s$
\sqrt{n}	32ns	$0.1\mu s$	$0.3\mu s$	$1\mu s$	$3.1\mu s$	$10\mu s$	$31\mu s$	0.1ms
n	100ns	$1\mu s$	$10\mu s$	0.1ms	1ms	10ms	0.1s	1s
$n \log n$	$0.3\mu s$	$6.6\mu s$	0.1ms	1.3ms	16ms	0.2s	2.3s	27s
$n^{3/2}$	$0.3\mu s$	$10\mu s$	0.3ms	10ms	0.3s	10s	5.2m	2.7h
n^2	$1\mu s$	0.1ms	10ms	1s	1.7m	2.8h	11d	3.2y
n^3	$10\mu s$	10ms	10s	2.8h	115d	317y	$3.2\cdot 10^5y$	
1.1^n	26ns	0.1ms	$7.8\cdot 10^{25}y$					
2^n	$10\mu s$	$4.0\cdot 10^{14}y$						
$n!$	36ms	$3.0\cdot 10^{142}y$						
n^n	1.7m	$3.2\cdot 10^{184}y$						

Big-O as an approximation

Describes the **the limiting behaviour of a function** (Wikipedia)

Big-O ignores everything except the **limiting** part of a piece of code.

Can be used to know the complexity of your code **without running it!**

What is the worst-case runtime of this?

```
def find_element_in_a_list(data_list, element):
    for idx, el in enumerate(data_list):
        if el == element:
            return idx, el
```

How often do we iterate over the elements of the list in the worst case?

What is the worst-case runtime of this?

```
def find_element_double_loop(data_list, element):
    for idx, el in enumerate(data_list):
        if el == element:
            first_result_idx = idx
            break
    for idx, el in enumerate(data_list):
        if el == element and idx == first_result_idx:
            return idx, el
```

How often do we iterate over the elements of the list in the worst case?

How often do we iterate over the elements of the list in the worst case?

What is the worst-case runtime of this?

```
def find_element_nested_loop(data_list, element):
    for idx, el in enumerate(data_list):
        for idx2, el2 in enumerate(data_list):
            if el == el2 == element and idx == idx2:
                return idx, el
```

How often do we iterate over the elements of the list in the worst case?

What is the worst-case runtime of this?

```
def find_element_recursive(data_list, element):
    half_idx = len(data_list) // 2

    if element == data_list[half_idx]:
        return half_idx
    elif element < data_list[half_idx]:
        lower_half_list = list(data_list[:half_idx])
        return find_element_recursive(lower_half_list, element)
    elif element > data_list[half_idx]:
        upper_half_list = list(data_list[half_idx:])
        return find_element_recursive(upper_half_list, element)
```

How often do we iterate over the elements of the list in the worst case?

How to count and *not* count...

When asked 'count the number of occurrences of all words in a list'. Assuming we have a list of words in `words` , here are two solutions:

In [4]:

```
1 words = ['seldom', 'heard', 'him', 'mention', 'her', 'under', 'any',
2          'other', 'name', 'In', 'his', 'eyes', 'she', 'eclipses',
3          'and', 'predominates', 'the', 'whole', 'of', 'her', 'sex',
4          'It', 'was', 'not', 'that', 'he', 'felt', 'any', 'emotion',
5          'akin', 'to', 'love', 'for', 'Irene', 'Adler', 'All',
6          'emotions', 'and', 'that', 'one', 'particularly', 'were',
7          'abhorrent', 'to', 'his', 'cold', 'precise', 'but',
8          'admirably', 'balanced', 'mind', 'He', 'was', 'I', 'take',
9          'it', 'the', 'most', 'perfect', 'reasoning', 'and',
10         'observing', 'machine', 'that', 'the', 'world', 'has',
11         'seen', 'but', 'as', 'a', 'lover', 'he', 'would', 'have',
12         'placed', 'himself', 'in', 'a', 'false', 'position', 'He',
13         'never', 'spoke', 'of', 'the', 'softer', 'passions', 'save',
14         'with', 'a', 'gibe', 'and', 'a', 'sneer']
```

How to count and *not* count...

When asked 'count the number of occurrences of all words in a list'. Assuming we have a list of words in `words` , here are two solutions:

In []:

```
1 word_counts = {}
2 for word in words:
3     word_counts.setdefault(word, 0)
4     word_counts[word] += 1
5 print(word_counts)
```

In []:

```
1 word_counts = {}
2 for word in words:
3     counts = words.count(word)
4     word_counts[word] = counts
5 print(word_counts)
```

- What is the running time complexity of each solution?
- Which one is thus preferable?

