VT-SBC-RK3568-NXP24-ARK-GEN2

Table of Content

Revisioc History

Rev.Code	Date	By	Check	Description
V1.0	2022-07-27	HYR		Initial Version

PWB1
YYBAGG20R2

Title: 01.COVER	Vantron	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.9, 3rd Wuke East Street, Wuhou District ,ChengDu , China 86-28-8512-3930	
Size: A3	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 1 of 50		

VT-SBC-RK3568-ARK_
Operating: -10-60℃&5-90%RH
Stotrage:-30-80℃&5-90%RH

: PCBA : IC : Connector



Title: 02.Block Diagram		ChengDu Vantron Technology.LTD 6th Floor, 1st Building,No.5, 3rd Wuhui East Street, Wuhou District ,ChengDu , China 86-28-8512-3930	
Size: A2	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 2 of 50		

VT-SBC-RK3568-ARK_



Title: 03.Power Tree	Vantron	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 3 of 50		

Power Sequence



Power description

Power Supply	PMIC Channel	Supply Limit	Power Name	Time Slot	Default Voltage	Default ON/OFF	Work Voltage	Peak Current	Sleep Current
+5V	RK809_BUCK1	2.5A	VDD_LOGIC	Slot:1	0.9V	ON	0.9V	TBD	TBD
+5V	RK809_BUCK2	2.5A	VDD_GPU	Slot:2	0.9V	ON	DVFS	TBD	TBD
+5V	RK809_BUCK3	1.5A	VCC_DDR	Slot:3	ADJ FB=0.8V	ON	1.1V (DDR4X)	TBD	TBD
+5V	RK809_BUCK4	1.5A	VDD_NPU	N/A	0V	OFF	DVFS	TBD	TBD
+5V	RK809_LDO1	0.4A	VDDA0V9_IMAGE	N/A	0V	OFF	0.9V	TBD	TBD
	RK809_LDO2	0.4A	VDDA_0V9	Slot:1	0.9V	ON	0.9V	TBD	TBD
	RK809_LDO3	0.1A	VDDA0V9_PMU	Slot:1	0.9V	ON	0.9V	TBD	TBD
+5V	RK809_LDO4	0.4A	VCCIO_ACODEC	N/A	0V	OFF	3.3V	TBD	TBD
	RK809_LDO5	0.4A	VCCIO_SD	Slot:4	3.3V	ON	3.3V or 1.8V (SD2.0=3.3V,SD3.0=1.8V)	TBD	TBD
	RK809_LDO6	0.4A	VCC3V3_PMU	Slot:2	3.3V	ON	3.3V	TBD	TBD
+5V	RK809_LDO7	0.4A	VCCA_1V8	Slot:2	1.8V	ON	1.8V	TBD	TBD
	RK809_LDO8	0.4A	VCCA1V8_PMU	Slot:2	1.8V	ON	1.8V	TBD	TBD
	RK809_LDO9	0.4A	VCCA1V8_IMAGE	N/A	0V	OFF	1.8V	TBD	TBD
+5V	RK809_SW2	2.1A	VCC_3V3_M.2	Slot:4	3.3V	ON	3.3V		
+5V	RK809_SW1 90mohm	2.1A	VCC_3V3	Slot:4	3.3V	ON	3.3V	TBD	TBD
	RK809_BUCK5	2.5A	VCC_1V8	Slot:2	1.8V	ON	1.8V	TBD	TBD
	RK809_RESETn			Slot:4+5					
+24V	EXT BUCK	3.0A	+12V	Slot:0	12V	ON	12V	TBD	TBD
+24V	EXT BUCK	3.0A	+5V	Slot:0	5.0V	ON	5.0V	TBD	TBD
+5V	EXT BUCK	6.0A	VDD_CPU	Slot:2A	1.025V	ON	DVFS	TBD	TBD

Title: 04.Power Sequence	Vantron	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930
Size: A3	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2	Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 4 of 50	

IO Power Domain Map

If IO domain power voltage is adjusted, the software DTS configuration must be updated synchronously, otherwise the IO may be damaged!

IO Domain	Pin Num	Support IO Voltage		Notes	Default IO Domain Voltage		
		3.3V	1.8V		Supply Power Net Name	Power Source	Voltage
PMUIO0 (PMUPLL_AVDD_1V8)	Pin Y21	✗	✓	PMUIO0 are fixed 1.8V level mode, which cannot be configured.	VCCA1V8_PMU	VCCA1V8_PMU	1.8V
PMUIO1	Pin Y20	✓	✗	PMUIO1 are fixed 3.3V level mode, which cannot be configured.	VCC3V3_PMU	VCC3V3_PMU	3.3V
PMUIO2	Pin W19	✓	✓	PMUIO2 supports 1.8V or 3.3V level mode Support configurable but require that their hardware power supply voltages must be consistent with the software configuration correspondingly.[2]	VCC3V3_PMU	VCC3V3_PMU	3.3V
VCCIO1	Pin H17	✓	✓	VCCIO1 supports 1.8V or 3.3V level mode Support configurable but require that their hardware power supply voltages must be consistent with the software configuration correspondingly.[2]	VCCIO_ACODEC	VCCIO_ACODEC	3.3V
VCCIO2	Pin H18	✓	✓	VCCIO2 supports 1.8V or 3.3V level mode Default is configured by hardware,namely PIN "FLASH_VOL_SEL" state determines which mode to work in.[1][2]	VCCIO_FLASH	VCC_1V8	1.8V
VCCIO3	Pin L22	✓	✓	VCCIO3 supports 1.8V or 3.3V level mode Support configurable but require that their hardware power supply voltages must be consistent with the software configuration correspondingly.[2][3]	VCCIO_SD	VCCIO_SD	3.3V
VCCIO4	Pin J21	✓	✓	VCCIO4 supports 1.8V or 3.3V level mode Support configurable but require that their hardware power supply voltages must be consistent with the software configuration correspondingly.[2]	VCCIO4	VCCIO_SD	3.3V
VCCIO5	Pin V10 Pin V11	✓	✓	VCCIO5 supports 1.8V or 3.3V level mode Support configurable but require that their hardware power supply voltages must be consistent with the software configuration correspondingly.[2]	VCC_3V3	VCC_3V3	3.3V
VCCIO6	Pin R9 Pin U9	✓	✓	VCCIO6 supports 1.8V or 3.3V level mode Support configurable but require that their hardware power supply voltages must be consistent with the software configuration correspondingly.[2]	VCCIO6	VCC_3V3	3.3V
VCCIO7	Pin V12	✓	✓	VCCIO7 supports 1.8V or 3.3V level mode Support configurable but require that their hardware power supply voltages must be consistent with the software configuration correspondingly.[2]	VCCIO7	VCC_1V8	1.8V

*For example, **the VCCIO4 hardware has been modified to 3.3V power supply, and the corresponding DTS must be modified to 3.3V configuration, otherwise the IO of VCCIO4 will be damaged.***

If a board needs to be compatible with two voltage choices, recommended to enable BOM ID

Notes

[1]:When VCCIO2 voltage is connected to 1.8V, FLASH_VOL_SEL must be high
When VCCIO2 voltage is connected to 3.3V, FLASH_VOL_SEL must be low
If VCCIO2 power supply voltage and FLASH_VOL_SEL fails to meet the above relationship, its function will be abnormally(for example, it cannot be started normally) or IO will be damaged.

[2]:When the IO domain power supply voltage is 1.8V, the IO domain voltage configuration in DTS must be set to 1.8V mode.
If it is misconfigured to 3.3V mode, the IO function of this power domain will be abnormally;
When the IO domain power supply voltage is 3.3V, the IO domain voltage configuration in DTS must be set to 3.3V mode.
If it is misconfigured to 1.8V mode, the IO in this power domain will be in overvoltage state, and the IO will be damaged after long-term operation.

[3]:When VCCIO3 IO domain is assigned as SD card function,:
If SD3.0 mode is to be supported, VCCIO3 power supply voltage must be support configurable, 3.3V in SD2.0 mode and 1.8V in SD3.0 mode.
If only SD2.0 mode is supported (SD3.0 card only works in SD2.0 mode), VCCIO3 only needs fixed power supply of 3.3V.
When VCCIO3 IO domain is assigned as other function,:
Such as uart5 and uart6, then note [2] should be followed

24V DCIN



24V DC to 12V DC



24V DC to 5V DC



24V DC to 3.3V DC



LDO



Title: 06.Power_DC IN	Vantron	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.5, 3rd Wuke East Street, Wuhou District ,ChengDu , China 86-28-6512-3930	
Size: C	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 6 of 50		


I2C0_SCL_PMIC [8,12]
I2C0_SDA_PMIC [8,12]
PMIC_INT_L [12]
PMIC_SLEEP_H [8,12]
RESETn [12,38]
RK809_PWRON [38]
I2S1_MCLK_M0_RK809 [19]
I2S1_SCLK_TX_M0_RK809 [19]
I2S1_LRCK_TX_M0_RK809 [19]
I2S1_SDO0_M0_RK809 [19]
I2S1_SDI0_M0/PDM_SDI0_M0_RK809 [19]
PDM_CLK0_M0_RK809 [19]
PMIC_32KOUT_WIFI [32]
HPL_OUT [40]
HP_SNS [40]
HPR_OUT [40]
MIC1_INN [40]
MIC1_INP [40]
OUT
VDD
FB
100R
RK3568
PMIC RK809 DCDC
VDD_LOGIC
VDD_GPU
VDD_NPU
VCC_DDR
U17A
RK809-5
VCC1
VCC2
VCC3
VCC4
BUCK1
BUCK2
BUCK3
BUCK4
SW1
SW2
SW3
SW4
FB1
FB2
FB3
FB4
2.5A
1.5A
0.5-2.4V
0.5-3.4V
FB3=0.8V
L26
L25
L18
L20
0.47uH/0.032R/4.1A
ON 0.9V
OFF 0.9V
Feedback from RK3566
VDD Pin
BUCK1/BUCK2
DDR4 1.2V 62K 1%
LPDDR4/4x 1.1V 47K 1%
DDR3 1.53V 110K 1%
DDR3L 1.35V 82K 1%
LPDDR3 1.2V 62K 1%
Default:1.1V
PMIC RK809 LDO
U17B
RK809-5
400mA LDO: 400mA@Vin>3V
200mA@Vin>2V
Default ON/OFF
LDO1 400mA
LDO2 400mA
Low noise LDO3 100mA
Codec vddio LDO4 400mA
LDO5 400mA
LDO6 400mA
LDO7 400mA
LDO8 400mA
LDO9 400mA
2.1A SWOUT2
2.1A SWOUT1
BUCK5 1.5V-3.6V 2.5A
VCC8\9: 2.7V-5.5V
VDDA0V9_IMAGE
VDDA_0V9
VDDA0V9_PMU
VCCIO_ACODEC
VCCIO_SD
VCC3V3_PMU
VCCA_1V8
VCCA1V8_PMU
VCCA1V8_IMAGE
VCC_1V8
USB_AVDD_0V9
USB_AVDD_1V8
MIPI_AVDD_0V9
MIPI_AVDD_1V8
PMIC RK809 Managerment
U17C
RK809-5
VREF
GNDREF
ePAD
XIN
XOUT
SDA
SCL
INT
SLEEP
CLK32K
RESETB
VCC_RTC
BATDIV
SNSP
SNSN
EXT_EN
VDC
PWRON
Gas Gauge
X2
32.768KHz
RK809_VREF
RK809_VDC
RK809_PWRON
SDA_809
SCL_809
PMIC_CLK32KOUT
1.2V
PMIC RK809 CODEC
U17D
RK809-5
VCC_SPK_HP
CPn
CPp
VCC_CPVDD
VCC_CPVSS
VCC_1P8D
VCC_1P8A
MCLK
BCLK
LRCLK
SDI
SDO/PDMDATA
PDMCLK
HPL_OUT
HP_SNS
HPR_OUT
SPK_OUTn
SPK_OUTp
MIC1p MIC_L
MIC1n MIC_R
SPKN_OUT
SPKP_OUT
TSPNT
TS3
TS4
180R
MIC1_INP
MIC1_INN
Note:
If RK809-5 codec is not used,
then Pin 14,15,16,17,19,40 Tie VSS
Pin 18,36,37,38,35,39,41,34,32,43,42
Leave floating
Title
07.Power_PMIC
Vantron
ChengDu Vantron Technology,LTD
6th Floor, 1st Building,No.9,
3rd WuKe East Street,
WuHou District ,ChengDu , China
86-28-8512-3930
Size A3
Document Number 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2
Rev <2.0>
Date: Monday, April 17, 2023
Sheet 7 of 50
Vantron CONFIDENTIAL

I2C0_SCL_PMIC [7,12]
I2C0_SDA_PMIC [7,12]
PMIC_SLEEP_H [7,12]
VDD_CPU_COM [10]

VDD_CPU



Title: 08.Power_VDD_CPU	Vantron	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 8 of 50		

FLASH_VOL_SEL [12]

Flash Power Manage

	VCCIO2 domain voltage: Recommend voltage value (VCCIO_FLASH)	FLASH_VOL_SEL state decided to VCCIO2 domain IO driven by default
eMMC	1.8V	FLASH_VOL_SEL --> Logic=H
Nand flash	Default 3.3V, Optional 1.8V	FLASH_VOL_SEL --> Logic=L(Default)
SPI flash	Default 1.8V, Optional 3.3V	FLASH_VOL_SEL --> Logic=H(Default)

Note:

According to the actual choice of mounted
Cannot be mounted at the same time





Note:
FLASH_VOL_SEL state decided
to VCCIO2 domain IO driven by default
Logic=L: 3.3V IO driven
Logic=H: 1.8V IO driven

When VCCIO2 voltage is connected to 1.8V, FLASH_VOL_SEL must be high
When VCCIO2 voltage is connected to 3.3V, FLASH_VOL_SEL must be low
If VCCIO2 power supply voltage and FLASH_VOL_SEL fails to meet the above relationship, its function will be abnormally(for example, it cannot be started normally) or IO will be damaged.

Title: 09.Power_Flash Power Manage	Vantron	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 9 of 50		

RK3568_ABCDE (Power&Gnd)











Title	10.RK3568_Power/GND	Vantron	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930
Size A4	Document Number 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev <2.0>
Date: Monday, April 17, 2023	Sheet 10 of 50		

RK3568_F (DDR PHY)

LPDDR4/4x DQ



LPDDR4/4x AC





Title	11.RK3568_DDR PHY	Vantron
Size	Document Number	Rev
A2	640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2	<2.0>
Date:	Monday, April 17, 2023	Sheet 11 of 50

ChengDu Vantron Technology.LTD
6th Floor, 1st Building,No.5,
3rd Wuke East Street,
Wuhou District ,ChengDu , China
86-28-8512-3930

RK3568_G(OSC/PLL/PMUIO1/2)

Note:
Adjusted the load capacitance according to the crystal specification.











Note:
If PMUIO2 domain power voltage is adjusted, the software DTS configuration must be updated synchronously, otherwise the IO may be damaged!

If the PMUIO2 hardware has been modified to 1.8V power supply, and the corresponding DTS must be modified to 1.8V configuration, otherwise the IO function of PMUIO2 will be abnormally.

The PMUIO2 hardware has been modified to 3.3V power supply, if the software DTS configuration is still 1.8V configuration, the IO of PMUIO2 will be damaged!

Note:
Caps of between dashed green lines and U1000 should be placed under the U1000 package.
Other caps should be placed close to the U1000 package

Title: 12.RK3568_OSC/PLL/PMUIO			
Size: A3	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023		Sheet 12 of 50	

Vantron
ChengDu Vantron Technology.,LTD
6th Floor, 1st Building,No.9,
3rd WuKe East Street,
WuHou District ,ChengDu , China
86-28-8512-3930

RK3568_I(VCCIO2 Domain)

U23I

VCCIO2 Domain

Operating Voltage=1.8V/3.3V

EMMC_D0	/ FLASH_D0	/ GPIO1_B4_u	A24	eMMC_D0/FLASH_D0 [21]
EMMC_D1	/ FLASH_D1	/ GPIO1_B5_u	C21	eMMC_D1/FLASH_D1 [21]
EMMC_D2	/ FLASH_D2	/ GPIO1_B6_u	B24	eMMC_D2/FLASH_D2 [21]
EMMC_D3	/ FLASH_D3	/ GPIO1_B7_u	D21	eMMC_D3/FLASH_D3 [21]
EMMC_D4	/ FLASH_D4	/ GPIO1_C0_u	A25	eMMC_D4/FLASH_D4 [21]
EMMC_D5	/ FLASH_D5	/ GPIO1_C1_u	E21	eMMC_D5/FLASH_D5 [21]
EMMC_D6	/ FLASH_D6	/ GPIO1_C2_u	E22	eMMC_D6/FLASH_D6 [21]
EMMC_D7	/ FLASH_D7	/ GPIO1_C3_u	B25	eMMC_D7/FLASH_D7 [21]
EMMC_CMD	/ FLASH_WRn	/ GPIO1_C4_u	B22	eMMC_CMD/FLASH_WRn [21]
EMMC_CLKOUT	/ FLASH_DQS	/ GPIO1_C5_d	A23	eMMC_CLKOUT/FLASH_DQS_SOC — R130 22R/1%/0402 — eMMC_CLKOUT/FLASH_DQS [21]
EMMC_DATA_STROBE	/ FSPI_CS1n / FLASH_CLE	/ GPIO1_C6_d	A26	eMMC_DATA_STROBE/FLASH_CLE [21]
EMMC_RSTn	/ FSPI_D2 / FLASH_WPn	/ GPIO1_C7_d	F20	eMMC_RSTn/FSPI_D2/FLASH_WPn [21]
	FSPI_CLK / FLASH_ALE	/ GPIO1_D0_d	A22	
	FSPI_D0 / FLASH_RDY	/ GPIO1_D1_u	C24	AUDIO_MUTE [37]
	FSPI_D1 / FLASH_RDn	/ GPIO1_D2_u	D23	PRTPWR5 [35]
	FSPI_CS0n / FLASH_CS0n	/ GPIO1_D3_u	C23	PRTPWR6 [35]
	FSPI_D3 / FLASH_CS1n	/ GPIO1_D4_u	A27	PRTPWR7 [35]

Default is determined by Pin
FLASH_VOL_SEL/GPIO0_A7_u:
L:VCCIO2 must supply 3.3V
H:VCCIO2 must supply 1.8V

VCCIO2

RK3568
VT_BGA_19X19_P65MMSP_636P_H1P68MM

VCCIO_FLASH — H18 — C430 0.1uF/16V

Note:

"FLASH_VOL_SEL" status and VCCIO_FLASH power supply voltage must match otherwise the IO function of VCCIO2 will be abnormally or the IO of VCCIO2 will be damaged!

When VCCIO2 voltage is connected to 1.8V, FLASH_VOL_SEL must be high
When VCCIO2 voltage is connected to 3.3V, FLASH_VOL_SEL must be low
If VCCIO2 power supply voltage and FLASH_VOL_SEL fails to meet the above relationship, its function will be abnormally(for example, it cannot be started normally) or IO will be damaged.

eMMC_D0/FLASH_D0 — 1 — SW4 — 2 — K2-1822SN — OPT

Note:

For eMMC or Nand Flash:
If eMMC_D0/FLASH_D0=0V at after power on and reset, then system will enter into Maskrom mode.

Layout note:

Test point must be placed on the line, and no branch can be added

RK3568_J(VCCIO3 Domain)

U23J

VCCIO3 Domain

Operating Voltage=1.8V/3.3V

SDMMC0_D0	/ UART2_TX_M1 / UART6_TX_M1	/ PWM8_M1 / GPIO1_D5_u	J25	SDMMC0_DATA0	SDMMC0_DATA0 [30]
SDMMC0_D1	/ UART2_RX_M1 / UART6_RX_M1	/ PWM9_M1 / GPIO1_D6_u	J24	SDMMC0_DATA1	SDMMC0_DATA1 [30]
SDMMC0_D2	/ ARMJTAG_TCK / UART5_CTSn_M0	/ GPIO1_D7_u	H26	SDMMC0_DATA2	SDMMC0_DATA2 [30]
SDMMC0_D3	/ ARMJTAG_TMS / UART5_RTSn_M0	/ GPIO2_A0_u	J23	SDMMC0_DATA3	SDMMC0_DATA3 [30]
SDMMC0_CMD	/ PWM10_M1 / UART5_RX_M0	/ CAN0_TX_M1 / GPIO2_A1_u	H27	SDMMC0_CMD	SDMMC0_CMD [30]
SDMMC0_CLK	/ TEST_CLKOUT / UART5_TX_M0	/ CAN0_RX_M1 / GPIO2_A2_d	H28	SDMMC0_CLK	SDMMC0_CLK [30]

VCCIO3

RK3568
VT_BGA_19X19_P65MMSP_636P_H1P68MM

VCCIO_SD — L22 — C416 0.1uF/16V

Note:

If VCCIO3 domain power voltage is adjusted, the software DTS configuration must be updated synchronously, otherwise the IO may be damaged!

If the VCCIO3 hardware has been modified to 1.8V power supply, and the corresponding DTS must be modified to 1.8V configuration, otherwise the IO function of VCCIO3 will be abnormally.

The VCCIO3 hardware has been modified to 3.3V power supply, if the software DTS configuration is still 1.8V configuration, the IO of VCCIO3 will be damaged!

If a board needs to be compatible with two voltage choices,
recommended to enable BOM_ID

Title	13.RK3568_Flash/SD Controller	Vantron	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930
Size	A3	Document Number	640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2
Rev	<2.0>		
Date:	Monday, April 17, 2023	Sheet	13 of 50

RK3568_U(USB3.0/SATA/QSGMII/PCIe2.0 x1)



Note:
In case of multiplexing,
impedance control:
Diff 90 Ohm ±10%

Note:
Caps of between dashed green lines and U1000
should be placed under the U1000 package.
Other caps should be placed close to the U1000 package

RK3568_V(USB2.0 HOST)



RK3568_W(PCIe3.0 x2)



Title: 14.RK3568_USB/PCIe/SATA PHY	Vantron	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size: A3	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet: 14 of 50		

RK3568_K(VCCIO4 Domain)

Note: *If VCCIO4 domain power voltage is adjusted, the software DTS configuration must be updated synchronously, otherwise the IO may be damaged!*
If the VCCIO4 hardware has been modified to 1.8V power supply, and the corresponding DTS must be modified to 1.8V configuration, otherwise the IO function of VCCIO4 will be abnormally.
The VCCIO4 hardware has been modified to 3.3V power supply, if the software DTS configuration is still 1.8V configuration, the IO of VCCIO4 will be damaged!

U23K

VCCIO4 Domain
Operating Voltage=1.8V/3.3V

SDMMC1_D0	GMAC0_RXD2	UART6_RX_M0		GPIO2_A3_u
SDMMC1_D1	GMAC0_RXD3	UART6_TX_M0		GPIO2_A4_u
SDMMC1_D2	GMAC0_RXCLK	UART7_RX_M0		GPIO2_A5_u
SDMMC1_D3	GMAC0_TXD2	UART7_TX_M0		GPIO2_A6_u
SDMMC1_CMD	GMAC0_TXD3	UART9_RX_M0		GPIO2_A7_u
SDMMC1_CLK	GMAC0_TXCLK	UART9_TX_M0		GPIO2_B0_d
SDMMC1_PWREN	I2C4_SDA_M1	UART8_RTSn_M0	CAN2_RX_M1	GPIO2_B1_d
SDMMC1_DET	I2C4_SCL_M1	UART8_CTSn_M0	CAN2_TX_M1	GPIO2_B2_u
	GMAC0_TXD0	UART1_RX_M0		GPIO2_B3_u
	GMAC0_TXD1	UART1_TX_M0		GPIO2_B4_u
	GMAC0_TXEN	UART1_RTSn_M0	SPI1_CLK_M0	GPIO2_B5_u
	GMAC0_RXD0	UART1_CTSn_M0	SPI1_MISO_M0	GPIO2_B6_u
I2S2_SCLK_RX_M0	GMAC0_RXD1	UART6_RTSn_M0	SPI1_MOSI_M0	GPIO2_B7_d
I2S2_LRCK_RX_M0	GMAC0_RXDV_CRS	UART6_CTSn_M0	SPI1_CS0_M0	GPIO2_C0_d
I2S2_MCLK_M0	ETHU_REFCLKO_25M	UART7_RTSn_M0	SPI1_CLK_M0	GPIO2_C1_d
I2S2_SCLK_TX_M0	GMAC0_MCLKINOUT	UART7_CTSn_M0	SPI2_MISO_M0	GPIO2_C2_d
I2S2_LRCK_TX_M0	GMAC0_MDC	UART9_RTSn_M0	SPI2_MOSI_M0	GPIO2_C3_d
I2S2_SDO_M0	GMAC0_MDIO	UART9_CTSn_M0	SPI2_CS0_M0	GPIO2_C4_d
I2S2_SDI_M0	GMAC0_RXER	UART8_TX_M0	SPI2_CS1_M0	GPIO2_C5_d
CLK32K_OUT1		UART8_RX_M0	SPI1_CS1_M0	GPIO2_C6_d

E27 SDMMC1_D0 [30]
E28 SDMMC1_D1 [30]
B28 SDMMC1_D2 [30]
C27 SDMMC1_D3 [30]
C28 SDMMC1_CMD [30]
D27 SDMMC1_CLK [30]
D26 CPU_CAN2_RX_M1 [43]
E25 CPU_CAN2_TX_M1 [43]
F28 CPU_UART1_RX_M0 [32]
G27 CPU_UART1_TX_M0 [32]
G28 CPU_UART1_RTS_M0 [32]
F27 CPU_UART1_CTS_M0 [32]
H25 AUDIO_OUT_select [40]
F24 USB3_PWREN [33]
G23 GPIO_MUX0_1 [41]
F25 CUP_IN_RESET1 [45]
H24 USBHUB2_RSTn [35]
H23 HP_DET_L_GPIO3_C2 [40]
F26 GPIO_MUX0_5 [41]
E26 MIC_IN_DET [40]

VCCIO_SD2 J21 VCCIO4
C412 0.1uF/16V
VCCIO_SD2 R534 1 2 0R/1%/0402 VCCIO_SD

If a board needs to be compatible with two voltage choices, recommended to enable BOM_ID

RK3568
VT_BGA_19X19_P65MMSP_636P_H1P68MM

RK3568_N(VCCIO7 Domain)

U23N

VCCIO7 Domain
Operating Voltage=1.8V/3.3V

PWM14_M1	SPI3_CLK_M1	CAN1_RX_M1	PCIE30X2_CLKREQn_M2	I2S3_MCLK_M1 GPIO4_C2_d
PWM15_IR_M1	SPI3_MOSI_M1	CAN1_TX_M1	PCIE30X2_WAKEn_M2	I2S3_SCLK_M1 GPIO4_C3_d
EDP_HPDIN_M0	SPDIF_TX_M2	SATA2_ACT_LED	PCIE30X2_PERSTn_M2	I2S3_LRCK_M1 GPIO4_C4_d
PWM12_M1	SPI3_MISO_M1	SATA1_ACT_LED	UART9_TX_M1	I2S3_SDO_M1 GPIO4_C5_d
PWM13_M1	SPI3_CS0_M1	SATA0_ACT_LED	UART9_RX_M1	I2S3_SDI_M1 GPIO4_C6_d
HDMITX_SCL	I2C5_SCL_M1			GPIO4_C7_u
HDMITX_SDA	I2C5_SDA_M1			GPIO4_D0_u
HDMITX_CEC_M0	SPI3_CS1_M1			GPIO4_D1_u
				GPIO4_D2_d

AF8 I2S3_MCLK_M1 R720 OPT 2 22R/1%/0402
AA11 I2S3_SCLK_M1 R721 2 22R/1%/0402
AH7 I2S3_LRCK_M1 R722 2 22R/1%/0402
AD8 I2S3_SDO_M1 R723 2 22R/1%/0402
AE8 I2S3_SDI_M1 R724 2 22R/1%/0402
I2S_SCK [32]
I2S_WS [32]
I2S_IN [32]
I2S_OUT [32]
AG8 HDMITX_SCL [26]
AG7 HDMITX_SDA [26]
AH6 HDMITX_CEC_M0 [26]
AB9

VCCIO7 V12 R719 1 0R/1%/0402 2 VCC_1V8
C511 0.1uF/16V

Note:
If VCCIO7 domain power voltage is adjusted, the software DTS configuration must be updated synchronously, otherwise the IO may be damaged!
If the VCCIO7 hardware has been modified to 1.8V power supply, and the corresponding DTS must be modified to 1.8V configuration, otherwise the IO function of VCCIO7 will be abnormally.
The VCCIO7 hardware has been modified to 3.3V power supply, if the software DTS configuration is still 1.8V configuration, the IO of VCCIO7 will be damaged!

RK3568
VT_BGA_19X19_P65MMSP_636P_H1P68MM

RK3568_O(SARADC/OTP)

U23O

SARADC

Recovery/ SARADC_VIN0	B27	SARADC_VIN0_KEY/RECOVERY	C123 1	2 1000pF/50V
SARADC_VIN1	C26	SARADC_VIN1_HW_ID	C377 1	2 1000pF/50V
SARADC_VIN2	D24	SARADC_VIN2_HP_HOOK	C395 1	2 1000pF/50V
SARADC_VIN3	E23			
SARADC_VIN4	G21			
SARADC_VIN5	F22			
SARADC_VIN6	G20			
SARADC_VIN7	F21			
SARADC_AVDD_1V8	H22			

VCCA_1V8
C410 0.1uF/16V

OTP OTP_VCC18 H20
VCC_1V8
C417 0.1uF/16V

RK3568
VT_BGA_19X19_P65MMSP_636P_H1P68MM

Note:
Must be mounted
VCCA_1V8 R127 10K/1%/0402 SARADC_VIN0_KEY/RECOVERY

If there is no **Key requirement**, two test points **must be reserved** to facilitate **firmware update**

It is suggested **to reserve a** Key to facilitate **the** development debug

If SARADC_VIN0=0V at after power **on and reset**, then system will enter into loader **mode.**

SARADC_VIN0_KEY/RECOVERY [38]
SARADC_VIN1_HW_ID [38]

Note:
Caps of between dashed green lines and U1000 should be placed under the U1000 package

Title	15.RK3568_SARADC/GPIO	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size	Document Number		Rev
A3	640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		<2.0>
Date:	Monday, April 17, 2023	Sheet 15 of 50	

RK3568_P(MIPI_CSI_RX)



Option1	Sensor1 x4Lane	MIPI_CSI_RX_D0-3 MIPI_CSI_RX_CLK0
Option2	Sensor1 x2Lane + Sensor2 x2Lane	MIPI_CSI_RX_D0-1 MIPI_CSI_RX_CLK0 MIPI_CSI_RX_D2-3 MIPI_CSI_RX_CLK1

RK3568_M(VCCIO6 Domain)



Note:
Caps of between dashed green lines and U1000
should be placed under the U1000 package.
Other caps should be placed close to the U1000 package

Note:
If VCCIO6 domain power voltage is adjusted,
the software DTS configuration must be
updated synchronously,
otherwise the IO may be damaged!

If the VCCIO6 hardware has been modified to
1.8V power supply, and the corresponding
DTS must be modified to 1.8V configuration,
otherwise the IO function of VCCIO6
will be abnormally.

The VCCIO6 hardware has been modified to
3.3V power supply, if the software DTS
configuration is still 1.8V configuration,
the IO of VCCIO6 will be damaged!

Note:
According to the actual choice of mounted
Cannot be mounted at the same time

Default:1.8V
Select the voltage according to the application

If the IO domain is to be used as FEPHY,
since some FEPHY only support 3.3V IO,
it is recommended to reallocate GPIO
to reduce the cost of level conversion

If a board needs to be compatible
with two voltage choices,
recommended to enable BOM_ID

Note:
Camera MCLK can select the following clock:
1:CAM_CLKOUT0
2:CAM_CLKOUT1
3:CIF_CLKOUT
4:REFCLK_OUT(24MHz)

Attention to the voltage matching

GMAC	Direction	GEPHY	GMAC	Direction	FEPHY
GMACx_TXD0	------->	PHYx_TXD0	GMACx_TXD0	------->	PHYx_TXD0
GMACx_TXD1	------->	PHYx_TXD1	GMACx_TXD1	------->	PHYx_TXD1
GMACx_TXD2	------->	PHYx_TXD2			
GMACx_TXD3	------->	PHYx_TXD3			
GMACx_TXEN	------->	PHYx_TXEN	GMACx_TXEN	------->	PHYx_TXEN
GMACx_TXCLK	------->	PHYx_TXCLK			
GMACx_RXD0	<-------	PHYx_RXD0	GMACx_RXD0	<-------	PHYx_RXD0
GMACx_RXD1	<-------	PHYx_RXD1	GMACx_RXD1	<-------	PHYx_RXD1
GMACx_RXD2	<-------	PHYx_RXD2			
GMACx_RXD3	<-------	PHYx_RXD3			
GMACx_RXDV	<-------	PHYx_RXDV	GMACx_RXDV	<-------	PHYx_CRS_DV
GMACx_RXCLK	<-------	PHYx_RXCLK			
GMACx_RXER			GMACx_RXER	<-------	PHYx_RXER
GMACx_MDC	------->	PHYx_MDC	GMACx_MDC	------->	PHYx_MDC
GMACx_MDIO	<------->	PHYx_MDIO	GMACx_MDIO	<------->	PHYx_MDIO
ETHx_REFCLKO_25M	------->	PHYx OSC	ETHx_REFCLKO_25M	------->	PHYx OSC
GMACx_MCLKINOUT	<-------	PHYx_CLKOUT125(Option)	GMACx_MCLKINOUT	<------->	PHYx_TXC
GPIO	------->	PHYx_RSTn	GPIO	------->	PHYx_RSTn
GPIO	<-------	PHYx_INT/PMEB	GPIO	<-------	PHYx_INT/PMEB

Title: 16.RK3568_VI Interface	Vantron	ChengDu Vantron Technology.LTD 6th Floor, 1st Building,No.5, 3rd Wuke East Street, Wuhou District ,ChengDu , China 86-28-8512-3930
Size: A2	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2	Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 16 of 50	

RK3568_R(MIPI_DSI_TX0/LVDS_TX0)



RK3568_S(MIPI_DSI_TX1)



RK3568_T(eDP TX)



RK3568_Q(HDMI2.0 TX)



Title	17.RK3568_VO Interface_1		
Size	A3	Document Number	640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2
Rev	<2.0>		
Date:	Monday, April 17, 2023	Sheet	17 of 50

ChengDu Vantron Technology.,LTD
6th Floor, 1st Building,No.9,
3rd WuKe East Street,
WuHou District ,ChengDu , China
86-28-8512-3930

RK3568_L(VCCIO5 Domain)

U23L

VCCIO5 Domain

Operating Voltage=1.8V/3.3V

LCDC_D0	/ VOP_BT656_D0_M0	/ SPI0_MISO_M1	/ PCIE20_CLKREQn_M1	/ I2S1_MCLK_M2	/ GPIO2_D0_d
LCDC_D1	/ VOP_BT656_D1_M0	/ SPI0_MOSI_M1	/ PCIE20_WAKEn_M1	/ I2S1_SCLK_TX_M2	/ GPIO2_D1_d
LCDC_D2	/ VOP_BT656_D2_M0	/ SPI0_CS0_M1	/ PCIE30X1_CLKREQn_M1	/ I2S1_LRCK_TX_M2	/ GPIO2_D2_d
LCDC_D3	/ VOP_BT656_D3_M0	/ SPI0_CLK_M1	/ PCIE30X1_WAKEn_M1	/ I2S1_SDI0_M2	/ GPIO2_D3_d
LCDC_D4	/ VOP_BT656_D4_M0	/ SPI2_CS1_M1	/ PCIE30X2_CLKREQn_M1	/ I2S1_SDI1_M2	/ GPIO2_D4_d
LCDC_D5	/ VOP_BT656_D5_M0	/ SPI2_CS0_M1	/ PCIE30X2_WAKEn_M1	/ I2S1_SDI2_M2	/ GPIO2_D5_d
LCDC_D6	/ VOP_BT656_D6_M0	/ SPI2_MOSI_M1	/ PCIE30X2_PERSTn_M1	/ I2S1_SDI3_M2	/ GPIO2_D6_d
LCDC_D7	/ VOP_BT656_D7_M0	/ SPI2_MISO_M1	/ UART8_TX_M1	/ I2S1_SDO0_M2	/ GPIO2_D7_d
LCDC_CLK	/ VOP_BT656_CLK_M0	/ SPI2_CLK_M1	/ UART8_RX_M1	/ I2S1_SDO1_M2	/ GPIO3_A0_d
LCDC_D8	/ VOP_BT1120_D0	/ SPI1_CS0_M1	/ PCIE30X1_PERSTn_M1	/ SDMMC2_D0_M1	/ GPIO3_A1_d
LCDC_D9	/ VOP_BT1120_D1	/ GMAC1_TXD2_M0	/ I2S3_MCLK_M0	/ SDMMC2_D1_M1	/ GPIO3_A2_d
LCDC_D10	/ VOP_BT1120_D2	/ GMAC1_TXD3_M0	/ I2S3_SCLK_M0	/ SDMMC2_D2_M1	/ GPIO3_A3_d
LCDC_D11	/ VOP_BT1120_D3	/ GMAC1_RXD2_M0	/ I2S3_LRCK_M0	/ SDMMC2_D3_M1	/ GPIO3_A4_d
LCDC_D12	/ VOP_BT1120_D4	/ GMAC1_RXD3_M0	/ I2S3_SDO_M0	/ SDMMC2_CMD_M1	/ GPIO3_A5_d
LCDC_D13	/ VOP_BT1120_CLK	/ GMAC1_TXCLK_M0	/ I2S3_SDI_M0	/ SDMMC2_CLK_M1	/ GPIO3_A6_d
LCDC_D14	/ VOP_BT1120_D5	/ GMAC1_RXCLK_M0		/ SDMMC2_DET_M1	/ GPIO3_A7_d
LCDC_D15	/ VOP_BT1120_D6	/ ETH1_REFCLKO_25M_M0		/ SDMMC2_PWREN_M1	/ GPIO3_B0_d
LCDC_D16	/ VOP_BT1120_D7	/ GMAC1_RXD0_M0	/ UART4_RX_M1	/ PWM8_M0	/ GPIO3_B1_d
LCDC_D17	/ VOP_BT1120_D8	/ GMAC1_RXD1_M0	/ UART4_TX_M1	/ PWM9_M0	/ GPIO3_B2_d
LCDC_D18	/ VOP_BT1120_D9	/ GMAC1_RXDV_CRS_M0	/ I2C5_SCL_M0	/ PDM_SDI0_M2	/ GPIO3_B3_d
LCDC_D19	/ VOP_BT1120_D10	/ GMAC1_RXER_M0	/ I2C5_SDA_M0	/ PDM_SDI1_M2	/ GPIO3_B4_d
LCDC_D20	/ VOP_BT1120_D11	/ GMAC1_TXD0_M0	/ I2C3_SCL_M1	/ PWM10_M0	/ GPIO3_B5_d
LCDC_D21	/ VOP_BT1120_D12	/ GMAC1_TXD1_M0	/ I2C3_SDA_M1	/ PWM11_IR_M0	/ GPIO3_B6_d
LCDC_D22	/ PWM12_M0	/ GMAC1_TXEN_M0	/ UART3_TX_M1	/ PDM_SDI2_M2	/ GPIO3_B7_d
LCDC_D23	/ PWM13_M0	/ GMAC1_MCLKINOUT_M0	/ UART3_RX_M1	/ PDM_SDI3_M2	/ GPIO3_C0_d
LCDC_HSYNC	/ VOP_BT1120_D13	/ SPI1_MOSI_M1	/ PCIE20_PERSTn_M1	/ I2S1_SDO2_M2	/ GPIO3_C1_d
LCDC_VSYNC	/ VOP_BT1120_D14	/ SPI1_MISO_M1	/ UART5_TX_M1	/ I2S1_SDO3_M2	/ GPIO3_C2_d
LCDC_DEN	/ VOP_BT1120_D15	/ SPI1_CLK_M1	/ UART5_RX_M1	/ I2S1_SCLK_RX_M2	/ GPIO3_C3_d
PWM14_M0	/ VOP_PWM_M1	/ GMAC1_MDC_M0	/ UART7_TX_M1	/ PDM_CLK1_M2	/ GPIO3_C4_d
PWM15_IR_M0	/ SPDIF_TX_M1	/ GMAC1_MDIO_M0	/ UART7_RX_M1	/ I2S1_LRCK_RX_M2	/ GPIO3_C5_d

RK3568

VT_BGA_19X19_P65MMSP_636P_H1P68MM

AG6 — R249 1 — 2 0R/1%/0402 — CPU_SPI0_FLASH_MISO [29]
AD7 — R250 1 — 2 0R/1%/0402 — CPU_SPI0_FLASH_MOSI [29]
AC8 — R251 1 — 2 0R/1%/0402 — CPU_SPI0_FLASH_CS [29]
AC7 — R252 1 — 2 0R/1%/0402 — CPU_SPI0_FLASH_SCK [29]
AF5 — LCD1_PWR_EN [27]
AF6 — CPU_CAN2_STBY [43]
AD6
AH5 — LCD1_5V_12V_SEL [27]
AH4 — LCD_BL1_EN [25]
AB8
AE5
AG4 — LCD2_PWR_EN [27]
AF4 — LCD2_5V_12V_SEL [27]
AH3
AG3 — SPEAKER_SD_A# [37]
AH2 — WD_SET [23]
AG2 — LCD1_EDID_LINK [25]
AG1 — Buzzer_EN_PWM [23]
AF2 — CPU_LED_status
AF1 — I2C5_SCL_M0 [22]
AE1 — I2C5_SDA_M0 [22]
AE2 — I2C3_SCL_M1 [25]
AE3
AD4 — UART3_TX_M1
AD2 — UART3_RX_M1
AD1 — LCD2_EDID_LINK [25]
AA7 — eDP_HPD# [25]
AC4 — EEPROM_WP [22]
AC3 — LCD_BL1_PWM [25]
AC2 — WD_WDI [23]

V10 — VCCIO5_1
V11 — VCCIO5_2

VCC_3V3 — C515 0.1uF/16V

Status

VCC_3V3 — D4 LED,Red — R97 1K/1%/0402 — Q13 JMTL2N7002KS — GND

CPU_LED_status — 1

Note:

If VCCIO5 domain power voltage is adjusted, the software DTS configuration must be updated synchronously, otherwise the IO may be damaged!

If the VCCIO5 hardware has been modified to 1.8V power supply, and the corresponding DTS must be modified to 1.8V configuration, otherwise the IO function of VCCIO5 will be abnormally.

The VCCIO5 hardware has been modified to 3.3V power supply, if the software DTS configuration is still 1.8V configuration, the IO of VCCIO5 will be damaged!

VCC_3V3 — R240 2.2K/1%/0402 — R237 2.2K/1%/0402 — I2C5_SCL_M0 — I2C5_SDA_M0

UART3_RX_M1 — R207 1 — 2 0R/1%/0402 — MCU_TO_CPU_UART5_TX [42]
UART3_TX_M1 — R208 1 — 2 0R/1%/0402 — MCU_TO_CPU_UART5_RX [42]

TO MCU

Title	18.RK3568_VO Interface_2	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size	A4	Document Number 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2	Rev <2.0>
Date:	Monday, April 17, 2023	Sheet 18 of 50	

RK3568_H(VCCIO1 Domain)

U23H

VCCIO1 Domain

Operating Voltage=1.8V/3.3V

I2C3_SDA_M0	/ UART3_RX_M0	/ CAN1_RX_M0		/ AUDIOPWM_LOUT_P	/ ACODEC_ADC_DATA	/ GPIO1_A0_u
I2C3_SCL_M0	/ UART3_TX_M0	/ CAN1_TX_M0		/ AUDIOPWM_LOUT_N	/ ACODEC_ADC_CLK	/ GPIO1_A1_u
I2S1_MCLK_M0	/ UART3_RTSn_M0	/ SCR_CLK	/ PCIE30X1_PERSTn_M2			/ GPIO1_A2_d
I2S1_SCLK_TX_M0	/ UART3_CTSn_M0	/ SCR_IO	/ PCIE30X1_WAKEn_M2		/ ACODEC_DAC_CLK	/ GPIO1_A3_d
I2S1_SCLK_RX_M0	/ UART4_RX_M0	/ PDM_CLK1_M0		/ SPDIF_TX_M0		/ GPIO1_A4_d
I2S1_LRCK_TX_M0	/ UART4_RTSn_M0	/ SCR_RST	/ PCIE30X1_CLKREQn_M2		/ ACODEC_DAC_SYNC	/ GPIO1_A5_d
I2S1_LRCK_RX_M0	/ UART4_TX_M0	/ PDM_CLK0_M0		/ AUDIOPWM_ROUT_P		/ GPIO1_A6_d
I2S1_SDO0_M0	/ UART4_CTSn_M0	/ SCR_DET		/ AUDIOPWM_ROUT_N	/ ACODEC_DAC_DATAL	/ GPIO1_A7_d
I2S1_SDO1_M0	/ I2S1_SDI3_M0	/ PDM_SDI3_M0	/ PCIE20_CLKREQn_M2		/ ACODEC_DAC_DATAR	/ GPIO1_B0_d
I2S1_SDO2_M0	/ I2S1_SDI2_M0	/ PDM_SDI2_M0	/ PCIE20_WAKEn_M2		/ ACODEC_ADC_SYNC	/ GPIO1_B1_d
I2S1_SDO3_M0	/ I2S1_SDI1_M0	/ PDM_SDI1_M0	/ PCIE20_PERSTn_M2			/ GPIO1_B2_d
	I2S1_SDI0_M0	/ PDM_SDI0_M0				/ GPIO1_B3_d

RK3568

VT_BGA_19X19_P65MMSP_636P_H1P68MM

D18 — USBHUB3_RSTn [36]
E18 — PRTPWR8 [36]

A19 — I2S1_MCLK_M0_SOC — R1391 2 22R/1%/0402 — I2S1_MCLK_M0_RK809 [7]

B19 — I2S1_SCLK_TX_M0_SOC — R1371 2 22R/1%/0402 — I2S1_SCLK_TX_M0_RK809 [7]
F18 — PRTPWR9 [36]

A20 — I2S1_LRCK_TX_M0_SOC — R1351 2 22R/1%/0402 — I2S1_LRCK_TX_M0_RK809 [7]
C20 — PDM_CLK0_M0_SOC — R5361 2 22R/1%/0402 — PDM_CLK0_M0_RK809 [7]

B20 — I2S1_SDO0_M0_RK809 [7]
D20 — GPIO_MUX0_2 [41]
E20 — PRTPWR10 [36]
A21 — GPIO_MUX0_3 [41]
B21 — I2S1_SDI0_M0/PDM_SDI0_M0_RK809 [7]

VCCIO_ACODEC

Default 3.3V

VCCIO1 — H17 — C436 0.1uF/16V

If a board needs to be compatible with two voltage choices, recommended to enable BOM_ID

Note:

If VCCIO1 domain power voltage is adjusted, the software DTS configuration must be updated synchronously, otherwise the IO may be damaged!

If the VCCIO1 hardware has been modified to 1.8V power supply, and the corresponding DTS must be modified to 1.8V configuration, otherwise the IO function of VCCIO1 will be abnormally.

The VCCIO1 hardware has been modified to 3.3V power supply, if the software DTS configuration is still 1.8V configuration, the IO of VCCIO1 will be damaged!

Note:

Caps of between dashed green lines and U1000 should be placed under the U1000 package

Title	19.RK3568_Audio Interface	Vantron	ChengDu Vantron Technology.,LTD 6th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930
Size	Document Number		Rev
A4	640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		<2.0>
Date:	Monday, April 17, 2023	Sheet	19 of 50

LPDDR4X









Title: 20.DRAM-LPDDR4_1x32bit_200P	Vantron	ChengDu Vantron Technology,LTD 6th Floor, 1st Building,No.9, 3rd Wuke East Street, Wuhou District ,ChengDu , China 86-28-8512-3930	
Size: A2	Document Number: 6408BAGZZNNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet: 20 of 50		

Siganal & Power

eMMC_D0/FLASH_D0 [13]
eMMC_D1/FLASH_D1 [13]
eMMC_D2/FLASH_D2 [13]
eMMC_D3/FLASH_D3 [13]
eMMC_D4/FLASH_D4 [13]
eMMC_D5/FLASH_D5 [13]
eMMC_D6/FLASH_D6 [13]
eMMC_D7/FLASH_D7 [13]

eMMC_CMD/FLASH_WRn [13]

eMMC_CLKOUT/FLASH_DQS [13]

eMMC_DATA_STROBE/FLASH_CLE [13]

eMMC_RSTn/FSPI_D2/FLASH_WPn [13]

VCCIO_FLASH — VCCIO_FLASH

VCC_3V3 — VCC_3V3

eMMC Flash





Title: 21.eMMC	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuke East Street, Wuhou District, ChengDu , China 86-28-8512-3930	
Size: A3	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 21 of 50		



EEPROM



RTC IC



Title	22.EEPROM/RTC	
Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2	Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 22 of 50	

Buzzer



WATCHDOG



Title: 23.Buzzer/WTD	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District, ChengDu , China 86-28-8512-3930	
Size: A3	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 23 of 50		


De-Couple Cap
LT8911EXB
LT8911EXB
QFN48
IRQ/Config I2C
AUX_P needs to connect
100K resistance to GND
AUX_N needs to connect
100K resistance to 3.3V
LT8911EXB_RSTN is
compatible with 3.3V
and 1.8V.
The IIC of LT8911EXB is compatible
with 3.3V and 1.8V and does not
require level shift.
PS: S_ADR
H-->Addr: 0x5a
L-->Addr: 0x52
Defualt =L;
The Reset pin of LT8911EXB
(T8911EXB_RSTN) must be
controlled by GPIO.
CONFIDENTIAL
Vantron
Title
24.MIPI to eDP
Vantron
ChangDu Vantron Technology,LTD
6th/5th Floor, 1st Building,No.9,
3rd Wuliu East Street,
Wuhou District ,ChangDu , China
86-28-8512-3930
Size
A2
Document Number
640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2
Rev
<2.0>
Date:
Monday, April 17, 2023
Sheet
24
of
50

Signal & Power



LCD_VCC5V











EDP



HPD



EDID

Reserved four groups DIP SWITCH for EDP1 and EDP2, The default status is high!

Determine what type of display is connected

ESD



Title	25.VO_eDP TX	Vantron	ChengDu Vantron Technology LTD 5th/6th Floor, 1st Building,No.5, 3rd Middle East Street, Wuhou District, ChengDu, China 86-28-8512-3930
Size	Document Number		Rev
Custom	640M0AGG2N0R2_SBC-RK3568-NXP24-ARK-GEN2		2.0>
Date:	Monday, April 17, 2023	Sheet 25 of 50	

Siganal & Power



Voltage Transition



Voltage Transition



ESD & EMI



HDMI



Title	26.VO-HDMI2.0 TX	Vantron
Size	A3	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2
Rev	<2.0>	
Date:	Monday, April 17, 2023	Sheet 26 of 50

ChengDu Vantron Technology.,LTD
6th/5th Floor, 1st Building,No.9, 3rd Wuke East Street, Wuhou District, ChengDu , China
86-28-8512-3930





Title	27.Load Switch	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuke East Street, Wuhou District, ChengDu , China 86-28-8512-3930
Size A3	Document Number 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		Rev <2.0>
Date: Monday, April 17, 2023	Sheet 27 of 50		



Title: 28.RS485	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2	Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 28 of 50	

[18] CPU_SPI0_FLASH_CS
[18] CPU_SPI0_FLASH_MISO
[18] CPU_SPI0_FLASH_SCK
[18] CPU_SPI0_FLASH_MOSI

NOR FLASH



Title: 29.SPI_FLASH	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 29 of 50		

MicroSD2





MicroSD1 For Download



Title: 30.CPU_SD CARD			
Size: A3	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 30 of 50		

ChengDu Vantron Technology.,LTD
6th/5th Floor, 1st Building,No.9,
3rd WuKe East Street,
WuHou District, ChengDu , China
86-28-8512-3930

Signal & Power





POWER ON STRAPPING

PHY Pin	PHY Core Config	Description	Default
RXD0	PHYADDRESS0	LED_ACT, RXD[1:0] sets the lower three bits of the physical address. The upper two bits of the physical address are set to the default, "00"	0
RXD1	PHYADDRESS1	LED_ACT, RXD[1:0] sets the lower three bits of the physical address. The upper two bits of the physical address are set to the default, "00"	0
LED_ACT	PHYADDRESS2	LED_ACT, RXD[1:0] sets the lower three bits of the physical address. The upper two bits of the physical address are set to the default, "00"	1
RX_DV	RGMII IO power selection	0= RGMII IO 3.3V 1= RGMII IO 2.5V	0
RXD2	PLLON selection	0= PLL off in hibernation when cable unplugged 1= PLL on in hibernation when cable unplugged	0
LED_1000	TEST Mode	0=Test Mode only for internal use 1=Normal Mode, Must external pull up	1
RXD3	Low Power Mode	0= Force Low Power mode for shorter cable application 1= Normal cable application	0
LED_10_100	RXC delay enable selection	0= RXC delay disable 1= RXC delay enable	1
RX_CLK	clk 25m disable	0= clk 25m output enable 1= clk 25m output disable	0

PHY Pin	PHY Core Config	Description	Default
RXD0	PHYADDRESS0	LED_ACT, RXD[1:0] sets the lower three bits of the physical address. The upper two bits of the physical address are set to the default, "00"	0
RXD1	PHYADDRESS1	LED_ACT, RXD[1:0] sets the lower three bits of the physical address. The upper two bits of the physical address are set to the default, "00"	0
LED_ACT	PHYADDRESS2	LED_ACT, RXD[1:0] sets the lower three bits of the physical address. The upper two bits of the physical address are set to the default, "00"	1



ETH CONNECT



ETHERNET



ETH LED



Symbol	10M link	10M active	100M link	100M active	1000M link	1000M active
LED_10_100	off	off	on	on	off	off
LED_1000	off	off	off	off	on	on
LED_ACT	on	blink	on	blink	on	blink

Title		
31.Ethernet-GEPHY_YT8511C	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.5, 3rd Wuke East Street, Wuhou District ,ChengDu , China 86-28-6512-3930
Size: C	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2	Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 31 of 50	

Signal & Power



Title	30.MiniPCIe2.0 Slot	Vantron	ChengDu Vantron Technology,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, Wuhou District ,ChengDu , China 86-28-8512-3930
Size	Document Number		Rev
A3	640BBAGG3RL22_SBC-RK3568-NXP1024-ARK-L2-GEN2		<2.0>
Date:	Monday, April 17, 2023	Sheet 32 of 50	

Siganal & Power





USB3.0







Title: 33.USB3.0	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District, ChengDu , China 86-28-8512-3930	
Size: A3	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2	Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 33 of 50	







USB HUB CONTROLLER

Layout: 90ohm differential pairs



USB2.0



USB2.0



USB2.0



USB2.0 OTG Type-A







EEPROM





Title: 34.USB2.0_USB_HUB_A	Vantron	ChangDu Vantron Technology,LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuhu East Street, Wuhou District,ChangDu ,China 86-28-8512-3930	
Size: A2	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet: 34 of 50		









Layout: 90ohm differential pairs

USB HUB CONTROLLER



USB2.0



USB2.0



USB2.0







EEPROM



USB2.0 CONNECTOR



Title	35.USB2.0_USB_HUB_B	Vantron	ChangDu Vantron Technology,LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuliq East Street, Wuhou District ,ChangDu , China 86-28-8512-3930
Size	Document Number		Rev
A2	640BBAG02RNK2_SBC-RK3568-NXP24-ARK-GEN2		<2.0>
Date:	Monday, April 17, 2023	Sheet	35 of 50







Layout: 90ohm differential pairs

USB HUB CONTROLLER

to U38 HUB













EEPROM



Title: 36.USB2.0_USB_HUB_C	Vantron	ChangDu Vantron Technology,LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuliu East Street, Wuhou District ,ChangDu ,China 86-28-8512-3930
Size: A2	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2	Rev: <2.0>
Date: Monday, April 17, 2023	Sheet: 36 of 50	

Signal











AMP 5W



Title: 37.AUDIO OUT	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuke East Street, Wuhou District, ChengDu , China 86-28-8512-3930	
Size: A3	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 37 of 50		

Signal & Power



HW_ID



Recovery Key



Note:

If there is no Key requirement,
It is suggested to reserve a
SW9200 Key to facilitate the
development debug

RECOVERY_Key function:
If SARADC_VIN0=0V
at after power on and reset,
then system will
enter into loader mode.

PowerOn/OFF_Key



Reset_Key



Title: 38.KEY Array/SARADC	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 38 of 50		

URAT2 Debug



Title: 39.Uart Debug	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 39 of 50		



Title	40.MIC/Headphone	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuke East Street, Wuhou District, ChengDu , China 86-28-8512-3930
Size	Document Number		Rev
A3	640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		<2.0>
Date:	Monday, April 17, 2023	Sheet	40 of 50



Title	41.User COMMS	
Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2	Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 41 of 50	



Table 22-1. Boot device select

Boot Device	BOOT_CFG1[7]	BOOT_CFG1[6]	BOOT_CFG1[5]	BOOT_CFG1[4]
FlexSPI1 (Serial NOR)	0	0	0	0
SD	0	0	1	x
MMC/eMMC	1	0	x	x
SEMC (NAND)	0	1	x	x
SEMC (NOR)	0	0	0	1

Table 9-2. Boot MODE pin settings

BOOT_MODE[1:0]	Boot Type
00	Boot From Fuses
01	Serial Downloader
10	Internal Boot
11	Reserved











Title	43.CPU_CAN0/1	
Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuke East Street, Wuhou District, ChengDu , China 86-28-8512-3930	
Size	Document Number	Rev
A3	640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2	<2.0>
Date:	Monday, April 17, 2023	Sheet 43 of 50



Title: 44.MCU_Motor	Vantron	ChangDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuliu East Street, Wuhou District ,ChangDu , China 86-28-8512-3930	
Size: A2	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet: 44 of 50		

Reset



Service



Title: 45.Reset Switch	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 45 of 50		



Title: 46.Weigh_ADC	Vantron	ChengDu Vantron Technology.LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuhu East Street, Wuhou District ,ChengDu ,China 86-28-8512-3930	
Size: A2	Document Number: 640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet: 46 of 50		



Address: 0X64

Low Lable Stock



Shoot-through



Paper Takeup Cassette



Head up switch









Title: 47.Printer_Sensor	Vantron	ChangDu Vantron Technology,LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuhu East Street, Wuhou District ,ChangDu , China 86-28-8512-3930	
Size: A2	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet: 47 of 50		



Title	48.Printhead_Driver	
Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd Wuke East Street, Wuhou District, ChengDu , China 86-28-8512-3930	
Size	Document Number	Rev
A3	640BBAGG2RNK2_SBC-RK3568-NXP24-ARK-GEN2	<2.0>
Date:	Monday, April 17, 2023	Sheet 48 of 50



Accelerometer



Title: 49.ACCEL		Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 49 of 50		

CUTTER







Title: 50.CUTTER	Vantron	ChengDu Vantron Technology.,LTD 6th/5th Floor, 1st Building,No.9, 3rd WuKe East Street, WuHou District ,ChengDu , China 86-28-8512-3930	
Size: A4	Document Number: 640BBAGG2RNK2 SBC-RK3568-NXP24-ARK-GEN2		Rev: <2.0>
Date: Monday, April 17, 2023	Sheet 50 of 50		