

Cursor

Man lo database me 10 lakh users hain.

Agar MongoDB ek hi baar me sab data bhej de:

- ✗ Memory crash ho sakta hai
- ✗ Network slow ho jayega

Isliye MongoDB kya karta hai:

- ☑ Cursor create karta hai
- ☑ Data batch by batch bhejta hai

```
const cursor = db.users.find()
```

Ye command documents return nahi karti immediately, balki cursor return karti hai.

MongoDB shell automatically cursor ko iterate karke documents dikha deta hai.

Cursor Methods

1. `next()` → Next document fetch karta hai.
2. `hasNext()` → Check karta hai aur documents bache hain ya nahi.
3. `limit()` → Kitne documents chahiye.
4. `skip()` → Documents skip karta hai.
5. `sort()` → Documents ko sort karta hai.

Example:

```
const cursor = db.users.find()  
// next  
cursor.next()  
// has next  
cursor.hasNext()  
  
// limit  
db.users.find().limit(5)  
// skip  
db.users.find().skip(5)  
// sort  
db.users.find().sort({age:1}) // ascending  
db.users.find().sort({age:-1}) // descending
```


Cursor Chain

```
db.users.find()  
    .sort({age:-1}) // sort by age  
    .skip(5) // skip first 5  
    .limit(5) // return next 5
```

Ye pagination me use hota hai.

**Thank
You**