

Module 1: Advanced SOS & Command Center Dispatch Protocol

The Feature: A multi-tiered, hardware-integrated emergency trigger system that immediately routes high-priority alerts to the RAHBAR Command & Control (C2) Center.

Technical Breakdown:

Dead Man's Switch: A primary in-app button that the user holds down when feeling threatened. Releasing it triggers a 10-second OTP (One-Time Password) window. If no OTP is entered (or if a Duress PIN is used), the Command Center is immediately alerted.

Stealth Hardware Trigger: If the user cannot touch the screen, pressing the physical side volume buttons 3-4 times rapidly bypasses the OTP and instantly dispatches the alert.

Command Center Role: The C2 center receives the alert, logs the exact coordinates, and takes authority to dispatch the nearest local police unit directly to the user.

Module 2: Discreet Evidence Vault & Dual-Storage Protocol

The Feature: An automated mechanism to capture and secure court-admissible evidence (voice, video, and location) without alerting the attacker.

Technical Breakdown:

Stealth Capture: The moment the SOS is triggered, the app automatically begins recording background audio and camera video without any visual changes to the UI (screen remains black or looks like a normal app) so the attacker does not know they are being recorded.

Dual-Vault Synchronization: This media, along with precise location data, is instantly saved to two secure locations simultaneously: a hidden, encrypted folder directly on the user's mobile device, and uploaded to the secure RAHBAR cloud server. If the physical phone is stolen or smashed, the C2 server still holds the evidence.

Module 3: Offline Resilience & Telemetry Fallback

The Feature: The critical failsafe infrastructure that ensures the user remains fully traceable even in total internet dead zones or during cellular jammers.

Technical Breakdown:

Local Breadcrumb Caching: The system continuously pings GPS coordinates every 10 seconds and saves them to an offline local backup folder on the device.

Automated SMS Fallback: If the app detects a total loss of 3G/4G/5G data (or predicts a signal drop), it automatically packages the offline 10-second location history folder into a compressed text payload and transmits it directly to the Command Center and Guardians using standard cellular SMS voice bands.

Module 4: Guardian Network & Live C2 Tracking

The Feature: A synchronized "Google Family" style monitoring dashboard that connects the user, their trusted contacts, and the central Command Center in real-time.

Technical Breakdown:

Aggressive Wake Alarms: If the SOS is triggered, connected Guardian apps bypass normal notification rules and trigger a loud, screen-waking alarm on the guardian's phone.

Live Telemetry: The Command Center and Guardians receive a live, high-frequency dashboard showing the victim's exact status: whether they are moving, idle, their speed, and their directional bearing, allowing police to track a moving vehicle if the user is kidnapped.

Module 5: Zero-Trust Transit Security & Spot Audits

The Feature: The infrastructure that secures inter-city buses by verifying passengers and preventing conductor corruption.

Technical Breakdown:

CNIC Database Verification: Conductors scan passenger CNIC barcodes. The RAHBAR server (not the conductor) decides if the passenger is clear. If a criminal is detected, a silent alert goes to the C2 center to intercept the bus.

Automated Check-Post Routing: Cleared buses receive a "Green Signal" routed by the C2 center to upcoming police check-posts to bypass manual stops.

Physical Spot Audits: To prevent conductors from taking bribes and sneaking unregistered passengers onboard, the system randomly assigns Spot Audits to check-posts. Police perform a physical headcount to ensure it perfectly matches the digital RAHBAR manifest.