

PT. YONGJIN JAVASUKA GARMENT

INTRUKSI KERJA PEMASANGAN KAIN MONIL PADA SCREEN

WORK INSTRUCTIONS FOR INSTALLING MONIL FABRIC ON THE SCREEN

No .Dokumen : YJ-IK.PRT.0014
Tgl.Efektif : 11 Januari 2024
No. Revisi : 00
Halaman : 1 Dari 1

	**1. Pastikan mesin dalam keadaan menyala / ON.** ***Make sure the machine is truned ON.***		**5. Atur peregangan kain dan ukur menggunakan tension meter, dan biarkan selama 15 - 30 menit agar peregangan kain monil kuat dan stabil.** ***Adjust the stretch of the fabric and measure it using a tension meter, and leave it for 15-30 minutes so that the streach of the monil fabric is strong and stable.***
	**2. Siapkan screen frame yang sudah bersih dan kain monil yang akan digunakan.** ***Prepare a clean screen frame and the monil cloth that will be used.***		**6. Berikan perekat (BLUE BON) disetiap sisi screen frame. (2 kali oles dan diamkan selama 30-60 menit agar kering merata.** ***Apply adhesive (BLUE BON) to each side of the screen frame (2 times apply and leave for 30-60 minutes to dry evenly)***
	**3. Susun rapi screen frame diatas mesin streacing (posisi screen disesuaikan dengan kebutuhan. Lurus / miring).** ***Arrange the screen frame neatly on the streaching machine (screen position adjust to needs. Straight / slanted)***		**7. Setelah kering, pisahkan screen dan rapikan sisa kain monil.** ***Once dry, separate the screen and trim the remaining monil cloth.***
	**4. Gelar kain monil diatas screen frame.** ***Hold the monil cloth over the screen frame***		**8. simpan di rak yang sudah disediakan dan di beri identitas.** ***Store it on the rack provided and provide identification.***