

PT. YONGJIN JAVASUKA GARMENT	**INSTRUKSI KERJA MESIN JAHIT LUBANG KANCING -** *WORK INSTRUCTION BUTTON HOLE SEWING MACHINE*	No.Dokumen : YJ-IK.SEW.0016 Tgl.Efektif : 01 Agustus 2018 No.Revisi : 01 Halaman : 1 dari 1

PREPARED BY	CHECKING BY	APPROVED BY
QA Officer	QA Manager	Factory Manager

OPC *(OPC)*	VISUAL / URAIAN *(Description)*	ALAT/KONDISI *(Equipment/condition)*	TARGET *(Target)*
1	 1. pasang jarum benang pada mesin jahit pasang kancing *(Attach needle and thread to button sewing machine)*	1. Manual *(Manual)*	Supaya jarum dan benang dapat tepasang dengan baik *(To attach needle and thread properly)*
2		2. Manual *(Manual)*	Mesin aktif *(Machine in active)*
3	 2. Nyalakan mesin jahit pasang kancing dengan menekan tombol "on" *(Turn on button sewing machine by pressing "ON")*	3.Manual kancing *(Manual Button)*	Agar posisi kancing dengan garment tepat untuk di jahit. *(To position button and garment accurately for sewing)*
4		4. Injak pedal *(Step on Pedal)*	Agar kecepatan jahitan dapat diatur dan jahitan pas dengan yang kita inginkan *(To adjust stiching speed and achieve desired stiching)*
5	 3. Pasang kancig dan garment yang ingin dijahit *(Attach button and garment to be sew)*	5. Semi otomatis *(Semi Automatic)*	Mesin beroperasi dengan baik *(Machine can be operate well)*
6		6. Manual *(Manual)*	Posisi mesin mati. *(Position machine is off)*



4. Injak pedal agar mesin beroperasi
(Step on the pedal to



5. Mesin beroperasi untuk menjahit kancing pada garment
(Machine is operating to sew button on to garment)



6. Tekan "of" untuk mematikan mesin
(Press "OFF" to power off machine)