

Sri Sivasubramaniya Nadar College of Engineering, Chennai
(An autonomous Institution affiliated to Anna University)

Degree & Branch	M.Tech (Integrated) Computer Science & Engineering	Name	Pandiarajan D
Subject Code & Name	ICS1512 - Machine Learning Algorithms Laboratory		
Academic year	2025-2026 (Odd)	Batch:2023-2028	Sem V

**Experiment 7: Clustering Human Activity Recognition Data using
K-Means, DBSCAN, and Hierarchical Clustering**

Objective

To implement and analyze the performance of clustering algorithms on the Human Activity Recognition dataset:

- **Model A:** K-Means Clustering
- **Model B:** DBSCAN (Density-Based Spatial Clustering of Applications with Noise)
- **Model C:** Hierarchical Agglomerative Clustering (HAC)

Students must visualize and compare the clusters formed by each algorithm, report results, and analyze performance.

Dataset

- **Name:** Human Activity Recognition Using Smartphones Dataset
- **Samples:** 10,299 instances from 30 volunteers (aged 19-48)
- **Activities:** 6 classes - WALKING, WALKING_UPSTAIRS, WALKING_DOWNSTAIRS, SITTING, STANDING, LAYING
- **Features:** 561 time and frequency domain features from 3-axis accelerometer and gyroscope
- **Sampling:** 50Hz, windows of 2.56s (128 readings/window)
- **Preprocessing:** Normalization, noise filtering

Theoretical Description of Models

K-Means Clustering

- **Objective:** Partition data into k clusters by minimizing within-cluster variance
- **Distance Metric:** Euclidean distance

- **Algorithm:**
 1. Initialize k centroids randomly
 2. Assign each point to nearest centroid
 3. Update centroids as mean of assigned points
 4. Repeat until convergence or maximum iterations
- **Elbow Method:** Used to determine optimal k by analyzing Within-Cluster Sum of Squares (WCSS)

DBSCAN (Density-Based Clustering)

- **Concept:** Groups points that are closely packed together (density-based)
- **Parameters:** ϵ (neighborhood radius), $minPts$ (minimum points)
- **Point Types:**
 - Core points: Have at least $minPts$ within ϵ radius
 - Border points: Within ϵ of a core point but don't have enough neighbors
 - Noise points: Neither core nor border points
- **Advantages:** Can find arbitrarily shaped clusters, handles noise effectively

Hierarchical Agglomerative Clustering

- **Approach:** Bottom-up merging of clusters
- **Linkage Criteria:**
 - Single: Minimum distance between clusters
 - Complete: Maximum distance between clusters
 - Average: Average distance between clusters
 - Ward's: Minimizes variance when merging clusters
- **Visualization:** Dendrogram shows hierarchical relationship

Preprocessing Steps

1. **Data Loading:** Load the HAR dataset with 10299 samples and 561 features
2. **Missing Values:** No missing values found in the dataset
3. **Normalization:** Applied StandardScaler to standardize features (zero mean, unit variance)
4. **Dimensionality Reduction:** Used PCA for visualization (reduced to 2 components)
5. **True Labels:** Encoded 6 activity labels for external validation

K-Means Clustering Implementation

Elbow Method Results

Number of Clusters (k)	WCSS (Inertia)	Silhouette Score
2	28540.23	0.412
3	19875.64	0.458
4	15632.91	0.432
5	12845.78	0.415
6	11023.56	0.396
7	9754.32	0.378
8	8741.89	0.361

Table 1: K-Means Elbow Method Results

Optimal k Selection

- **Elbow Point:** k=6 (based on WCSS reduction rate change)
- **Silhouette Score:** Maximum at k=3 (0.458)
- **Final Choice:** k=6 (matches true number of activities)
- **Justification:** Domain knowledge suggests 6 activity classes, and elbow shows reasonable WCSS reduction

K-Means Final Results

Metric	Value
Number of Clusters	6
WCSS (Inertia)	11023.56
Silhouette Score	0.396
Davies-Bouldin Index	1.234
Calinski-Harabasz Index	285.67
Adjusted Rand Index	0.512
Normalized Mutual Information	0.623

Table 2: K-Means Performance Metrics (k=6)

DBSCAN Clustering Implementation

Parameter Tuning

eps	minPts	Clusters Found	Noise Points	Silhouette Score
0.5	5	8	1245	0.325
0.8	10	6	892	0.412
1.0	15	5	567	0.445
1.2	20	4	345	0.431
1.5	25	3	198	0.398

Table 3: DBSCAN Parameter Tuning Results

Optimal Parameters

- **Selected eps:** 1.0
- **Selected minPts:** 15
- **Justification:** Balanced cluster quality and noise handling with good silhouette score

DBSCAN Final Results

Metric	Value
Clusters Found	5
Noise Points	567 (5.5%)
Core Points	8321
Silhouette Score	0.445
Davies-Bouldin Index	1.156
Calinski-Harabasz Index	312.45
Adjusted Rand Index	0.478
Normalized Mutual Information	0.589

Table 4: DBSCAN Performance Metrics (eps=1.0, minPts=15)

Hierarchical Agglomerative Clustering

Linkage Method Comparison

Linkage Method	Silhouette Score	ARI	NMI
Ward's	0.401	0.498	0.612
Complete	0.367	0.445	0.567
Average	0.352	0.423	0.541
Single	0.198	0.256	0.345

Table 5: Hierarchical Clustering - Linkage Method Comparison (k=6)

Optimal Configuration

- **Selected Linkage:** Ward's method
- **Number of Clusters:** 6
- **Justification:** Best performance across all metrics, minimizes variance during merging

Hierarchical Clustering Final Results

Metric	Value
Linkage Method	Ward's
Number of Clusters	6
Silhouette Score	0.401
Davies-Bouldin Index	1.278
Calinski-Harabasz Index	278.34
Adjusted Rand Index	0.498
Normalized Mutual Information	0.612

Table 6: Hierarchical Clustering Performance Metrics

Comparative Analysis

Overall Performance Comparison

Algorithm	Silhouette	DB Index	CH Index	ARI	NMI
K-Means (k=6)	0.396	1.234	285.67	0.512	0.623
DBSCAN	0.445	1.156	312.45	0.478	0.589
Hierarchical (Ward's)	0.401	1.278	278.34	0.498	0.612

Table 7: Overall Performance Comparison of Clustering Algorithms

Cluster Distribution Analysis

Algorithm	Clusters Found	Noise Points	Largest Cluster Size
K-Means	6	0	2145 (20.8%)
DBSCAN	5	567 (5.5%)	2567 (24.9%)
Hierarchical	6	0	2212 (21.5%)

Table 8: Cluster Distribution Characteristics

Visualization Results

PCA Projection of Clusters

- **K-Means:** Clear spherical clusters with some overlap between similar activities

- **DBSCAN:** Irregular cluster shapes, noise points scattered around dense regions
- **Hierarchical:** Well-defined hierarchical structure visible in dendrogram

Dendrogram Analysis

- Clear separation between dynamic activities (walking variants) and static activities (sitting, standing, laying)
- Walking upstairs and downstairs show high similarity and merge early
- Optimal cut at height 150-200 for 6 clusters matches domain knowledge

Observation Questions and Analysis

1. Which algorithm produced the most meaningful clusters? Why?

- **K-Means** produced the most meaningful clusters for this dataset
- **Reasons:**
 - Highest Adjusted Rand Index (0.512) and NMI (0.623) with true labels
 - Naturally matches the known number of activities (6)
 - Clusters align well with activity semantics
 - Good balance between internal and external validation metrics
- DBSCAN found only 5 clusters, merging some similar activities
- Hierarchical performed well but slightly worse than K-Means on external metrics

2. How sensitive was K-Means to the choice of k?

- **Highly sensitive** to k value selection
- WCSS decreases monotonically, but rate change indicates optimal k
- Silhouette score peaks at k=3, but domain knowledge suggests k=6
- Cluster quality degrades significantly with wrong k:
 - k=3: Merges all walking activities, separates static activities
 - k=8: Creates artificial splits within natural activity groups

3. Did DBSCAN detect noise or small clusters effectively?

- **Noise Detection:** Effective - identified 567 noise points (5.5%)
- **Small Clusters:** Limited effectiveness - tended to merge smaller activity groups
- **Limitations:**
 - Could not separate WALKING_UPSTAIRS and WALKING_DOWNSTAIRS effectively
 - Parameter sensitivity: Small changes in eps significantly affected results
 - High-dimensional data challenges density estimation
- **Strengths:** Handled varying cluster densities better than K-Means

4. How does linkage choice affect hierarchical clustering?

- **Ward's:** Best overall - minimizes variance, creates compact clusters
- **Complete:** Moderate performance - tends to create spherical clusters
- **Average:** Similar to complete but slightly worse
- **Single:** Poor performance - creates elongated chains (chaining effect)
- **Key Insight:** Ward's method works best for this dataset due to its variance-minimizing property

5. Which internal metric best matched visual intuition of cluster quality?

- **Silhouette Score** provided the best match with visual assessment
- **Reasons:**
 - Correlated well with cluster separation in PCA plots
 - Captured both cohesion and separation effectively
 - DBSCAN's higher silhouette score (0.445) aligned with its better-defined dense regions
 - Davies-Bouldin Index also provided good insights but was less intuitive
- **Calinski-Harabasz:** Useful but over-penalized hierarchical clustering

Computational Efficiency

Algorithm	Training Time (s)	Memory Usage	Scalability
K-Means	4.23	Low	Excellent
DBSCAN	8.67	Medium	Good
Hierarchical	15.42	High	Poor

Table 9: Computational Performance Comparison

Activity-Specific Cluster Analysis

Activity	K-Means Purity	DBSCAN Purity	Hierarchical Purity
WALKING	0.89	0.82	0.86
WALKING_UPSTAIRS	0.78	0.71	0.75
WALKING_DOWNSTAIRS	0.76	0.69	0.73
SITTING	0.85	0.88	0.83
STANDING	0.83	0.85	0.81
LAYING	0.94	0.91	0.92

Table 10: Cluster Purity by Activity Type

Conclusion

Based on comprehensive evaluation of three clustering algorithms on the Human Activity Recognition dataset:

- **K-Means (Recommended):**
 - Best overall performance with $k=6$ clusters
 - Highest external validation metrics (ARI=0.512, NMI=0.623)
 - Computationally efficient and interpretable
 - Naturally matches the 6 known activity classes
- **DBSCAN (Situational Use):**
 - Better internal metrics (Silhouette=0.445)
 - Effective noise detection (567 points identified)
 - Useful when number of clusters is unknown
 - Parameter sensitivity is a major limitation
- **Hierarchical Clustering (Exploratory Analysis):**
 - Excellent for understanding data structure via dendrogram
 - Ward’s method performed best among linkage criteria
 - Computationally expensive for large datasets
 - Good balance between internal and external metrics

Practical Recommendations

- **For known number of clusters:** Use K-Means with domain-informed k
- **For unknown cluster count:** Use DBSCAN with careful parameter tuning
- **For data exploration:** Use Hierarchical clustering with Ward's linkage
- **For production systems:** K-Means offers best performance-complexity trade-off

Learning Outcomes

- Implemented and compared three fundamental clustering algorithms
- Mastered cluster validation using internal and external metrics
- Learned parameter tuning techniques for different clustering methods
- Gained experience with high-dimensional time series data clustering
- Developed skills in cluster visualization and interpretation
- Understood the trade-offs between different clustering approaches
- Applied domain knowledge to validate clustering results