

docker exec

VIA: <https://docs.docker.com/engine/reference/commandline/exec/>

Run a command in a running container

- i, --interactive Keep STDIN open even if not attached
- t, --tty Allocate a pseudo-TTY
- c Run many commands:

USO: `docker exec [OPTIONS] CONTAINER COMMAND [ARG...]`

Permite ejecutar un comando en un contenedor lanzado.

sqlplus /nolog

VIA: https://docs.oracle.com/cd/B19306_01/server.102/b14238/smtosp.htm

If you want SQLPlus to behave in the same way as Server Manager, then use the *NOLOG* option when you start SQLPlus. SQL*Plus starts and you can use the *CONNECT* command to connect as a user.

USO: `sqlplus /nolog`

Lanza la aplicación de SQLPLUS por la cual se puede conectar a una BBDD e interactuar con ella empleando SQL.

connect

VIA: https://docs.oracle.com/cd/B19306_01/server.102/b14238/smtosp.htm

VIA: <https://docs.oracle.com/database/121/ADMQS/GUID-DE8A79BD-FAE4-4364-98FF-D2BD992A06E7.htm>

To start Server Manager, enter the name of the Server Manager program at a system prompt; the name of this program is operating system-specific. After you start up Server Manager, connect using the *CONNECT* command.

USO: dos opciones válidas:

`CONNECT hr/hr` o `CONNECT hr AS hr`

Tras haber lanzado el comando de sqlplus, esta opción nos permite conectar a una BBDD concreta con un usuario determinado.