



Garza, Itzel &lt;igarza8@cps.edu&gt;

## Forms of Programming

1 message

Google Forms <forms-receipts-noreply@google.com>  
To: igarza8@cps.edu

Wed, Sep 4, 2024 at 1:51 PM

Thanks for filling out [Forms of Programming](#)

Here's what was received.

[View score](#)

## Forms of Programming

Email \*

[igarza8@cps.edu](mailto:igarza8@cps.edu)

1. As a programmer, some forms of programming give you direct access to the \_\_\_\_\_ while others abstract the hardware into more \_\_\_\_\_ that needs to be translated or converted into the \_\_\_\_\_ of the hardware. \*

- ☒ computer processor; human language; native language
- ☐ computer hardware; computer code; machine language
- ☐ CPU; programming language; compiled code
- ☐ RAM; binary code; operating system

2. \_\_\_\_\_ allow programmers to code instructions directly to the processor or hardware. \*

- ☒ Machine languages
- ☐ Interpreted languages
- ☐ Assembly languages
- ☐ Scripting languages

3. \_\_\_\_\_ can be programmed by sending sequences and patterns of bits through the processor to enable actions to take place. \*

- ☒ Processors
- ☐ Compilers
- ☐ Interpreters
- ☐ Assemblers

4. \_\_\_\_\_, which is an abstraction of machine language, uses codes to modify processor registers and perform functions. \*

- ☒ Assembly languages
- ☐ High-level languages
- ☐ Machine languages
- ☐ Object-oriented languages

5. \_\_\_\_\_ are readable by humans more easily than assembly or machine languages. \*

- ☒ Interpreted languages
- ☐ Compiled languages

- ☐ Machine languages
- ☐ Low-level languages

6. A \_\_\_\_\_ called an interpreter reads each line of code and then interprets it into native instructions for the computer. The process is much slower than \_\_\_\_\_ since the interpreter needs to convert each instruction provided by the programmer. \*

- ☒ component; machine language
- ☐ processor; assembly language
- ☐ compiler; machine code
- ☐ transistor; binary language

7. \_\_\_\_\_ is an example of an \_\_\_\_\_ language. A programmer can stop the execution of the program, make a change to a line, and then run it again without any other steps. \*

- ☒ JavaScript; interpreted
- ☐ C++; compiled
- ☐ Python; compiled
- ☐ HTML; scripting

8. A \_\_\_\_\_ language takes instructions written by a human and sends that code to something called a \_\_\_\_\_. \*

- ☒ compiled; compiler
- ☐ scripting; parser
- ☐ assembly; interpreter

☐ interpreted; assembler

9. A \_\_\_\_\_ takes the program instructions and converts it to \_\_\_\_\_ or native code for the hardware and creates a program called an \_\_\_\_\_. \*

☒ compiler; binary; executable

☐ interpreter; assembly; script

☐ assembler; text; application

☐ linker; hex; batch file

10. \_\_\_\_\_ is native to the hardware and operating system and can't easily be converted back to the original program instructions. \*

☒ This program

☐ Machine code

☐ Source code

☐ Assembly code

11. \_\_\_\_\_ is an example of a compiled language. \*

☒ C

☐ Python

☐ JavaScript

☐ Ruby

12. \_\_\_\_\_, or OOP, treats everything as an object. \*

☒ Object-oriented programming

- ☐ Functional programming
- ☐ Procedural programming
- ☐ Assembly language

13. \_\_\_\_\_ and \_\_\_\_\_ are examples of object-oriented languages. \*

- ☒ Java; C#
- ☐ Python; SQL
- ☐ HTML; CSS
- ☐ Assembly; COBOL

14. \_\_\_\_\_ is a language designed for working with databases. \*

- ☒ SQL or sequel
- ☐ Python
- ☐ JavaScript
- ☐ Bash

15. What are scripting languages? \*

- ☒ Languages designed for automating tasks
- ☐ Languages that compile to binary
- ☐ Languages that directly modify hardware
- ☐ Languages used for creating hardware drivers

Report Abuse