

# Exactly Sparse Memory Efficient SLAM using the Multi-Block Alternating Direction Method of Multipliers: Supplementary Material

Siddharth Choudhary, Luca Carbone, Henrik I. Christensen, Frank Dellaert \*†

In the supplementary material, we present additional results on large synthetic grid graphs. We consider a manhattan world with poses arranged as a regular grid. Each node in the grid is connected to all of its four neighbors. We ran all approaches on a single thread on a desktop using Ubuntu 14.04 with Intel(R) Core(TM) i7-3770 CPU running at 3.40GHz.

Figure 1 shows the results on  $48 \times 48$  grid ( $n = 2401$ ,  $m = 4074$ ) which is divided into subgraphs of size  $12 \times 12$ . Figure 2 shows the results on  $150 \times 150$  grid ( $n = 22801$ ,  $m = 45300$ ) which is divided into subgraphs of size  $30 \times 30$ . Additionally the figures show the subgraph estimates after 20 and 100 iterations of ADMM-adapt algorithm and the time taken per iteration (in seconds).

Figure 3 shows the results on  $210 \times 210$  grid ( $n = 44521$ ,  $m = 88620$ ), figure 4 shows the results on  $270 \times 270$  grid ( $n = 73441$ ,  $m = 146340$ ) and figure 5 shows the results on  $361 \times 361$  grid ( $n = 130321$ ,  $m = 259920$ ) which are divided into subgraphs of size  $30 \times 30$ .




Figure 1: (a)  $\chi^2$  error comparing the proposed approach (ADMM-adapt) against the final error of a centralized solver. (b) Initial guess, (c,d) ADMM-adapt estimate at different iterations (synthetic dataset), (e) time taken per iteration (in sec). Each subgraph is shown in a different color. The size of the graph is  $48 \times 48$  ( $n = 2401$ ,  $m = 4074$ ) which is divided into subgraphs of size  $12 \times 12$ .




Figure 2: (a)  $\chi^2$  error comparing the proposed approach (ADMM-adapt) against the final error of a centralized solver. (b) Initial guess, (c,d) ADMM-adapt estimate at different iterations (synthetic dataset), (e) time taken per iteration (in sec). Each subgraph is shown in a different color. The size of the graph is  $150 \times 150$  ( $n = 22801$ ,  $m = 45300$ ) which is divided into subgraphs of size  $30 \times 30$ .

\*This work was partially funded by the ARL MAST CTA Project 1436607 “Autonomous Multifunctional Mobile Microsystems” and by the National Science Foundation Award 11115678 “RI: Small: Ultra-Sparsifiers for Fast and Scalable Mapping and 3D Reconstruction on Mobile Robots”.

†S. Choudhary, L. Carbone, H. I. Christensen, and F. Dellaert are with the College of Computing, Georgia Institute of Technology, Atlanta, GA, USA, {siddharth.choudhary,luca.carbone}@gatech.edu, {hic,frank}@cc.gatech.edu.




Figure 3: (a)  $\chi^2$  error comparing the proposed approach (ADMM-adapt) against the final error of a centralized solver, (b) time taken per iteration (in sec) for the graph of size  $210 \times 210$  ( $n = 44521$ ,  $m = 88620$ ) which is divided into subgraphs of size  $30 \times 30$ .




Figure 4:  $\chi^2$  error comparing the proposed approach (ADMM-adapt) against the final error of a centralized solver, (b) time taken per iteration (in sec) for the graph of size  $270 \times 270$  ( $n = 73441$ ,  $m = 146340$ ) which is divided into subgraphs of size  $30 \times 30$ .




Figure 5:  $\chi^2$  error comparing the proposed approach (ADMM-adapt) against the final error of a centralized solver, (b) time taken per iteration (in sec) for the graph of size  $360 \times 360$  ( $n = 130321$ ,  $m = 259920$ ) which is divided into subgraphs of size  $30 \times 30$ .