



BITS Pilani
Pilani Campus

Applied Machine Learning


Dr. Harikrishnan N B
Computer Science and Information Systems



SE ZG568 / SS ZG568, Applied Machine Learning Lecture No. 16

Human Brain






Frontal Lobe

Frontal Lobe

Motor Functions


Planning, Emotions, Social Behaviour



Parietal Lobe

Parietal Lobe


Sensations, touch, pain



Temporal Lobe

Temporal Lobe


Hearing, Memory



Occipital Lobe

Occipital Lobe

Vision, optic nerve arising from retina goes to occipital lobe through other lobes.




Brain Stem

Brain Stem

Mid Brain - controls eye movement

Pons - controls facial movement

Medulla Oblongata - control of respiration




86 billion neurons


Patient HM and Memory

Patient HM (Henry Molaison) and Memory:


<https://www.youtube.com/watch?v=i488aUN5RXA>




Lobes



Lobes




Neural Circuit



Brain: The Ultimate Machine

- High complexity (non-linear)
- Very high neural noise and interference
- Very low SNR: -29 dB to -20 dB*
- Neural signal multiplexing[†]
- Low power “neural computation” (~12.6 Watts^{**})
- How does it work? No idea!



***Ref:** G. Czanner et al., Measuring the signal-to-noise ratio of a neuron, PNAS 112 (23), 2015

[†]**Ref:** M L R Meister et al., Signal multiplexing and single-neuron computations in Lateral Intraparietal Area during decision-making, J. Neurosci. 33 (6), 2013

^{**}**Ref:** Scientific American, 18 July 2012

Neuroscience Inspired AI

- Rich source of inspiration for new types of algorithms and architectures, independent and complementary to the mathematical and logic based methods.
- Neuroscience can provide a validation of AI techniques that already exists.

Reinvestigate the current learning algorithms

- Brain science is still in *Faraday Stage* [1]
- Brain has ~86 billion neurons [2]
- Complex network of neurons
- Neurons are inherently **non-linear** & found to exhibit **Chaos**
- ***Current AI only loosely inspired from the brain***

1. Ramachandran, Vilayanur S., Sandra Blakeslee, and Neil Shah. *Phantoms in the brain: Probing the mysteries of the human mind*. 1998.
2. Azevedo, Frederico AC, et al. "Equal numbers of neuronal and nonneuronal cells make the human brain an isometrically scaled-up primate brain." *Journal of Comparative Neurology* 513.5 (2009): 532-541.

Artificial vs. Biological Neural Networks

Research and Development Gap

Artificial Neural Networks (ANN) ✓	Biological Neural Networks
Linearity + Non-linear activation.	Non-linearity at the neuronal level. [3, 4] ○
Current deep learning architectures does not exhibit chaotic behaviour at the neuronal level for classification.	Exhibits different behaviours - from periodic to chaotic at different spatiotemporal scales.
Not robust to noise. ✓	Robust to noise and interference. ✓
Need huge amount of training data.	Learning from limited samples.

3. Faure, Philippe, and Henri Korn. "Is there chaos in the brain? I. Concepts of nonlinear dynamics and methods of investigation."

Comptes Rendus de l'Académie des Sciences-Series III-Sciences de la Vie 324.9 (2001): 773-793.

4. Korn, Henri, and Philippe Faure. "Is there chaos in the brain? II. Experimental evidence and related models." *Comptes rendus biologies* 326.9 (2003): 787-

840.

4 data instance

3 features

2 layer NN

3 Nodes in the i/p layer



$y^{(i)} \in \{0, 1\}$

0.2 Analysis of a 2-Layer Neural Network

Input Layer

Hidden Layer

Output Layer



classification
→ Binary


2 layer NN architecture

$y^{(1)}$
 $y^{(2)}$
 $y^{(3)}$
 $y^{(4)}$

Example

0.2 Analysis of a 2-Layer Neural Network

Input Layer Hidden Layer Output Layer



Forward Propagation


Computation of Loss

Backward Propagation

Update of Weights and Bias

Tetris


i/p
layer



Forward Propagation

0.2 Analysis of a 2-Layer Neural Network

Input Layer Hidden Layer Output Layer



Hidden Layer 1 and Neuron 1

oth data instance



$$\sigma(w_{31}^{(1)} x_1^{(i)} + w_{32}^{(1)} x_2^{(i)} + w_{33}^{(1)} x_3^{(i)} + b_3^{(1)})$$

$$\sigma(w_{41}^{(1)} x_1^{(i)} + w_{42}^{(1)} x_2^{(i)} + w_{43}^{(1)} x_3^{(i)} + b_4^{(1)})$$

$$\sigma(w_{21}^{(1)} x_1^{(i)} + w_{22}^{(1)} x_2^{(i)} + w_{23}^{(1)} x_3^{(i)} + b_2^{(1)})$$

[1] → Layer
 w_{13} → bias which i/p is
 under of the
 the neuron in the first
 hidden layer
 i/p is
 contribute to
 the neuron.

$$(h_1) \Rightarrow w_{11}^{(1)} x_1^{(i)} + w_{12}^{(1)} x_2^{(i)} + w_{13}^{(1)} x_3^{(i)} + b_1^{(1)}$$

(activation sigmoidal activation)

$$a_1^{[1]} = \sigma(w_{11}^{[1]} x_1 + w_{12}^{[1]} x_2 + w_{13}^{[1]} x_3 + b_1^{[1]})$$

weights & bias are learnable

$$a_2^{[1]}$$

$$a_3^{[1]}$$

$$a_4^{[1]}$$

$$h_1 \quad a_1^{[1]}$$

$$h_2 \quad a_2^{[1]}$$

$$h_3 \quad a_3^{[1]}$$

$$h_4 \quad a_4^{[1]}$$

$$y = \sigma(w_{11}^{[2]} a_1^{[1]} + w_{12}^{[2]} a_2^{[1]} + w_{13}^{[2]} a_3^{[1]} + w_{14}^{[2]} a_4^{[1]} + b_1^{[2]})$$

y
o/p neuron

Layer 2


$$x^{(i)} = \begin{bmatrix} x_1^{(i)} \\ x_2^{(i)} \\ x_3^{(i)} \end{bmatrix}$$

$$W^{[1]} x^{(i)} + b^{[1]}$$

For our example, $m = 4$, $n = 3$ and $n_h = 4$. We get the following matrices.

0.2 Analysis of a 2-Layer Neural Network

Input Layer Hidden Layer Output Layer



$$W^{[1]} = \begin{bmatrix} w_{11}^{[1]} & w_{12}^{[1]} & w_{13}^{[1]} \\ w_{21}^{[1]} & w_{22}^{[1]} & w_{23}^{[1]} \\ w_{31}^{[1]} & w_{32}^{[1]} & w_{33}^{[1]} \\ w_{41}^{[1]} & w_{42}^{[1]} & w_{43}^{[1]} \end{bmatrix}$$

$$W^{[2]} = \begin{bmatrix} w_{11}^{[2]} & w_{12}^{[2]} & w_{13}^{[2]} & w_{14}^{[2]} \end{bmatrix}$$

$$b^{[1]} = \begin{bmatrix} b_1^{[1]} \\ b_2^{[1]} \\ b_3^{[1]} \\ b_4^{[1]} \end{bmatrix}$$

$$b^{[2]} = \begin{bmatrix} b_1^{[2]} \end{bmatrix}$$



$$W^{[2]} = \begin{bmatrix} w_{11}^{[2]} & w_{12}^{[2]} & w_{13}^{[2]} & w_{14}^{[2]} \\ w_{21}^{[2]} & w_{22}^{[2]} & w_{23}^{[2]} & w_{24}^{[2]} \end{bmatrix} \quad b^{[2]} = [b_1^{[2]}]$$

$$W^{[1]} = \begin{bmatrix} w_{11}^{[1]} & w_{12}^{[1]} & w_{13}^{[1]} \\ w_{21}^{[1]} & w_{22}^{[1]} & w_{23}^{[1]} \\ w_{31}^{[1]} & w_{32}^{[1]} & w_{33}^{[1]} \\ w_{41}^{[1]} & w_{42}^{[1]} & w_{43}^{[1]} \end{bmatrix} \quad b^{[1]} = \begin{bmatrix} b_1^{[1]} \\ b_2^{[1]} \\ b_3^{[1]} \\ b_4^{[1]} \end{bmatrix}$$


Applying sigmoidal on each row

$$A^{[1]} = \sigma \left(W^{[1]} x^{(i)} + b^{[1]} \right) = \begin{bmatrix} w_{11}^{[1]} x_1^{(i)} + w_{12}^{[1]} x_2^{(i)} + w_{13}^{[1]} x_3^{(i)} + b_1^{[1]} \\ w_{21}^{[1]} x_1^{(i)} + w_{22}^{[1]} x_2^{(i)} + w_{23}^{[1]} x_3^{(i)} + b_2^{[1]} \\ w_{31}^{[1]} x_1^{(i)} + w_{32}^{[1]} x_2^{(i)} + w_{33}^{[1]} x_3^{(i)} + b_3^{[1]} \\ w_{41}^{[1]} x_1^{(i)} + w_{42}^{[1]} x_2^{(i)} + w_{43}^{[1]} x_3^{(i)} + b_4^{[1]} \end{bmatrix} = \begin{bmatrix} a_1^{[1]} \\ a_2^{[1]} \\ a_3^{[1]} \\ a_4^{[1]} \end{bmatrix}$$

$$\sigma \left(W^{[2]} A^{[1]} + b^{[2]} \right) = y$$

0.2 Analysis of a 2-Layer Neural Network

Input Layer Hidden Layer Output Layer



$$Z^{[1](i)} = W^{[1]}x^{(i)} + b^{[1]}$$

$$a^{[1](i)} = \sigma(Z^{[1](i)})$$

$$Z^{[2](i)} = W^{[2]}a^{[1](i)} + b^{[2]}$$

$$a^{[2](i)} = \sigma(Z^{[2](i)})$$

input instance

Computation of Loss

$$a_1^{[2](i)} = \sigma(w_{11}^{[2]} a_1^{[1](i)} + w_{12}^{[2]} a_2^{[1](i)} + w_{14}^{[2]} a_4^{[1](i)} + b_1^{[2]})$$

Let the total loss be denoted by J .

J depends on

$a_1^{[2](i)}$

$w_{11}^{[2]}$

$$J = \frac{1}{m} \sum_{i=1}^m L(\hat{y}^{(i)}, y^{(i)})$$

is 1 to m
considering all
training data

$$J = \frac{1}{m} \sum_{i=1}^m L(a_1^{[2](i)}, y^{(i)}) = -\frac{1}{m} \sum_{i=1}^m (y^{(i)} \log(a_1^{[2](i)}) + (1 - y^{(i)}) \log(1 - a_1^{[2](i)}))$$

update

my weight & bias
so that my J will be min

binary cross entropy!

Backpropagation

$$\frac{\partial J}{\partial w^{(1)}}, \frac{\partial J}{\partial w^{(2)}}, \frac{\partial J}{\partial b^{(1)}}, \frac{\partial J}{\partial b^{(2)}}$$

Objective is to compute the following:

$$\frac{\partial J}{\partial w^{(1)}}, \frac{\partial J}{\partial w^{(2)}}, \frac{\partial J}{\partial b^{(1)}}, \frac{\partial J}{\partial b^{(2)}}$$

For the i^{th} training data, we can calculate the gradient for $w_{11}^{(2)}$ using chain rule as follows:

$$\frac{\partial J^{(i)}}{\partial w_{11}^{(2)}} = \frac{\partial J^{(i)}}{\partial a^{(2)(i)}} \times \frac{\partial a^{(2)(i)}}{\partial z^{(2)(i)}} \times \frac{\partial z^{(2)(i)}}{\partial w_{11}^{(2)}}$$

$$da^{(2)(i)} = \frac{\partial J^{(i)}}{\partial a^{(2)(i)}} = \frac{-y^{(i)}}{a^{(2)(i)}} + \frac{1-y^{(i)}}{1-a^{(2)(i)}}$$

$$\frac{\partial a^{(2)(i)}}{\partial z^{(2)(i)}} = a^{(2)(i)}(1-a^{(2)(i)})$$

$$\frac{\partial z^{(2)(i)}}{\partial w_{11}^{(2)}} = a_1^{(1)}$$

$$dw_{11}^{(2)} = \frac{\partial J^{(i)}}{\partial w_{11}^{(2)}} = \frac{-y^{(i)}}{a^{(2)(i)}} + \frac{1-y^{(i)}}{1-a^{(2)(i)}} \times a^{(2)(i)}(1-a^{(2)(i)}) \times a_1^{(1)}$$

$$= (-y^{(i)} + a^{(2)(i)})a_1^{(1)}$$


Now, extending the same for the other weights:

$$\frac{\partial J^{(i)}}{\partial w_{12}^{(2)}} = (-y^{(i)} + a^{(2)(i)})a_2^{(1)}$$

$$a_1 = \sigma(z_1^{(2)})$$

0.2 Analysis of a 2-Layer Neural Network

Input Layer Hidden Layer Output Layer



$$\frac{\partial J}{\partial w_{11}^{(2)}}$$

$$z_1^{(2)} = w_{11}^{(2)} a_1^{(1)} + w_{12}^{(2)} a_2^{(1)} + w_{13}^{(2)} a_3^{(1)} + w_{14}^{(2)} a_4^{(1)} + b_1^{(2)}$$

We can continue this gradient calculation to get the gradients corresponding to the weights and biases to the hidden layer:

$$\frac{\partial J^{(i)}}{\partial w_{11}^{[1]}} = (a^{[2](i)} - y^{(i)})w_{11}^{[2]}a_1^{[1](i)}(1 - a_1^{[1](i)})x_1^{(i)}$$

$$\frac{\partial J^{(i)}}{\partial w_{12}^{[1]}} = (a^{[2](i)} - y^{(i)})w_{11}^{[2]}a_1^{[1](i)}(1 - a_1^{[1](i)})x_2^{(i)}$$

$$\frac{\partial J^{(i)}}{\partial w_{21}^{[1]}} = (a^{[2](i)} - y^{(i)})w_{12}^{[2]}a_2^{[1](i)}(1 - a_2^{[1](i)})x_1^{(i)}$$

$$\frac{\partial J^{(i)}}{\partial w_{22}^{[1]}} = (a^{[2](i)} - y^{(i)})w_{12}^{[2]}a_2^{[1](i)}(1 - a_2^{[1](i)})x_2^{(i)}$$

We can continue this gradient calculation to get the gradients corresponding to the weights and biases to the hidden layer:

$$\frac{\partial J^{(i)}}{\partial w_{11}^{[1]}} = (a^{[2](i)} - y^{(i)})w_{11}^{[2]}a_1^{[1](i)}(1 - a_1^{[1](i)})x_1^{(i)}$$

$$\frac{\partial J^{(i)}}{\partial w_{12}^{[1]}} = (a^{[2](i)} - y^{(i)})w_{11}^{[2]}a_1^{[1](i)}(1 - a_1^{[1](i)})x_2^{(i)}$$

$$\frac{\partial J^{(i)}}{\partial w_{21}^{[1]}} = (a^{[2](i)} - y^{(i)})w_{12}^{[2]}a_2^{[1](i)}(1 - a_2^{[1](i)})x_1^{(i)}$$

$$\frac{\partial J^{(i)}}{\partial w_{22}^{[1]}} = (a^{[2](i)} - y^{(i)})w_{12}^{[2]}a_2^{[1](i)}(1 - a_2^{[1](i)})x_2^{(i)}$$

Weight Updation

gradient descent

1 forward
1 back ward } 1 epoch

↓
1 weight
update

100 epochs


$$W^{[1]} \leftarrow W^{[1]} - \alpha \frac{\partial J}{\partial W^{[1]}}$$

$$W^{[2]} \leftarrow W^{[2]} - \alpha \frac{\partial J}{\partial W^{[2]}}$$

$$b^{[1]} \leftarrow b^{[1]} - \alpha \frac{\partial J}{\partial b^{[1]}}$$

$$b^{[2]} \leftarrow b^{[2]} - \alpha \frac{\partial J}{\partial b^{[2]}}$$

$$n=4 \quad \vec{x} = \begin{bmatrix} x_1 \\ x_2 \\ x_3 \\ \vdots \\ x_n \end{bmatrix}$$



$$\frac{dx(t)}{dt} = \frac{x(t+1) - x(t)}{\Delta t} \quad 1$$

$$\rightarrow \begin{bmatrix} x_2 - x_1 \\ x_3 - x_2 \\ \vdots \\ x_n - x_{n-1} \end{bmatrix}_{3 \times 7} \quad n=4$$

$$\underline{\underline{D}}_{3 \times 4} \begin{bmatrix} x_1 \\ x_2 \\ x_3 \\ x_4 \end{bmatrix}_{4 \times 1} =$$

Neural N/ws

forward Propagation, Computation of loss
Backward ", weight updation.