2023 International Conference on Emerging Research in Computational Science (ICERCS) | 979-8-3503-5976-3/23/$31.00 ©2023 IEEE | DOI: 10.1109/ICERCS57948.2023.10433994

Prediction of Major Wave Heights from Scatterometry measurement Data via Machine Learning Mode

[1st]Hasan Harith Jameel Mahdi
Computer Technologies Engineering, Al-Turath University College
Baghdad,Iraq
*hasan.harith@turath.edu.iq

[2nd]Ammar H. Shnawa
Department of Medical Devices Engineering Technologies, National University of Science and Technology
Dhi Qar, Nasiriyah, Iraq
ammar.h.shnawa@nust.edu.iq

[3rd]Ragheed Hussam
Medical instruments engineering techniques, Al-farahidi University
Baghdad, Iraq
Ragheed Hussam@uoalfarahidi.edu.iq

[4th]Raaid Alubady
Technical Engineering College, Al-Ayen University
Thi-Qar, Iraq
alubadyraaid@alayen.edu.iq

[5th]Mustafa Al-Tahee
Technical Computer Engineering Department, Al-Kunooze University College
Basrah, Iraq
Mustafa .Al-Tahee@ kunoozu .edu.Iq

[6th]Imad Matti
computer Technology Engineering,Al-Maamoun University College
Baghdad,Iraq
Imad.m.bko@almamonuc.edu.iq

***Abstract*— Scatterometry (SC) is a microwave radar sensor that scans the surface from an aircraft or a satellite and measures the normalizing radar crossing section of the surface; the scatterometer can measure wave height and other pertinent data, although the altimeter is more limited in its scope. Presently, the challenging characteristics in scatterometry measurement data, which include natural energy intensity, wind speed stability, improper disaster management, earth atmosphere, predicting ocean current wave height from the observed challenges in this research developing an improved machine learning (MLSC) assisted scatterometer data allows a network program to learn and adapt to new data without the need for human intervention. It keeps a device's built-in algorithms up to date regardless of changes in the global economy. In machine learning-enabled scatterometry data, supervised learning (SL) has been proposed to reduce the natural energy intensity in significant wave height scatterometry measurement and analyze the atmosphere and wind speed stability by improving remote sensing measurement data gathered by sensors. Reinforcement learning (RL) has been included, which helps to reduce the risk of controlling the improper disaster management to improve the predicting ocean current wave height with the impact of earth's atmosphere changes in the climate, the release of pollutants into the atmosphere condition, which helps to enhance the prediction of significant wave height form scatterometry measurement data. The experimental results show the proposed model improves natural energy intensity, wind speed stability, improper disaster management, earth atmosphere, and predicting current ocean waves in the reinforcement learning method.**

Index Terms: Scatterometry, Wave, SL, RL, ML, Remote sensing.

I. CONCEPT OF SCATTEROMETRY DATA IN WAVE HEIGHTS USING MACHINE LEARNING

Scatterometers can monitor sea conditions, and the investigation advances the use of scatterometers, as initially designed for wind-related investigations, to ocean wave work [1].The important effect in the dynamic maritime environment is sea surface wind. Sea surface wind and ocean wave retrievals can be obtained using scatterometers, radiometers, synthetic aperture radars, and altimeters, and this information is crucial for socioeconomic growth [2].Analyzing the long-term maximum wind speed generated from a combined scatterometer and a calibrated altimeter, the altimeter product is overestimated and higher than the scatterometer winds [3].Satellite systems for altimeters, radiometers, and scatterometers get the potential to save regional coverage and a record of these systems. The accuracy and depth of numerical models are improved, but they need to be tested against actual measurements [4].Wind energy development, weather forecasting, model validation, marine catastrophe monitoring, and wind climatology rely on precise wind speed and direction observations [5]. Winds and waves on the ocean's surface are crucial to the ocean's physical processes and habitat. Observations of air-sea interactions and catastrophe monitoring rely heavily on generating local wind waves by wind blowing on the sea's surface [6]. Doppler scatterometry is a possible way of measuring ocean surface currents and winds simultaneously. There are several uses for surface currents and winds, like determining the optimal operating conditions for marine vessels or monitoring material dispersion into the ocean [7]. Combining models and observations in remote sensing products can be useful for specific reasons [8].The back-scattering characteristics of the ocean surface are used in scatterometers to offer vital ocean surface wind information. Bragg scattering from wind-driven centimeter-scale capillary waves accounts for the findings' wind sensitivity [9].The surface wind speed and direction within tropical cyclones are crucial for various applications. The measured inflow angles ahead of the storm drop while those behind the storm grow as forwarding velocity and central pressure increase [10].

The main contribution of this article:

- Machine learning (ML) in scatterometry is an effective method for finding high frequency measuring capability of the current system in wave height.
- Supervised learning (SL) agents can perceive and interpret their environment, reduce natural energy intensity, and control wind speed stability.
- Reinforcement learning (RL) solves the problem by learning improper disaster management without labels and reducing the earth's atmosphere's concealing and distorting

979-8-3503-5976-3/23/$31.00©2023IEEE

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on January 12,2026 at 09:07:13 UTC from IEEE Xplore. Restrictions apply.

effect of ocean wave height series on increasing the ocean currents vital.

- The wave height based on MLSC can help promote scatterometry measurement data to predict significant wave height and quickly identify trends and patterns.

II. Discussion about the Scatterometry Measurement Data in Significant Wave Height

Xiaoyu Zhang et al. (2021) proposed an innovative approach for predicting ocean wave height series considered numerical long short-term memory (LSTM) [11]. In the structure of wave height representation, the LSTM algorithm represents a collection of measurements and the current wave height.

Sung-Hwan Park et al. (2021) introduced marine weather and disaster management to improve satellite-based sea wind measurements. The Advanced Scatterometer (ASCAT) has typically calibrated remote-sensed wind data using the linear regression technique. [12].

Xiaohui Li et al. (2021) detailed measuring sea surface wind speed using global navigation satellite system reflectometry (GNSS-R) satellites for coastal navigation [13]. The frequency of distinct stability conditions in coastal areas is critical information essential in local and microscale atmospheric circulation, including the wind field's stability.

Haijun Ye et al. (2021) mentioned the wind retrieval performance of the China-France Oceanography Satellite (CFOSAT) was assessed through the passage of tropical storms [14]. CFOSAT wind retrievals are found to be accurate enough for scientific investigation, although additional enhancements are needed to make them more precise.

Nikolaos Kokkos et al. (2021) initiated the power generation sector of Copernicus marine environmental service (CMEMS) to adopt a clean energy transition strategy, focusing on renewable energy sources [15]. In the absence of offshore meteorological stations, scatterometer data have been regularly used in literature to estimate large-scale wind resources.

Xingou Xu et al. (2021) [16] proposed the well-researched machine learning approach of support vector machines (SVM) to handle this hard problem in a regression based on data. SVM sources are thoroughly analyzed to ensure their suitability for the situation, and the system may be confidently implemented.

Wolfgang Matthias Klesse et al. (2020) [17] detailed laser stripping methods in microelectronics to produce device architectures in the nano-scale range to meet the ever-increasing need for smaller feature sizes. Micromechanical systems, semiconductors, lasers, and nano-scale devices use surface features in this size range. Precision in surface and reflectance measurements is so great that the resulting data does not adequately depict the process.

III. The Machine Learning-Based Prediction of Main Wave Height

Machine learning is used to forecast ocean wave conditions. Accurate representations of significant wave heights and periods can be utilized to anticipate ocean conditions through supervised training of machine learning models on several iterations of a physics-based wave model. The few practical uses of accurate wave height calculations in coastal waters include coastal engineering, environmental monitoring, coast protection, and maritime transportation and transportation by sea. The methods of scatterometry and machine learning that allow quick and accurate measurements of numerous parameters of interest at large samplings can be a focus of the current effort. A valuable technique for interpreting the data is a measurement space representation of the radar scattering quartets to overcome the problem in the proposed method, MLSC.

A. Artificial intelligence in pressure measurement using scatterometry based on ocean current wave height series

The below diagram describes the measurement of scatterometry in ocean currents.




Fig. 1. Machine learning method in predicting ocean currents

Figure 1 shows that artificial intelligence emulates human intellectual processes by machines, notably computer systems. Specific applications of ML include expert systems, natural language processing, speech recognition, and machine vision. In computing, an expert system is software that mimics human or organizational judgment and behavior via advanced technology. Planners work through exactly the need to reach the desired outcome. The earth's atmosphere acts as a comforter, shielding it from the sun's scorching rays and limiting the planet's temperature extremes. The vision statement outlines the future of the organization. This way, it acts as a lighthouse, indicating the organization's direction.

1) The derivatives of Machine learning wave height

$$A = h\left[1+\frac{E-1}{2}\right]f(a)\sqrt{1+E-1+\frac{(E-1)}{6}}\iint\frac{y_3-y^1}{6} = \frac{2h}{3} \quad (1)$$

As shown in equation (1), artificial intelligence boosts humanity's speed, precision, and $h\left[1+\frac{E-1}{2}\right]$efficacy. In current organizations, $f(a)$ AI approaches can predict the transactions are likely to be fraudulent, adopt rapid and accurate credit ratings, $\sqrt{1+E-1+\frac{(E-1)}{6}}$and automate manually demanding $\iint\frac{y_3-y^1}{6}$data administration activities, as represented in equation (2).

$$\mathrm{B} = I_2 = \left(\frac{I_2-I_1}{3}\right)\int(a+bx+cx^2)dx = \left[ax+\frac{bx^2}{2}+\frac{cx^2}{3}\right]+ 2ah\frac{d^2y}{dx^2} \quad (2)$$

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on January 12,2026 at 09:07:13 UTC from IEEE Xplore. Restrictions apply.

As shown in equation (2), vertical motion is intimately I_2linked to distinct weather systems$\left(\frac{I_2-I_1}{3}\right)$ and the intensity to measure a $(a+bx+cx^2)$atmospheric stability is the capacity of the atmosphere to discourage or inhibit vertical motion. Observers analyze$\left[ax+\frac{bx^2}{2}+\frac{cx^2}{3}\right]$ the temperature difference between a $2ah\frac{d^2y}{dx^2}$rising air parcel and its surrounding air at the same elevation to gauge atmospheric stability.

$$C=\cos\theta\frac{dy}{dx}\int\frac{1}{1+x}+\frac{h}{\log(1+\Delta)}\left[1+\frac{E-1}{2}\right]\Delta\log(y_x)+\tan-1\left(\frac{\alpha}{\beta}\right) \quad (3)$$

As shown in equation (3), thermal radiation, visible light, and ultraviolet light $\cos\theta\frac{dy}{dx}$ is shortwave radiation. The shortwave radiation is $\frac{1}{1+x}$is present on the earth's surface during the hours of$\frac{h}{\log(1+\Delta)}$ daylight. Light$\left[1+\frac{E-1}{2}\right]$ from the sun is the primary source $\Delta\log(y\ )$ of shortwave radiation. The majority of the light that travels $\tan-1\left(\frac{\alpha}{\beta}\right)$through the atmosphere to the earth's surface is absorbed, although a little amount is reflected in the sky, the next result is Supervised learning.

B. Supervised learning mode in disruption of the natural energy intensity by improving wind speed stability

Figure 2 denotes the disruption of the natural energy intensity by improving wind speed stability condition




Fig. 2. Supervised learning in natural energy intensity for improving wind speed stability

Figure 2 shows that supervised machine learning transforms raw data into valuable insights that can be applied right away. The data and companies can identify and avoid undesirable consequences or increase desired outcomes for their goal variable. Solar panel glass cells can develop microscopic fractures, hot spots, and cracks that can expand in size across time and reduce the efficiency of solar cells. A decision tree is a decision assistance tool that employs a tree-like model of decisions and probable outcomes, including chance event outcomes, resource costs, and utility.

1) The derivatives of the supervised learning method

$$D=\sum sin(\theta+\beta)=\frac{tan\,\alpha\,sin\,\beta}{\mu}\iint\frac{u\sin\alpha}{u+u\ \cos\theta}=\frac{\pi}{2}\left(x_n+\frac{N}{x_n}\right) \quad (4)$$

As shown in equation (4), an algorithm considered as Classification is a$\sum sin(\theta+\beta)$. A supervised learning approach that uses training data $\frac{tan\,\alpha\,sin\,\beta}{\mu}$to identify new observations. Programs can $\iint\frac{u\sin\alpha}{u+u\ \cos\theta}$be trained to classify new observations $\frac{\pi}{2}$based on initial datasets or observations. Classification is a supervised learning concept in machine learning that divides$\left(x_n+\frac{N}{x_n}\right)$ a set of data into distinct categories.

$$E=\iint\frac{\partial y}{\partial x}\frac{\Delta^2}{E}+\left(\frac{\Delta^2u_x}{Eu_x}\right)m^2g^2+m^2\frac{v^4}{r^2}\sqrt{\frac{\pi}{2}p^2}+2p^2\cos\alpha+p^2 \quad (5)$$

As shown in equation (5), in support vector machines, players can perform$\iint\frac{\partial y}{\partial x}\frac{\Delta^2}{E}$ tasks like Classification, regression, and outlier identification $\left(\frac{\Delta^2u_x}{Eu_x}\right)m^2$that require supervised learning$m^2\frac{v^4}{r^2}$ methods.

$$F=cos\,\varphi\ *\frac{p\,sin\propto}{p+p\,cos\propto}\iint\frac{1}{\emptyset(1+\Delta)}f(x)\left(\frac{E+E^{-1}}{2}\right)\Delta^3Y_2 \quad (6)$$

As shown in equation (6), decision trees are supervised machine learning $\cos\varphi$ $*$algorithms and the decision tree algorithm is key to them.




Fig. 3. Mathematical structure of scatterometry measurement data

In its broadest sense, figure 3 shows that scatterometry is the study of light diffracted by periodic structures of the measurement and interpretation of the data. The grating form is reflected in the scattered or diffracted light pattern that serves as a fingerprint or signature.

$$G=(x^2+QR)=\frac{QR(Q+R)}{Q^2+R^2-Y^2}+2PQ-\left(\frac{Q+R}{2P}\right) \quad (7)$$

As shown in equation (7), the ocean's temperature can be determined $(x^2+QR)$with the use of satellites. To color data assists scientists $\frac{QR(Q+R)}{Q^2+R^2-Y^2}$in identifying the flooding near the shore$2PQ$ affects fish and marine animals, detecting the river $\left(\frac{Q+R}{2P}\right)$flows and algae bloom.

Equation (7) has supervised learning, and the outcomes are indicated in equation (6):

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on January 12,2026 at 09:07:13 UTC from IEEE Xplore. Restrictions apply.

$$H = \frac{1}{2}\delta^2 + \delta\sqrt{1+\frac{\delta^2}{4}}\Sigma\frac{\partial y}{\partial x}y_r = \binom{n}{1}y_1 + \binom{n}{2}\Delta y_1 + \binom{n}{3}\Delta^2 y_1 \quad (8)$$

As shown in equation (8), an object's reflection of broad-band light $\frac{1}{2}\delta^2$ is measured using optical scatterometry to characterize $\delta\sqrt{1+\frac{\delta^2}{4}}$unrelated features of the sample.

C. *Reinforcement learning for prevention of disaster management for reducing earth's atmosphere and decreasing wave height*

Figure 4 denotes the prevention of disaster management by reducing the earth's atmosphere and decreasing ocean current wave height in reinforcement learning.




Fig. 4. Reinforcement learning in disaster management for reducing earth's atmosphere and decreasing wave height

Figure 4 shows that model-based design provides a shared design environment that simplifies general communication, data analysis, and system verification among multiple organizations. Machine learning is reinforcement learning, and it is all about adopting the best possible course of action to get them out of a circumstance. A radial fracture is a break in a glass that radiates outward from the spot of the glass was trucked, like the spoke of a wheel. A disaster is a significant crisis that occurs in a short or long period that causes widespread human, material, and economic or environmental loss that surpasses the ability of the afflicted community or society to deal using its resources.

1) *The derivatives of reinforcement learning*

$$I = \frac{H}{4}\left(\frac{R^2+2Rr+3r^2}{R^2+Rr+r^2}\right) + \pi r^2\left(h-\frac{h_1}{3}\right)\sqrt{\frac{b^2}{a^2+2ab}} + \frac{1}{2}\delta^2 + \delta \quad (9)$$

As shown in equation (9), reinforcement learning is based on rewarding $\frac{H}{4}$and punishing desired behavior. Suppose an agent is trained to learn$\left(\frac{R^2+2Rr+3r^2}{R^2+Rr+r^2}\right)$ through trial and error. Reinforcement πr^2learning with models implementing policies and witnessing $\left(h-\frac{h_1}{3}\right)$the outcomes include the$\sqrt{\frac{b^2}{a^2+2ab}}$ next state and an instant reward is a common$\frac{1}{2}\delta^2 + \delta$ way to learn to behave optimally in a new environment.

$$J = \int cos(px+E) + 2\,sin\frac{ph}{2} * cos\left[px+E+\frac{(ph+\pi)}{2}\right] + \left(\frac{h}{1+hx+x^2}\right) \quad (10)$$

As shown in equation (10), value-based reinforcement learning is built $cos(px+E)$around the idea of value learning. As a starting point2 $sin\frac{ph}{2}$ for learning RL, the properly related network in deep learning is just fundamental. It predicts likely a person can achieve$cos\left[px+E+\frac{(ph+\pi)}{2}\right]$ a given condition or do a particular action. Combining$\left(\frac{h}{1+hx+x^2}\right)$ Role-plays and textbooks and value-based education teach values in the classroom and at home.

$$J = \int cos(px+E) + 2\,sin\frac{ph}{2} * cos\left[px+E+\frac{(ph+\pi)}{2}\right] + \left(\frac{h}{1+hx+x^2}\right) + \frac{u(u-1)(u-2)}{6}\Delta^3 y_\theta (11)$$

As shown in equation (11), the layer of earth's atmosphere that shields the $h^2u^2\left(u+\frac{d^2u}{d\theta^2}\right)$Planet from solar radiation. Even though the$\int \sin\theta\frac{u(u-1)}{2}$ phenomena are typical; they happen $\Delta^2 y_\theta$throughout a solar storm. In $\frac{u(u-1)(u-2)}{6}$certain areas, a phenomenon characterized as $\Delta^3 y_\theta$magnetic reconnection could allow the solar wind's electrically charged particles to flow through a break in the shield.




Fig. 5. Machine learning to process wave height using scatterometry measurement

Figure 5 shows that wave mode, altimeters, and synthetic aperture radars can be used to remotely measure globally critical wave heights, although both suffer from spatial and temporal sampling restrictions. On the alternative hand, scatterometers possess a broad swath and a high return frequency, and far they have consistently provided ocean winds instead of waves. In sea-level estimates, the results indicate that the data-driven technique is realistic and promising for operational application in the future.

$$L = x_1 \underset{f^1(x)}{\frac{f(x_1)}{f(x_2)-f(x_1)}}(x_2-x_1)\int\frac{\pi}{2}Df(x) = \frac{d}{dx}f(x) = \quad (12)$$

As shown in equation (12), various factors determine the wave height $\frac{f(x_1)}{f(x_2)-f(x_1)}$and include speed, duration, and fetch. If the wind speed is (x_2-x_1)low, even if the wind duration

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on January 12,2026 at 09:07:13 UTC from IEEE Xplore. Restrictions apply.

or fetch is long,$\int \frac{\pi}{2}$small waves are generated. Scattered microwave radar signals from an aircraft or spacecraft are measured in scatterometers that$Df(x)$ are microwave radar sensors that measure the surface's standardized radar cross-section. The vertical distance between a wave's crest $\frac{d}{dx}f(x)$and trough is recognized as its wave height. The lake was calm and flat; it would be at the Still-Water Line. The crest of a wave is the $f^1(x)the$ highest point beyond the still-water line on the water's surface.




Fig. 6. (a)Scatter plot for significant ML (b) Absolute wind speed difference

Figure 6 a, b shown in wave scattering is the collision and dispersion with a material item, like sunlight scattered by raindrops to generate a rainbow. The average height of the highest one-third of the waves, measured from trough to crest, is considered significant wave height.

IV. Experimental Analysis of Scatterometry Measurement via Wave Height

A significant wave height is expressed by the average wave height, from trough to crest, of the highest reach of the waves. Using the MLSC method solving the radar scatterometer works by sending a pulse of microwave radiation toward the earth's atmosphere and measuring reflected energy [18]. Optical scatterometry is a technique that measures the wind stability of an object's broad-band light reflection [19]. An observer at sea uses ML as an estimate based on the average height of the excessive quarter of the waves recorded to estimate the significant ocean current in wave height [20]. The wind height is altered on the wind blowing in a single direction for energy intensity [21]. It reduces exposure to risks, decreases person's and property's vulnerability, and improves readiness for adverse occurrences [22].




Fig. 7. Distribution of wind speed stability

Figure 7 shows that the wind speed probability distribution is familiar with how the wind energy distribution can be calculated. Pressure, variations in solar energy on earth's surface, and climatic circumstances, like wind speed, all affect wind energy distributed over the planet's surface. As an indicator of lateral turbulence, the standard deviation of wind direction is incorporated into an SL method to solve air pollution dispersion's wind speed stability category. The amount of accessible wind energy and the energy conversion system's efficiency is determined by the wind speed distribution at a given place.




Fig. 8. Measurement of the disaster management using sensors

Figure 8 shows that remote sensing can help reduce risk by identifying flood plain, coastal inundation and erosion, and active fault hazard zones. Verifying hazard models by taking measurements of actual occurrences can be done using this technology.




Fig. 9. The performance of scatterometry analysis in the earth's atmosphere

Figure 9 shows in an active microwave remote sensor, scatterometers emit heat pulses to the earth's surface and measure the power returned to the device. Earth's climate is heavily influenced by wind, and they directly influence the turbulent exchanges of heat, moisture, and greenhouse gases between the atmosphere and the ocean. The remote-sensing systems can give continuous, precise, and high-resolution wind speed and direction measurements regardless of weather conditions.

V. Conclusion

This paper discussed wave height prediction from scatterometry measurement data and the application of MLSC that could improve this assisted machine learning technology. Scatterometer are active remote sensing sensors

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on January 12,2026 at 09:07:13 UTC from IEEE Xplore. Restrictions apply.

for calculating wind direction and speed from the roughness of the water. MLSC has a fundamental finding that reduces the submerged landslides that can have serious implications for coastal areas and are huge movements of silt. The importance of MLSC in model-based scatterometry is that it can provide structural profile information that can be used to detect parameter variations, and machine learning provides excellent correlation to a defined reference. It concludes that MLSC-assisted SL and RL technology in scatterometry of wave height improves the prediction of measurement data accessible to be surveyed and managed correctly and effectively and presented successfully applied on MLSC.

REFERENCES

[1] H. Wang et al., "Estimation of significant wave heights from ASCAT scatterometer data via deep learning network," Remote Sens. (Basel), vol. 13, no. 2, p. 195, 2021.

[2] J. Yang, J. Zhang, Y. Jia, C. Fan, and W. Cui, "Validation of Sentinel-3A/3B and Jason-3 altimeter wind speeds and significant wave heights using buoy and ASCAT data," Remote Sens. (Basel), vol. 12, no. 13, p. 2079, 2020.

[3] S. Sreelakshmi and P. K. Bhaskaran, "Spatio-temporal distribution and variability of high threshold wind speed and significant wave height for the Indian ocean," Pure Appl. Geophys., vol. 177, no. 9, pp. 4559–4575, 2020.

[4] I. R. Young, E. Kirezci, and A. Ribal, "The global wind resource observed by scatterometer," Remote Sens. (Basel), vol. 12, no. 18, p. 2920, 2020.

[5] A. Ribal and I. R. Young, "Global calibration and error estimation of altimeter, scatterometer, and radiometer wind speed using triple collocation," Remote Sens. (Basel), vol. 12, no. 12, p. 1997, 2020.

[6] J. Liu et al., "First results from the rotating fan beam scatterometer onboard CFOSAT," IEEE Trans. Geosci. Remote Sens., vol. 58, no. 12, pp. 8793–8806, 2020.

[7] E. Rodríguez et al., "Ka-band Doppler scatterometry over a loop current eddy," Remote Sens. (Basel), vol. 12, no. 15, p. 2388, 2020.

[8] J.-V. Björkqvist, S. Rikka, V. Alari, A. Männik, L. Tuomi, and H. Pettersson, "Wave height return periods from combined measurement–model data: a Baltic Sea case study," Nat. Hazards Earth Syst. Sci., vol. 20, no. 12, pp. 3593–3609, 2020.

[9] R. Balasubramaniam and C. Ruf, "Characterization of rain impact on L-Band GNSS-R ocean surface measurements," Remote Sens. Environ., vol. 239, no. 111607, p. 111607, 2020.

[10] A. Tamizi, I. R. Young, A. Ribal, and J.-H. Alves, "Global scatterometer observations of the structure of tropical cyclone wind fields," Mon. Weather Rev., vol. 148, no. 11, pp. 4673–4692, 2020.

[11] X. Zhang, Y. Li, S. Gao, and P. Ren, "Ocean wave height series prediction with numerical long short-term memory," J. Mar. Sci. Eng., vol. 9, no. 5, p. 514, 2021.

[12] S. H. Park, J. Yoo, D. Son, J. Kim, and H. S. Jung, "Improved Calibration of Wind Estimates from Advanced ScatterometerMetOp-B in Korean Seas Using Deep Neural Network," Remote Sensing, vol. 13, no. 20, 2021.

[13] X. Li et al., "Analysis of coastal wind speed retrieval from CYGNSS mission using artificial neural network," Remote Sens. Environ., vol. 260, no. 112454, p. 112454, 2021.

[14] H. Ye et al., "Evaluation of CFOSAT scatterometer wind data in global oceans," Remote Sens. (Basel), vol. 13, no. 10, p. 1926, 2021.

[15] N. Kokkos, M. Zoidou, K. Zachopoulos, M. M. Nezhad, D. A. Garcia, and G. Sylaios, "Wind climate and wind power resource assessment based on gridded scatterometer data: A Thracian Sea case study," Energies, vol. 14, no. 12, p. 3448, 2021.

[16] X. Xu and A. Stoffelen, "Support vector machine tropical wind speed retrieval in the presence of rain for Ku-band wind scatterometry," Atmos. Meas. Tech., vol. 14, no. 12, pp. 7435–7451, 2021.

[17] W. M. Klesse, A. Rathsfeld, C. Groß, E. Malguth, O. Skibitzki, and L. Zealouk, "Fast scatterometric measurement of periodic surface structures in plasma-etching processes," Measurement (Lond.), vol. 170, no. 108721, p. 108721, 2021.

[18] B. Dincer, "MAIN SURFACE FORCES / CLIMATE CHANGE / NASA." 04-Oct-2021.

[19] R. Tanoeiro, "Tibau Wind Speed." 08-Jun-2021.

[20] UCI Machine Learning, "Household electric power consumption." 23-Aug-2016

[21] NOAA, "NOAA ICOADS." 13-Mar-2018.

[22] Heads or Tails, "US natural disaster declarations." 01-Apr-2023.

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on January 12,2026 at 09:07:13 UTC from IEEE Xplore. Restrictions apply.