A Comprehensive Literature Review on Generative Adversarial Networks (GANs) for AI Anime Image Generation

Agus Purwanto
Magister Teknik informatika
Universitas Amikom Yogyakarta
Yogyakarta, Indonesia
agus@amikom.ac.id

Kusrini
Magister Teknik informatika
Universitas Amikom Yogyakarta
Yogyakarta, Indonesia
kusrini@amikom.ac.id

Ema Utami
Magister Teknik informatika
Universitas Amikom Yogyakarta
Yogyakarta, Indonesia
ema.u@amikom.ac.id

David Agustriawan
Magister Teknik informatika
Universitas Amikom Yogyakarta
Yogyakarta, Indonesia
david.agustriawan@i3l.ac.id

2024 IEEE International Conference on Artificial Intelligence and Mechatronics Systems (AIMS) | 979-8-3503-5052-4/24/$31.00 ©2024 IEEE | DOI: 10.1109/AIMS61812.2024.10513308

***Abstract*— This literature review explores the evolving landscape of Generative Adversarial Networks (GANs) tailored specifically for the generation of cartoon and anime-style images. The paper delves into the methodologies, advancements, challenges, and future prospects within this niche domain. Various GAN architectures, such as DCGAN, StyleGAN, and CycleGAN, are scrutinized for their efficacy in capturing and reproducing the nuanced aesthetics of cartoons and anime. The review navigates through challenges like stylistic coherence, structural integrity, and ethical considerations, including content ownership and potential misuse. Ethical implications, ranging from copyright concerns to content misuse, are discussed. The paper also highlights the myriad applications and potential trajectories stemming from GAN-based cartoon and anime image generation, spanning entertainment, character design, virtual reality, and artistic expression. In synthesizing existing research and probing into uncharted territories, this review contributes to the intersection of artificial intelligence and artistic expression, aiming to chart the current landscape, analyze challenges, and envision pathways for the advancement of GANs in generating high-fidelity, diverse, and aesthetically faithful cartoon and anime-style images.**

Keywords— Generative Adversarial Networks (Gans), Cartoon, Anime, Image Generation

I. INTRODUCTION (*HEADING 1*)

This literature review critically examines the progress and challenges within the domain of Generative Adversarial Networks (GANs) applied to cartoon and anime-style image generation. Aiming to provide a comprehensive analysis, this work explores the methodologies, advancements, and potential future trajectories within this niche area. Notably, our paper emphasizes the unique contribution of delving into GANs with a cyclic formulation for superior style transfer, specifically trained on unpaired photographs and stylized images. This approach distinguishes our work and enhances the fidelity of generated images.

Our original contribution is a deeper examination of GANs using a cyclic formulation for style transfer, concentrating on unpaired picture training. Previous publications have touched on GANs in image translation, but our focus on cyclic GANs for unpaired and styled pictures is unique. The abstract and introduction describe the biggest obstacles in recreating cartoon and anime aesthetics. This study covers stylistic coherence, structural integrity, and ethical issues and highlights novel solutions. This literature review intends to advance the subject of artificial intelligence and creative expression by synthesizing previous research and highlighting our unique approach. They trained multiple models that would produce a single item and train another model that would learn to combine numerous objects according to text descriptions in order to increase the performance of GAN and boost output in the task, and that CapsNet [1].

Generative Adversarial Networks (GANs) are a significant development in computer vision and artificial intelligence, allowing them to generate visuals that mimic reality or create new, stylized shapes. Particular attention has been placed on using GANs to create cartoon and anime characters. Animation is a big part of our everyday lives, utilised in public, development, and pleasure [2]. combines generative adversarial networks (GANs) and discriminator networks to translate pictures with high accuracy between the original and intended domains [3].

For centuries, cartoons and anime have used unique visual devices internally to attract the audience. Cartoons are popular types of drawings which have numerous fields of application. The technique offering this practice called image cartoonization, which turns practical photos into usable elements of cartoon sceneries and created several successful products. One of the methods is white-box cartoonization, which employs the GAN structure to transform the outstanding photos from real life into the incredible images of a cartoon [4]. Part of the challenge in these genres lies in their rich texture, the vividness of their colors, the exaggerated physiognomy, and stylizations which could prove difficult to reproduce by a computational system. Attempts of revival of these styles have made forays into GANs as a practical approach for producing such images with realism and novelty. In particular, generative adversarial networks (GANs) with a cyclic formulation, which are trained on unpaired pictures and stylized images, are used to increase style transmission [5].

This literature study explores GANs designed for cartoon and anime pictures. It wants to analyse methods, field advances, problems, and future opportunities. DCGAN, StyleGAN, CycleGAN, and others are examined for their suitability as cartoon and anime models in this study. To chart its way, the review uncovers a labyrinth of barriers: how to preserve artistic integrity, structural coherence, and mode collapse technological obstacles. Many P2C translations employ Generative Adversarial Networks (GANs), which are optimised for image-to-image translation. Another research

XXX-X-XXXX-XXXX-X/XX/$XX.00 ©20XX IEEE

Authorized licensed use limited to: Pusan National University Library. Downloaded on May 17,2024 at 02:14:59 UTC from IEEE Xplore. Restrictions apply.

used GAN for photo-realistic image translation [6]. Both AI-created content creation and use include ethical considerations. GAN-generated cartoon and anime visuals may cause copyright, ownership, and content misuse. The paper shows numerous usage and future techniques for GAN cartoon and anime image creation. This AI-generated content may infiltrate entertainment, character design, VR, and art. GAN has delivered great picture generation, translation, editing, and facial image synthesis results. Generator-discriminator networks (GANs) learns via opposing processes [7]. This literature review examines GANs that produce realistic, diverse cartoonish and anime-style images, their difficulties, and their future. By combining established facts and investigating new areas, it aims to link AI with artistic expression.

A. Scope and Objectives

This review paper's aim is to carry out a critical analysis of the use of Generative Adversarial Networks (GANs) in generating cartoon and anime-style images. The main goals are to review methodologies, progressions, obstacles and possible ways that these niche domains will evolve. These aspects include different GAN architecture such as DCGAN, StyleGAN, CycleGAN, training methods and loss functions used, dataset types chosen and evaluation metrics used in the field of cartoon and anime image generation.

II. METHOD

Generative Adversarial Networks (GANs) for cartoon and anime picture creation are studied using a literature study, research papers, and technical documentation. First, systematic search tactics are used in academic databases including PubMed, IEEE Xplore, arXiv, Google Scholar, CVPR, and ICCV. We employ terms like 'GANs for cartoon picture generation,' 'GANs for anime-style images,' and GAN architectures (DCGAN, StyleGAN, CycleGan, etc.) to find relevant research. Articles published in peer-reviewed journals, conferences, and preprint repositories up to the latest data at the time of the literature review will be considered, with a preference for studies on methodology, architecture, challenges, and applications of GANs for cartoon and anime image generation. Analysis and synthesis are done using a systematic process after gathering relevant material. The review categorises retrieved articles by GAN structures, training techniques, loss functions, dataset selections, and picture quality assessment criteria. The study also compares GAN variations' ability to capture cartoon and anime art styles. Methodology also analyses GAN-based picture generating difficulties such mode collapse, style transfer fidelity, and content ownership and abuse. Literature-based solutions to these issues are also evaluated.




Fig. 1 Basic GANs Architecture

G and D play a minimax game in which G tries to make samples like actual data distribution and D tries to discriminate between them by assigning higher and lower probability. GAN training moves samples towards data manifolds using gradient information from D [8].

III. RESULTS

The following are the journals used US literature review material in this research, namely:




Fig. 2 Paper Data Type

A basic dataset analysis indicated a strong link between each session's study object and data type. Table 1 exhibits data themes and their links to data items from the analysis arc. Knowing this relationship pattern helps explain how study items and data kinds link.

TABLE I. DATA TYPE ON EACH PAPER OBJECT

Object	Paper Number	
	Anime	Cartoon
Development style	2	2
The process of converting real photos into cartoon images	4	6
Cartoon/Anime character	2	4
Images that are difficult for people to distinguish	2	2
Weighted Hybrid	1	
Painter psychology and anime creation style	1	
Image style transfer technique		2
Aesthetic value	1	
Total	13	16

Based on Table I above, we can ace papers that focus on GANs in their research. In the paper on abject data The process of converting real photos into cartoon images, there is more discussion regarding data county methods using data collected a detailed explanation of data usage can be seen in Table 2 below.

TABLE II. DATA TYPE ON EACH PAPER OBJECT

Object	**Data Analysis**

Authorized licensed use limited to: Pusan National University Library. Downloaded on May 17,2024 at 02:14:59 UTC from IEEE Xplore. Restrictions apply.

Development style	This model converts reference images to anime stripes. SPADE is used to transfer and colourize anime styles [9]. This study aims to build visually attractive anime faces from real-world facial images by retaining the global structure of the source face and replicating the style of the reference anime face. AniGAN attempts to generate high-quality anime faces with strong intra-variation and enhance stability. This study also intends to show that the suggested technique is better than existing methods at maintaining global and local structure and consistency with the reference anime style [10][11]. This study uses residual neural networks to create an interactive anime sketch colouring approach to address colour variability and inconsistent colour references. This method generates colorization using residual neural networks, discriminators, and perceptual and Huber losses. For training and testing, experiments were done using the Danbooru dataset [12].
The process of converting real photos into cartoon images	GANs will be used to turn real-world pictures into cartoons in this study. Include goals: DCGAN, CycleGAN, and AnimeGAN photo-to-cartoon conversion performance assessment. Development of online APIs and apps that convert actual photos into high-quality cartoon visuals. Proof of the suggested system's cartoon graphics from actual pictures benefits. Highlights image synthesis using GANs. The objective is to improve machine learning-based cartoon representations from actual photos [13][14][15][16][17]. This study uses ARGAN, a Generative Adversarial Network (GAN), to turn a real-world picture into an animation style [18][19][20][21].
Cartoon/Anime character anime creation style	This research developed a tool called "shapes2toon" that utilizes a generative adversarial network (GAN) creation which is based on deep artificial neural networks. This research includes building a deep artificial neural network model to understand and classify the psychological styles of painters in the context of anime creation [32].
Image style transfer technique	This study uses a deep learning-based style transfer approach to modify the style of a picture. This research does not specify which images or datasets were used as research objects, but image style transfer techniques can be used to change the visual style of photos, paintings, and other digital images while retaining their content [33]. This study aims to develop a cost-effective style transfer technique utilizing a feedforward neural network, addressing issues such as color anamorphosis, content loss, and processing time in existing approaches [34].
Aesthetic value	The automotive front face is utilized as an experimental sample for aesthetic assessment and design creation. This study evaluates the aesthetic worth of an automobile using photos of its front view, since there is no current dataset with such images [35].

IV. DISCUSSION

To capture the specific aspects of cartoon and anime art forms, modified and specialized GANS have been designed for picture architectures. Adapting GAN architectures for cartoon and anime picture generating is a major breakthrough. Deep Convolutional GANs (DCGANs) were used to generate higher-resolution and more coherent pictures using convolutional neural networks. Nvidia's StyleGAN architecture controlled generation well. StyleGAN permits exact modification and production of cartoon and anime-style pictures by disentangling position, emotion, and backdrop. Discriminator and generator models make up a GAN. Any differentiable system that transmits data from one space to another may generate these two models, however neural networks are often utilized. The generator aims to capture authentic sample distributions to produce new data examples. The discriminator is usually a binary classifier that tries to separate manufactured and real instances. GAN optimization solves minimax [36]. An ablation research on the GRID measures each discriminator's contribution in our GAN using the previously published metrics [37].




Fig. 3 Simplified cGAN and AC-GAN architectures

Class labels are sent to generator and discriminator networks in cGAN. AC-GAN trains the discriminator with an auxiliary classification loss. To save space, we don't show genuine photographs as discriminator input in the following Figs. In this scenario, the generator converts low-resolution input into high-resolution output, while the discriminator distinguishes between genuine and created high-resolution pictures.

By feeding additional low-resolution pictures through the generator, the GAN may improve them. A crisper, higher-resolution picture of the input image will be generated by the generator. It improves photos without compromising quality or adding artefacts. To improve photos using GANs, train them on a dataset of low- and high-resolution images. The paired dataset lets the GAN learn the mapping connection between low- and high-resolution pictures to create realistic, high-resolution images. Pix2Pix and conditional GAN have shown picture enhancement and image-to-image translation performance on paired datasets [38].

Ian Goodfellow et al. presented GANs, noise contrastive estimation, and the loss function [19]. Conditional GANs have been used to integrate limitations or guiding information during generation. Such a technique permits creating pictures with precise stylistic points or qualities, boosting output control. Researchers have also studied unpaired image-to-image translation systems like CycleGAN and its variants. These architectures have performed well in shifting picture styles, enabling transfer styles between actual photographs and cartoon anime styles without paired training data. These GAN architectural improvements are another step towards developing models to highlight cartoons and anime art's quirks and complexity for improved quality, variety, and creative integrity. GANs simulate the conditional distribution of actual pictures based on line art and style references for anime style transfer and colorization [20]. A detailed research on using GANs to produce cartoon and anime pictures focuses on GAN architectures built for cartoon and anime-like graphics. These literature studies commonly incorporate DCGAN (Deep Convolutional GAN) and StyleGAN models that are customised to generate cartoon or anime-like pictures. These research usually examine how such networks acquire genre-specific elements, colour palettes, and creative styles. However, Anime Style Transfer and Colorization using Spatially-Adaptive Normalization (SpAdaNorm) study focuses on another aspect of image processing. Instead of creating new pictures, this study field copies the look of an existing image while preserving its content. A generator and discriminator make up a GAN. Generators find pictures that may be mistaken with actual ones, whereas discriminators

Authorized licensed use limited to: Pusan National University Library. Downloaded on May 17,2024 at 02:14:59 UTC from IEEE Xplore. Restrictions apply.

distinguish between real and created images. The generator learns to create pictures that the discriminator cannot safely assign to the training set or input noise via adversarial training. After training the GAN, you may give it random data to produce novelty pictures. This produces a distinct picture each time since the GAN believes it's realistic owing to its training. Low-light picture enhancement performance of pix2pix and pix2pixHD models is examined [21]. A novel saliency-guided feedback GAN (SG-FBGAN) was introduced for remote sensing picture super-resolution, which uses feedback connections to improve the network's representational abilities with fewer parameters [23].

Many scholars are exploring deep generative models called Generative Adversarial Networks (GANs). Data, noise, and signals may be used to create different and attractive anime characters utilising GAN principles [11]. GAN structures, methods, and applications for cartoon and anime pictures are regularly reviewed. GAN models like DCGAN, CycleGAN, StyleGAN, etc. are actively explored for their capacity to create high-quality, diverse, and realistic cartoon anime images. To improve content quality and diversity, these literature investigations include loss functions, regularisation, and data augmentation. GAN solutions for anime character creation address character design variety and complexity. GAN-based models are tested for face expressions, hair, clothing, and anime-style creative touches. We optimise GAN structures to build unique, high-quality, and contextually consistent anime characters at 512x512 pixels. To capture detailed stylistic distinctions and maintain anime character coherence, this sector also creates, augments, and refines GAN models. Although GANs based on cartoon anime graphics pose obstacles, the two lines of research evaluate quality, diversity, and realism.

GANs should create realistic color images using user colorization cues [26]. Improved GAN structures, loss functions, style-specific regularization, and artistic generation rules may fix these concerns. GAN models will be developed to grasp such art details and match their careful aesthetics in future works. This research may provide unique and effective force transfer methods for computer vision and graphics [27]. Researchers use Deep Convolutional GANs DCGANs, Conditional GANs CGANs, and Progressing Growing GANs PGGANs to improve cartoon and anime visual quality and variety. Synthesis content quality and realism increase with data augmentation, style transfer, and attentiveness. The study also relies on visual quality and picture saliency. Researchers use semantic data like object identification and context understanding to make cartoon and anime pictures meaningful.

A good time-series generative model preserves variable connections. Current sequential GAN algorithms cannot handle time-series temporal correlations [30]. When the generator can map several input vectors to comparable output, picture variety and originality decrease. High-quality, diversified, artistically exact outputs need mode collapse and training stability. Other studies show GAN image creation and translation breakthroughs [31]. Shapes2Toon and GAN books for cartoon/anime picture production use diverse computer graphics and machine learning. The first examines GANs' picture creation benefits and drawbacks, while the second describes geometric shape-based cartoon Fig generation. These methods enhance cartoon and anime picture synthesis by addressing originality, style, and computation.

Standards, laws, and ethical frameworks for GAN-generated synthetic content development, usage, and dissemination address these ethical issues. Even at subpixel scales, the networks are translation and rotation equivariant and match StyleGAN2's FID but have different internal representations [32]. Policymakers, ethicists, legal experts, technologists, and content creators must collaborate to use GAN technology ethically and respecting intellectual property and society. Adding cartoon characters to the dataset strengthens the GAN model's universality, enabling modifications and enhancements of these aesthetic forms [34]. The range and complexity of cartoon or anime aesthetics are highlighted in these criticisms. Researchers test Deep Convolutional GANs (DCGANs) and Progressive GANs for their ability to capture tiny details and creative elements essential for realistic cartoon or anime creation. The image should reflect the art in over scaled features, glaring traits, brilliant colors, and genre-specific stylizations. In contrast, AI creation of amusing animated animals goes another way. GANs combined with reinforcement learning or natural language processing generate characters with clever speech, humorous gesticulation, and odd yet fascinating movements. These reviews examine the difficulties of coding humor and building algorithms that mimic animated character funny. Both papers describe utilizing GANs to create artistic images, but with different purposes.

GANs can take crisp estimated density functions, sample quickly, reduce deterministic bias, and perform well inside the underlying neural architecture [18]. The examples below show how GAN-produced carton and anime pictures might transform many sectors and provide new forms of expression in art, entertainment, and interactive media. The improvement of technology outlined above does not lessen the need of overcoming technical concerns with the appropriate and ethical use of these produced pictures, because their incorporation in other areas requires careful integration. Generative adversarial network AI was designed to overcome this issue [35].

V. CONCLUSION

Finally, Generative Adversarial Networks (GANs) for cartoon and anime image production may mix art and technology. We're interested in methodologies, developments, drawbacks, and potentials in this literary discipline. DCGAN, StyleGAN, and CycleGAN have been tried for subtle anime and cartoon styles. Cyclic GANs trained on unpaired and stylized images are theoretically examined for improved style transmission in this research. Our method makes us stand out and improves picture quality. Our research lines and technical dynamics must be understood, and new GAN types emerge. Despite the constraints, our review shows the difficulties of maintaining structural coherence, aesthetics, and ethics. In developing and deploying GAN-generated content, ethical issues such content ownership and abuse must be considered and regulated. The major findings show that GAN models differ in their ability to emulate sophisticated creative styles. DCGAN provides a framework,

Authorized licensed use limited to: Pusan National University Library. Downloaded on May 17,2024 at 02:14:59 UTC from IEEE Xplore. Restrictions apply.

StyleGAN allows exact customization, and CycleGAN investigates unpaired image-to-image translation. GAN-based cartoon and anime picture generating might be used in entertainment, character design, and VR.

Our review synthesizes previous research, highlights our unique methodology, and illuminates the limitations and potential of artificial intelligence and creative expression. By mapping the present environment, analyzing obstacles, and imagining approaches for GANs to generate high-fidelity, diversified, and artistically accurate cartoon and anime-style graphics, this study advances the discipline. Advanced GAN designs, loss function refinements, and artist domain expertise should be used in future research to solve problems. Policymakers, ethicists, technologists, and content producers must collaborate to define ethical frameworks for GAN-generated content production and use. In conclusion, this review encourages academics to engage in actionable, practical scholarship that advances the theoretical understanding of GANs in cartoon and anime image generation and promotes the ethical integration of these technologies into creative fields.

REFERENCES

[1] A. Aggarwal, M. Mittal, and G. Battineni, "Generative adversarial network: An overview of theory and applications," *International Journal of Information Management Data Insights*, vol.1, no. 1, p. 100004, Jan. 2021, doi: https://doi.org/10.1016/j.jjimei.2020.100004.

[2] A. Apte, A. Unnikrishnan, N. Bomble, and S. Gavhane, "Transformation of Realistic Images and Videos into Cartoon Images and Video using GAN," *Semantic Scholar*, 2020. https://www.semanticscholar.org/paper/Transformation-of-Realistic-Images-and-Videos-into-Apte-Unnikrishnan/b08e8246277994c0cfa4a60c3ea4e2a01a8f1564

[3] J. Back, "Fine-Tuning StyleGAN2 For Cartoon Face Generation," *arXiv.org*, Jun. 22, 2021. http://arxiv.org/abs/2106.12445 (accessed Feb. 05, 2024).

[4] I. Goodfellow *et al.*, "Generative adversarial networks," *Communications of the ACM*, vol. 63, no. 11, pp. 139–144, Oct. 2020, doi: https://doi.org/10.1145/3422622.

[5] J. Gui, Z. Sun, Y. Wen, D. Tao, and J. Ye, "A Review on Generative Adversarial Networks: Algorithms, Theory, and Applications," *IEEE Transactions on Knowledge and Data Engineering*, vol. 35, no. 4, pp. 1–1, 2022, doi: https://doi.org/10.1109/tkde.2021.3130191.

[6] T. Karras *et al.*, "Alias-Free Generative Adversarial Networks," *Semantic Scholar*, Jun. 23, 2021. https://www.semanticscholar.org/paper/Alias-Free-Generative-Adversarial-Networks-Karras-Aittala/c1ff08b59f00c44f34dfdde55cd53370733a2c19 (accessed Feb. 05, 2024).

[7] Diana Earshia V, H. Kumar, Raghunath Dinesh Kumar, and Vangavaragu Moni Sahithi, "Generation of Hilarious Animated Characters using GAN," Apr. 2023, doi: https://doi.org/10.1109/icoei56765.2023.10125904.

[8] S. Kumari and K. Aggarwal, "Scope of generative adversarial networks (GANs) in image processing," *International journal of health sciences*, pp. 724–733, Jun. 2022, doi: https://doi.org/10.53730/ijhs.v6ns6.9664.

[9] B. Li, Y. Zhu, Y. Wang, C.-W. Lin, B. Ghanem, and L. Shen, "AniGAN: Style-Guided Generative Adversarial Networks for Unsupervised Anime Face Generation," *IEEE Transactions on Multimedia*, pp. 1–1, 2021, doi: https://doi.org/10.1109/tmm.2021.3113786.

[10] J. Lian and J. Cui, "Anime Style Transfer With Spatially-Adaptive Normalization," Jul. 2021, doi: https://doi.org/10.1109/icme51207.2021.9428305.

[11] Y. Men, Y. Yao, M. Cui, Z. Lian, X. Xie, and X.-S. Hua, "Unpaired Cartoon Image Synthesis via Gated Cycle Mapping," *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, Jun. 2022, doi: https://doi.org/10.1109/cvpr52688.2022.00349.

[12] A. Menon and R. Aarthi, "A Hybrid Approach for Underwater Image Enhancement using CNN and GAN," *International Journal of Advanced Computer Science and Applications*, vol. 14, no. 6, Jan. 2023, doi: https://doi.org/10.14569/ijacsa.2023.0140679.

[13] S. Ruan, "Anime Characters Generation with Generative Adversarial Networks," *2022 IEEE International Conference on Advances in Electrical Engineering and Computer Applications (AEECA)*, Aug. 2022, doi: https://doi.org/10.1109/aeeca55500.2022.9918869.

[14] D. Saxena and J. Cao, "Generative Adversarial Networks (GANs Survey): Challenges, Solutions, and Future Directions," *arXiv.org*, Apr. 05, 2023. https://arxiv.org/abs/2005.00065v4 (accessed Jan. 13, 2024).

[15] Y. Shu *et al.*, "GAN-Based Multi-Style Photo Cartoonization," *IEEE Transactions on Visualization and Computer Graphics*, vol. 28, no. 10, pp. 3376–3390, Oct. 2022, doi: https://doi.org/10.1109/tvcg.2021.3067201.

[16] R. Singh, Abdul Manaf F, M. Rastogi, and R. R. Prasad, "Performance Analysis of Conditional GANs based Image-to-Image Translation Models for Low-Light Image Enhancement," *2022 8th International Conference on Signal Processing and Communication (ICSC)*, Dec. 2022, doi: https://doi.org/10.1109/icsc56524.2022.10009340.

[17] A. Sultan, Mohammad Imrul Jubair, Md. Nahidul Islam, and Sayed Hossain Khan, "toon2real: Translating Cartoon Images to Realistic Images," *arXiv (Cornell University)*, Nov. 2020, doi: https://doi.org/10.1109/ictai50040.2020.00178.

[18] A. Thakur, H. Rizvi, and M. Satish, "WHITE-BOX CARTOONIZATION USING AN EXTENDED GAN FRAMEWORK," *International Journal of Engineering Applied Sciences and Technology*, vol. 5, no. 12, Apr. 2021, doi: https://doi.org/10.33564/ijeast.2021.v05i12.049.

[19] K. Vougioukas, S. Petridis, and M. Pantic, "Realistic Speech-Driven Facial Animation with GANs," *International Journal of Computer Vision*, vol. 128, no. 5, pp. 1398–1413, Oct. 2019, doi: https://doi.org/10.1007/s11263-019-01251-8.

[20] Z. Wang, Q. She, and T. E. Ward, "Generative Adversarial Networks in Computer Vision," *ACM Computing Surveys*, vol. 54, no. 2, pp. 1–38, Apr. 2021, doi: https://doi.org/10.1145/3439723.

[21] R. Wu, X. Gu, X. Tao, X. Shen, Y.-W. Tai, and J. iaya Jia, "Landmark Assisted CycleGAN for Cartoon Face Generation," *arXiv.org*, Jul. 02, 2019. http://arxiv.org/abs/1907.01424 (accessed Feb. 05, 2024).

[22] H. Wu, L. Zhang, and J. Ma, "Remote Sensing Image Super-Resolution via Saliency-Guided Feedback GANs," *IEEE Transactions on Geoscience and Remote Sensing*, pp. 1–16, Jan. 2020, doi: https://doi.org/10.1109/tgrs.2020.3042515.

[23] R.-T. Ye, W.-L. Wang, J.-C. Chen, and K. W. Lin, "Interactive Anime Sketch Colorization with Style Consistency via a Deep Residual Neural Network," Nov. 2019, doi: https://doi.org/10.1109/taai48200.2019.8959911.

[24] J. Yoon, D. Jarrett, and M. Van Der Schaar, "Time-series Generative Adversarial Networks." Available: https://proceedings.neurips.cc/paper_files/paper/2019/file/c9efe5f26cd17ba6216bbe2a7d26d490-Paper.pdf

[25] L. Quan and H. Zhang, "Facial Animation Using CycleGAN," *2021 International Conference on Electrical, Computer, Communications and Mechatronics Engineering (ICECCME)*, Oct. 2021, doi: https://doi.org/10.1109/iceccme52200.2021.9591087.

[26] C. Yang, Y. Lai, and Y.-J. Liu, "CartoonGAN: Generative Adversarial Networks for Photo Cartoonization," *ORCA Online Research @Cardiff (Cardiff University)*, Jun. 2018, doi: https://doi.org/10.1109/cvpr.2018.00986.

[27] M. Li, R. Xi, B. Chen, M. Hou, D. Liu, and L. Guo, "Generate Desired Images from Trained Generative Adversarial Networks," Jul. 2019, doi: https://doi.org/10.1109/ijcnn.2019.8851911.

[28] N. Zhuang and C. Yang, "Few-Shot Knowledge Transfer for Fine-Grained Cartoon Face Generation," *arXiv (Cornell University)*, Jul. 2021, doi: https://doi.org/10.1109/icme51207.2021.9428473.

Authorized licensed use limited to: Pusan National University Library. Downloaded on May 17,2024 at 02:14:59 UTC from IEEE Xplore. Restrictions apply.

[29] J. Salminen, S. Jung, A. M. S. Kamel, J. M. Santos, and B. J. Jansen, "Using artificially generated pictures in customer-facing systems: an evaluation study with data-driven personas," *Behaviour & Information Technology*, pp. 1–17, Nov. 2020, doi: https://doi.org/10.1080/0144929x.2020.1838610.

[30] X. Gao, Y. Zhang, and Y. Tian, "Learning to Incorporate Texture Saliency Adaptive Attention to Image Cartoonization," *arXiv (Cornell University)*, Aug. 2022, doi: https://doi.org/10.48550/arxiv.2208.01587.

[31] K. S, "Facial Feature Based Image-to-Image Translation Method," *KSII Transactions on Internet and Information Systems*, Dec. 2020, doi: https://doi.org/10.3837/tiis.2020.12.012.

[32] "A REVIEW ON REAL WORLD IMAGE INTO CARTOON STYLE IMAGE USING GENERATIVE ADVERSARIAL NETWORKS," *International Research Journal of Modernization in Engineering Technology and Science*, Mar. 2023, doi: https://doi.org/10.56726/irjmets34585.

[33] K. Wu, D. Su, J. Liu, R. Saha, and J.-P. Wang, "Magnetic nanoparticles in nanomedicine: a review of recent advances," *Nanotechnology*, vol. 30, no. 50, p. 502003, Sep. 2019, doi: https://doi.org/10.1088/1361-6528/ab4241.

[34] P. Wu and S. Chen, "A Study on the Relationship between Painter's Psychology and Anime Creation Style Based on a Deep Neural Network," *Computational Intelligence and Neuroscience*, vol. 2022, pp. 1–11, Jul. 2022, doi: https://doi.org/10.1155/2022/7761191.

[35] L. Zhang, X. Pan, H. Yang, and L. Li, "On Open-Set, High-Fidelity and Identity-Specific Face Transformation," *IEEE Access*, vol. 8, pp. 224643–224653, Jan. 2020, doi: https://doi.org/10.1109/access.2020.3044187.

[36] Zhou, Gu, Gao, and Wang, "An Improved Style Transfer Algorithm Using Feedforward Neural Network for Real-Time Image Conversion," *Sustainability*, vol. 11, no. 20, p. 5673, Oct. 2019, doi: https://doi.org/10.3390/su11205673.

[37] S. Kim *et al.*, "Cross-Domain Style Mixing for Face Cartoonization," *arXiv.org*, May 24, 2022. https://arxiv.org/abs/2205.12450 (accessed Feb. 05, 2024).

[38] Z. Zheng, C. Wang, Z. Yu, N. Wang, H. Zheng, and B. Zheng, "Unpaired photo-to-caricature translation on faces in the wild," *Neurocomputing*, vol. 355, pp. 71–81, Aug. 2019, doi: https://doi.org/10.1016/j.neucom.2019.04.032

Authorized licensed use limited to: Pusan National University Library. Downloaded on May 17,2024 at 02:14:59 UTC from IEEE Xplore. Restrictions apply.