

## Documentation YACC

<https://github.com/iuliaaai/LFTC>

### LEX file - specif.lxi:

```
%{
    #include <stdio.h>
    #include <string.h>
    #include "y.tab.h"
    int lines = 0;
}%

%option noyywrap
%option caseless

DIGIT      [0-9]
NON_ZERO_DIGIT [1-9]
INT_CONSTANT [-]?{NON_ZERO_DIGIT}{DIGIT}*|0
LETTER [a-zA-Z]
STRING_CONSTANT [""]({LETTER}{DIGIT}|" ")*[""]
IDENTIFIER {LETTER}{LETTER}{DIGIT}*

%%

func {printf("Reserved word: %s\n", yytext); return FUNC;}
Int   {printf("Reserved word: %s\n", yytext); return INT;}
String {printf("Reserved word: %s\n", yytext); return STRING;}
Bool   {printf("Reserved word: %s\n", yytext); return BOOL;}
Char   {printf("Reserved word: %s\n", yytext); return CHAR;}
if     {printf("Reserved word: %s\n", yytext); return IF;}
elif   {printf("Reserved word: %s\n", yytext); return ELIF;}
else   {printf("Reserved word: %s\n", yytext); return ELSE;}
let    {printf("Reserved word: %s\n", yytext); return LET;}
var    {printf("Reserved word: %s\n", yytext); return VAR;}
ret    {printf("Reserved word: %s\n", yytext); return RET;}
True   {printf("Reserved word: %s\n", yytext); return TRUE;}
False  {printf("Reserved word: %s\n", yytext); return FALSE;}
read   {printf("Reserved word: %s\n", yytext); return READ;}
print  {printf("Reserved word: %s\n", yytext); return PRINT;}
loop   {printf("Reserved word: %s\n", yytext); return LOOP;}
GO     {printf("Reserved word: %s\n", yytext); return GO;}
STOP   {printf("Reserved word: %s\n", yytext); return STOP;}

{IDENTIFIER} {printf("Identifier: %s\n", yytext ); return ID;}
```

```
{INT_CONSTANT}    {printf( "Constant: %s\n", yytext ); return INT_CONST;}
{STRING_CONSTANT} {printf( "Constant: %s\n", yytext ); return STRING_CONST;}
```

```
"@" {printf( "Separator: %s\n", yytext ); return AT_SIGN;}
"#" {printf( "Separator: %s\n", yytext ); return HASHTAG;}
";" {printf( "Separator: %s\n", yytext ); return SEMI_COLON;}
"'" {printf( "Separator: %s\n", yytext ); return APOSTROPHE;}
"{" {printf( "Separator: %s\n", yytext ); return OPEN_CURLY_BRACKET;}
"}" {printf( "Separator: %s\n", yytext ); return CLOSED_CURLY_BRACKET;}
"(" {printf( "Separator: %s\n", yytext ); return OPEN_ROUND_BRACKET;}
")" {printf( "Separator: %s\n", yytext ); return CLOSED_ROUND_BRACKET;}
"[" {printf( "Separator: %s\n", yytext ); return OPEN_STRAIGHT_BRACKET;}
"]" {printf( "Separator: %s\n", yytext ); return CLOSED_STRAIGHT_BRACKET;}
"+" {printf( "Operator: %s\n", yytext ); return PLUS;}
"-" {printf( "Operator: %s\n", yytext ); return MINUS;}
"*" {printf( "Operator: %s\n", yytext ); return MUL;}
"/" {printf( "Operator: %s\n", yytext ); return DIV;}
"<" {printf( "Operator: %s\n", yytext ); return LESS;}
">" {printf( "Operator: %s\n", yytext ); return GREATER;}
"<=" {printf( "Operator: %s\n", yytext ); return LESS_EQ;}
">=" {printf( "Operator: %s\n", yytext ); return GREATER_EQ;}
"!=" {printf( "Operator: %s\n", yytext ); return DIFF;}
"==" {printf( "Operator: %s\n", yytext ); return EQUAL;}
"=" {printf( "Separator: %s\n", yytext ); return ATRIBUTION;}
"!" {printf( "Operator: %s\n", yytext ); return NEGATION;}
"?:" {printf( "Operator: %s\n", yytext ); return TERNARY_OP;}
"%" {printf( "Operator: %s\n", yytext ); return MOD;}
```

```
[ \t]+ {}
[\n]+ {lines++;}
```

```
.      {printf("Error at token %s at line %d\n", yytext, lines); return -1;}
```

```
%%
```

### YACC file - lang.y:

```
%{
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
```

```
int yylex();  
int yyerror(char *s);
```

```
#define YYDEBUG 1  
%}
```

```
%token FUNC  
%token INT  
%token STRING  
%token BOOL  
%token CHAR  
%token IF  
%token ELIF  
%token ELSE  
%token LET  
%token VAR  
%token RET  
%token TRUE  
%token FALSE  
%token READ  
%token PRINT  
%token LOOP  
%token GO  
%token STOP
```

```
%token ID  
%token INT_CONST  
%token STRING_CONST
```

```
%token AT_SIGN  
%token HASHTAG  
%token SEMI_COLON  
%token APOSTROPHE  
%token OPEN_CURLY_BRACKET  
%token CLOSED_CURLY_BRACKET  
%token OPEN_ROUND_BRACKET  
%token CLOSED_ROUND_BRACKET  
%token OPEN_STRAIGHT_BRACKET  
%token CLOSED_STRAIGHT_BRACKET  
%token PLUS  
%token MINUS  
%token MUL  
%token DIV  
%token LESS
```

%token GREATER  
%token LESS\_EQ  
%token GREATER\_EQ  
%token DIFF  
%token EQUAL  
%token ATRIBUTION  
%token NEGATION  
%token TERNARY\_OP  
%token MOD

%left '+' '-' '\*' '/'

%start program

%%

program : GO tempDecl STOP ;  
tempDecl : /\*Empty\*/ | tempDecl declList | tempDecl stmtList ;  
declList : declaration | declaration declList ;  
declaration : variableDeclaration | constDeclaration ;  
variableDeclaration : VAR ID AT\_SIGN type ATRIBUTION expression SEMI\_COLON | VAR ID  
AT\_SIGN type SEMI\_COLON ;  
constDeclaration : LET ID AT\_SIGN type ATRIBUTION expression SEMI\_COLON ;  
type1 : BOOL | INT | CHAR | STRING ;  
arrayDecl : OPEN\_STRAIGHT\_BRACKET type1 CLOSED\_STRAIGHT\_BRACKET ;  
type : type1 | arrayDecl ;  
stmtList : stmt | stmt stmtList ;  
stmt : simplStmt | structStmt ;  
simplStmt : assignStmt | ioStmt ;  
assignStmt : ID ATRIBUTION expression SEMI\_COLON ;  
expression : expression PLUS term | expression MINUS term | term | BOOL ;  
term : term MUL factor | term DIV factor | term MOD factor | factor ;  
factor : OPEN\_ROUND\_BRACKET expression CLOSED\_ROUND\_BRACKET | ID |  
INT\_CONST ;  
ioStmt : READ OPEN\_ROUND\_BRACKET ID CLOSED\_ROUND\_BRACKET SEMI\_COLON |  
PRINT OPEN\_ROUND\_BRACKET stringExp CLOSED\_ROUND\_BRACKET SEMI\_COLON ;  
stringExp : STRING\_CONST | ID ;  
structStmt : ifStmt | whileStmt ;  
ifStmt : IF condition OPEN\_CURLY\_BRACKET stmtList CLOSED\_CURLY\_BRACKET  
tempElifStmt | IF condition OPEN\_CURLY\_BRACKET stmtList CLOSED\_CURLY\_BRACKET  
tempElifStmt elseStmt ;  
tempElifStmt : /\*Empty\*/ | tempElifStmt elifStmt ;  
elseStmt : ELSE OPEN\_CURLY\_BRACKET stmtList CLOSED\_CURLY\_BRACKET ;  
elifStmt : ELIF condition OPEN\_CURLY\_BRACKET stmtList CLOSED\_CURLY\_BRACKET ;

```
whileStmt : LOOP condition OPEN_CURLY_BRACKET stmtList CLOSED_CURLY_BRACKET ;
condition : expression relation expression ;
relation : LESS | LESS_EQ | EQUAL | GREATER_EQ | GREATER | DIFF ;
```

```
%%
int yyerror(char *s) {
    printf("Error: %s", s);
}

extern FILE *yyin;

int main(int argc, char** argv) {
    if (argc > 1)
        yyin = fopen(argv[1], "r");
    if (!yyparse())
        fprintf(stderr, "\tOK\n");
}
```

**p1.txt:**

```
GO
let count@Int = 0;
let n@Int = 432567;

loop n != 0 {
    n = n / 10;
    count = count + 1;
}
n = -3;
print(count);
if n < 2 {
    print("yes");
}
STOP
```

**res.exe:**

```
Reserved word: GO
Reserved word: let
Identifier: count
Separator: @
Reserved word: Int
Separator: =
Constant: 0
Separator: ;
```

Reserved word: let  
Identifier: n  
Separator: @  
Reserved word: Int  
Separator: =  
Constant: 432567  
Separator: ;  
Reserved word: loop  
Identifier: n  
Operator: !=  
Constant: 0  
Separator: {  
Identifier: n  
Separator: =  
Identifier: n  
Operator: /  
Constant: 10  
Separator: ;  
Identifier: count  
Separator: =  
Identifier: count  
Operator: +  
Constant: 1  
Separator: ;  
Separator: }  
Identifier: n  
Separator: =  
Constant: -3  
Separator: ;  
Reserved word: print  
Separator: (  
Identifier: count  
Separator: )  
Separator: ;  
Reserved word: if  
Identifier: n  
Operator: <  
Constant: 2  
Separator: {  
Reserved word: print  
Separator: (  
Constant: "yes"  
Separator: )  
Separator: ;

Separator: }

Reserved word: STOP

OK