



# PROTON BEAMS FORMATION FROM DENSE PLASMA OF ECR DISCHARGE SUSTAINED BY 37.5 GHZ GYROTRON RADIATION

V. Skalyga, S. Golubev, I. Izotov, S. Razin, A. Sidorov, V. Zorin

Institute of Applied Physics of Russian Academy of Sciences, Nizhny Novgorod, Russia

O. Tarvainen, H. Koivisto, T. Kalvas

University of Jyväskylä, Department of Physics, Jyväskylä, Finland

# Outline

- Motivation to try proton beams production
- SMIS 37
- Experimental results
- Future plans and ideas

# Motivation

Modern accelerators requirements:  
hundreds of mA with normalized emittance lower than  $1 \pi \cdot \text{mm} \cdot \text{mrad}$


ECRIS has a good emittance and high ionization efficiency

Proton (deuteron) beams with higher current are needed



Lets try high current gasdynamic ECRIS for proton production!

# SMIS 37




Frequency 37,5 GHz  
Power up to 100 kW  
Pulse duration 1 ms  
Trap magnetic field up to 5 T


# SMIS 37 main goals

- Unique plasma parameters  
( $N_e > 10^{13} \text{ cm}^{-3}$ ,  $\tau \approx 5 \div 50 \mu\text{s}$ ,  $T_e \approx 50 \div 300 \text{ eV}$ )
- High current density ( $j \approx 100 \div 600 \text{ mA/cm}^2$ )
- Low emittance values
- High (unique) flexibility

4.5 mA



# 1-hole extraction




$I = 4.5 \text{ mA}$


$j = 570 \text{ mA/cm}^2$

Extractor was placed in 12 cm behind the plug  
(magnetic field in extraction area was about 0.2 T)

# Beam emittance (single hole)





$$\varepsilon_n = 0.03 \pi \cdot \text{mm} \cdot \text{mrad}$$



$$B_n = 5 \text{ A} / (\pi \cdot \text{mm} \cdot \text{mrad})^2$$



# 9-hole extraction



$I = 60 \text{ mA}$

$j = 200 \text{ mA/cm}^2$


Extractor was placed in 22 cm behind the plug  
(magnetic field in extraction area was about 0.03 T)




# Beam emittance (9-hole)



Pepper-pot image




Emittance diagram



$$\varepsilon_n = 0.5 \pi \cdot \text{mm} \cdot \text{mrad}$$

$$B_n = 0.24 \text{ A}/(\pi \cdot \text{mm} \cdot \text{mrad})^2$$

200 mA



# 13-hole extraction



$I = 200 \text{ mA}$


$j = 220 \text{ mA/cm}^2$

Extractor was placed in 20 cm behind the plug  
(magnetic field in extraction area was about 0.03 T)

# Beam emittance (13-hole)




Pepper-pot image




$$\varepsilon_n = 1.1 \pi \cdot \text{mm} \cdot \text{mrad}$$

Emittance diagram



$$B_n = 0.17 \text{ A} / (\pi \cdot \text{mm} \cdot \text{mrad})^2$$

# Ion spectrum



$\text{H}^+ > 94\%$   
 $\text{H}_2^+ < 6\%$

# Results summary

Extraction system	Faraday cup current, mA	Puller current, mA	Normalized emittance, $\pi \cdot \text{mm} \cdot \text{mrad}$	Extraction voltage, kV	Normalized brightness, $\text{A}/(\pi \cdot \text{mm} \cdot \text{mrad})^2$
1 hole (d = 1 mm)	4.5	2	0.03	50	5
9 holes (d = 2 mm)	60	30	0.5	45	0.24
13 holes (d = 3 mm)	200	250	1.1	45	0.17

$\text{H}^+ > 94 \%$

$\text{H}_2^+ < 6 \%$

# Future plans

- Higher voltage
- New extractors design
- 24 GHz CW source

Thank you for your attention!