


# Installation and Commissioning of an Ultrafast Electron Diffraction Facility as Part of the ATF-II Upgrade

M.A. Palmer, M. Babzien, M. Fedurin, C. Folz, M. Fulkerson, K. Kusche, J. Li, R. Malone, T. Shaftan, J. Skaritka, L. Snydstrup, C. Swinson, and F. Willeke  
Brookhaven National Laboratory, Upton, NY



## Ultrafast Electron Diffraction with MeV Electron Beams



Beam source:


- 1.6 cell photocathode gun
- 2,856 MHz

Operational beam energy:  
2.8 MeV


Operational beam charge:  
1 pC

Laser:

- Ti:Sapphire, 160 fs pulse
- 1  $\mu$ J at photocathode
- 100  $\mu$ J at sample chamber




## ATF-II Facility Plan – BNL Building 912



- ATF: A DOE Office of Science National User Facility for the **Accelerator Stewardship Program**
  - Funded through the Office of High Energy Physics
  - Main facility operating in BNL Building 820
- ATF-II: Upgrade and move of the facility to BNL Building 912
  - Additional and more flexible experimental space
  - Allows space for significantly upgraded CO<sub>2</sub> Laser Capabilities
    - Higher Power (100 TW class is goal)
    - Shorter bunches (100 fs goal)
  - First operational element is the UED Facility
    - ATF focus is developing this accelerator-based capability to its fullest extent
    - Experimental station treated as a co-developed “beam line” for material science users
      - Required element to validate the accelerator capabilities


## UED Milestones

- December 2015: Layout was developed and approved
- January – February 2016: RF system and beamline were assembled in new location
- March 2016: RF system was commissioned, klystron and gun were conditioned to operational power, control system was ready for operation
- April 2016: UED readiness review; laser system commissioning
- May-June 2016: Beamline commissioning, dark current and first beam observed at detector
- June 2016: First diffraction pattern at detector
- July-August 2016: Updates for environmental stability in BNL Building 912
- September 2016: Preparation for User Experiments




## UED Energy Calibration

Calibrated steering magnet was installed  
Beam energy was calculated by measured displacement on the detector screen




## UED Diffraction Pattern



## UED Capabilities: Present and Future

Beam energy = 3 MeV,  
Operational charge = 1 pC  
Repetition rate = 1 Hz (<5Hz)

UED beamline diagnostics:  
YAG screen at Gun has Basler camera and Faraday cup;  
Detector has phosphor screen with Andor camera;  
Faraday cup at beam dump.



Compress 50 pC electron bunch ( $\sim 10^8$  electrons/bunch)  


- Bunch Length: 160 fs
- Bunch Size: 30 microns

**LDRD-Funded Upgrade Path**

Application: UED, UEM

Test principle of the method to remove time jitter between laser and electron bunch

**Accelerator based MeV electron microscopes,**



### LDRD UED Bunch Compressor in Space Charge Regime

Novel and non-conventional electron bunch compression scheme

- Utilize correlated energy spread and energy-dependent path length to compress the bunch length
- Space charge effect is used to generate the time-energy correlation
- Compression technique developed for electron beam slicing :
- Focusing → space charge energy increase at head (chirped bunch)
- High energy particle comes earlier, but takes longer path (R56>0)
- compression

