


Time-Resolved Images of Coherent Synchrotron Radiation Effects in the *LCLS* First Bunch Compressor

- C. Behrens, **DESY**
- P. Emma, LBNL
- F. Zhou, Z. Huang, SLAC


Motivation & Idea

- "...would like to see the time-resolved effects of CSR"
 - Joe Bisognano (UW), 2008 LBNL FEL Workshop
- "Can we use a skew quad?" Oleg Shevchenko (BINP), 2008 LBNL FEL Workshop
- Yes ... Skew quad is a poor man's transverse RF deflector, with a few differences
- Skew quad installed at LCLS-BC1 in 2009 (PAC'09)
- \blacksquare Creates vertical dispersion after chicane, revealing x vs. t space (CSR effects)
- Measurements & simulations discussed here ...

Add a CSR-Diagnostic Skew Quad in BC1





How it Works (first measurements Dec. 15, 2009)




~1% chirped energy spread at 220 MeV and large dispersion at chicane center


Skew quad generates y' from x: $\Delta y' = x/f$








Simulation of skew quad effect at OTR12 for 1nC, with and without CSR



X-band RF Linearizer (L1X) varied for different L1S phases:

too weak (16 MV), too strong (22 MV), and just right (19 MV)




L1X = 16 MV(too weak)


Region of high peak current moves from head to tail (pre-BC1)


L1X = 22 MV (too strong)


Region of high peak current moves from tail to head (pre-BC1)


L1X = 19 MV (just right), linearizes phase space, not shown here



































































































































































































TAIL











TAIL



























































































































Summary of previous 3 slides

Measured OTR screen images:

X-band RF set at: 16 MV (*left*), 19 MV (*center*), and 22 MV (*right*)




Bunch length (vertical streak) is ~6 ps FWHM

pre-BC1 bunch head at the top of each image.

-33.0° -35.0° -34.0° -36.0° -35.0° -37.0° -36.0° -38.0° -37.0° -39.0° -40.0° -38.0° 41.0° -39.0° -42.0° -40.0° -41.0° 43.0°

Now Switch OFF L1X RF

Measurements (left) and simulations (right) with X-band RF switched off.
The L1S phase settings differ between measurement and simulation by 2°.




Summary

- Skew quad is simple, inexpensive, and adds timeresolved electron beam measurements
- Reasonable agreement with simulations (1d-CSR model in elegant), but preliminary results
- Limited beam time has been available
- Should repeat and run more careful simulations as well
- Skew quad can also be used to correct vertical dispersion


Thanks for your Attention


Blow-up reasonably well modeled at extreme compression

Vertical (time) is pre-BC1 bunch-length coordinate, not post-BC1, so blow-up is not so familiar w.r.t. usual simulations



Elegant





Measurement(L1X = 19 MV)