

Instruction for production :
Tolerance : ISO 2768-Fine

Disque_Superieur : Quantity 100
- Material : PVC black

Support_Piezo : Quantity 100
- Material : PVC Black

Corps_AL_V2 : Quantity 100
- Material : PVC black

Support_Sensor_V2 : Quantity 50
- Material : PVC
- No Thread

Moule : Quantity 10
- Material : Aluminium
- Finish : Sand blasted / no anodization
- 3 Threads in M4

Bras Lateral : Quantity 25
- Material Stainless Steel 316
- 2 M5 Threads
- Tolerance is fine only for holes, and can be rough elsewhere.

Protection_SQ26 : Quantity 50
- Material Stainless Steel 316
- Can be welded
- Except for the 2 holes, tolerance is rough

Mise_Air_Libre_M10_IA : Quantity 50
- Material Stainless Steel 316
- M7-0.75 (fine) Tapping at the bottom (inside, diameter 6.2mm, length 10mm)
- M10-1.5 (normal) Thread at the bottom (outside, diameter 10mm, as long as possible)
- M14-1 (fine) Tapping in the top hole (inside, diameter 13mm, length 7mm)

Mise_Air_Libre_M10_Bouchon_IA : Quantity 50
- Material Stainless Steel 316
- M14-1 (fine) Threading (outside, diameter 14mm)

Penetrteur_M10_6mm_IA : Quantity 100 / 200 (quote both please)
- Material Stainless Steel 316
- M10-1.5 (normal) Thread at the bottom (outside, diameter 10mm, as long as possible)

Penetrteur_M14_10mm_IA : Quantity 100 / 200 (quote both please)
- Material Stainless Steel 316
- M14-2 (normal) Thread at the bottom (outside, diameter 14mm, as long as possible)

Bride_6_Pouce_Metal : Quantity 12 or 24 (quote both please)
- Material : Stainless Steel 316
- 24 M8 Threads (12 blind)

- 4 M4 Threads (blind)