```c
/**
 * @file sensors.c
 * @brief Implementation of hardware abstraction for sensors
 * Copyright (C) 2017 Ethan Wells
 *
 * This program is free software: you can redistribute it and/or modify it
 * under the terms of the GNU General Public License as published by the Free
 * Software Foundation, either version 3 of the License, or(at your option) any
 * later version.
 *
 * This program is distributed in the hope that it will be useful, but WITHOUT
 * ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS
 * FOR A PARTICULAR PURPOSE. See the GNU General Public License for more
 * details.
 *
 * You should have received a copy of the GNU General Public License along
 * with this program. If not, see <https://www.gnu.org/licenses/>
 */

#include "../include/sensors.h"
#include <math.h>

float defaultRecalc(int n) {
	return n;
} /* defaultRecalc */

int readSensorValue(Sensor *s) {
	switch (s->_type) {
		case Digital:
			return digitalRead(s->port);

		case Analog:
			return (s->calibrate) ?
				analogReadCalibrated(s->port) :
				analogRead(s->port);

		case AnalogHR:
			return analogReadCalibratedHR(s->port);

		case Sonic:
			return ultrasonicGet(s->_pros);

		case Quad:
			return encoderGet(s->_pros);

		case Gyroscope:
```

```
                        return gyroGet(s->_pros);

                default:
                        return 0;
        } /* switch */
} /* readValue */

void sensorRefresh(Sensor *s) {
        if (!s) {
                return;
        }

        if (s->child) {
                sensorRefresh(s->child);
        }

        if (!mutexTake(s->_mutex, 5)) {
                print("= Cannot take mutex =");
                return;
        }

        int val = (s->_type == Digital) ? readSensorValue(s) :
                  (readSensorValue(s) - s->zero);

        if (s->inverted) {
                if (s->_type == Digital) {
                        val = !val;
                } else {
                        val = -val;
                }
        }

        if (s->recalc) {
                val = round(s->recalc(val));
        }

        s->value   = val;
        s->average = s->child ? ((s->value + s->child->average) / 2) : s->value;

        mutexGive(s->_mutex);
} /* sensorRefresh */

void sensorReset(Sensor *s) {
        if (s->child) {
                sensorReset(s->child);
        }
```

```
        switch (s->_type) {
                case Gyroscope:
                        gyroReset(s->_pros);
                        s->zero = 0;
                        break;

                case Quad:
                        encoderReset(s->_pros);
                        s->zero = 0;
                        break;

                default:
                        s->zero = readSensorValue(s);
                        break;
        } /* switch */
} /* sensorReset */

Sensor newSensor(SensorType     type,
                 unsigned char  port,
                 bool           inverted,
                 unsigned short calibrate) {
        if (port < 1) {
                port = 1;
        }

        Sensor s = {
                ._type     = type,
                .recalc    = &defaultRecalc,
                .port      = port,
                .inverted  = inverted,
                .calibrate = calibrate,
                ._mutex    = mutexCreate(),
        };

        switch (type) {
                case Digital:
                        pinMode(port, INPUT);
                        break;

                case Analog:

                        if (calibrate) {
                                analogCalibrate(port);
                        }
                        break;
```

```
                case AnalogHR:
                        analogCalibrate(port);
                    break;

                case Sonic:
                        s._pros = ultrasonicInit(port, (char)calibrate);
                        break;

                case Quad:
                        s._pros = encoderInit(port, (char)calibrate, false);
                        break;

                case Gyroscope:
                        s._pros = gyroInit(port, calibrate);
                        break;

                default:
                        break;
        } /* switch */

        sensorReset(&s);
        return s;
} /* newsensor */

Sensor newDigital(unsigned char port, bool inverted) {
        return newSensor(Digital, port, inverted, false);
} /* newDigital */

Sensor newSonic(unsigned char orange, unsigned char yellow) {
        return newSensor(Sonic, orange, false, yellow);
} /* newSonic */

Sensor newQuad(unsigned char top, unsigned char bottom, bool inverted) {
        return newSensor(Quad, top, inverted, bottom);
} /* newQuad */

Sensor newAnalog(unsigned char port, bool calibrate) {
        return newSensor(Analog, port, false, calibrate);
} /* newAnalog */

Sensor newAnalogHR(unsigned char port) {
        return newSensor(AnalogHR, port, false, true);
} /* newAnalogHR */

Sensor newGyro(unsigned char port, bool inverted, int calibration) {
```

```
        return newSensor(Gyroscope, port, inverted, calibration);
} /* newGyro */
```