```
/**
 * Ofile sensors.c
 * Obrief Implementation of hardware abstraction for sensors
 * Copyright (C) 2017 Ethan Wells
 * This program is free software: you can redistribute it and/or modify it
 * under the terms of the GNU General Public License as published by the Free
 * Software Foundation, either version 3 of the License, or(at your option) any
 * later version.
 * This program is distributed in the hope that it will be useful, but WITHOUT
 * ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS
 * FOR A PARTICULAR PURPOSE. See the GNU General Public License for more
 * details.
 * You should have received a copy of the GNU General Public License along
 * with this program. If not, see <a href="https://www.gnu.org/licenses/">https://www.gnu.org/licenses/</a>
#include "../include/sensors.h"
#include <math.h>
float defaultRecalc(int n) {
        return n;
} /* defaultRecalc */
int readSensorValue(Sensor *s) {
        switch (s->_type) {
                case Digital:
                         return digitalRead(s->port);
                case Analog:
                         return (s->calibrate) ?
                                analogReadCalibrated(s->port) :
                                analogRead(s->port);
                 case AnalogHR:
                         return analogReadCalibratedHR(s->port);
                 case Sonic:
                         return ultrasonicGet(s->_pros);
                case Quad:
                         return encoderGet(s->_pros);
                 case Gyroscope:
```

```
return gyroGet(s->_pros);
                default:
                        return 0;
        } /* switch */
} /* readValue */
void sensorRefresh(Sensor *s) {
        if (!s) {
                return;
        }
        if (s->child) {
                sensorRefresh(s->child);
        }
        if (!mutexTake(s->_mutex, 5)) {
                #ifdef DEBUG_MODE
                        print("= Cannot take mutex =");
                #endif
                return;
        }
        int val = (s->_type == Digital) ? readSensorValue(s) :
                  (readSensorValue(s) - s->zero);
        if (s->inverted) {
                if (s->_type == Digital) {
                        val = !val;
                } else {
                        val = -val;
        }
        if (s->recalc) {
                val = round(s->recalc(val));
        s->value = val;
        s->average = s->child ? ((s->value + s->child->average) / 2) : s->value;
        mutexGive(s->_mutex);
} /* sensorRefresh */
void sensorReset(Sensor *s) {
        if (s->child) {
```

```
sensorReset(s->child);
        }
        switch (s->_type) {
                case Gyroscope:
                        gyroReset(s->_pros);
                        s->zero = 0;
                        break;
                case Quad:
                        encoderReset(s->_pros);
                        s->zero = 0;
                        break;
                default:
                        s->zero = readSensorValue(s);
                        break;
        } /* switch */
} /* sensorReset */
Sensor newSensor(SensorType
                                type,
                 unsigned char port,
                 bool
                                inverted,
                 unsigned short calibrate) {
        if (port < 1) {
                port = 1;
        }
        Sensor s = \{
                        = type,
                ._type
                .recalc
                          = &defaultRecalc,
                .port
                           = port,
                .inverted = inverted,
                .calibrate = calibrate,
                ._mutex
                         = mutexCreate(),
        };
        switch (type) {
                case Digital:
                        pinMode(port, INPUT);
                        break;
                case Analog:
                        if (calibrate) {
                                analogCalibrate(port);
```

```
break;
                case AnalogHR:
                          analogCalibrate(port);
                        break;
                case Sonic:
                        s._pros = ultrasonicInit(port, (char)calibrate);
                        break;
                case Quad:
                        s._pros = encoderInit(port, (char)calibrate, false);
                        break;
                case Gyroscope:
                        s._pros = gyroInit(port, calibrate);
                        break;
                default:
                        break;
        } /* switch */
        sensorReset(&s);
        return s;
} /* newsensor */
Sensor newDigital(unsigned char port, bool inverted) {
        return newSensor(Digital, port, inverted, false);
} /* newDigital */
Sensor newSonic(unsigned char orange, unsigned char yellow) {
        return newSensor(Sonic, orange, false, yellow);
} /* newSonic */
Sensor newQuad(unsigned char top, unsigned char bottom, bool inverted) {
        return newSensor(Quad, top, inverted, bottom);
} /* newQuad */
Sensor newAnalog(unsigned char port, bool calibrate) {
        return newSensor(Analog, port, false, calibrate);
} /* newAnalog */
Sensor newAnalogHR(unsigned char port) {
        return newSensor(AnalogHR, port, false, true);
} /* newAnalogHR */
```

```
Sensor newGyro(unsigned char port, bool inverted, int calibration) {
    return newSensor(Gyroscope, port, inverted, calibration);
} /* newGyro */
```