```
/**
 * Ofile auto.c
 * Obrief The primary source for the autonomous operation period
 * Copyright (C) 2017 Ethan Wells
 * This program is free software: you can redistribute it and/or modify it
 * under the terms of the GNU General Public License as published by the Free
 * Software Foundation, either version 3 of the License, or(at your option) any
 * later version.
 * This program is distributed in the hope that it will be useful, but WITHOUT
 * ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS
 * FOR A PARTICULAR PURPOSE. See the GNU General Public License for more
 * details.
 * You should have received a copy of the GNU General Public License along
 * with this program. If not, see <a href="https://www.gnu.org/licenses/">https://www.gnu.org/licenses/</a>
#include "../include/auto.h"
bool isAuto = true;
void autonNone() {}
void autoHerbLeft();
void autoHerbRight();
void autoMeatLeft();
void autoMeatRight();
      selectedAuton
                         = 1;
Auton autons[MAX_AUTON + 1] =
{ {
                // index 0
                       = "none",
                .name
                .sensorName = "lDrv",
                .sensor = &drive[0].sensor,
                .execute
                            = &autonNone,
        },{
                // index 1
                .name = "herb 1",
                .sensorName = "rDrv",
                .sensor = &drive[1].sensor,
                .execute = &autoHerbLeft,
        },{
                // index 2
                            = "herb r",
                .name
```

```
.sensorName = "lIntake",
                .sensor
                           = &intake[0].sensor,
                            = &autoHerbRight,
                .execute
        },{
                // index 3
                            = "meat 1",
                .name
                .sensorName = "rIntake",
                .sensor = &intake[1].sensor,
                .execute
                            = &autoMeatLeft,
        },{
                // index 4
                            = "meat r",
                .name
                .sensorName = "gyroC",
                .sensor = &gyro.child,
                            = &autoMeatRight,
                .execute
        },
};
void driveToPosition(int 1, int r, unsigned long until) {
        driveSettings[0].target = 1;
        driveSettings[1].target = r;
        until
                               += millis();
        do {
                PID(&driveSettings[0]);
                PID(&driveSettings[1]);
                motorUpdate(&lift);
                sensorRefresh(lift.sensor);
                sensorRefresh(&gyro);
                for (int i = 0; i < 2; i++) {
                        motorUpdate(&drive[i]);
                        sensorRefresh(drive[i].sensor);
                }
                delay(10);
        } while ((!driveSettings[0].isTargetReached ||
                  !driveSettings[1].isTargetReached) &&
                   millis() < until);</pre>
        drive[0].power = 0;
        drive[1].power = 0;
        update();
} /* driveToPosition */
```

```
void driveToPositionAngle(int 1, int r, int a, unsigned long until) {
        int gError;
        driveSettings[0].target = 1;
        driveSettings[1].target = r;
                               += millis();
        do {
                gError = (a - gyro.averageVal) * 1.5;
                PID(&driveSettings[0]);
                PID(&driveSettings[1]);
                drive[0].power += gError;
                drive[1].power -= gError;
                motorUpdate(&lift);
                sensorRefresh(lift.sensor);
                sensorRefresh(&gyro);
                for (int i = 0; i < 2; i++) {
                        motorUpdate(&drive[i]);
                        sensorRefresh(drive[i].sensor);
                }
                delay(10);
        } while ((!driveSettings[0].isTargetReached ||
                  !driveSettings[1].isTargetReached) &&
                                                  millis() < until);</pre>
        drive[0].power = 0;
        drive[1].power = 0;
        update();
} /* driveToPosition */
void turnTo(int angle, unsigned long until) {
        until += millis();
        gyroSettings[0].target = angle;
        gyroSettings[1].target = angle;
        do {
                PID(&gyroSettings[0]);
                PID(&gyroSettings[1]);
                update();
                delay(10);
        } while ((!gyroSettings[0].isTargetReached ||
```

```
!gyroSettings[1].isTargetReached) &&
                                                  millis() < until);</pre>
        driveSet(0, 0);
} /* turnTo */
void autonomous() {
        unsigned long startTime = millis();
        isAuto = true;
        reset();
        selectedAuton = clipNum(selectedAuton, MAX_AUTON, 0);
        if (autons[selectedAuton].execute != NULL)
                autons[selectedAuton].execute();
        #ifdef DEBUG_MODE
                printf("\n\n\rFinished autonomous in %ldms\n\n", millis() - startTime);
        #endif
        while (isAutonomous()) {
                update();
                delay(10);
} /* autonomous */
Task driveToPositionAngleT(void *triple) {
        Triple *t = (Triple *)triple;
        driveSettings[0].target = t->a;
        driveSettings[1].target = t->b;
        do {
                PID(&driveSettings[0]);
                PID(&driveSettings[1]);
                drive[0].power += (t->c - gyro.averageVal) * 2.3;
                drive[1].power -= (t->c - gyro.averageVal) * 2.3;
                motorUpdate(&lift);
                sensorRefresh(lift.sensor);
                sensorRefresh(&gyro);
                for (int i = 0; i < 2; i++) {
                        motorUpdate(&drive[i]);
                        sensorRefresh(drive[i].sensor);
                }
                delay(10);
```