```
/**
 * Ofile autoStack.c
 * Obrief Drive forward and stack cones from the loader
 * Copyright (C) 2017 Ethan Wells
 * This program is free software: you can redistribute it and/or modify it
 * under the terms of the GNU General Public License as published by the Free
 * Software Foundation, either version 3 of the License, or(at your option) any
 * later version.
 * This program is distributed in the hope that it will be useful, but WITHOUT
 * ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS
 * FOR A PARTICULAR PURPOSE. See the GNU General Public License for more
 * details.
 * You should have received a copy of the GNU General Public License along
 * with this program. If not, see <a href="https://www.gnu.org/licenses/">https://www.gnu.org/licenses/</a>
#include "../include/auto.h"
void updateLinesDrive();
void autonStack() {
        update();
        driveSet(35, 35);
        int angle;
        Mutex m = angleFromUpcomingLine(&angle, NULL, 5000);
        mutexTakeDelete(m, -1);
        angle = -angle;
        #ifdef DEBUG_MODE
                printf("\n\n'\n', angle);
        #endif
        sensorRefresh(&gyro);
        #ifdef DEBUG_MODE
                printf("\n\n\r%d\n\n", gyro.average);
        #endif
        gyro.zero = angle;
        gyro.child->zero = angle;
        sensorRefresh(&gyro);
        #ifdef DEBUG_MODE
                printf("\n\n\r%d\n\n", gyro.average);
        #endif
```

```
turnTo(90, 3500);
        #ifdef DEBUG_MODE
                print("\n\n\rturned and stuff\n\n");
        #endif
        driveSet(25, 25);
        while (gline(0) + gline(1) + gline(2)) {
                updateLinesDrive();
                delay(10);
        }
        claw.power = 50;
        motorUpdate(&claw);
        armSettings.target = ARM_3_QUARTER;
        TaskHandle delet = GO(armPID, NULL);
        driveToPositionAngle(drivePos(0) + 350, drivePos(1) + 350, 90, 1600);
        taskDelete(delet);
        armToPosition(ARM_3_QUARTER, 750);
        #ifdef DEBUG_MODE
                print("\n\nready to stack\n\n");
        #endif
        for (int i = 0; i < 5; i++) {
                claw.power = -75;
                update();
                delay(500);
                claw.power = -30;
                update();
                armToPosition(ARM_QUARTER / 2 + (ARM_QUARTER * .25 * i), 3000);
                claw.power = 127;
                update();
                delay(400);
                claw.power = 10;
                update();
                armToPosition(ARM_3_QUARTER, 3000);
} /* autonLeftRed12 */
```

driveToPositionAngle(drivePos(0) - 300, drivePos(1) - 300, 0, 2000);