An Explainable Hybrid of Lexicon Rules and Multilingual Transformers for Bilingual Hate Speech Detection: System Evaluation, Fusion and Latency

Kha Vy Pham[1] and Hong Nga Cao[1(*)]

FPT University, Can Tho, Vietnam
phamkhavycm2004@gmail.com
caohongnga@gmail.com
(*)Corresponding author

Abstract. Fine-tuned multilingual transformers dominate content moderation, yet they are opaque and brittle on the surface forms moderation sees: teencode, dropped diacritics, inserted separators and abbreviated profanity. We present **SensitiveAI**, a bilingual language-aware pipeline that couples two lexicon-driven rule engines (Vietnamese and English) with per-language mDeBERTa-v3-base backbones through language detection, language-aware routing, pseudo-probability fusion and decision thresholds. On the ViHSD test split the hybrid is macro-F1 neutral (0.6575 to 0.6602; bootstrap $p = 0.29$) but provides auditable provenance for the 38 changed decisions and a design agenda for evidence-gated fusion. Extending the same architecture to English (Davidson et al., 818-entry expanded lexicon) and to a balanced mixed Vietnamese/English sample of 1,000 comments, the end-to-end system reaches 87.00% accuracy with macro-F1 0.7829, 11.6 ms latency and 86,000 req/s throughput on a single laptop GPU, with an AI-only macro-F1 of 0.8027 on the 941 samples where a checkpoint is available.

Keywords: Hate speech · multilingual transformers · lexicon rules · hybrid fusion · language-aware routing · explainable AI.

1 Introduction

Content moderation at scale demands three properties that pure neural systems struggle to provide simultaneously: *coverage* over the long tail of teencode and obfuscation, *provenance* for audit and appeal, and *latency* within real-time service-level agreements. Multilingual transformers (mDeBERTa-v3-base, XLM-R, etc.) achieve strong macro-F1 on Vietnamese (HATE/OFFENSIVE/CLEAN 0.65–0.68) and English (0.77–0.81) benchmarks, yet they remain opaque: a flipped decision gives no human-readable trace, and adversarial respellings bypass the model without retraining.

Lexicon rule engines offer the converse: deterministic matching, editable dictionaries and span-level evidence. Their weakness is brittleness—low recall on implicit hate and poor generalisation to new slurs—unless combined with neural contextualisation.

This paper presents **SensitiveAI**, a bilingual language-aware pipeline that treats a rule engine as an *evidence channel* rather than a competing classifier. The system consists of:

1. a hybrid language detector (heuristics + langid backend) producing `vi/en/mix/other` with confidence;
2. a language-aware tokenizer that segments each comment into per-language spans;
3. two independent rule engines (668-entry Vietnamese lexicon `v1`, 818-entry English lexicon `v1-en-combined`) with anti-obfuscation views (accentless, leet, repeat-collapsed, separator-stripped);
4. per-language mDeBERTa-v3-base checkpoints (SENSITIVEAI-VI-CUSTOM and SENSITIVEAI-EN-STAGE2);
5. a language-aware fusion module that blends AI probabilities and rule pseudo-probabilities channel-wise with per-language weights ($\alpha_{\text{VI}} = 0.70$, $\alpha_{\text{EN}} = 0.70$, $\alpha_{\text{mix}} = 0.65$, $\alpha_{\text{multilingual}} = 0.80$) and per-class decision thresholds.

We evaluate on three axes:

– **Per-language backbone comparison**: four Vietnamese backbones (differing only in head and curriculum) and three English backbones on their respective held-out test sets.
– **Rule engine standalone**: macro-F1 0.345 (VI) and 0.504 (EN) with thresholded decisions.
– **Fusion variants**: global α, per-channel α, per-class thresholds, logistic meta-classifier—all tuned on validation, frozen for test.
– **End-to-end mixed evaluation**: 1,000 balanced comments (500 VI / 500 EN) yielding 87.00% accuracy, macro-F1 0.7829, 11.6 ms latency and 86,000 req/s on a single RTX 4060 laptop GPU.

The headline finding is *not* an accuracy breakthrough: on ViHSD the hybrid gains 0.0027 macro-F1 (8 comments, $p = 0.29$). The contribution is the provenance of every changed decision (38 on ViHSD: 23 corrections, 15 regressions) and a design agenda—evidence-gated fusion, profanity vs. political entry separation, negation and accent-less matching restoration—for turning a neutral aggregate into an operationally useful system.

2 Related Work

Vietnamese hate speech. The UIT-ViHSD corpus [10] established the three-class HATE/OFFENSIVE/CLEAN task. Prior work has explored monolingual PhoBERT [13], multilingual mBERT/XLM-R [5], and data augmentation [14]. Ensemble and curriculum learning [2] raised macro-F1 to 0.66–0.68, but the decision process remains a black box.

English hate speech. The Davidson et al. [7] dataset (Hate Speech and Offensive Language) is the de facto benchmark for English HATE/OFFENSIVE/CLEAN. Fine-tuned BERT/RoBERTa reach 0.77–0.81 macro-F1; recent work uses multi-task learning and adversarial training [11].

Hybrid rule + neural systems. Early hybrids concatenated lexical features to neural inputs [17]. [16] argue for interpretable components. [3] fuse rule scores with neural logits via learnable weights; [1] propose evidence channels. Most approaches evaluate on a single language and do not provide span-level evidence or language-aware routing.

Language-aware routing. Mixed-language moderation is addressed by language identification [9] followed by per-language models [15]. Code-mixed text (Vi-En) is handled by multilingual backbones or dedicated tokenizers [14]. Our design differs by keeping both rule engines active on `mix` and fallback segments, and by fusing per-language scores rather than training a single multilingual head.

Explainable moderation. Post-hoc explanations (LIME, SHAP, attention) are common [6]. Our approach provides *intrinsic* evidence: matched lexicon spans, match types and arithmetic scores, which survive deployment without additional computation.

3 Data and Lexicons

3.1 Vietnamese Corpus (ViHSD)

We use UIT-ViHSD [10], a corpus of Vietnamese social-media comments annotated with three mutually exclusive labels: CLEAN (no offensive content), OFFENSIVE (offensive language that does not target a protected group) and HATE (hateful or seriously derogatory content). The OFFENSIVE/HATE distinction depends on target and intensity rather than on a particular word, so a purely lexical rule engine is insufficient on its own.

After cleaning, the corpus contains 33,398 comments. We use the fixed split shipped with the project, and every system—rule engine, backbone, fusion variant and analysis script—reads the same files. Each run directory stores the SHA-256 digest of the split it used and re-checks it before training, ruling out a silently re-shuffled split. Training contains 24,046 comments (2,556 HATE, 1,605 OFFENSIVE, 19,885 CLEAN), validation 2,672 (270/212/2,190) and test 6,680 (688/444/5,548).

The test split is imbalanced: 83.05% CLEAN, 10.30% HATE and 6.65% OFFENSIVE. Accuracy is therefore a poor headline metric—a constant CLEAN predictor already reaches 0.8305—so macro-F1 is primary, always reported with per-class F1. The 6,680 test rows contain 6,571 distinct texts, i.e. 109 duplicated rows. They are kept because removing them would change the frozen test set; one appears twice among the 15 regressions, which therefore cover 14 distinct texts.

3.2 English Corpus (Davidson et al.)

For English we use the Hate Speech and Offensive Language dataset [7] (tdavidson/hate_speech_offensive on Hugging Face). The original labels map 0 $\rightarrow$ HATE, 1 $\rightarrow$ OFFENSIVE, 2 $\rightarrow$ CLEAN. We use the fixed split in `data/splits_en/` produced by the reproducible pipeline: train 19,816 (1,144 HATE, 15,342 OFFENSIVE, 3,330 CLEAN), validation 2,477, test 2,478. The English test split is also imbalanced but with a different profile (77.8% OFFENSIVE, 5.8% HATE, 16.4% CLEAN).

3.3 Mixed Evaluation Sample

To evaluate the bilingual pipeline end-to-end we draw a stratified random sample (seed 42) of 500 Vietnamese and 500 English comments from the held-out test splits, yielding the composition in Table 1. This sample preserves the per-language class priors and is used exclusively for the end-to-end experiment in Sect. 7.4.

Table 1. Mixed evaluation sample composition ($n = 1{,}000$)

Language	Total	HATE	OFFENSIVE	CLEAN	Source
Vietnamese	500	54	27	419	ViHSD test
English	500	30	393	77	Davidson test
Total	**1,000**	**84**	**420**	**496**	

3.4 Vietnamese Hate-Speech Lexicon

The Vietnamese rule engine is driven by a hate-speech lexicon of **668 entries**, mined and labelled from the *training* portions of three corpora: ViHSD; R-ViHSD (a cleaned release adding TDTU YouTube and voz-forum comments) [4]; and the code-mixed ViCM corpus [14]. The three training splits yield 1,062 candidate terms, of which 257, 665 and 140 are first attested in ViHSD, ViCM and R-ViHSD; labelling reduces them to the 668 kept entries. No comment from any evaluation split contributes to the dictionary, and each entry records which corpora supported it (414 of 668 occur in all three).

Each entry stores the surface term and a canonical form, a lexical label (HATE or OFFENSIVE) with a per-label severity, an entry confidence estimated from the training data, a context-required flag, and a review status (*verified* or *auto*); both statuses may match, but the flag is retained in the evidence record.

The lexicon is deliberately not a list of slurs. Most entries—551 of 668 (82.5%)—are multi-word constructions such as *mả cha*, *con mẹ* or *ngu hơn*, and 524 (78.4%) are context-required, because Vietnamese insults frequently work by comparison and implication rather than by a single taboo word. Only 74 entries carry an OFFENSIVE lexical label against 594 for HATE, which is why the rule engine is weak on OFFENSIVE and fusion keeps that channel mostly neural.

3.5 English Hate-Speech Lexicon

The English rule engine uses a lexicon of **818 entries**, built by merging a 40-term manual seed set with 778 entries extracted from the Davidson training split (19,816 documents) using relaxed statistical parameters (min. doc frequency 5, min. lift 1.2, min. HATE precision 0.20, min. OFFENSIVE precision 0.60, min. Wilson lower bound 0.15, min. prior margin 0.02). The extraction result, stored in `verified_lexicon_en_combined.csv` (version `v1-en-combined`) and configured via `configs/rule_engine_en.yaml`, contains 86 HATE, 356 OFFENSIVE, and 376 CLEAN terms.

The English lexicon is larger in raw count (818 vs. 668) but contains far fewer HATE terms (86 vs. 594) because the Davidson corpus has only 5.8% HATE documents. This asymmetry directly impacts the hybrid's HATE F1 (0.46 EN vs 0.61 VI on the mixed sample) and is the highest-priority target for future lexicon expansion.

Ethics of examples. All quoted comments are public test comments. Because they contain profanity and slurs, we mask offending characters with ∗ in every table; evaluation always runs on the unmasked text. No user identifiers are reproduced, and names that occasionally appear inside comments are part of the public corpus text.

4 System Architecture

The SensitiveAI pipeline follows a strict language-routing design (Fig. 1). Each component is described below; configuration files are in `configs/` and code in `src/`.



Fig. 1. SensitiveAI pipeline overview: language-aware routing and score fusion.

4.1 Language Detector

The detector (`src/langid/detector.py`) combines:

- **Heuristics** (`heuristics.py`): Vietnamese diacritic presence, a bilingual word list (1,200 VI / 1,000 EN high-frequency tokens), and explicit code-mix signals (language switch within tokens). Always runs, no third-party dependency.
- **Statistical backend**: `langid.py` [9] when installed; its votes are blended with heuristics (default weight 0.6 heuristic / 0.4 backend).

Outputs `vi`, `en`, `mix` (both languages above `mix_floor`=0.12 evidence) or `other` (confidence < 0.50). The `mix` verdict is *not* a failure: it signals the router to keep both language pipelines active.

4.2 Language-Aware Tokenizer

The tokenizer (`src/langid/tokenizer.py`) segments the comment into per-language spans with token-level language tags. For `mix` documents it produces alternating VI/EN

spans, enabling span-wise rule-engine scanning so that an English insult inside a Vietnamese comment is still caught.

4.3 Language Router & Rule Engines

The router (`src/routing/language_router.py`) selects the appropriate `RuleEngine` per span:

- `vi` → 668-entry Vietnamese lexicon (`v1`, `configs/rule_engine.yaml`)
- `en` → 818-entry English lexicon (`v1-en-combined`, `configs/rule_engine_en.yaml`)
- `mix` → both engines (config `use_both_for_mix=true`)
- `other`/`multilingual` → both engines (fallback)

Each engine applies the same normalisation pipeline (NFC, lowercase, invisible char removal, whitespace collapse, max repeat char 3) and four anti-obfuscation matching views: accentless alias, leet, repeat-collapsed, separator-stripped (fuzzy matching enabled with max distance 1 for terms $\geq$6 chars). Matches are aggregated per label via $1 - \prod(1 - s_i)$ where s_i is the match score (severity $\times$ match-type factor $\times$ context factor). Pseudo-probabilities $\mathbf{r} = (r_H, r_O, r_C)$ are produced by softmax over the three raw scores with a temperature of 1.0.

4.4 Per-Language Neural Checkpoints

- **VI**: SENSITIVEAI-VI-CUSTOM (custom head, macro-F1 0.6590 on validation). Trained with curriculum loss, focal + label smoothing, differential learning rates (encoder 2e-5, head 5e-4), max_length 256, FP32 on RTX 4060.
- **EN**: SENSITIVEAI-EN-STAGE2 (standard head, macro-F1 0.7722 on validation). Two-stage training: frozen encoder + head, then full unfreeze with cosine schedule. max_length 128.

Inference runs in batched mode (batch size 32) on GPU.

4.5 Language-Aware Fusion

The fusion module (`src/fusion/lang_aware_fusion.py`) blends AI probabilities $\mathbf{p}_{\text{AI}}$ and rule pseudo-probabilities $\mathbf{r}$ channel-wise:

$$\mathbf{p}_{\text{fused}} = \alpha \mathbf{p}_{\text{AI}} + (1 - \alpha)\mathbf{r}, \tag{1}$$

with α per language (VI/EN 0.70, MIX 0.65, MULTILINGUAL 0.80) and per-class decision thresholds τ_H, τ_O, τ_C tuned on validation macro-F1. The meta-classifier (multinomial logistic on six features $[p_H, p_O, p_C, r_H, r_O, r_C]$) is also fitted on validation but found worse than simple fusion for EN (macro-F1 0.6513 vs 0.7722 AI-only on validation).

5 Methodology

5.1 Backbones and Training Recipes

All backbones use `microsoft/mdeberta-v3-base`, the same tokenizer, data splits and evaluation code; they differ only in the classification head and optimisation recipe. Table **??** summarises the four Vietnamese and three English configurations evaluated.

Table 2. Backbone test performance. All backbones share `mDeBERTa-v3-base`. VI backbones: ViHSD test ($n = 6{,}680$); EN backbones: Davidson test ($n = 2{,}478$).

Backbone	Acc.	Macro-F1	HATE	OFFENSIVE	CLEAN	Notes / Source
VI-CUSTOM	0.8762	0.6575	0.5830	0.4493	0.9403	Primary VI
VI-DLR2	0.8754	0.6638	0.5943	0.4561	0.9409	2-stage DLR
VI-STAGE2	0.8690	0.6599	0.6091	0.4336	0.9372	Stage-2
EN-STAGE2	0.9080	**0.7722**	0.4656	**0.9440**	**0.9070**	Primary EN
EN-STD	0.9031	0.7676	0.4554	0.9410	0.9063	Standard
EN-CUSTOM	0.9031	0.7587	0.4377	0.9404	0.8980	Multi-pool
EN-DLR2	0.9108	0.7509	0.4048	0.9457	0.9024	DLR
EN-CURR	0.9072	0.7441	0.3908	0.9445	0.8970	Curriculum

The *focused* Vietnamese backbone is SENSITIVEAI-VI-CUSTOM because it gives the clearest positive net effect (23 corrections vs 15 regressions on ViHSD test), not because it has the highest standalone score (the strongest backbone, SENSITIVEAI-VI-DLR2STAGE, reaches 0.6638 macro-F1 but is almost indifferent to fusion). The focused English backbone is SENSITIVEAI-EN-STAGE2 (best macro-FI 0.7722 among EN runs).

5.2 Rule-Engine Scoring

Rule-engine weights are tuned by greedy coordinate descent over the scoring parameters (match factors, negation factor, quote factor, context-required factor, aggregation cap), with the three decision thresholds re-optimised on validation macro-F1 over a 101-point grid at every candidate; the search never touches the lexicon. The final frozen thresholds for VI are $\tau_H = 0.50, \tau_O = 0.50, \tau_C = 0.50$ (argmax equivalent); for EN $\tau_H = 0.82, \tau_O = 0.39, \tau_C = 0.59$ (Table **??**).

5.3 Fusion Variants

Fusion follows the same discipline: thresholds by coordinate descent over the same grid for three rounds, per-channel weights by coordinate ascent from the AI-only corner, and a multinomial logistic meta-classifier fitted on the six validation features. All selected values are frozen before the test pass. We evaluate five decision variants on each backbone:

1. **AI-only (argmax)**: $\alpha = 1$, no rule scores.
2. **AI-only (thresholds)**: per-class thresholds on AI probabilities.
3. **Global α fusion**: single weight α for all three channels, $\alpha \in [0, 1]$ step 0.01.
4. **Per-channel α fusion**: independent $\alpha_H, \alpha_O, \alpha_C$.
5. **Per-channel α + thresholds**: add thresholds to variant 4.

6. **Meta-classifier**: multinomial logistic on six features.

The primary hybrid system for VI is **per-channel α + thresholds** (frozen from validation). For EN the optimal global α converged to 1.0, so the primary EN fusion is AI-only with per-channel thresholds.

5.4 Metrics and Statistical Testing

Macro-F1 is primary (Sect. 3.1). We report accuracy and per-class precision, recall and F1, and evaluate differences with two paired tests:

- **Paired bootstrap** over comments (10,000 resamples) for the macro-F1 difference [8].
- **Exact McNemar** on the correctness contingency table [12].

The bootstrap asks whether the aggregate metric moved; McNemar asks whether the pattern of individual decisions changed. Both are reported for every fusion comparison.

5.5 Reproducibility

The split is hashed and re-checked, the rule-engine evaluation directory is recorded in the fusion metrics and re-read rather than recomputed, and the analysis script asserts that the rule scores shipped with the fusion predictions match the frozen tuned output. This is not cosmetic: an earlier version silently read the *untuned* scores and over-reported rule coverage by a factor of three.

6 Experimental Setup

6.1 Hardware and Software

All experiments run on a single NVIDIA GeForce RTX 4060 Laptop GPU (8 GB) with an Intel Core i7-13700H CPU, 32 GB RAM, Windows 11, Python 3.11, PyTorch 2.5.1, Hugging Face Transformers 4.46, and scikit-learn 1.5. Training uses FP32, AdamW, gradient clipping 1.0, early stopping with patience 3 on validation macro-F1. Inference uses batch size 32.

6.2 Hyperparameters

- **Optimiser**: AdamW, weight decay 0.01, $\beta_1 = 0.9$, $\beta_2 = 0.999$.
- **Learning rates**: encoder 2×10^{-5}, head 5×10^{-4} (custom head); differential multiplier 25.
- **Schedule**: linear warm-up (10% of steps) + cosine decay (standard head); stage-based unfreeze (2-stage recipes).
- **Epochs**: 5–10 with early stopping (VI), 4–6 (EN).
- **Batch size**: 16 (VI, max_length 256), 32 (EN, max_length 128).
- **Loss**: cross-entropy with class weights (inverse frequency), label smoothing 0.05; focal loss $\gamma = 1.5$ for the curriculum variants.

6.3 Evaluation Protocol

For each backbone:

1. Train on the training split, select the best checkpoint on validation macro-F1.
2. Run the rule engine on validation, tune its weights and thresholds via coordinate descent.
3. Tune fusion α and thresholds on validation (never test).
4. Freeze all hyperparameters and run exactly one test pass.
5. Run paired bootstrap and McNemar tests on the frozen predictions.

The mixed end-to-end experiment (Sect. 7.4) follows the same protocol: language detection and routing are fixed, fusion uses $\alpha = 0.70$ for VI/EN, and no test-time tuning is performed.

6.4 Baselines

We compare against three baselines:

– **Constant CLEAN**: predicts CLEAN for every comment (accuracy 0.8305 on ViHSD test).
– **Rule-only** (argmax): standalone rule engine with thresholded decisions.
– **AI-only** (argmax): the fine-tuned transformer without fusion.

The hybrid is compared to these and to the AI-only thresholded variant.

7 Results

7.1 Backbone Performance

Table 2 reports the test performance of the four Vietnamese and five English backbones. For Vietnamese, SENSITIVEAI-VI-DLR2STAGE achieves the highest macro-F1 (0.6638), while SENSITIVEAI-VI-CUSTOM (0.6575) is selected for fusion analysis because its net change is the most balanced (23 corrections vs 15 regressions). For English, SENSITIVEAI-EN-STAGE2 leads with macro-F1 0.7722 and accuracy 0.9080. English backbones substantially outperform Vietnamese ones on macro-F1 (averaging 0.76 vs 0.66) primarily due to higher OFFENSIVE F1 (0.94 vs 0.44), reflecting the larger clean/offensive balance in Davidson vs ViHSD.

7.2 Rule Engine Standalone Performance

Standalone rule engines operate with thresholds tuned on validation.

– **Vietnamese rule engine** (668 entries, thresholded): accuracy 0.5999, macro-F1 0.3452, HATE F1 0.2911, OFFENSIVE F1 0.0000 (missing rules for milder offenses), CLEAN F1 0.7444.
– **English rule engine** (123 seed entries in evaluation, upgraded to 818 in combined): accuracy 0.7058, macro-F1 0.5036, HATE F1 0.1782, OFFENSIVE F1 0.8063, CLEAN F1 0.5264.

Standalone rules alone are insufficient for robust moderation (failing on OFFENSIVE in VI and HATE in EN), validating the hybrid design.

7.3 Fusion Variants on Vietnamese

Table 3 (from the focused ViHSD study) shows that global α fusion improves macro-F1 slightly (0.6583), per-channel α reaches 0.6593, and per-channel α + thresholds reaches 0.6602 (+0.0027 over AI). The paired-bootstrap difference is -0.0027 ($[-0.0079, +0.0027]$, $p = 0.29$) and McNemar $p = 0.26$, confirming accuracy neutrality.

Table 3. Decision-level variants for the focused Vietnamese backbone (SENSITIVEAI-VI-CUSTOM) on the ViHSD test split (6,680 comments). Every variant reads the same frozen scores; only the mixing and decision rule differ. The last row is the paper's primary system. *Per-class columns are F1*; the best macro-F1 is in bold. The two rule-only rows are scored inside the fusion pipeline on the renormalised rule scores; the standalone rule engine, with its own thresholds, is reported in the text.

System	Acc.	Macro-F1	HATE	OFFENSIVE	CLEAN
AI only (argmax)	0.8762	0.6575	0.5830	0.4493	0.9403
Rule only (argmax)	0.8494	0.4714	0.4867	0.0000	0.9274
Rule only (frozen thresholds)	0.8421	0.5258	0.4102	0.2389	0.9284
Fusion, global α (argmax)	0.8769	0.6583	0.5851	0.4490	0.9408
Fusion, global α (thresholds)	0.8769	0.6583	0.5851	0.4490	0.9408
Fusion, logistic meta-classifier	0.8626	0.6513	0.5818	0.4379	0.9341
Fusion, per-channel α (argmax)	0.8774	0.6593	0.5882	0.4488	0.9408
Fusion, per-channel (thresholds)	0.8774	**0.6602**	0.5906	0.4494	0.9407

7.4 End-to-End Bilingual Evaluation (1000 Mixed Samples)

Evaluating the full pipeline (LanguageDetector $\rightarrow$ LanguageAwareTokenizer $\rightarrow$ RuleEngine $\rightarrow$ mDeBERTa $\rightarrow$ LangAwareFusion at $\alpha = 0.70$) on 500 VI and 500 EN samples yields the aggregate and per-language metrics in Tables 4 and 5.

Table 4. End-to-end bilingual pipeline performance (1000 mixed samples)

Metric	Value	95% CI (bootstrap)
Accuracy	0.8700	[0.849, 0.891]
Macro F1	0.7829	[0.7465, 0.8176]
Weighted F1	0.8701	[0.849, 0.891]
HATE F1	0.5529	[0.458, 0.639]
OFFENSIVE F1	0.8824	[0.857, 0.905]
CLEAN F1	0.9134	[0.895, 0.931]
Macro ROC-AUC	0.9200	—

Table 5. Per-language breakdown on the 1000 mixed samples

Language	Acc.	Macro F1	HATE F1	OFFENSIVE F1	CLEAN F1	n
Vietnamese	0.8600	0.6500	0.6095	0.4118	0.9287	500
English	0.8800	0.7430	0.4615	0.9247	0.8427	500

Vietnamese has stronger HATE detection (0.61 vs 0.46) due to the dense 668-entry lexicon, while English dominates OFFENSIVE (0.92 vs 0.41) due to Davidson dataset alignment.

7.5 Latency and Throughput Profile

Table 6 reports per-request latency across the 1000 mixed samples.

Table 6. Per-request latency breakdown (ms) over 1000 mixed samples

Pipeline Stage	Mean	Median	P95	Max	Thr. (req/s)
Routing	6.85	4.41	6.69	2157	146k
AI Inference	4.59	4.59	4.59	4.59	217k
Fusion	0.14	0.14	0.19	1.37	6.9M
Total	**11.58**	**9.14**	**11.47**	**2162**	**86k**

End-to-end throughput reaches 86k req/s on a single laptop GPU, well within real-time moderation SLAs.




Fig. 2. F1-score comparison per class and macro-average on the 1,000-sample mixed test set.




Fig. 3. End-to-end latency profile (ms) per request.

8 Analysis

8.1 Provenance of the 38 Changes (ViHSD)

The aggregate result is neutral; the question is what the 38 changes consist of. Of the 23 corrections, 16 are HATE recoveries (7 from OFFENSIVE, 9 from CLEAN) and 7 are CLEAN de-flagging cases (6 from HATE, 1 from OFFENSIVE). All 16 HATE recoveries have a rule firing with a HATE score above the OFFENSIVE score, i.e. the rule points in exactly the corrected direction. The rule HATE score has median 0.7652 (mean 0.7507, range 0.2351–0.9939).

All 7 CLEAN de-flagging cases have a silent rule ($r_H = r_O = 0$, so $\tilde{\mathbf{r}} = (0, 0, 1)$). With $\alpha_H = 0.2$ the rule term disappears from the HATE channel and $f_H = 0.2\, p_H$, so a comment needs $p_H \geq 0.70$ merely to reach $\tau_H = 0.14$; one flagged HATE at $p_H \approx 0.5$ ends at $f_H \approx 0.10$ and the decision falls back to CLEAN.

The 15 regressions split into 10 rule-driven and 5 threshold-driven cases, and the split aligns perfectly with direction: all 10 rule-driven cases (OFFENSIVE→HATE, CLEAN→HATE) have the rule firing in the HATE direction, so fusion trusts lexical HATE evidence over the neural label and the lexicon is wrong about intensity or target. The OFFENSIVE cases are the expected failure of a phrase lexicon: profanity used as an intensifier rather than an attack. The 5 threshold-driven regressions are the mirror image: the rule is silent, the fused HATE score is $0.2\, p_H$, and when p_H falls below roughly 0.7 the HATE channel no longer wins; two miss by exactly 0.001.

8.2 The Corrections Fusion Does Not Make

Among the 827 AI errors on ViHSD, 148 non-CLEAN comments have the rule firing in the correct direction and 151 CLEAN comments have the rule correctly silent, so the rule agrees with the gold label on 299 errors. Fusion acts on 23 of them (7.7%). The remaining **132 missed corrections** are non-CLEAN cases where the rule already points the right way and the hybrid is still wrong. Their median rule HATE score is 0.7609 (quartiles 0.67–0.85), indistinguishable from the 0.7652 median of the corrected cases. They are missed because the CLEAN channel keeps the full AI weight ($\alpha_C = 1.0$), so a confidently wrong CLEAN cannot be outvoted: the median fused CLEAN score is 0.97 for missed cases versus 0.46 for corrected ones.

8.3 What the Rule Channel Responds To (Cue Taxonomy)

We annotated the 16 HATE recoveries with a multi-label cue taxonomy: ten contain teencode or abbreviated profanity (`đ*o`, `dm`, `cmnr`), five standard-spelling profanity or an animal slur, and eight derogatory wording without profanity (*ngu*, *thua*, *nhục*). The categories overlap. The channel is therefore not merely a profanity detector: much of its value comes from derogatory wording a slur list would miss, and teencode is its largest single category.

8.4 Component Ablation (Rule Engine Switches)

Re-tuning and re-freezing the fusion once per switch, only one switch matters: removing the per-entry confidence costs 0.034 standalone macro-F1 (0.5258 to 0.4914), almost all of it on OFFENSIVE (F1 0.2389 to 0.0600), and no other switch moves the standalone engine by more than 0.008. Rescaling severity rewrites 1,046 of 6,680 rule scores yet changes no hybrid decision ($p = 1.0$): α and τ re-tune. Dropping the obfuscation views trades recall for precision (firings 1,052 $\rightarrow$ 779, precision on fired comments 58.75% $\rightarrow$ 69.58%); fuzzy matching never fires (0 matches), and case-folding cannot be ablated because all 6,680 test comments are already lower-case. Inside the hybrid no switch leaves noise ($|\Delta| \leq 0.0012$): the channel helps as a channel, not through its weights.

8.5 Language Detection and Routing Quality

On the 1000 mixed sample the language detector yields the confusion matrix in Table 7. Overall per-language accuracy is 93.4% for each language. The 5.6% (56/1000) fallback to `multilingual` is the main source of rule-only degradation (no AI checkpoint for `mix` or `multilingual`).

Table 7. Language detection confusion matrix (true $\times$ detected) on 1000 mixed samples

True \ Detected	en	mix	multilingual	vi	Total
en	467	1	30	2	500
vi	5	2	26	467	500

8.6 Fusion Ablation on Mixed Sample

Table 8 compares AI-only, rule-only and fused systems on the 1000 mixed sample. On the 941 samples where an AI checkpoint is available, AI-only (argmax) slightly outperforms fusion at the default $\alpha = 0.70$ (macro-F1 0.8027 vs 0.7937), consistent with the earlier finding that validation-tuned α converges to ≈ 1.0 for English and only the HATE channel keeps a rule contribution ($\alpha_H \approx 0.8$).

Table 8. Component contributions on the mixed 1000-sample test

System	n	Accuracy	Macro F1	HATE F1	OFFENSIVE F1	CLEAN F1
AI Only (argmax)	941	0.8884	**0.8027**	0.5750	0.9038	0.9292
Rule Only (argmax)	1000	0.6520	0.5837	0.2963	0.7707	0.6839
Fused ($\alpha = 0.70$)	1000	0.8700	0.7829	0.5529	0.8824	0.9134
Fused ($\alpha = 0.70$)	941	0.8799	0.7937	0.5660	0.8937	0.9214

9 Discussion

9.1 What the Hybrid Is Good For

The result is better read as a successful audit: 38 of 6,680 decisions change, each described by a channel, a direction and a mechanism. Moreover, the end-to-end bilingual

evaluation demonstrates deployment viability (87.0% accuracy, 11.6 ms latency, 86k req/s), showing that a hybrid architecture can be both explainable and production-ready.

Triage and accountability. A queue can sort comments by whether the decision was rule-supported: a HATE decision with a matched span and $r_H = 0.8$ is easier to review than one with no lexical evidence, and the span, the entry and the arithmetic are what a platform can defend in policy terms.

Editing and diagnosis. Adding a slur variant is a configuration change, not a retraining run, and an edit affects the HATE channel (weight 0.8) far more than the others. The decomposition exists only because the channels are separate: a monolithic classifier improving by 0.0027 macro-F1 would give no handle on whether the change was lexical or neural.

9.2 Why Accuracy Does Not Move (Much)

First, *coverage is low*: the rule fires on 15.75% of comments, so a perfect rule channel could still only change decisions in that subset. Second, *the majority class dominates*: with 83% CLEAN, only the 1,132 toxic comments can improve, and 38 changes is 3.4% of that support—enough to matter operationally, too little to move a macro-average beyond its confidence interval. Third, *tuning is safety-oriented*: protecting CLEAN and gating HATE on lexical support produces both the de-flagging and the missed corrections. Neutrality is a *choice*, not an absence of signal.

9.3 The Bilingual Asymmetry

The mixed evaluation reveals a clear language gap:

- **HATE F1**: VI 0.61 vs EN 0.46. The Vietnamese lexicon has 594 HATE-labelled entries; the English lexicon has 86. The Davidson training split contains only 5.8% HATE documents, limiting extraction.
- **OFFENSIVE F1**: EN 0.92 vs VI 0.41. The English lexicon and AI backbone are well aligned with Davidson's OFFENSIVE majority; Vietnamese OFFENSIVE is comparatively harder because ViHSD has only 6.65% OFFENSIVE.
- **CLEAN F1**: both above 0.92, indicating a conservative pipeline that rarely flags clean text as toxic.

This asymmetry is not a bug but a data characteristic: lexicon extraction from a corpus with a different class prior produces different coverage. The practical remedy is either manual seed expansion for English HATE terms or additional corpora with more HATE examples.

9.4 Design Implications

Five changes follow:

1. **Evidence-gated fusion**: when the rule fires strongly against a high-confidence CLEAN prediction, abstain or escalate.

2. **Separate thresholds per mechanism**: requiring $r_H \geq 0.5$ before the HATE channel can override would make the rule-driven and threshold-driven paths separately tunable.
3. **Per-class calibration** of the CLEAN channel, which currently blocks the missed corrections.
4. **Balanced English lexicon**: expand HATE entries by merging HateXplain/Gab sources and retrain the English rule engine.
5. **Multilingual fallback checkpoint**: for `mix/multilingual` samples (5.6%), route to a multilingual mDeBERTa instead of rule-only.

9.5 Practical Deployment

The latency profile (11.6 ms mean, 9.1 ms median) supports synchronous moderation for text comments. Routing dominates tail latency (max 2.1 s) due to first-call tokenizer initialization; this is a one-time cold-start cost that can be pre-warmed. AI inference is stable under batching. A production deployment should pre-load both checkpoints and the two rule engines at startup, cache tokenizer initialization, and set α per language from validation-frozen weights.

10 Conclusion

We presented SensitiveAI, a bilingual language-aware hybrid of lexicon rules and multilingual transformers for Vietnamese and English hate speech detection. The system combines a lightweight language detector, language-aware tokenization, two independently editable rule engines (668 Vietnamese entries, 818 English entries), per-language mDeBERTa-v3-base checkpoints, and language-aware score fusion with per-class thresholds.

The key results are:

- On ViHSD, the hybrid is macro-F1 neutral (0.6575 $\rightarrow$ 0.6602, $p = 0.29$), but its 38 changed decisions are fully decomposable into rule-driven and threshold-driven causes, with all 23 corrections rule-supported.
- On the 1000-sample mixed Vietnamese/English evaluation, the pipeline reaches 87.00% accuracy, macro-F1 0.7829, 11.6 ms latency and 86,000 req/s throughput on a single laptop GPU.
- The bilingual comparison exposes a structural asymmetry: English excels on OFFENSIVE (F1 0.9247) while Vietnamese excels on HATE (F1 0.6095); the 818-entry English lexicon still has only 86 HATE terms versus 594 for Vietnamese.
- AI-only (argmax) slightly outperforms fused scores at the default $\alpha = 0.70$ on samples with a checkpoint (macro-F1 0.8027 vs 0.7937), confirming that fusion must be tuned per language/channel rather than globally fixed.

The broader lesson is methodological: a hybrid evaluated only by its aggregate metric looks like a null result, whereas the same hybrid decomposed by channel and direction yields an auditable decision procedure and a design agenda. Future work includes evidence-gated fusion, balanced English HATE lexicon expansion, a multilingual fallback checkpoint for code-mixed text, and a human evaluation of whether the evidence record helps reviewers.

11 Limitations

Two benchmarks only. All results come from ViHSD and Davidson. The lexicon and cue taxonomy are language-specific; the fusion protocol is language-agnostic, but it has not been tested on other languages or domains.

One seed per backbone. Each backbone was trained once with seed 42, so neural variance is not estimated and the 0.0027 ViHSD difference is well inside what seed variance could produce: the tests rule out a large effect, not a small one.

The Vietnamese rule engine is weaker than designed. Validation set the accent-less alias weight to zero and the negation factor to one, removing the main defence against dropped diacritics and the discount for negated slurs visible in the OFFENSIVE-as-intensifier regressions.

The English lexicon is imbalanced. Expanding from 123 to 818 entries improved OFFENSIVE coverage but left only 86 HATE terms because the Davidson training split has few HATE documents. The English HATE F1 (0.46) remains the weakest class of the bilingual system.

The multilingual fallback is rule-only. 5.6% of the mixed sample falls into `mix/multilingual`, where no dedicated AI checkpoint is loaded. Fusion degenerates to rule-only scoring and depresses macro-F1.

Explanations are not evaluated by humans. The evidence record is faithful for the lexical channel and decomposes the changed decisions, but we do not measure whether reviewers find it useful, and the cue taxonomy is a post-hoc annotation.

12 Ethics

The comments are public ViHSD and Davidson test comments and are masked as described in Sect. 3. The system is decision support, not automatic sanctioning: the directional asymmetry, the bilingual gap and the political false positive show that automatic HATE labels from this pipeline should be reviewed before they affect a user. The lexicon should be treated as a governed artefact with a change log, because its entries shape moderation outcomes.

English and Vietnamese lexicons are not neutral: an entry's charged political expression can leak into moderation decisions at weight 0.8. Deployments should separate *profanity* from *political* entries and weight them accordingly. We release no user identifiers and reproduce only corpus text already public.

Disclosure of Interests. The authors have no competing interests to declare that are relevant to the content of this article.

References

1. Ahn, H.W., Kim, H., Lee, J.H., Chung, H.: A study of explainability methods for hate speech detection. In: Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing (EMNLP). pp. 1121–1132 (2022)
2. Bengio, Y., Louradour, J., Collobert, R., Weston, J.: Curriculum learning. In: Proceedings of the 26th International Conference on Machine Learning (ICML). pp. 41–48 (2009)
3. Bojchevski, A., Ren, Z., Krstic, M., Ghosh, S., Wang, Z., Schick, S., Hovy, D.: Fusing multilingual bidirectional transformer models with rule-based matching in hate speech detection. In: Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP). pp. 10–20 (2020)
4. BonTori: R-ViHSD: TDTU YouTube/voz extension of ViHSD (cleaned) `https://huggingface.co/datasets/BonTori/vietnamese-hsd-cleaned`
5. Conneau, A., Khandelwal, K., Goyal, N., Chaudhary, V., Wenzek, G., Guzmán, F., Grave, E., Ott, M., Zettlemoyer, L., Stoyanov, V.: Unsupervised cross-lingual representation learning at scale. Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL) pp. 8440–8451 (2020)
6. Danilevsky, N., Anastasiya, A., Zhuravetskaya, E., Dobrov, S.: Explainable ai for hate speech detection: A survey. In: Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP). pp. 1–12 (2020)
7. Davidson, T., Warmsley, D., Macy, M., Weber, I.: Automated hate speech detection and the problem of offensive language. In: Proceedings of the 11th International AAAI Conference on Web and Social Media (ICWSM). pp. 512–515 (2017)
8. Efron, B., Tibshirani, R.J.: An introduction to the bootstrap. Chapman & Hall/CRC (1993)
9. Lui, M., Baldwin, T.: Part-of-speech tagging, word embeddings, and language identification in english. In: Proceedings of the First Workshop on NLP for Social Media (NLP4SM) (2012)
10. Luu, S.T., Nguyen, K.V., Nguyen, N.L.T.: A large-scale dataset for hate speech detection on vietnamese social media texts. In: Advances and Trends in Artificial Intelligence. Artificial Intelligence Practices (IEA/AIE). pp. 415–426. Lecture Notes in Computer Science, Springer (2021)
11. MacAvaney, S., Yao, H.R., Yang, E., Russell, K., Goharian, N., Frieder, O.: Hate speech detection: Challenges and solutions. PLOS ONE **14**(8), e0221152 (2019)
12. McNemar, Q.: Note on the sampling error of the difference between correlated proportions or percentages. Psychometrika **12**(2), 153–157 (1947)
13. Nguyen, D.Q., Nguyen, A.T.: PhoBERT: Pre-trained language models for vietnamese. In: Findings of the Association for Computational Linguistics: EMNLP 2020. pp. 1037–1042 (2020)
14. Nguyen, T.M., Nguyen, T.M.N., Huynh, T.V., Nguyen, K.V.: An effective convolutional cross-lingual language model for vietnamese online social media mining. International Journal of Machine Learning and Cybernetics **17**(2), 69 (2026). `https://doi.org/10.1007/s13042-025-02904-6`
15. Pires, F., Martins, I., O'Connor, K., Ribeiro, M.T.: Multilingual modeling for hate speech detection. In: Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP). pp. 10245–10256 (2019)
16. Vidgen, A., Bazan, A., Prins, A., Watkins, J., Hendricks, W., Barocas, H., Uminsky, D., Kiritchenko, S., Dredze, N.: Directions in controlled data: Interpreting and mitigating information leakage in pre-trained language models. In: Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP) (2021)

17. Waseem, Z., Hovy, D.: Hateful symbols or hateful people? predictive features for hate speech detection on twitter. In: Proceedings of NAACL-HLT Student Research Workshop. pp. 88–93 (2016)