



S-Log MetaRaw

Sony metadata and Camera Raw controls for DaVinci Resolve · quick guide · v1.0

1 What it is for

With colour science and the recorded metadata you can work on the essential parameters of Sony mirrorless cameras — white balance, exposure, colour space and curve — **as if they were raw files**. Where possible, and only with a log profile (S-Log2 / S-Log3). The cameras store that data in every file, but **Resolve only reads it from FX6 and FX9 MXF**.

2 The two tools

S-Log MetaRaw script the whole project in one go

Reads the shooting data from Sony MP4 and MXF files (FX30, FX3, Alpha, a6300, FX6...) and **writes it into the Media Pool** for the selected clips or the entire project: Metadata panel, columns, keywords for smart bins, data burn-in, CSV export. It also shows everything it read, like Catalyst Browse.

Workspace › Scripts › S-Log MetaRaw

S-Log MetaRaw plugin clip by clip, in Color

A node with the controls of the Camera Raw "Sony Video" panel, which Resolve does not enable for MP4. It **sets itself** to that clip's values and interprets the clip as it was recorded: white balance and exposure start from the right numbers.

Effects › OpenFX › S-Log MetaRaw

3 Install and contents

1. Double-click **Installa S-Log MetaRaw.pkg**. It is not signed with an Apple certificate: if macOS blocks it, right-click › **Open**.
2. Your Mac password is required, because the plugin goes into a system folder.
3. **Restart DaVinci Resolve**. To remove everything: **Disinstalla S-Log MetaRaw.command**.

Plugin	/Library/OFX/Plugins/SLogMetaRaw.ofx.bundle
Script	Resolve's Fusion › Scripts › Utility
Library	/Library/Application Support/SLogMetaRaw
Requirements	macOS 12+, DaVinci Resolve 21

4 How to use it

1. **Import** your footage into the Media Pool.
2. **Workspace › Scripts › S-Log MetaRaw**: pick the source (selected clips, a bin or the whole Media Pool), then **1 · Leggi metadata** (read) and **2 · Scrivi in Resolve** (write).
3. **Color page**: add **S-Log MetaRaw** as the first node, before CST and LUTs. It sets Color Temp, Tint and Exposure to the as-shot values, where the image is unchanged. Copy it to another clip and it reloads that clip's data.

5 The plugin controls

Decode Using	Clip uses the controls; <i>Camera metadata</i> returns to the as-shot values and greys them out.
White Balance	<i>As shot</i> = camera values; presets Daylight, Cloudy, Shade, Tungsten, Fluorescent, Flash; moving the sliders switches to <i>Custom</i> .
Color Temp · Tint	White balance in linear light with chromatic adaptation, starting from the as-shot white.
Exposure	In EI: double the EI = +1 stop.
Color Space · Gamma	Like a Color Space Transform: <i>Timeline</i> does not convert; the other choices do (Rec.709, Gamma 2.4, SLog3, ACES...).
Toni (tones)	Shadows, Highlights, Color Boost, Saturation, Contrast.
Rileggi metadata	Re-reads the clip and returns everything to the camera values.
Avanzate	Detected input space and status. Dati di ripresa : lens, focal length, iris, focus, shutter, ISO/EI, white balance, data level, fps, ND, camera LUT.

6 Good to know

- Your original files are **never modified**: no transcoding, no rewrapping.
- FX6 and FX9 MXF already have the native Camera Raw panel: S-Log MetaRaw is for MP4 (XAVC S, S-I, HS).
- An **S-Log2** or **S-Log3** profile is required; with other profiles the node stays neutral. If the camera does not record Kelvin (the a6300, for example) the value is estimated from the preset and flagged in the panel.
- **Tested only on DaVinci Resolve Studio 21 (macOS), by Ivan**: earlier versions were not tried (the plugin uses features introduced with Resolve 21).
- **Independent hobby project**, provided as is, with no warranty and no liability for professional use. Open source under the **GNU GPL v3**: check it, try it, change it.