

MovieLens Recommendation System

Dr. Ivan S. Zapreev

2019-12-31

According to Wikipedia:

A recommender system or a recommendation system (sometimes replacing ‘system’ with a synonym such as platform or engine) is a subclass of information filtering system that seeks to predict the “rating” or “preference” a user would give to an item.

Introduction

Recommendation systems are widely used in commercial application to provide targeted commercials or suggest online content. In the latter, one can think of *Spotify* suggesting songs or *Youtube* proposing videos. The main goal of a recommendation system is to accurately predict client’s preferences, based on available data on the previous user behavior. Note that, such data includes the behaviour of all the clients.

The goal of this work is to build a movie recommendation system based on the MovieLens 10M dataset available from <https://grouplens.org/datasets/movielens/10m/>. To reach our goal we will use supervised machine learning techniques studied within the “*PH125.8x Data Science: Machine Learning*” course (a part of the broader HarvardX *Data Science Professional* certification program). The recommendation system will be therefore based on (linear) statistical models trained on the subset of the MovieLens 10M dataset.

The rest of the document is organized as follows. The “*Analysis*” section explains the process and techniques used, such as data cleaning, data exploration and visualization, any insights gained, and your modeling approach. The “*Results*” presents the modeling results and discusses the model performance. The “*Conclusions*” section gives a brief summary of the report, its limitations and future work.

The remainder of this section first present the data set, next analyze the dataset properties, then defines the goal of this project more concretely, and finally identifies the main steps that have been taken to reach the goal.

Dataset overview

As stated in the README of the original MovieLens 10M dataset, it contains 10000054 ratings and 95580 tags (not used in this study) applied to 10681 movies by 71567 users of the MovieLens service.

All ratings are contained in the file `ml-10M100K/ratings.dat`. Each line of this file represents one rating specified by the rating value (`rating`), the movie identifier (`movieId`), the identifier of the user (`userId`) and the submission timestamp (`timestamp`). Ratings are made on a 5-star scale, with half-star increments. Timestamps represent seconds since midnight *Coordinated Universal Time (UTC)* of January 1, 1970.

Movie information is contained in the file `ml-10M100K/movies.dat`. Each line of this file represents one movie specified by its identifier (`movieId`), movie title (`title`) and the corresponding genres (`genres`). The movie titles are entered manually, so errors and inconsistencies may exist. Genres are pipe-separated lists, of the individual genres from the following set:

```
("Action", "Adventure", "Animation", "Children's", "Comedy", "Crime", "Documentary",  
"Drama", "Fantasy", "Film-Noir", "Horror", "Musical", "Mystery", "Romance", "Sci-Fi",  
"Thriller", "War", "Western").
```

In this project, we use a pre-processed subset of the original dataset, using only the data from the `ratings.dat` and `movies.dat` files thereof. To facilitate supervised learning, the data is pre-processed in the following way:

1. The `ratings.dat` and `movies.dat` are loaded into `ratings` and `movies` data frames
 1. `ratings` – with columns named `userId`, `movieId`, `rating`, `timestamp`
 2. `movies` – columns named `movieId`, `title`, `genres`
2. The ratings are coupled with the movies information by the `movieId` into a new `movielens` data frame
3. The `movielens` data frame is randomly split into two parts:
 2. `edx` – a training set storing the 90% of the observations from the `movielens`
 3. `validation` – a testing set storing the 10% of the observations from the `movielens`
4. The `validation` set is filtered to only contain movies and users present in `edx`
5. The observations filtered out in the previous step are added back to the `edx` set

For more details, see the `create_movielens_sets` function located in the `movielens_project.R` script. As a result of pre-processing we have two sets with the following metrics, the training set `edx`:

```
## # A tibble: 1 x 3  
##   num_observations num_movies num_users  
##         <int>         <int>    <int>  
## 1         9000055         10677    69878
```


and the testing set `validation`:

```
## # A tibble: 1 x 3  
##   num_observations num_movies num_users  
##         <int>         <int>    <int>  
## 1          999999          9809    68534
```

As one can see the `edx` set stores 90% of the total number of observations (`num_observations`) and the `validation` set contains 10%. The difference in the number of distinct movies (`num_movies`) and the number of distinct users (`num_users`) is explained by the observations being moved back from `validation` to `edx` in the last data preprocessing step, described above.

Dataset analysis


Note that, from the number of distinct user, movies and observations (ratings) in the `edx` set it is clear that not every user has rated every movie as $69878 * 10677 < 9000055$. The same can be seen via the next plot for randomly sampled 100 unique users and 100 unique movies:



So the the task of a recommendation system we are to build can be seen as filling in the missing ratings. The complexity of this task is also induced by is not limited by the following factors:

- Some movies are rated more often than the others


```
movielens_data$edx %>%
  count(movieId) %>%
  ggplot(aes(n)) +
  geom_histogram(bins = 30, color = "black") +
  scale_x_log10() +
  ggtitle("Movie rating counts")
```



- Some users are more active in rating than the others

```
movielens_data$edx %>%  
  count(userId) %>%  
  ggplot(aes(n)) +  
  geom_histogram(bins = 30, color = "black") +  
  scale_x_log10() +  
  ggtitle("Users rating counts")
```


Users rating counts



- Each movie may differ from another movie in its ratings

```
#Sample 10 individual movie ids
movie_ids <- unique(movielens_data$edx$movieId)
set.seed(10000)
sample_movie_ids <- sample(movie_ids, 10)


#Use the boxplot to show variations in ratings between different movies
movielens_data$edx %>%
  filter(movieId %in% sample_movie_ids) %>%
  ggplot(aes(title, rating, group=movieId)) +
  geom_boxplot() +
  scale_x_discrete(labels = paste("movieId ", as.character(sample_movie_ids))) +
  theme(axis.text.x = element_text(angle = 90)) +
  labs(x = "Selected movies")
```



- Each user can be more or less inclined to give a range of low grades

```
#Sample 10 individual user ids
user_ids <- unique(movielens_data$edx$userId)
set.seed(9)
sample_user_ids <- sample(user_ids, 10)

#Use the boxplot to show variations in ratings between different users
movielens_data$edx %>%
  filter(userId %in% sample_user_ids) %>%
  mutate(userName = paste("userId ", as.character(userId))) %>%
  group_by(userId) %>%
  ggplot(aes(userName, rating, group=userId)) +
  geom_boxplot() +
  theme(axis.text.x = element_text(angle = 90)) +
  labs(x = "Selected users")
```



- The rating that is given may also depend on the day of the week

Project goal

Executive summary

Analysis

Results

Conclusions