

Playwright/JavaScript - Smoke Test Suite

1. Tag Your Smoke Tests

Update your test files to add `@smoke` tags. Here's how:

tests/login.spec.js

javascript

```
const { test, expect } = require('@playwright/test');
const LoginPage = require('../pages/LoginPage');
const config = require('../config/config');

test.describe('Login Tests @smoke', () => { // Added @smoke tag
  let loginPage;

  test.beforeEach(async ({ page }) => {
    loginPage = new LoginPage(page);
    await page.goto(config.baseUrl);
  });

  test('Valid login test', async () => {
    await loginPage.login(config.validEmail, config.validPassword);

    const isLoggedIn = await loginPage.isLoginSuccessful();
    expect(isLoggedIn, 'Valid login proof should contain text "Odjava").toBeTruthy();
  });

  test('Invalid login test', async () => {
    await loginPage.login(config.invalidEmail, config.invalidPassword);

    const isLoginFailed = await loginPage.isLoginFailed();
    expect(isLoginFailed, 'Invalid login proof should contain text "Prijava").toBeTruthy();
  });

  test('Empty fields login test', async () => {
    await loginPage.login("", "");

    const isLoginFailed = await loginPage.isLoginFailed();
    expect(isLoginFailed, 'Failed login proof should contain text "Prijava" when fields are empty').toBeTruthy();
  });
});
```

tests/search.spec.js

javascript

```
test.describe('Search Tests @smoke', () => { // Added @smoke tag
  // ... rest of the code
});
```

tests/cart.spec.js

javascript

```
test.describe('Cart Tests @smoke', () => { // Added @smoke tag
  // ... rest of the code
});
```

tests/buyFlow.spec.js

javascript

```
test.describe('Buy Flow Test @smoke', () => { // Added @smoke tag
  // ... rest of the code
});
```

2. Update package.json

Add smoke test script:

json

```
{  
  "scripts": {  
    "test": "npx playwright test",  
    "test:headed": "npx playwright test --headed",  
    "test:chrome": "npx playwright test --project=chromium",  
    "test:firefox": "npx playwright test --project=firefox",  
    "test:edge": "npx playwright test --project=msedge",  
    "test:smoke": "npx playwright test --grep @smoke",  
    "test:login": "npx playwright test login",  
    "test:search": "npx playwright test search",  
    "test:cart": "npx playwright test cart",  
    "test:buyflow": "npx playwright test buyFlow",  
    "report": "npx playwright show-report"  
  }  
}
```

3. Run Smoke Tests Locally

bash

Run all smoke tests

`npm run test:smoke`

Run smoke tests on specific browser

`npx playwright test --grep @smoke --project=chromium`

4. GitHub Actions Workflow

Create file: `.github/workflows/playwright-smoke-tests.yml`

yaml

name: Playwright Smoke Tests

on:

schedule:

Runs every day at 6:00 AM CET (5:00 AM UTC in winter, 4:00 AM UTC in summer)

- **cron:** '0 5 * * *'

Allows manual trigger from GitHub Actions tab

workflow_dispatch:

jobs:

smoke-tests:

timeout-minutes: 60

runs-on: ubuntu-latest

steps:

- **name:** Checkout code

uses: actions/checkout@v3

- **name:** Setup Node.js

uses: actions/setup-node@v3

with:

node-version: '18'

- **name:** Install dependencies

run: npm ci

- **name:** Install Playwright Browsers

run: npx playwright install --with-deps chromium

- **name:** Run Smoke Tests

run: npm run test:smoke

env:

CI: true

- **name:** Upload Test Results

if: always()

uses: actions/upload-artifact@v3

with:

name: playwright-report

path: playwright-report/

retention-days: 30

```
- name: Upload Screenshots
  if: failure()
  uses: actions/upload-artifact@v3
  with:
    name: screenshots
    path: screenshots/
    retention-days: 30

- name: Upload Videos
  if: failure()
  uses: actions/upload-artifact@v3
  with:
    name: videos
    path: test-results/**/video.webm
    retention-days: 30
```

5. Setup Instructions

Step 1: Update Test Files

Add `@smoke` tag to all `test.describe()` as shown above.

Step 2: Update package.json

Add the `test:smoke` script as shown above.

Step 3: Create GitHub Workflow Directory

```
bash

mkdir -p .github/workflows
```

Step 4: Add Workflow File

Create `.github/workflows/playwright-smoke-tests.yml` with the content above.

Step 5: Create Config for CI

Create a new file `config/config.ci.js`:

```
javascript
```

```
module.exports = {  
  validEmail: process.env.TEST_EMAIL || 'test@example.com',  
  validPassword: process.env.TEST_PASSWORD || 'test_password',  
  
  invalidEmail: 'invalid@example.com',  
  invalidPassword: 'wrongpassword',  
  
  baseUrl: 'https://laguna.rs/',  
  browser: 'chromium',  
  
  searchInput: 'ivo andric',  
  productTitle: 'Na Drini',  
  
  buyer: {  
    name: 'Bugs Bunny',  
    email: process.env.TEST_EMAIL || 'test@example.com',  
    country: 'Srbija',  
    phone: '641234567',  
    street: 'My Street',  
    streetNumber: '10',  
    city: '21000 Novi Sad'  
  },  
  
  timeout: {  
    default: 20000,  
    navigation: 30000,  
    action: 20000  
  }  
};
```

Step 6: Update Test Files to Use CI Config

In each test file, change:

```
javascript  
  
// Before  
const config = require('./config/config');  
  
// After (detects CI environment)  
const config = process.env.CI  
  ? require('./config/config.ci')  
  : require('./config/config');
```

Step 7: Commit and Push

```
bash

git add .github/workflows/playwright-smoke-tests.yml
git add config/config.ci.js
git add tests/*.spec.js
git add package.json
git commit -m "Add smoke test suite and GitHub Actions workflow"
git push
```

6. Add GitHub Secrets

1. Go to repository → Settings → Secrets and variables → Actions
2. Click "New repository secret"
3. Add:
 - Name: `TEST_EMAIL`
 - Value: `ivanans90@hotmail.com`
4. Add another:
 - Name: `TEST_PASSWORD`
 - Value: `your_actual_password`

Update workflow to use secrets:

```
yaml

- name: Run Smoke Tests
  env:
    TEST_EMAIL: ${ secrets.TEST_EMAIL }
    TEST_PASSWORD: ${ secrets.TEST_PASSWORD }
    CI: true
  run: npm run test:smoke
```

7. Manual Trigger

To run tests manually:

1. Go to GitHub repository → Actions tab

2. Click "Playwright Smoke Tests"
 3. Click "Run workflow" dropdown
 4. Click green "Run workflow" button
-

8. View Results

After tests run:

1. Go to Actions tab
 2. Click on the workflow run
 3. See test results in logs
 4. Download artifacts:
 - HTML report
 - Screenshots (if failed)
 - Videos (if failed)
-

9. Alternative: Run Only Critical Tests

If you want to run only the most critical smoke tests (excluding some):

Tag Individual Tests

```
javascript

test('Valid login test @critical', async () => {
  // test code
});

test('Complete buy flow test @critical', async () => {
  // test code
});
```

Run Only Critical

```
bash

npx playwright test --grep @critical
```

10. Test on Multiple Browsers in CI

Update workflow to test all browsers:

```
yaml
jobs:
  smoke-tests:
    timeout-minutes: 60
    runs-on: ubuntu-latest
    strategy:
      matrix:
        browser: [chromium, firefox, webkit]

    steps:
      - name: Checkout code
        uses: actions/checkout@v3

      - name: Setup Node.js
        uses: actions/setup-node@v3
        with:
          node-version: '18'

      - name: Install dependencies
        run: npm ci

      - name: Install Playwright Browsers
        run: npx playwright install --with-deps ${{ matrix.browser }}

      - name: Run Smoke Tests
        run: npx playwright test --grep @smoke --project=${{ matrix.browser }}
        env:
          TEST_EMAIL: ${{ secrets.TEST_EMAIL }}
          TEST_PASSWORD: ${{ secrets.TEST_PASSWORD }}
          CI: true
```

Important Notes

⚠ Time Zone:

- Cron runs in UTC

- 6 AM CET = 5 AM UTC (winter) / 4 AM UTC (summer)
- Adjust cron if needed for daylight saving time

 Costs:

- GitHub Actions: Free for public repos
- Private repos: 2,000 minutes/month free

 Test Duration:

- Smoke tests take ~5-7 minutes
- Daily run = ~210 minutes/month
- Well within free tier!

 **Your Playwright smoke tests will now run automatically every day at 6 AM CET!**