

Entrega de capturas 5-14

JS WINDOW

The screenshot shows the top part of an MDN article titled "JavaScript Window - The Browser Object Model". It includes a breadcrumb trail, navigation buttons for "Previous" and "Next", and the first paragraph explaining that the Browser Object Model (BOM) allows JavaScript to "talk to" the browser. The article is structured with sections for "The Browser Object Model (BOM)", "The Window Object", and "Global variables are properties of the window object".

JavaScript Window - The Browser Object Model

[< Previous](#) [Next >](#)

The Browser Object Model (BOM) allows JavaScript to "talk to" the browser.

The Browser Object Model (BOM)

There are no official standards for the **B**rowser **O**bject **M**odel (BOM).

Since modern browsers have implemented (almost) the same methods and properties for JavaScript interactivity, it is often referred to, as methods and properties of the BOM.

The Window Object

The `window` object is supported by all browsers. It represents the browser's window.

All global JavaScript objects, functions, and variables automatically become members of the window object.

Global variables are properties of the window object.

Global functions are methods of the window object.

JS SCREEN

The screenshot shows the MDN article "Window Screen Pixel Depth". It features a sidebar with a navigation menu for "JS Advanced" topics, including "JS Screen" which is currently selected. The main content area explains the `screen.pixelDepth` property and includes a code example to display the pixel depth of the screen.

JS versions

JS Advanced

- JS Functions
- JS Objects
- JS Classes
- JS Asynchronous
- JS Modules
- JS Meta & Proxy
- JS Typed Arrays
- JS HTML DOM
- JS Windows
- JS Window
- JS Screen**
- JS Location
- JS History
- JS Navigator
- JS Popup Alert
- JS Timing
- JS Cookies
- JS Web APIs
- JS AJAX
- JS JSON
- JS jQuery
- JS Graphics
- JS Examples

The `#rrggbb` (rgb) values used in HTML represents "True Colors" (16,777,216 different colors)

Window Screen Pixel Depth

The `screen.pixelDepth` property returns the pixel depth of the screen.

Example

Display the pixel depth of the screen in bits:

```
document.getElementById("demo").innerHTML =  
"Screen Pixel Depth: " + screen.pixelDepth;
```

Result will be:

Screen Pixel Depth: 24

[Try it Yourself >](#)

JS LOCATION

JS Advanced

JS Functions

JS Objects

JS Classes

JS Asynchronous

JS Modules

JS Meta & Proxy

JS Typed Arrays

JS HTML DOM

JS Windows

JS Window

JS Screen

JS Location

JS History

JS Navigator

JS Popup Alert

JS Timing

JS Cookies

JS Web APIs

JS AJAX

JS JSON

JS jQuery

JS Graphics

JS Examples

JS Reference

Most browsers will not display default port numbers (80 for http and 443 for https)

Window Location Assign

The `window.location.assign()` method loads a new document.

Example

Load a new document:

```
<html>
<head>
<script>
function newDoc() {
  window.location.assign("https://www.w3schools.com")
}
</script>
</head>
<body>

<input type="button" value="Load new document" onclick="newDoc()">

</body>
</html>
```

JS HISTORY

JS Advanced

JS Functions

JS Objects

JS Classes

JS Asynchronous

JS Modules

JS Meta & Proxy

JS Typed Arrays

JS HTML DOM

JS Windows

JS Window

JS Screen

JS Location

JS History

JS Navigator

JS Popup Alert

JS Timing

JS Cookies

JS Web APIs

JS AJAX

JS JSON

JS jQuery

JS Graphics

JS Examples

JS Reference

Window History Forward

The `history.forward()` method loads the next URL in the history list.

This is the same as clicking the Forward button in the browser.

Example

Create a forward button on a page:

```
<html>
<head>
<script>
function goForward() {
  window.history.forward()
}
</script>
</head>
<body>

<input type="button" value="Forward" onclick="goForward()">

</body>
</html>
```

The output of the code above will be: