

Entrega de capturas 5-15

JS NAVIGATOR

JS Functions

JS Objects

JS Classes

JS Asynchronous

JS Modules

JS Meta & Proxy

JS Typed Arrays

JS HTML DOM

JS Windows

JS Navigator

JS Popup Alert

JS Timing

JS Cookies

JS Web APIs

JS AJAX

JS JSON

JS jQuery

JS Graphics

JS Examples

JS Reference

Try it Yourself »

Warning

This property is removed (deprecated) in the latest web standard.

Most browsers (Chrome, Edge, Firefox, Safari) returns **Mozilla** as `appName`.

The Browser Engine

The `product` property returns the product name of the browser engine:

Example

```
<p id="demo"></p>

<script>
document.getElementById("demo").innerHTML =
"navigator.product is " + navigator.product;
</script>
```

JS POPUP ALERT

HTML

CSS

JAVASCRIPT

SQL

PYTHON

JAVA

PHP

HOW TO

W3.CSS

C

C++

C#

BOOTSTRAP

REACT

MYSQL

JQUERY

EXCEL

XML

JS Functions

JS Objects

JS Classes

JS Asynchronous

JS Modules

JS Meta & Proxy

JS Typed Arrays

JS HTML DOM

JS Windows

JS Navigator

JS Popup Alert

JS Timing

JS Cookies

JS Web APIs

JS AJAX

JS JSON

JS jQuery

JS Graphics

JS Examples

JS Reference

Prompt Box

A prompt box is often used if you want the user to input a value before entering a page.

When a prompt box pops up, the user will have to click either "OK" or "Cancel" to proceed after entering an input value.

If the user clicks "OK" the box returns the input value. If the user clicks "Cancel" the box returns null.

Syntax

```
window.prompt("sometext", "defaultText");
```

The `window.prompt()` method can be written without the window prefix.

Example

```
let person = prompt("Please enter your name", "Harry Potter");
let text;
if (person == null || person == "") {
  text = "User cancelled the prompt.";
} else {
  text = "Hello " + person + "! How are you today?";
}
```

Try it Yourself »

JS TIMING

JS Versions

JS Advanced

JS Functions

JS Objects

JS Classes

JS Asynchronous

JS Modules

JS Meta & Proxy

JS Typed Arrays

JS HTML DOM

JS Windows

JS Window

JS Screen

JS Location

JS History

JS Navigator

JS Popup Alert

JS Timing

JS Cookies

JS Web APIs

JS AJAX

JS JSON

JS jQuery

JS Graphics

JS Examples

JS Reference

How to Stop the Execution?

The `clearInterval()` method stops the executions of the function specified in the `setInterval()` method.

```
window.clearInterval(timerVariable)
```

The `window.clearInterval()` method can be written without the window prefix.

The `clearInterval()` method uses the variable returned from `setInterval()`:

```
let myVar = setInterval(function, milliseconds);
clearInterval(myVar);
```

Example

Same example as above, but we have added a "Stop time" button:

```
<p id="demo"></p>

<button onclick="clearInterval(myVar)">Stop time</button>

<script>
let myVar = setInterval(myTimer, 1000);
function myTimer() {
  const d = new Date();
  document.getElementById("demo").innerHTML = d.toLocaleTimeString();
}
}
```

JS COOKIES

HTML

CSS

JAVASCRIPT

SQL

PYTHON

JAVA

PHP

HOW TO

W3.CSS

C

C++

C#

BOOTSTRAP

REACT

MYSQL

JQUERY

EXCEL

XML

JS Math

JS RegExp

JS Data Types

JS Errors

JS Events

JS Conventions

JS References

JS Versions

JS Advanced

JS Functions

JS Objects

JS Classes

JS Asynchronous

JS Modules

JS Meta & Proxy

JS Typed Arrays

JS HTML DOM

JS Windows

JS Window

JS Screen

JS Location

JS History

JS Navigator

JS Popup Alert

JS Timing

The parameters of the function above are the name of the cookie (cname), the value of the cookie (cvalue), and the number of days until the cookie should expire (exdays).

The function sets a cookie by adding together the cookienname, the cookie value, and the expires string.

A Function to Get a Cookie

Then, we create a `function` that returns the value of a specified cookie:

Example

```
function getCookie(cname) {
  let name = cname + "=";
  let decodedCookie = decodeURIComponent(document.cookie);
  let ca = decodedCookie.split(';');
  for(let i = 0; i <ca.length; i++) {
    let c = ca[i];
    while (c.charAt(0) == ' ') {
      c = c.substring(1);
    }
    if (c.indexOf(name) == 0) {
      return c.substring(name.length, c.length);
    }
  }
  return "";
}
```