

Keithley 2602 Demo Program: Resistor Component Test Example

This example program demonstrates the Model 2602 using Keithley's embedded Test Script Processor™ technology to perform a high speed component test on a resistor.




Physical Connections


Parts needed:

- 1 Model 8101- 4TRX Test Fixture
- 2 Model 2600-Demo-TRX Cables
- 1 10k resistor (R-76-10k)

Connections:



Test Schematic




KEITHLEY

Simple Component Test Overview

- **R test:**
 - Resistance measurement
 - Procedure
 - Source test current
 - Measure voltage and current simultaneously, calculate resistance, evaluate pass / fail




Simple Component Test Sequence



The Traditional Test System

- Full test sequence is controlled in the PC
- PC sends many low level source and measure commands to control SMU instruments
- Data must be sent to the PC to perform pass / fail decisions
- Excessive communications between the PC and instruments result in poor test speed
- The 2600 Series SourceMeters are compatible with traditional test systems using basic instrument control commands
- BUT...For dramatically faster test times, use Keithley's Test Script Processor (TSP)




KEITHLEY

Faster Test Times With Embedded Test Script Processor!

- With Keithley's Test Script Processor:
 - The full diode test sequence runs inside Model 2602 System SourceMeter instead of on the PC
 - PC initiates all testing with a single instrument command
 - Pass / fail decisions are performed by the instrument and data is stored
 - Component handler or prober can also be controlled by the 2602
 - Data is retrieved during dead times while the handler/prober is incrementing or at the end of testing

- Elimination of excessive communication and PC delays results in up to **10X faster test times**



KEITHLEY