

# Introduction to Big Data with Apache Spark



# This Lecture

Programming Spark

Resilient Distributed Datasets (RDDs)

Creating an RDD


Spark Transformations and Actions

Spark Programming Model

# Python Spark (pySpark)

- We are using the Python programming interface to Spark ([pySpark](#))
- pySpark provides an easy-to-use programming abstraction and parallel runtime:
  - » “Here’s an operation, run it on all of the data”
- RDDs are the key concept

# Spark Driver and Workers



- A Spark program is two programs:
  - » A **driver program** and a **workers program**
- Worker programs run on cluster nodes or in local threads
- RDDs are distributed across workers

# Spark Context

- A Spark program first creates a **SparkContext** object
  - » Tells Spark how and where to access a cluster
  - » pySpark shell and Databricks Cloud automatically create the **sc** variable
  - » [iPython](#) and programs must use a constructor to create a new **SparkContext**
- Use **SparkContext** to create RDDs

In the labs, we create the SparkContext for you

# Spark Essentials: Master

- The **master** parameter for a **SparkContext** determines which type and size of cluster to use

Master Parameter	Description
<code>local</code>	run Spark locally with one worker thread (no parallelism)
<code>local[K]</code>	run Spark locally with K worker threads (ideally set to number of cores)
<code>spark://HOST:PORT</code>	connect to a Spark standalone cluster; PORT depends on config (7077 by default)
<code>mesos://HOST:PORT</code>	connect to a Mesos cluster; PORT depends on config (5050 by default)

In the labs, we set the master parameter for you

# Resilient Distributed Datasets

- The primary abstraction in Spark
  - » **Immutable once constructed**
  - » Track lineage information to efficiently recompute lost data
  - » Enable operations on collection of elements in parallel
- You construct RDDs
  - » by *parallelizing* existing Python collections (lists)
  - » by *transforming* an existing RDDs
  - » from *files* in HDFS or any other storage system

# RDDs

- Programmer specifies number of partitions for an RDD  
(Default value used if unspecified)

RDD split into 5 partitions

item-1	item-6	item-11	item-16	item-21
item-2	item-7	item-12	item-17	item-22
item-3	item-8	item-13	item-18	item-23
item-4	item-9	item-14	item-19	item-24
item-5	item-10	item-15	item-20	item-25

*more partitions = more parallelism*

Worker  
Spark  
executor

Worker  
Spark  
executor


Worker  
Spark  
executor




# RDDs

- Two types of operations: *transformations* and *actions*
- Transformations are lazy (*not computed immediately*)
- Transformed RDD is executed when action runs on it
- Persist (cache) RDDs in memory or disk

# Working with RDDs

- Create an RDD from a data source:  <list>
- Apply transformations to an RDD: map filter
- Apply actions to an RDD: collect count



# Spark References

- <http://spark.apache.org/docs/latest/programming-guide.html>
- <http://spark.apache.org/docs/latest/api/python/index.html>

# Creating an RDD

- Create RDDs from Python collections (lists)

```
>>> data = [1, 2, 3, 4, 5]
```

```
>>> data
```

```
[1, 2, 3, 4, 5]
```

```
>>> rDD = sc.parallelize(data, 4)
```

```
>>> rDD
```

```
ParallelCollectionRDD[0] at parallelize at PythonRDD.scala:229
```

No computation occurs with `sc.parallelize()`

- Spark only records how to create the RDD with four partitions



# Creating RDDs

- From HDFS, text files, [Hypertable](#), [Amazon S3](#), [Apache Hbase](#), SequenceFiles, any other Hadoop `InputFormat`, and directory or glob wildcard: `/data/201404*`

```
>>> distFile = sc.textFile("README.md", 4)
```


```
>>> distFile
```

```
MappedRDD[2] at textFile at
```

```
NativeMethodAccessorImpl.java:-2
```

## Creating an RDD from a File

```
distFile = sc.textFile("...", 4)
```



- RDD distributed in 4 partitions
- Elements are lines of input
- *Lazy evaluation* means no execution happens now

# Spark Transformations

- Create new datasets from an existing one
- Use *lazy evaluation*: results not computed right away – instead Spark remembers set of transformations applied to base dataset
  - » Spark optimizes the required calculations
  - » Spark recovers from failures and slow workers
- Think of this as a recipe for creating result

# Some Transformations

Transformation	Description
<code>map(<i>func</i>)</code>	return a new distributed dataset formed by passing each element of the source through a function <i>func</i>
<code>filter(<i>func</i>)</code>	return a new dataset formed by selecting those elements of the source on which <i>func</i> returns true
<code>distinct([<i>numTasks</i>]))</code>	return a new dataset that contains the distinct elements of the source dataset
<code>flatMap(<i>func</i>)</code>	similar to map, but each input item can be mapped to 0 or more output items (so <i>func</i> should return a Seq rather than a single item)



# Review: Python **lambda** Functions

- Small anonymous functions (not bound to a name)  
**lambda a, b: a + b**  
» returns the sum of its two arguments
- Can use lambda functions wherever function objects are required
- Restricted to a single expression

# Transformations

```
>>> rdd = sc.parallelize([1, 2, 3, 4])  
>>> rdd.map(lambda x: x * 2)  
RDD: [1, 2, 3, 4] → [2, 4, 6, 8]
```

Function literals (green)  
are closures automatically  
passed to workers

```
>>> rdd.filter(lambda x: x % 2 == 0)  
RDD: [1, 2, 3, 4] → [2, 4]
```

```
>>> rdd2 = sc.parallelize([1, 4, 2, 2, 3])  
>>> rdd2.distinct()  
RDD: [1, 4, 2, 2, 3] → [1, 4, 2, 3]
```

# Transformations

```
>>> rdd = sc.parallelize([1, 2, 3])  
>>> rdd.Map(lambda x: [x, x+5])  
RDD: [1, 2, 3] → [[1, 6], [2, 7], [3, 8]]
```


```
>>> rdd.flatMap(lambda x: [x, x+5])  
RDD: [1, 2, 3] → [1, 6, 2, 7, 3, 8]
```

Function literals (green)  
are closures automatically  
passed to workers

# Transforming an RDD

```
lines = sc.textFile("...", 4)
```

```
comments = lines.filter(isComment)
```



Lazy evaluation means  
nothing executes –  
Spark saves recipe for  
transforming source

# Spark Actions

- Cause Spark to execute recipe to transform source
- Mechanism for getting results out of Spark

# Some Actions

Action	Description
<code>reduce(func)</code>	aggregate dataset's elements using function <i>func</i> . <i>func</i> takes two arguments and returns one, and is commutative and associative so that it can be computed correctly in parallel
<code>take(n)</code>	return an array with the first <i>n</i> elements
<code>collect()</code>	return all the elements as an array <b>WARNING:</b> make sure will fit in driver program
<code>takeOrdered(n, key=func)</code>	return <i>n</i> elements ordered in ascending order or as specified by the optional key function

# Getting Data Out of RDDs

```
>>> rdd = sc.parallelize([1, 2, 3])  
>>> rdd.reduce(lambda a, b: a * b)  
Value: 6
```

```
>>> rdd.take(2)  
Value: [1,2] # as list
```

```
>>> rdd.collect()  
Value: [1,2,3] # as list
```

# Getting Data Out of RDDs


```
>>> rdd = sc.parallelize([5,3,1,2])  
>>> rdd.takeOrdered(3, lambda s: -1 * s)  
Value: [5,3,2] # as list
```



# Spark Programming Model

```
lines = sc.textFile("...", 4)
```

```
print lines.count()
```




**count()** causes Spark to:

- read data
- sum within partitions
- combine sums in driver


# Spark Programming Model

```
lines = sc.textFile("...", 4)  
comments = lines.filter(isComment)  
print lines.count(), comments.count()
```



# Caching RDDs

```
lines = sc.textFile("...", 4)  
lines.cache() # save, don't recompute!  
comments = lines.filter(isComment)  
print lines.count(), comments.count()
```



# Spark Program Lifecycle

1. Create RDDs from external data or parallelize a collection in your driver program
2. Lazily transform them into new RDDs
3. **cache()** some RDDs for reuse
4. Perform actions to execute parallel computation and produce results

# Spark Key-Value RDDs

- Similar to Map Reduce, Spark supports Key-Value pairs
- Each element of a Pair RDD is a pair tuple

```
>>> rdd = sc.parallelize([(1, 2), (3, 4)])  
RDD: [(1, 2), (3, 4)]
```

# Some Key-Value Transformations

Key-Value Transformation	Description
<code>reduceByKey(<i>func</i>)</code>	return a new distributed dataset of (K,V) pairs where the values for each key are aggregated using the given reduce function <i>func</i> , which must be of type (V,V) $\rightarrow$ V
<code>sortByKey()</code>	return a new dataset (K,V) pairs sorted by keys in ascending order
<code>groupByKey()</code>	return a new dataset of (K, Iterable<V>) pairs

# Key-Value Transformations

```
>>> rdd = sc.parallelize([(1,2), (3,4), (3,6)])
```

```
>>> rdd.reduceByKey(lambda a, b: a + b)
```

```
RDD: [(1,2), (3,4), (3,6)] → [(1,2), (3,10)]
```

```
>>> rdd2 = sc.parallelize([(1,'a'), (2,'c'), (1,'b')])
```

```
>>> rdd2.sortByKey()
```

```
RDD: [(1,'a'), (2,'c'), (1,'b')] →  
      [(1,'a'), (1,'b'), (2,'c')]
```

# Key-Value Transformations

```
>>> rdd2 = sc.parallelize([(1, 'a'), (2, 'c'), (1, 'b')])
>>> rdd2.groupByKey()
RDD: [(1, 'a'), (1, 'b'), (2, 'c')] →
      [(1, ['a', 'b']), (2, ['c'])]
```

Be careful using **groupByKey()** as it can cause a lot of data movement across the network and create large Iterables at workers



# Summary

