

Category Theory

Ivan Murashko

July 20, 2018

Contents

1	Base definitions	7
1.1	Definitions	7
1.1.1	Object	7
1.1.2	Morphism	7
1.1.3	Category	9
1.2	Examples	9
1.2.1	Set category	9
1.2.2	Hask category	10
2	Objects and morphisms	11
2.1	Equality	11
2.1.1	Equality of objects	11
2.1.2	Equality of morphisms	11
2.2	Initial and terminal objects	11
2.3	Product and sum	11
3	Functors	13
4	Monads	15
	Index	17

Introduction

There is an introduction to Category Theory.

Chapter 1

Base definitions

1.1 Definitions

1.1.1 Object

Definition 1.1 (Class). A class is a collection of sets (or sometimes other mathematical objects) that can be unambiguously defined by a property that all its members share.

Definition 1.2 (Object). In category theory object is considered as something that does not have internal structure (aka point) but has a property that makes different objects belong to the same [Class](#)

Remark 1.3 (Class of Objects). The [Class](#) of [Objects](#) will be marked as $\text{ob}(C)$

1.1.2 Morphism

Morphism is a kind of relation between 2 [Objects](#).

Definition 1.4 (Morphism). A relation between two [Objects](#) a and b

$$f_{ab} : a \rightarrow b$$

is called *morphism*. Morphism assumes a direction i.e. one [Object](#) (a) is called *source* and another one (b) *target*.

[Morphisms](#) have several properties. ¹

¹The properties don't have any proof and postulated as axioms

Property 1.5 (Composition). If we have 3 *Objects* a, b and c and 2 *Morphisms*

$$f_{ab} : a \rightarrow b$$

and

$$f_{bc} : b \rightarrow c$$

then there exists *Morphism*

$$f_{ac} : a \rightarrow c$$

such that

$$f_{ac} = f_{bc} \circ f_{ab}$$

Remark 1.6 (Composition). The equation

$$f_{ac} = f_{bc} \circ f_{ab}$$

means that we apply f_{ab} first and then we apply f_{bc} to the result of the application i.e. if our objects are sets and $x \in a$ then

$$f_{ac}(x) = f_{bc}(f_{ab}(x)),$$

where $f_{ab}(x) \in b$.

Property 1.7 (Associativity). The *Morphisms Composition* (*Property 1.5*) should follow associativity property:

$$f_{ce} \circ (f_{bc} \circ f_{ab}) = (f_{ce} \circ f_{bc}) \circ f_{ab} = f_{ce} \circ f_{bc} \circ f_{ab}.$$

Definition 1.8 (Identity morphism). For every *Object* a we define a special *Morphism* $1a : a \rightarrow a$ with the following properties: $\forall f_{ab} : a \rightarrow b$

$$1a \circ f_{ab} = f_{ab}$$


and $\forall f_{ba} : b \rightarrow a$

$$f_{ba} \circ 1a = f_{ba}.$$

This morphism is called *identity morphism*.

Definition 1.9 (Commutative diagram). A commutative diagram is a diagram of *Objects* (also known as vertices) and *Morphisms* (also known as arrows or edges) such that all directed paths in the diagram with the same start and endpoints lead to the same result by composition

The following diagram commutes if $f_{ab} = f_{cb} \circ f_{ac}$.



Remark 1.10 (Class of Morphisms). The [Class of Morphisms](#) will be marked as $\text{hom}(C)$

Definition 1.11 (Monomorphism). If $\forall g_1, g_2$ the equation

$$f \circ g_1 = f \circ g_2$$

leads to

$$g_1 = g_2$$

then f is called *monomorphism*.

Definition 1.12 (Epimorphism). If $\forall g_1, g_2$ the equation

$$g_1 \circ f = g_2 \circ f$$

leads to

$$g_1 = g_2$$

then f is called *epimorphism*.

1.1.3 Category

Definition 1.13 (Category). A category \mathbf{C} consists of

- [Class of Objects](#) $\text{ob}(C)$
- [Class of Morphisms](#) $\text{hom}(C)$ defined for $\text{ob}(C)$, i.e. each morphism f_{ab} from $\text{hom}(C)$ has both source a and target b from $\text{ob}(C)$

For any [Object](#) a there should be unique [Identity morphism](#) $1a$. Any morphism should satisfy [Composition](#) ([Property 1.5](#)) and [Associativity](#) ([Property 1.7](#)) properties.

1.2 Examples

There are several examples of categories that will also be used later

1.2.1 Set category

Definition 1.14 (Set). TBD

Definition 1.15 (Function). If A and B are 2 [Sets](#) then a subset of $A \times B$ is called function f between the 2 sets, i.e. $f \subset A \times B$.

Example 1.16 (Set category). *In the set category we consider a **Set** of **Sets** where **Objects** are the **Sets** and **Morphisms** are **Functions** between the sets.*

Remark 1.17 (Set vs Category). There is an interesting relation between sets and categories. In both we consider objects(sets) and relations between them(morphisms/functions).

In the set theory we can get info about functions by looking inside the objects(sets) aka use “microscope” [1]

Contrary in the category theory we initially don’t have info about object internal structure but can get it using the relation between the objects i.e. using **Morphisms**. In other words we can use “telescope” [1] there.

Definition 1.18 (Domain). TBD

Definition 1.19 (Codomain). TBD

Definition 1.20 (Surjection). The function $f : X \rightarrow Y$ is surjective (or onto) if $\forall y \in Y, \exists x \in X$ such that $f(x) = y$.

Remark 1.21 (Surjection vs Epimorphism). TBD

Definition 1.22 (Injection). The function $f : X \rightarrow Y$ is injective (or one-to-one function) if $\forall x_1, x_2 \in X$, such that $x_1 \neq x_2$ then $f(x_1) \neq f(x_2)$.

Remark 1.23 (Injection vs Monomorphism). TBD

1.2.2 Hask category

Example 1.24 (Hask category). *Types in Haskell are considered as **Objects** Functions are considered as **Morphisms***

For instance consider the function even that converts Int type into Bool.

`even :: Int -> Bool`

TBD

Chapter 2

Objects and morphisms

2.1 Equality

2.1.1 Equality of objects

via unique isomorphism

2.1.2 Equality of morphisms

TBD

2.2 Initial and terminal objects

2.3 Product and sum

TBD

Chapter 3

Functors

TBD

Chapter 4

Monads

TBD

Index

- Hask category
 - example, [10](#)
- Set category
 - example, [10](#)
- Associativity property, [9](#)
 - declaration, [8](#)
- Category
 - definition, [9](#)
- Class, [7](#), [9](#)
 - definition, [7](#)
- Class of Morphisms
 - remark, [9](#)
- Class of Objects
 - remark, [7](#)
- Codomain
 - definition, [10](#)
- Commutative diagram
 - definition, [8](#)
- Composition
 - remark, [8](#)
- Composition property, [8](#), [9](#)
 - declaration, [8](#)
- Domain
 - definition, [10](#)
- Epimorphism
 - definition, [9](#)
- Function, [10](#)
 - definition, [9](#)
- Identity morphism, [9](#)
 - definition, [8](#)
- Injection
 - definition, [10](#)
- Injection vs Monomorphism
 - remark, [10](#)
- Monomorphism
 - definition, [9](#)
- Morphism, [7–10](#)
 - Hask** example, [10](#)
 - Set** example, [10](#)
 - definition, [7](#)
- Object, [7–10](#)
 - Hask** example, [10](#)
 - Set** example, [10](#)
 - definition, [7](#)
- Set, [9](#), [10](#)
 - definition, [9](#)
- Set vs Category
 - remark, [10](#)
- Surjection
 - definition, [10](#)
- Surjection vs Epimorphism
 - remark, [10](#)

Bibliography

- [1] Milewski, B. Category Theory for Programmers / B. Milewski. — Bartosz Milewski, 2018. — <https://github.com/hmemcpy/milewski-ctfp-pdf/releases/download/v0.7.0/category-theory-for-programmers.pdf>.