



DCA3702

MinHeap

ivanovitch.silva@ufrn.br

Properties of a Min-Heap

P1: A Min-Heap is a complete binary tree, meaning all levels of the tree are fully filled except possibly for the last level, which is filled from left to right.

P2: Every node must be less than or equal to its children.


P3: Array Representation:

A Min-Heap can be efficiently represented using an array, where:

- The parent of a node at index i is located at $(i - 1) // 2$
- The left child is at $2 * i + 1$
- The right child is at $2 * i + 2$

P4: Main Operations

- **Build Heap:** Constructs the heap from an unsorted array.
- **Sift Down:** Reorganizes the heap after removing or replacing the top element.
- **Sift Up:** Reorganizes the heap after inserting a new element.
- **Insert:** Adds a new element to the heap and restores the heap property.
- **Remove:** Removes the smallest element (the root) and restructures the heap.



Index (i)	0	1	2	3	4	5	6	7	8
Array	[8	, 12	, 23	, 17	, 31	, 30	, 44	, 102	, 18]

Properties of a Min-Heap

P1: A Min-Heap is a complete binary tree, meaning all levels of the tree are fully filled except possibly for the last level, which is filled from left to right.

P2: Every node must be less than or equal to its children.



P3: Array Representation:

A Min-Heap can be efficiently represented using an array, where:

- The parent of a node at index i is located at $(i - 1) // 2$
- The left child is at $2 * i + 1$
- The right child is at $2 * i + 2$

P4: Main Operations

- **Build Heap:** Constructs the heap from an unsorted array.
- **Sift Down:** Reorganizes the heap after removing or replacing the top element.
- **Sift Up:** Reorganizes the heap after inserting a new element.
- **Insert:** Adds a new element to the heap and restores the heap property.
- **Remove:** Removes the smallest element (the root) and restructures the heap.



Properties of a Min-Heap

P1: A Min-Heap is a complete binary tree, meaning all levels of the tree are fully filled except possibly for the last level, which is filled from left to right.

P2: Every node must be less than or equal to its children.



P3: Array Representation:

A Min-Heap can be efficiently represented using an array, where:

- The parent of a node at index i is located at $(i - 1) // 2$
- The left child is at $2 * i + 1$
- The right child is at $2 * i + 2$

P4: Main Operations

- **Build Heap:** Constructs the heap from an unsorted array.
- **Sift Down:** Reorganizes the heap after removing or replacing the top element.
- **Sift Up:** Reorganizes the heap after inserting a new element.
- **Insert:** Adds a new element to the heap and restores the heap property.
- **Remove:** Removes the smallest element (the root) and restructures the heap.



Time Complexity - $O(\log n)$
Space Complexity - $O(1)$

Properties of a Min-Heap

P1: A Min-Heap is a complete binary tree, meaning all levels of the tree are fully filled except possibly for the last level, which is filled from left to right.

P2: Every node must be less than or equal to its children.



P3: Array Representation:

A Min-Heap can be efficiently represented using an array, where:

- The parent of a node at index i is located at $(i - 1) // 2$
- The left child is at $2 * i + 1$
- The right child is at $2 * i + 2$

P4: Main Operations

- **Build Heap:** Constructs the heap from an unsorted array.
- **Sift Down:** Reorganizes the heap after removing or replacing the top element.
- **Sift Up:** Reorganizes the heap after inserting a new element.
- **Insert:** Adds a new element to the heap and restores the heap property.
- **Remove:** Removes the smallest element (the root) and restructures the heap.



Properties of a Min-Heap

P1: A Min-Heap is a complete binary tree, meaning all levels of the tree are fully filled except possibly for the last level, which is filled from left to right.

P2: Every node must be less than or equal to its children.


P3: Array Representation:

A Min-Heap can be efficiently represented using an array, where:



- The parent of a node at index i is located at $(i - 1) // 2$
- The left child is at $2 * i + 1$
- The right child is at $2 * i + 2$

P4: Main Operations

- **Build Heap:** Constructs the heap from an unsorted array.
- **Sift Down:** Reorganizes the heap after removing or replacing the top element.
- **Sift Up:** Reorganizes the heap after inserting a new element.
- **Insert:** Adds a new element to the heap and restores the heap property.
- **Remove:** Removes the smallest element (the root) and restructures the heap.



Index (i) 0 1 2 3 4 5 6 7 8
Array [31, 9, 23, 17, 12, 30, 44, 102, 18]



Properties of a Min-Heap

P1: A Min-Heap is a complete binary tree, meaning all levels of the tree are fully filled except possibly for the last level, which is filled from left to right.

P2: Every node must be less than or equal to its children.



P3: Array Representation:

A Min-Heap can be efficiently represented using an array, where:

- The parent of a node at index i is located at $(i - 1) // 2$
- The left child is at $2 * i + 1$
- The right child is at $2 * i + 2$

P4: Main Operations

- **Build Heap:** Constructs the heap from an unsorted array.
- **Sift Down:** Reorganizes the heap after removing or replacing the top element.
- **Sift Up:** Reorganizes the heap after inserting a new element.
- **Insert:** Adds a new element to the heap and restores the heap property.
- **Remove:** Removes the smallest element (the root) and restructures the heap.



Time Complexity - $O(\log n)$

Space Complexity - $O(1)$

How to calculate the time complexity?

$$N \rightarrow \frac{N}{2} \rightarrow \frac{N}{2^2} \rightarrow \frac{N}{2^3} \rightarrow \dots \rightarrow \frac{N}{2^k}$$

In the worst case scenario:

$$2^k = N$$

$$\log 2^k = \log N$$

$$k = \log N$$

$$O(\log N)$$

$$\frac{N}{2^k} = 1$$

Properties of a Min-Heap

P1: A Min-Heap is a complete binary tree, meaning all levels of the tree are fully filled except possibly for the last level, which is filled from left to right.

P2: Every node must be less than or equal to its children.




P3: Array Representation:

A Min-Heap can be efficiently represented using an array, where:

- The parent of a node at index i is located at $(i - 1) // 2$
- The left child is at $2 * i + 1$
- The right child is at $2 * i + 2$

P4: Main Operations

- **Build Heap:** Constructs the heap from an unsorted array.
- **Sift Down:** Reorganizes the heap after removing or replacing the top element.
- **Sift Up:** Reorganizes the heap after inserting a new element.
- **Insert:** Adds a new element to the heap and restores the heap property.
- **Remove:** Removes the smallest element (the root) and restructures the heap.



Properties of a Min-Heap

P1: A Min-Heap is a complete binary tree, meaning all levels of the tree are fully filled except possibly for the last level, which is filled from left to right.

P2: Every node must be less than or equal to its children.




P3: Array Representation:

A Min-Heap can be efficiently represented using an array, where:

- The parent of a node at index i is located at $(i - 1) // 2$
- The left child is at $2 * i + 1$
- The right child is at $2 * i + 2$

P4: Main Operations

- **Build Heap:** Constructs the heap from an unsorted array.
- **Sift Down:** Reorganizes the heap after removing or replacing the top element.
- **Sift Up:** Reorganizes the heap after inserting a new element.
- **Insert:** Adds a new element to the heap and restores the heap property.
- **Remove:** Removes the smallest element (the root) and restructures the heap.



Properties of a Min-Heap

P1: A Min-Heap is a complete binary tree, meaning all levels of the tree are fully filled except possibly for the last level, which is filled from left to right.

P2: Every node must be less than or equal to its children.



P3: Array Representation:

A Min-Heap can be efficiently represented using an array, where:

- The parent of a node at index i is located at $(i - 1) // 2$
- The left child is at $2 * i + 1$
- The right child is at $2 * i + 2$

P4: Main Operations

- **Build Heap:** Constructs the heap from an unsorted array.
- **Sift Down:** Reorganizes the heap after removing or replacing the top element.
- **Sift Up:** Reorganizes the heap after inserting a new element.
- **Insert:** Adds a new element to the heap and restores the heap property.
- **Remove:** Removes the smallest element (the root) and restructures the heap.



Properties of a Min-Heap

P1: A Min-Heap is a complete binary tree, meaning all levels of the tree are fully filled except possibly for the last level, which is filled from left to right.

P2: Every node must be less than or equal to its children.



P3: Array Representation:

A Min-Heap can be efficiently represented using an array, where:

- The parent of a node at index i is located at $(i - 1) // 2$
- The left child is at $2 * i + 1$
- The right child is at $2 * i + 2$


P4: Main Operations

- **Build Heap:** Constructs the heap from an unsorted array.
- **Sift Down:** Reorganizes the heap after removing or replacing the top element.
- **Sift Up:** Reorganizes the heap after inserting a new element.
- **Insert:** Adds a new element to the heap and restores the heap property.
- **Remove:** Removes the smallest element (the root) and restructures the heap.



Time and Space Complexity Analysis of MinHeap Operations

Method	Time Complexity	Space Complexity	Note
buildHeap	$O(n)$	$O(1)$	Use bottom-up heapify
siftDown	$O(\log n)$	$O(1)$	Moves node downward
siftUp	$O(\log n)$	$O(1)$	Moves node upward
insert	$O(\log n)$	$O(1)$	Append and sift up
remove	$O(\log n)$	$O(1)$	Swap root with last, pop, and sift down
peek	$O(1)$	$O(1)$	Direct access to index 0



$$O(1) < O(\log n) < O(n) < O(n \log n) < O(n^2) < O(2^n) < O(n!)$$