

Shopify Admin API

The REST Admin API lets you build apps and other integrations for the Shopify admin.
Version 2020-10

Revisions

Date	Version	Author	Description
2024-06-01	1.0.0		
2024-06-15	1.1.0		
2024-07-01	1.2.0		

Summary

[OpenAPI JSON](https://raw.githubusercontent.com/allengrant/shopify_openapi/refs/heads/master/shopify_openapi.json): https://raw.githubusercontent.com/allengrant/shopify_openapi/refs/heads/master/shopify_openapi.json

Table of Contents

abandoned-checkouts

GET	/admin/api/2020-01/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-04/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-07/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-10/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2021-01/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/unstable/checkouts/count.json	Retrieves a count of checkouts from the past 90 days

access

GET	/admin/oauth/access_scopes.json	Retrieves a list of access scopes associated to the access token.
GET	/admin/api/2020-01/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-01/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-01/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2020-04/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-04/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-04/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2020-07/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-07/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-07/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2020-10/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-10/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-10/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2021-01/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2021-01/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2021-01/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/unstable/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/unstable/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/unstable/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token

access/accessscope

GET	/admin/oauth/access_scopes.json	Retrieves a list of access scopes associated to the access token.
---------------------	---	---

access/storefrontaccesstoken

GET	/admin/api/2020-01/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-01/storefront_access_tokens.json	Creates a new storefront access token

DELETE	/admin/api/2020-01/storefront_access_tokens/{storefront_access_token_id}.json Deletes an existing storefront access token
GET	/admin/api/2020-04/storefront_access_tokens.json Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-04/storefront_access_tokens.json Creates a new storefront access token
DELETE	/admin/api/2020-04/storefront_access_tokens/{storefront_access_token_id}.json Deletes an existing storefront access token
GET	/admin/api/2020-07/storefront_access_tokens.json Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-07/storefront_access_tokens.json Creates a new storefront access token
DELETE	/admin/api/2020-07/storefront_access_tokens/{storefront_access_token_id}.json Deletes an existing storefront access token
GET	/admin/api/2020-10/storefront_access_tokens.json Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-10/storefront_access_tokens.json Creates a new storefront access token
DELETE	/admin/api/2020-10/storefront_access_tokens/{storefront_access_token_id}.json Deletes an existing storefront access token
GET	/admin/api/2021-01/storefront_access_tokens.json Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2021-01/storefront_access_tokens.json Creates a new storefront access token
DELETE	/admin/api/2021-01/storefront_access_tokens/{storefront_access_token_id}.json Deletes an existing storefront access token
GET	/admin/api/unstable/storefront_access_tokens.json Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/unstable/storefront_access_tokens.json Creates a new storefront access token
DELETE	/admin/api/unstable/storefront_access_tokens/{storefront_access_token_id}.json Deletes an existing storefront access token

accessscope

GET	/admin/oauth/access_scopes.json Retrieves a list of access scopes associated to the access token.
------------	--

analytics

GET	/admin/api/2020-01/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/reports.json Creates a new report
GET	/admin/api/2020-01/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2020-01/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-01/reports/{report_id}.json Deletes a report
GET	/admin/api/2020-04/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/reports.json Creates a new report
GET	/admin/api/2020-04/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2020-04/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-04/reports/{report_id}.json Deletes a report
GET	/admin/api/2020-07/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/reports.json Creates a new report
GET	/admin/api/2020-07/reports/{report_id}.json Retrieves a single report created by your app

PUT	/admin/api/2020-07/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-07/reports/{report_id}.json Deletes a report
GET	/admin/api/2020-10/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/reports.json Creates a new report
GET	/admin/api/2020-10/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2020-10/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-10/reports/{report_id}.json Deletes a report
GET	/admin/api/2021-01/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/reports.json Creates a new report
GET	/admin/api/2021-01/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2021-01/reports/{report_id}.json Updates a report
DELETE	/admin/api/2021-01/reports/{report_id}.json Deletes a report
GET	/admin/api/unstable/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/reports.json Creates a new report
GET	/admin/api/unstable/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/unstable/reports/{report_id}.json Updates a report
DELETE	/admin/api/unstable/reports/{report_id}.json Deletes a report

analytics/report

GET	/admin/api/2020-01/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/reports.json Creates a new report
GET	/admin/api/2020-01/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2020-01/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-01/reports/{report_id}.json Deletes a report
GET	/admin/api/2020-04/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/reports.json Creates a new report
GET	/admin/api/2020-04/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2020-04/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-04/reports/{report_id}.json Deletes a report
GET	/admin/api/2020-07/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/reports.json Creates a new report
GET	/admin/api/2020-07/reports/{report_id}.json Retrieves a single report created by your app

PUT	/admin/api/2020-07/reports/{report_id}.json	Updates a report
DELETE	/admin/api/2020-07/reports/{report_id}.json	Deletes a report
GET	/admin/api/2020-10/reports.json	Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/reports.json	Creates a new report
GET	/admin/api/2020-10/reports/{report_id}.json	Retrieves a single report created by your app
PUT	/admin/api/2020-10/reports/{report_id}.json	Updates a report
DELETE	/admin/api/2020-10/reports/{report_id}.json	Deletes a report
GET	/admin/api/2021-01/reports.json	Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/reports.json	Creates a new report
GET	/admin/api/2021-01/reports/{report_id}.json	Retrieves a single report created by your app
PUT	/admin/api/2021-01/reports/{report_id}.json	Updates a report
DELETE	/admin/api/2021-01/reports/{report_id}.json	Deletes a report
GET	/admin/api/unstable/reports.json	Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/reports.json	Creates a new report
GET	/admin/api/unstable/reports/{report_id}.json	Retrieves a single report created by your app
PUT	/admin/api/unstable/reports/{report_id}.json	Updates a report
DELETE	/admin/api/unstable/reports/{report_id}.json	Deletes a report

applicationcharge

GET	/admin/api/2020-01/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2020-01/application_charges.json	Creates an application charge
GET	/admin/api/2020-01/application_charges/{application_charge_id}.json	Retrieves an application charge
POST	/admin/api/2020-01/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-04/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2020-04/application_charges.json	Creates an application charge
GET	/admin/api/2020-04/application_charges/{application_charge_id}.json	Retrieves an application charge
POST	/admin/api/2020-04/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-07/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2020-07/application_charges.json	Creates an application charge
GET	/admin/api/2020-07/application_charges/{application_charge_id}.json	Retrieves an application charge
POST	/admin/api/2020-07/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-10/application_charges.json	Retrieves a list of application charges

POST	/admin/api/2020-10/application_charges.json	Creates an application charge
GET	/admin/api/2020-10/application_charges/{application_charge_id}.json	Retrieves an application charge
POST	/admin/api/2020-10/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2021-01/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2021-01/application_charges.json	Creates an application charge
GET	/admin/api/2021-01/application_charges/{application_charge_id}.json	Retrieves an application charge
GET	/admin/api/unstable/application_charges.json	Retrieves a list of application charges
POST	/admin/api/unstable/application_charges.json	Creates an application charge
GET	/admin/api/unstable/application_charges/{application_charge_id}.json	Retrieves an application charge

applicationcredit

GET	/admin/api/2020-01/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-01/application_credits.json	Creates an application credit
GET	/admin/api/2020-01/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-04/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-04/application_credits.json	Creates an application credit
GET	/admin/api/2020-04/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-07/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-07/application_credits.json	Creates an application credit
GET	/admin/api/2020-07/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-10/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-10/application_credits.json	Creates an application credit
GET	/admin/api/2020-10/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2021-01/application_credits.json	Retrieves all application credits
POST	/admin/api/2021-01/application_credits.json	Creates an application credit
GET	/admin/api/2021-01/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/unstable/application_credits.json	Retrieves all application credits
POST	/admin/api/unstable/application_credits.json	Creates an application credit
GET	/admin/api/unstable/application_credits/{application_credit_id}.json	Retrieves a single application credit

article

GET	/admin/api/2020-01/blogs/{blog_id}/articles.json	Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/blogs/{blog_id}/articles.json	Creates an article for a blog
GET	/admin/api/2020-01/blogs/{blog_id}/articles/count.json	Retrieves a count of all articles from a blog
GET	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json	

	Retrieves a single article
PUT	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json
	Updates an article
DELETE	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json
	Deletes an article
GET	/admin/api/2020-01/articles/authors.json
	Retrieves a list all of article authors
GET	/admin/api/2020-01/articles/tags.json
	Retrieves a list of all the tags
GET	/admin/api/2020-04/blogs/{blog_id}/articles.json
	Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/blogs/{blog_id}/articles.json
	Creates an article for a blog
GET	/admin/api/2020-04/blogs/{blog_id}/articles/count.json
	Retrieves a count of all articles from a blog
GET	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json
	Retrieves a single article
PUT	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json
	Updates an article
DELETE	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json
	Deletes an article
GET	/admin/api/2020-04/articles/authors.json
	Retrieves a list all of article authors
GET	/admin/api/2020-04/articles/tags.json
	Retrieves a list of all the tags
GET	/admin/api/2020-07/blogs/{blog_id}/articles.json
	Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/blogs/{blog_id}/articles.json
	Creates an article for a blog
GET	/admin/api/2020-07/blogs/{blog_id}/articles/count.json
	Retrieves a count of all articles from a blog
GET	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json
	Retrieves a single article
PUT	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json
	Updates an article
DELETE	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json
	Deletes an article
GET	/admin/api/2020-07/articles/authors.json
	Retrieves a list all of article authors
GET	/admin/api/2020-07/articles/tags.json
	Retrieves a list of all the tags
GET	/admin/api/2020-10/blogs/{blog_id}/articles.json
	Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/blogs/{blog_id}/articles.json
	Creates an article for a blog
GET	/admin/api/2020-10/blogs/{blog_id}/articles/count.json
	Retrieves a count of all articles from a blog
GET	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json
	Retrieves a single article
PUT	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json
	Updates an article
DELETE	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json
	Deletes an article
GET	/admin/api/2020-10/articles/authors.json
	Retrieves a list all of article authors
GET	/admin/api/2020-10/articles/tags.json
	Retrieves a list of all the tags
GET	/admin/api/2021-01/blogs/{blog_id}/articles.json
	Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/blogs/{blog_id}/articles.json
	Creates an article for a blog
GET	/admin/api/2021-01/blogs/{blog_id}/articles/count.json
	Retrieves a count of all articles from a blog
GET	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json

PUT	Retrieves a single article /admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2021-01/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2021-01/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/unstable/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/unstable/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/unstable/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/unstable/articles/tags.json Retrieves a list of all the tags

asset

GET	/admin/api/2020-01/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-01/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-01/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-04/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-04/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-04/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-07/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-07/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-07/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-10/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-10/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-10/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2021-01/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2021-01/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.

DELETE	/admin/api/2021-01/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/unstable/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties .
PUT	/admin/api/unstable/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/unstable/themes/{theme_id}/assets.json Deletes an asset from a theme.

assignedfulfillmentorder

GET	/admin/api/2020-01/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.
GET	/admin/api/2020-04/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.
GET	/admin/api/2020-07/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.
GET	/admin/api/2020-10/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.
GET	/admin/api/2021-01/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.
GET	/admin/api/unstable/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.

balance

GET	/admin/api/2020-01/shopify_payments/balance.json Retrieves the account's current balance.
GET	/admin/api/2020-04/shopify_payments/balance.json Retrieves the account's current balance.
GET	/admin/api/2020-07/shopify_payments/balance.json Retrieves the account's current balance.
GET	/admin/api/2020-10/shopify_payments/balance.json Retrieves the account's current balance.
GET	/admin/api/2021-01/shopify_payments/balance.json Retrieves the account's current balance.
GET	/admin/api/unstable/shopify_payments/balance.json Retrieves the account's current balance.

billing

GET	/admin/api/2020-01/application_charges.json Retrieves a list of application charges
POST	/admin/api/2020-01/application_charges.json Creates an application charge
GET	/admin/api/2020-01/application_charges/{application_charge_id}.json Retrieves an application charge
POST	/admin/api/2020-01/application_charges/{application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-04/application_charges.json Retrieves a list of application charges
POST	/admin/api/2020-04/application_charges.json Creates an application charge
GET	/admin/api/2020-04/application_charges/{application_charge_id}.json Retrieves an application charge
POST	/admin/api/2020-04/application_charges/{application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-07/application_charges.json Retrieves a list of application charges
POST	/admin/api/2020-07/application_charges.json Creates an application charge
GET	/admin/api/2020-07/application_charges/{application_charge_id}.json Retrieves an application charge
POST	/admin/api/2020-07/application_charges/{application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

GET	/admin/api/2020-10/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2020-10/application_charges.json	Creates an application charge
GET	/admin/api/2020-10/application_charges/{application_charge_id}.json	Retrieves an application charge
POST	/admin/api/2020-10/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2021-01/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2021-01/application_charges.json	Creates an application charge
GET	/admin/api/2021-01/application_charges/{application_charge_id}.json	Retrieves an application charge
GET	/admin/api/unstable/application_charges.json	Retrieves a list of application charges
POST	/admin/api/unstable/application_charges.json	Creates an application charge
GET	/admin/api/unstable/application_charges/{application_charge_id}.json	Retrieves an application charge
GET	/admin/api/2020-01/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-01/application_credits.json	Creates an application credit
GET	/admin/api/2020-01/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-04/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-04/application_credits.json	Creates an application credit
GET	/admin/api/2020-04/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-07/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-07/application_credits.json	Creates an application credit
GET	/admin/api/2020-07/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-10/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-10/application_credits.json	Creates an application credit
GET	/admin/api/2020-10/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2021-01/application_credits.json	Retrieves all application credits
POST	/admin/api/2021-01/application_credits.json	Creates an application credit
GET	/admin/api/2021-01/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/unstable/application_credits.json	Retrieves all application credits
POST	/admin/api/unstable/application_credits.json	Creates an application credit
GET	/admin/api/unstable/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-01/recurring_application_charges.json	Retrieves a list of recurring application charges
POST	/admin/api/2020-01/recurring_application_charges.json	Creates a recurring application charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json	Retrieves a single charge
DELETE	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json	Cancels a recurring application charge
POST	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/activate.json	

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

PUT /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

GET /admin/api/2020-04/recurring_application_charges.json

Retrieves a list of recurring application charges

POST /admin/api/2020-04/recurring_application_charges.json

Creates a recurring application charge

GET /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

DELETE /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

POST /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

PUT /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

GET /admin/api/2020-07/recurring_application_charges.json

Retrieves a list of recurring application charges

POST /admin/api/2020-07/recurring_application_charges.json

Creates a recurring application charge

GET /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

DELETE /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

POST /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

PUT /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

GET /admin/api/2020-10/recurring_application_charges.json

Retrieves a list of recurring application charges

POST /admin/api/2020-10/recurring_application_charges.json

Creates a recurring application charge

GET /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

DELETE /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

POST /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

PUT /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

GET /admin/api/2021-01/recurring_application_charges.json

Retrieves a list of recurring application charges

POST /admin/api/2021-01/recurring_application_charges.json

Creates a recurring application charge

GET /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

DELETE /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

PUT /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

GET /admin/api/unstable/recurring_application_charges.json

Retrieves a list of recurring application charges

POST /admin/api/unstable/recurring_application_charges.json

Creates a recurring application charge

GET /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

DELETE /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

PUT /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

GET /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Retrieves a list of usage charges

POST /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Creates a usage charge

GET /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

GET	Retrieves a single charge /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
POST	Retrieves a list of usage charges /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
GET	Creates a usage charge /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json
GET	Retrieves a single charge /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
POST	Retrieves a list of usage charges /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
GET	Creates a usage charge /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json
GET	Retrieves a single charge /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
POST	Retrieves a list of usage charges /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
GET	Creates a usage charge /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json
GET	Retrieves a single charge /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
POST	Retrieves a list of usage charges /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
GET	Creates a usage charge /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json
GET	Retrieves a single charge /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
POST	Retrieves a list of usage charges /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
GET	Creates a usage charge /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

billing/applicationcharge

GET	/admin/api/2020-01/application_charges.json Retrieves a list of application charges
POST	/admin/api/2020-01/application_charges.json Creates an application charge
GET	/admin/api/2020-01/application_charges/{application_charge_id}.json Retrieves an application charge
POST	/admin/api/2020-01/application_charges/{application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-04/application_charges.json Retrieves a list of application charges
POST	/admin/api/2020-04/application_charges.json Creates an application charge
GET	/admin/api/2020-04/application_charges/{application_charge_id}.json Retrieves an application charge
POST	/admin/api/2020-04/application_charges/{application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-07/application_charges.json Retrieves a list of application charges
POST	/admin/api/2020-07/application_charges.json Creates an application charge
GET	/admin/api/2020-07/application_charges/{application_charge_id}.json Retrieves an application charge
POST	/admin/api/2020-07/application_charges/{application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-10/application_charges.json Retrieves a list of application charges
POST	/admin/api/2020-10/application_charges.json Creates an application charge
GET	/admin/api/2020-10/application_charges/{application_charge_id}.json Retrieves an application charge
POST	/admin/api/2020-10/application_charges/{application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

GET	/admin/api/2021-01/application_charges.json
	Retrieves a list of application charges
POST	/admin/api/2021-01/application_charges.json
	Creates an application charge
GET	/admin/api/2021-01/application_charges/{application_charge_id}.json
	Retrieves an application charge
GET	/admin/api/unstable/application_charges.json
	Retrieves a list of application charges
POST	/admin/api/unstable/application_charges.json
	Creates an application charge
GET	/admin/api/unstable/application_charges/{application_charge_id}.json
	Retrieves an application charge

billing/applicationcredit

GET	/admin/api/2020-01/application_credits.json
	Retrieves all application credits
POST	/admin/api/2020-01/application_credits.json
	Creates an application credit
GET	/admin/api/2020-01/application_credits/{application_credit_id}.json
	Retrieves a single application credit
GET	/admin/api/2020-04/application_credits.json
	Retrieves all application credits
POST	/admin/api/2020-04/application_credits.json
	Creates an application credit
GET	/admin/api/2020-04/application_credits/{application_credit_id}.json
	Retrieves a single application credit
GET	/admin/api/2020-07/application_credits.json
	Retrieves all application credits
POST	/admin/api/2020-07/application_credits.json
	Creates an application credit
GET	/admin/api/2020-07/application_credits/{application_credit_id}.json
	Retrieves a single application credit
GET	/admin/api/2020-10/application_credits.json
	Retrieves all application credits
POST	/admin/api/2020-10/application_credits.json
	Creates an application credit
GET	/admin/api/2020-10/application_credits/{application_credit_id}.json
	Retrieves a single application credit
GET	/admin/api/2021-01/application_credits.json
	Retrieves all application credits
POST	/admin/api/2021-01/application_credits.json
	Creates an application credit
GET	/admin/api/2021-01/application_credits/{application_credit_id}.json
	Retrieves a single application credit
GET	/admin/api/unstable/application_credits.json
	Retrieves all application credits
POST	/admin/api/unstable/application_credits.json
	Creates an application credit
GET	/admin/api/unstable/application_credits/{application_credit_id}.json
	Retrieves a single application credit

billing/recurringapplicationcharge

GET	/admin/api/2020-01/recurring_application_charges.json
	Retrieves a list of recurring application charges
POST	/admin/api/2020-01/recurring_application_charges.json
	Creates a recurring application charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json
	Retrieves a single charge
DELETE	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json
	Cancels a recurring application charge
POST	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/activate.json
	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/customize.json
	Updates the capped amount of an active recurring application charge

GET	/admin/api/2020-04/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/2020-04/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
POST	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-07/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/2020-07/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
POST	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-10/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/2020-10/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge
GET	/admin/api/2021-01/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/2021-01/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
PUT	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge
GET	/admin/api/unstable/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/unstable/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
PUT	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge

billing/usagcharge

GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge

GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge

blog

GET	/admin/api/2020-01/blogs.json Retrieve a list of all blogs. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/blogs.json Create a new blog
GET	/admin/api/2020-01/blogs/count.json Get a count of all blogs
GET	/admin/api/2020-01/blogs/{blog_id}.json Get a single blog by its ID
PUT	/admin/api/2020-01/blogs/{blog_id}.json Update a blog
DELETE	/admin/api/2020-01/blogs/{blog_id}.json Delete a blog

cancellationrequest

POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json Sends a cancellation request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json Accepts a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json Rejects a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json Sends a cancellation request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json Accepts a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json Rejects a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json Sends a cancellation request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json Accepts a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json Rejects a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json Sends a cancellation request to the fulfillment service of a fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

carrierservice

GET /admin/api/2020-01/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2020-01/carrier_services.json
Creates a carrier service

GET /admin/api/2020-01/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-01/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-01/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2020-04/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2020-04/carrier_services.json
Creates a carrier service

GET /admin/api/2020-04/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-04/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-04/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2020-07/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2020-07/carrier_services.json
Creates a carrier service

GET /admin/api/2020-07/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-07/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-07/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2020-10/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2020-10/carrier_services.json
Creates a carrier service

GET /admin/api/2020-10/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-10/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-10/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2021-01/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2021-01/carrier_services.json
Creates a carrier service

GET /admin/api/2021-01/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2021-01/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE	/admin/api/2021-01/carrier_services/{carrier_service_id}.json Deletes a carrier service
GET	/admin/api/unstable/carrier_services.json Retrieves a list of carrier services
POST	/admin/api/unstable/carrier_services.json Creates a carrier service
GET	/admin/api/unstable/carrier_services/{carrier_service_id}.json Retrieves a single carrier service by its ID
PUT	/admin/api/unstable/carrier_services/{carrier_service_id}.json Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/unstable/carrier_services/{carrier_service_id}.json Deletes a carrier service

checkout

POST	/admin/api/2020-01/checkouts.json Creates a checkout
POST	/admin/api/2020-04/checkouts.json Creates a checkout
POST	/admin/api/2020-07/checkouts.json Creates a checkout
POST	/admin/api/2020-10/checkouts.json Creates a checkout
POST	/admin/api/2021-01/checkouts.json Creates a checkout
POST	/admin/api/unstable/checkouts.json Creates a checkout
POST	/admin/api/2020-01/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-01/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-01/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-01/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-04/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-04/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-04/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-04/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-07/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-07/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-07/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-07/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-10/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-10/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-10/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-10/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to

update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

POST </admin/api/2021-01/checkouts/{token}/complete.json>

Completes a checkout

GET </admin/api/2021-01/checkouts/{token}.json>

Retrieves a checkout

PUT </admin/api/2021-01/checkouts/{token}.json>

Modifies an existing checkout

GET /admin/api/2021-01/checkouts/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

POST </admin/api/unstable/checkouts/{token}/complete.json>

Completes a checkout

GET </admin/api/unstable/checkouts/{token}.json>

Retrieves a checkout

PUT </admin/api/unstable/checkouts/{token}.json>

Modifies an existing checkout

GET /admin/api/unstable/checkouts/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

collect

GET </admin/api/2020-01/collects.json>

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/collects.json>

Adds a product to a custom collection.

GET /admin/api/2020-01/collects/{collect_id}.json

Retrieves a specific collect by its ID.

DELETE /admin/api/2020-01/collects/{collect_id}.json

Removes a product from a collection.

GET </admin/api/2020-01/collects/count.json>

Retrieves a count of collects.

GET </admin/api/2020-04/collects.json>

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-04/collects.json>

Adds a product to a custom collection.

GET /admin/api/2020-04/collects/{collect_id}.json

Retrieves a specific collect by its ID.

DELETE /admin/api/2020-04/collects/{collect_id}.json

Removes a product from a collection.

GET </admin/api/2020-04/collects/count.json>

Retrieves a count of collects.

GET </admin/api/2020-07/collects.json>

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-07/collects.json>

Adds a product to a custom collection.

GET /admin/api/2020-07/collects/{collect_id}.json

Retrieves a specific collect by its ID.

DELETE /admin/api/2020-07/collects/{collect_id}.json

Removes a product from a collection.

GET </admin/api/2020-07/collects/count.json>

Retrieves a count of collects.

GET </admin/api/2020-10/collects.json>

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-10/collects.json>

Adds a product to a custom collection.

GET /admin/api/2020-10/collects/{collect_id}.json

Retrieves a specific collect by its ID.

DELETE /admin/api/2020-10/collects/{collect_id}.json

Removes a product from a collection.

GET </admin/api/2020-10/collects/count.json>

GET	/admin/api/2021-01/collects.json	Retrieves a count of collects.
POST	/admin/api/2021-01/collects.json	Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/collects/{collect_id}.json	Adds a product to a custom collection.
DELETE	/admin/api/2021-01/collects/{collect_id}.json	Retrieves a specific collect by its ID.
GET	/admin/api/2021-01/collects/count.json	Removes a product from a collection.
GET	/admin/api/unstable/collects.json	Retrieves a count of collects.
POST	/admin/api/unstable/collects.json	Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/collects/{collect_id}.json	Adds a product to a custom collection.
DELETE	/admin/api/unstable/collects/{collect_id}.json	Retrieves a specific collect by its ID.
GET	/admin/api/unstable/collects/count.json	Removes a product from a collection.
GET	/admin/api/unstable/collects/count.json	Retrieves a count of collects.

collection

GET	/admin/api/2020-01/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-01/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-04/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-04/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-07/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-07/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-10/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-10/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2021-01/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2021-01/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/unstable/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/unstable/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

collectionlisting

GET	/admin/api/2020-01/collection_listings.json	Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/collection_listings/{collection_listing_id}/product_ids.json	Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-01/collection_listings/{collection_listing_id}.json

PUT /admin/api/2020-01/collection_listings/{collection_listing_id}.json

DELETE /admin/api/2020-01/collection_listings/{collection_listing_id}.json

[GET /admin/api/2020-04/collection_listings.json](#)

[GET](#) [/admin/api/2020-04/collection_listings/{collection_listing_id}/product_ids.json](#)

GET /admin/api/2020-04/collection_listings/{collection_listing_id}.json

PUT /admin/api/2020-04/collection_listings/{collection_listing_id}.json

DELETE /admin/api/2020-04/collection_listings/{collection_listing_id}.json

[GET /admin/api/2020-07/collection_listings.json](#)

[GET /admin/api/2020-07/collection_listings/{collection_listing_id}/product_ids.json](#)

[GET /admin/api/2020-07/collection_listings/{collection_listing_id}.json](#)

PUT [/admin/api/2020-07/collection_listings/{collection_listing_id}.json](#)

DELETE /admin/api/2020-07/collection_listings/{collection_listing_id}.json

[GET /admin/api/2020-10/collection_listings.json](#)

[GET /admin/api/2020-10/collection_listings/{collection_listing_id}/product_ids.json](#)

[GET](#) [/admin/api/2020-10/collection_listings/{collection_listing_id}.json](#)

PUT /admin/api/2020-10/collection_listings/{collection_listing_id}.json

DELETE /admin/api/2020-10/collection_listings/{collection_listing_id}.json

[GET /admin/api/2021-01/collection_listings.json](#)

[GET /admin/api/2021-01/collection_listings/{collection_listing_id}/product_ids.json](#)

[GET /admin/api/2021-01/collection_listings/{collection_listing_id}.json](#)

PUT /admin/api/2021-01/collection_listings/{collection_listing_id}.json

DELETE /admin/api/2021-01/collection_listings/{collection_listing_id}.json

GET /admin/api/unstable/collection_listings.json

GET [/admin/api/unstable/collection_listings/{collection_listing_id}/product_ids.json](#)

[GET](#) [/admin/api/unstable/collection_listings/{collection_listing_id}.json](#)

[PUT](#) [/admin/api/unstable/collection_listings/{collection_listing_id}.json](#)

Create a collection listing to publish a collection to your app

[DELETE](#) [/admin/api/unstable/collection_listings/{collection_listing_id}.json](#)

Delete a collection listing to unpublish a collection from your app

comment

[GET](#) [/admin/api/2020-01/comments.json](#)

Retrieves a list of comments. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-01/comments.json](#)

Creates a comment for an article

[GET](#) [/admin/api/2020-01/comments/count.json](#)

Retrieves a count of comments

[GET](#) [/admin/api/2020-01/comments/{comment_id}.json](#)

Retrieves a single comment by its ID

[PUT](#) [/admin/api/2020-01/comments/{comment_id}.json](#)

Updates a comment of an article

[POST](#) [/admin/api/2020-01/comments/{comment_id}/spam.json](#)

Marks a comment as spam

[POST](#) [/admin/api/2020-01/comments/{comment_id}/not_spam.json](#)

Marks a comment as not spam

[POST](#) [/admin/api/2020-01/comments/{comment_id}/approve.json](#)

Approves a comment

[POST](#) [/admin/api/2020-01/comments/{comment_id}/remove.json](#)

Removes a comment

[POST](#) [/admin/api/2020-01/comments/{comment_id}/restore.json](#)

Restores a previously removed comment

country

[GET](#) [/admin/api/2020-01/countries.json](#)

Retrieves a list of countries.

[POST](#) [/admin/api/2020-01/countries.json](#)

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

[GET](#) [/admin/api/2020-01/countries/count.json](#)

Retrieves a count of countries.

[GET](#) [/admin/api/2020-01/countries/{country_id}.json](#)

Retrieves a specific county.

[PUT](#) [/admin/api/2020-01/countries/{country_id}.json](#)

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

[DELETE](#) [/admin/api/2020-01/countries/{country_id}.json](#)

Deletes a country.

[GET](#) [/admin/api/2020-04/countries.json](#)

Retrieves a list of countries.

[POST](#) [/admin/api/2020-04/countries.json](#)

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

[GET](#) [/admin/api/2020-04/countries/count.json](#)

Retrieves a count of countries.

[GET](#) [/admin/api/2020-04/countries/{country_id}.json](#)

Retrieves a specific county.

[PUT](#) [/admin/api/2020-04/countries/{country_id}.json](#)

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

[DELETE](#) [/admin/api/2020-04/countries/{country_id}.json](#)

Deletes a country.

[GET](#) [/admin/api/2020-07/countries.json](#)

Retrieves a list of countries.

[POST](#) [/admin/api/2020-07/countries.json](#)

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

[GET](#) [/admin/api/2020-07/countries/count.json](#)

Retrieves a count of countries.

[GET](#) [/admin/api/2020-07/countries/{country_id}.json](#)

Retrieves a specific county.

[PUT](#) [/admin/api/2020-07/countries/{country_id}.json](#)

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

[DELETE](#) [/admin/api/2020-07/countries/{country_id}.json](#)

Deletes a country.

[GET](#) [/admin/api/2020-10/countries.json](#)

Retrieves a list of countries.

POST	/admin/api/2020-10/countries.json Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-10/countries/count.json Retrieves a count of countries.
GET	/admin/api/2020-10/countries/{country_id}.json Retrieves a specific county.
PUT	/admin/api/2020-10/countries/{country_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-10/countries/{country_id}.json Deletes a country.
GET	/admin/api/2021-01/countries.json Retrieves a list of countries.
POST	/admin/api/2021-01/countries.json Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2021-01/countries/count.json Retrieves a count of countries.
GET	/admin/api/2021-01/countries/{country_id}.json Retrieves a specific county.
PUT	/admin/api/2021-01/countries/{country_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2021-01/countries/{country_id}.json Deletes a country.
GET	/admin/api/unstable/countries.json Retrieves a list of countries.
POST	/admin/api/unstable/countries.json Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/unstable/countries/count.json Retrieves a count of countries.
GET	/admin/api/unstable/countries/{country_id}.json Retrieves a specific county.
PUT	/admin/api/unstable/countries/{country_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/unstable/countries/{country_id}.json Deletes a country.

currency

GET	/admin/api/2020-01/currencies.json Retrieves a list of currencies enabled on a shop
GET	/admin/api/2020-04/currencies.json Retrieves a list of currencies enabled on a shop
GET	/admin/api/2020-07/currencies.json Retrieves a list of currencies enabled on a shop
GET	/admin/api/2020-10/currencies.json Retrieves a list of currencies enabled on a shop
GET	/admin/api/2021-01/currencies.json Retrieves a list of currencies enabled on a shop
GET	/admin/api/unstable/currencies.json Retrieves a list of currencies enabled on a shop

customcollection

GET	/admin/api/2020-01/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/custom_collections.json Creates a custom collection
GET	/admin/api/2020-01/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-01/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-01/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-01/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2020-04/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/custom_collections.json

GET	/admin/api/2020-04/custom_collections/count.json Creates a custom collection Retrieves a count of custom collections
GET	/admin/api/2020-04/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-04/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-04/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2020-07/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/custom_collections.json Creates a custom collection
GET	/admin/api/2020-07/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-07/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-07/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-07/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2020-10/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/custom_collections.json Creates a custom collection
GET	/admin/api/2020-10/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2021-01/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/custom_collections.json Creates a custom collection
GET	/admin/api/2021-01/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/unstable/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/custom_collections.json Creates a custom collection
GET	/admin/api/unstable/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/unstable/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/unstable/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/unstable/custom_collections/{custom_collection_id}.json Deletes a custom collection

customer

GET	/admin/api/2020-01/customers.json Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customers.json Creates a customer.

GET	/admin/api/2020-01/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/2020-01/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/2020-01/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-01/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-01/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/2020-01/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2020-01/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-04/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customers.json	Creates a customer.
GET	/admin/api/2020-04/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/2020-04/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/2020-04/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-04/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-04/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/2020-04/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2020-04/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-07/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customers.json	Creates a customer.
GET	/admin/api/2020-07/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/2020-07/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/2020-07/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-07/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-07/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.

GET	/admin/api/2020-07/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2020-07/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-10/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customers.json	Creates a customer.
GET	/admin/api/2020-10/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/2020-10/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/2020-10/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-10/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-10/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/2020-10/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2020-10/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2021-01/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/customers.json	Creates a customer.
GET	/admin/api/2021-01/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/2021-01/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/2021-01/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2021-01/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2021-01/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/2021-01/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2021-01/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/unstable/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/customers.json	Creates a customer.
GET	/admin/api/unstable/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/unstable/customers/{customer_id}.json	

DELETE	/admin/api/unstable/customers/{customer_id}.json	Updates a customer.
POST	/admin/api/unstable/customers/{customer_id}/account_activation_url.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/unstable/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/unstable/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/unstable/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/unstable/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

customer-address

GET	/admin/api/2020-01/customers/{customer_id}/addresses.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customers/{customer_id}/addresses.json	Creates a new address for a customer.
GET	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json	Retrieves details a single customer address.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json	Updates an existing customer address.
DELETE	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json	Removes an address from a customer's address list.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/set.json	Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}/default.json	Sets the default address for a customer.
GET	/admin/api/2020-04/customers/{customer_id}/addresses.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customers/{customer_id}/addresses.json	Creates a new address for a customer.
GET	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json	Retrieves details a single customer address.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json	Updates an existing customer address.
DELETE	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json	Removes an address from a customer's address list.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/set.json	Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}/default.json	Sets the default address for a customer.
GET	/admin/api/2020-07/customers/{customer_id}/addresses.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customers/{customer_id}/addresses.json	Creates a new address for a customer.
GET	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json	Retrieves details a single customer address.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json	Updates an existing customer address.
DELETE	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json	Removes an address from a customer's address list.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/set.json	Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}/default.json	Sets the default address for a customer.
GET	/admin/api/2020-10/customers/{customer_id}/addresses.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customers/{customer_id}/addresses.json	Creates a new address for a customer.
GET	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json	Retrieves details a single customer address.

PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2021-01/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/unstable/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.

customers

GET	/admin/api/2020-01/customers.json Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customers.json Creates a customer.
GET	/admin/api/2020-01/customers/search.json Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/customers/{customer_id}.json Retrieves a single customer.
PUT	/admin/api/2020-01/customers/{customer_id}.json Updates a customer.
DELETE	/admin/api/2020-01/customers/{customer_id}.json Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-01/customers/{customer_id}/account_activation_url.json Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-01/customers/{customer_id}/send_invite.json Sends an account invite to a customer.
GET	/admin/api/2020-01/customers/count.json Retrieves a count of all customers.
GET	/admin/api/2020-01/customers/{customer_id}/orders.json Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-04/customers.json

	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customers.json
	Creates a customer.
GET	/admin/api/2020-04/customers/search.json
	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/customers/{customer_id}.json
	Retrieves a single customer.
PUT	/admin/api/2020-04/customers/{customer_id}.json
	Updates a customer.
DELETE	/admin/api/2020-04/customers/{customer_id}.json
	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-04/customers/{customer_id}/account_activation_url.json
	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-04/customers/{customer_id}/send_invite.json
	Sends an account invite to a customer.
GET	/admin/api/2020-04/customers/count.json
	Retrieves a count of all customers.
GET	/admin/api/2020-04/customers/{customer_id}/orders.json
	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-07/customers.json
	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customers.json
	Creates a customer.
GET	/admin/api/2020-07/customers/search.json
	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/customers/{customer_id}.json
	Retrieves a single customer.
PUT	/admin/api/2020-07/customers/{customer_id}.json
	Updates a customer.
DELETE	/admin/api/2020-07/customers/{customer_id}.json
	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-07/customers/{customer_id}/account_activation_url.json
	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-07/customers/{customer_id}/send_invite.json
	Sends an account invite to a customer.
GET	/admin/api/2020-07/customers/count.json
	Retrieves a count of all customers.
GET	/admin/api/2020-07/customers/{customer_id}/orders.json
	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-10/customers.json
	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customers.json
	Creates a customer.
GET	/admin/api/2020-10/customers/search.json
	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/customers/{customer_id}.json
	Retrieves a single customer.
PUT	/admin/api/2020-10/customers/{customer_id}.json
	Updates a customer.
DELETE	/admin/api/2020-10/customers/{customer_id}.json
	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-10/customers/{customer_id}/account_activation_url.json
	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself.

The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

POST /admin/api/2020-10/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

GET </admin/api/2020-10/customers/count.json>

Retrieves a count of all customers.

GET /admin/api/2020-10/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

GET </admin/api/2021-01/customers.json>

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2021-01/customers.json>

Creates a customer.

GET </admin/api/2021-01/customers/search.json>

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2021-01/customers/{customer_id}.json

Retrieves a single customer.

PUT /admin/api/2021-01/customers/{customer_id}.json

Updates a customer.

DELETE /admin/api/2021-01/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.

POST /admin/api/2021-01/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

POST /admin/api/2021-01/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

GET </admin/api/2021-01/customers/count.json>

Retrieves a count of all customers.

GET /admin/api/2021-01/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

GET </admin/api/unstable/customers.json>

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/unstable/customers.json>

Creates a customer.

GET </admin/api/unstable/customers/search.json>

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/unstable/customers/{customer_id}.json

Retrieves a single customer.

PUT /admin/api/unstable/customers/{customer_id}.json

Updates a customer.

DELETE /admin/api/unstable/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.

POST /admin/api/unstable/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

POST /admin/api/unstable/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

GET </admin/api/unstable/customers/count.json>

Retrieves a count of all customers.

GET /admin/api/unstable/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

GET /admin/api/2020-01/customers/{customer_id}/addresses.json

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/customers/{customer_id}/addresses.json

Creates a new address for a customer.

GET /admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json

Retrieves details a single customer address.

PUT /admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json

Updates an existing customer address.

DELETE /admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json
Removes an address from a customer's address list.

PUT /admin/api/2020-01/customers/{customer_id}/addresses/set.json
Performs bulk operations for multiple customer addresses.

PUT /admin/api/2020-01/customers/{customer_id}/addresses/{address_id}/default.json
Sets the default address for a customer.

GET /admin/api/2020-04/customers/{customer_id}/addresses.json
Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/customers/{customer_id}/addresses.json
Creates a new address for a customer.

GET /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json
Retrieves details a single customer address.

PUT /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json
Updates an existing customer address.

DELETE /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json
Removes an address from a customer's address list.

PUT /admin/api/2020-04/customers/{customer_id}/addresses/set.json
Performs bulk operations for multiple customer addresses.

PUT /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}/default.json
Sets the default address for a customer.

GET /admin/api/2020-07/customers/{customer_id}/addresses.json
Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/customers/{customer_id}/addresses.json
Creates a new address for a customer.

GET /admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json
Retrieves details a single customer address.

PUT /admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json
Updates an existing customer address.

DELETE /admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json
Removes an address from a customer's address list.

PUT /admin/api/2020-07/customers/{customer_id}/addresses/set.json
Performs bulk operations for multiple customer addresses.

PUT /admin/api/2020-07/customers/{customer_id}/addresses/{address_id}/default.json
Sets the default address for a customer.

GET /admin/api/2020-10/customers/{customer_id}/addresses.json
Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/customers/{customer_id}/addresses.json
Creates a new address for a customer.

GET /admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json
Retrieves details a single customer address.

PUT /admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json
Updates an existing customer address.

DELETE /admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json
Removes an address from a customer's address list.

PUT /admin/api/2020-10/customers/{customer_id}/addresses/set.json
Performs bulk operations for multiple customer addresses.

PUT /admin/api/2020-10/customers/{customer_id}/addresses/{address_id}/default.json
Sets the default address for a customer.

GET /admin/api/2021-01/customers/{customer_id}/addresses.json
Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/customers/{customer_id}/addresses.json
Creates a new address for a customer.

GET /admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json
Retrieves details a single customer address.

PUT /admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json
Updates an existing customer address.

DELETE /admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json
Removes an address from a customer's address list.

PUT /admin/api/2021-01/customers/{customer_id}/addresses/set.json
Performs bulk operations for multiple customer addresses.

PUT /admin/api/2021-01/customers/{customer_id}/addresses/{address_id}/default.json
Sets the default address for a customer.

GET /admin/api/unstable/customers/{customer_id}/addresses.json

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/customers/{customer_id}/addresses.json

Creates a new address for a customer.

GET /admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json

Retrieves details a single customer address.

PUT /admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json

Updates an existing customer address.

DELETE /admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json

Removes an address from a customer's address list.

PUT /admin/api/unstable/customers/{customer_id}/addresses/set.json

Performs bulk operations for multiple customer addresses.

PUT /admin/api/unstable/customers/{customer_id}/addresses/{address_id}/default.json

Sets the default address for a customer.

GET /admin/api/2020-01/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/2020-01/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

GET /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

PUT /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

DELETE /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

GET /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

GET /admin/api/2020-04/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/2020-04/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

GET /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

PUT /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

DELETE /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

GET /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

GET /admin/api/2020-07/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/2020-07/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

GET /admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

PUT /admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

DELETE /admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

GET /admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

GET /admin/api/2020-10/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/2020-10/customer_saved_searches/count.json

GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a count of all customer saved searches.
PUT	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a single customer saved search.
DELETE	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json	Updates a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}/customers.json	Deletes a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}/customers.json	Retrieves all customers returned by a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches.json	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/customer_saved_searches.json	Creates a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches/count.json	Retrieves a count of all customer saved searches.
GET	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a single customer saved search.
PUT	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json	Updates a customer saved search.
DELETE	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json	Deletes a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}/customers.json	Retrieves all customers returned by a customer saved search.
GET	/admin/api/unstable/customer_saved_searches.json	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/customer_saved_searches.json	Creates a customer saved search.
GET	/admin/api/unstable/customer_saved_searches/count.json	Retrieves a count of all customer saved searches.
GET	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a single customer saved search.
PUT	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json	Updates a customer saved search.
DELETE	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json	Deletes a customer saved search.
GET	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}/customers.json	Retrieves all customers returned by a customer saved search.

customers/customer

GET	/admin/api/2020-01/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customers.json	Creates a customer.
GET	/admin/api/2020-01/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/2020-01/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/2020-01/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-01/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-01/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/2020-01/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2020-01/customers/{customer_id}/orders.json	

	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-04/customers.json
	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customers.json
	Creates a customer.
GET	/admin/api/2020-04/customers/search.json
	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/customers/{customer_id}.json
	Retrieves a single customer.
PUT	/admin/api/2020-04/customers/{customer_id}.json
	Updates a customer.
DELETE	/admin/api/2020-04/customers/{customer_id}.json
	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-04/customers/{customer_id}/account_activation_url.json
	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-04/customers/{customer_id}/send_invite.json
	Sends an account invite to a customer.
GET	/admin/api/2020-04/customers/count.json
	Retrieves a count of all customers.
GET	/admin/api/2020-04/customers/{customer_id}/orders.json
	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-07/customers.json
	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customers.json
	Creates a customer.
GET	/admin/api/2020-07/customers/search.json
	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/customers/{customer_id}.json
	Retrieves a single customer.
PUT	/admin/api/2020-07/customers/{customer_id}.json
	Updates a customer.
DELETE	/admin/api/2020-07/customers/{customer_id}.json
	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-07/customers/{customer_id}/account_activation_url.json
	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-07/customers/{customer_id}/send_invite.json
	Sends an account invite to a customer.
GET	/admin/api/2020-07/customers/count.json
	Retrieves a count of all customers.
GET	/admin/api/2020-07/customers/{customer_id}/orders.json
	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-10/customers.json
	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customers.json
	Creates a customer.
GET	/admin/api/2020-10/customers/search.json
	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/customers/{customer_id}.json
	Retrieves a single customer.
PUT	/admin/api/2020-10/customers/{customer_id}.json
	Updates a customer.
DELETE	/admin/api/2020-10/customers/{customer_id}.json
	Deletes a customer. A customer can't be deleted if they have existing orders.

POST	/admin/api/2020-10/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-10/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/2020-10/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2020-10/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2021-01/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/customers.json	Creates a customer.
GET	/admin/api/2021-01/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/2021-01/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/2021-01/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2021-01/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2021-01/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/2021-01/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2021-01/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/unstable/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/customers.json	Creates a customer.
GET	/admin/api/unstable/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/unstable/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/unstable/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/unstable/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/unstable/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/unstable/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/unstable/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

customers/customer-address

GET	/admin/api/2020-01/customers/{customer_id}/addresses.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
---------------------	---	--

POST	/admin/api/2020-01/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2020-04/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2020-07/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2020-10/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2021-01/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.

PUT	/admin/api/2021-01/customers/{customer_id}/addresses/set.json	Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}/default.json	Sets the default address for a customer.
GET	/admin/api/unstable/customers/{customer_id}/addresses.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/customers/{customer_id}/addresses.json	Creates a new address for a customer.
GET	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json	Retrieves details a single customer address.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json	Updates an existing customer address.
DELETE	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json	Removes an address from a customer's address list.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/set.json	Performs bulk operations for multiple customer addresses.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}/default.json	Sets the default address for a customer.

customers/customersavedsearch

GET	/admin/api/2020-01/customer_saved_searches.json	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customer_saved_searches.json	Creates a customer saved search.
GET	/admin/api/2020-01/customer_saved_searches/count.json	Retrieves a count of all customer saved searches.
GET	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a single customer saved search.
PUT	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json	Updates a customer saved search.
DELETE	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json	Deletes a customer saved search.
GET	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}/customers.json	Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-04/customer_saved_searches.json	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customer_saved_searches.json	Creates a customer saved search.
GET	/admin/api/2020-04/customer_saved_searches/count.json	Retrieves a count of all customer saved searches.
GET	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a single customer saved search.
PUT	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json	Updates a customer saved search.
DELETE	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json	Deletes a customer saved search.
GET	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}/customers.json	Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-07/customer_saved_searches.json	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customer_saved_searches.json	Creates a customer saved search.
GET	/admin/api/2020-07/customer_saved_searches/count.json	Retrieves a count of all customer saved searches.
GET	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a single customer saved search.
PUT	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json	Updates a customer saved search.
DELETE	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json	Deletes a customer saved search.
GET	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}/customers.json	

GET	/admin/api/2020-10/customer_saved_searches.json Retrieves all customers returned by a customer saved search.
POST	/admin/api/2020-10/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json Updates a customer saved search.
DELETE	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json Updates a customer saved search.
DELETE	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.
GET	/admin/api/unstable/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/unstable/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json Updates a customer saved search.
DELETE	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.

customersavedsearch

GET	/admin/api/2020-01/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/2020-01/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json Updates a customer saved search.
DELETE	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-04/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/2020-04/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

GET /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

PUT /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

DELETE /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

GET /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

GET /admin/api/2020-07/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/2020-07/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

GET /admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

PUT /admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

DELETE /admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

GET /admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

GET /admin/api/2020-10/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/2020-10/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

GET /admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

PUT /admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

DELETE /admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

GET /admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

GET /admin/api/2021-01/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/2021-01/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

GET /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

PUT /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

DELETE /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

GET /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

GET /admin/api/unstable/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/customer_saved_searches.json

Creates a customer saved search.

GET	/admin/api/unstable/customer_saved_searches/count.json	Retrieves a count of all customer saved searches.
GET	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a single customer saved search.
PUT	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json	Updates a customer saved search.
DELETE	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json	Deletes a customer saved search.
GET	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}/customers.json	Retrieves all customers returned by a customer saved search.

deprecated_api_calls

GET	/admin/api/2021-01/deprecated_api_calls.json	Retrieves a list of deprecated API calls made by the authenticated private app in the past 30 days.
GET	/admin/api/unstable/deprecated_api_calls.json	Retrieves a list of deprecated API calls made by the authenticated private app in the past 30 days.

discountcode

GET	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json	Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json	Creates a discount code
GET	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Retrieves a single discount code
PUT	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Updates an existing discount code
DELETE	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Deletes a discount code
GET	/admin/api/2020-01/discount_codes/lookup.json	Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-01/price_rules/{price_rule_id}/batch.json	Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}.json	Retrieves a discount code creation job
GET	/admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json	Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json	Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json	Creates a discount code
GET	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Retrieves a single discount code
PUT	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Updates an existing discount code
DELETE	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Deletes a discount code
GET	/admin/api/2020-04/discount_codes/lookup.json	Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-04/price_rules/{price_rule_id}/batch.json	Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}.json	Retrieves a discount code creation job
GET	/admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json	

	Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json
	Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json
	Creates a discount code
GET	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
	Retrieves a single discount code
PUT	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
	Updates an existing discount code
DELETE	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
	Deletes a discount code
GET	/admin/api/2020-07/discount_codes/lookup.json
	Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-07/price_rules/{price_rule_id}/batch.json
	Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}.json
	Retrieves a discount code creation job
GET	/admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json
	Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json
	Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json
	Creates a discount code
GET	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
	Retrieves a single discount code
PUT	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
	Updates an existing discount code
DELETE	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
	Deletes a discount code
GET	/admin/api/2020-10/discount_codes/lookup.json
	Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-10/price_rules/{price_rule_id}/batch.json
	Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}.json
	Retrieves a discount code creation job
GET	/admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json
	Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json
	Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json
	Creates a discount code
GET	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
	Retrieves a single discount code
PUT	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
	Updates an existing discount code
DELETE	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
	Deletes a discount code
GET	/admin/api/2021-01/discount_codes/lookup.json
	Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2021-01/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a `discount_code_creation` object that can be monitored for completion. Response fields that are specific to the batch endpoint include: `status`: The state of the discount code creation job. Possible values are: `queued`: The job is acknowledged, but not started. `running`: The job is in process. `completed`: The job has finished. `codes_count`: The number of discount codes to create. `imported_count`: The number of discount codes created successfully. `failed_count`: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. `logs`: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

GET /admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated `id` field. Discount codes that encountered errors during the creation process include a populated `errors` field.

GET /admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

GET /admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

PUT /admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

DELETE /admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

GET /admin/api/unstable/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the `location` header, not in the `DiscountCode` object itself. Depending on your HTTP client, the location of the discount code might follow the `location` header automatically.

POST /admin/api/unstable/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a `discount_code_creation` object that can be monitored for completion. Response fields that are specific to the batch endpoint include: `status`: The state of the discount code creation job. Possible values are: `queued`: The job is acknowledged, but not started. `running`: The job is in process. `completed`: The job has finished. `codes_count`: The number of discount codes to create. `imported_count`: The number of discount codes created successfully. `failed_count`: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. `logs`: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

GET /admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated `id` field. Discount codes that encountered errors during the creation process include a populated `errors` field.

discounts

GET /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

GET /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

PUT /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

DELETE /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

GET /admin/api/2020-01/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the `location` header, not in the `DiscountCode` object itself. Depending on your HTTP client, the location of the discount code might follow the `location` header automatically.

POST /admin/api/2020-01/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a `discount_code_creation` object that can be monitored for completion. Response fields that are specific to the batch endpoint include: `status`: The state of the discount code creation job. Possible values are: `queued`: The job is acknowledged, but not started. `running`: The job is in process. `completed`: The job has finished. `codes_count`: The number of discount codes to create. `imported_count`: The number of discount codes created successfully. `failed_count`: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. `logs`: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

GET /admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated `id` field. Discount codes that encountered errors during the creation process include a populated `errors` field.

GET /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

GET /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Retrieves a single discount code

PUT /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Updates an existing discount code

DELETE /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Deletes a discount code

GET /admin/api/2020-04/discount_codes/lookup.json
Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2020-04/price_rules/{price_rule_id}/batch.json
Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}.json
Retrieves a discount code creation job

GET /admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json
Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

GET /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json
Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json
Creates a discount code

GET /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Retrieves a single discount code

PUT /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Updates an existing discount code

DELETE /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Deletes a discount code

GET /admin/api/2020-07/discount_codes/lookup.json
Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2020-07/price_rules/{price_rule_id}/batch.json
Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}.json
Retrieves a discount code creation job

GET /admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json
Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

GET /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json
Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json
Creates a discount code

GET /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Retrieves a single discount code

PUT /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Updates an existing discount code

DELETE /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Deletes a discount code

GET /admin/api/2020-10/discount_codes/lookup.json
Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2020-10/price_rules/{price_rule_id}/batch.json
Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}.json
Retrieves a discount code creation job

GET	/admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json	Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json	Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json	Creates a discount code
GET	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Retrieves a single discount code
PUT	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Updates an existing discount code
DELETE	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Deletes a discount code
GET	/admin/api/2021-01/discount_codes/lookup.json	Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2021-01/price_rules/{price_rule_id}/batch.json	Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}.json	Retrieves a discount code creation job
GET	/admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json	Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json	Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json	Creates a discount code
GET	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Retrieves a single discount code
PUT	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Updates an existing discount code
DELETE	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Deletes a discount code
GET	/admin/api/unstable/discount_codes/lookup.json	Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/unstable/price_rules/{price_rule_id}/batch.json	Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}.json	Retrieves a discount code creation job
GET	/admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json	Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

discounts/discountcode

GET	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json	Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json	Creates a discount code
GET	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Retrieves a single discount code
PUT	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Updates an existing discount code
DELETE	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Deletes a discount code
GET	/admin/api/2020-01/discount_codes/lookup.json	

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2020-01/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

GET /admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

GET /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

GET /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

PUT /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

DELETE /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

GET /admin/api/2020-04/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2020-04/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

GET /admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

GET /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

GET /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

PUT /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

DELETE /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

GET /admin/api/2020-07/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2020-07/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

GET /admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

GET /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

GET /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Retrieves a single discount code

PUT /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Updates an existing discount code

DELETE /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Deletes a discount code

GET /admin/api/2020-10/discount_codes/lookup.json
Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2020-10/price_rules/{price_rule_id}/batch.json
Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}.json
Retrieves a discount code creation job

GET /admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json
Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

GET /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json
Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json
Creates a discount code

GET /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Retrieves a single discount code

PUT /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Updates an existing discount code

DELETE /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Deletes a discount code

GET /admin/api/2021-01/discount_codes/lookup.json
Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2021-01/price_rules/{price_rule_id}/batch.json
Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}.json
Retrieves a discount code creation job

GET /admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json
Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

GET /admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json
Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json
Creates a discount code

GET /admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Retrieves a single discount code

PUT /admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Updates an existing discount code

DELETE /admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json
Deletes a discount code

GET /admin/api/unstable/discount_codes/lookup.json
Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/unstable/price_rules/{price_rule_id}/batch.json
Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}.json
Retrieves a discount code creation job

[GET](#) [/admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json](#)

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

dispute

[GET](#) [/admin/api/2020-01/shopify_payments/disputes.json](#)

Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-01/shopify_payments/disputes/{dispute_id}.json](#)

Retrieves a single dispute by ID.

[GET](#) [/admin/api/2020-04/shopify_payments/disputes.json](#)

Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

event

[GET](#) [/admin/api/2020-01/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-01/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-01/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2020-04/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-04/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-04/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2020-07/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-07/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-07/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2020-10/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-10/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-10/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2021-01/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2021-01/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2021-01/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/unstable/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/unstable/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/unstable/events/count.json](#)

Retrieves a count of events

events

[GET](#) [/admin/api/2020-01/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-01/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-01/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2020-04/events.json](#)

	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/events/{event_id}.json
	Retrieves a single event by its ID
GET	/admin/api/2020-04/events/count.json
	Retrieves a count of events
GET	/admin/api/2020-07/events.json
	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/events/{event_id}.json
	Retrieves a single event by its ID
GET	/admin/api/2020-07/events/count.json
	Retrieves a count of events
GET	/admin/api/2020-10/events.json
	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/events/{event_id}.json
	Retrieves a single event by its ID
GET	/admin/api/2020-10/events/count.json
	Retrieves a count of events
GET	/admin/api/2021-01/events.json
	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/events/{event_id}.json
	Retrieves a single event by its ID
GET	/admin/api/2021-01/events/count.json
	Retrieves a count of events
GET	/admin/api/unstable/events.json
	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/events/{event_id}.json
	Retrieves a single event by its ID
GET	/admin/api/unstable/events/count.json
	Retrieves a count of events
GET	/admin/api/2020-01/webhooks.json
	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/webhooks.json
	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-01/webhooks/count.json
	Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-01/webhooks/{webhook_id}.json
	Retrieves a single webhook subscription
PUT	/admin/api/2020-01/webhooks/{webhook_id}.json
	Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-01/webhooks/{webhook_id}.json
	Delete a webhook subscription
GET	/admin/api/2020-04/webhooks.json
	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/webhooks.json
	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-04/webhooks/count.json
	Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-04/webhooks/{webhook_id}.json
	Retrieves a single webhook subscription
PUT	/admin/api/2020-04/webhooks/{webhook_id}.json
	Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-04/webhooks/{webhook_id}.json
	Delete a webhook subscription
GET	/admin/api/2020-07/webhooks.json
	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/webhooks.json
	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-07/webhooks/count.json
	Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-07/webhooks/{webhook_id}.json
	Retrieves a single webhook subscription

PUT	/admin/api/2020-07/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-07/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/2020-10/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-10/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-10/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2020-10/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-10/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/2021-01/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2021-01/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/2021-01/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2021-01/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2021-01/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/unstable/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/unstable/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/unstable/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/unstable/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/unstable/webhooks/{webhook_id}.json Delete a webhook subscription

events/event

GET	/admin/api/2020-01/events.json Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/events/{event_id}.json Retrieves a single event by its ID
GET	/admin/api/2020-01/events/count.json Retrieves a count of events
GET	/admin/api/2020-04/events.json Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/events/{event_id}.json Retrieves a single event by its ID
GET	/admin/api/2020-04/events/count.json Retrieves a count of events
GET	/admin/api/2020-07/events.json Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/events/{event_id}.json Retrieves a single event by its ID
GET	/admin/api/2020-07/events/count.json Retrieves a count of events
GET	/admin/api/2020-10/events.json

	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/events/{event_id}.json
	Retrieves a single event by its ID
GET	/admin/api/2020-10/events/count.json
	Retrieves a count of events
GET	/admin/api/2021-01/events.json
	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/events/{event_id}.json
	Retrieves a single event by its ID
GET	/admin/api/2021-01/events/count.json
	Retrieves a count of events
GET	/admin/api/unstable/events.json
	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/events/{event_id}.json
	Retrieves a single event by its ID
GET	/admin/api/unstable/events/count.json
	Retrieves a count of events

events/webhook

GET	/admin/api/2020-01/webhooks.json	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/webhooks.json	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-01/webhooks/count.json	Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-01/webhooks/{webhook_id}.json	Retrieves a single webhook subscription
PUT	/admin/api/2020-01/webhooks/{webhook_id}.json	Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-01/webhooks/{webhook_id}.json	Delete a webhook subscription
GET	/admin/api/2020-04/webhooks.json	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/webhooks.json	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-04/webhooks/count.json	Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-04/webhooks/{webhook_id}.json	Retrieves a single webhook subscription
PUT	/admin/api/2020-04/webhooks/{webhook_id}.json	Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-04/webhooks/{webhook_id}.json	Delete a webhook subscription
GET	/admin/api/2020-07/webhooks.json	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/webhooks.json	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-07/webhooks/count.json	Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-07/webhooks/{webhook_id}.json	Retrieves a single webhook subscription
PUT	/admin/api/2020-07/webhooks/{webhook_id}.json	Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-07/webhooks/{webhook_id}.json	Delete a webhook subscription
GET	/admin/api/2020-10/webhooks.json	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/webhooks.json	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-10/webhooks/count.json	Retrieves a count of existing webhook subscriptions

GET	/admin/api/2020-10/webhooks/{webhook_id}.json	Retrieves a single webhook subscription
PUT	/admin/api/2020-10/webhooks/{webhook_id}.json	Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-10/webhooks/{webhook_id}.json	Delete a webhook subscription
GET	/admin/api/2021-01/webhooks.json	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/webhooks.json	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2021-01/webhooks/count.json	Retrieves a count of existing webhook subscriptions
GET	/admin/api/2021-01/webhooks/{webhook_id}.json	Retrieves a single webhook subscription
PUT	/admin/api/2021-01/webhooks/{webhook_id}.json	Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2021-01/webhooks/{webhook_id}.json	Delete a webhook subscription
GET	/admin/api/unstable/webhooks.json	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/webhooks.json	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/unstable/webhooks/count.json	Retrieves a count of existing webhook subscriptions
GET	/admin/api/unstable/webhooks/{webhook_id}.json	Retrieves a single webhook subscription
PUT	/admin/api/unstable/webhooks/{webhook_id}.json	Update a webhook subscription's topic or address URIs
DELETE	/admin/api/unstable/webhooks/{webhook_id}.json	Delete a webhook subscription

fulfillment

GET	/admin/api/2020-01/orders/{order_id}/fulfillments.json	Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/fulfillments.json	Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json	Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/count.json	Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json	Retrieve a specific fulfillment
PUT	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json	Update information associated with a fulfillment
POST	/admin/api/2020-01/fulfillments.json	Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-01/fulfillments/{fulfillment_id}/update_tracking.json	Updates the tracking information for a fulfillment.
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json	Mark a fulfillment as complete
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json	Mark a fulfillment as open
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json	Cancel a fulfillment for a specific order ID

POST	/admin/api/2020-01/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-04/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-04/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-04/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-04/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-07/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-07/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-07/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open

POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-07/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-10/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2021-01/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2021-01/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete

POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/unstable/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/unstable/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/unstable/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/unstable/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/unstable/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.

fulfillmentevent

GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event

GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Creates a fulfillment event
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Retrieves a specific fulfillment event
DELETE	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Deletes a fulfillment event
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Creates a fulfillment event
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Retrieves a specific fulfillment event
DELETE	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Deletes a fulfillment event
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Creates a fulfillment event
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Retrieves a specific fulfillment event
DELETE	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Deletes a fulfillment event

fulfillmentorder

GET	/admin/api/2020-01/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/close.json
	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/move.json
	Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-04/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/close.json
	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/move.json
	Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-07/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/close.json
	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/move.json
	Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-10/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.

GET /admin/api/2021-01/orders/{order_id}/fulfillment_orders.json

Retrieves a list of fulfillment orders for a specific order.

GET /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}.json

Retrieves a specific fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancel.json

Marks a fulfillment order as cancelled.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/open.json

Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/reschedule.json

Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.

GET /admin/api/unstable/orders/{order_id}/fulfillment_orders.json

Retrieves a list of fulfillment orders for a specific order.

GET /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}.json

Retrieves a specific fulfillment order.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancel.json

Marks a fulfillment order as cancelled.

POST /admin/api/unstable/fulfillment_orders/release_hold.json

Releases the fulfillment order holds for a specific order. Fulfillment orders are created with an ON_HOLD status if the channel that created the order has a fulfillment hold policy.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/open.json

Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/reschedule.json

Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.

fulfillmentrequest

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST [/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json](#)
Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json](#)
Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json](#)
Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json](#)
Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json](#)
Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

fulfillmentservice

GET [/fetch_tracking_numbers](#)
Get tracking numbers for orders

GET [/fetch_stock](#)
Get inventory levels

GET [/admin/api/2020-01/fulfillment_services.json](#)

POST [/admin/api/2020-01/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json](#)

DELETE [/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json](#)

GET [/admin/api/2020-04/fulfillment_services.json](#)

POST [/admin/api/2020-04/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json](#)

DELETE [/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json](#)

GET [/admin/api/2020-07/fulfillment_services.json](#)

POST [/admin/api/2020-07/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json](#)

DELETE [/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json](#)

GET [/admin/api/2020-10/fulfillment_services.json](#)

POST [/admin/api/2020-10/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)

DELETE [/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)

GET [/admin/api/2021-01/fulfillment_services.json](#)

POST [/admin/api/2021-01/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)

DELETE [/admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)

GET [/admin/api/unstable/fulfillment_services.json](#)

POST [/admin/api/unstable/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)

[DELETE](#) [/admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)

giftcard

[GET](#) [/admin/api/2020-01/gift_cards.json](#)

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-01/gift_cards.json](#)

Creates a gift card

[GET](#) [/admin/api/2020-01/gift_cards/{gift_card_id}.json](#)

Retrieves a single gift card by its ID

[PUT](#) [/admin/api/2020-01/gift_cards/{gift_card_id}.json](#)

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

[GET](#) [/admin/api/2020-01/gift_cards/count.json](#)

Retrieves a count of gift cards

[POST](#) [/admin/api/2020-01/gift_cards/{gift_card_id}/disable.json](#)

Disables a gift card. Disabling a gift card can't be undone.

[GET](#) [/admin/api/2020-01/gift_cards/search.json](#)

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-04/gift_cards.json](#)

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-04/gift_cards.json](#)

Creates a gift card

[GET](#) [/admin/api/2020-04/gift_cards/{gift_card_id}.json](#)

Retrieves a single gift card by its ID

[PUT](#) [/admin/api/2020-04/gift_cards/{gift_card_id}.json](#)

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

[GET](#) [/admin/api/2020-04/gift_cards/count.json](#)

Retrieves a count of gift cards

[POST](#) [/admin/api/2020-04/gift_cards/{gift_card_id}/disable.json](#)

Disables a gift card. Disabling a gift card can't be undone.

[GET](#) [/admin/api/2020-04/gift_cards/search.json](#)

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-07/gift_cards.json](#)

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-07/gift_cards.json](#)

Creates a gift card

[GET](#) [/admin/api/2020-07/gift_cards/{gift_card_id}.json](#)

Retrieves a single gift card by its ID

[PUT](#) [/admin/api/2020-07/gift_cards/{gift_card_id}.json](#)

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

[GET](#) [/admin/api/2020-07/gift_cards/count.json](#)

Retrieves a count of gift cards

[POST](#) [/admin/api/2020-07/gift_cards/{gift_card_id}/disable.json](#)

Disables a gift card. Disabling a gift card can't be undone.

[GET](#) [/admin/api/2020-07/gift_cards/search.json](#)

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-10/gift_cards.json](#)

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-10/gift_cards.json](#)

Creates a gift card

[GET](#) [/admin/api/2020-10/gift_cards/{gift_card_id}.json](#)

Retrieves a single gift card by its ID

[PUT](#) [/admin/api/2020-10/gift_cards/{gift_card_id}.json](#)

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

[GET](#) [/admin/api/2020-10/gift_cards/count.json](#)

Retrieves a count of gift cards

[POST](#) [/admin/api/2020-10/gift_cards/{gift_card_id}/disable.json](#)

Disables a gift card. Disabling a gift card can't be undone.

GET	/admin/api/2020-10/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/gift_cards.json	Creates a gift card
GET	/admin/api/2021-01/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2021-01/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2021-01/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2021-01/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2021-01/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/gift_cards.json	Creates a gift card
GET	/admin/api/unstable/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/unstable/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/unstable/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/unstable/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/unstable/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

inventory

GET	/admin/api/2020-01/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-01/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-04/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-04/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-07/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-07/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-10/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-10/inventory_items/{inventory_item_id}.json	

GET	/admin/api/2021-01/inventory_items.json	Updates an existing inventory item
		Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2021-01/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/unstable/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/unstable/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-01/inventory_levels.json	Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-01/inventory_levels.json	Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-01/inventory_levels/adjust.json	Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2020-01/inventory_levels/connect.json	Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2020-01/inventory_levels/set.json	Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/2020-04/inventory_levels.json	Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-04/inventory_levels.json	Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-04/inventory_levels/adjust.json	Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2020-04/inventory_levels/connect.json	Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2020-04/inventory_levels/set.json	Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/2020-07/inventory_levels.json	Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-07/inventory_levels.json	Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-07/inventory_levels/adjust.json	Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2020-07/inventory_levels/connect.json	Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2020-07/inventory_levels/set.json	Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/2020-10/inventory_levels.json	Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-10/inventory_levels.json	Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-10/inventory_levels/adjust.json	Adjusts the inventory level of an inventory item at a single location

POST [/admin/api/2020-10/inventory_levels/connect.json](#)
Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST [/admin/api/2020-10/inventory_levels/set.json](#)
Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET [/admin/api/2021-01/inventory_levels.json](#)
Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE [/admin/api/2021-01/inventory_levels.json](#)
Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST [/admin/api/2021-01/inventory_levels/adjust.json](#)
Adjusts the inventory level of an inventory item at a single location

POST [/admin/api/2021-01/inventory_levels/connect.json](#)
Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST [/admin/api/2021-01/inventory_levels/set.json](#)
Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET [/admin/api/unstable/inventory_levels.json](#)
Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE [/admin/api/unstable/inventory_levels.json](#)
Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST [/admin/api/unstable/inventory_levels/adjust.json](#)
Adjusts the inventory level of an inventory item at a single location

POST [/admin/api/unstable/inventory_levels/connect.json](#)
Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST [/admin/api/unstable/inventory_levels/set.json](#)
Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET [/admin/api/2020-01/locations.json](#)
Retrieves a list of locations

GET [/admin/api/2020-01/locations/{location_id}.json](#)
Retrieves a single location by its ID

GET [/admin/api/2020-01/locations/count.json](#)
Retrieves a count of locations

GET [/admin/api/2020-01/locations/{location_id}/inventory_levels.json](#)
Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET [/admin/api/2020-04/locations.json](#)
Retrieves a list of locations

GET [/admin/api/2020-04/locations/{location_id}.json](#)
Retrieves a single location by its ID

GET [/admin/api/2020-04/locations/count.json](#)
Retrieves a count of locations

GET [/admin/api/2020-04/locations/{location_id}/inventory_levels.json](#)
Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET [/admin/api/2020-07/locations.json](#)
Retrieves a list of locations

GET [/admin/api/2020-07/locations/{location_id}.json](#)
Retrieves a single location by its ID

GET [/admin/api/2020-07/locations/count.json](#)
Retrieves a count of locations

GET [/admin/api/2020-07/locations/{location_id}/inventory_levels.json](#)
Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET [/admin/api/2020-10/locations.json](#)
Retrieves a list of locations

GET [/admin/api/2020-10/locations/{location_id}.json](#)
Retrieves a single location by its ID

GET	/admin/api/2020-10/locations/count.json	Retrieves a count of locations
GET	/admin/api/2020-10/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/locations.json	Retrieves a list of locations
GET	/admin/api/2021-01/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2021-01/locations/count.json	Retrieves a count of locations
GET	/admin/api/2021-01/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/locations.json	Retrieves a list of locations
GET	/admin/api/unstable/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/unstable/locations/count.json	Retrieves a count of locations
GET	/admin/api/unstable/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

inventory/inventoryitem

GET	/admin/api/2020-01/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-01/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-04/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-04/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-07/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-07/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-10/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-10/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2021-01/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2021-01/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/unstable/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/unstable/inventory_items/{inventory_item_id}.json	

Updates an existing inventory item

inventory/inventorylevel

GET /admin/api/2020-01/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2020-01/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-01/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-01/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-01/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2020-04/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2020-04/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-04/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-04/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-04/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2020-07/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2020-07/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-07/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-07/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-07/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2020-10/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2020-10/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-10/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-10/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-10/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2021-01/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2021-01/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2021-01/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2021-01/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2021-01/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/unstable/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/unstable/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/unstable/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/unstable/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/unstable/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

inventory/location

GET </admin/api/2020-01/locations.json>

Retrieves a list of locations

GET /admin/api/2020-01/locations/{location_id}.json

Retrieves a single location by its ID

GET </admin/api/2020-01/locations/count.json>

Retrieves a count of locations

GET /admin/api/2020-01/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET </admin/api/2020-04/locations.json>

Retrieves a list of locations

GET /admin/api/2020-04/locations/{location_id}.json

Retrieves a single location by its ID

GET </admin/api/2020-04/locations/count.json>

Retrieves a count of locations

GET /admin/api/2020-04/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET </admin/api/2020-07/locations.json>

Retrieves a list of locations

GET /admin/api/2020-07/locations/{location_id}.json

Retrieves a single location by its ID

GET </admin/api/2020-07/locations/count.json>

Retrieves a count of locations

GET /admin/api/2020-07/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET </admin/api/2020-10/locations.json>

Retrieves a list of locations

GET /admin/api/2020-10/locations/{location_id}.json

Retrieves a single location by its ID

GET </admin/api/2020-10/locations/count.json>

Retrieves a count of locations

GET /admin/api/2020-10/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET </admin/api/2021-01/locations.json>

Retrieves a list of locations

GET	/admin/api/2021-01/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2021-01/locations/count.json	Retrieves a count of locations
GET	/admin/api/2021-01/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/locations.json	Retrieves a list of locations
GET	/admin/api/unstable/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/unstable/locations/count.json	Retrieves a count of locations
GET	/admin/api/unstable/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

inventoryitem

GET	/admin/api/2020-01/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-01/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-04/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-04/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-07/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-07/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-10/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-10/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2021-01/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2021-01/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/unstable/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/unstable/inventory_items/{inventory_item_id}.json	Updates an existing inventory item

inventorylevel

GET	/admin/api/2020-01/inventory_levels.json	Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-01/inventory_levels.json	

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-01/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-01/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-01/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2020-04/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2020-04/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-04/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-04/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-04/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2020-07/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2020-07/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-07/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-07/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-07/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2020-10/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2020-10/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-10/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-10/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-10/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2021-01/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2021-01/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2021-01/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2021-01/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2021-01/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET [/admin/api/unstable/inventory_levels.json](#)

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE [/admin/api/unstable/inventory_levels.json](#)

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST [/admin/api/unstable/inventory_levels/adjust.json](#)

Adjusts the inventory level of an inventory item at a single location

POST [/admin/api/unstable/inventory_levels/connect.json](#)

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST [/admin/api/unstable/inventory_levels/set.json](#)

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

latest_api_version

GET [/admin/oauth/access_scopes.json](#)

Retrieves a list of access scopes associated to the access token.

GET [/admin/api/2020-10/storefront_access_tokens.json](#)

Retrieves a list of storefront access tokens that have been issued

POST [/admin/api/2020-10/storefront_access_tokens.json](#)

Creates a new storefront access token

DELETE [/admin/api/2020-10/storefront_access_tokens/{storefront_access_token_id}.json](#)

Deletes an existing storefront access token

GET [/admin/api/2020-10/reports.json](#)

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST [/admin/api/2020-10/reports.json](#)

Creates a new report

GET [/admin/api/2020-10/reports/{report_id}.json](#)

Retrieves a single report created by your app

PUT [/admin/api/2020-10/reports/{report_id}.json](#)

Updates a report

DELETE [/admin/api/2020-10/reports/{report_id}.json](#)

Deletes a report

GET [/admin/api/2020-10/application_charges.json](#)

Retrieves a list of application charges

POST [/admin/api/2020-10/application_charges.json](#)

Creates an application charge

GET [/admin/api/2020-10/application_charges/{application_charge_id}.json](#)

Retrieves an application charge

POST [/admin/api/2020-10/application_charges/{application_charge_id}/activate.json](#)

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

GET [/admin/api/2020-10/application_credits.json](#)

Retrieves all application credits

POST [/admin/api/2020-10/application_credits.json](#)

Creates an application credit

GET [/admin/api/2020-10/application_credits/{application_credit_id}.json](#)

Retrieves a single application credit

GET [/admin/api/2020-10/recurring_application_charges.json](#)

Retrieves a list of recurring application charges

POST [/admin/api/2020-10/recurring_application_charges.json](#)

Creates a recurring application charge

GET [/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json](#)

Retrieves a single charge

DELETE [/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json](#)

Cancels a recurring application charge

POST [/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/activate.json](#)

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

PUT [/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/customize.json](#)

Updates the capped amount of an active recurring application charge

GET [/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json](#)

Retrieves a list of usage charges

POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-10/customers.json Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customers.json Creates a customer.
GET	/admin/api/2020-10/customers/search.json Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/customers/{customer_id}.json Retrieves a single customer.
PUT	/admin/api/2020-10/customers/{customer_id}.json Updates a customer.
DELETE	/admin/api/2020-10/customers/{customer_id}.json Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-10/customers/{customer_id}/account_activation_url.json Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-10/customers/{customer_id}/send_invite.json Sends an account invite to a customer.
GET	/admin/api/2020-10/customers/count.json Retrieves a count of all customers.
GET	/admin/api/2020-10/customers/{customer_id}/orders.json Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-10/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2020-10/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json Updates a customer saved search.
DELETE	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code

PUT	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Updates an existing discount code
DELETE	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Deletes a discount code
GET	/admin/api/2020-10/discount_codes/lookup.json	Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-10/price_rules/{price_rule_id}/batch.json	Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}.json	Retrieves a discount code creation job
GET	/admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json	Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-10/events.json	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/events/{event_id}.json	Retrieves a single event by its ID
GET	/admin/api/2020-10/events/count.json	Retrieves a count of events
GET	/admin/api/2020-10/webhooks.json	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/webhooks.json	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-10/webhooks/count.json	Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-10/webhooks/{webhook_id}.json	Retrieves a single webhook subscription
PUT	/admin/api/2020-10/webhooks/{webhook_id}.json	Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-10/webhooks/{webhook_id}.json	Delete a webhook subscription
GET	/admin/api/2020-10/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-10/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-10/inventory_levels.json	Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-10/inventory_levels.json	Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-10/inventory_levels/adjust.json	Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2020-10/inventory_levels/connect.json	Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2020-10/inventory_levels/set.json	Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/2020-10/locations.json	Retrieves a list of locations
GET	/admin/api/2020-10/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2020-10/locations/count.json	Retrieves a count of locations
GET	/admin/api/2020-10/locations/{location_id}/inventory_levels.json	

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET </admin/api/2020-10/metafields.json>

Retrieves a list of metafields that belong to a Product Image resource.

POST </admin/api/2020-10/metafields.json>

Creates a new metafield for a resource.

GET </admin/api/2020-10/metafields/count.json>

Retrieves a count of a resource's metafields.

GET /admin/api/2020-10/metafields/{metafield_id}.json

Retrieves a single metafield from a resource by its ID.

PUT /admin/api/2020-10/metafields/{metafield_id}.json

Updates a metafield.

DELETE /admin/api/2020-10/metafields/{metafield_id}.json

Deletes a metafield by its ID.

GET /admin/api/2020-10/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/blogs/{blog_id}/articles.json

Creates an article for a blog

GET /admin/api/2020-10/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

GET /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article

PUT /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Updates an article

DELETE /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

GET </admin/api/2020-10/articles/authors.json>

Retrieves a list all of article authors

GET </admin/api/2020-10/articles/tags.json>

Retrieves a list of all the tags

GET /admin/api/2020-10/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.

PUT /admin/api/2020-10/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

DELETE /admin/api/2020-10/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET </admin/api/2020-10/redirects.json>

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-10/redirects.json>

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

GET </admin/api/2020-10/redirects/count.json>

Retrieves a count of URL redirects

GET /admin/api/2020-10/redirects/{redirect_id}.json

Retrieves a single redirect

PUT /admin/api/2020-10/redirects/{redirect_id}.json

Updates an existing redirect

DELETE /admin/api/2020-10/redirects/{redirect_id}.json

Deletes a redirect

GET /admin/api/2020-10/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/script_tags.json

Creates a new script tag

GET /admin/api/2020-10/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-10/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-10/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-10/script_tags/{script_tag_id}.json

Deletes a script tag

GET </admin/api/2020-10/themes.json>

POST	/admin/api/2020-10/themes.json Retrieves a list of themes. Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-10/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-10/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-10/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2020-10/checkouts/count.json Retrieves a count of checkouts from the past 90 days
POST	/admin/api/2020-10/checkouts.json Creates a checkout
GET	/admin/api/2020-10/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-10/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-10/orders/{order_id}/refunds/{refund_id}.json Retrieves a specific refund.
POST	/admin/api/2020-10/orders/{order_id}/refunds/calculate.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind" : "refund" for the refund to be accepted.
GET	/admin/api/2020-10/gift_cards.json Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/gift_cards.json Creates a gift card
GET	/admin/api/2020-10/gift_cards/{gift_card_id}.json Retrieves a single gift card by its ID
PUT	/admin/api/2020-10/gift_cards/{gift_card_id}.json Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-10/gift_cards/count.json Retrieves a count of gift cards
POST	/admin/api/2020-10/gift_cards/{gift_card_id}/disable.json Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-10/gift_cards/search.json Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/users/{user_id}.json Retrieves a single user
GET	/admin/api/2020-10/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-10/collects.json

	Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/collects.json Adds a product to a custom collection.
GET	/admin/api/2020-10/collects/{collect_id}.json Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-10/collects/{collect_id}.json Removes a product from a collection.
GET	/admin/api/2020-10/collects/count.json Retrieves a count of collects.
GET	/admin/api/2020-10/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2020-10/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-10/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/custom_collections.json Creates a custom collection
GET	/admin/api/2020-10/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2020-10/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-10/products/count.json Retrieves a count of products.
GET	/admin/api/2020-10/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2020-10/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-10/products/{product_id}.json Deletes a product.
GET	/admin/api/2020-10/products/{product_id}/images.json Get all product images
POST	/admin/api/2020-10/products/{product_id}/images.json Create a new product image
GET	/admin/api/2020-10/products/{product_id}/images/count.json Get a count of all product images
GET	/admin/api/2020-10/products/{product_id}/images/{image_id}.json Get a single product image by id
PUT	/admin/api/2020-10/products/{product_id}/images/{image_id}.json Modify an existing product image
DELETE	/admin/api/2020-10/products/{product_id}/images/{image_id}.json
GET	/admin/api/2020-10/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/2020-10/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/2020-10/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/2020-10/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/2020-10/smart_collections/{smart_collection_id}.json

PUT	Removes a smart collection /admin/api/2020-10/smart_collections/{smart_collection_id}/order.json
POST	Updates the ordering type of products in a smart collection /admin/api/2020-10/checkouts/{token}/complete.json
GET	Completes a checkout /admin/api/2020-10/checkouts/{token}.json
PUT	Retrieves a checkout /admin/api/2020-10/checkouts/{token}.json
GET	Modifies an existing checkout /admin/api/2020-10/checkouts/{token}/shipping_rates.json
GET	Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate. /admin/api/2020-10/collection_listings.json
GET	Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2020-10/collection_listings/{collection_listing_id}/product_ids.json
GET	Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2020-10/collection_listings/{collection_listing_id}.json
PUT	Retrieve a specific collection listing that is published to your app /admin/api/2020-10/collection_listings/{collection_listing_id}.json
DELETE	Create a collection listing to publish a collection to your app /admin/api/2020-10/collection_listings/{collection_listing_id}.json
GET	Delete a collection listing to unpublish a collection from your app /admin/api/2020-10/checkouts/{token}/payments.json
POST	Retrieves a list of payments on a particular checkout /admin/api/2020-10/checkouts/{token}/payments.json
GET	Creates a payment on a checkout using the session ID returned by the card vault /admin/api/2020-10/checkouts/{token}/payments/{payment_id}.json
GET	Retrieves the payment information for an existing payment /admin/api/2020-10/checkouts/{token}/payments/count.json
GET	Counts the number of payments attempted on a checkout /admin/api/2020-10/assigned_fulfillment_orders.json
POST	Retrieves a list of fulfillment orders on a shop for a specific app. /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json
POST	Sends a cancellation request to the fulfillment service of a fulfillment order. /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json
POST	Accepts a cancellation request sent to a fulfillment service for a fulfillment order. /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json
GET	Rejects a cancellation request sent to a fulfillment service for a fulfillment order. /admin/api/2020-10/carrier_services.json
POST	Retrieves a list of carrier services /admin/api/2020-10/carrier_services.json
GET	Creates a carrier service /admin/api/2020-10/carrier_services/{carrier_service_id}.json
PUT	Retrieves a single carrier service by its ID /admin/api/2020-10/carrier_services/{carrier_service_id}.json
DELETE	Updates a carrier service. Only the app that creates a carrier service can update it. /admin/api/2020-10/carrier_services/{carrier_service_id}.json
GET	Deletes a carrier service /admin/api/2020-10/orders/{order_id}/fulfillments.json
POST	Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2020-10/orders/{order_id}/fulfillments.json
GET	Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment. /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

GET	/admin/api/2020-10/orders/{order_id}/fulfillments/count.json	Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json	Retrieves a count of fulfillments associated with a specific order
PUT	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json	Retrieve a specific fulfillment
POST	/admin/api/2020-10/fulfillments.json	Update information associated with a fulfillment
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/update_tracking.json	Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json	Updates the tracking information for a fulfillment.
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/open.json	Mark a fulfillment as complete
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/open.json	Mark a fulfillment as open
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json	Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/cancel.json	Cancels a fulfillment.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Creates a fulfillment event
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Retrieves a specific fulfillment event
DELETE	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Deletes a fulfillment event
GET	/admin/api/2020-10/orders/{order_id}/fulfillment_orders.json	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}.json	Retrieves a specific fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancel.json	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/close.json	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/move.json	Moves a fulfillment order from one merchant managed location to another merchant managed location.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
GET	/admin/api/2020-10/fulfillment_services.json	
POST	/admin/api/2020-10/fulfillment_services.json	To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.
GET	/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json	
PUT	/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json	
DELETE	/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json	
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/2020-10/shopify_payments/balance.json	Retrieves the account's current balance.
GET	/admin/api/2020-10/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2020-10/countries.json	Retrieves a list of countries.
POST	/admin/api/2020-10/countries.json	Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET	/admin/api/2020-10/countries/count.json	Retrieves a count of countries.
GET	/admin/api/2020-10/countries/{country_id}.json	Retrieves a specific county.
PUT	/admin/api/2020-10/countries/{country_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-10/countries/{country_id}.json	Deletes a country.
GET	/admin/api/2020-10/currencies.json	Retrieves a list of currencies enabled on a shop
GET	/admin/api/2020-10/policies.json	Retrieves a list of the shop's policies
GET	/admin/api/2020-10/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2020-10/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-10/shipping_zones.json	Get a list of all shipping zones
GET	/admin/api/2020-10/shop.json	Retrieves the shop's configuration
GET	/admin/api/2020-10/tender_transactions.json	Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

location

GET	/admin/api/2020-01/locations.json	Retrieves a list of locations
GET	/admin/api/2020-01/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2020-01/locations/count.json	Retrieves a count of locations
GET	/admin/api/2020-01/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/locations.json	Retrieves a list of locations
GET	/admin/api/2020-04/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2020-04/locations/count.json	Retrieves a count of locations
GET	/admin/api/2020-04/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/locations.json	Retrieves a list of locations
GET	/admin/api/2020-07/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2020-07/locations/count.json	Retrieves a count of locations
GET	/admin/api/2020-07/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/locations.json	Retrieves a list of locations
GET	/admin/api/2020-10/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2020-10/locations/count.json	Retrieves a count of locations
GET	/admin/api/2020-10/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET	/admin/api/2021-01/locations.json	Retrieves a list of locations
GET	/admin/api/2021-01/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2021-01/locations/count.json	Retrieves a count of locations
GET	/admin/api/2021-01/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/locations.json	Retrieves a list of locations
GET	/admin/api/unstable/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/unstable/locations/count.json	Retrieves a count of locations
GET	/admin/api/unstable/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

locationsformove

GET	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

metafield

GET	/admin/api/2020-01/metafields.json	Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/2020-01/metafields.json	Creates a new metafield for a resource.
GET	/admin/api/2020-01/metafields/count.json	Retrieves a count of a resource's metafields.
GET	/admin/api/2020-01/metafields/{metafield_id}.json	Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/2020-01/metafields/{metafield_id}.json	Updates a metafield.
DELETE	/admin/api/2020-01/metafields/{metafield_id}.json	Deletes a metafield by its ID.
GET	/admin/api/2020-04/metafields.json	Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/2020-04/metafields.json	Creates a new metafield for a resource.
GET	/admin/api/2020-04/metafields/count.json	Retrieves a count of a resource's metafields.
GET	/admin/api/2020-04/metafields/{metafield_id}.json	Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/2020-04/metafields/{metafield_id}.json	Updates a metafield.
DELETE	/admin/api/2020-04/metafields/{metafield_id}.json	Deletes a metafield by its ID.
GET	/admin/api/2020-07/metafields.json	Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/2020-07/metafields.json	

GET	/admin/api/2020-07/metafields/count.json	Creates a new metafield for a resource.
		Retrieves a count of a resource's metafields.
GET	/admin/api/2020-07/metafields/{metafield_id}.json	
		Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/2020-07/metafields/{metafield_id}.json	
		Updates a metafield.
DELETE	/admin/api/2020-07/metafields/{metafield_id}.json	
		Deletes a metafield by its ID.
GET	/admin/api/2020-10/metafields.json	
		Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/2020-10/metafields.json	
		Creates a new metafield for a resource.
GET	/admin/api/2020-10/metafields/count.json	
		Retrieves a count of a resource's metafields.
GET	/admin/api/2020-10/metafields/{metafield_id}.json	
		Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/2020-10/metafields/{metafield_id}.json	
		Updates a metafield.
DELETE	/admin/api/2020-10/metafields/{metafield_id}.json	
		Deletes a metafield by its ID.
GET	/admin/api/2021-01/metafields.json	
		Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/2021-01/metafields.json	
		Creates a new metafield for a resource.
GET	/admin/api/2021-01/metafields/count.json	
		Retrieves a count of a resource's metafields.
GET	/admin/api/2021-01/metafields/{metafield_id}.json	
		Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/2021-01/metafields/{metafield_id}.json	
		Updates a metafield.
DELETE	/admin/api/2021-01/metafields/{metafield_id}.json	
		Deletes a metafield by its ID.
GET	/admin/api/unstable/metafields.json	
		Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/unstable/metafields.json	
		Creates a new metafield for a resource.
GET	/admin/api/unstable/metafields/count.json	
		Retrieves a count of a resource's metafields.
GET	/admin/api/unstable/metafields/{metafield_id}.json	
		Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/unstable/metafields/{metafield_id}.json	
		Updates a metafield.
DELETE	/admin/api/unstable/metafields/{metafield_id}.json	
		Deletes a metafield by its ID.

online-store

GET	/admin/api/2020-01/blogs/{blog_id}/articles.json	
		Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/blogs/{blog_id}/articles.json	
		Creates an article for a blog
GET	/admin/api/2020-01/blogs/{blog_id}/articles/count.json	
		Retrieves a count of all articles from a blog
GET	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json	
		Retrieves a single article
PUT	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json	
		Updates an article
DELETE	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json	
		Deletes an article
GET	/admin/api/2020-01/articles/authors.json	
		Retrieves a list all of article authors
GET	/admin/api/2020-01/articles/tags.json	
		Retrieves a list of all the tags
GET	/admin/api/2020-04/blogs/{blog_id}/articles.json	
		Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<u>POST</u>	<u>/admin/api/2020-04/blogs/{blog_id}/articles.json</u> Creates an article for a blog
<u>GET</u>	<u>/admin/api/2020-04/blogs/{blog_id}/articles/count.json</u> Retrieves a count of all articles from a blog
<u>GET</u>	<u>/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json</u> Retrieves a single article
<u>PUT</u>	<u>/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json</u> Updates an article
<u>DELETE</u>	<u>/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json</u> Deletes an article
<u>GET</u>	<u>/admin/api/2020-04/articles/authors.json</u> Retrieves a list all of article authors
<u>GET</u>	<u>/admin/api/2020-04/articles/tags.json</u> Retrieves a list of all the tags
<u>GET</u>	<u>/admin/api/2020-07/blogs/{blog_id}/articles.json</u> Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<u>POST</u>	<u>/admin/api/2020-07/blogs/{blog_id}/articles.json</u> Creates an article for a blog
<u>GET</u>	<u>/admin/api/2020-07/blogs/{blog_id}/articles/count.json</u> Retrieves a count of all articles from a blog
<u>GET</u>	<u>/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json</u> Retrieves a single article
<u>PUT</u>	<u>/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json</u> Updates an article
<u>DELETE</u>	<u>/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json</u> Deletes an article
<u>GET</u>	<u>/admin/api/2020-07/articles/authors.json</u> Retrieves a list all of article authors
<u>GET</u>	<u>/admin/api/2020-07/articles/tags.json</u> Retrieves a list of all the tags
<u>GET</u>	<u>/admin/api/2020-10/blogs/{blog_id}/articles.json</u> Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<u>POST</u>	<u>/admin/api/2020-10/blogs/{blog_id}/articles.json</u> Creates an article for a blog
<u>GET</u>	<u>/admin/api/2020-10/blogs/{blog_id}/articles/count.json</u> Retrieves a count of all articles from a blog
<u>GET</u>	<u>/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json</u> Retrieves a single article
<u>PUT</u>	<u>/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json</u> Updates an article
<u>DELETE</u>	<u>/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json</u> Deletes an article
<u>GET</u>	<u>/admin/api/2020-10/articles/authors.json</u> Retrieves a list all of article authors
<u>GET</u>	<u>/admin/api/2020-10/articles/tags.json</u> Retrieves a list of all the tags
<u>GET</u>	<u>/admin/api/2021-01/blogs/{blog_id}/articles.json</u> Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<u>POST</u>	<u>/admin/api/2021-01/blogs/{blog_id}/articles.json</u> Creates an article for a blog
<u>GET</u>	<u>/admin/api/2021-01/blogs/{blog_id}/articles/count.json</u> Retrieves a count of all articles from a blog
<u>GET</u>	<u>/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json</u> Retrieves a single article
<u>PUT</u>	<u>/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json</u> Updates an article
<u>DELETE</u>	<u>/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json</u> Deletes an article
<u>GET</u>	<u>/admin/api/2021-01/articles/authors.json</u> Retrieves a list all of article authors
<u>GET</u>	<u>/admin/api/2021-01/articles/tags.json</u> Retrieves a list of all the tags
<u>GET</u>	<u>/admin/api/unstable/blogs/{blog_id}/articles.json</u> Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST	/admin/api/unstable/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/unstable/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/unstable/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/unstable/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-01/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-01/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-01/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-04/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-04/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-04/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-07/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-07/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-07/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-10/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-10/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-10/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2021-01/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2021-01/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2021-01/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/unstable/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/unstable/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/unstable/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-01/blogs.json Retrieve a list of all blogs. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST	/admin/api/2020-01/blogs.json Create a new blog
GET	/admin/api/2020-01/blogs/count.json Get a count of all blogs
GET	/admin/api/2020-01/blogs/{blog_id}.json Get a single blog by its ID
PUT	/admin/api/2020-01/blogs/{blog_id}.json Update a blog
DELETE	/admin/api/2020-01/blogs/{blog_id}.json Delete a blog
GET	/admin/api/2020-01/comments.json Retrieves a list of comments. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/comments.json Creates a comment for an article
GET	/admin/api/2020-01/comments/count.json Retrieves a count of comments
GET	/admin/api/2020-01/comments/{comment_id}.json Retrieves a single comment by its ID
PUT	/admin/api/2020-01/comments/{comment_id}.json Updates a comment of an article
POST	/admin/api/2020-01/comments/{comment_id}/spam.json Marks a comment as spam
POST	/admin/api/2020-01/comments/{comment_id}/not_spam.json Marks a comment as not spam
POST	/admin/api/2020-01/comments/{comment_id}/approve.json Approves a comment
POST	/admin/api/2020-01/comments/{comment_id}/remove.json Removes a comment
POST	/admin/api/2020-01/comments/{comment_id}/restore.json Restores a previously removed comment
GET	/admin/api/2020-01/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-01/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2020-01/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2020-01/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2020-01/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2020-04/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-04/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2020-04/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2020-04/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2020-04/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2020-07/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-07/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2020-07/redirects/{redirect_id}.json

PUT	Retrieves a single redirect /admin/api/2020-07/redirects/{redirect_id}.json
	Updates an existing redirect
DELETE	/admin/api/2020-07/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2020-10/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-10/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2020-10/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2020-10/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2020-10/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2021-01/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2021-01/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2021-01/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2021-01/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2021-01/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/unstable/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/unstable/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/unstable/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/unstable/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/unstable/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2020-01/script_tags.json Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/script_tags.json Creates a new script tag
GET	/admin/api/2020-01/script_tags/count.json Retrieves a count of all script tags
GET	/admin/api/2020-01/script_tags/{script_tag_id}.json Retrieves a single script tag
PUT	/admin/api/2020-01/script_tags/{script_tag_id}.json Updates a script tag
DELETE	/admin/api/2020-01/script_tags/{script_tag_id}.json Deletes a script tag
GET	/admin/api/2020-04/script_tags.json Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/script_tags.json Creates a new script tag
GET	/admin/api/2020-04/script_tags/count.json Retrieves a count of all script tags
GET	/admin/api/2020-04/script_tags/{script_tag_id}.json Retrieves a single script tag

PUT /admin/api/2020-04/script_tags/{script_tag_id}.json
Updates a script tag

DELETE /admin/api/2020-04/script_tags/{script_tag_id}.json
Deletes a script tag

GET /admin/api/2020-07/script_tags.json
Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/script_tags.json
Creates a new script tag

GET /admin/api/2020-07/script_tags/count.json
Retrieves a count of all script tags

GET /admin/api/2020-07/script_tags/{script_tag_id}.json
Retrieves a single script tag

PUT /admin/api/2020-07/script_tags/{script_tag_id}.json
Updates a script tag

DELETE /admin/api/2020-07/script_tags/{script_tag_id}.json
Deletes a script tag

GET /admin/api/2020-10/script_tags.json
Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/script_tags.json
Creates a new script tag

GET /admin/api/2020-10/script_tags/count.json
Retrieves a count of all script tags

GET /admin/api/2020-10/script_tags/{script_tag_id}.json
Retrieves a single script tag

PUT /admin/api/2020-10/script_tags/{script_tag_id}.json
Updates a script tag

DELETE /admin/api/2020-10/script_tags/{script_tag_id}.json
Deletes a script tag

GET /admin/api/2021-01/script_tags.json
Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/script_tags.json
Creates a new script tag

GET /admin/api/2021-01/script_tags/count.json
Retrieves a count of all script tags

GET /admin/api/2021-01/script_tags/{script_tag_id}.json
Retrieves a single script tag

PUT /admin/api/2021-01/script_tags/{script_tag_id}.json
Updates a script tag

DELETE /admin/api/2021-01/script_tags/{script_tag_id}.json
Deletes a script tag

GET /admin/api/unstable/script_tags.json
Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/script_tags.json
Creates a new script tag

GET /admin/api/unstable/script_tags/count.json
Retrieves a count of all script tags

GET /admin/api/unstable/script_tags/{script_tag_id}.json
Retrieves a single script tag

PUT /admin/api/unstable/script_tags/{script_tag_id}.json
Updates a script tag

DELETE /admin/api/unstable/script_tags/{script_tag_id}.json
Deletes a script tag

GET </admin/api/2020-01/themes.json>
Retrieves a list of themes.

POST </admin/api/2020-01/themes.json>
Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

GET /admin/api/2020-01/themes/{theme_id}.json
Retrieves a single theme.

PUT /admin/api/2020-01/themes/{theme_id}.json
Updates an existing theme.

DELETE /admin/api/2020-01/themes/{theme_id}.json
Deletes a theme.

GET	/admin/api/2020-04/themes.json	Retrieves a list of themes.
POST	/admin/api/2020-04/themes.json	Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-04/themes/{theme_id}.json	Retrieves a single theme.
PUT	/admin/api/2020-04/themes/{theme_id}.json	Updates an existing theme.
DELETE	/admin/api/2020-04/themes/{theme_id}.json	Deletes a theme.
GET	/admin/api/2020-07/themes.json	Retrieves a list of themes.
POST	/admin/api/2020-07/themes.json	Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-07/themes/{theme_id}.json	Retrieves a single theme.
PUT	/admin/api/2020-07/themes/{theme_id}.json	Updates an existing theme.
DELETE	/admin/api/2020-07/themes/{theme_id}.json	Deletes a theme.
GET	/admin/api/2020-10/themes.json	Retrieves a list of themes.
POST	/admin/api/2020-10/themes.json	Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-10/themes/{theme_id}.json	Retrieves a single theme.
PUT	/admin/api/2020-10/themes/{theme_id}.json	Updates an existing theme.
DELETE	/admin/api/2020-10/themes/{theme_id}.json	Deletes a theme.
GET	/admin/api/2021-01/themes.json	Retrieves a list of themes.
POST	/admin/api/2021-01/themes.json	Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2021-01/themes/{theme_id}.json	Retrieves a single theme.
PUT	/admin/api/2021-01/themes/{theme_id}.json	Updates an existing theme.
DELETE	/admin/api/2021-01/themes/{theme_id}.json	Deletes a theme.
GET	/admin/api/unstable/themes.json	Retrieves a list of themes.
POST	/admin/api/unstable/themes.json	Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/unstable/themes/{theme_id}.json	Retrieves a single theme.
PUT	/admin/api/unstable/themes/{theme_id}.json	Updates an existing theme.
DELETE	/admin/api/unstable/themes/{theme_id}.json	Deletes a theme.

online-store/article

GET	/admin/api/2020-01/blogs/{blog_id}/articles.json	Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/blogs/{blog_id}/articles.json	Creates an article for a blog
GET	/admin/api/2020-01/blogs/{blog_id}/articles/count.json	Retrieves a count of all articles from a blog

GET	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-01/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-01/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-04/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-04/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-04/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-04/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-07/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-07/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-07/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-07/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-10/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-10/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-10/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-10/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2021-01/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2021-01/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog

GET	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2021-01/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2021-01/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/unstable/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/unstable/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/unstable/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/unstable/articles/tags.json Retrieves a list of all the tags

online-store/asset

GET	/admin/api/2020-01/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.
PUT	/admin/api/2020-01/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.
DELETE	/admin/api/2020-01/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-04/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.
PUT	/admin/api/2020-04/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.
DELETE	/admin/api/2020-04/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-07/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.
PUT	/admin/api/2020-07/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.
DELETE	/admin/api/2020-07/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-10/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.
PUT	/admin/api/2020-10/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.
DELETE	/admin/api/2020-10/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2021-01/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.
PUT	/admin/api/2021-01/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

DELETE /admin/api/2021-01/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET /admin/api/unstable/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.

PUT /admin/api/unstable/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

DELETE /admin/api/unstable/themes/{theme_id}/assets.json

Deletes an asset from a theme.

online-store/blog

GET </admin/api/2020-01/blogs.json>

Retrieve a list of all blogs. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/blogs.json>

Create a new blog

GET </admin/api/2020-01/blogs/count.json>

Get a count of all blogs

GET /admin/api/2020-01/blogs/{blog_id}.json

Get a single blog by its ID

PUT /admin/api/2020-01/blogs/{blog_id}.json

Update a blog

DELETE /admin/api/2020-01/blogs/{blog_id}.json

Delete a blog

online-store/comment

GET </admin/api/2020-01/comments.json>

Retrieves a list of comments. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/comments.json>

Creates a comment for an article

GET </admin/api/2020-01/comments/count.json>

Retrieves a count of comments

GET /admin/api/2020-01/comments/{comment_id}.json

Retrieves a single comment by its ID

PUT /admin/api/2020-01/comments/{comment_id}.json

Updates a comment of an article

POST /admin/api/2020-01/comments/{comment_id}/spam.json

Marks a comment as spam

POST /admin/api/2020-01/comments/{comment_id}/not_spam.json

Marks a comment as not spam

POST /admin/api/2020-01/comments/{comment_id}/approve.json

Approves a comment

POST /admin/api/2020-01/comments/{comment_id}/remove.json

Removes a comment

POST /admin/api/2020-01/comments/{comment_id}/restore.json

Restores a previously removed comment

online-store/redirect

GET </admin/api/2020-01/redirects.json>

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/redirects.json>

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

GET </admin/api/2020-01/redirects/count.json>

Retrieves a count of URL redirects

GET /admin/api/2020-01/redirects/{redirect_id}.json

Retrieves a single redirect

PUT /admin/api/2020-01/redirects/{redirect_id}.json

Updates an existing redirect

DELETE /admin/api/2020-01/redirects/{redirect_id}.json

Deletes a redirect

GET </admin/api/2020-04/redirects.json>

	Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/redirects.json
	Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-04/redirects/count.json
	Retrieves a count of URL redirects
GET	/admin/api/2020-04/redirects/{redirect_id}.json
	Retrieves a single redirect
PUT	/admin/api/2020-04/redirects/{redirect_id}.json
	Updates an existing redirect
DELETE	/admin/api/2020-04/redirects/{redirect_id}.json
	Deletes a redirect
GET	/admin/api/2020-07/redirects.json
	Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/redirects.json
	Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-07/redirects/count.json
	Retrieves a count of URL redirects
GET	/admin/api/2020-07/redirects/{redirect_id}.json
	Retrieves a single redirect
PUT	/admin/api/2020-07/redirects/{redirect_id}.json
	Updates an existing redirect
DELETE	/admin/api/2020-07/redirects/{redirect_id}.json
	Deletes a redirect
GET	/admin/api/2020-10/redirects.json
	Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/redirects.json
	Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-10/redirects/count.json
	Retrieves a count of URL redirects
GET	/admin/api/2020-10/redirects/{redirect_id}.json
	Retrieves a single redirect
PUT	/admin/api/2020-10/redirects/{redirect_id}.json
	Updates an existing redirect
DELETE	/admin/api/2020-10/redirects/{redirect_id}.json
	Deletes a redirect
GET	/admin/api/2021-01/redirects.json
	Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/redirects.json
	Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2021-01/redirects/count.json
	Retrieves a count of URL redirects
GET	/admin/api/2021-01/redirects/{redirect_id}.json
	Retrieves a single redirect
PUT	/admin/api/2021-01/redirects/{redirect_id}.json
	Updates an existing redirect
DELETE	/admin/api/2021-01/redirects/{redirect_id}.json
	Deletes a redirect
GET	/admin/api/unstable/redirects.json
	Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/redirects.json
	Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/unstable/redirects/count.json
	Retrieves a count of URL redirects
GET	/admin/api/unstable/redirects/{redirect_id}.json
	Retrieves a single redirect
PUT	/admin/api/unstable/redirects/{redirect_id}.json
	Updates an existing redirect
DELETE	/admin/api/unstable/redirects/{redirect_id}.json
	Deletes a redirect

online-store/scripttag

GET /admin/api/2020-01/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/script_tags.json

Creates a new script tag

GET /admin/api/2020-01/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-01/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-01/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-01/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2020-04/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/script_tags.json

Creates a new script tag

GET /admin/api/2020-04/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-04/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-04/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-04/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2020-07/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/script_tags.json

Creates a new script tag

GET /admin/api/2020-07/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-07/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-07/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-07/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2020-10/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/script_tags.json

Creates a new script tag

GET /admin/api/2020-10/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-10/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-10/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-10/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2021-01/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/script_tags.json

Creates a new script tag

GET /admin/api/2021-01/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2021-01/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2021-01/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2021-01/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/unstable/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST	/admin/api/unstable/script_tags.json Creates a new script tag
GET	/admin/api/unstable/script_tags/count.json Retrieves a count of all script tags
GET	/admin/api/unstable/script_tags/{script_tag_id}.json Retrieves a single script tag
PUT	/admin/api/unstable/script_tags/{script_tag_id}.json Updates a script tag
DELETE	/admin/api/unstable/script_tags/{script_tag_id}.json Deletes a script tag

online-store/theme

GET	/admin/api/2020-01/themes.json Retrieves a list of themes.
POST	/admin/api/2020-01/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-01/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-01/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-01/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2020-04/themes.json Retrieves a list of themes.
POST	/admin/api/2020-04/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-04/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-04/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-04/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2020-07/themes.json Retrieves a list of themes.
POST	/admin/api/2020-07/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-07/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-07/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-07/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2020-10/themes.json Retrieves a list of themes.
POST	/admin/api/2020-10/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-10/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-10/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-10/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2021-01/themes.json Retrieves a list of themes.
POST	/admin/api/2021-01/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2021-01/themes/{theme_id}.json

PUT	/admin/api/2021-01/themes/{theme_id}.json	Retrieves a single theme.
		Updates an existing theme.
DELETE	/admin/api/2021-01/themes/{theme_id}.json	Deletes a theme.
GET	/admin/api/unstable/themes.json	Retrieves a list of themes.
POST	/admin/api/unstable/themes.json	Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/unstable/themes/{theme_id}.json	Retrieves a single theme.
PUT	/admin/api/unstable/themes/{theme_id}.json	Updates an existing theme.
DELETE	/admin/api/unstable/themes/{theme_id}.json	Deletes a theme.

order

GET	/admin/api/2020-01/orders.json	Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders.json	Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: <code>inventory_behaviour</code> : The behaviour to use when updating inventory. (default: <code>bypass</code>) <code>bypass</code> : Do not claim inventory. <code>decrement_ignoring_policy</code> : Ignore the product's inventory policy and claim inventory. <code>decrement_obeying_policy</code> : Follow the product's inventory policy and claim inventory, if possible. <code>send_receipt</code> : Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when <code>send_receipt</code> is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. <code>send_fulfillment_receipt</code> : Whether to send a shipping confirmation to the customer. Note If you are including <code>shipping_address</code> or <code>billing_address</code> , make sure to pass both <code>first_name</code> and <code>last_name</code> . Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.
GET	/admin/api/2020-01/orders/{order_id}.json	Retrieves a specific order
PUT	/admin/api/2020-01/orders/{order_id}.json	Updates an order
DELETE	/admin/api/2020-01/orders/{order_id}.json	Deletes an order. Orders that interact with an online gateway can't be deleted.
GET	/admin/api/2020-01/orders/count.json	Retrieves an order count
POST	/admin/api/2020-01/orders/{order_id}/close.json	Closes an order
POST	/admin/api/2020-01/orders/{order_id}/open.json	Re-opens a closed order
POST	/admin/api/2020-01/orders/{order_id}/cancel.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.
GET	/admin/api/2020-04/orders.json	Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders.json	Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: <code>inventory_behaviour</code> : The behaviour to use when updating inventory. (default: <code>bypass</code>) <code>bypass</code> : Do not claim inventory. <code>decrement_ignoring_policy</code> : Ignore the product's inventory policy and claim inventory. <code>decrement_obeying_policy</code> : Follow the product's inventory policy and claim inventory, if possible. <code>send_receipt</code> : Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when <code>send_receipt</code> is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. <code>send_fulfillment_receipt</code> : Whether to send a shipping confirmation to the customer. Note If you are including <code>shipping_address</code> or <code>billing_address</code> , make sure to pass both <code>first_name</code> and <code>last_name</code> . Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.
GET	/admin/api/2020-04/orders/{order_id}.json	Retrieves a specific order
PUT	/admin/api/2020-04/orders/{order_id}.json	Updates an order
DELETE	/admin/api/2020-04/orders/{order_id}.json	Deletes an order. Orders that interact with an online gateway can't be deleted.
GET	/admin/api/2020-04/orders/count.json	Retrieves an order count
POST	/admin/api/2020-04/orders/{order_id}/close.json	Closes an order
POST	/admin/api/2020-04/orders/{order_id}/open.json	Re-opens a closed order
POST	/admin/api/2020-04/orders/{order_id}/cancel.json	

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.

GET </admin/api/2020-07/orders.json>

Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

order-risk

GET /admin/api/2020-01/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/orders/{order_id}/risks.json

Creates an order risk for an order

GET /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

PUT /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

DELETE /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

GET /admin/api/2020-04/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/orders/{order_id}/risks.json

Creates an order risk for an order

GET /admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

PUT /admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

DELETE /admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

GET /admin/api/2020-07/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/orders/{order_id}/risks.json

Creates an order risk for an order

GET /admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

PUT /admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

DELETE /admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

GET /admin/api/2020-10/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/orders/{order_id}/risks.json

Creates an order risk for an order

GET /admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

PUT /admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

DELETE /admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

GET /admin/api/2021-01/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/orders/{order_id}/risks.json

Creates an order risk for an order

GET /admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

PUT /admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

DELETE /admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

GET /admin/api/unstable/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API

	endpoints.
POST	/admin/api/unstable/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

orders

GET	/admin/api/2020-01/checkouts/count.json Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-04/checkouts/count.json Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-07/checkouts/count.json Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-10/checkouts/count.json Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2021-01/checkouts/count.json Retrieves a count of checkouts from the past 90 days
GET	/admin/api/unstable/checkouts/count.json Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-01/orders.json Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders.json Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: <code>inventory_behaviour</code> : The behaviour to use when updating inventory. (default: <code>bypass</code>) <code>bypass</code> : Do not claim inventory. <code>decrement_ignoring_policy</code> : Ignore the product's inventory policy and claim inventory. <code>decrement_obeying_policy</code> : Follow the product's inventory policy and claim inventory, if possible. <code>send_receipt</code> : Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when <code>send_receipt</code> is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. <code>send_fulfillment_receipt</code> : Whether to send a shipping confirmation to the customer. Note If you are including <code>shipping_address</code> or <code>billing_address</code> , make sure to pass both <code>first_name</code> and <code>last_name</code> . Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.
GET	/admin/api/2020-01/orders/{order_id}.json Retrieves a specific order
PUT	/admin/api/2020-01/orders/{order_id}.json Updates an order
DELETE	/admin/api/2020-01/orders/{order_id}.json Deletes an order. Orders that interact with an online gateway can't be deleted.
GET	/admin/api/2020-01/orders/count.json Retrieves an order count
POST	/admin/api/2020-01/orders/{order_id}/close.json Closes an order
POST	/admin/api/2020-01/orders/{order_id}/open.json Re-opens a closed order
POST	/admin/api/2020-01/orders/{order_id}/cancel.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.
GET	/admin/api/2020-04/orders.json Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders.json Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: <code>inventory_behaviour</code> : The behaviour to use when updating inventory. (default: <code>bypass</code>) <code>bypass</code> : Do not claim inventory. <code>decrement_ignoring_policy</code> : Ignore the product's inventory policy and claim inventory. <code>decrement_obeying_policy</code> : Follow the product's inventory policy and claim inventory, if possible. <code>send_receipt</code> : Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when <code>send_receipt</code> is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. <code>send_fulfillment_receipt</code> : Whether to send a shipping confirmation to the customer. Note If you are including <code>shipping_address</code> or <code>billing_address</code> , make sure to pass both <code>first_name</code> and <code>last_name</code> . Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.
GET	/admin/api/2020-04/orders/{order_id}.json Retrieves a specific order
PUT	/admin/api/2020-04/orders/{order_id}.json Updates an order
DELETE	/admin/api/2020-04/orders/{order_id}.json Deletes an order. Orders that interact with an online gateway can't be deleted.
GET	/admin/api/2020-04/orders/count.json Retrieves an order count
POST	/admin/api/2020-04/orders/{order_id}/close.json

POST	/admin/api/2020-04/orders/{order_id}/open.json	Closes an order
		Re-opens a closed order
POST	/admin/api/2020-04/orders/{order_id}/cancel.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.
GET	/admin/api/2020-07/orders.json	Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/risks.json	Creates an order risk for an order
GET	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
PUT	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-04/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/risks.json	Creates an order risk for an order
GET	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
PUT	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-07/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/orders/{order_id}/risks.json	Creates an order risk for an order
GET	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
PUT	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-10/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/risks.json	Creates an order risk for an order
GET	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
PUT	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2021-01/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/orders/{order_id}/risks.json	Creates an order risk for an order
GET	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
PUT	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/unstable/orders/{order_id}/risks.json	

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/orders/{order_id}/risks.json

Creates an order risk for an order

GET /admin/api/unstable/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

PUT /admin/api/unstable/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

DELETE /admin/api/unstable/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

GET /admin/api/2020-01/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2020-01/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2020-01/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2020-04/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2020-04/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2020-04/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2020-07/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2020-07/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2020-07/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2020-10/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2020-10/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2020-10/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more

items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2021-01/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2021-01/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2021-01/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/unstable/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/unstable/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/unstable/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

orders/abandoned-checkouts

GET </admin/api/2020-01/checkouts/count.json>

Retrieves a count of checkouts from the past 90 days

GET </admin/api/2020-04/checkouts/count.json>

Retrieves a count of checkouts from the past 90 days

GET </admin/api/2020-07/checkouts/count.json>

Retrieves a count of checkouts from the past 90 days

GET </admin/api/2020-10/checkouts/count.json>

Retrieves a count of checkouts from the past 90 days

GET </admin/api/2021-01/checkouts/count.json>

Retrieves a count of checkouts from the past 90 days

GET </admin/api/unstable/checkouts/count.json>

Retrieves a count of checkouts from the past 90 days

orders/order

GET </admin/api/2020-01/orders.json>

Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/orders.json>

Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: `inventory_behaviour`: The behaviour to use when updating inventory. (default: `bypass`) `bypass`: Do not claim inventory. `decrement_ignoring_policy`: Ignore the product's inventory policy and claim inventory. `decrement_obeying_policy`: Follow the product's inventory policy and claim inventory, if possible. `send_receipt`: Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when `send_receipt` is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. `send_fulfillment_receipt`: Whether to send a shipping confirmation to the customer. Note If you are including `shipping_address` or `billing_address`, make sure to pass both `first_name` and `last_name`. Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.

GET /admin/api/2020-01/orders/{order_id}.json

Retrieves a specific order

PUT /admin/api/2020-01/orders/{order_id}.json

Updates an order

DELETE /admin/api/2020-01/orders/{order_id}.json

Deletes an order. Orders that interact with an online gateway can't be deleted.

GET </admin/api/2020-01/orders/count.json>

Retrieves an order count

POST /admin/api/2020-01/orders/{order_id}/close.json

POST	/admin/api/2020-01/orders/{order_id}/open.json Closes an order Re-opens a closed order
POST	/admin/api/2020-01/orders/{order_id}/cancel.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.
GET	/admin/api/2020-04/orders.json Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders.json Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: <code>inventory_behaviour</code> : The behaviour to use when updating inventory. (default: <code>bypass</code>) <code>bypass</code> : Do not claim inventory. <code>decrement_ignoring_policy</code> : Ignore the product's inventory policy and claim inventory. <code>decrement_obeying_policy</code> : Follow the product's inventory policy and claim inventory, if possible. <code>send_receipt</code> : Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when <code>send_receipt</code> is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. <code>send_fulfillment_receipt</code> : Whether to send a shipping confirmation to the customer. Note If you are including <code>shipping_address</code> or <code>billing_address</code> , make sure to pass both <code>first_name</code> and <code>last_name</code> . Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.
GET	/admin/api/2020-04/orders/{order_id}.json Retrieves a specific order
PUT	/admin/api/2020-04/orders/{order_id}.json Updates an order
DELETE	/admin/api/2020-04/orders/{order_id}.json Deletes an order. Orders that interact with an online gateway can't be deleted.
GET	/admin/api/2020-04/orders/count.json Retrieves an order count
POST	/admin/api/2020-04/orders/{order_id}/close.json Closes an order
POST	/admin/api/2020-04/orders/{order_id}/open.json Re-opens a closed order
POST	/admin/api/2020-04/orders/{order_id}/cancel.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.
GET	/admin/api/2020-07/orders.json Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

orders/order-risk

GET	/admin/api/2020-01/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-04/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-07/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json

DELETE	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
GET	/admin/api/2020-10/orders/{order_id}/risks.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
POST	/admin/api/2020-10/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Creates an order risk for an order
PUT	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
DELETE	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
GET	/admin/api/2021-01/orders/{order_id}/risks.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
POST	/admin/api/2021-01/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json	Creates an order risk for an order
PUT	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
DELETE	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
GET	/admin/api/unstable/orders/{order_id}/risks.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
POST	/admin/api/unstable/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json	Creates an order risk for an order
PUT	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
DELETE	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

orders/refund

GET	/admin/api/2020-01/orders/{order_id}/refunds.json	Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/refunds.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-01/orders/{order_id}/refunds/{refund_id}.json	Retrieves a specific refund.
POST	/admin/api/2020-01/orders/{order_id}/refunds/calculate.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.
GET	/admin/api/2020-04/orders/{order_id}/refunds.json	Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/refunds.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-04/orders/{order_id}/refunds/{refund_id}.json	Retrieves a specific refund.
POST	/admin/api/2020-04/orders/{order_id}/refunds/calculate.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more

items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2020-07/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2020-07/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2020-07/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2020-10/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2020-10/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2020-10/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2021-01/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2021-01/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2021-01/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/unstable/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/unstable/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/unstable/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

payment

GET </admin/api/2020-01/checkouts/{token}/payments.json>

Retrieves a list of payments on a particular checkout

POST </admin/api/2020-01/checkouts/{token}/payments.json>

GET	/admin/api/2020-01/checkouts/{token}/payments/{payment_id}.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-01/checkouts/{token}/payments/count.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-01/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-04/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-04/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-04/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-04/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-07/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-07/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-07/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-07/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-10/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-10/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-10/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-10/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2021-01/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2021-01/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2021-01/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2021-01/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/unstable/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/unstable/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/unstable/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/unstable/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout

payout

GET	/admin/api/2020-01/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2020-04/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2020-07/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2020-10/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET	/admin/api/2020-10/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2021-01/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/unstable/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.

plus

GET	/admin/api/2020-01/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/gift_cards.json	Creates a gift card
GET	/admin/api/2020-01/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2020-01/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-01/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2020-01/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-01/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/gift_cards.json	Creates a gift card
GET	/admin/api/2020-04/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2020-04/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-04/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2020-04/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-04/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/gift_cards.json	Creates a gift card
GET	/admin/api/2020-07/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2020-07/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-07/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2020-07/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-07/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-10/gift_cards.json](#)
Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-10/gift_cards.json](#)
Creates a gift card

[GET](#) [/admin/api/2020-10/gift_cards/{gift_card_id}.json](#)
Retrieves a single gift card by its ID

[PUT](#) [/admin/api/2020-10/gift_cards/{gift_card_id}.json](#)
Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

[GET](#) [/admin/api/2020-10/gift_cards/count.json](#)
Retrieves a count of gift cards

[POST](#) [/admin/api/2020-10/gift_cards/{gift_card_id}/disable.json](#)
Disables a gift card. Disabling a gift card can't be undone.

[GET](#) [/admin/api/2020-10/gift_cards/search.json](#)
Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2021-01/gift_cards.json](#)
Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2021-01/gift_cards.json](#)
Creates a gift card

[GET](#) [/admin/api/2021-01/gift_cards/{gift_card_id}.json](#)
Retrieves a single gift card by its ID

[PUT](#) [/admin/api/2021-01/gift_cards/{gift_card_id}.json](#)
Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

[GET](#) [/admin/api/2021-01/gift_cards/count.json](#)
Retrieves a count of gift cards

[POST](#) [/admin/api/2021-01/gift_cards/{gift_card_id}/disable.json](#)
Disables a gift card. Disabling a gift card can't be undone.

[GET](#) [/admin/api/2021-01/gift_cards/search.json](#)
Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/unstable/gift_cards.json](#)
Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/unstable/gift_cards.json](#)
Creates a gift card

[GET](#) [/admin/api/unstable/gift_cards/{gift_card_id}.json](#)
Retrieves a single gift card by its ID

[PUT](#) [/admin/api/unstable/gift_cards/{gift_card_id}.json](#)
Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

[GET](#) [/admin/api/unstable/gift_cards/count.json](#)
Retrieves a count of gift cards

[POST](#) [/admin/api/unstable/gift_cards/{gift_card_id}/disable.json](#)
Disables a gift card. Disabling a gift card can't be undone.

[GET](#) [/admin/api/unstable/gift_cards/search.json](#)
Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-01/users.json](#)
Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-01/users/{user_id}.json](#)
Retrieves a single user

[GET](#) [/admin/api/2020-01/users/current.json](#)
Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

[GET](#) [/admin/api/2020-04/users.json](#)
Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-04/users/{user_id}.json](#)
Retrieves a single user

[GET](#) [/admin/api/2020-04/users/current.json](#)
Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

[GET](#) [/admin/api/2020-07/users.json](#)

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2020-07/users/{user_id}.json

Retrieves a single user

[GET](#) </admin/api/2020-07/users/current.json>

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

[GET](#) </admin/api/2020-10/users.json>

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2020-10/users/{user_id}.json

Retrieves a single user

[GET](#) </admin/api/2020-10/users/current.json>

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

[GET](#) </admin/api/2021-01/users.json>

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2021-01/users/{user_id}.json

Retrieves a single user

[GET](#) </admin/api/2021-01/users/current.json>

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

[GET](#) </admin/api/unstable/users.json>

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/unstable/users/{user_id}.json

Retrieves a single user

[GET](#) </admin/api/unstable/users/current.json>

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

plus/giftcard

[GET](#) /admin/api/2020-01/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) /admin/api/2020-01/gift_cards.json

Creates a gift card

[GET](#) /admin/api/2020-01/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

[PUT](#) /admin/api/2020-01/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

[GET](#) /admin/api/2020-01/gift_cards/count.json

Retrieves a count of gift cards

[POST](#) /admin/api/2020-01/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

[GET](#) /admin/api/2020-01/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2020-04/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) /admin/api/2020-04/gift_cards.json

Creates a gift card

[GET](#) /admin/api/2020-04/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

[PUT](#) /admin/api/2020-04/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

[GET](#) /admin/api/2020-04/gift_cards/count.json

Retrieves a count of gift cards

[POST](#) /admin/api/2020-04/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

[GET](#) /admin/api/2020-04/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2020-07/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/gift_cards.json

Creates a gift card

GET /admin/api/2020-07/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

PUT /admin/api/2020-07/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

GET /admin/api/2020-07/gift_cards/count.json

Retrieves a count of gift cards

POST /admin/api/2020-07/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

GET /admin/api/2020-07/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-10/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/gift_cards.json

Creates a gift card

GET /admin/api/2020-10/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

PUT /admin/api/2020-10/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

GET /admin/api/2020-10/gift_cards/count.json

Retrieves a count of gift cards

POST /admin/api/2020-10/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

GET /admin/api/2020-10/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2021-01/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/gift_cards.json

Creates a gift card

GET /admin/api/2021-01/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

PUT /admin/api/2021-01/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

GET /admin/api/2021-01/gift_cards/count.json

Retrieves a count of gift cards

POST /admin/api/2021-01/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

GET /admin/api/2021-01/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/unstable/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/gift_cards.json

Creates a gift card

GET /admin/api/unstable/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

PUT /admin/api/unstable/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

GET /admin/api/unstable/gift_cards/count.json

Retrieves a count of gift cards

POST /admin/api/unstable/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

GET /admin/api/unstable/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

plus/user

GET	/admin/api/2020-01/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/users/{user_id}.json Retrieves a single user
GET	/admin/api/2020-01/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-04/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/users/{user_id}.json Retrieves a single user
GET	/admin/api/2020-04/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-07/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/users/{user_id}.json Retrieves a single user
GET	/admin/api/2020-07/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-10/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/users/{user_id}.json Retrieves a single user
GET	/admin/api/2020-10/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2021-01/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/users/{user_id}.json Retrieves a single user
GET	/admin/api/2021-01/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/unstable/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/users/{user_id}.json Retrieves a single user
GET	/admin/api/unstable/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

policy

GET	/admin/api/2020-01/policies.json Retrieves a list of the shop's policies
GET	/admin/api/2020-04/policies.json Retrieves a list of the shop's policies
GET	/admin/api/2020-07/policies.json Retrieves a list of the shop's policies
GET	/admin/api/2020-10/policies.json Retrieves a list of the shop's policies
GET	/admin/api/2021-01/policies.json Retrieves a list of the shop's policies
GET	/admin/api/unstable/policies.json Retrieves a list of the shop's policies

product

GET	/admin/api/2020-01/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/products.json

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: `metafields_global_title_tag`: The name of the product used for SEO purposes. Generally added to the `<meta name='title'>` tag. `metafields_global_description_tag`: A description of the product used for SEO purposes. Generally added to the `<meta name='description'>` tag.

[GET /admin/api/2020-01/products/count.json](#)

Retrieves a count of products.

[GET /admin/api/2020-01/products/{product_id}.json](#)

Retrieves a single product.

[PUT /admin/api/2020-01/products/{product_id}.json](#)

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: `metafields_global_title_tag`: The name of the product used for SEO purposes. Generally added to the `<meta name='title'>` tag. `metafields_global_description_tag`: A description of the product used for SEO purposes. Generally added to the `<meta name='description'>` tag.

[DELETE /admin/api/2020-01/products/{product_id}.json](#)

Deletes a product.

[GET /admin/api/2020-04/products.json](#)

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST /admin/api/2020-04/products.json](#)

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: `metafields_global_title_tag`: The name of the product used for SEO purposes. Generally added to the `<meta name='title'>` tag. `metafields_global_description_tag`: A description of the product used for SEO purposes. Generally added to the `<meta name='description'>` tag.

[GET /admin/api/2020-04/products/count.json](#)

Retrieves a count of products.

[GET /admin/api/2020-04/products/{product_id}.json](#)

Retrieves a single product.

[PUT /admin/api/2020-04/products/{product_id}.json](#)

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: `metafields_global_title_tag`: The name of the product used for SEO purposes. Generally added to the `<meta name='title'>` tag. `metafields_global_description_tag`: A description of the product used for SEO purposes. Generally added to the `<meta name='description'>` tag.

[DELETE /admin/api/2020-04/products/{product_id}.json](#)

Deletes a product.

[GET /admin/api/2020-07/products.json](#)

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST /admin/api/2020-07/products.json](#)

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: `metafields_global_title_tag`: The name of the product used for SEO purposes. Generally added to the `<meta name='title'>` tag. `metafields_global_description_tag`: A description of the product used for SEO purposes. Generally added to the `<meta name='description'>` tag.

[GET /admin/api/2020-07/products/count.json](#)

Retrieves a count of products.

[GET /admin/api/2020-07/products/{product_id}.json](#)

Retrieves a single product.

[PUT /admin/api/2020-07/products/{product_id}.json](#)

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: `metafields_global_title_tag`: The name of the product used for SEO purposes. Generally added to the `<meta name='title'>` tag. `metafields_global_description_tag`: A description of the product used for SEO purposes. Generally added to the `<meta name='description'>` tag.

[DELETE /admin/api/2020-07/products/{product_id}.json](#)

Deletes a product.

[GET /admin/api/2020-10/products.json](#)

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST /admin/api/2020-10/products.json](#)

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: `metafields_global_title_tag`: The name of the product used for SEO purposes. Generally added to the `<meta name='title'>` tag. `metafields_global_description_tag`: A description of the product used for SEO purposes. Generally added to the `<meta name='description'>` tag.

[GET /admin/api/2020-10/products/count.json](#)

Retrieves a count of products.

[GET /admin/api/2020-10/products/{product_id}.json](#)

Retrieves a single product.

[PUT /admin/api/2020-10/products/{product_id}.json](#)

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: `metafields_global_title_tag`: The name of the product used for SEO purposes. Generally added to the `<meta name='title'>` tag. `metafields_global_description_tag`: A description of the product used for SEO purposes. Generally added to the `<meta name='description'>` tag.

[DELETE /admin/api/2020-10/products/{product_id}.json](#)

Deletes a product.

[GET /admin/api/2021-01/products.json](#)

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST /admin/api/2021-01/products.json](#)

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: `metafields_global_title_tag`: The name of the product used for SEO purposes. Generally added to the `<meta name='title'>` tag. `metafields_global_description_tag`: A description of the product used for SEO purposes. Generally added to the `<meta name='description'>` tag.

[GET /admin/api/2021-01/products/count.json](#)

GET	/admin/api/2021-01/products/{product_id}.json	Retrieves a count of products.
PUT	/admin/api/2021-01/products/{product_id}.json	Retrieves a single product.
DELETE	/admin/api/2021-01/products/{product_id}.json	Deletes a product.
GET	/admin/api/unstable/products.json	Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/products.json	Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/unstable/products/count.json	Retrieves a count of products.
GET	/admin/api/unstable/products/{product_id}.json	Retrieves a single product.
PUT	/admin/api/unstable/products/{product_id}.json	Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/unstable/products/{product_id}.json	Deletes a product.

product-image

GET	/admin/api/2020-01/products/{product_id}/images.json	Get all product images
POST	/admin/api/2020-01/products/{product_id}/images.json	Create a new product image
GET	/admin/api/2020-01/products/{product_id}/images/count.json	Get a count of all product images
GET	/admin/api/2020-01/products/{product_id}/images/{image_id}.json	Get a single product image by id
PUT	/admin/api/2020-01/products/{product_id}/images/{image_id}.json	Modify an existing product image
DELETE	/admin/api/2020-01/products/{product_id}/images/{image_id}.json	
GET	/admin/api/2020-04/products/{product_id}/images.json	Get all product images
POST	/admin/api/2020-04/products/{product_id}/images.json	Create a new product image
GET	/admin/api/2020-04/products/{product_id}/images/count.json	Get a count of all product images
GET	/admin/api/2020-04/products/{product_id}/images/{image_id}.json	Get a single product image by id
PUT	/admin/api/2020-04/products/{product_id}/images/{image_id}.json	Modify an existing product image
DELETE	/admin/api/2020-04/products/{product_id}/images/{image_id}.json	
GET	/admin/api/2020-07/products/{product_id}/images.json	Get all product images
POST	/admin/api/2020-07/products/{product_id}/images.json	Create a new product image
GET	/admin/api/2020-07/products/{product_id}/images/count.json	Get a count of all product images
GET	/admin/api/2020-07/products/{product_id}/images/{image_id}.json	Get a single product image by id
PUT	/admin/api/2020-07/products/{product_id}/images/{image_id}.json	Modify an existing product image
DELETE	/admin/api/2020-07/products/{product_id}/images/{image_id}.json	
GET	/admin/api/2020-10/products/{product_id}/images.json	Get all product images
POST	/admin/api/2020-10/products/{product_id}/images.json	Create a new product image
GET	/admin/api/2020-10/products/{product_id}/images/count.json	Get a count of all product images
GET	/admin/api/2020-10/products/{product_id}/images/{image_id}.json	

PUT	Get a single product image by id /admin/api/2020-10/products/{product_id}/images/{image_id}.json
	Modify an existing product image
DELETE	/admin/api/2020-10/products/{product_id}/images/{image_id}.json
GET	/admin/api/2021-01/products/{product_id}/images.json Get all product images
POST	/admin/api/2021-01/products/{product_id}/images.json Create a new product image
GET	/admin/api/2021-01/products/{product_id}/images/count.json Get a count of all product images
GET	/admin/api/2021-01/products/{product_id}/images/{image_id}.json Get a single product image by id
PUT	/admin/api/2021-01/products/{product_id}/images/{image_id}.json Modify an existing product image
DELETE	/admin/api/2021-01/products/{product_id}/images/{image_id}.json
GET	/admin/api/unstable/products/{product_id}/images.json Get all product images
POST	/admin/api/unstable/products/{product_id}/images.json Create a new product image
GET	/admin/api/unstable/products/{product_id}/images/count.json Get a count of all product images
GET	/admin/api/unstable/products/{product_id}/images/{image_id}.json Get a single product image by id
PUT	/admin/api/unstable/products/{product_id}/images/{image_id}.json Modify an existing product image
DELETE	/admin/api/unstable/products/{product_id}/images/{image_id}.json

productlisting

GET	/admin/api/2020-01/product_listings.json Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/product_listings/product_ids.json Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-01/product_listings/count.json Retrieve a count of products that are published to your app
GET	/admin/api/2020-01/product_listings/{product_listing_id}.json Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-01/product_listings/{product_listing_id}.json Create a product listing to publish a product to your app
DELETE	/admin/api/2020-01/product_listings/{product_listing_id}.json Delete a product listing to unpublish a product from your app
GET	/admin/api/2020-04/product_listings.json Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/product_listings/product_ids.json Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-04/product_listings/count.json Retrieve a count of products that are published to your app
GET	/admin/api/2020-04/product_listings/{product_listing_id}.json Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-04/product_listings/{product_listing_id}.json Create a product listing to publish a product to your app
DELETE	/admin/api/2020-04/product_listings/{product_listing_id}.json Delete a product listing to unpublish a product from your app
GET	/admin/api/2020-07/product_listings.json Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/product_listings/product_ids.json Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-07/product_listings/count.json Retrieve a count of products that are published to your app
GET	/admin/api/2020-07/product_listings/{product_listing_id}.json Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-07/product_listings/{product_listing_id}.json Create a product listing to publish a product to your app

DELETE /admin/api/2020-07/product_listings/{product_listing_id}.json
Delete a product listing to unpublish a product from your app

products

GET </admin/api/2020-01/collects.json>
Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/collects.json>
Adds a product to a custom collection.

GET /admin/api/2020-01/collects/{collect_id}.json
Retrieves a specific collect by its ID.

DELETE /admin/api/2020-01/collects/{collect_id}.json
Removes a product from a collection.

GET </admin/api/2020-01/collects/count.json>
Retrieves a count of collects.

GET </admin/api/2020-04/collects.json>
Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-04/collects.json>
Adds a product to a custom collection.

GET /admin/api/2020-04/collects/{collect_id}.json
Retrieves a specific collect by its ID.

DELETE /admin/api/2020-04/collects/{collect_id}.json
Removes a product from a collection.

GET </admin/api/2020-04/collects/count.json>
Retrieves a count of collects.

GET </admin/api/2020-07/collects.json>
Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-07/collects.json>
Adds a product to a custom collection.

GET /admin/api/2020-07/collects/{collect_id}.json
Retrieves a specific collect by its ID.

DELETE /admin/api/2020-07/collects/{collect_id}.json
Removes a product from a collection.

GET </admin/api/2020-07/collects/count.json>
Retrieves a count of collects.

GET </admin/api/2020-10/collects.json>
Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-10/collects.json>
Adds a product to a custom collection.

GET /admin/api/2020-10/collects/{collect_id}.json
Retrieves a specific collect by its ID.

DELETE /admin/api/2020-10/collects/{collect_id}.json
Removes a product from a collection.

GET </admin/api/2020-10/collects/count.json>
Retrieves a count of collects.

GET </admin/api/2021-01/collects.json>
Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2021-01/collects.json>
Adds a product to a custom collection.

GET /admin/api/2021-01/collects/{collect_id}.json
Retrieves a specific collect by its ID.

DELETE /admin/api/2021-01/collects/{collect_id}.json
Removes a product from a collection.

GET </admin/api/2021-01/collects/count.json>
Retrieves a count of collects.

GET </admin/api/unstable/collects.json>
Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/unstable/collects.json>
Adds a product to a custom collection.

GET /admin/api/unstable/collects/{collect_id}.json
Retrieves a specific collect by its ID.

DELETE /admin/api/unstable/collects/{collect_id}.json
Removes a product from a collection.

GET	/admin/api/unstable/collects/count.json	Retrieves a count of collects.
GET	/admin/api/2020-01/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-01/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-04/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-04/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-07/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-07/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-10/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-10/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2021-01/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2021-01/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/unstable/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/unstable/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-01/custom_collections.json	Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/custom_collections.json	Creates a custom collection
GET	/admin/api/2020-01/custom_collections/count.json	Retrieves a count of custom collections
GET	/admin/api/2020-01/custom_collections/{custom_collection_id}.json	Retrieves a single custom collection
PUT	/admin/api/2020-01/custom_collections/{custom_collection_id}.json	Updates an existing custom collection
DELETE	/admin/api/2020-01/custom_collections/{custom_collection_id}.json	Deletes a custom collection
GET	/admin/api/2020-04/custom_collections.json	Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/custom_collections.json	Creates a custom collection
GET	/admin/api/2020-04/custom_collections/count.json	Retrieves a count of custom collections
GET	/admin/api/2020-04/custom_collections/{custom_collection_id}.json	Retrieves a single custom collection
PUT	/admin/api/2020-04/custom_collections/{custom_collection_id}.json	Updates an existing custom collection
DELETE	/admin/api/2020-04/custom_collections/{custom_collection_id}.json	Deletes a custom collection
GET	/admin/api/2020-07/custom_collections.json	Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/custom_collections.json	Creates a custom collection
GET	/admin/api/2020-07/custom_collections/count.json	

GET	Retrieves a count of custom collections /admin/api/2020-07/custom_collections/{custom_collection_id}.json
PUT	Retrieves a single custom collection /admin/api/2020-07/custom_collections/{custom_collection_id}.json
DELETE	Updates an existing custom collection /admin/api/2020-07/custom_collections/{custom_collection_id}.json
GET	Deletes a custom collection /admin/api/2020-10/custom_collections.json
POST	Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2020-10/custom_collections.json
GET	Creates a custom collection /admin/api/2020-10/custom_collections/count.json
GET	Retrieves a count of custom collections /admin/api/2020-10/custom_collections/{custom_collection_id}.json
PUT	Retrieves a single custom collection /admin/api/2020-10/custom_collections/{custom_collection_id}.json
DELETE	Updates an existing custom collection /admin/api/2020-10/custom_collections/{custom_collection_id}.json
GET	Deletes a custom collection /admin/api/2021-01/custom_collections.json
POST	Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2021-01/custom_collections.json
GET	Creates a custom collection /admin/api/2021-01/custom_collections/count.json
GET	Retrieves a count of custom collections /admin/api/2021-01/custom_collections/{custom_collection_id}.json
PUT	Retrieves a single custom collection /admin/api/2021-01/custom_collections/{custom_collection_id}.json
DELETE	Updates an existing custom collection /admin/api/2021-01/custom_collections/{custom_collection_id}.json
GET	Deletes a custom collection /admin/api/unstable/custom_collections.json
POST	Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/unstable/custom_collections.json
GET	Creates a custom collection /admin/api/unstable/custom_collections/count.json
GET	Retrieves a count of custom collections /admin/api/unstable/custom_collections/{custom_collection_id}.json
PUT	Retrieves a single custom collection /admin/api/unstable/custom_collections/{custom_collection_id}.json
DELETE	Updates an existing custom collection /admin/api/unstable/custom_collections/{custom_collection_id}.json
GET	Deletes a custom collection /admin/api/2020-01/products.json
POST	Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2020-01/products.json
GET	Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag. /admin/api/2020-01/products/count.json
GET	Retrieves a count of products. /admin/api/2020-01/products/{product_id}.json
PUT	Retrieves a single product. /admin/api/2020-01/products/{product_id}.json
DELETE	Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag. /admin/api/2020-01/products/{product_id}.json
GET	Deletes a product. /admin/api/2020-04/products.json
POST	Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2020-04/products.json
GET	Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

GET	/admin/api/2020-04/products/count.json Retrieves a count of products.
GET	/admin/api/2020-04/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2020-04/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-04/products/{product_id}.json Deletes a product.
GET	/admin/api/2020-07/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-07/products/count.json Retrieves a count of products.
GET	/admin/api/2020-07/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2020-07/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-07/products/{product_id}.json Deletes a product.
GET	/admin/api/2020-10/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-10/products/count.json Retrieves a count of products.
GET	/admin/api/2020-10/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2020-10/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-10/products/{product_id}.json Deletes a product.
GET	/admin/api/2021-01/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2021-01/products/count.json Retrieves a count of products.
GET	/admin/api/2021-01/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2021-01/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2021-01/products/{product_id}.json Deletes a product.
GET	/admin/api/unstable/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/unstable/products/count.json Retrieves a count of products.
GET	/admin/api/unstable/products/{product_id}.json Retrieves a single product.

PUT [/admin/api/unstable/products/{product_id}.json](#)
Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties:
metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag.
metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

DELETE [/admin/api/unstable/products/{product_id}.json](#)
Deletes a product.

GET [/admin/api/2020-01/products/{product_id}/images.json](#)
Get all product images

POST [/admin/api/2020-01/products/{product_id}/images.json](#)
Create a new product image

GET [/admin/api/2020-01/products/{product_id}/images/count.json](#)
Get a count of all product images

GET [/admin/api/2020-01/products/{product_id}/images/{image_id}.json](#)
Get a single product image by id

PUT [/admin/api/2020-01/products/{product_id}/images/{image_id}.json](#)
Modify an existing product image

DELETE [/admin/api/2020-01/products/{product_id}/images/{image_id}.json](#)

GET [/admin/api/2020-04/products/{product_id}/images.json](#)
Get all product images

POST [/admin/api/2020-04/products/{product_id}/images.json](#)
Create a new product image

GET [/admin/api/2020-04/products/{product_id}/images/count.json](#)
Get a count of all product images

GET [/admin/api/2020-04/products/{product_id}/images/{image_id}.json](#)
Get a single product image by id

PUT [/admin/api/2020-04/products/{product_id}/images/{image_id}.json](#)
Modify an existing product image

DELETE [/admin/api/2020-04/products/{product_id}/images/{image_id}.json](#)

GET [/admin/api/2020-07/products/{product_id}/images.json](#)
Get all product images

POST [/admin/api/2020-07/products/{product_id}/images.json](#)
Create a new product image

GET [/admin/api/2020-07/products/{product_id}/images/count.json](#)
Get a count of all product images

GET [/admin/api/2020-07/products/{product_id}/images/{image_id}.json](#)
Get a single product image by id

PUT [/admin/api/2020-07/products/{product_id}/images/{image_id}.json](#)
Modify an existing product image

DELETE [/admin/api/2020-07/products/{product_id}/images/{image_id}.json](#)

GET [/admin/api/2020-10/products/{product_id}/images.json](#)
Get all product images

POST [/admin/api/2020-10/products/{product_id}/images.json](#)
Create a new product image

GET [/admin/api/2020-10/products/{product_id}/images/count.json](#)
Get a count of all product images

GET [/admin/api/2020-10/products/{product_id}/images/{image_id}.json](#)
Get a single product image by id

PUT [/admin/api/2020-10/products/{product_id}/images/{image_id}.json](#)
Modify an existing product image

DELETE [/admin/api/2020-10/products/{product_id}/images/{image_id}.json](#)

GET [/admin/api/2021-01/products/{product_id}/images.json](#)
Get all product images

POST [/admin/api/2021-01/products/{product_id}/images.json](#)
Create a new product image

GET [/admin/api/2021-01/products/{product_id}/images/count.json](#)
Get a count of all product images

GET [/admin/api/2021-01/products/{product_id}/images/{image_id}.json](#)
Get a single product image by id

PUT [/admin/api/2021-01/products/{product_id}/images/{image_id}.json](#)
Modify an existing product image

DELETE [/admin/api/2021-01/products/{product_id}/images/{image_id}.json](#)

GET [/admin/api/unstable/products/{product_id}/images.json](#)
Get all product images

POST [/admin/api/unstable/products/{product_id}/images.json](#)
Create a new product image

GET [/admin/api/unstable/products/{product_id}/images/count.json](#)
Get a count of all product images

GET /admin/api/unstable/products/{product_id}/images/{image_id}.json
Get a single product image by id

PUT /admin/api/unstable/products/{product_id}/images/{image_id}.json
Modify an existing product image

DELETE /admin/api/unstable/products/{product_id}/images/{image_id}.json

GET /admin/api/2020-01/smart_collections.json
Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/smart_collections.json
Creates a new smart collection using the specified rules.

GET /admin/api/2020-01/smart_collections/count.json
Retrieves a count of smart collections

GET /admin/api/2020-01/smart_collections/{smart_collection_id}.json
Retrieves a single smart collection

PUT /admin/api/2020-01/smart_collections/{smart_collection_id}.json
Updates an existing smart collection

DELETE /admin/api/2020-01/smart_collections/{smart_collection_id}.json
Removes a smart collection

PUT /admin/api/2020-01/smart_collections/{smart_collection_id}/order.json
Updates the ordering type of products in a smart collection

GET /admin/api/2020-04/smart_collections.json
Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/smart_collections.json
Creates a new smart collection using the specified rules.

GET /admin/api/2020-04/smart_collections/count.json
Retrieves a count of smart collections

GET /admin/api/2020-04/smart_collections/{smart_collection_id}.json
Retrieves a single smart collection

PUT /admin/api/2020-04/smart_collections/{smart_collection_id}.json
Updates an existing smart collection

DELETE /admin/api/2020-04/smart_collections/{smart_collection_id}.json
Removes a smart collection

PUT /admin/api/2020-04/smart_collections/{smart_collection_id}/order.json
Updates the ordering type of products in a smart collection

GET /admin/api/2020-07/smart_collections.json
Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/smart_collections.json
Creates a new smart collection using the specified rules.

GET /admin/api/2020-07/smart_collections/count.json
Retrieves a count of smart collections

GET /admin/api/2020-07/smart_collections/{smart_collection_id}.json
Retrieves a single smart collection

PUT /admin/api/2020-07/smart_collections/{smart_collection_id}.json
Updates an existing smart collection

DELETE /admin/api/2020-07/smart_collections/{smart_collection_id}.json
Removes a smart collection

PUT /admin/api/2020-07/smart_collections/{smart_collection_id}/order.json
Updates the ordering type of products in a smart collection

GET /admin/api/2020-10/smart_collections.json
Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/smart_collections.json
Creates a new smart collection using the specified rules.

GET /admin/api/2020-10/smart_collections/count.json
Retrieves a count of smart collections

GET /admin/api/2020-10/smart_collections/{smart_collection_id}.json
Retrieves a single smart collection

PUT /admin/api/2020-10/smart_collections/{smart_collection_id}.json
Updates an existing smart collection

DELETE /admin/api/2020-10/smart_collections/{smart_collection_id}.json
Removes a smart collection

PUT /admin/api/2020-10/smart_collections/{smart_collection_id}/order.json
Updates the ordering type of products in a smart collection

GET /admin/api/2021-01/smart_collections.json
Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST	/admin/api/2021-01/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/2021-01/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/2021-01/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection
GET	/admin/api/unstable/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/unstable/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/unstable/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/unstable/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/unstable/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/unstable/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection

products/collect

GET	/admin/api/2020-01/collects.json Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/collects.json Adds a product to a custom collection.
GET	/admin/api/2020-01/collects/{collect_id}.json Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-01/collects/{collect_id}.json Removes a product from a collection.
GET	/admin/api/2020-01/collects/count.json Retrieves a count of collects.
GET	/admin/api/2020-04/collects.json Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/collects.json Adds a product to a custom collection.
GET	/admin/api/2020-04/collects/{collect_id}.json Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-04/collects/{collect_id}.json Removes a product from a collection.
GET	/admin/api/2020-04/collects/count.json Retrieves a count of collects.
GET	/admin/api/2020-07/collects.json Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/collects.json Adds a product to a custom collection.
GET	/admin/api/2020-07/collects/{collect_id}.json Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-07/collects/{collect_id}.json Removes a product from a collection.
GET	/admin/api/2020-07/collects/count.json Retrieves a count of collects.
GET	/admin/api/2020-10/collects.json Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/collects.json Adds a product to a custom collection.
GET	/admin/api/2020-10/collects/{collect_id}.json

DELETE	/admin/api/2020-10/collects/{collect_id}.json	Retrieves a specific collect by its ID.
GET	/admin/api/2020-10/collects/count.json	Removes a product from a collection.
GET	/admin/api/2021-01/collects.json	Retrieves a count of collects.
GET	/admin/api/2021-01/collects/{collect_id}.json	Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/collects.json	Adds a product to a custom collection.
GET	/admin/api/2021-01/collects/{collect_id}.json	Retrieves a specific collect by its ID.
DELETE	/admin/api/2021-01/collects/{collect_id}.json	Removes a product from a collection.
GET	/admin/api/2021-01/collects/count.json	Retrieves a count of collects.
GET	/admin/api/unstable/collects.json	Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/collects.json	Adds a product to a custom collection.
GET	/admin/api/unstable/collects/{collect_id}.json	Retrieves a specific collect by its ID.
DELETE	/admin/api/unstable/collects/{collect_id}.json	Removes a product from a collection.
GET	/admin/api/unstable/collects/count.json	Retrieves a count of collects.

products/collection

GET	/admin/api/2020-01/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-01/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-04/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-04/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-07/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-07/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-10/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2020-10/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. The products returned are sorted by the collection's sort order.
GET	/admin/api/2021-01/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/2021-01/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. The products returned are sorted by the collection's sort order.
GET	/admin/api/unstable/collections/{collection_id}.json	Retrieves a single collection
GET	/admin/api/unstable/collections/{collection_id}/products.json	Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. The products returned are sorted by the collection's sort order.

products/customcollection

GET	/admin/api/2020-01/custom_collections.json	Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
---------------------	--	--

POST [/admin/api/2020-01/custom_collections.json](#)
Creates a custom collection

GET [/admin/api/2020-01/custom_collections/count.json](#)
Retrieves a count of custom collections

GET [/admin/api/2020-01/custom_collections/{custom_collection_id}.json](#)
Retrieves a single custom collection

PUT [/admin/api/2020-01/custom_collections/{custom_collection_id}.json](#)
Updates an existing custom collection

DELETE [/admin/api/2020-01/custom_collections/{custom_collection_id}.json](#)
Deletes a custom collection

GET [/admin/api/2020-04/custom_collections.json](#)
Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST [/admin/api/2020-04/custom_collections.json](#)
Creates a custom collection

GET [/admin/api/2020-04/custom_collections/count.json](#)
Retrieves a count of custom collections

GET [/admin/api/2020-04/custom_collections/{custom_collection_id}.json](#)
Retrieves a single custom collection

PUT [/admin/api/2020-04/custom_collections/{custom_collection_id}.json](#)
Updates an existing custom collection

DELETE [/admin/api/2020-04/custom_collections/{custom_collection_id}.json](#)
Deletes a custom collection

GET [/admin/api/2020-07/custom_collections.json](#)
Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST [/admin/api/2020-07/custom_collections.json](#)
Creates a custom collection

GET [/admin/api/2020-07/custom_collections/count.json](#)
Retrieves a count of custom collections

GET [/admin/api/2020-07/custom_collections/{custom_collection_id}.json](#)
Retrieves a single custom collection

PUT [/admin/api/2020-07/custom_collections/{custom_collection_id}.json](#)
Updates an existing custom collection

DELETE [/admin/api/2020-07/custom_collections/{custom_collection_id}.json](#)
Deletes a custom collection

GET [/admin/api/2020-10/custom_collections.json](#)
Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST [/admin/api/2020-10/custom_collections.json](#)
Creates a custom collection

GET [/admin/api/2020-10/custom_collections/count.json](#)
Retrieves a count of custom collections

GET [/admin/api/2020-10/custom_collections/{custom_collection_id}.json](#)
Retrieves a single custom collection

PUT [/admin/api/2020-10/custom_collections/{custom_collection_id}.json](#)
Updates an existing custom collection

DELETE [/admin/api/2020-10/custom_collections/{custom_collection_id}.json](#)
Deletes a custom collection

GET [/admin/api/2021-01/custom_collections.json](#)
Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST [/admin/api/2021-01/custom_collections.json](#)
Creates a custom collection

GET [/admin/api/2021-01/custom_collections/count.json](#)
Retrieves a count of custom collections

GET [/admin/api/2021-01/custom_collections/{custom_collection_id}.json](#)
Retrieves a single custom collection

PUT [/admin/api/2021-01/custom_collections/{custom_collection_id}.json](#)
Updates an existing custom collection

DELETE [/admin/api/2021-01/custom_collections/{custom_collection_id}.json](#)
Deletes a custom collection

GET [/admin/api/unstable/custom_collections.json](#)
Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST [/admin/api/unstable/custom_collections.json](#)
Creates a custom collection

GET [/admin/api/unstable/custom_collections/count.json](#)

GET	Retrieves a count of custom collections /admin/api/unstable/custom_collections/{custom_collection_id}.json
	Retrieves a single custom collection
PUT	/admin/api/unstable/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/unstable/custom_collections/{custom_collection_id}.json Deletes a custom collection

products/product

GET	/admin/api/2020-01/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-01/products/count.json Retrieves a count of products.
GET	/admin/api/2020-01/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2020-01/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-01/products/{product_id}.json Deletes a product.
GET	/admin/api/2020-04/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-04/products/count.json Retrieves a count of products.
GET	/admin/api/2020-04/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2020-04/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-04/products/{product_id}.json Deletes a product.
GET	/admin/api/2020-07/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-07/products/count.json Retrieves a count of products.
GET	/admin/api/2020-07/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2020-07/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-07/products/{product_id}.json Deletes a product.
GET	/admin/api/2020-10/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-10/products/count.json Retrieves a count of products.
GET	/admin/api/2020-10/products/{product_id}.json Retrieves a single product.

PUT	/admin/api/2020-10/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-10/products/{product_id}.json Deletes a product.
GET	/admin/api/2021-01/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2021-01/products/count.json Retrieves a count of products.
GET	/admin/api/2021-01/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2021-01/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2021-01/products/{product_id}.json Deletes a product.
GET	/admin/api/unstable/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/unstable/products/count.json Retrieves a count of products.
GET	/admin/api/unstable/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/unstable/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/unstable/products/{product_id}.json Deletes a product.

products/product-image

GET	/admin/api/2020-01/products/{product_id}/images.json Get all product images
POST	/admin/api/2020-01/products/{product_id}/images.json Create a new product image
GET	/admin/api/2020-01/products/{product_id}/images/count.json Get a count of all product images
GET	/admin/api/2020-01/products/{product_id}/images/{image_id}.json Get a single product image by id
PUT	/admin/api/2020-01/products/{product_id}/images/{image_id}.json Modify an existing product image
DELETE	/admin/api/2020-01/products/{product_id}/images/{image_id}.json
GET	/admin/api/2020-04/products/{product_id}/images.json Get all product images
POST	/admin/api/2020-04/products/{product_id}/images.json Create a new product image
GET	/admin/api/2020-04/products/{product_id}/images/count.json Get a count of all product images
GET	/admin/api/2020-04/products/{product_id}/images/{image_id}.json Get a single product image by id
PUT	/admin/api/2020-04/products/{product_id}/images/{image_id}.json Modify an existing product image
DELETE	/admin/api/2020-04/products/{product_id}/images/{image_id}.json
GET	/admin/api/2020-07/products/{product_id}/images.json Get all product images
POST	/admin/api/2020-07/products/{product_id}/images.json Create a new product image
GET	/admin/api/2020-07/products/{product_id}/images/count.json

GET	/admin/api/2020-07/products/{product_id}/images/{image_id}.json	Get a count of all product images
PUT	/admin/api/2020-07/products/{product_id}/images/{image_id}.json	Get a single product image by id
DELETE	/admin/api/2020-07/products/{product_id}/images/{image_id}.json	Modify an existing product image
GET	/admin/api/2020-10/products/{product_id}/images.json	Get all product images
POST	/admin/api/2020-10/products/{product_id}/images.json	Create a new product image
GET	/admin/api/2020-10/products/{product_id}/images/count.json	Get a count of all product images
GET	/admin/api/2020-10/products/{product_id}/images/{image_id}.json	Get a single product image by id
PUT	/admin/api/2020-10/products/{product_id}/images/{image_id}.json	Modify an existing product image
DELETE	/admin/api/2020-10/products/{product_id}/images/{image_id}.json	
GET	/admin/api/2021-01/products/{product_id}/images.json	Get all product images
POST	/admin/api/2021-01/products/{product_id}/images.json	Create a new product image
GET	/admin/api/2021-01/products/{product_id}/images/count.json	Get a count of all product images
GET	/admin/api/2021-01/products/{product_id}/images/{image_id}.json	Get a single product image by id
PUT	/admin/api/2021-01/products/{product_id}/images/{image_id}.json	Modify an existing product image
DELETE	/admin/api/2021-01/products/{product_id}/images/{image_id}.json	
GET	/admin/api/unstable/products/{product_id}/images.json	Get all product images
POST	/admin/api/unstable/products/{product_id}/images.json	Create a new product image
GET	/admin/api/unstable/products/{product_id}/images/count.json	Get a count of all product images
GET	/admin/api/unstable/products/{product_id}/images/{image_id}.json	Get a single product image by id
PUT	/admin/api/unstable/products/{product_id}/images/{image_id}.json	Modify an existing product image
DELETE	/admin/api/unstable/products/{product_id}/images/{image_id}.json	

products/smartcollection

GET	/admin/api/2020-01/smart_collections.json	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/smart_collections.json	Creates a new smart collection using the specified rules.
GET	/admin/api/2020-01/smart_collections/count.json	Retrieves a count of smart collections
GET	/admin/api/2020-01/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
PUT	/admin/api/2020-01/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
DELETE	/admin/api/2020-01/smart_collections/{smart_collection_id}.json	Removes a smart collection
PUT	/admin/api/2020-01/smart_collections/{smart_collection_id}/order.json	Updates the ordering type of products in a smart collection
GET	/admin/api/2020-04/smart_collections.json	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/smart_collections.json	Creates a new smart collection using the specified rules.
GET	/admin/api/2020-04/smart_collections/count.json	Retrieves a count of smart collections
GET	/admin/api/2020-04/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
PUT	/admin/api/2020-04/smart_collections/{smart_collection_id}.json	Updates an existing smart collection

DELETE	/admin/api/2020-04/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/2020-04/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection
GET	/admin/api/2020-07/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/2020-07/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/2020-07/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/2020-07/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/2020-07/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/2020-07/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection
GET	/admin/api/2020-10/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/2020-10/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/2020-10/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/2020-10/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/2020-10/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/2020-10/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection
GET	/admin/api/2021-01/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/2021-01/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/2021-01/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection
GET	/admin/api/unstable/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/unstable/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/unstable/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/unstable/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/unstable/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/unstable/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection

province

GET	/admin/api/2020-01/countries/{country_id}/provinces.json
---------------------	--

GET	Retrieves a list of provinces /admin/api/2020-01/countries/{country_id}/provinces/count.json
	Retrieves a count of provinces for a country
GET	/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json
	Retrieves a single province for a country
PUT	/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json
	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-04/countries/{country_id}/provinces.json
	Retrieves a list of provinces
GET	/admin/api/2020-04/countries/{country_id}/provinces/count.json
	Retrieves a count of provinces for a country
GET	/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json
	Retrieves a single province for a country
PUT	/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json
	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-07/countries/{country_id}/provinces.json
	Retrieves a list of provinces
GET	/admin/api/2020-07/countries/{country_id}/provinces/count.json
	Retrieves a count of provinces for a country
GET	/admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json
	Retrieves a single province for a country
PUT	/admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json
	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-10/countries/{country_id}/provinces.json
	Retrieves a list of provinces
GET	/admin/api/2020-10/countries/{country_id}/provinces/count.json
	Retrieves a count of provinces for a country
GET	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json
	Retrieves a single province for a country
PUT	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json
	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2021-01/countries/{country_id}/provinces.json
	Retrieves a list of provinces
GET	/admin/api/2021-01/countries/{country_id}/provinces/count.json
	Retrieves a count of provinces for a country
GET	/admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json
	Retrieves a single province for a country
PUT	/admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json
	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/unstable/countries/{country_id}/provinces.json
	Retrieves a list of provinces
GET	/admin/api/unstable/countries/{country_id}/provinces/count.json
	Retrieves a count of provinces for a country
GET	/admin/api/unstable/countries/{country_id}/provinces/{province_id}.json
	Retrieves a single province for a country
PUT	/admin/api/unstable/countries/{country_id}/provinces/{province_id}.json
	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

recurringapplicationcharge

GET	/admin/api/2020-01/recurring_application_charges.json
	Retrieves a list of recurring application charges
POST	/admin/api/2020-01/recurring_application_charges.json
	Creates a recurring application charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json
	Retrieves a single charge
DELETE	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json
	Cancels a recurring application charge
POST	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/activate.json
	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/customize.json
	Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-04/recurring_application_charges.json
	Retrieves a list of recurring application charges
POST	/admin/api/2020-04/recurring_application_charges.json
	Creates a recurring application charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json

	Retrieves a single charge
DELETE	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json
	Cancels a recurring application charge
POST	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/activate.json
	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/customize.json
	Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-07/recurring_application_charges.json
	Retrieves a list of recurring application charges
POST	/admin/api/2020-07/recurring_application_charges.json
	Creates a recurring application charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json
	Retrieves a single charge
DELETE	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json
	Cancels a recurring application charge
POST	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/activate.json
	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/customize.json
	Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-10/recurring_application_charges.json
	Retrieves a list of recurring application charges
POST	/admin/api/2020-10/recurring_application_charges.json
	Creates a recurring application charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json
	Retrieves a single charge
DELETE	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json
	Cancels a recurring application charge
POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/activate.json
	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/customize.json
	Updates the capped amount of an active recurring application charge
GET	/admin/api/2021-01/recurring_application_charges.json
	Retrieves a list of recurring application charges
POST	/admin/api/2021-01/recurring_application_charges.json
	Creates a recurring application charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json
	Retrieves a single charge
DELETE	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json
	Cancels a recurring application charge
PUT	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/customize.json
	Updates the capped amount of an active recurring application charge
GET	/admin/api/unstable/recurring_application_charges.json
	Retrieves a list of recurring application charges
POST	/admin/api/unstable/recurring_application_charges.json
	Creates a recurring application charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json
	Retrieves a single charge
DELETE	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json
	Cancels a recurring application charge
PUT	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/customize.json
	Updates the capped amount of an active recurring application charge

redirect

GET	/admin/api/2020-01/redirects.json
	Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/redirects.json
	Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-01/redirects/count.json
	Retrieves a count of URL redirects
GET	/admin/api/2020-01/redirects/{redirect_id}.json
	Retrieves a single redirect
PUT	/admin/api/2020-01/redirects/{redirect_id}.json
	Updates an existing redirect

DELETE	/admin/api/2020-01/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2020-04/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-04/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2020-04/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2020-04/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2020-04/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2020-07/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-07/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2020-07/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2020-07/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2020-07/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2020-10/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-10/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2020-10/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2020-10/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2020-10/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2021-01/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2021-01/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2021-01/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2021-01/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2021-01/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/unstable/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/unstable/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/unstable/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/unstable/redirects/{redirect_id}.json

[DELETE](#) [/admin/api/unstable/redirects/{redirect_id}.json](#)
Updates an existing redirect
Deletes a redirect

refund

[GET](#) [/admin/api/2020-01/orders/{order_id}/refunds.json](#)
Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-01/orders/{order_id}/refunds.json](#)
Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

[GET](#) [/admin/api/2020-01/orders/{order_id}/refunds/{refund_id}.json](#)
Retrieves a specific refund.

[POST](#) [/admin/api/2020-01/orders/{order_id}/refunds/calculate.json](#)
Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

[GET](#) [/admin/api/2020-04/orders/{order_id}/refunds.json](#)
Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-04/orders/{order_id}/refunds.json](#)
Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

[GET](#) [/admin/api/2020-04/orders/{order_id}/refunds/{refund_id}.json](#)
Retrieves a specific refund.

[POST](#) [/admin/api/2020-04/orders/{order_id}/refunds/calculate.json](#)
Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

[GET](#) [/admin/api/2020-07/orders/{order_id}/refunds.json](#)
Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-07/orders/{order_id}/refunds.json](#)
Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

[GET](#) [/admin/api/2020-07/orders/{order_id}/refunds/{refund_id}.json](#)
Retrieves a specific refund.

[POST](#) [/admin/api/2020-07/orders/{order_id}/refunds/calculate.json](#)
Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

[GET](#) [/admin/api/2020-10/orders/{order_id}/refunds.json](#)
Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-10/orders/{order_id}/refunds.json](#)
Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

[GET](#) [/admin/api/2020-10/orders/{order_id}/refunds/{refund_id}.json](#)
Retrieves a specific refund.

[POST](#) [/admin/api/2020-10/orders/{order_id}/refunds/calculate.json](#)
Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

[GET](#) [/admin/api/2021-01/orders/{order_id}/refunds.json](#)
Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST	/admin/api/2021-01/orders/{order_id}/refunds.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2021-01/orders/{order_id}/refunds/{refund_id}.json	Retrieves a specific refund.
POST	/admin/api/2021-01/orders/{order_id}/refunds/calculate.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind" : "refund" for the refund to be accepted.
GET	/admin/api/unstable/orders/{order_id}/refunds.json	Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/orders/{order_id}/refunds.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/unstable/orders/{order_id}/refunds/{refund_id}.json	Retrieves a specific refund.
POST	/admin/api/unstable/orders/{order_id}/refunds/calculate.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind" : "refund" for the refund to be accepted.

report

GET	/admin/api/2020-01/reports.json	Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/reports.json	Creates a new report
GET	/admin/api/2020-01/reports/{report_id}.json	Retrieves a single report created by your app
PUT	/admin/api/2020-01/reports/{report_id}.json	Updates a report
DELETE	/admin/api/2020-01/reports/{report_id}.json	Deletes a report
GET	/admin/api/2020-04/reports.json	Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/reports.json	Creates a new report
GET	/admin/api/2020-04/reports/{report_id}.json	Retrieves a single report created by your app
PUT	/admin/api/2020-04/reports/{report_id}.json	Updates a report
DELETE	/admin/api/2020-04/reports/{report_id}.json	Deletes a report
GET	/admin/api/2020-07/reports.json	Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/reports.json	Creates a new report
GET	/admin/api/2020-07/reports/{report_id}.json	Retrieves a single report created by your app
PUT	/admin/api/2020-07/reports/{report_id}.json	Updates a report
DELETE	/admin/api/2020-07/reports/{report_id}.json	Deletes a report
GET	/admin/api/2020-10/reports.json	Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/reports.json	Creates a new report
GET	/admin/api/2020-10/reports/{report_id}.json	

PUT	Retrieves a single report created by your app /admin/api/2020-10/reports/{report_id}.json
	Updates a report
DELETE	/admin/api/2020-10/reports/{report_id}.json Deletes a report
GET	/admin/api/2021-01/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/reports.json Creates a new report
GET	/admin/api/2021-01/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2021-01/reports/{report_id}.json Updates a report
DELETE	/admin/api/2021-01/reports/{report_id}.json Deletes a report
GET	/admin/api/unstable/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/reports.json Creates a new report
GET	/admin/api/unstable/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/unstable/reports/{report_id}.json Updates a report
DELETE	/admin/api/unstable/reports/{report_id}.json Deletes a report

sales-channels

POST	/admin/api/2020-01/checkouts.json Creates a checkout
POST	/admin/api/2020-04/checkouts.json Creates a checkout
POST	/admin/api/2020-07/checkouts.json Creates a checkout
POST	/admin/api/2020-10/checkouts.json Creates a checkout
POST	/admin/api/2021-01/checkouts.json Creates a checkout
POST	/admin/api/unstable/checkouts.json Creates a checkout
POST	/admin/api/2020-01/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-01/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-01/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-01/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-04/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-04/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-04/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-04/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-07/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-07/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-07/checkouts/{token}.json Modifies an existing checkout

GET	/admin/api/2020-07/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-10/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-10/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-10/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-10/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2021-01/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2021-01/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2021-01/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2021-01/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/unstable/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/unstable/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/unstable/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/unstable/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
GET	/admin/api/2020-01/collection_listings.json Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/collection_listings/{collection_listing_id}/product_ids.json Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/collection_listings/{collection_listing_id}.json Retrieve a specific collection listing that is published to your app
PUT	/admin/api/2020-01/collection_listings/{collection_listing_id}.json Create a collection listing to publish a collection to your app
DELETE	/admin/api/2020-01/collection_listings/{collection_listing_id}.json Delete a collection listing to unpublish a collection from your app
GET	/admin/api/2020-04/collection_listings.json Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/collection_listings/{collection_listing_id}/product_ids.json Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/collection_listings/{collection_listing_id}.json Retrieve a specific collection listing that is published to your app
PUT	/admin/api/2020-04/collection_listings/{collection_listing_id}.json Create a collection listing to publish a collection to your app
DELETE	/admin/api/2020-04/collection_listings/{collection_listing_id}.json Delete a collection listing to unpublish a collection from your app
GET	/admin/api/2020-07/collection_listings.json Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-07/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

PUT /admin/api/2020-07/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

DELETE /admin/api/2020-07/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

GET /admin/api/2020-10/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-10/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-10/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

PUT /admin/api/2020-10/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

DELETE /admin/api/2020-10/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

GET /admin/api/2021-01/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2021-01/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2021-01/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

PUT /admin/api/2021-01/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

DELETE /admin/api/2021-01/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

GET /admin/api/unstable/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/unstable/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/unstable/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

PUT /admin/api/unstable/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

DELETE /admin/api/unstable/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

GET </admin/api/2020-01/checkouts/{token}/payments.json>

Retrieves a list of payments on a particular checkout

POST </admin/api/2020-01/checkouts/{token}/payments.json>

Creates a payment on a checkout using the session ID returned by the card vault

GET /admin/api/2020-01/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

GET </admin/api/2020-01/checkouts/{token}/payments/count.json>

Counts the number of payments attempted on a checkout

GET </admin/api/2020-04/checkouts/{token}/payments.json>

Retrieves a list of payments on a particular checkout

POST </admin/api/2020-04/checkouts/{token}/payments.json>

Creates a payment on a checkout using the session ID returned by the card vault

GET /admin/api/2020-04/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

GET </admin/api/2020-04/checkouts/{token}/payments/count.json>

Counts the number of payments attempted on a checkout

GET </admin/api/2020-07/checkouts/{token}/payments.json>

Retrieves a list of payments on a particular checkout

POST </admin/api/2020-07/checkouts/{token}/payments.json>

GET	Creates a payment on a checkout using the session ID returned by the card vault /admin/api/2020-07/checkouts/{token}/payments/{payment_id}.json
	Retrieves the payment information for an existing payment
GET	/admin/api/2020-07/checkouts/{token}/payments/count.json
	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-10/checkouts/{token}/payments.json
	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-10/checkouts/{token}/payments.json
	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-10/checkouts/{token}/payments/{payment_id}.json
	Retrieves the payment information for an existing payment
GET	/admin/api/2020-10/checkouts/{token}/payments/count.json
	Counts the number of payments attempted on a checkout
GET	/admin/api/2021-01/checkouts/{token}/payments.json
	Retrieves a list of payments on a particular checkout
POST	/admin/api/2021-01/checkouts/{token}/payments.json
	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2021-01/checkouts/{token}/payments/{payment_id}.json
	Retrieves the payment information for an existing payment
GET	/admin/api/2021-01/checkouts/{token}/payments/count.json
	Counts the number of payments attempted on a checkout
GET	/admin/api/unstable/checkouts/{token}/payments.json
	Retrieves a list of payments on a particular checkout
POST	/admin/api/unstable/checkouts/{token}/payments.json
	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/unstable/checkouts/{token}/payments/{payment_id}.json
	Retrieves the payment information for an existing payment
GET	/admin/api/unstable/checkouts/{token}/payments/count.json
	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-01/product_listings.json
	Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/product_listings/product_ids.json
	Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-01/product_listings/count.json
	Retrieve a count of products that are published to your app
GET	/admin/api/2020-01/product_listings/{product_listing_id}.json
	Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-01/product_listings/{product_listing_id}.json
	Create a product listing to publish a product to your app
DELETE	/admin/api/2020-01/product_listings/{product_listing_id}.json
	Delete a product listing to unpublish a product from your app
GET	/admin/api/2020-04/product_listings.json
	Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/product_listings/product_ids.json
	Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-04/product_listings/count.json
	Retrieve a count of products that are published to your app
GET	/admin/api/2020-04/product_listings/{product_listing_id}.json
	Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-04/product_listings/{product_listing_id}.json
	Create a product listing to publish a product to your app
DELETE	/admin/api/2020-04/product_listings/{product_listing_id}.json
	Delete a product listing to unpublish a product from your app
GET	/admin/api/2020-07/product_listings.json
	Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/product_listings/product_ids.json
	Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-07/product_listings/count.json
	Retrieve a count of products that are published to your app
GET	/admin/api/2020-07/product_listings/{product_listing_id}.json
	Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-07/product_listings/{product_listing_id}.json

Create a product listing to publish a product to your app
[DELETE](#) [/admin/api/2020-07/product_listings/{product_listing_id}.json](#)
Delete a product listing to unpublish a product from your app

sales-channels/checkout

[POST](#) [/admin/api/2020-01/checkout.json](#)
Creates a checkout

[POST](#) [/admin/api/2020-04/checkout.json](#)
Creates a checkout

[POST](#) [/admin/api/2020-07/checkout.json](#)
Creates a checkout

[POST](#) [/admin/api/2020-10/checkout.json](#)
Creates a checkout

[POST](#) [/admin/api/2021-01/checkout.json](#)
Creates a checkout

[POST](#) [/admin/api/unstable/checkout.json](#)
Creates a checkout

[POST](#) [/admin/api/2020-01/checkout/{token}/complete.json](#)
Completes a checkout

[GET](#) [/admin/api/2020-01/checkout/{token}.json](#)
Retrieves a checkout

[PUT](#) [/admin/api/2020-01/checkout/{token}.json](#)
Modifies an existing checkout

[GET](#) [/admin/api/2020-01/checkout/{token}/shipping_rates.json](#)
Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

[POST](#) [/admin/api/2020-04/checkout/{token}/complete.json](#)
Completes a checkout

[GET](#) [/admin/api/2020-04/checkout/{token}.json](#)
Retrieves a checkout

[PUT](#) [/admin/api/2020-04/checkout/{token}.json](#)
Modifies an existing checkout

[GET](#) [/admin/api/2020-04/checkout/{token}/shipping_rates.json](#)
Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

[POST](#) [/admin/api/2020-07/checkout/{token}/complete.json](#)
Completes a checkout

[GET](#) [/admin/api/2020-07/checkout/{token}.json](#)
Retrieves a checkout

[PUT](#) [/admin/api/2020-07/checkout/{token}.json](#)
Modifies an existing checkout

[GET](#) [/admin/api/2020-07/checkout/{token}/shipping_rates.json](#)
Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

[POST](#) [/admin/api/2020-10/checkout/{token}/complete.json](#)
Completes a checkout

[GET](#) [/admin/api/2020-10/checkout/{token}.json](#)
Retrieves a checkout

[PUT](#) [/admin/api/2020-10/checkout/{token}.json](#)
Modifies an existing checkout

[GET](#) [/admin/api/2020-10/checkout/{token}/shipping_rates.json](#)
Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

[POST](#) [/admin/api/2021-01/checkout/{token}/complete.json](#)
Completes a checkout

[GET](#) [/admin/api/2021-01/checkout/{token}.json](#)
Retrieves a checkout

[PUT](#) [/admin/api/2021-01/checkout/{token}.json](#)
Modifies an existing checkout

[GET](#) [/admin/api/2021-01/checkout/{token}/shipping_rates.json](#)
Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to

update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

POST </admin/api/unstable/checkout/{token}/complete.json>

Completes a checkout

GET </admin/api/unstable/checkout/{token}.json>

Retrieves a checkout

PUT </admin/api/unstable/checkout/{token}.json>

Modifies an existing checkout

GET /admin/api/unstable/checkout/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

sales-channels/collectionlisting

GET /admin/api/2020-01/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-01/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-01/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

PUT /admin/api/2020-01/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

DELETE /admin/api/2020-01/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

GET /admin/api/2020-04/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-04/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-04/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

PUT /admin/api/2020-04/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

DELETE /admin/api/2020-04/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

GET /admin/api/2020-07/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-07/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-07/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

PUT /admin/api/2020-07/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

DELETE /admin/api/2020-07/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

GET /admin/api/2020-10/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-10/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-10/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

PUT /admin/api/2020-10/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

DELETE /admin/api/2020-10/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

GET /admin/api/2021-01/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2021-01/collection_listings/{collection_listing_id}/product_ids.json](#)

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2021-01/collection_listings/{collection_listing_id}.json](#)

Retrieve a specific collection listing that is published to your app

[PUT](#) [/admin/api/2021-01/collection_listings/{collection_listing_id}.json](#)

Create a collection listing to publish a collection to your app

[DELETE](#) [/admin/api/2021-01/collection_listings/{collection_listing_id}.json](#)

Delete a collection listing to unpublish a collection from your app

[GET](#) [/admin/api/unstable/collection_listings.json](#)

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/unstable/collection_listings/{collection_listing_id}/product_ids.json](#)

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/unstable/collection_listings/{collection_listing_id}.json](#)

Retrieve a specific collection listing that is published to your app

[PUT](#) [/admin/api/unstable/collection_listings/{collection_listing_id}.json](#)

Create a collection listing to publish a collection to your app

[DELETE](#) [/admin/api/unstable/collection_listings/{collection_listing_id}.json](#)

Delete a collection listing to unpublish a collection from your app

sales-channels/payment

[GET](#) [/admin/api/2020-01/checkouts/{token}/payments.json](#)

Retrieves a list of payments on a particular checkout

[POST](#) [/admin/api/2020-01/checkouts/{token}/payments.json](#)

Creates a payment on a checkout using the session ID returned by the card vault

[GET](#) [/admin/api/2020-01/checkouts/{token}/payments/{payment_id}.json](#)

Retrieves the payment information for an existing payment

[GET](#) [/admin/api/2020-01/checkouts/{token}/payments/count.json](#)

Counts the number of payments attempted on a checkout

[GET](#) [/admin/api/2020-04/checkouts/{token}/payments.json](#)

Retrieves a list of payments on a particular checkout

[POST](#) [/admin/api/2020-04/checkouts/{token}/payments.json](#)

Creates a payment on a checkout using the session ID returned by the card vault

[GET](#) [/admin/api/2020-04/checkouts/{token}/payments/{payment_id}.json](#)

Retrieves the payment information for an existing payment

[GET](#) [/admin/api/2020-04/checkouts/{token}/payments/count.json](#)

Counts the number of payments attempted on a checkout

[GET](#) [/admin/api/2020-07/checkouts/{token}/payments.json](#)

Retrieves a list of payments on a particular checkout

[POST](#) [/admin/api/2020-07/checkouts/{token}/payments.json](#)

Creates a payment on a checkout using the session ID returned by the card vault

[GET](#) [/admin/api/2020-07/checkouts/{token}/payments/{payment_id}.json](#)

Retrieves the payment information for an existing payment

[GET](#) [/admin/api/2020-07/checkouts/{token}/payments/count.json](#)

Counts the number of payments attempted on a checkout

[GET](#) [/admin/api/2020-10/checkouts/{token}/payments.json](#)

Retrieves a list of payments on a particular checkout

[POST](#) [/admin/api/2020-10/checkouts/{token}/payments.json](#)

Creates a payment on a checkout using the session ID returned by the card vault

[GET](#) [/admin/api/2020-10/checkouts/{token}/payments/{payment_id}.json](#)

Retrieves the payment information for an existing payment

[GET](#) [/admin/api/2020-10/checkouts/{token}/payments/count.json](#)

Counts the number of payments attempted on a checkout

[GET](#) [/admin/api/2021-01/checkouts/{token}/payments.json](#)

Retrieves a list of payments on a particular checkout

[POST](#) [/admin/api/2021-01/checkouts/{token}/payments.json](#)

Creates a payment on a checkout using the session ID returned by the card vault

[GET](#) [/admin/api/2021-01/checkouts/{token}/payments/{payment_id}.json](#)

Retrieves the payment information for an existing payment

[GET](#) [/admin/api/2021-01/checkouts/{token}/payments/count.json](#)

Counts the number of payments attempted on a checkout

GET	/admin/api/unstable/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/unstable/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/unstable/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/unstable/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout

sales-channels/productlisting

GET	/admin/api/2020-01/product_listings.json	Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/product_listings/product_ids.json	Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-01/product_listings/count.json	Retrieve a count of products that are published to your app
GET	/admin/api/2020-01/product_listings/{product_listing_id}.json	Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-01/product_listings/{product_listing_id}.json	Create a product listing to publish a product to your app
DELETE	/admin/api/2020-01/product_listings/{product_listing_id}.json	Delete a product listing to unpublish a product from your app
GET	/admin/api/2020-04/product_listings.json	Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/product_listings/product_ids.json	Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-04/product_listings/count.json	Retrieve a count of products that are published to your app
GET	/admin/api/2020-04/product_listings/{product_listing_id}.json	Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-04/product_listings/{product_listing_id}.json	Create a product listing to publish a product to your app
DELETE	/admin/api/2020-04/product_listings/{product_listing_id}.json	Delete a product listing to unpublish a product from your app
GET	/admin/api/2020-07/product_listings.json	Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/product_listings/product_ids.json	Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-07/product_listings/count.json	Retrieve a count of products that are published to your app
GET	/admin/api/2020-07/product_listings/{product_listing_id}.json	Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-07/product_listings/{product_listing_id}.json	Create a product listing to publish a product to your app
DELETE	/admin/api/2020-07/product_listings/{product_listing_id}.json	Delete a product listing to unpublish a product from your app

scripttag

GET	/admin/api/2020-01/script_tags.json	Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/script_tags.json	Creates a new script tag
GET	/admin/api/2020-01/script_tags/count.json	Retrieves a count of all script tags
GET	/admin/api/2020-01/script_tags/{script_tag_id}.json	Retrieves a single script tag
PUT	/admin/api/2020-01/script_tags/{script_tag_id}.json	Updates a script tag
DELETE	/admin/api/2020-01/script_tags/{script_tag_id}.json	Deletes a script tag
GET	/admin/api/2020-04/script_tags.json	

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/script_tags.json

Creates a new script tag

GET /admin/api/2020-04/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-04/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-04/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-04/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2020-07/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/script_tags.json

Creates a new script tag

GET /admin/api/2020-07/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-07/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-07/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-07/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2020-10/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/script_tags.json

Creates a new script tag

GET /admin/api/2020-10/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-10/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-10/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-10/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2021-01/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/script_tags.json

Creates a new script tag

GET /admin/api/2021-01/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2021-01/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2021-01/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2021-01/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/unstable/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/script_tags.json

Creates a new script tag

GET /admin/api/unstable/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/unstable/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/unstable/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/unstable/script_tags/{script_tag_id}.json

Deletes a script tag

shipping-and-fulfillment

GET /admin/api/2020-01/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.

[illegible]

POST	Retrieves a list of carrier services /admin/api/2020-07/carrier_services.json
GET	Creates a carrier service /admin/api/2020-07/carrier_services/{carrier_service_id}.json
PUT	Retrieves a single carrier service by its ID /admin/api/2020-07/carrier_services/{carrier_service_id}.json
DELETE	Updates a carrier service. Only the app that creates a carrier service can update it. /admin/api/2020-07/carrier_services/{carrier_service_id}.json
GET	Deletes a carrier service /admin/api/2020-10/carrier_services.json
POST	Retrieves a list of carrier services /admin/api/2020-10/carrier_services.json
GET	Creates a carrier service /admin/api/2020-10/carrier_services/{carrier_service_id}.json
PUT	Retrieves a single carrier service by its ID /admin/api/2020-10/carrier_services/{carrier_service_id}.json
DELETE	Updates a carrier service. Only the app that creates a carrier service can update it. /admin/api/2020-10/carrier_services/{carrier_service_id}.json
GET	Deletes a carrier service /admin/api/2021-01/carrier_services.json
POST	Retrieves a list of carrier services /admin/api/2021-01/carrier_services.json
GET	Creates a carrier service /admin/api/2021-01/carrier_services/{carrier_service_id}.json
PUT	Retrieves a single carrier service by its ID /admin/api/2021-01/carrier_services/{carrier_service_id}.json
DELETE	Updates a carrier service. Only the app that creates a carrier service can update it. /admin/api/2021-01/carrier_services/{carrier_service_id}.json
GET	Deletes a carrier service /admin/api/unstable/carrier_services.json
POST	Retrieves a list of carrier services /admin/api/unstable/carrier_services.json
GET	Creates a carrier service /admin/api/unstable/carrier_services/{carrier_service_id}.json
PUT	Retrieves a single carrier service by its ID /admin/api/unstable/carrier_services/{carrier_service_id}.json
DELETE	Updates a carrier service. Only the app that creates a carrier service can update it. /admin/api/unstable/carrier_services/{carrier_service_id}.json
GET	Deletes a carrier service /admin/api/2020-01/orders/{order_id}/fulfillments.json
POST	Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2020-01/orders/{order_id}/fulfillments.json
POST	Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment. /admin/api/2020-01/orders/{order_id}/fulfillments.json
GET	Retrieves fulfillments associated with a fulfillment order. /admin/api/2020-01/orders/{order_id}/fulfillments/count.json
GET	Retrieves a count of fulfillments associated with a specific order /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json
PUT	Retrieve a specific fulfillment /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json
POST	Update information associated with a fulfillment /admin/api/2020-01/fulfillments.json
POST	Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location. /admin/api/2020-01/fulfillments/{fulfillment_id}/update_tracking.json
POST	Updates the tracking information for a fulfillment. /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

POST	Mark a fulfillment as complete /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-01/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-04/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-04/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-04/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-04/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-07/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-07/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-07/fulfillments/{fulfillment_id}/update_tracking.json

POST	Updates the tracking information for a fulfillment. /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-07/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-10/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2021-01/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2021-01/fulfillments.json

	Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/unstable/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/unstable/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/unstable/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/unstable/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/unstable/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

	Retrieves a specific fulfillment event
DELETE	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Deletes a fulfillment event
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Creates a fulfillment event
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Retrieves a specific fulfillment event
DELETE	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Deletes a fulfillment event
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Creates a fulfillment event
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Retrieves a specific fulfillment event
DELETE	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Deletes a fulfillment event
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json
	Creates a fulfillment event
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Retrieves a specific fulfillment event
DELETE	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json
	Deletes a fulfillment event
GET	/admin/api/2020-01/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/close.json
	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/move.json
	Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-04/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/close.json
	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/move.json
	Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-07/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/close.json
	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/move.json
	Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-10/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.

GET /admin/api/2021-01/orders/{order_id}/fulfillment_orders.json

Retrieves a list of fulfillment orders for a specific order.

GET /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}.json

Retrieves a specific fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancel.json

Marks a fulfillment order as cancelled.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/open.json

Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/reschedule.json

Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.

GET /admin/api/unstable/orders/{order_id}/fulfillment_orders.json

Retrieves a list of fulfillment orders for a specific order.

GET /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}.json

Retrieves a specific fulfillment order.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancel.json

Marks a fulfillment order as cancelled.

POST /admin/api/unstable/fulfillment_orders/release_hold.json

Releases the fulfillment order holds for a specific order. Fulfillment orders are created with an ON_HOLD status if the channel that created the order has a fulfillment hold policy.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/open.json

Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/reschedule.json

Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json](#)
Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json](#)
Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json](#)
Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json](#)
Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

GET [/fetch_tracking_numbers](#)
Get tracking numbers for orders

GET [/fetch_stock](#)
Get inventory levels

GET [/admin/api/2020-01/fulfillment_services.json](#)

POST [/admin/api/2020-01/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json](#)

DELETE [/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json](#)

GET [/admin/api/2020-04/fulfillment_services.json](#)

POST [/admin/api/2020-04/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json](#)

DELETE [/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json](#)

GET [/admin/api/2020-07/fulfillment_services.json](#)

POST [/admin/api/2020-07/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json](#)

DELETE [/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json](#)

GET [/admin/api/2020-10/fulfillment_services.json](#)

POST [/admin/api/2020-10/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)

DELETE [/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)

GET [/admin/api/2021-01/fulfillment_services.json](#)

POST [/admin/api/2021-01/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)

DELETE [/admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)

GET [/admin/api/unstable/fulfillment_services.json](#)

POST [/admin/api/unstable/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET [/admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)

PUT [/admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)

DELETE [/admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)

GET [/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)
Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

<u>GET</u>	<u>/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json</u>	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
<u>GET</u>	<u>/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json</u>	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
<u>GET</u>	<u>/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json</u>	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
<u>GET</u>	<u>/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json</u>	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
<u>GET</u>	<u>/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json</u>	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

shipping-and-fulfillment/assignedfulfillmentorder

<u>GET</u>	<u>/admin/api/2020-01/assigned_fulfillment_orders.json</u>	Retrieves a list of fulfillment orders on a shop for a specific app.
<u>GET</u>	<u>/admin/api/2020-04/assigned_fulfillment_orders.json</u>	Retrieves a list of fulfillment orders on a shop for a specific app.
<u>GET</u>	<u>/admin/api/2020-07/assigned_fulfillment_orders.json</u>	Retrieves a list of fulfillment orders on a shop for a specific app.
<u>GET</u>	<u>/admin/api/2020-10/assigned_fulfillment_orders.json</u>	Retrieves a list of fulfillment orders on a shop for a specific app.
<u>GET</u>	<u>/admin/api/2021-01/assigned_fulfillment_orders.json</u>	Retrieves a list of fulfillment orders on a shop for a specific app.
<u>GET</u>	<u>/admin/api/unstable/assigned_fulfillment_orders.json</u>	Retrieves a list of fulfillment orders on a shop for a specific app.

shipping-and-fulfillment/cancellationrequest

[illegible]

shipping-and-fulfillment/carrierservice

GET	/admin/api/2020-01/carrier_services.json	Retrieves a list of carrier services
POST	/admin/api/2020-01/carrier_services.json	Creates a carrier service
GET	/admin/api/2020-01/carrier_services/{carrier_service_id}.json	Retrieves a single carrier service by its ID
PUT	/admin/api/2020-01/carrier_services/{carrier_service_id}.json	Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/2020-01/carrier_services/{carrier_service_id}.json	Deletes a carrier service
GET	/admin/api/2020-04/carrier_services.json	Retrieves a list of carrier services
POST	/admin/api/2020-04/carrier_services.json	Creates a carrier service
GET	/admin/api/2020-04/carrier_services/{carrier_service_id}.json	Retrieves a single carrier service by its ID
PUT	/admin/api/2020-04/carrier_services/{carrier_service_id}.json	Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/2020-04/carrier_services/{carrier_service_id}.json	Deletes a carrier service
GET	/admin/api/2020-07/carrier_services.json	Retrieves a list of carrier services
POST	/admin/api/2020-07/carrier_services.json	Creates a carrier service
GET	/admin/api/2020-07/carrier_services/{carrier_service_id}.json	Retrieves a single carrier service by its ID
PUT	/admin/api/2020-07/carrier_services/{carrier_service_id}.json	Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/2020-07/carrier_services/{carrier_service_id}.json	Deletes a carrier service
GET	/admin/api/2020-10/carrier_services.json	Retrieves a list of carrier services
POST	/admin/api/2020-10/carrier_services.json	Creates a carrier service
GET	/admin/api/2020-10/carrier_services/{carrier_service_id}.json	Retrieves a single carrier service by its ID
PUT	/admin/api/2020-10/carrier_services/{carrier_service_id}.json	Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/2020-10/carrier_services/{carrier_service_id}.json	Deletes a carrier service
GET	/admin/api/2021-01/carrier_services.json	Retrieves a list of carrier services
POST	/admin/api/2021-01/carrier_services.json	Creates a carrier service
GET	/admin/api/2021-01/carrier_services/{carrier_service_id}.json	Retrieves a single carrier service by its ID
PUT	/admin/api/2021-01/carrier_services/{carrier_service_id}.json	Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/2021-01/carrier_services/{carrier_service_id}.json	Deletes a carrier service
GET	/admin/api/unstable/carrier_services.json	Retrieves a list of carrier services
POST	/admin/api/unstable/carrier_services.json	Creates a carrier service
GET	/admin/api/unstable/carrier_services/{carrier_service_id}.json	Retrieves a single carrier service by its ID
PUT	/admin/api/unstable/carrier_services/{carrier_service_id}.json	Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/unstable/carrier_services/{carrier_service_id}.json	Deletes a carrier service

shipping-and-fulfillment/fulfillment

GET	/admin/api/2020-01/orders/{order_id}/fulfillments.json	Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
-----	---	---

POST	/admin/api/2020-01/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-01/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-01/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-01/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-04/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-04/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-04/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-04/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-07/orders/{order_id}/fulfillments.json

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/orders/{order_id}/fulfillments.json

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

GET /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

GET /admin/api/2020-07/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

GET /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

PUT /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

POST </admin/api/2020-07/fulfillments.json>

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

POST /admin/api/2020-07/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

POST /admin/api/2020-07/fulfillments/{fulfillment_id}/cancel.json

Cancels a fulfillment.

GET /admin/api/2020-10/orders/{order_id}/fulfillments.json

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/orders/{order_id}/fulfillments.json

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

GET /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

GET /admin/api/2020-10/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

GET /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

PUT /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

POST </admin/api/2020-10/fulfillments.json>

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

POST /admin/api/2020-10/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

POST /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

POST /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

POST /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

POST /admin/api/2020-10/fulfillments/{fulfillment_id}/cancel.json

GET	/admin/api/2021-01/orders/{order_id}/fulfillments.json	Cancels a fulfillment.
		Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments.json	Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json	Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/count.json	Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json	Retrieve a specific fulfillment
PUT	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json	Update information associated with a fulfillment
POST	/admin/api/2021-01/fulfillments.json	Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/update_tracking.json	Updates the tracking information for a fulfillment.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json	Mark a fulfillment as complete
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json	Mark a fulfillment as open
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json	Cancel a fulfillment for a specific order ID
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/cancel.json	Cancels a fulfillment.
GET	/admin/api/unstable/orders/{order_id}/fulfillments.json	Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/orders/{order_id}/fulfillments.json	Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillments.json	Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/unstable/orders/{order_id}/fulfillments/count.json	Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json	Retrieve a specific fulfillment
PUT	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json	Update information associated with a fulfillment
POST	/admin/api/unstable/fulfillments.json	Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/unstable/fulfillments/{fulfillment_id}/update_tracking.json	Updates the tracking information for a fulfillment.
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json	Mark a fulfillment as complete
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/open.json	Mark a fulfillment as open
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json	

POST [/admin/api/unstable/fulfillments/{fulfillment_id}/cancel.json](#)
Cancel a fulfillment for a specific order ID
Cancels a fulfillment.

shipping-and-fulfillment/fulfillmentevent

GET [/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Retrieves a list of fulfillment events for a specific fulfillment

POST [/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Creates a fulfillment event

GET [/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Retrieves a specific fulfillment event

DELETE [/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Deletes a fulfillment event

GET [/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Retrieves a list of fulfillment events for a specific fulfillment

POST [/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Creates a fulfillment event

GET [/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Retrieves a specific fulfillment event

DELETE [/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Deletes a fulfillment event

GET [/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Retrieves a list of fulfillment events for a specific fulfillment

POST [/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Creates a fulfillment event

GET [/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Retrieves a specific fulfillment event

DELETE [/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Deletes a fulfillment event

GET [/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Retrieves a list of fulfillment events for a specific fulfillment

POST [/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Creates a fulfillment event

GET [/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Retrieves a specific fulfillment event

DELETE [/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Deletes a fulfillment event

GET [/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Retrieves a list of fulfillment events for a specific fulfillment

POST [/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Creates a fulfillment event

GET [/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Retrieves a specific fulfillment event

DELETE [/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Deletes a fulfillment event

GET [/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Retrieves a list of fulfillment events for a specific fulfillment

POST [/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json](#)
Creates a fulfillment event

GET [/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Retrieves a specific fulfillment event

DELETE [/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json](#)
Deletes a fulfillment event

shipping-and-fulfillment/fulfillmentorder

GET [/admin/api/2020-01/orders/{order_id}/fulfillment_orders.json](#)
Retrieves a list of fulfillment orders for a specific order.

GET [/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}.json](#)
Retrieves a specific fulfillment order.

POST [/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancel.json](#)
Marks a fulfillment order as cancelled.

POST [/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/close.json](#)
Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

POST [/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/move.json](#)
Moves a fulfillment order from one merchant managed location to another merchant managed location.

GET [/admin/api/2020-04/orders/{order_id}/fulfillment_orders.json](#)

GET	Retrieves a list of fulfillment orders for a specific order. /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/close.json
	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/move.json
	Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-07/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/close.json
	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/move.json
	Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-10/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/close.json
	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/move.json
	Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2021-01/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/close.json
	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/move.json
	Moves a fulfillment order from one merchant managed location to another merchant managed location.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/open.json
	Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/reschedule.json
	Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.
GET	/admin/api/unstable/orders/{order_id}/fulfillment_orders.json
	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}.json
	Retrieves a specific fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancel.json
	Marks a fulfillment order as cancelled.
POST	/admin/api/unstable/fulfillment_orders/release_hold.json
	Releases the fulfillment order holds for a specific order. Fulfillment orders are created with an ON_HOLD status if the channel that created the order has a fulfillment hold policy.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/close.json
	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/move.json
	Moves a fulfillment order from one merchant managed location to another merchant managed location.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/open.json
	Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/reschedule.json
	Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.

shipping-and-fulfillment/fulfillmentrequest

POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

shipping-and-fulfillment/fulfillmentservice

GET	/fetch_tracking_numbers Get tracking numbers for orders
GET	/fetch_stock Get inventory levels
GET	/admin/api/2020-01/fulfillment_services.json
POST	/admin/api/2020-01/fulfillment_services.json To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.
GET	/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json
PUT	/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json
DELETE	/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json
GET	/admin/api/2020-04/fulfillment_services.json
POST	/admin/api/2020-04/fulfillment_services.json To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.
GET	/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json
PUT	/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json
DELETE	/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json
GET	/admin/api/2020-07/fulfillment_services.json
POST	/admin/api/2020-07/fulfillment_services.json To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.
GET	/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

[PUT /admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json](#)
[DELETE /admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json](#)
[GET /admin/api/2020-10/fulfillment_services.json](#)
[POST /admin/api/2020-10/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

[GET /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)
[PUT /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)
[DELETE /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)
[GET /admin/api/2021-01/fulfillment_services.json](#)
[POST /admin/api/2021-01/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

[GET /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)
[PUT /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)
[DELETE /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)
[GET /admin/api/unstable/fulfillment_services.json](#)
[POST /admin/api/unstable/fulfillment_services.json](#)
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

[GET /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)
[PUT /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)
[DELETE /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)

shipping-and-fulfillment/locationsformove

[GET /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)
Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)
Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)
Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)
Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)
Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)
Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

shippingzone

[GET /admin/api/2020-01/shipping_zones.json](#)
Get a list of all shipping zones

[GET /admin/api/2020-04/shipping_zones.json](#)
Get a list of all shipping zones

[GET /admin/api/2020-07/shipping_zones.json](#)
Get a list of all shipping zones

[GET /admin/api/2020-10/shipping_zones.json](#)
Get a list of all shipping zones

[GET /admin/api/2021-01/shipping_zones.json](#)
Get a list of all shipping zones

[GET /admin/api/unstable/shipping_zones.json](#)
Get a list of all shipping zones

shop

[GET /admin/api/2020-01/shop.json](#)
Retrieves the shop's configuration

[GET /admin/api/2020-04/shop.json](#)
Retrieves the shop's configuration

[GET](#) </admin/api/2020-07/shop.json>
Retrieves the shop's configuration

[GET](#) </admin/api/2020-10/shop.json>
Retrieves the shop's configuration

[GET](#) </admin/api/2021-01/shop.json>
Retrieves the shop's configuration

[GET](#) </admin/api/unstable/shop.json>
Retrieves the shop's configuration

shopify_payments

[GET](#) /admin/api/2020-01/shopify_payments/balance.json
Retrieves the account's current balance.

[GET](#) /admin/api/2020-04/shopify_payments/balance.json
Retrieves the account's current balance.

[GET](#) /admin/api/2020-07/shopify_payments/balance.json
Retrieves the account's current balance.

[GET](#) /admin/api/2020-10/shopify_payments/balance.json
Retrieves the account's current balance.

[GET](#) /admin/api/2021-01/shopify_payments/balance.json
Retrieves the account's current balance.

[GET](#) /admin/api/unstable/shopify_payments/balance.json
Retrieves the account's current balance.

[GET](#) /admin/api/2020-01/shopify_payments/disputes.json
Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2020-01/shopify_payments/disputes/{dispute_id}.json
Retrieves a single dispute by ID.

[GET](#) /admin/api/2020-04/shopify_payments/disputes.json
Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2020-01/shopify_payments/payouts.json
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2020-01/shopify_payments/payouts/{payout_id}.json
Retrieves a single payout by id.

[GET](#) /admin/api/2020-04/shopify_payments/payouts.json
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2020-04/shopify_payments/payouts/{payout_id}.json
Retrieves a single payout by id.

[GET](#) /admin/api/2020-07/shopify_payments/payouts.json
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2020-07/shopify_payments/payouts/{payout_id}.json
Retrieves a single payout by id.

[GET](#) /admin/api/2020-10/shopify_payments/payouts.json
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2020-10/shopify_payments/payouts/{payout_id}.json
Retrieves a single payout by id.

[GET](#) /admin/api/2021-01/shopify_payments/payouts.json
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/2021-01/shopify_payments/payouts/{payout_id}.json
Retrieves a single payout by id.

[GET](#) /admin/api/unstable/shopify_payments/payouts.json
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) /admin/api/unstable/shopify_payments/payouts/{payout_id}.json
Retrieves a single payout by id.

[GET](#) /admin/api/2020-01/shopify_payments/balance/transactions.json
Retrieves a list of all balance transactions ordered by processing time, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see

Making requests to paginated REST Admin API endpoints.

shopify_payments/balance

- [GET](#) [/admin/api/2020-01/shopify_payments/balance.json](#)
Retrieves the account's current balance.
- [GET](#) [/admin/api/2020-04/shopify_payments/balance.json](#)
Retrieves the account's current balance.
- [GET](#) [/admin/api/2020-07/shopify_payments/balance.json](#)
Retrieves the account's current balance.
- [GET](#) [/admin/api/2020-10/shopify_payments/balance.json](#)
Retrieves the account's current balance.
- [GET](#) [/admin/api/2021-01/shopify_payments/balance.json](#)
Retrieves the account's current balance.
- [GET](#) [/admin/api/unstable/shopify_payments/balance.json](#)
Retrieves the account's current balance.

shopify_payments/dispute

- [GET](#) [/admin/api/2020-01/shopify_payments/disputes.json](#)
Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) [/admin/api/2020-01/shopify_payments/disputes/{dispute_id}.json](#)
Retrieves a single dispute by ID.
- [GET](#) [/admin/api/2020-04/shopify_payments/disputes.json](#)
Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

shopify_payments/payout

- [GET](#) [/admin/api/2020-01/shopify_payments/payouts.json](#)
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) [/admin/api/2020-01/shopify_payments/payouts/{payout_id}.json](#)
Retrieves a single payout by id.
- [GET](#) [/admin/api/2020-04/shopify_payments/payouts.json](#)
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) [/admin/api/2020-04/shopify_payments/payouts/{payout_id}.json](#)
Retrieves a single payout by id.
- [GET](#) [/admin/api/2020-07/shopify_payments/payouts.json](#)
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) [/admin/api/2020-07/shopify_payments/payouts/{payout_id}.json](#)
Retrieves a single payout by id.
- [GET](#) [/admin/api/2020-10/shopify_payments/payouts.json](#)
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) [/admin/api/2020-10/shopify_payments/payouts/{payout_id}.json](#)
Retrieves a single payout by id.
- [GET](#) [/admin/api/2021-01/shopify_payments/payouts.json](#)
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) [/admin/api/2021-01/shopify_payments/payouts/{payout_id}.json](#)
Retrieves a single payout by id.
- [GET](#) [/admin/api/unstable/shopify_payments/payouts.json](#)
Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) [/admin/api/unstable/shopify_payments/payouts/{payout_id}.json](#)
Retrieves a single payout by id.

shopify_payments/transaction

- [GET](#) [/admin/api/2020-01/shopify_payments/balance/transactions.json](#)
Retrieves a list of all balance transactions ordered by processing time, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

smartcollection

GET /admin/api/2020-01/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/smart_collections.json

Creates a new smart collection using the specified rules.

GET /admin/api/2020-01/smart_collections/count.json

Retrieves a count of smart collections

GET /admin/api/2020-01/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection

PUT /admin/api/2020-01/smart_collections/{smart_collection_id}.json

Updates an existing smart collection

DELETE /admin/api/2020-01/smart_collections/{smart_collection_id}.json

Removes a smart collection

PUT /admin/api/2020-01/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection

GET /admin/api/2020-04/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/smart_collections.json

Creates a new smart collection using the specified rules.

GET /admin/api/2020-04/smart_collections/count.json

Retrieves a count of smart collections

GET /admin/api/2020-04/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection

PUT /admin/api/2020-04/smart_collections/{smart_collection_id}.json

Updates an existing smart collection

DELETE /admin/api/2020-04/smart_collections/{smart_collection_id}.json

Removes a smart collection

PUT /admin/api/2020-04/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection

GET /admin/api/2020-07/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/smart_collections.json

Creates a new smart collection using the specified rules.

GET /admin/api/2020-07/smart_collections/count.json

Retrieves a count of smart collections

GET /admin/api/2020-07/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection

PUT /admin/api/2020-07/smart_collections/{smart_collection_id}.json

Updates an existing smart collection

DELETE /admin/api/2020-07/smart_collections/{smart_collection_id}.json

Removes a smart collection

PUT /admin/api/2020-07/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection

GET /admin/api/2020-10/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/smart_collections.json

Creates a new smart collection using the specified rules.

GET /admin/api/2020-10/smart_collections/count.json

Retrieves a count of smart collections

GET /admin/api/2020-10/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection

PUT /admin/api/2020-10/smart_collections/{smart_collection_id}.json

Updates an existing smart collection

DELETE /admin/api/2020-10/smart_collections/{smart_collection_id}.json

Removes a smart collection

PUT /admin/api/2020-10/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection

GET /admin/api/2021-01/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/smart_collections.json

Creates a new smart collection using the specified rules.

GET /admin/api/2021-01/smart_collections/count.json

GET	Retrieves a count of smart collections /admin/api/2021-01/smart_collections/{smart_collection_id}.json
PUT	Retrieves a single smart collection /admin/api/2021-01/smart_collections/{smart_collection_id}.json
DELETE	Updates an existing smart collection /admin/api/2021-01/smart_collections/{smart_collection_id}.json
PUT	Removes a smart collection /admin/api/2021-01/smart_collections/{smart_collection_id}/order.json
GET	Updates the ordering type of products in a smart collection /admin/api/unstable/smart_collections.json
POST	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/unstable/smart_collections.json
GET	Creates a new smart collection using the specified rules. /admin/api/unstable/smart_collections/count.json
GET	Retrieves a count of smart collections /admin/api/unstable/smart_collections/{smart_collection_id}.json
PUT	Retrieves a single smart collection /admin/api/unstable/smart_collections/{smart_collection_id}.json
DELETE	Updates an existing smart collection /admin/api/unstable/smart_collections/{smart_collection_id}.json
PUT	Removes a smart collection /admin/api/unstable/smart_collections/{smart_collection_id}/order.json
GET	Updates the ordering type of products in a smart collection /admin/api/unstable/smart_collections/{smart_collection_id}/order.json

store-properties

GET	/admin/api/2020-01/countries.json Retrieves a list of countries.
POST	/admin/api/2020-01/countries.json Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-01/countries/count.json Retrieves a count of countries.
GET	/admin/api/2020-01/countries/{country_id}.json Retrieves a specific county.
PUT	/admin/api/2020-01/countries/{country_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-01/countries/{country_id}.json Deletes a country.
GET	/admin/api/2020-04/countries.json Retrieves a list of countries.
POST	/admin/api/2020-04/countries.json Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-04/countries/count.json Retrieves a count of countries.
GET	/admin/api/2020-04/countries/{country_id}.json Retrieves a specific county.
PUT	/admin/api/2020-04/countries/{country_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-04/countries/{country_id}.json Deletes a country.
GET	/admin/api/2020-07/countries.json Retrieves a list of countries.
POST	/admin/api/2020-07/countries.json Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-07/countries/count.json Retrieves a count of countries.
GET	/admin/api/2020-07/countries/{country_id}.json Retrieves a specific county.
PUT	/admin/api/2020-07/countries/{country_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-07/countries/{country_id}.json Deletes a country.
GET	/admin/api/2020-10/countries.json Retrieves a list of countries.
POST	/admin/api/2020-10/countries.json Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-10/countries/count.json

[GET](#) [/admin/api/2020-10/countries/{country_id}.json](#)
Retrieves a count of countries.

[PUT](#) [/admin/api/2020-10/countries/{country_id}.json](#)
Retrieves a specific county.
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

[DELETE](#) [/admin/api/2020-10/countries/{country_id}.json](#)
Deletes a country.

[GET](#) [/admin/api/2021-01/countries.json](#)
Retrieves a list of countries.

[POST](#) [/admin/api/2021-01/countries.json](#)
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

[GET](#) [/admin/api/2021-01/countries/count.json](#)
Retrieves a count of countries.

[GET](#) [/admin/api/2021-01/countries/{country_id}.json](#)
Retrieves a specific county.

[PUT](#) [/admin/api/2021-01/countries/{country_id}.json](#)
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

[DELETE](#) [/admin/api/2021-01/countries/{country_id}.json](#)
Deletes a country.

[GET](#) [/admin/api/unstable/countries.json](#)
Retrieves a list of countries.

[POST](#) [/admin/api/unstable/countries.json](#)
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

[GET](#) [/admin/api/unstable/countries/count.json](#)
Retrieves a count of countries.

[GET](#) [/admin/api/unstable/countries/{country_id}.json](#)
Retrieves a specific county.

[PUT](#) [/admin/api/unstable/countries/{country_id}.json](#)
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

[DELETE](#) [/admin/api/unstable/countries/{country_id}.json](#)
Deletes a country.

[GET](#) [/admin/api/2020-01/currencies.json](#)
Retrieves a list of currencies enabled on a shop

[GET](#) [/admin/api/2020-04/currencies.json](#)
Retrieves a list of currencies enabled on a shop

[GET](#) [/admin/api/2020-07/currencies.json](#)
Retrieves a list of currencies enabled on a shop

[GET](#) [/admin/api/2020-10/currencies.json](#)
Retrieves a list of currencies enabled on a shop

[GET](#) [/admin/api/2021-01/currencies.json](#)
Retrieves a list of currencies enabled on a shop

[GET](#) [/admin/api/unstable/currencies.json](#)
Retrieves a list of currencies enabled on a shop

[GET](#) [/admin/api/2020-01/policies.json](#)
Retrieves a list of the shop's policies

[GET](#) [/admin/api/2020-04/policies.json](#)
Retrieves a list of the shop's policies

[GET](#) [/admin/api/2020-07/policies.json](#)
Retrieves a list of the shop's policies

[GET](#) [/admin/api/2020-10/policies.json](#)
Retrieves a list of the shop's policies

[GET](#) [/admin/api/2021-01/policies.json](#)
Retrieves a list of the shop's policies

[GET](#) [/admin/api/unstable/policies.json](#)
Retrieves a list of the shop's policies

[GET](#) [/admin/api/2020-01/countries/{country_id}/provinces.json](#)
Retrieves a list of provinces

[GET](#) [/admin/api/2020-01/countries/{country_id}/provinces/count.json](#)
Retrieves a count of provinces for a country

[GET](#) [/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json](#)
Retrieves a single province for a country

[PUT](#) [/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json](#)
Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

[GET](#) [/admin/api/2020-04/countries/{country_id}/provinces.json](#)
Retrieves a list of provinces

[GET](#) [/admin/api/2020-04/countries/{country_id}/provinces/count.json](#)
Retrieves a count of provinces for a country

GET	/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json Retrieves a single province for a country
PUT	/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-07/countries/{country_id}/provinces.json Retrieves a list of provinces
GET	/admin/api/2020-07/countries/{country_id}/provinces/count.json Retrieves a count of provinces for a country
GET	/admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json Retrieves a single province for a country
PUT	/admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-10/countries/{country_id}/provinces.json Retrieves a list of provinces
GET	/admin/api/2020-10/countries/{country_id}/provinces/count.json Retrieves a count of provinces for a country
GET	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json Retrieves a single province for a country
PUT	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2021-01/countries/{country_id}/provinces.json Retrieves a list of provinces
GET	/admin/api/2021-01/countries/{country_id}/provinces/count.json Retrieves a count of provinces for a country
GET	/admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json Retrieves a single province for a country
PUT	/admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/unstable/countries/{country_id}/provinces.json Retrieves a list of provinces
GET	/admin/api/unstable/countries/{country_id}/provinces/count.json Retrieves a count of provinces for a country
GET	/admin/api/unstable/countries/{country_id}/provinces/{province_id}.json Retrieves a single province for a country
PUT	/admin/api/unstable/countries/{country_id}/provinces/{province_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-01/shipping_zones.json Get a list of all shipping zones
GET	/admin/api/2020-04/shipping_zones.json Get a list of all shipping zones
GET	/admin/api/2020-07/shipping_zones.json Get a list of all shipping zones
GET	/admin/api/2020-10/shipping_zones.json Get a list of all shipping zones
GET	/admin/api/2021-01/shipping_zones.json Get a list of all shipping zones
GET	/admin/api/unstable/shipping_zones.json Get a list of all shipping zones
GET	/admin/api/2020-01/shop.json Retrieves the shop's configuration
GET	/admin/api/2020-04/shop.json Retrieves the shop's configuration
GET	/admin/api/2020-07/shop.json Retrieves the shop's configuration
GET	/admin/api/2020-10/shop.json Retrieves the shop's configuration
GET	/admin/api/2021-01/shop.json Retrieves the shop's configuration
GET	/admin/api/unstable/shop.json Retrieves the shop's configuration

store-properties/country

GET	/admin/api/2020-01/countries.json Retrieves a list of countries.
POST	/admin/api/2020-01/countries.json Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET </admin/api/2020-01/countries/count.json>
Retrieves a count of countries.

GET /admin/api/2020-01/countries/{country_id}.json
Retrieves a specific county.

PUT /admin/api/2020-01/countries/{country_id}.json
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE /admin/api/2020-01/countries/{country_id}.json
Deletes a country.

GET </admin/api/2020-04/countries.json>
Retrieves a list of countries.

POST </admin/api/2020-04/countries.json>
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET </admin/api/2020-04/countries/count.json>
Retrieves a count of countries.

GET /admin/api/2020-04/countries/{country_id}.json
Retrieves a specific county.

PUT /admin/api/2020-04/countries/{country_id}.json
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE /admin/api/2020-04/countries/{country_id}.json
Deletes a country.

GET </admin/api/2020-07/countries.json>
Retrieves a list of countries.

POST </admin/api/2020-07/countries.json>
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET </admin/api/2020-07/countries/count.json>
Retrieves a count of countries.

GET /admin/api/2020-07/countries/{country_id}.json
Retrieves a specific county.

PUT /admin/api/2020-07/countries/{country_id}.json
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE /admin/api/2020-07/countries/{country_id}.json
Deletes a country.

GET </admin/api/2020-10/countries.json>
Retrieves a list of countries.

POST </admin/api/2020-10/countries.json>
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET </admin/api/2020-10/countries/count.json>
Retrieves a count of countries.

GET /admin/api/2020-10/countries/{country_id}.json
Retrieves a specific county.

PUT /admin/api/2020-10/countries/{country_id}.json
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE /admin/api/2020-10/countries/{country_id}.json
Deletes a country.

GET </admin/api/2021-01/countries.json>
Retrieves a list of countries.

POST </admin/api/2021-01/countries.json>
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET </admin/api/2021-01/countries/count.json>
Retrieves a count of countries.

GET /admin/api/2021-01/countries/{country_id}.json
Retrieves a specific county.

PUT /admin/api/2021-01/countries/{country_id}.json
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE /admin/api/2021-01/countries/{country_id}.json
Deletes a country.

GET </admin/api/unstable/countries.json>
Retrieves a list of countries.

POST </admin/api/unstable/countries.json>
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET </admin/api/unstable/countries/count.json>
Retrieves a count of countries.

GET /admin/api/unstable/countries/{country_id}.json
Retrieves a specific county.

PUT /admin/api/unstable/countries/{country_id}.json
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE /admin/api/unstable/countries/{country_id}.json

Deletes a country.

store-properties/currency

GET	/admin/api/2020-01/currencies.json	Retrieves a list of currencies enabled on a shop
GET	/admin/api/2020-04/currencies.json	Retrieves a list of currencies enabled on a shop
GET	/admin/api/2020-07/currencies.json	Retrieves a list of currencies enabled on a shop
GET	/admin/api/2020-10/currencies.json	Retrieves a list of currencies enabled on a shop
GET	/admin/api/2021-01/currencies.json	Retrieves a list of currencies enabled on a shop
GET	/admin/api/unstable/currencies.json	Retrieves a list of currencies enabled on a shop

store-properties/policy

GET	/admin/api/2020-01/policies.json	Retrieves a list of the shop's policies
GET	/admin/api/2020-04/policies.json	Retrieves a list of the shop's policies
GET	/admin/api/2020-07/policies.json	Retrieves a list of the shop's policies
GET	/admin/api/2020-10/policies.json	Retrieves a list of the shop's policies
GET	/admin/api/2021-01/policies.json	Retrieves a list of the shop's policies
GET	/admin/api/unstable/policies.json	Retrieves a list of the shop's policies

store-properties/province

GET	/admin/api/2020-01/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2020-01/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-04/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2020-04/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-07/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2020-07/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-10/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2020-10/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2021-01/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2021-01/countries/{country_id}/provinces/count.json	

GET	Retrieves a count of provinces for a country /admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json
	Retrieves a single province for a country
PUT	/admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json
	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/unstable/countries/{country_id}/provinces.json
	Retrieves a list of provinces
GET	/admin/api/unstable/countries/{country_id}/provinces/count.json
	Retrieves a count of provinces for a country
GET	/admin/api/unstable/countries/{country_id}/provinces/{province_id}.json
	Retrieves a single province for a country
PUT	/admin/api/unstable/countries/{country_id}/provinces/{province_id}.json
	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

store-properties/shippingzone

GET	/admin/api/2020-01/shipping_zones.json
	Get a list of all shipping zones
GET	/admin/api/2020-04/shipping_zones.json
	Get a list of all shipping zones
GET	/admin/api/2020-07/shipping_zones.json
	Get a list of all shipping zones
GET	/admin/api/2020-10/shipping_zones.json
	Get a list of all shipping zones
GET	/admin/api/2021-01/shipping_zones.json
	Get a list of all shipping zones
GET	/admin/api/unstable/shipping_zones.json
	Get a list of all shipping zones

store-properties/shop

GET	/admin/api/2020-01/shop.json
	Retrieves the shop's configuration
GET	/admin/api/2020-04/shop.json
	Retrieves the shop's configuration
GET	/admin/api/2020-07/shop.json
	Retrieves the shop's configuration
GET	/admin/api/2020-10/shop.json
	Retrieves the shop's configuration
GET	/admin/api/2021-01/shop.json
	Retrieves the shop's configuration
GET	/admin/api/unstable/shop.json
	Retrieves the shop's configuration

storefrontaccesstoken

GET	/admin/api/2020-01/storefront_access_tokens.json
	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-01/storefront_access_tokens.json
	Creates a new storefront access token
DELETE	/admin/api/2020-01/storefront_access_tokens/{storefront_access_token_id}.json
	Deletes an existing storefront access token
GET	/admin/api/2020-04/storefront_access_tokens.json
	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-04/storefront_access_tokens.json
	Creates a new storefront access token
DELETE	/admin/api/2020-04/storefront_access_tokens/{storefront_access_token_id}.json
	Deletes an existing storefront access token
GET	/admin/api/2020-07/storefront_access_tokens.json
	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-07/storefront_access_tokens.json
	Creates a new storefront access token
DELETE	/admin/api/2020-07/storefront_access_tokens/{storefront_access_token_id}.json
	Deletes an existing storefront access token
GET	/admin/api/2020-10/storefront_access_tokens.json
	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-10/storefront_access_tokens.json
	Creates a new storefront access token
DELETE	/admin/api/2020-10/storefront_access_tokens/{storefront_access_token_id}.json
	Deletes an existing storefront access token

GET	/admin/api/2021-01/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2021-01/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2021-01/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/unstable/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/unstable/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/unstable/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token

tendertransaction

GET	/admin/api/2020-01/tender_transactions.json	Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/tender_transactions.json	Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/tender_transactions.json	Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/tender_transactions.json	Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/tender_transactions.json	Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/tender_transactions.json	Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

theme

GET	/admin/api/2020-01/themes.json	Retrieves a list of themes.
POST	/admin/api/2020-01/themes.json	Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-01/themes/{theme_id}.json	Retrieves a single theme.
PUT	/admin/api/2020-01/themes/{theme_id}.json	Updates an existing theme.
DELETE	/admin/api/2020-01/themes/{theme_id}.json	Deletes a theme.
GET	/admin/api/2020-04/themes.json	Retrieves a list of themes.
POST	/admin/api/2020-04/themes.json	Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-04/themes/{theme_id}.json	Retrieves a single theme.
PUT	/admin/api/2020-04/themes/{theme_id}.json	Updates an existing theme.
DELETE	/admin/api/2020-04/themes/{theme_id}.json	Deletes a theme.
GET	/admin/api/2020-07/themes.json	Retrieves a list of themes.
POST	/admin/api/2020-07/themes.json	Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-07/themes/{theme_id}.json	Retrieves a single theme.
PUT	/admin/api/2020-07/themes/{theme_id}.json	Updates an existing theme.
DELETE	/admin/api/2020-07/themes/{theme_id}.json	

GET	/admin/api/2020-10/themes.json Deletes a theme.
POST	/admin/api/2020-10/themes.json Retrieves a list of themes.
GET	/admin/api/2020-10/themes/{theme_id}.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
PUT	/admin/api/2020-10/themes/{theme_id}.json Retrieves a single theme.
DELETE	/admin/api/2020-10/themes/{theme_id}.json Updates an existing theme.
GET	/admin/api/2021-01/themes.json Deletes a theme.
POST	/admin/api/2021-01/themes.json Retrieves a list of themes.
GET	/admin/api/2021-01/themes/{theme_id}.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
PUT	/admin/api/2021-01/themes/{theme_id}.json Retrieves a single theme.
DELETE	/admin/api/2021-01/themes/{theme_id}.json Updates an existing theme.
GET	/admin/api/unstable/themes.json Deletes a theme.
POST	/admin/api/unstable/themes.json Retrieves a list of themes.
GET	/admin/api/unstable/themes/{theme_id}.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
PUT	/admin/api/unstable/themes/{theme_id}.json Retrieves a single theme.
DELETE	/admin/api/unstable/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/unstable/themes/{theme_id}.json Deletes a theme.

transaction

GET	/admin/api/2020-01/shopify_payments/balance/transactions.json Retrieves a list of all balance transactions ordered by processing time, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
---------------------	--

usagecharge

GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge

GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
	Retrieves a list of usage charges
POST	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
	Creates a usage charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json
	Retrieves a single charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
	Retrieves a list of usage charges
POST	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json
	Creates a usage charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json
	Retrieves a single charge

user

GET	/admin/api/2020-01/users.json
	Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/users/{user_id}.json
	Retrieves a single user
GET	/admin/api/2020-01/users/current.json
	Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-04/users.json
	Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/users/{user_id}.json
	Retrieves a single user
GET	/admin/api/2020-04/users/current.json
	Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-07/users.json
	Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/users/{user_id}.json
	Retrieves a single user
GET	/admin/api/2020-07/users/current.json
	Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-10/users.json
	Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/users/{user_id}.json
	Retrieves a single user
GET	/admin/api/2020-10/users/current.json
	Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2021-01/users.json
	Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/users/{user_id}.json
	Retrieves a single user
GET	/admin/api/2021-01/users/current.json
	Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/unstable/users.json
	Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/users/{user_id}.json
	Retrieves a single user
GET	/admin/api/unstable/users/current.json
	Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

webhook

GET	/admin/api/2020-01/webhooks.json
	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/webhooks.json
	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-01/webhooks/count.json

GET	Retrieves a count of existing webhook subscriptions /admin/api/2020-01/webhooks/{webhook_id}.json
PUT	Retrieves a single webhook subscription /admin/api/2020-01/webhooks/{webhook_id}.json
DELETE	Update a webhook subscription's topic or address URIs /admin/api/2020-01/webhooks/{webhook_id}.json
GET	Delete a webhook subscription /admin/api/2020-04/webhooks.json
POST	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2020-04/webhooks.json
GET	Create a new webhook subscription by specifying both an address and a topic /admin/api/2020-04/webhooks/count.json
GET	Retrieves a count of existing webhook subscriptions /admin/api/2020-04/webhooks/{webhook_id}.json
PUT	Retrieves a single webhook subscription /admin/api/2020-04/webhooks/{webhook_id}.json
DELETE	Update a webhook subscription's topic or address URIs /admin/api/2020-04/webhooks/{webhook_id}.json
GET	Delete a webhook subscription /admin/api/2020-07/webhooks.json
POST	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2020-07/webhooks.json
GET	Create a new webhook subscription by specifying both an address and a topic /admin/api/2020-07/webhooks/count.json
GET	Retrieves a count of existing webhook subscriptions /admin/api/2020-07/webhooks/{webhook_id}.json
PUT	Retrieves a single webhook subscription /admin/api/2020-07/webhooks/{webhook_id}.json
DELETE	Update a webhook subscription's topic or address URIs /admin/api/2020-07/webhooks/{webhook_id}.json
GET	Delete a webhook subscription /admin/api/2020-10/webhooks.json
POST	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2020-10/webhooks.json
GET	Create a new webhook subscription by specifying both an address and a topic /admin/api/2020-10/webhooks/count.json
GET	Retrieves a count of existing webhook subscriptions /admin/api/2020-10/webhooks/{webhook_id}.json
PUT	Retrieves a single webhook subscription /admin/api/2020-10/webhooks/{webhook_id}.json
DELETE	Update a webhook subscription's topic or address URIs /admin/api/2020-10/webhooks/{webhook_id}.json
GET	Delete a webhook subscription /admin/api/2021-01/webhooks.json
POST	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/2021-01/webhooks.json
GET	Create a new webhook subscription by specifying both an address and a topic /admin/api/2021-01/webhooks/count.json
GET	Retrieves a count of existing webhook subscriptions /admin/api/2021-01/webhooks/{webhook_id}.json
PUT	Retrieves a single webhook subscription /admin/api/2021-01/webhooks/{webhook_id}.json
DELETE	Update a webhook subscription's topic or address URIs /admin/api/2021-01/webhooks/{webhook_id}.json
GET	Delete a webhook subscription /admin/api/unstable/webhooks.json
POST	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints. /admin/api/unstable/webhooks.json
GET	Create a new webhook subscription by specifying both an address and a topic /admin/api/unstable/webhooks/count.json
GET	Retrieves a count of existing webhook subscriptions /admin/api/unstable/webhooks/{webhook_id}.json
GET	Retrieves a single webhook subscription

[PUT](#) [/admin/api/unstable/webhooks/{webhook_id}.json](#)
Update a webhook subscription's topic or address URIs

[DELETE](#) [/admin/api/unstable/webhooks/{webhook_id}.json](#)
Delete a webhook subscription

REST Api

GET

/admin/oauth/access_scopes.json

Retrieves a list of access scopes associated to the access token.
<https://shopify.dev/docs/admin-api/rest/reference/access/accessscope#index-2020-10>

Responses

200

GET

/admin/api/2020-01/storefront_access_tokens.json

Retrieves a list of storefront access tokens that have been issued
<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-2020-01>

Responses

200

POST

/admin/api/2020-01/storefront_access_tokens.json

Creates a new storefront access token
<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-2020-01>

Responses

200

DELETE

/admin/api/2020-01/storefront_access_tokens/{storefront_access_token_id}.json

Deletes an existing storefront access token
<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
storefront_access_token_id	string	path	required	storefront_access_token_id

Responses

200

GET

/admin/api/2020-04/storefront_access_tokens.json

Retrieves a list of storefront access tokens that have been issued
<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-2020-04>

Responses

200

POST

/admin/api/2020-04/storefront_access_tokens.json

Creates a new storefront access token
<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-2020-04>

Responses

200

DELETE

/admin/api/2020-04/storefront_access_tokens/{storefront_access_token_id}.json

Deletes an existing storefront access token
<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
storefront_access_token_id	string	path	required	storefront_access_token_id

Responses

200

GET

/admin/api/2020-07/storefront_access_tokens.json

Retrieves a list of storefront access tokens that have been issued

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-2020-07

Responses

200

POST

/admin/api/2020-07/storefront_access_tokens.json

Creates a new storefront access token
https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-2020-07

Responses

200

DELETE

/admin/api/2020-07/storefront_access_tokens/{storefront_access_token_id}.json

Deletes an existing storefront access token
https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-2020-07

Parameters

Name	Type	In	Required	Description
storefront_access_token_id	string	path	required	storefront_access_token_id

Responses

200

GET

/admin/api/2020-10/storefront_access_tokens.json

Retrieves a list of storefront access tokens that have been issued
https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-2020-10

Responses

200

POST

/admin/api/2020-10/storefront_access_tokens.json

Creates a new storefront access token
https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-2020-10

Responses

200

DELETE

/admin/api/2020-10/storefront_access_tokens/{storefront_access_token_id}.json

Deletes an existing storefront access token
https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-2020-10

Parameters

Name	Type	In	Required	Description
storefront_access_token_id	string	path	required	storefront_access_token_id

Responses

200

GET

/admin/api/2021-01/storefront_access_tokens.json

Retrieves a list of storefront access tokens that have been issued
https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-2021-01

Responses

200

POST

/admin/api/2021-01/storefront_access_tokens.json

Creates a new storefront access token
https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-2021-01

Responses

200

DELETE /admin/api/2021-01/storefront_access_tokens/{storefront_access_token_id}.json

Deletes an existing storefront access token

<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
storefront_access_token_id	string	path	required	storefront_access_token_id

Responses

200

GET /admin/api/unstable/storefront_access_tokens.json

Retrieves a list of storefront access tokens that have been issued

<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-unstable>

Responses

200

POST /admin/api/unstable/storefront_access_tokens.json

Creates a new storefront access token

<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-unstable>

Responses

200

DELETE /admin/api/unstable/storefront_access_tokens/{storefront_access_token_id}.json

Deletes an existing storefront access token

<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-unstable>

Parameters

Name	Type	In	Required	Description
storefront_access_token_id	string	path	required	storefront_access_token_id

Responses

200

GET /admin/api/2020-01/reports.json

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-2020-01>

Parameters

Name	Type	In	Required	Description
ids		query		A comma-separated list of report IDs.
limit		query		The amount of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
updated_at_min		query		Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-01/reports.json

Creates a new report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-2020-01>

Parameters

Name	Type	In	Required	Description
name		query		The name of the report. Maximum length: 255 characters.
shopify_ql		query		The ShopifyQL the report will query.

Responses

200

GET /admin/api/2020-01/reports/{report_id}.json

Retrieves a single report created by your app

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-2020-01>

Parameters

Name	Type	In	Required	Description
report_id fields	string	path query	required	report_id A comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/2020-01/reports/{report_id}.json

Updates a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-2020-01>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

DELETE /admin/api/2020-01/reports/{report_id}.json

Deletes a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

GET /admin/api/2020-04/reports.json

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-2020-04>

Parameters

Name	Type	In	Required	Description
ids		query		A comma-separated list of report IDs.
limit		query		The amount of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
updated_at_min		query		Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-04/reports.json

Creates a new report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-2020-04>

Parameters

Name	Type	In	Required	Description
name shopify_ql		query query		The name of the report. Maximum length: 255 characters. The ShopifyQL the report will query.

Responses

200

GET /admin/api/2020-04/reports/{report_id}.json

Retrieves a single report created by your app

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-2020-04>

Parameters

Name	Type	In	Required	Description
report_id fields	string	path query	required	report_id A comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/2020-04/reports/{report_id}.json

Updates a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-2020-04>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

DELETE /admin/api/2020-04/reports/{report_id}.json

Deletes a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

GET /admin/api/2020-07/reports.json

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-2020-07>

Parameters

Name	Type	In	Required	Description
ids		query		A comma-separated list of report IDs.
limit		query		The amount of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
updated_at_min		query		Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-07/reports.json

Creates a new report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-2020-07>

Parameters

Name	Type	In	Required	Description
name		query		The name of the report. Maximum length: 255 characters.
shopify_ql		query		The ShopifyQL the report will query.

Responses

200

GET /admin/api/2020-07/reports/{report_id}.json

Retrieves a single report created by your app

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-2020-07>

Parameters

Name	Type	In	Required	Description
report_id fields	string	path query	required	report_id A comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/2020-07/reports/{report_id}.json

Updates a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-2020-07>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

DELETE /admin/api/2020-07/reports/{report_id}.json

Deletes a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

GET /admin/api/2020-10/reports.json

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-2020-10>

Parameters

Name	Type	In	Required	Description
ids		query		A comma-separated list of report IDs.
limit		query		The amount of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
updated_at_min		query		Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-10/reports.json

Creates a new report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-2020-10>

Parameters

Name	Type	In	Required	Description
name		query		The name of the report. Maximum length: 255 characters.
shopify_ql		query		The ShopifyQL the report will query.

Responses

200

GET /admin/api/2020-10/reports/{report_id}.json

Retrieves a single report created by your app

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-2020-10>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/2020-10/reports/{report_id}.json

Updates a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-2020-10>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

DELETE /admin/api/2020-10/reports/{report_id}.json

Deletes a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

GET /admin/api/2021-01/reports.json

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-2021-01>

Parameters

Name	Type	In	Required	Description
ids		query		A comma-separated list of report IDs.
limit		query		The amount of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
updated_at_min		query		Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2021-01/reports.json

Creates a new report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-2021-01>

Parameters

Name	Type	In	Required	Description
name		query		The name of the report. Maximum length: 255 characters.
shopify_ql		query		The ShopifyQL the report will query.

Responses

200

GET /admin/api/2021-01/reports/{report_id}.json

Retrieves a single report created by your app

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-2021-01>

Parameters

Name	Type	In	Required	Description
report_id fields	string	path query	required	report_id A comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/2021-01/reports/{report_id}.json

Updates a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-2021-01>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

DELETE /admin/api/2021-01/reports/{report_id}.json

Deletes a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

GET /admin/api/unstable/reports.json

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-unstable>

Parameters

Name	Type	In	Required	Description
ids		query		A comma-separated list of report IDs.
limit		query		The amount of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
updated_at_min		query		Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/unstable/reports.json

Creates a new report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-unstable>

Parameters

Name	Type	In	Required	Description
name shopify_ql		query query		The name of the report. Maximum length: 255 characters. The ShopifyQL the report will query.

Responses

200

GET /admin/api/unstable/reports/{report_id}.json

Retrieves a single report created by your app

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-unstable>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

fields

query

A comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/unstable/reports/{report_id}.json

Updates a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-unstable>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

DELETE /admin/api/unstable/reports/{report_id}.json

Deletes a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-unstable>

Parameters

Name	Type	In	Required	Description
report_id	string	path	required	report_id

Responses

200

GET /admin/api/2020-01/application_charges.json

Retrieves a list of application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-2020-01>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-01/application_charges.json

Creates an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-2020-01>

Responses

200

GET /admin/api/2020-01/application_charges/{application_charge_id}.json

Retrieves an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-2020-01>

Parameters

Name	Type	In	Required	Description
application_charge_id	string	path	required	application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-01/application_charges/{application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#activate-2020-01>

Parameters

Name	Type	In	Required	Description
application_charge_id	string	path	required	application_charge_id

Responses

200

GET /admin/api/2020-04/application_charges.json

Retrieves a list of application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-2020-04>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-04/application_charges.json

Creates an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-2020-04>

Responses

200

GET /admin/api/2020-04/application_charges/{application_charge_id}.json

Retrieves an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-2020-04>

Parameters

Name	Type	In	Required	Description
application_charge_id	string	path	required	application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-04/application_charges/{application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#activate-2020-04>

Parameters

Name	Type	In	Required	Description
application_charge_id	string	path	required	application_charge_id

Responses

200

GET /admin/api/2020-07/application_charges.json

Retrieves a list of application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-2020-07>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-07/application_charges.json

Creates an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-2020-07>

Responses

200

GET /admin/api/2020-07/application_charges/{application_charge_id}.json

Retrieves an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-2020-07>

Parameters

Name	Type	In	Required	Description
application_charge_id	string	path	required	application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-07/application_charges/{application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#activate-2020-07>

Parameters

Name	Type	In	Required	Description
application_charge_id	string	path	required	application_charge_id

Responses

200

GET /admin/api/2020-10/application_charges.json

Retrieves a list of application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-2020-10>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-10/application_charges.json

Creates an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-2020-10>

Responses

200

GET /admin/api/2020-10/application_charges/{application_charge_id}.json

Retrieves an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-2020-10>

Parameters

Name	Type	In	Required	Description
application_charge_id	string	path	required	application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-10/application_charges/{application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#activate-2020-10

Parameters

Name	Type	In	Required	Description
application_charge_id	string	path	required	application_charge_id

Responses

200

GET /admin/api/2021-01/application_charges.json

Retrieves a list of application charges

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-2021-01

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2021-01/application_charges.json

Creates an application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-2021-01

Responses

200

GET /admin/api/2021-01/application_charges/{application_charge_id}.json

Retrieves an application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-2021-01

Parameters

Name	Type	In	Required	Description
application_charge_id	string	path	required	application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET /admin/api/unstable/application_charges.json

Retrieves a list of application charges

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-unstable

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/unstable/application_charges.json

Creates an application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-unstable

Responses

200

GET /admin/api/unstable/application_charges/{application_charge_id}.json

Retrieves an application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-unstable

Parameters

Name	Type	In	Required	Description
application_charge_id fields	string	path query	required	application_charge_id A comma-separated list of fields to include in the response.

Responses

200

GET

/admin/api/2020-01/application_credits.json

Retrieves all application credits
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-2020-01>

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2020-01/application_credits.json

Creates an application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-2020-01>

Responses

200

GET

/admin/api/2020-01/application_credits/{application_credit_id}.json

Retrieves a single application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-2020-01>

Parameters

Name	Type	In	Required	Description
application_credit_id fields	string	path query	required	application_credit_id A comma-separated list of fields to include in the response.

Responses

200

GET

/admin/api/2020-04/application_credits.json

Retrieves all application credits
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-2020-04>

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2020-04/application_credits.json

Creates an application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-2020-04>

Responses

200

GET

/admin/api/2020-04/application_credits/{application_credit_id}.json

Retrieves a single application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-2020-04>

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

application_credit_id fields	string	path query	required	application_credit_id A comma-separated list of fields to include in the response.
------------------------------	--------	------------	----------	---

Responses

200

GET

/admin/api/2020-07/application_credits.json

Retrieves all application credits
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-2020-07>

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2020-07/application_credits.json

Creates an application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-2020-07>

Responses

200

GET

/admin/api/2020-07/application_credits/{application_credit_id}.json

Retrieves a single application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-2020-07>

Parameters

Name	Type	In	Required	Description
application_credit_id fields	string	path query	required	application_credit_id A comma-separated list of fields to include in the response.

Responses

200

GET

/admin/api/2020-10/application_credits.json

Retrieves all application credits
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-2020-10>

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2020-10/application_credits.json

Creates an application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-2020-10>

Responses

200

GET

/admin/api/2020-10/application_credits/{application_credit_id}.json

Retrieves a single application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-2020-10>

Parameters

Name	Type	In	Required	Description
application_credit_id fields	string	path query	required	application_credit_id A comma-separated list of fields to include in the response.

Responses

200

GET

/admin/api/2021-01/application_credits.json

Retrieves all application credits
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-2021-01>

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2021-01/application_credits.json

Creates an application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-2021-01>

Responses

200

GET

/admin/api/2021-01/application_credits/{application_credit_id}.json

Retrieves a single application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-2021-01>

Parameters

Name	Type	In	Required	Description
application_credit_id	string	path	required	application_credit_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET

/admin/api/unstable/application_credits.json

Retrieves all application credits
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-unstable>

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/unstable/application_credits.json

Creates an application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-unstable>

Responses

200

GET

/admin/api/unstable/application_credits/{application_credit_id}.json

Retrieves a single application credit
<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-unstable>

Parameters

Name	Type	In	Required	Description
application_credit_id	string	path	required	application_credit_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET /admin/api/2020-01/recurring_application_charges.json

Retrieves a list of recurring application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-2020-01>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-01/recurring_application_charges.json

Creates a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-2020-01>

Responses

200

GET /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-2020-01>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

DELETE /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

POST /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#activate-2020-01>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

PUT /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-2020-01>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
recurring_application_charge[capped_amount]	integer	query		recurring_application_charge[capped_amount]

Responses

200

GET /admin/api/2020-04/recurring_application_charges.json

Retrieves a list of recurring application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-2020-04>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-04/recurring_application_charges.json

Creates a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-2020-04>

Responses

200

GET /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-2020-04>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

DELETE /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

POST /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#activate-2020-04>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

PUT /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-2020-04>

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

recurring_application_charge_id

string

path

required

recurring_application_charge_id

recurring_application_charge[capped_amount]

integer

query

recurring_application_charge[capped_amount]

Responses

200

GET

/admin/api/2020-07/recurring_application_charges.json

Retrieves a list of recurring application charges

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-2020-07

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2020-07/recurring_application_charges.json

Creates a recurring application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-2020-07

Responses

200

GET

/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-2020-07

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

DELETE

/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-2020-07

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

POST

/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#activate-2020-07

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

PUT

/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-2020-07

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
recurring_application_charge[capped_amount]	integer	query		recurring_application_charge[capped_amount]

Responses

200

GET /admin/api/2020-10/recurring_application_charges.json

Retrieves a list of recurring application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-2020-10>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-10/recurring_application_charges.json

Creates a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-2020-10>

Responses

200

GET /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-2020-10>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

DELETE /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

POST /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#activate-2020-10>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

PUT /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-2020-10>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
recurring_application_charge[capped_amount]	integer	query		recurring_application_charge[capped_amount]

Responses

200

GET

/admin/api/2021-01/recurring_application_charges.json

Retrieves a list of recurring application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-2021-01>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2021-01/recurring_application_charges.json

Creates a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-2021-01>

Responses

200

GET

/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-2021-01>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

DELETE

/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

PUT

/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-2021-01>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
recurring_application_charge[capped_amount]	integer	query		recurring_application_charge[capped_amount]

Responses

200

GET /admin/api/unstable/recurring_application_charges.json

Retrieves a list of recurring application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-unstable>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/unstable/recurring_application_charges.json

Creates a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-unstable>

Responses

200

GET /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-unstable>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

DELETE /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-unstable>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

PUT /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-unstable>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
recurring_application_charge[capped_amount]	integer	query		recurring_application_charge[capped_amount]

Responses

200

GET /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Retrieves a list of usage charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-2020-01>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Creates a usage charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-2020-01>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

GET

/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-2020-01>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
usage_charge_id	string	path	required	usage_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET

/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Retrieves a list of usage charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-2020-04>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Creates a usage charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-2020-04>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

GET

/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-2020-04>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
usage_charge_id	string	path	required	usage_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Retrieves a list of usage charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-2020-07>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Creates a usage charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-2020-07>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

GET /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-2020-07>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
usage_charge_id	string	path	required	usage_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Retrieves a list of usage charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-2020-10>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Creates a usage charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-2020-10>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

GET /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Retrieves a single charge

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-2020-10

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
usage_charge_id		path	required	usage_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Retrieves a list of usage charges

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-2021-01

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Creates a usage charge

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-2021-01

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

GET /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Retrieves a single charge

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-2021-01

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
usage_charge_id		path	required	usage_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Retrieves a list of usage charges

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-unstable

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Creates a usage charge

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-unstable

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id

Responses

200

GET /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-unstable>

Parameters

Name	Type	In	Required	Description
recurring_application_charge_id	string	path	required	recurring_application_charge_id
usage_charge_id	string	path	required	usage_charge_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET /admin/api/2020-01/customers.json

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-2020-01>

Parameters

Name	Type	In	Required	Description
ids		query		Restrict results to customers specified by a comma-separated list of IDs.
since_id		query		Restrict results to those after the specified ID.
created_at_min		query		Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-01/customers.json

Creates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-2020-01>

Responses

200

GET /admin/api/2020-01/customers/search.json

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-2020-01>

Parameters

Name	Type	In	Required	Description
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
query		query		Text to search for in the shop's customer data.
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-01/customers/{customer_id}.json

Retrieves a single customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-2020-01>

Parameters

Name	Type	In	Required	Description
customer_id fields	string	path query	required	customer_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-01/customers/{customer_id}.json

Updates a customer.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-2020-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

DELETE /admin/api/2020-01/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2020-01/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-2020-01

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2020-01/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.
https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-2020-01

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/2020-01/customers/count.json

Retrieves a count of all customers.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-2020-01>

Responses

200

GET /admin/api/2020-01/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-2020-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET

/admin/api/2020-04/customers.json

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-2020-04>

Parameters

Name	Type	In	Required	Description
ids		query		Restrict results to customers specified by a comma-separated list of IDs.
since_id		query		Restrict results to those after the specified ID.
created_at_min		query		Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-04/customers.json

Creates a customer.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-2020-04>

Responses

200

GET

/admin/api/2020-04/customers/search.json

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-2020-04>

Parameters

Name	Type	In	Required	Description
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
query		query		Text to search for in the shop's customer data.
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET

/admin/api/2020-04/customers/{customer_id}.json

Retrieves a single customer.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-2020-04>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-04/customers/{customer_id}.json

Updates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-2020-04>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

DELETE /admin/api/2020-04/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2020-04/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-2020-04

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2020-04/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-2020-04

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/2020-04/customers/count.json

Retrieves a count of all customers.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-2020-04>

Responses

200

GET /admin/api/2020-04/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-2020-04>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

GET

/admin/api/2020-07/customers.json

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-2020-07

Parameters

Name	Type	In	Required	Description
ids		query		Restrict results to customers specified by a comma-separated list of IDs.
since_id		query		Restrict results to those after the specified ID.
created_at_min		query		Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-07/customers.json

Creates a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-2020-07

Responses

200

GET

/admin/api/2020-07/customers/search.json

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-2020-07

Parameters

Name	Type	In	Required	Description
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
query		query		Text to search for in the shop's customer data.
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET

/admin/api/2020-07/customers/{customer_id}.json

Retrieves a single customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-2020-07

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-07/customers/{customer_id}.json

Updates a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-2020-07

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

DELETE

/admin/api/2020-07/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST

/admin/api/2020-07/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-2020-07

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST

/admin/api/2020-07/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.
https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-2020-07

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET

/admin/api/2020-07/customers/count.json

Retrieves a count of all customers.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-2020-07>

Responses

200

GET

/admin/api/2020-07/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-2020-07>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET

/admin/api/2020-10/customers.json

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-2020-10>

Parameters

Name	Type	In	Required	Description
ids		query		Restrict results to customers specified by a comma-separated list of IDs.
since_id		query		Restrict results to those after the specified ID.
created_at_min		query		Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-10/customers.json

Creates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-2020-10>

Responses

200

GET /admin/api/2020-10/customers/search.json

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-2020-10>

Parameters

Name	Type	In	Required	Description
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
query		query		Text to search for in the shop's customer data.
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-10/customers/{customer_id}.json

Retrieves a single customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-2020-10>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-10/customers/{customer_id}.json

Updates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-2020-10>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

DELETE /admin/api/2020-10/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2020-10/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-2020-10

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2020-10/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-2020-10

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/2020-10/customers/count.json

Retrieves a count of all customers.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-2020-10>

Responses

200

GET /admin/api/2020-10/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-2020-10>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/2021-01/customers.json

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-2021-01>

Parameters

Name	Type	In	Required	Description
ids		query		Restrict results to customers specified by a comma-separated list of IDs.
since_id		query		Restrict results to those after the specified ID.
created_at_min		query		Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)

updated_at_max	query	Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit	query	The maximum number of results to show. (default: 50, maximum: 250)
fields	query	Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2021-01/customers.json

Creates a customer.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-2021-01>

Responses

200

GET

/admin/api/2021-01/customers/search.json

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-2021-01>

Parameters

Name	Type	In	Required	Description
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
query		query		Text to search for in the shop's customer data.
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET

/admin/api/2021-01/customers/{customer_id}.json

Retrieves a single customer.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-2021-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2021-01/customers/{customer_id}.json

Updates a customer.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-2021-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

DELETE

/admin/api/2021-01/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2021-01/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-2021-01

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2021-01/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-2021-01

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/2021-01/customers/count.json

Retrieves a count of all customers.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-2021-01>

Responses

200

GET /admin/api/2021-01/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-2021-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/unstable/customers.json

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-unstable>

Parameters

Name	Type	In	Required	Description
ids		query		Restrict results to customers specified by a comma-separated list of IDs.
since_id		query		Restrict results to those after the specified ID.
created_at_min		query		Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/unstable/customers.json

Creates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-unstable>

Responses

200

GET /admin/api/unstable/customers/search.json

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-unstable>

Parameters

Name	Type	In	Required	Description
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
query		query		Text to search for in the shop's customer data.
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/unstable/customers/{customer_id}.json

Retrieves a single customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-unstable>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/unstable/customers/{customer_id}.json

Updates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-unstable>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

DELETE /admin/api/unstable/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-unstable>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/unstable/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-unstable

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/unstable/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-unstable

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/unstable/customers/count.json

Retrieves a count of all customers.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-unstable>

Responses

200

GET /admin/api/unstable/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-unstable>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/2020-01/customers/{customer_id}/addresses.json

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-2020-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2020-01/customers/{customer_id}/addresses.json

Creates a new address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-2020-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json

Retrieves details a single customer address.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-2020-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT /admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json

Updates an existing customer address.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-2020-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

DELETE /admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json

Removes an address from a customer's address list.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT /admin/api/2020-01/customers/{customer_id}/addresses/set.json

Performs bulk operations for multiple customer addresses.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-2020-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_ids[]	integer	query		address_ids[]
operation	string	query		operation

Responses

200

PUT /admin/api/2020-01/customers/{customer_id}/addresses/{address_id}/default.json

Sets the default address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-2020-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

GET /admin/api/2020-04/customers/{customer_id}/addresses.json

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-2020-04>

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

customer_id	string	path	required	customer_id
-------------	--------	------	----------	-------------

Responses

200

POST /admin/api/2020-04/customers/{customer_id}/addresses.json

Creates a new address for a customer.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-2020-04>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json

Retrieves details a single customer address.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-2020-04>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json

Updates an existing customer address.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-2020-04>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

DELETE /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json

Removes an address from a customer's address list.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT /admin/api/2020-04/customers/{customer_id}/addresses/set.json

Performs bulk operations for multiple customer addresses.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-2020-04>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_ids[]	integer	query		address_ids[]
operation	string	query		operation

Responses

200

PUT /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}/default.json

Sets the default address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-2020-04>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

GET /admin/api/2020-07/customers/{customer_id}/addresses.json

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-2020-07>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2020-07/customers/{customer_id}/addresses.json

Creates a new address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-2020-07>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json

Retrieves details a single customer address.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-2020-07>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT /admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json

Updates an existing customer address.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-2020-07>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

DELETE /admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json

Removes an address from a customer's address list.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT /admin/api/2020-07/customers/{customer_id}/addresses/set.json

Performs bulk operations for multiple customer addresses.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-2020-07>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_ids[]	integer	query		address_ids[]
operation	string	query		operation

Responses

200

PUT /admin/api/2020-07/customers/{customer_id}/addresses/{address_id}/default.json

Sets the default address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-2020-07>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

GET /admin/api/2020-10/customers/{customer_id}/addresses.json

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-2020-10>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2020-10/customers/{customer_id}/addresses.json

Creates a new address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-2020-10>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json

Retrieves details a single customer address.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-2020-10>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT /admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json

Updates an existing customer address.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-2020-10>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

DELETE /admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json

Removes an address from a customer's address list.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT /admin/api/2020-10/customers/{customer_id}/addresses/set.json

Performs bulk operations for multiple customer addresses.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-2020-10>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_ids[]	integer	query		address_ids[]
operation	string	query		operation

Responses

200

PUT /admin/api/2020-10/customers/{customer_id}/addresses/{address_id}/default.json

Sets the default address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-2020-10>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

GET /admin/api/2021-01/customers/{customer_id}/addresses.json

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-2021-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST /admin/api/2021-01/customers/{customer_id}/addresses.json

Creates a new address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-2021-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET /admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json

Retrieves details a single customer address.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-2021-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT /admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json

Updates an existing customer address.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-2021-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

DELETE /admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json

Removes an address from a customer's address list.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT /admin/api/2021-01/customers/{customer_id}/addresses/set.json

Performs bulk operations for multiple customer addresses.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-2021-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_ids[]	integer	query		address_ids[]
operation	string	query		operation

Responses

200

PUT /admin/api/2021-01/customers/{customer_id}/addresses/{address_id}/default.json

Sets the default address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-2021-01>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

GET

/admin/api/unstable/customers/{customer_id}/addresses.json

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-unstable>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

POST

/admin/api/unstable/customers/{customer_id}/addresses.json

Creates a new address for a customer.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-unstable>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id

Responses

200

GET

/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json

Retrieves details a single customer address.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-unstable>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT

/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json

Updates an existing customer address.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-unstable>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

DELETE

/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json

Removes an address from a customer's address list.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-unstable>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

PUT /admin/api/unstable/customers/{customer_id}/addresses/set.json

Performs bulk operations for multiple customer addresses.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-unstable>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_ids[]	integer	query		address_ids[]
operation	string	query		operation

Responses

200

PUT /admin/api/unstable/customers/{customer_id}/addresses/{address_id}/default.json

Sets the default address for a customer.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-unstable>

Parameters

Name	Type	In	Required	Description
customer_id	string	path	required	customer_id
address_id	string	path	required	address_id

Responses

200

GET /admin/api/2020-01/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-2020-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-01/customer_saved_searches.json

Creates a customer saved search.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-2020-01>

Responses

200

GET /admin/api/2020-01/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-2020-01>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID

Responses

200

GET /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-2020-01>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-2020-01>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

DELETE /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

GET /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-2020-01>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-04/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-2020-04>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-04/customer_saved_searches.json

Creates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-2020-04>

Responses

200

GET /admin/api/2020-04/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-2020-04>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID

Responses

200

GET /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-2020-04>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-2020-04>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

DELETE /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

GET /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-2020-04>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-07/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-2020-07

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-07/customer_saved_searches.json

Creates a customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-2020-07

Responses

200

GET

/admin/api/2020-07/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-2020-07

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID

Responses

200

GET

/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-2020-07

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-2020-07

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

DELETE

/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-2020-07

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

GET /admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-2020-07>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-10/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-2020-10>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-10/customer_saved_searches.json

Creates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-2020-10>

Responses

200

GET /admin/api/2020-10/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-2020-10>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID

Responses

200

GET /admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-2020-10>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-2020-10>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

DELETE /admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

GET /admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-2020-10>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2021-01/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-2021-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2021-01/customer_saved_searches.json

Creates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-2021-01>

Responses

200

GET /admin/api/2021-01/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-2021-01>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID

Responses

200

GET /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-2021-01>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-2021-01>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

DELETE /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

GET /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-2021-01>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/unstable/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-unstable>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/unstable/customer_saved_searches.json

Creates a customer saved search.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-unstable>

Responses

200

GET /admin/api/unstable/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-unstable>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID

Responses

200

GET /admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-unstable>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-unstable>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

DELETE /admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-unstable>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id

Responses

200

GET /admin/api/unstable/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.
<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-unstable>

Parameters

Name	Type	In	Required	Description
customer_saved_search_id	string	path	required	customer_saved_search_id
order		query		Set the field and direction by which to order results. (default: last_order_date DESC)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

GET

/admin/api/2021-01/deprecated_api_calls.json

Retrieves a list of deprecated API calls made by the authenticated private app in the past 30 days.
https://shopify.dev/docs/admin-api/rest/reference/deprecated_api_calls#index-2021-01

Responses

200

GET

/admin/api/unstable/deprecated_api_calls.json

Retrieves a list of deprecated API calls made by the authenticated private app in the past 30 days.
https://shopify.dev/docs/admin-api/rest/reference/deprecated_api_calls#index-unstable

Responses

200

GET

/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-2020-01>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

POST

/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code
<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-2020-01>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

GET

/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code
<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-2020-01>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

PUT

/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code
<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-2020-01>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

DELETE /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

GET /admin/api/2020-01/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-2020-01>

Parameters

Name	Type	In	Required	Description
code	integer	query		code

Responses

200

POST /admin/api/2020-01/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-2020-01

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

GET /admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-2020-01

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
batch_id	string	path	required	batch_id

Responses

200

GET /admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-2020-01

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
batch_id	string	path	required	batch_id

Responses

200

GET /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-2020-04>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

POST /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-2020-04>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

GET /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-2020-04>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

PUT /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-2020-04>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

DELETE /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

GET /admin/api/2020-04/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-2020-04>

Parameters

Name	Type	In	Required	Description
code	integer	query		code

Responses

200

POST /admin/api/2020-04/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-2020-04

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

GET /admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-2020-04

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
batch_id	string	path	required	batch_id

Responses

200

GET /admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-2020-04

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
batch_id	string	path	required	batch_id

Responses

200

GET /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-2020-07>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

POST /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-2020-07>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

GET /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-2020-07>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

PUT /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-2020-07>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

DELETE /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

GET /admin/api/2020-07/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-2020-07>

Parameters

Name	Type	In	Required	Description
code	integer	query		code

Responses

200

POST /admin/api/2020-07/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-2020-07

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

price_rule_id string path required price_rule_id

Responses

200

GET /admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job
https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-2020-07

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
batch_id	string	path	required	batch_id

Responses

200

GET /admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-2020-07

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
batch_id	string	path	required	batch_id

Responses

200

GET /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-2020-10>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

POST /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code
<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-2020-10>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

GET /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code
<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-2020-10>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

PUT /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-2020-10>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

DELETE /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

GET /admin/api/2020-10/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-2020-10>

Parameters

Name	Type	In	Required	Description
code	integer	query		code

Responses

200

POST /admin/api/2020-10/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-2020-10

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

GET /admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-2020-10

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
batch_id	string	path	required	batch_id

Responses

200

GET /admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-2020-10

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
batch_id	string	path	required	batch_id

Responses

200

GET /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-2021-01>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

POST /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-2021-01>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

GET /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-2021-01>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

PUT /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-2021-01>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

DELETE /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

GET /admin/api/2021-01/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-2021-01>

Parameters

Name	Type	In	Required	Description
code	integer	query		code

Responses

200

POST /admin/api/2021-01/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-2021-01

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

GET /admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-2021-01

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
batch_id	string	path	required	batch_id

Responses

200

GET /admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-2021-01

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
batch_id	string	path	required	batch_id

Responses

200

GET /admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-unstable>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

POST /admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-unstable>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id

Responses

200

GET /admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-unstable>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

PUT /admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-unstable>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

DELETE /admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-unstable>

Parameters

Name	Type	In	Required	Description
price_rule_id	string	path	required	price_rule_id
discount_code_id	string	path	required	discount_code_id

Responses

200

GET /admin/api/unstable/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-unstable>

Parameters

Name	Type	In	Required	Description
code	integer	query		code

Responses

200

POST /admin/api/unstable/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a `discount_code_creation` object that can be monitored for completion. Response fields that are specific to the batch endpoint include: `status`: The state of the discount code creation job. Possible values are: `queued`: The job is acknowledged, but not started. `running`: The job is in process. `completed`: The job has finished. `codes_count`: The number of discount codes to create. `imported_count`: The number of discount codes created successfully. `failed_count`: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. `logs`: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-unstable

Parameters

Name	Type	In	Required	Description
<code>price_rule_id</code>	string	path	required	<code>price_rule_id</code>

Responses

200

GET /admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-unstable

Parameters

Name	Type	In	Required	Description
<code>price_rule_id</code>	string	path	required	<code>price_rule_id</code>
<code>batch_id</code>	string	path	required	<code>batch_id</code>

Responses

200

GET /admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated `id` field. Discount codes that encountered errors during the creation process include a populated `errors` field.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-unstable

Parameters

Name	Type	In	Required	Description
<code>price_rule_id</code>	string	path	required	<code>price_rule_id</code>
<code>batch_id</code>	string	path	required	<code>batch_id</code>

Responses

200

GET /admin/api/2020-01/events.json

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/events/event#index-2020-01>

Parameters

Name	Type	In	Required	Description
<code>limit</code>		query		The number of results to show. (default: 50, maximum: 250)
<code>since_id</code>		query		Show only results after the specified ID.
<code>created_at_min</code>		query		Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
<code>created_at_max</code>		query		Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
<code>filter</code>		query		Show events specified in this filter.
<code>verb</code>		query		Show events of a certain type.
<code>fields</code>		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-01/events/{event_id}.json

Retrieves a single event by its ID

<https://shopify.dev/docs/admin-api/rest/reference/events/event#show-2020-01>

Parameters

Name	Type	In	Required	Description
event_id fields	string	path query	required	event_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-01/events/count.json

Retrieves a count of events

<https://shopify.dev/docs/admin-api/rest/reference/events/event#count-2020-01>

Parameters

Name	Type	In	Required	Description
created_at_min		query		Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

200

GET /admin/api/2020-04/events.json

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/events/event#index-2020-04>

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to show. (default: 50, maximum: 250)
since_id		query		Show only results after the specified ID.
created_at_min		query		Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
filter		query		Show events specified in this filter.
verb		query		Show events of a certain type.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-04/events/{event_id}.json

Retrieves a single event by its ID

<https://shopify.dev/docs/admin-api/rest/reference/events/event#show-2020-04>

Parameters

Name	Type	In	Required	Description
event_id fields	string	path query	required	event_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-04/events/count.json

Retrieves a count of events

<https://shopify.dev/docs/admin-api/rest/reference/events/event#count-2020-04>

Parameters

Name	Type	In	Required	Description
created_at_min		query		Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

200

GET /admin/api/2020-07/events.json

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/event#index-2020-07>

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to show. (default: 50, maximum: 250)
since_id		query		Show only results after the specified ID.
created_at_min		query		Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
filter		query		Show events specified in this filter.
verb		query		Show events of a certain type.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-07/events/{event_id}.json

Retrieves a single event by its ID

<https://shopify.dev/docs/admin-api/rest/reference/events/event#show-2020-07>

Parameters

Name	Type	In	Required	Description
event_id	string	path	required	event_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-07/events/count.json

Retrieves a count of events

<https://shopify.dev/docs/admin-api/rest/reference/events/event#count-2020-07>

Parameters

Name	Type	In	Required	Description
created_at_min		query		Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

200

GET /admin/api/2020-10/events.json

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/event#index-2020-10>

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to show. (default: 50, maximum: 250)
since_id		query		Show only results after the specified ID.
created_at_min		query		Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
filter		query		Show events specified in this filter.
verb		query		Show events of a certain type.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-10/events/{event_id}.json

Retrieves a single event by its ID

https://shopify.dev/docs/admin-api/rest/reference/events/event#show-2020-10

Parameters

Name	Type	In	Required	Description
event_id	string	path	required	event_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-10/events/count.json

Retrieves a count of events

https://shopify.dev/docs/admin-api/rest/reference/events/event#count-2020-10

Parameters

Name	Type	In	Required	Description
created_at_min		query		Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

200

GET /admin/api/2021-01/events.json

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/events/event#index-2021-01

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to show. (default: 50, maximum: 250)
since_id		query		Show only results after the specified ID.
created_at_min		query		Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
filter		query		Show events specified in this filter.
verb		query		Show events of a certain type.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2021-01/events/{event_id}.json

Retrieves a single event by its ID

https://shopify.dev/docs/admin-api/rest/reference/events/event#show-2021-01

Parameters

Name	Type	In	Required	Description
event_id	string	path	required	event_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2021-01/events/count.json

Retrieves a count of events

https://shopify.dev/docs/admin-api/rest/reference/events/event#count-2021-01

Parameters

Name	Type	In	Required	Description
created_at_min		query		Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

GET

/admin/api/unstable/events.json

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/events/event#index-unstable

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to show. (default: 50, maximum: 250)
since_id		query		Show only results after the specified ID.
created_at_min		query		Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
filter		query		Show events specified in this filter.
verb		query		Show events of a certain type.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET

/admin/api/unstable/events/{event_id}.json

Retrieves a single event by its ID

https://shopify.dev/docs/admin-api/rest/reference/events/event#show-unstable

Parameters

Name	Type	In	Required	Description
event_id	string	path	required	event_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET

/admin/api/unstable/events/count.json

Retrieves a count of events

https://shopify.dev/docs/admin-api/rest/reference/events/event#count-unstable

Parameters

Name	Type	In	Required	Description
created_at_min		query		Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

200

GET

/admin/api/2020-01/webhooks.json

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-2020-01

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max		query		Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min		query		Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields		query		Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit		query		Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id		query		Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.
topic		query		Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>

updated_at_min	query	Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).
updated_at_max	query	Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST /admin/api/2020-01/webhooks.json

Create a new webhook subscription by specifying both an address and a topic
<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-2020-01>

Parameters

Name	Type	In	Required	Description
format		query		Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Responses

200

GET /admin/api/2020-01/webhooks/count.json

Retrieves a count of existing webhook subscriptions
<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-2020-01>

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI. Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
topic		query		

Responses

200

GET /admin/api/2020-01/webhooks/{webhook_id}.json

Retrieves a single webhook subscription
<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-2020-01>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
fields		query		

Responses

200

PUT /admin/api/2020-01/webhooks/{webhook_id}.json

Update a webhook subscription's topic or address URIs
<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-2020-01>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

DELETE /admin/api/2020-01/webhooks/{webhook_id}.json

Delete a webhook subscription
<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

GET

/admin/api/2020-04/webhooks.json

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-2020-04>

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max		query		Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min		query		Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields		query		Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit		query		Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id		query		Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.
topic		query		Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
updated_at_min		query		Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST

/admin/api/2020-04/webhooks.json

Create a new webhook subscription by specifying both an address and a topic

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-2020-04>

Parameters

Name	Type	In	Required	Description
format		query		Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Responses

200

GET

/admin/api/2020-04/webhooks/count.json

Retrieves a count of existing webhook subscriptions

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-2020-04>

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI.
topic		query		Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>

Responses

200

GET

/admin/api/2020-04/webhooks/{webhook_id}.json

Retrieves a single webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-2020-04>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id
fields		query		Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.

Responses

PUT

/admin/api/2020-04/webhooks/{webhook_id}.json

Update a webhook subscription's topic or address URIs

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-2020-04>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

DELETE

/admin/api/2020-04/webhooks/{webhook_id}.json

Delete a webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

GET

/admin/api/2020-07/webhooks.json

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-2020-07>

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max		query		Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min		query		Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields		query		Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit		query		Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id		query		Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.
topic		query		Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
updated_at_min		query		Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST

/admin/api/2020-07/webhooks.json

Create a new webhook subscription by specifying both an address and a topic

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-2020-07>

Parameters

Name	Type	In	Required	Description
format		query		Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Responses

200

GET

/admin/api/2020-07/webhooks/count.json

Retrieves a count of existing webhook subscriptions

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-2020-07

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI.
topic		query		Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>

Responses

200

GET

/admin/api/2020-07/webhooks/{webhook_id}.json

Retrieves a single webhook subscription

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-2020-07

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id
fields		query		Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.

Responses

200

PUT

/admin/api/2020-07/webhooks/{webhook_id}.json

Update a webhook subscription's topic or address URIs

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-2020-07

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

DELETE

/admin/api/2020-07/webhooks/{webhook_id}.json

Delete a webhook subscription

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-2020-07

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

GET

/admin/api/2020-10/webhooks.json

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-2020-10

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max		query		Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min		query		Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields		query		Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit		query		Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id		query		Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.

topic	query	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
updated_at_min	query	Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).
updated_at_max	query	Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST /admin/api/2020-10/webhooks.json

Create a new webhook subscription by specifying both an address and a topic

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-2020-10>

Parameters

Name	Type	In	Required	Description
format		query		Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Responses

200

GET /admin/api/2020-10/webhooks/count.json

Retrieves a count of existing webhook subscriptions

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-2020-10>

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI.
topic		query		Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>

Responses

200

GET /admin/api/2020-10/webhooks/{webhook_id}.json

Retrieves a single webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-2020-10>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id
fields		query		Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.

Responses

200

PUT /admin/api/2020-10/webhooks/{webhook_id}.json

Update a webhook subscription's topic or address URIs

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-2020-10>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

DELETE /admin/api/2020-10/webhooks/{webhook_id}.json

Delete a webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

GET /admin/api/2021-01/webhooks.json

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-2021-01>

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max		query		Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min		query		Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields		query		Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit		query		Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id		query		Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.
topic		query		Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
updated_at_min		query		Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST /admin/api/2021-01/webhooks.json

Create a new webhook subscription by specifying both an address and a topic

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-2021-01>

Parameters

Name	Type	In	Required	Description
format		query		Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Responses

200

GET /admin/api/2021-01/webhooks/count.json

Retrieves a count of existing webhook subscriptions

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-2021-01>

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI.
topic		query		Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>

Responses

200

GET /admin/api/2021-01/webhooks/{webhook_id}.json

Retrieves a single webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-2021-01>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

fields query Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.

Responses

200

PUT /admin/api/2021-01/webhooks/{webhook_id}.json

Update a webhook subscription's topic or address URIs

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-2021-01>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

DELETE /admin/api/2021-01/webhooks/{webhook_id}.json

Delete a webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

GET /admin/api/unstable/webhooks.json

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-unstable>

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max		query		Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min		query		Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields		query		Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit		query		Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id		query		Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.
topic		query		Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
updated_at_min		query		Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST /admin/api/unstable/webhooks.json

Create a new webhook subscription by specifying both an address and a topic

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-unstable>

Parameters

Name	Type	In	Required	Description
format		query		Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Responses

GET

/admin/api/unstable/webhooks/count.json

Retrieves a count of existing webhook subscriptions

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-unstable>

Parameters

Name	Type	In	Required	Description
address		query		Retrieve webhook subscriptions that send the POST request to this URI. Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
topic		query		

Responses

200

GET

/admin/api/unstable/webhooks/{webhook_id}.json

Retrieves a single webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-unstable>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id
fields		query		Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.

Responses

200

PUT

/admin/api/unstable/webhooks/{webhook_id}.json

Update a webhook subscription's topic or address URIs

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-unstable>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

DELETE

/admin/api/unstable/webhooks/{webhook_id}.json

Delete a webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-unstable>

Parameters

Name	Type	In	Required	Description
webhook_id	string	path	required	webhook_id

Responses

200

GET

/admin/api/2020-01/inventory_items.json

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-2020-01>

Parameters

Name	Type	In	Required	Description
ids		query		Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)
limit		query		
ids	integer	query		The maximum number of results to show. (default: 50, maximum: 250)

Responses

200

GET /admin/api/2020-01/inventory_items/{inventory_item_id}.json

Retrieves a single inventory item by ID

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-2020-01>

Parameters

Name	Type	In	Required	Description
inventory_item_id	string	path	required	inventory_item_id

Responses

200

PUT /admin/api/2020-01/inventory_items/{inventory_item_id}.json

Updates an existing inventory item

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-2020-01>

Parameters

Name	Type	In	Required	Description
inventory_item_id	string	path	required	inventory_item_id

Responses

200

GET /admin/api/2020-04/inventory_items.json

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-2020-04>

Parameters

Name	Type	In	Required	Description
ids required		query		Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
ids	integer	query		ids

Responses

200

GET /admin/api/2020-04/inventory_items/{inventory_item_id}.json

Retrieves a single inventory item by ID

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-2020-04>

Parameters

Name	Type	In	Required	Description
inventory_item_id	string	path	required	inventory_item_id

Responses

200

PUT /admin/api/2020-04/inventory_items/{inventory_item_id}.json

Updates an existing inventory item

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-2020-04>

Parameters

Name	Type	In	Required	Description
inventory_item_id	string	path	required	inventory_item_id

Responses

200

GET /admin/api/2020-07/inventory_items.json

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-2020-07>

Parameters

Name	Type	In	Required	Description
ids required		query		Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)
limit ids	integer	query		The maximum number of results to show. (default: 50, maximum: 250)

Responses

200

GET /admin/api/2020-07/inventory_items/{inventory_item_id}.json

Retrieves a single inventory item by ID

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-2020-07>

Parameters

Name	Type	In	Required	Description
inventory_item_id	string	path	required	inventory_item_id

Responses

200

PUT /admin/api/2020-07/inventory_items/{inventory_item_id}.json

Updates an existing inventory item

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-2020-07>

Parameters

Name	Type	In	Required	Description
inventory_item_id	string	path	required	inventory_item_id

Responses

200

GET /admin/api/2020-10/inventory_items.json

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-2020-10>

Parameters

Name	Type	In	Required	Description
ids required		query		Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)
limit ids	integer	query		The maximum number of results to show. (default: 50, maximum: 250)

Responses

200

GET /admin/api/2020-10/inventory_items/{inventory_item_id}.json

Retrieves a single inventory item by ID

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-2020-10>

Parameters

Name	Type	In	Required	Description
inventory_item_id	string	path	required	inventory_item_id

Responses

200

PUT /admin/api/2020-10/inventory_items/{inventory_item_id}.json

Updates an existing inventory item

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-2020-10>

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

inventory_item_id string path required inventory_item_id

Responses

200

GET /admin/api/2021-01/inventory_items.json

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-2021-01>

Parameters

Name	Type	In	Required	Description
ids required		query		Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)
limit ids	integer	query		The maximum number of results to show. (default: 50, maximum: 250) ids

Responses

200

GET /admin/api/2021-01/inventory_items/{inventory_item_id}.json

Retrieves a single inventory item by ID
<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-2021-01>

Parameters

Name	Type	In	Required	Description
inventory_item_id	string	path	required	inventory_item_id

Responses

200

PUT /admin/api/2021-01/inventory_items/{inventory_item_id}.json

Updates an existing inventory item
<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-2021-01>

Parameters

Name	Type	In	Required	Description
inventory_item_id	string	path	required	inventory_item_id

Responses

200

GET /admin/api/unstable/inventory_items.json

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-unstable>

Parameters

Name	Type	In	Required	Description
ids required		query		Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)
limit ids	integer	query		The maximum number of results to show. (default: 50, maximum: 250) ids

Responses

200

GET /admin/api/unstable/inventory_items/{inventory_item_id}.json

Retrieves a single inventory item by ID
<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-unstable>

Parameters

Name	Type	In	Required	Description
inventory_item_id	string	path	required	inventory_item_id

Responses

200

PUT /admin/api/unstable/inventory_items/{inventory_item_id}.json

Updates an existing inventory item
<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-unstable>

Parameters

Name	Type	In	Required	Description
inventory_item_id	string	path	required	inventory_item_id

Responses

200

GET /admin/api/2020-01/inventory_levels.json

Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-2020-01>

Parameters

Name	Type	In	Required	Description
inventory_item_ids		query		A comma-separated list of inventory item IDs. (maximum: 50)
location_ids		query		A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
updated_at_min		query		Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

200

DELETE /admin/api/2020-01/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
inventory_item_id required		query		The ID of the inventory item.
location_id required		query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
inventory_item_id	integer	query		inventory_item_id
location_id	integer	query		location_id

Responses

200

POST /admin/api/2020-01/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location
<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#adjust-2020-01>

Parameters

Name	Type	In	Required	Description
inventory_item_id required		query		The ID of the inventory item.
location_id required		query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available_adjustment required		query		The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3decreases the current available quantity by 3.

Responses

200

POST /admin/api/2020-01/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID of the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
relocate_if_necessary		query		Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

POST

/admin/api/2020-01/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-2020-01

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID for the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available	required	query		Sets the available inventory quantity.
disconnect_if_necessary		query		Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

GET

/admin/api/2020-04/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-2020-04

Parameters

Name	Type	In	Required	Description
inventory_item_ids		query		A comma-separated list of inventory item IDs. (maximum: 50)
location_ids		query		A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
updated_at_min		query		Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

200

DELETE

/admin/api/2020-04/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-2020-04

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID for the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
inventory_item_id	integer	query		inventory_item_id
location_id	integer	query		location_id

Responses

200

POST

/admin/api/2020-04/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID of the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available_adjustment		query		The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3decreases the current available quantity by 3.

Responses

200

POST

/admin/api/2020-04/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#connect-2020-04

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID of the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
relocate_if_necessary		query		Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

POST

/admin/api/2020-04/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-2020-04

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID for the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available	required	query		Sets the available inventory quantity.
disconnect_if_necessary		query		Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

GET

/admin/api/2020-07/inventory_levels.json

Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-2020-07

Parameters

Name	Type	In	Required	Description
inventory_item_ids		query		A comma-separated list of inventory item IDs. (maximum: 50)
location_ids		query		A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
updated_at_min		query		Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

200

DELETE

/admin/api/2020-07/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
inventory_item_id		query		The ID for the inventory item.
location_id		query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
inventory_item_id	integer	query		inventory_item_id location_id
location_id	integer	query		

Responses

200

POST

/admin/api/2020-07/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#adjust-2020-07>

Parameters

Name	Type	In	Required	Description
inventory_item_id		query		The ID of the inventory item.
location_id		query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available_adjustment		query		The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3decreases the current available quantity by 3.

Responses

200

POST

/admin/api/2020-07/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#connect-2020-07>

Parameters

Name	Type	In	Required	Description
inventory_item_id		query		The ID of the inventory item.
location_id		query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
relocate_if_necessary		query		Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

POST

/admin/api/2020-07/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-2020-07>

Parameters

Name	Type	In	Required	Description
inventory_item_id		query		The ID for the inventory item.
location_id		query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available		query		Sets the available inventory quantity.
disconnect_if_necessary		query		Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

GET

/admin/api/2020-10/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-2020-10>

Parameters

Name	Type	In	Required	Description
<code>inventory_item_ids</code> <code>location_ids</code>		query query		A comma-separated list of inventory item IDs. (maximum: 50) A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
<code>limit</code> <code>updated_at_min</code>		query query		The maximum number of results to show. (default: 50, maximum: 250) Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

200

DELETE

/admin/api/2020-10/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
<code>inventory_item_id</code> required <code>location_id</code> required		query query		The ID for the inventory item. The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
<code>inventory_item_id</code> <code>location_id</code>	integer integer	query query		<code>inventory_item_id</code> <code>location_id</code>

Responses

200

POST

/admin/api/2020-10/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#adjust-2020-10>

Parameters

Name	Type	In	Required	Description
<code>inventory_item_id</code> required <code>location_id</code> required		query query		The ID of the inventory item. The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
<code>available_adjustment</code> required		query		The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3decreases the current available quantity by 3.

Responses

200

POST

/admin/api/2020-10/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#connect-2020-10>

Parameters

Name	Type	In	Required	Description
<code>inventory_item_id</code> required <code>location_id</code> required		query query		The ID of the inventory item. The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
<code>relocate_if_necessary</code>		query		Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

POST

/admin/api/2020-10/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-2020-10>

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID for the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available	required	query		Sets the available inventory quantity.
disconnect_if_necessary		query		Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

GET

/admin/api/2021-01/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-2021-01>

Parameters

Name	Type	In	Required	Description
inventory_item_ids		query		A comma-separated list of inventory item IDs. (maximum: 50)
location_ids		query		A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
updated_at_min		query		Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

200

DELETE

/admin/api/2021-01/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID for the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
inventory_item_id	integer	query		inventory_item_id
location_id	integer	query		location_id

Responses

200

POST

/admin/api/2021-01/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#adjust-2021-01>

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID of the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available_adjustment		query		The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3 decreases the current available quantity by 3.

Responses

200

POST

/admin/api/2021-01/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#connect-2021-01>

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID of the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
relocate_if_necessary		query		Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

POST /admin/api/2021-01/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-2021-01>

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID for the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available	required	query		Sets the available inventory quantity.
disconnect_if_necessary		query		Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

GET /admin/api/unstable/inventory_levels.json

Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-unstable>

Parameters

Name	Type	In	Required	Description
inventory_item_ids		query		A comma-separated list of inventory item IDs. (maximum: 50)
location_ids		query		A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
updated_at_min		query		Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

200

DELETE /admin/api/unstable/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-unstable>

Parameters

Name	Type	In	Required	Description
inventory_item_id	required	query		The ID for the inventory item.
location_id	required	query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
inventory_item_id	integer	query		inventory_item_id
location_id	integer	query		location_id

Responses

200

POST /admin/api/unstable/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#adjust-unstable>

Parameters

Name	Type	In	Required	Description
inventory_item_id required		query		The ID of the inventory item.
location_id required		query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available_adjustment required		query		The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3decreases the current available quantity by 3.

Responses

200

POST

/admin/api/unstable/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#connect-unstable>

Parameters

Name	Type	In	Required	Description
inventory_item_id required		query		The ID of the inventory item.
location_id required		query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
relocate_if_necessary		query		Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

POST

/admin/api/unstable/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-unstable>

Parameters

Name	Type	In	Required	Description
inventory_item_id required		query		The ID for the inventory item.
location_id required		query		The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available required		query		Sets the available inventory quantity.
disconnect_if_necessary		query		Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Responses

200

GET

/admin/api/2020-01/locations.json

Retrieves a list of locations

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-2020-01>

Responses

200

GET

/admin/api/2020-01/locations/{location_id}.json

Retrieves a single location by its ID

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-2020-01>

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

GET

/admin/api/2020-01/locations/count.json

Retrieves a count of locations

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-2020-01>

Responses

200

GET

/admin/api/2020-01/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-2020-01

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

200

GET

/admin/api/2020-04/locations.json

Retrieves a list of locations

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-2020-04>

Responses

200

GET

/admin/api/2020-04/locations/{location_id}.json

Retrieves a single location by its ID

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-2020-04>

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

200

GET

/admin/api/2020-04/locations/count.json

Retrieves a count of locations

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-2020-04>

Responses

200

GET

/admin/api/2020-04/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-2020-04

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

200

GET

/admin/api/2020-07/locations.json

Retrieves a list of locations

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-2020-07>

Responses

200

GET

/admin/api/2020-07/locations/{location_id}.json

Retrieves a single location by its ID
<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-2020-07>

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

200

GET

/admin/api/2020-07/locations/count.json

Retrieves a count of locations
<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-2020-07>

Responses

200

GET

/admin/api/2020-07/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).
https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-2020-07

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

200

GET

/admin/api/2020-10/locations.json

Retrieves a list of locations
<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-2020-10>

Responses

200

GET

/admin/api/2020-10/locations/{location_id}.json

Retrieves a single location by its ID
<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-2020-10>

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

200

GET

/admin/api/2020-10/locations/count.json

Retrieves a count of locations
<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-2020-10>

Responses

200

GET

/admin/api/2020-10/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).
https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-2020-10

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

200

GET

/admin/api/2021-01/locations.json

Retrieves a list of locations
<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-2021-01>

Responses

200

GET

/admin/api/2021-01/locations/{location_id}.json

Retrieves a single location by its ID
<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-2021-01>

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

200

GET

/admin/api/2021-01/locations/count.json

Retrieves a count of locations
<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-2021-01>

Responses

200

GET

/admin/api/2021-01/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).
https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-2021-01

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

200

GET

/admin/api/unstable/locations.json

Retrieves a list of locations
<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-unstable>

Responses

200

GET

/admin/api/unstable/locations/{location_id}.json

Retrieves a single location by its ID
<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-unstable>

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

200

GET /admin/api/unstable/locations/count.json

Retrieves a count of locations

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-unstable>

Responses

200

GET /admin/api/unstable/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-unstable

Parameters

Name	Type	In	Required	Description
location_id	string	path	required	location_id

Responses

200

GET /admin/api/2020-01/metafields.json

Retrieves a list of metafields that belong to a Product Image resource.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#index-2020-01>

Parameters

Name	Type	In	Required	Description
metafield[owner_id]	integer	query		metafield[owner_id]
metafield[owner_resource]	string	query		metafield[owner_resource]

Responses

200

POST /admin/api/2020-01/metafields.json

Creates a new metafield for a resource.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#create-2020-01>

Responses

200

GET /admin/api/2020-01/metafields/count.json

Retrieves a count of a resource's metafields.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#count-2020-01>

Responses

200

GET /admin/api/2020-01/metafields/{metafield_id}.json

Retrieves a single metafield from a resource by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#show-2020-01>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-01/metafields/{metafield_id}.json

Updates a metafield.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#update-2020-01>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

DELETE /admin/api/2020-01/metafields/{metafield_id}.json

Deletes a metafield by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

GET /admin/api/2020-04/metafields.json

Retrieves a list of metafields that belong to a Product Image resource.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#index-2020-04>

Parameters

Name	Type	In	Required	Description
metafield[owner_id]	integer	query		metafield[owner_id]
metafield[owner_resource]	string	query		metafield[owner_resource]

Responses

200

POST /admin/api/2020-04/metafields.json

Creates a new metafield for a resource.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#create-2020-04>

Responses

200

GET /admin/api/2020-04/metafields/count.json

Retrieves a count of a resource's metafields.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#count-2020-04>

Responses

200

GET /admin/api/2020-04/metafields/{metafield_id}.json

Retrieves a single metafield from a resource by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#show-2020-04>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-04/metafields/{metafield_id}.json

Updates a metafield.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#update-2020-04>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

DELETE

/admin/api/2020-04/metafields/{metafield_id}.json

Deletes a metafield by its ID.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

GET

/admin/api/2020-07/metafields.json

Retrieves a list of metafields that belong to a Product Image resource.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#index-2020-07>

Parameters

Name	Type	In	Required	Description
metafield[owner_id]	integer	query		metafield[owner_id]
metafield[owner_resource]	string	query		metafield[owner_resource]

Responses

200

POST

/admin/api/2020-07/metafields.json

Creates a new metafield for a resource.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#create-2020-07>

Responses

200

GET

/admin/api/2020-07/metafields/count.json

Retrieves a count of a resource's metafields.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#count-2020-07>

Responses

200

GET

/admin/api/2020-07/metafields/{metafield_id}.json

Retrieves a single metafield from a resource by its ID.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#show-2020-07>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-07/metafields/{metafield_id}.json

Updates a metafield.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#update-2020-07>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

DELETE /admin/api/2020-07/metafields/{metafield_id}.json

Deletes a metafield by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

GET /admin/api/2020-10/metafields.json

Retrieves a list of metafields that belong to a Product Image resource.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#index-2020-10>

Parameters

Name	Type	In	Required	Description
metafield[owner_id]	integer	query		metafield[owner_id]
metafield[owner_resource]	string	query		metafield[owner_resource]

Responses

200

POST /admin/api/2020-10/metafields.json

Creates a new metafield for a resource.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#create-2020-10>

Responses

200

GET /admin/api/2020-10/metafields/count.json

Retrieves a count of a resource's metafields.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#count-2020-10>

Responses

200

GET /admin/api/2020-10/metafields/{metafield_id}.json

Retrieves a single metafield from a resource by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#show-2020-10>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-10/metafields/{metafield_id}.json

Updates a metafield.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#update-2020-10>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

DELETE /admin/api/2020-10/metafields/{metafield_id}.json

Deletes a metafield by its ID.

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

GET

/admin/api/2021-01/metafields.json

Retrieves a list of metafields that belong to a Product Image resource.

https://shopify.dev/docs/admin-api/rest/reference/metafield#index-2021-01

Parameters

Name	Type	In	Required	Description
metafield[owner_id]	integer	query		metafield[owner_id]
metafield[owner_resource]	string	query		metafield[owner_resource]

Responses

200

POST

/admin/api/2021-01/metafields.json

Creates a new metafield for a resource.

https://shopify.dev/docs/admin-api/rest/reference/metafield#create-2021-01

Responses

200

GET

/admin/api/2021-01/metafields/count.json

Retrieves a count of a resource's metafields.

https://shopify.dev/docs/admin-api/rest/reference/metafield#count-2021-01

Responses

200

GET

/admin/api/2021-01/metafields/{metafield_id}.json

Retrieves a single metafield from a resource by its ID.

https://shopify.dev/docs/admin-api/rest/reference/metafield#show-2021-01

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2021-01/metafields/{metafield_id}.json

Updates a metafield.

https://shopify.dev/docs/admin-api/rest/reference/metafield#update-2021-01

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

DELETE

/admin/api/2021-01/metafields/{metafield_id}.json

Deletes a metafield by its ID.

https://shopify.dev/docs/admin-api/rest/reference/metafield#destroy-2021-01

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

GET

/admin/api/unstable/metafields.json

Retrieves a list of metafields that belong to a Product Image resource.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#index-unstable>

Parameters

Name	Type	In	Required	Description
metafield[owner_id]	integer	query		metafield[owner_id]
metafield[owner_resource]	string	query		metafield[owner_resource]

Responses

200

POST

/admin/api/unstable/metafields.json

Creates a new metafield for a resource.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#create-unstable>

Responses

200

GET

/admin/api/unstable/metafields/count.json

Retrieves a count of a resource's metafields.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#count-unstable>

Responses

200

GET

/admin/api/unstable/metafields/{metafield_id}.json

Retrieves a single metafield from a resource by its ID.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#show-unstable>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/unstable/metafields/{metafield_id}.json

Updates a metafield.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#update-unstable>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

DELETE

/admin/api/unstable/metafields/{metafield_id}.json

Deletes a metafield by its ID.
<https://shopify.dev/docs/admin-api/rest/reference/metafield#destroy-unstable>

Parameters

Name	Type	In	Required	Description
metafield_id	string	path	required	metafield_id

Responses

200

GET /admin/api/2020-01/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-2020-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle		query		Retrieve an article with a specific handle.
tag		query		Filter articles with a specific tag.
author		query		Filter articles by article author.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-01/blogs/{blog_id}/articles.json

Creates an article for a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-2020-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id

Responses

200

GET /admin/api/2020-01/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#count-2020-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
created_at_min		query		Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

200

GET /admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#show-2020-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json

Updates an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#update-2020-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

DELETE /admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

GET /admin/api/2020-01/articles/authors.json

Retrieves a list all of article authors

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#authors-2020-01>

Responses

200

GET /admin/api/2020-01/articles/tags.json

Retrieves a list of all the tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#tags-2020-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of tags to retrieve.
popular		query		A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

200

GET /admin/api/2020-04/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-2020-04>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle		query		Retrieve an article with a specific handle.

tag

author

fields

query

query

query

Filter articles with a specific tag.

Filter articles by article author.

Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-04/blogs/{blog_id}/articles.json

Creates an article for a blog

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-2020-04

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id

Responses

200

GET

/admin/api/2020-04/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#count-2020-04

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
created_at_min		query		Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

200

GET

/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#show-2020-04

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json

Updates an article

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#update-2020-04

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

DELETE

/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#destroy-2020-04

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

GET /admin/api/2020-04/articles/authors.json

Retrieves a list all of article authors

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#authors-2020-04>

Responses

200

GET /admin/api/2020-04/articles/tags.json

Retrieves a list of all the tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#tags-2020-04>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of tags to retrieve.
popular		query		A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

200

GET /admin/api/2020-07/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-2020-07>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle		query		Retrieve an article with a specific handle.
tag		query		Filter articles with a specific tag.
author		query		Filter articles by article author.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-07/blogs/{blog_id}/articles.json

Creates an article for a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-2020-07>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id

Responses

200

GET /admin/api/2020-07/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
created_at_min		query		Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

200

GET /admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json

Updates an article

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

DELETE /admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

GET /admin/api/2020-07/articles/authors.json

Retrieves a list all of article authors

Responses

200

GET /admin/api/2020-07/articles/tags.json

Retrieves a list of all the tags

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of tags to retrieve.
popular		query		A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

200

GET /admin/api/2020-10/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-2020-10>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle		query		Retrieve an article with a specific handle.
tag		query		Filter articles with a specific tag.
author		query		Filter articles by article author.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-10/blogs/{blog_id}/articles.json

Creates an article for a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-2020-10>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id

Responses

200

GET /admin/api/2020-10/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#count-2020-10>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
created_at_min		query		Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

200

GET /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#show-2020-10>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Updates an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#update-2020-10>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

DELETE /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

GET /admin/api/2020-10/articles/authors.json

Retrieves a list all of article authors

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#authors-2020-10>

Responses

200

GET /admin/api/2020-10/articles/tags.json

Retrieves a list of all the tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#tags-2020-10>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of tags to retrieve.
popular		query		A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

200

GET /admin/api/2021-01/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-2021-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).

updated_at_max	query	Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	query	Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	query	Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	query	Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle	query	Retrieve an article with a specific handle.
tag	query	Filter articles with a specific tag.
author	query	Filter articles by article author.
fields	query	Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2021-01/blogs/{blog_id}/articles.json

Creates an article for a blog
<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-2021-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id

Responses

200

GET

/admin/api/2021-01/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog
<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#count-2021-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
created_at_min		query		Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

200

GET

/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article
<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#show-2021-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json

Updates an article
<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#update-2021-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

DELETE /admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

GET /admin/api/2021-01/articles/authors.json

Retrieves a list all of article authors

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#authors-2021-01>

Responses

200

GET /admin/api/2021-01/articles/tags.json

Retrieves a list of all the tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#tags-2021-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of tags to retrieve.
popular		query		A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

200

GET /admin/api/unstable/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-unstable>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle		query		Retrieve an article with a specific handle.
tag		query		Filter articles with a specific tag.
author		query		Filter articles by article author.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/unstable/blogs/{blog_id}/articles.json

Creates an article for a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-unstable>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id

Responses

200

GET /admin/api/unstable/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#count-unstable>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
created_at_min		query		Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

200

GET /admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#show-unstable>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Updates an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#update-unstable>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

DELETE /admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#destroy-unstable>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
article_id	string	path	required	article_id

Responses

200

GET /admin/api/unstable/articles/authors.json

Retrieves a list all of article authors

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#authors-unstable>

Responses

200

GET /admin/api/unstable/articles/tags.json

Retrieves a list of all the tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#tags-unstable>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of tags to retrieve.
popular		query		A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

200

GET /admin/api/2020-01/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see [Asset properties](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-2020-01>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
fields		query		Show only certain fields, specified by a comma-separated list of field names
asset[key]	string	query		asset[key]

Responses

200

PUT /admin/api/2020-01/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-2020-01>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
src		query		The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key		query		The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Responses

200

DELETE /admin/api/2020-01/themes/{theme_id}/assets.json

Deletes an asset from a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
asset[key]	string	query		asset[key]

Responses

200

GET /admin/api/2020-04/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see [Asset properties](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-2020-04>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
fields		query		Show only certain fields, specified by a comma-separated list of field names
asset[key]	string	query		asset[key]

Responses

200

PUT

/admin/api/2020-04/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-2020-04>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
src		query		The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key		query		The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Responses

200

DELETE

/admin/api/2020-04/themes/{theme_id}/assets.json

Deletes an asset from a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
asset[key]	string	query		asset[key]

Responses

200

GET

/admin/api/2020-07/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-2020-07>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
fields		query		Show only certain fields, specified by a comma-separated list of field names
asset[key]	string	query		asset[key]

Responses

200

PUT

/admin/api/2020-07/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-2020-07>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
src		query		The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key		query		The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Responses

200

DELETE

/admin/api/2020-07/themes/{theme_id}/assets.json

Deletes an asset from a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

theme_id asset[key]	string string	path query	required	theme_id asset[key]
------------------------	------------------	---------------	----------	------------------------

Responses

200

GET /admin/api/2020-10/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-2020-10>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
fields asset[key]	string	query query		Show only certain fields, specified by a comma-separated list of field names asset[key]

Responses

200

PUT /admin/api/2020-10/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-2020-10>

Parameters

Name	Type	In	Required	Description
theme_id src	string	path query	required	theme_id The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key		query		The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Responses

200

DELETE /admin/api/2020-10/themes/{theme_id}/assets.json

Deletes an asset from a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
theme_id asset[key]	string string	path query	required	theme_id asset[key]

Responses

200

GET /admin/api/2021-01/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-2021-01>

Parameters

Name	Type	In	Required	Description
theme_id fields asset[key]	string string	path query query	required	theme_id Show only certain fields, specified by a comma-separated list of field names asset[key]

Responses

200

PUT /admin/api/2021-01/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-2021-01>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
src		query		The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key		query		The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Responses

200

DELETE /admin/api/2021-01/themes/{theme_id}/assets.json

Deletes an asset from a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
asset[key]	string	query		asset[key]

Responses

200

GET /admin/api/unstable/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-unstable>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
fields		query		Show only certain fields, specified by a comma-separated list of field names
asset[key]	string	query		asset[key]

Responses

200

PUT /admin/api/unstable/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-unstable>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
src		query		The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key		query		The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Responses

200

DELETE /admin/api/unstable/themes/{theme_id}/assets.json

Deletes an asset from a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-unstable>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
asset[key]	string	query		asset[key]

Responses

200

GET /admin/api/2020-01/blogs.json

Retrieve a list of all blogs. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#index-2020-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID
handle		query		Filter by blog handle
fields		query		comma-separated list of fields to include in the response

Responses

200

POST /admin/api/2020-01/blogs.json

Create a new blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#create-2020-01>

Responses

200

GET /admin/api/2020-01/blogs/count.json

Get a count of all blogs

<https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#count-2020-01>

Responses

200

GET /admin/api/2020-01/blogs/{blog_id}.json

Get a single blog by its ID

<https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#show-2020-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id
fields		query		comma-separated list of fields to include in the response

Responses

200

PUT /admin/api/2020-01/blogs/{blog_id}.json

Update a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#update-2020-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id

Responses

200

DELETE /admin/api/2020-01/blogs/{blog_id}.json

Delete a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
blog_id	string	path	required	blog_id

Responses

200

GET /admin/api/2020-01/comments.json

Retrieves a list of comments. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#index-2020-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show comments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Show comments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show comments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show comments last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Show comments published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Show comments published before date (format: 2014-04-25T16:15:47-04:00).
fields		query		Show only certain fields, specified by a comma-separated list of field names.
published_status		query		Filter results by their published status. (default: any) published: Show only published comments. unpublished: Show only unpublished comments. any: Show comments of any published status.
status		query		Filter results by their status. pending: Show only pending comments. published: Show only published comments. unapproved: Show only unapproved comments.
article_id	integer	query		article_id
blog_id	integer	query		blog_id

Responses

200

POST

/admin/api/2020-01/comments.json

Creates a comment for an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#create-2020-01>

Responses

200

GET

/admin/api/2020-01/comments/count.json

Retrieves a count of comments

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#count-2020-01>

Parameters

Name	Type	In	Required	Description
created_at_min		query		Count comments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count comments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count comments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count comments last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count comments published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count comments published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Retrieve a count of comments with a given published status. (default: any) published: Count only published comments. unpublished: Count only unpublished comments. any: Count comments of any published status.
status		query		Retrieve a count of comments with a given status. pending: Count pending comments. published: Count published comments. unapproved: Count unapproved comments.
article_id	integer	query		article_id
blog_id	integer	query		blog_id

Responses

200

GET

/admin/api/2020-01/comments/{comment_id}.json

Retrieves a single comment by its ID

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#show-2020-01>

Parameters

Name	Type	In	Required	Description
comment_id	string	path	required	comment_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-01/comments/{comment_id}.json

Updates a comment of an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#update-2020-01>

Parameters

Name	Type	In	Required	Description
comment_id	string	path	required	comment_id

Responses

200

POST /admin/api/2020-01/comments/{comment_id}/spam.json

Marks a comment as spam

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#spam-2020-01>

Parameters

Name	Type	In	Required	Description
comment_id	string	path	required	comment_id

Responses

200

POST /admin/api/2020-01/comments/{comment_id}/not_spam.json

Marks a comment as not spam

https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#not_spam-2020-01

Parameters

Name	Type	In	Required	Description
comment_id	string	path	required	comment_id

Responses

200

POST /admin/api/2020-01/comments/{comment_id}/approve.json

Approves a comment

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#approve-2020-01>

Parameters

Name	Type	In	Required	Description
comment_id	string	path	required	comment_id

Responses

200

POST /admin/api/2020-01/comments/{comment_id}/remove.json

Removes a comment

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#remove-2020-01>

Parameters

Name	Type	In	Required	Description
comment_id	string	path	required	comment_id

Responses

200

POST /admin/api/2020-01/comments/{comment_id}/restore.json

Restores a previously removed comment

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#restore-2020-01>

Parameters

Name	Type	In	Required	Description
comment_id	string	path	required	comment_id

Responses

200

GET

/admin/api/2020-01/redirects.json

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-2020-01

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
path		query		Show redirects with a given path.
target		query		Show redirects with a given target.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-01/redirects.json

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-2020-01

Responses

200

GET

/admin/api/2020-01/redirects/count.json

Retrieves a count of URL redirects

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-2020-01

Parameters

Name	Type	In	Required	Description
path		query		Count redirects with given path.
target		query		Count redirects with given target.

Responses

200

GET

/admin/api/2020-01/redirects/{redirect_id}.json

Retrieves a single redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-2020-01

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-01/redirects/{redirect_id}.json

Updates an existing redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-2020-01

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

DELETE

/admin/api/2020-01/redirects/{redirect_id}.json

Deletes a redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-2020-01

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

GET /admin/api/2020-04/redirects.json

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-2020-04

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
path		query		Show redirects with a given path.
target		query		Show redirects with a given target.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-04/redirects.json

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-2020-04

Responses

200

GET /admin/api/2020-04/redirects/count.json

Retrieves a count of URL redirects

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-2020-04

Parameters

Name	Type	In	Required	Description
path		query		Count redirects with given path.
target		query		Count redirects with given target.

Responses

200

GET /admin/api/2020-04/redirects/{redirect_id}.json

Retrieves a single redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-2020-04

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-04/redirects/{redirect_id}.json

Updates an existing redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-2020-04

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

DELETE

/admin/api/2020-04/redirects/{redirect_id}.json

Deletes a redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-2020-04

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

GET

/admin/api/2020-07/redirects.json

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-2020-07

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
path		query		Show redirects with a given path.
target		query		Show redirects with a given target.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-07/redirects.json

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-2020-07

Responses

200

GET

/admin/api/2020-07/redirects/count.json

Retrieves a count of URL redirects

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-2020-07

Parameters

Name	Type	In	Required	Description
path		query		Count redirects with given path.
target		query		Count redirects with given target.

Responses

200

GET

/admin/api/2020-07/redirects/{redirect_id}.json

Retrieves a single redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-2020-07

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-07/redirects/{redirect_id}.json

Updates an existing redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-2020-07

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

DELETE /admin/api/2020-07/redirects/{redirect_id}.json

Deletes a redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-2020-07

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

GET /admin/api/2020-10/redirects.json

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-2020-10

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
path		query		Show redirects with a given path.
target		query		Show redirects with a given target.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-10/redirects.json

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-2020-10

Responses

200

GET /admin/api/2020-10/redirects/count.json

Retrieves a count of URL redirects

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-2020-10

Parameters

Name	Type	In	Required	Description
path		query		Count redirects with given path.
target		query		Count redirects with given target.

Responses

200

GET /admin/api/2020-10/redirects/{redirect_id}.json

Retrieves a single redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-2020-10

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-10/redirects/{redirect_id}.json

Updates an existing redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-2020-10>

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

DELETE /admin/api/2020-10/redirects/{redirect_id}.json

Deletes a redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

GET /admin/api/2021-01/redirects.json

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-2021-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
path		query		Show redirects with a given path.
target		query		Show redirects with a given target.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2021-01/redirects.json

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-2021-01>

Responses

200

GET /admin/api/2021-01/redirects/count.json

Retrieves a count of URL redirects

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-2021-01>

Parameters

Name	Type	In	Required	Description
path		query		Count redirects with given path.
target		query		Count redirects with given target.

Responses

200

GET /admin/api/2021-01/redirects/{redirect_id}.json

Retrieves a single redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-2021-01>

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2021-01/redirects/{redirect_id}.json

Updates an existing redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-2021-01

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

DELETE /admin/api/2021-01/redirects/{redirect_id}.json

Deletes a redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-2021-01

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

GET /admin/api/unstable/redirects.json

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-unstable

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
path		query		Show redirects with a given path.
target		query		Show redirects with a given target.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/unstable/redirects.json

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-unstable

Responses

200

GET /admin/api/unstable/redirects/count.json

Retrieves a count of URL redirects

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-unstable

Parameters

Name	Type	In	Required	Description
path		query		Count redirects with given path.
target		query		Count redirects with given target.

Responses

200

GET /admin/api/unstable/redirects/{redirect_id}.json

Retrieves a single redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-unstable>

Parameters

Name	Type	In	Required	Description
redirect_id fields	string	path query	required	redirect_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/unstable/redirects/{redirect_id}.json

Updates an existing redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-unstable>

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

DELETE /admin/api/unstable/redirects/{redirect_id}.json

Deletes a redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-unstable>

Parameters

Name	Type	In	Required	Description
redirect_id	string	path	required	redirect_id

Responses

200

GET /admin/api/2020-01/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-2020-01>

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)
src		query		Show script tags with this URL.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-01/script_tags.json

Creates a new script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-2020-01>

Responses

200

GET /admin/api/2020-01/script_tags/count.json

Retrieves a count of all script tags

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-2020-01

Parameters

Name	Type	In	Required	Description
src		query		Count only script tags with a given URL.

Responses

200

GET

/admin/api/2020-01/script_tags/{script_tag_id}.json

Retrieves a single script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-2020-01

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT

/admin/api/2020-01/script_tags/{script_tag_id}.json

Updates a script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-2020-01

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

DELETE

/admin/api/2020-01/script_tags/{script_tag_id}.json

Deletes a script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-2020-01

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

GET

/admin/api/2020-04/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-2020-04

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)
src		query		Show script tags with this URL.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2020-04/script_tags.json

Creates a new script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-2020-04

Responses

200

GET /admin/api/2020-04/script_tags/count.json

Retrieves a count of all script tags

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-2020-04

Parameters

Name	Type	In	Required	Description
src		query		Count only script tags with a given URL.

Responses

200

GET /admin/api/2020-04/script_tags/{script_tag_id}.json

Retrieves a single script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-2020-04

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/2020-04/script_tags/{script_tag_id}.json

Updates a script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-2020-04

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

DELETE /admin/api/2020-04/script_tags/{script_tag_id}.json

Deletes a script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-2020-04

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

GET /admin/api/2020-07/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-2020-07

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)

src
fields

query
query

Show script tags with this URL.
A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2020-07/script_tags.json

Creates a new script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-2020-07

Responses

200

GET

/admin/api/2020-07/script_tags/count.json

Retrieves a count of all script tags

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-2020-07

Parameters

Name	Type	In	Required	Description
src		query		Count only script tags with a given URL.

Responses

200

GET

/admin/api/2020-07/script_tags/{script_tag_id}.json

Retrieves a single script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-2020-07

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT

/admin/api/2020-07/script_tags/{script_tag_id}.json

Updates a script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-2020-07

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

DELETE

/admin/api/2020-07/script_tags/{script_tag_id}.json

Deletes a script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-2020-07

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

GET

/admin/api/2020-10/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-2020-10

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)
src		query		Show script tags with this URL.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/2020-10/script_tags.json

Creates a new script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-2020-10>

Responses

200

GET /admin/api/2020-10/script_tags/count.json

Retrieves a count of all script tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-2020-10>

Parameters

Name	Type	In	Required	Description
src		query		Count only script tags with a given URL.

Responses

200

GET /admin/api/2020-10/script_tags/{script_tag_id}.json

Retrieves a single script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-2020-10>

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/2020-10/script_tags/{script_tag_id}.json

Updates a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-2020-10>

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

DELETE /admin/api/2020-10/script_tags/{script_tag_id}.json

Deletes a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

GET

/admin/api/2021-01/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-2021-01>

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)
src		query		Show script tags with this URL.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST

/admin/api/2021-01/script_tags.json

Creates a new script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-2021-01>

Responses

200

GET

/admin/api/2021-01/script_tags/count.json

Retrieves a count of all script tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-2021-01>

Parameters

Name	Type	In	Required	Description
src		query		Count only script tags with a given URL.

Responses

200

GET

/admin/api/2021-01/script_tags/{script_tag_id}.json

Retrieves a single script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-2021-01>

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT

/admin/api/2021-01/script_tags/{script_tag_id}.json

Updates a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-2021-01>

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

DELETE /admin/api/2021-01/script_tags/{script_tag_id}.json

Deletes a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

GET /admin/api/unstable/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-unstable>

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to return. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)
src		query		Show script tags with this URL.
fields		query		A comma-separated list of fields to include in the response.

Responses

200

POST /admin/api/unstable/script_tags.json

Creates a new script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-unstable>

Responses

200

GET /admin/api/unstable/script_tags/count.json

Retrieves a count of all script tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-unstable>

Parameters

Name	Type	In	Required	Description
src		query		Count only script tags with a given URL.

Responses

200

GET /admin/api/unstable/script_tags/{script_tag_id}.json

Retrieves a single script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-unstable>

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/unstable/script_tags/{script_tag_id}.json

Updates a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-unstable>

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

DELETE /admin/api/unstable/script_tags/{script_tag_id}.json

Deletes a script tag
<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-unstable>

Parameters

Name	Type	In	Required	Description
script_tag_id	string	path	required	script_tag_id

Responses

200

GET /admin/api/2020-01/themes.json

Retrieves a list of themes.
<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-2020-01>

Parameters

Name	Type	In	Required	Description
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-01/themes.json

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-2020-01>

Responses

200

GET /admin/api/2020-01/themes/{theme_id}.json

Retrieves a single theme.
<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-2020-01>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-01/themes/{theme_id}.json

Updates an existing theme.
<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-2020-01>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

DELETE /admin/api/2020-01/themes/{theme_id}.json

Deletes a theme.
<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

GET

/admin/api/2020-04/themes.json

Retrieves a list of themes.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-2020-04>

Parameters

Name	Type	In	Required	Description
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-04/themes.json

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-2020-04>

Responses

200

GET

/admin/api/2020-04/themes/{theme_id}.json

Retrieves a single theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-2020-04>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-04/themes/{theme_id}.json

Updates an existing theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-2020-04>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

DELETE

/admin/api/2020-04/themes/{theme_id}.json

Deletes a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

GET

/admin/api/2020-07/themes.json

Retrieves a list of themes.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-2020-07>

Parameters

Name	Type	In	Required	Description
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-07/themes.json

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-2020-07>

Responses

200

GET

/admin/api/2020-07/themes/{theme_id}.json

Retrieves a single theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-2020-07>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-07/themes/{theme_id}.json

Updates an existing theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-2020-07>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

DELETE

/admin/api/2020-07/themes/{theme_id}.json

Deletes a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

GET

/admin/api/2020-10/themes.json

Retrieves a list of themes.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-2020-10>

Parameters

Name	Type	In	Required	Description
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-10/themes.json

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-2020-10

Responses

200

GET /admin/api/2020-10/themes/{theme_id}.json

Retrieves a single theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-2020-10

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-10/themes/{theme_id}.json

Updates an existing theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-2020-10

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

DELETE /admin/api/2020-10/themes/{theme_id}.json

Deletes a theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-2020-10

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

GET /admin/api/2021-01/themes.json

Retrieves a list of themes.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-2021-01

Parameters

Name	Type	In	Required	Description
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2021-01/themes.json

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-2021-01

Responses

200

GET /admin/api/2021-01/themes/{theme_id}.json

Retrieves a single theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-2021-01

Parameters

Name	Type	In	Required	Description
theme_id fields	string	path query	required	theme_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2021-01/themes/{theme_id}.json

Updates an existing theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-2021-01>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

DELETE /admin/api/2021-01/themes/{theme_id}.json

Deletes a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

GET /admin/api/unstable/themes.json

Retrieves a list of themes.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-unstable>

Parameters

Name	Type	In	Required	Description
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/unstable/themes.json

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-unstable>

Responses

200

GET /admin/api/unstable/themes/{theme_id}.json

Retrieves a single theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-unstable>

Parameters

Name	Type	In	Required	Description
theme_id fields	string	path query	required	theme_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/unstable/themes/{theme_id}.json

Updates an existing theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-unstable>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

DELETE /admin/api/unstable/themes/{theme_id}.json

Deletes a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-unstable>

Parameters

Name	Type	In	Required	Description
theme_id	string	path	required	theme_id

Responses

200

GET /admin/api/2020-01/checkouts/count.json

Retrieves a count of checkouts from the past 90 days

<https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-2020-01>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status		query		Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

200

POST /admin/api/2020-01/checkouts.json

Creates a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-2020-01>

Responses

200

GET /admin/api/2020-04/checkouts/count.json

Retrieves a count of checkouts from the past 90 days

<https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-2020-04>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status		query		Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

200

POST /admin/api/2020-04/checkouts.json

Creates a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-2020-04>

Responses

200

GET /admin/api/2020-07/checkouts/count.json

Retrieves a count of checkouts from the past 90 days

<https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-2020-07>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status		query		Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

200

POST /admin/api/2020-07/checkouts.json

Creates a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-2020-07>

Responses

200

GET /admin/api/2020-10/checkouts/count.json

Retrieves a count of checkouts from the past 90 days

<https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-2020-10>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status		query		Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

200

POST /admin/api/2020-10/checkouts.json

Creates a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-2020-10>

Responses

200

GET /admin/api/2021-01/checkouts/count.json

Retrieves a count of checkouts from the past 90 days

<https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-2021-01>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status		query		Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

200

POST /admin/api/2021-01/checkouts.json

Creates a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-2021-01>

Responses

200

GET /admin/api/unstable/checkouts/count.json

Retrieves a count of checkouts from the past 90 days

<https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-unstable>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
created_at_min		query		Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status		query		Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

200

POST /admin/api/unstable/checkouts.json

Creates a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-unstable>

Responses

200

GET /admin/api/2020-01/orders.json

Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#index-2020-01>

Parameters

Name	Type	In	Required	Description
ids		query		Retrieve only orders specified by a comma-separated list of order IDs.
limit		query		The maximum number of results to show on a page. (default: 50, maximum: 250)
since_id		query		Show orders after the specified ID.
created_at_min		query		Show orders created at or after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Show orders created at or before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show orders last updated at or after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show orders last updated at or before date (format: 2014-04-25T16:15:47-04:00).
processed_at_min		query		Show orders imported at or after date (format: 2014-04-25T16:15:47-04:00).
processed_at_max		query		Show orders imported at or before date (format: 2014-04-25T16:15:47-04:00).

attribution_app_id	query	Show orders attributed to a certain app, specified by the app ID. Set as current to show orders for the app currently consuming the API.
status	query	Filter orders by their status. (default: open) open: Show only open orders. closed: Show only closed orders. cancelled: Show only canceled orders. any: Show orders of any status, including archived orders.
financial_status	query	Filter orders by their financial status. (default: any) authorized: Show only authorized orders pending: Show only pending orders paid: Show only paid orders partially_paid: Show only partially paid orders refunded: Show only refunded orders voided: Show only voided orders partially_refunded: Show only partially refunded orders any: Show orders of any financial status. unpaid: Show authorized and partially paid orders.
fulfillment_status	query	Filter orders by their fulfillment status. (default: any) shipped: Show orders that have been shipped. Returns orders with fulfillment_status of fulfilled. partial: Show partially shipped orders. unshipped: Show orders that have not yet been shipped. Returns orders with fulfillment_status of null. any: Show orders of any fulfillment status. unfulfilled: Returns orders with fulfillment_status of null or partial.
fields	query	Retrieve only certain fields, specified by a comma-separated list of fields names.

Responses

200

POST /admin/api/2020-01/orders.json

Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: inventory_behaviour: The behaviour to use when updating inventory. (default: bypass) bypass: Do not claim inventory. decrement_ignoring_policy: Ignore the product's inventory policy and claim inventory. decrement_obeying_policy: Follow the product's inventory policy and claim inventory, if possible. send_receipt: Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when send_receipt is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. send_fulfillment_receipt: Whether to send a shipping confirmation to the customer. Note If you are including shipping_address or billing_address, make sure to pass both first_name and last_name. Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#create-2020-01>

Responses

200

GET /admin/api/2020-01/orders/{order_id}.json

Retrieves a specific order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#show-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fields		query		Retrieve only certain fields, specified by a comma-separated list of fields names.

Responses

200

PUT /admin/api/2020-01/orders/{order_id}.json

Updates an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#update-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

DELETE /admin/api/2020-01/orders/{order_id}.json

Deletes an order. Orders that interact with an online gateway can't be deleted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET /admin/api/2020-01/orders/count.json

Retrieves an order count

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#count-2020-01>

Parameters

Name	Type	In	Required	Description
created_at_min		query		Count orders created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count orders created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count orders last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count orders last updated before date (format: 2014-04-25T16:15:47-04:00).
status		query		Count orders of a given status. (default: open) open: Count open orders. closed: Count closed orders. any: Count orders of any status.
financial_status		query		Count orders of a given financial status. (default: any) authorized: Count authorized orders. pending: Count pending orders. paid: Count paid orders. refunded: Count refunded orders. voided: Count voided orders. any: Count orders of any financial status.
fulfillment_status		query		Filter orders by their fulfillment status. (default: any) shipped: Show orders that have been shipped. Returns orders with fulfillment_status of fulfilled. partial: Show partially shipped orders. unshipped: Show orders that have not yet been shipped. Returns orders with fulfillment_status of null. any: Show orders of any fulfillment status. unfulfilled: Returns orders with fulfillment_status of null or partial.

Responses

200

POST /admin/api/2020-01/orders/{order_id}/close.json

Closes an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#close-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

POST /admin/api/2020-01/orders/{order_id}/open.json

Re-opens a closed order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#open-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

POST /admin/api/2020-01/orders/{order_id}/cancel.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#cancel-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
amount		query		The amount to refund. If set, Shopify attempts to void or refund the payment, depending on its status. Shopify refunds through a manual gateway in cases where the original transaction was not made in Shopify. Refunds through a manual gateway are recorded as a refund on Shopify, but the customer is not refunded.
currency		query		The currency of the refund that's issued when the order is canceled. Required for multi-currency orders whenever the amount property is provided.
restock deprecated		query		Whether to restock refunded items back to your store's inventory. (default: false)
reason		query		The reason for the order cancellation. Valid values: customer, inventory, fraud, declined, and other.) (default: other)
email		query		Whether to send an email to the customer notifying them of the cancellation. (default: false)

refund

query

The refund transactions to perform. Required for some more complex refund situations. For more information, see the Refund API.

Responses

200

GET /admin/api/2020-04/orders.json

Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/orders/order#index-2020-04

Parameters

Name	Type	In	Required	Description
ids		query		Retrieve only orders specified by a comma-separated list of order IDs.
limit		query		The maximum number of results to show on a page. (default: 50, maximum: 250)
since_id		query		Show orders after the specified ID.
created_at_min		query		Show orders created at or after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Show orders created at or before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show orders last updated at or after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show orders last updated at or before date (format: 2014-04-25T16:15:47-04:00).
processed_at_min		query		Show orders imported at or after date (format: 2014-04-25T16:15:47-04:00).
processed_at_max		query		Show orders imported at or before date (format: 2014-04-25T16:15:47-04:00).
attribution_app_id		query		Show orders attributed to a certain app, specified by the app ID. Set as current to show orders for the app currently consuming the API.
status		query		Filter orders by their status. (default: open) open: Show only open orders. closed: Show only closed orders. cancelled: Show only canceled orders. any: Show orders of any status, including archived orders.
financial_status		query		Filter orders by their financial status. (default: any) authorized: Show only authorized orders pending: Show only pending orders paid: Show only paid orders partially_paid: Show only partially paid orders refunded: Show only refunded orders voided: Show only voided orders partially_refunded: Show only partially refunded orders any: Show orders of any financial status. unpaid: Show authorized and partially paid orders.
fulfillment_status		query		Filter orders by their fulfillment status. (default: any) shipped: Show orders that have been shipped. Returns orders with fulfillment_status of fulfilled. partial: Show partially shipped orders. unshipped: Show orders that have not yet been shipped. Returns orders with fulfillment_status of null. any: Show orders of any fulfillment status. unfulfilled: Returns orders with fulfillment_status of null or partial.
fields		query		Retrieve only certain fields, specified by a comma-separated list of fields names.

Responses

200

POST /admin/api/2020-04/orders.json

Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: inventory_behaviour: The behaviour to use when updating inventory. (default: bypass) bypass: Do not claim inventory. decrement_ignoring_policy: Ignore the product's inventory policy and claim inventory. decrement_obeying_policy: Follow the product's inventory policy and claim inventory, if possible. send_receipt: Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when send_receipt is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. send_fulfillment_receipt: Whether to send a shipping confirmation to the customer. Note If you are including shipping_address or billing_address, make sure to pass both first_name and last_name. Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.

https://shopify.dev/docs/admin-api/rest/reference/orders/order#create-2020-04

Responses

200

GET /admin/api/2020-04/orders/{order_id}.json

Retrieves a specific order

https://shopify.dev/docs/admin-api/rest/reference/orders/order#show-2020-04

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fields		query		Retrieve only certain fields, specified by a comma-separated list of fields names.

Responses

200

PUT /admin/api/2020-04/orders/{order_id}.json

Updates an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#update-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

DELETE

/admin/api/2020-04/orders/{order_id}.json

Deletes an order. Orders that interact with an online gateway can't be deleted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET

/admin/api/2020-04/orders/count.json

Retrieves an order count

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#count-2020-04>

Parameters

Name	Type	In	Required	Description
created_at_min		query		Count orders created after date (format: 2014-04-25T16:15:47-04:00). Count orders created before date (format: 2014-04-25T16:15:47-04:00). Count orders last updated after date (format: 2014-04-25T16:15:47-04:00). Count orders last updated before date (format: 2014-04-25T16:15:47-04:00). Count orders of a given status. (default: open) open: Count open orders. closed: Count closed orders. any: Count orders of any status.
created_at_max		query		
updated_at_min		query		
updated_at_max		query		
status		query		
financial_status		query		Count orders of a given financial status. (default: any) authorized: Count authorized orders. pending: Count pending orders. paid: Count paid orders. refunded: Count refunded orders. voided: Count voided orders. any: Count orders of any financial status.
fulfillment_status		query		Filter orders by their fulfillment status. (default: any) shipped: Show orders that have been shipped. Returns orders with fulfillment_status of fulfilled. partial: Show partially shipped orders. unshipped: Show orders that have not yet been shipped. Returns orders with fulfillment_status of null. any: Show orders of any fulfillment status. unfulfilled: Returns orders with fulfillment_status of null or partial.

Responses

200

POST

/admin/api/2020-04/orders/{order_id}/close.json

Closes an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#close-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

POST

/admin/api/2020-04/orders/{order_id}/open.json

Re-opens a closed order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#open-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

POST /admin/api/2020-04/orders/{order_id}/cancel.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#cancel-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
amount		query		The amount to refund. If set, Shopify attempts to void or refund the payment, depending on its status. Shopify refunds through a manual gateway in cases where the original transaction was not made in Shopify. Refunds through a manual gateway are recorded as a refund on Shopify, but the customer is not refunded.
currency		query		The currency of the refund that's issued when the order is canceled. Required for multi-currency orders whenever the amount property is provided.
restock deprecated		query		Whether to restock refunded items back to your store's inventory. (default: false)
reason		query		The reason for the order cancellation. Valid values: customer, inventory, fraud, declined, and other.) (default: other)
email		query		Whether to send an email to the customer notifying them of the cancellation. (default: false)
refund		query		The refund transactions to perform. Required for some more complex refund situations. For more information, see the Refund API.

Responses

200

GET /admin/api/2020-07/orders.json

Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#index-2020-07>

Parameters

Name	Type	In	Required	Description
ids		query		Retrieve only orders specified by a comma-separated list of order IDs.
limit		query		The maximum number of results to show on a page. (default: 50, maximum: 250)
since_id		query		Show orders after the specified ID.
created_at_min		query		Show orders created at or after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Show orders created at or before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show orders last updated at or after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show orders last updated at or before date (format: 2014-04-25T16:15:47-04:00).
processed_at_min		query		Show orders imported at or after date (format: 2014-04-25T16:15:47-04:00).
processed_at_max		query		Show orders imported at or before date (format: 2014-04-25T16:15:47-04:00).
attribution_app_id		query		Show orders attributed to a certain app, specified by the app ID. Set as current to show orders for the app currently consuming the API.
status		query		Filter orders by their status. (default: open) open: Show only open orders. closed: Show only closed orders. cancelled: Show only canceled orders. any: Show orders of any status, including archived orders.
financial_status		query		Filter orders by their financial status. (default: any) authorized: Show only authorized orders pending: Show only pending orders paid: Show only paid orders partially_paid: Show only partially paid orders refunded: Show only refunded orders voided: Show only voided orders partially_refunded: Show only partially refunded orders any: Show orders of any financial status. unpaid: Show authorized and partially paid orders.
fulfillment_status		query		Filter orders by their fulfillment status. (default: any) shipped: Show orders that have been shipped. Returns orders with fulfillment_status of fulfilled. partial: Show partially shipped orders. unshipped: Show orders that have not yet been shipped. Returns orders with fulfillment_status of null. any: Show orders of any fulfillment status. unfulfilled: Returns orders with fulfillment_status of null or partial.
fields		query		Retrieve only certain fields, specified by a comma-separated list of fields names.

Responses

200

GET /admin/api/2020-01/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

POST /admin/api/2020-01/orders/{order_id}/risks.json

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

PUT /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

DELETE /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

GET /admin/api/2020-04/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

POST

/admin/api/2020-04/orders/{order_id}/risks.json

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET

/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

PUT

/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

DELETE

/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

GET

/admin/api/2020-07/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-2020-07>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

POST

/admin/api/2020-07/orders/{order_id}/risks.json

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-2020-07>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET

/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-2020-07>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

PUT

/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-2020-07>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

DELETE

/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

GET

/admin/api/2020-10/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

POST

/admin/api/2020-10/orders/{order_id}/risks.json

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET /admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

PUT /admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

DELETE /admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

GET /admin/api/2021-01/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

POST /admin/api/2021-01/orders/{order_id}/risks.json

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET /admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

PUT /admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

DELETE /admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

GET /admin/api/unstable/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

POST /admin/api/unstable/orders/{order_id}/risks.json

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET /admin/api/unstable/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

PUT /admin/api/unstable/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

DELETE /admin/api/unstable/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
risk_id	string	path	required	risk_id

Responses

200

GET /admin/api/2020-01/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency		query		Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/2020-01/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
restock deprecated		query		Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.
notify		query		Whether to send a refund notification to the customer.
note		query		An optional note attached to a refund.
discrepancy_reason		query		An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping		query		Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.

refund_line_items	query	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.
transactions currency	query query	A list of transactions to process as refunds. The three-letter code (ISO 4217 format) for the currency used for the refund.

Responses

200

GET /admin/api/2020-01/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.
<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
refund_id	string	path	required	refund_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency		query		Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/2020-01/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind" : "refund" for the refund to be accepted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
shipping		query		Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items		query		A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.
currency		query		The three-letter code (ISO 4217 format) for the currency used for the refund. Note: Required whenever the shipping amount property is provided.

Responses

200

GET /admin/api/2020-04/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency		query		Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/2020-04/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
restock deprecated		query		Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.
notify		query		Whether to send a refund notification to the customer.
note		query		An optional note attached to a refund.
discrepancy_reason		query		An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping		query		Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items		query		A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.
transactions		query		A list of transactions to process as refunds.
currency		query		The three-letter code (ISO 4217 format) for the currency used for the refund.

Responses

200

GET /admin/api/2020-04/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
refund_id	string	path	required	refund_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency		query		Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/2020-04/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind" : "refund" for the refund to be accepted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-2020-04>

Parameters

Name	Type	In	Required	Description
order_id shipping	string	path query	required	order_id Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items		query		A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.
currency		query		The three-letter code (ISO 4217 format) for the currency used for the refund. Note: Required whenever the shipping amount property is provided.

Responses

200

GET /admin/api/2020-07/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-2020-07>

Parameters

Name	Type	In	Required	Description
order_id limit fields in_shop_currency	string	path query query query	required	order_id The maximum number of results to retrieve. (default: 50, maximum: 250) Show only certain fields, specified by a comma-separated list of field names. Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/2020-07/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-2020-07>

Parameters

Name	Type	In	Required	Description
order_id restock deprecated	string	path query	required	order_id Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.
notify note discrepancy_reason		query query query		Whether to send a refund notification to the customer. An optional note attached to a refund. An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping		query		Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items		query		A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.

transactions currency	query query	A list of transactions to process as refunds. The three-letter code (ISO 4217 format) for the currency used for the refund.
--------------------------	----------------	--

Responses

200

GET /admin/api/2020-07/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.
<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-2020-07>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
refund_id	string	path	required	refund_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency		query		Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/2020-07/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.
<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-2020-07>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
shipping		query		Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items		query		A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.
currency		query		The three-letter code (ISO 4217 format) for the currency used for the refund. Note: Required whenever the shipping amount property is provided.

Responses

200

GET /admin/api/2020-10/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency		query		Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/2020-10/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
restock deprecated		query		Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.
notify		query		Whether to send a refund notification to the customer.
note		query		An optional note attached to a refund.
discrepancy_reason		query		An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping		query		Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items		query		A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.
transactions		query		A list of transactions to process as refunds.
currency		query		The three-letter code (ISO 4217 format) for the currency used for the refund.

Responses

200

GET /admin/api/2020-10/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
refund_id	string	path	required	refund_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency		query		Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/2020-10/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
shipping		query		Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items		query		A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items

currency

query

have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease.
return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged.
location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.
The three-letter code (ISO 4217 format) for the currency used for the refund.
Note: Required whenever the shipping amount property is provided.

Responses

200

GET /admin/api/2021-01/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency		query		Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/2021-01/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
restock deprecated		query		Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.
notify		query		Whether to send a refund notification to the customer.
note		query		An optional note attached to a refund.
discrepancy_reason		query		An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping		query		Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items		query		A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.
transactions		query		A list of transactions to process as refunds.
currency		query		The three-letter code (ISO 4217 format) for the currency used for the refund.

Responses

200

GET /admin/api/2021-01/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
refund_id	string	path	required	refund_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency		query		Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/2021-01/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
shipping		query		Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items		query		A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.
currency		query		The three-letter code (ISO 4217 format) for the currency used for the refund. Note: Required whenever the shipping amount property is provided.

Responses

200

GET /admin/api/unstable/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency		query		Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/unstable/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
restock deprecated		query		Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.

notify	query	Whether to send a refund notification to the customer.
note	query	An optional note attached to a refund.
discrepancy_reason	query	An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping	query	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	query	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.
transactions	query	A list of transactions to process as refunds.
currency	query	The three-letter code (ISO 4217 format) for the currency used for the refund.

Responses

200

GET /admin/api/unstable/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
refund_id	string	path	required	refund_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency		query		Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

200

POST /admin/api/unstable/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
shipping		query		Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items		query		A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.
currency		query		The three-letter code (ISO 4217 format) for the currency used for the refund. Note: Required whenever the shipping amount property is provided.

Responses

GET

/admin/api/2020-01/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#index-2020-01

Parameters

Name	Type	In	Required	Description
status		query		Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-01/gift_cards.json

Creates a gift card

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-2020-01

Responses

200

GET

/admin/api/2020-01/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-2020-01

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

PUT

/admin/api/2020-01/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-2020-01

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

GET

/admin/api/2020-01/gift_cards/count.json

Retrieves a count of gift cards

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-2020-01

Parameters

Name	Type	In	Required	Description
status		query		Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses

200

POST

/admin/api/2020-01/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-2020-01

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

GET

/admin/api/2020-01/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-2020-01>

Parameters

Name	Type	In	Required	Description
order		query		The field and direction to order results by. (default: disabled_at DESC)
query		query		The text to search for.
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET

/admin/api/2020-04/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#index-2020-04>

Parameters

Name	Type	In	Required	Description
status		query		Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-04/gift_cards.json

Creates a gift card

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-2020-04>

Responses

200

GET

/admin/api/2020-04/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-2020-04>

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

PUT

/admin/api/2020-04/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-2020-04>

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

GET /admin/api/2020-04/gift_cards/count.json

Retrieves a count of gift cards

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-2020-04>

Parameters

Name	Type	In	Required	Description
status		query		Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses

200

POST /admin/api/2020-04/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-2020-04>

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

GET /admin/api/2020-04/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-2020-04>

Parameters

Name	Type	In	Required	Description
order		query		The field and direction to order results by. (default: disabled_at DESC)
query		query		The text to search for.
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-07/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#index-2020-07>

Parameters

Name	Type	In	Required	Description
status		query		Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-07/gift_cards.json

Creates a gift card

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-2020-07>

Responses

200

GET /admin/api/2020-07/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-2020-07>

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

PUT /admin/api/2020-07/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-2020-07>

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

GET /admin/api/2020-07/gift_cards/count.json

Retrieves a count of gift cards

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-2020-07>

Parameters

Name	Type	In	Required	Description
status		query		Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses

200

POST /admin/api/2020-07/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-2020-07>

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

GET /admin/api/2020-07/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-2020-07>

Parameters

Name	Type	In	Required	Description
order		query		The field and direction to order results by. (default: disabled_at DESC)
query		query		The text to search for.
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-10/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

Parameters

Name	Type	In	Required	Description
status		query		Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-10/gift_cards.json

Creates a gift card

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-2020-10

Responses

200

GET

/admin/api/2020-10/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-2020-10

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

PUT

/admin/api/2020-10/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-2020-10

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

GET

/admin/api/2020-10/gift_cards/count.json

Retrieves a count of gift cards

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-2020-10

Parameters

Name	Type	In	Required	Description
status		query		Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses

200

POST

/admin/api/2020-10/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-2020-10

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

GET

/admin/api/2020-10/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-2020-10

Parameters

Name	Type	In	Required	Description
order		query		The field and direction to order results by. (default: disabled_at DESC)
query		query		The text to search for.
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET

/admin/api/2021-01/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#index-2021-01

Parameters

Name	Type	In	Required	Description
status		query		Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2021-01/gift_cards.json

Creates a gift card

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-2021-01

Responses

200

GET

/admin/api/2021-01/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-2021-01

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

PUT

/admin/api/2021-01/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-2021-01

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

GET

/admin/api/2021-01/gift_cards/count.json

Retrieves a count of gift cards

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-2021-01>

Parameters

Name	Type	In	Required	Description
status		query		Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses

200

POST

/admin/api/2021-01/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-2021-01>

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

GET

/admin/api/2021-01/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-2021-01>

Parameters

Name	Type	In	Required	Description
order		query		The field and direction to order results by. (default: disabled_at DESC)
query		query		The text to search for.
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET

/admin/api/unstable/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#index-unstable>

Parameters

Name	Type	In	Required	Description
status		query		Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/unstable/gift_cards.json

Creates a gift card

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-unstable>

Responses

200

GET

/admin/api/unstable/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-unstable>

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

PUT /admin/api/unstable/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-unstable>

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

GET /admin/api/unstable/gift_cards/count.json

Retrieves a count of gift cards
<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-unstable>

Parameters

Name	Type	In	Required	Description
status		query		Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses

200

POST /admin/api/unstable/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.
<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-unstable>

Parameters

Name	Type	In	Required	Description
gift_card_id	string	path	required	gift_card_id

Responses

200

GET /admin/api/unstable/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-unstable>

Parameters

Name	Type	In	Required	Description
order		query		The field and direction to order results by. (default: disabled_at DESC)
query		query		The text to search for.
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-01/users.json

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-2020-01>

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

limit	query	The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info	query	A unique ID used to access a certain page of results.

Responses

200

GET /admin/api/2020-01/users/{user_id}.json

Retrieves a single user
<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-2020-01>

Parameters

Name	Type	In	Required	Description
user_id	string	path	required	user_id

Responses

200

GET /admin/api/2020-01/users/current.json

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-2020-01>

Responses

200

GET /admin/api/2020-04/users.json

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-2020-04>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info		query		A unique ID used to access a certain page of results.

Responses

200

GET /admin/api/2020-04/users/{user_id}.json

Retrieves a single user
<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-2020-04>

Parameters

Name	Type	In	Required	Description
user_id	string	path	required	user_id

Responses

200

GET /admin/api/2020-04/users/current.json

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-2020-04>

Responses

200

GET /admin/api/2020-07/users.json

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-2020-07>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info		query		A unique ID used to access a certain page of results.

Responses

200

GET /admin/api/2020-07/users/{user_id}.json

Retrieves a single user

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-2020-07>

Parameters

Name	Type	In	Required	Description
user_id	string	path	required	user_id

Responses

200

GET /admin/api/2020-07/users/current.json

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-2020-07>

Responses

200

GET /admin/api/2020-10/users.json

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-2020-10>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info		query		A unique ID used to access a certain page of results.

Responses

200

GET /admin/api/2020-10/users/{user_id}.json

Retrieves a single user

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-2020-10>

Parameters

Name	Type	In	Required	Description
user_id	string	path	required	user_id

Responses

200

GET /admin/api/2020-10/users/current.json

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-2020-10>

Responses

200

GET /admin/api/2021-01/users.json

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-2021-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info		query		A unique ID used to access a certain page of results.

Responses

200

GET /admin/api/2021-01/users/{user_id}.json

Retrieves a single user

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-2021-01>

Parameters

Name	Type	In	Required	Description
user_id	string	path	required	user_id

Responses

200

GET /admin/api/2021-01/users/current.json

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-2021-01>

Responses

200

GET /admin/api/unstable/users.json

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-unstable>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info		query		A unique ID used to access a certain page of results.

Responses

200

GET /admin/api/unstable/users/{user_id}.json

Retrieves a single user

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-unstable>

Parameters

Name	Type	In	Required	Description
user_id	string	path	required	user_id

Responses

200

GET /admin/api/unstable/users/current.json

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-unstable>

Responses

200

GET /admin/api/2020-01/collects.json

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-2020-01

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-01/collects.json

Adds a product to a custom collection.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-2020-01

Responses

200

GET

/admin/api/2020-01/collects/{collect_id}.json

Retrieves a specific collect by its ID.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-2020-01

Parameters

Name	Type	In	Required	Description
collect_id	string	path	required	collect_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

DELETE

/admin/api/2020-01/collects/{collect_id}.json

Removes a product from a collection.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-2020-01

Parameters

Name	Type	In	Required	Description
collect_id	string	path	required	collect_id

Responses

200

GET

/admin/api/2020-01/collects/count.json

Retrieves a count of collects.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#count-2020-01

Parameters

Name	Type	In	Required	Description
collection_id	integer	query		collection_id

Responses

200

GET

/admin/api/2020-04/collects.json

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-2020-04

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

POST

/admin/api/2020-04/collects.json

Adds a product to a custom collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-2020-04>

Responses

200

GET

/admin/api/2020-04/collects/{collect_id}.json

Retrieves a specific collect by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-2020-04>

Parameters

Name	Type	In	Required	Description
collect_id	string	path	required	collect_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

DELETE

/admin/api/2020-04/collects/{collect_id}.json

Removes a product from a collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
collect_id	string	path	required	collect_id

Responses

200

GET

/admin/api/2020-04/collects/count.json

Retrieves a count of collects.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#count-2020-04>

Parameters

Name	Type	In	Required	Description
collection_id	integer	query		collection_id

Responses

200

GET

/admin/api/2020-07/collects.json

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-2020-07>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-07/collects.json

Adds a product to a custom collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-2020-07>

Responses

200

GET /admin/api/2020-07/collects/{collect_id}.json

Retrieves a specific collect by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-2020-07>

Parameters

Name	Type	In	Required	Description
collect_id fields	string	path query	required	collect_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

DELETE /admin/api/2020-07/collects/{collect_id}.json

Removes a product from a collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
collect_id	string	path	required	collect_id

Responses

200

GET /admin/api/2020-07/collects/count.json

Retrieves a count of collects.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#count-2020-07>

Parameters

Name	Type	In	Required	Description
collection_id	integer	query		collection_id

Responses

200

GET /admin/api/2020-10/collects.json

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-2020-10>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-10/collects.json

Adds a product to a custom collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-2020-10>

Responses

200

GET /admin/api/2020-10/collects/{collect_id}.json

Retrieves a specific collect by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-2020-10>

Parameters

Name	Type	In	Required	Description
collect_id fields	string	path query	required	collect_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

DELETE

/admin/api/2020-10/collects/{collect_id}.json

Removes a product from a collection.
<https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
collect_id	string	path	required	collect_id

Responses

200

GET

/admin/api/2020-10/collects/count.json

Retrieves a count of collects.
<https://shopify.dev/docs/admin-api/rest/reference/products/collect#count-2020-10>

Parameters

Name	Type	In	Required	Description
collection_id	integer	query		collection_id

Responses

200

GET

/admin/api/2021-01/collects.json

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-2021-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250) Restrict results to after the specified ID. Show only certain fields, specified by a comma-separated list of field names.
since_id		query		
fields		query		

Responses

200

POST

/admin/api/2021-01/collects.json

Adds a product to a custom collection.
<https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-2021-01>

Responses

200

GET

/admin/api/2021-01/collects/{collect_id}.json

Retrieves a specific collect by its ID.
<https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-2021-01>

Parameters

Name	Type	In	Required	Description
collect_id	string	path	required	collect_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

DELETE

/admin/api/2021-01/collects/{collect_id}.json

Removes a product from a collection.
<https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
collect_id	string	path	required	collect_id

Responses

200

GET /admin/api/2021-01/collects/count.json

Retrieves a count of collects.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#count-2021-01>

Parameters

Name	Type	In	Required	Description
collection_id	integer	query		collection_id

Responses

200

GET /admin/api/unstable/collects.json

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-unstable>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to show. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/unstable/collects.json

Adds a product to a custom collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-unstable>

Responses

200

GET /admin/api/unstable/collects/{collect_id}.json

Retrieves a specific collect by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-unstable>

Parameters

Name	Type	In	Required	Description
collect_id	string	path	required	collect_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

DELETE /admin/api/unstable/collects/{collect_id}.json

Removes a product from a collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-unstable>

Parameters

Name	Type	In	Required	Description
collect_id	string	path	required	collect_id

Responses

200

GET /admin/api/unstable/collects/count.json

Retrieves a count of collects.

https://shopify.dev/docs/admin-api/rest/reference/products/collection#count-unstable

Parameters

Name	Type	In	Required	Description
collection_id	integer	query		collection_id

Responses

200

GET

/admin/api/2020-01/collections/{collection_id}.json

Retrieves a single collection

https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-2020-01

Parameters

Name	Type	In	Required	Description
collection_id	string	path	required	collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET

/admin/api/2020-01/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-2020-01

Parameters

Name	Type	In	Required	Description
collection_id	string	path	required	collection_id
limit		query		The number of products to retrieve. (default: 50, maximum: 250)

Responses

200

GET

/admin/api/2020-04/collections/{collection_id}.json

Retrieves a single collection

https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-2020-04

Parameters

Name	Type	In	Required	Description
collection_id	string	path	required	collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET

/admin/api/2020-04/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-2020-04

Parameters

Name	Type	In	Required	Description
collection_id	string	path	required	collection_id
limit		query		The number of products to retrieve. (default: 50, maximum: 250)

Responses

200

GET

/admin/api/2020-07/collections/{collection_id}.json

Retrieves a single collection

https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-2020-07

Parameters

Name	Type	In	Required	Description
collection_id fields	string	path query	required	collection_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-07/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-2020-07>

Parameters

Name	Type	In	Required	Description
collection_id limit	string	path query	required	collection_id The number of products to retrieve. (default: 50, maximum: 250)

Responses

200

GET /admin/api/2020-10/collections/{collection_id}.json

Retrieves a single collection

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-2020-10>

Parameters

Name	Type	In	Required	Description
collection_id fields	string	path query	required	collection_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2020-10/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-2020-10>

Parameters

Name	Type	In	Required	Description
collection_id limit	string	path query	required	collection_id The number of products to retrieve. (default: 50, maximum: 250)

Responses

200

GET /admin/api/2021-01/collections/{collection_id}.json

Retrieves a single collection

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-2021-01>

Parameters

Name	Type	In	Required	Description
collection_id fields	string	path query	required	collection_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/2021-01/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-2021-01>

Parameters

Name	Type	In	Required	Description
collection_id	string	path	required	collection_id
limit		query		The number of products to retrieve. (default: 50, maximum: 250)

Responses

200

GET /admin/api/unstable/collections/{collection_id}.json

Retrieves a single collection

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-unstable>

Parameters

Name	Type	In	Required	Description
collection_id	string	path	required	collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

GET /admin/api/unstable/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-unstable>

Parameters

Name	Type	In	Required	Description
collection_id	string	path	required	collection_id
limit		query		The number of products to retrieve. (default: 50, maximum: 250)

Responses

200

GET /admin/api/2020-01/custom_collections.json

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-2020-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
ids		query		Show only collections specified by a comma-separated list of IDs.
since_id		query		Restrict results to after the specified ID.
title		query		Show custom collections with a given title.
product_id		query		Show custom collections that include a given product.
handle		query		Filter by custom collection handle.
updated_at_min		query		Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Show custom collectson with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-01/custom_collections.json

Creates a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-2020-01>

Responses

200

GET /admin/api/2020-01/custom_collections/count.json

Retrieves a count of custom collections

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-2020-01>

Parameters

Name	Type	In	Required	Description
title		query		Count custom collections with given title.
product_id		query		Count custom collections that include a given product.
updated_at_min		query		Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.

Responses

200

GET /admin/api/2020-01/custom_collections/{custom_collection_id}.json

Retrieves a single custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-2020-01>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-01/custom_collections/{custom_collection_id}.json

Updates an existing custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-2020-01>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

200

DELETE /admin/api/2020-01/custom_collections/{custom_collection_id}.json

Deletes a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

200

GET /admin/api/2020-04/custom_collections.json

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-2020-04>

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

limit	query	The maximum number of results to retrieve. (default: 50, maximum: 250)
ids	query	Show only collections specified by a comma-separated list of IDs.
since_id	query	Restrict results to after the specified ID.
title	query	Show custom collections with a given title.
product_id	query	Show custom collections that include a given product.
handle	query	Filter by custom collection handle.
updated_at_min	query	Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	query	Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	query	Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	query	Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	query	Show custom collectson with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields	query	Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-04/custom_collections.json

Creates a custom collection
<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-2020-04>

Responses

200

GET

/admin/api/2020-04/custom_collections/count.json

Retrieves a count of custom collections
<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-2020-04>

Parameters

Name	Type	In	Required	Description
title		query		Count custom collections with given title.
product_id		query		Count custom collections that include a given product.
updated_at_min		query		Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.

Responses

200

GET

/admin/api/2020-04/custom_collections/{custom_collection_id}.json

Retrieves a single custom collection
<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-2020-04>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-04/custom_collections/{custom_collection_id}.json

Updates an existing custom collection
<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-2020-04>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

200

DELETE /admin/api/2020-04/custom_collections/{custom_collection_id}.json

Deletes a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

200

GET /admin/api/2020-07/custom_collections.json

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-2020-07>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
ids		query		Show only collections specified by a comma-separated list of IDs.
since_id		query		Restrict results to after the specified ID.
title		query		Show custom collections with a given title.
product_id		query		Show custom collections that include a given product.
handle		query		Filter by custom collection handle.
updated_at_min		query		Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Show custom collections with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-07/custom_collections.json

Creates a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-2020-07>

Responses

200

GET /admin/api/2020-07/custom_collections/count.json

Retrieves a count of custom collections

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-2020-07>

Parameters

Name	Type	In	Required	Description
title		query		Count custom collections with given title.
product_id		query		Count custom collections that include a given product.
updated_at_min		query		Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).

published_status	query	Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.
------------------	-------	--

Responses

200

GET /admin/api/2020-07/custom_collections/{custom_collection_id}.json

Retrieves a single custom collection
<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-2020-07>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-07/custom_collections/{custom_collection_id}.json

Updates an existing custom collection
<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-2020-07>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

200

DELETE /admin/api/2020-07/custom_collections/{custom_collection_id}.json

Deletes a custom collection
<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

200

GET /admin/api/2020-10/custom_collections.json

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-2020-10>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
ids		query		Show only collections specified by a comma-separated list of IDs.
since_id		query		Restrict results to after the specified ID.
title		query		Show custom collections with a given title.
product_id		query		Show custom collections that include a given product.
handle		query		Filter by custom collection handle.
updated_at_min		query		Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Show custom collectson with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-10/custom_collections.json

Creates a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-2020-10>

Responses

200

GET

/admin/api/2020-10/custom_collections/count.json

Retrieves a count of custom collections

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-2020-10>

Parameters

Name	Type	In	Required	Description
title		query		Count custom collections with given title.
product_id		query		Count custom collections that include a given product.
updated_at_min		query		Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.

Responses

200

GET

/admin/api/2020-10/custom_collections/{custom_collection_id}.json

Retrieves a single custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-2020-10>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-10/custom_collections/{custom_collection_id}.json

Updates an existing custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-2020-10>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

200

DELETE

/admin/api/2020-10/custom_collections/{custom_collection_id}.json

Deletes a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

GET

/admin/api/2021-01/custom_collections.json

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-2021-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
ids		query		Show only collections specified by a comma-separated list of IDs.
since_id		query		Restrict results to after the specified ID.
title		query		Show custom collections with a given title.
product_id		query		Show custom collections that include a given product.
handle		query		Filter by custom collection handle.
updated_at_min		query		Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Show custom collections with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2021-01/custom_collections.json

Creates a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-2021-01>

Responses

200

GET

/admin/api/2021-01/custom_collections/count.json

Retrieves a count of custom collections

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-2021-01>

Parameters

Name	Type	In	Required	Description
title		query		Count custom collections with given title.
product_id		query		Count custom collections that include a given product.
updated_at_min		query		Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.

Responses

200

GET

/admin/api/2021-01/custom_collections/{custom_collection_id}.json

Retrieves a single custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-2021-01>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2021-01/custom_collections/{custom_collection_id}.json

Updates an existing custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-2021-01>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

200

DELETE /admin/api/2021-01/custom_collections/{custom_collection_id}.json

Deletes a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

200

GET /admin/api/unstable/custom_collections.json

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-unstable>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
ids		query		Show only collections specified by a comma-separated list of IDs.
since_id		query		Restrict results to after the specified ID.
title		query		Show custom collections with a given title.
product_id		query		Show custom collections that include a given product.
handle		query		Filter by custom collection handle.
updated_at_min		query		Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Show custom collections with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/unstable/custom_collections.json

Creates a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-unstable>

Responses

200

GET /admin/api/unstable/custom_collections/count.json

Retrieves a count of custom collections

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-unstable>

Parameters

Name	Type	In	Required	Description
title		query		Count custom collections with given title.
product_id		query		Count custom collections that include a given product.
updated_at_min		query		Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min		query		Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max		query		Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status		query		Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.

Responses

200

GET /admin/api/unstable/custom_collections/{custom_collection_id}.json

Retrieves a single custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-unstable>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/unstable/custom_collections/{custom_collection_id}.json

Updates an existing custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-unstable>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

200

DELETE /admin/api/unstable/custom_collections/{custom_collection_id}.json

Deletes a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-unstable>

Parameters

Name	Type	In	Required	Description
custom_collection_id	string	path	required	custom_collection_id

Responses

200

GET /admin/api/2020-01/products.json

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#index-2020-01>

Parameters

Name	Type	In	Required	Description
ids		query		Return only products specified by a comma-separated list of product IDs.
limit		query		Return up to this many results per page. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
title		query		Filter results by product title.
vendor		query		Filter results by product vendor.
handle		query		Filter results by product handle.
product_type		query		Filter results by product type.
status		query		Return products by their status. (default: active) active: Show only active products. archived: Show only archived products.

collection_id	query	draft: Show only draft products. Filter results by product collection ID.
created_at_min	query	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	query	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	query	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	query	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	query	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	query	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	query	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.
fields	query	Show only certain fields, specified by a comma-separated list of field names.
presentment_currencies	query	Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

200

POST

/admin/api/2020-01/products.json

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

https://shopify.dev/docs/admin-api/rest/reference/products/product#create-2020-01

Responses

200

GET

/admin/api/2020-01/products/count.json

Retrieves a count of products.

https://shopify.dev/docs/admin-api/rest/reference/products/product#count-2020-01

Parameters

Name	Type	In	Required	Description
vendor		query		Filter results by product vendor.
product_type		query		Filter results by product type.
collection_id		query		Filter results by collection ID.
created_at_min		query		Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

200

GET

/admin/api/2020-01/products/{product_id}.json

Retrieves a single product.

https://shopify.dev/docs/admin-api/rest/reference/products/product#show-2020-01

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT

/admin/api/2020-01/products/{product_id}.json

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

https://shopify.dev/docs/admin-api/rest/reference/products/product#update-2020-01

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

DELETE

/admin/api/2020-01/products/{product_id}.json

Deletes a product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET

/admin/api/2020-04/products.json

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#index-2020-04>

Parameters

Name	Type	In	Required	Description
ids		query		Return only products specified by a comma-separated list of product IDs.
limit		query		Return up to this many results per page. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
title		query		Filter results by product title.
vendor		query		Filter results by product vendor.
handle		query		Filter results by product handle.
product_type		query		Filter results by product type.
status		query		Return products by their status. (default: active) active: Show only active products. archived: Show only archived products. draft: Show only draft products.
collection_id		query		Filter results by product collection ID.
created_at_min		query		Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.
fields		query		Show only certain fields, specified by a comma-separated list of field names.
presentment_currencies		query		Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

200

POST

/admin/api/2020-04/products.json

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#create-2020-04>

Responses

200

GET

/admin/api/2020-04/products/count.json

Retrieves a count of products.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#count-2020-04>

Parameters

Name	Type	In	Required	Description
vendor		query		Filter results by product vendor.
product_type		query		Filter results by product type.
collection_id		query		Filter results by collection ID.
created_at_min		query		Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show products published before date. (format: 2014-04-25T16:15:47-04:00)

published_status

query

Return products by their published status (default: any)
published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

200

GET

/admin/api/2020-04/products/{product_id}.json

Retrieves a single product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#show-2020-04>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT

/admin/api/2020-04/products/{product_id}.json

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#update-2020-04>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

DELETE

/admin/api/2020-04/products/{product_id}.json

Deletes a product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET

/admin/api/2020-07/products.json

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#index-2020-07>

Parameters

Name	Type	In	Required	Description
ids		query		Return only products specified by a comma-separated list of product IDs.
limit		query		Return up to this many results per page. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
title		query		Filter results by product title.
vendor		query		Filter results by product vendor.
handle		query		Filter results by product handle.
product_type		query		Filter results by product type.
status		query		Return products by their status. (default: active) active: Show only active products. archived: Show only archived products. draft: Show only draft products.
collection_id		query		Filter results by product collection ID.
created_at_min		query		Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

fields

presentment_currencies

query

query

Show only certain fields, specified by a comma-separated list of field names.
Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

200

POST

/admin/api/2020-07/products.json

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

https://shopify.dev/docs/admin-api/rest/reference/products/product#create-2020-07

Responses

200

GET

/admin/api/2020-07/products/count.json

Retrieves a count of products.

https://shopify.dev/docs/admin-api/rest/reference/products/product#count-2020-07

Parameters

Name	Type	In	Required	Description
vendor		query		Filter results by product vendor.
product_type		query		Filter results by product type.
collection_id		query		Filter results by collection ID.
created_at_min		query		Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

200

GET

/admin/api/2020-07/products/{product_id}.json

Retrieves a single product.

https://shopify.dev/docs/admin-api/rest/reference/products/product#show-2020-07

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT

/admin/api/2020-07/products/{product_id}.json

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

https://shopify.dev/docs/admin-api/rest/reference/products/product#update-2020-07

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

DELETE

/admin/api/2020-07/products/{product_id}.json

Deletes a product.

https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-2020-07

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET /admin/api/2020-10/products.json

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#index-2020-10>

Parameters

Name	Type	In	Required	Description
ids		query		Return only products specified by a comma-separated list of product IDs.
limit		query		Return up to this many results per page. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
title		query		Filter results by product title.
vendor		query		Filter results by product vendor.
handle		query		Filter results by product handle.
product_type		query		Filter results by product type.
status		query		Return products by their status. (default: active) active: Show only active products. archived: Show only archived products. draft: Show only draft products.
collection_id		query		Filter results by product collection ID.
created_at_min		query		Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.
fields		query		Show only certain fields, specified by a comma-separated list of field names.
presentment_currencies		query		Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

200

POST /admin/api/2020-10/products.json

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: `metafields_global_title_tag`: The name of the product used for SEO purposes. Generally added to the `<meta name="title">` tag. `metafields_global_description_tag`: A description of the product used for SEO purposes. Generally added to the `<meta name="description">` tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#create-2020-10>

Responses

200

GET /admin/api/2020-10/products/count.json

Retrieves a count of products.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#count-2020-10>

Parameters

Name	Type	In	Required	Description
vendor		query		Filter results by product vendor.
product_type		query		Filter results by product type.
collection_id		query		Filter results by collection ID.
created_at_min		query		Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

200

GET /admin/api/2020-10/products/{product_id}.json

Retrieves a single product.

Parameters

Name	Type	In	Required	Description
product_id fields	string	path query	required	product_id A comma-separated list of fields to include in the response.

Responses

200

PUT

/admin/api/2020-10/products/{product_id}.json

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

https://shopify.dev/docs/admin-api/rest/reference/products/product#update-2020-10

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

DELETE

/admin/api/2020-10/products/{product_id}.json

Deletes a product.

https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-2020-10

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET

/admin/api/2021-01/products.json

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/products/product#index-2021-01

Parameters

Name	Type	In	Required	Description
ids		query		Return only products specified by a comma-separated list of product IDs.
limit		query		Return up to this many results per page. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
title		query		Filter results by product title.
vendor		query		Filter results by product vendor.
handle		query		Filter results by product handle.
product_type		query		Filter results by product type.
status		query		Return products by their status. (default: active) active: Show only active products. archived: Show only archived products. draft: Show only draft products.
collection_id		query		Filter results by product collection ID.
created_at_min		query		Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.
fields		query		Show only certain fields, specified by a comma-separated list of field names.
presentment_currencies		query		Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

200

POST

/admin/api/2021-01/products.json

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

the <meta name='description'> tag.
<https://shopify.dev/docs/admin-api/rest/reference/products/product#create-2021-01>

Responses

200

GET /admin/api/2021-01/products/count.json

Retrieves a count of products.
<https://shopify.dev/docs/admin-api/rest/reference/products/product#count-2021-01>

Parameters

Name	Type	In	Required	Description
vendor		query		Filter results by product vendor.
product_type		query		Filter results by product type.
collection_id		query		Filter results by collection ID.
created_at_min		query		Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

200

GET /admin/api/2021-01/products/{product_id}.json

Retrieves a single product.
<https://shopify.dev/docs/admin-api/rest/reference/products/product#show-2021-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/2021-01/products/{product_id}.json

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
<https://shopify.dev/docs/admin-api/rest/reference/products/product#update-2021-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

DELETE /admin/api/2021-01/products/{product_id}.json

Deletes a product.
<https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET /admin/api/unstable/products.json

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

Parameters

Name	Type	In	Required	Description
ids		query		Return only products specified by a comma-separated list of product IDs.
limit		query		Return up to this many results per page. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
title		query		Filter results by product title.
vendor		query		Filter results by product vendor.
handle		query		Filter results by product handle.
product_type		query		Filter results by product type.
status		query		Return products by their status. (default: active) active: Show only active products. archived: Show only archived products. draft: Show only draft products.
collection_id		query		Filter results by product collection ID.
created_at_min		query		Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.
fields		query		Show only certain fields, specified by a comma-separated list of field names.
presentment_currencies		query		Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

200

POST

/admin/api/unstable/products.json

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: `metafields_global_title_tag`: The name of the product used for SEO purposes. Generally added to the `<meta name="title">` tag. `metafields_global_description_tag`: A description of the product used for SEO purposes. Generally added to the `<meta name="description">` tag.

https://shopify.dev/docs/admin-api/rest/reference/products/product#create-unstable

Responses

200

GET

/admin/api/unstable/products/count.json

Retrieves a count of products.

https://shopify.dev/docs/admin-api/rest/reference/products/product#count-unstable

Parameters

Name	Type	In	Required	Description
vendor		query		Filter results by product vendor.
product_type		query		Filter results by product type.
collection_id		query		Filter results by collection ID.
created_at_min		query		Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max		query		Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min		query		Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

200

GET

/admin/api/unstable/products/{product_id}.json

Retrieves a single product.

https://shopify.dev/docs/admin-api/rest/reference/products/product#show-unstable

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
fields		query		A comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/unstable/products/{product_id}.json

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#update-unstable>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

DELETE /admin/api/unstable/products/{product_id}.json

Deletes a product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-unstable>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET /admin/api/2020-01/products/{product_id}/images.json

Get all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-2020-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
since_id		query		Restrict results to after the specified ID
fields		query		comma-separated list of fields to include in the response

Responses

200

POST /admin/api/2020-01/products/{product_id}/images.json

Create a new product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-2020-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET /admin/api/2020-01/products/{product_id}/images/count.json

Get a count of all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-2020-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
since_id		query		Restrict results to after the specified ID

Responses

200

GET /admin/api/2020-01/products/{product_id}/images/{image_id}.json

Get a single product image by id

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-2020-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id
fields		query		comma-separated list of fields to include in the response

Responses

200

PUT /admin/api/2020-01/products/{product_id}/images/{image_id}.json

Modify an existing product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-2020-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id

Responses

200

DELETE /admin/api/2020-01/products/{product_id}/images/{image_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id

Responses

200

GET /admin/api/2020-04/products/{product_id}/images.json

Get all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-2020-04>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
since_id		query		Restrict results to after the specified ID
fields		query		comma-separated list of fields to include in the response

Responses

200

POST /admin/api/2020-04/products/{product_id}/images.json

Create a new product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-2020-04>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET /admin/api/2020-04/products/{product_id}/images/count.json

Get a count of all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-2020-04>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
since_id		query		Restrict results to after the specified ID

Responses

200

GET

/admin/api/2020-04/products/{product_id}/images/{image_id}.json

Get a single product image by id

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-2020-04>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id
fields		query		comma-separated list of fields to include in the response

Responses

200

PUT

/admin/api/2020-04/products/{product_id}/images/{image_id}.json

Modify an existing product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-2020-04>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id

Responses

200

DELETE

/admin/api/2020-04/products/{product_id}/images/{image_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id

Responses

200

GET

/admin/api/2020-07/products/{product_id}/images.json

Get all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-2020-07>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
since_id		query		Restrict results to after the specified ID
fields		query		comma-separated list of fields to include in the response

Responses

200

POST

/admin/api/2020-07/products/{product_id}/images.json

Create a new product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-2020-07>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET

/admin/api/2020-07/products/{product_id}/images/count.json

Get a count of all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-2020-07>

Parameters

Name	Type	In	Required	Description
product_id since_id	string	path query	required	product_id Restrict results to after the specified ID

Responses

200

GET /admin/api/2020-07/products/{product_id}/images/{image_id}.json

Get a single product image by id

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-2020-07>

Parameters

Name	Type	In	Required	Description
product_id image_id fields	string string	path path query	required required	product_id image_id comma-separated list of fields to include in the response

Responses

200

PUT /admin/api/2020-07/products/{product_id}/images/{image_id}.json

Modify an existing product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-2020-07>

Parameters

Name	Type	In	Required	Description
product_id image_id	string string	path path	required required	product_id image_id

Responses

200

DELETE /admin/api/2020-07/products/{product_id}/images/{image_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
product_id image_id	string string	path path	required required	product_id image_id

Responses

200

GET /admin/api/2020-10/products/{product_id}/images.json

Get all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-2020-10>

Parameters

Name	Type	In	Required	Description
product_id since_id fields	string	path query query	required	product_id Restrict results to after the specified ID comma-separated list of fields to include in the response

Responses

200

POST /admin/api/2020-10/products/{product_id}/images.json

Create a new product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-2020-10>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET

/admin/api/2020-10/products/{product_id}/images/count.json

Get a count of all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-2020-10>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
since_id		query		Restrict results to after the specified ID

Responses

200

GET

/admin/api/2020-10/products/{product_id}/images/{image_id}.json

Get a single product image by id

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-2020-10>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id
fields		query		comma-separated list of fields to include in the response

Responses

200

PUT

/admin/api/2020-10/products/{product_id}/images/{image_id}.json

Modify an existing product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-2020-10>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id

Responses

200

DELETE

/admin/api/2020-10/products/{product_id}/images/{image_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id

Responses

200

GET

/admin/api/2021-01/products/{product_id}/images.json

Get all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-2021-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
since_id		query		Restrict results to after the specified ID
fields		query		comma-separated list of fields to include in the response

Responses

200

POST /admin/api/2021-01/products/{product_id}/images.json

Create a new product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-2021-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET /admin/api/2021-01/products/{product_id}/images/count.json

Get a count of all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-2021-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
since_id		query		Restrict results to after the specified ID

Responses

200

GET /admin/api/2021-01/products/{product_id}/images/{image_id}.json

Get a single product image by id

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-2021-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id
fields		query		comma-separated list of fields to include in the response

Responses

200

PUT /admin/api/2021-01/products/{product_id}/images/{image_id}.json

Modify an existing product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-2021-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id

Responses

200

DELETE /admin/api/2021-01/products/{product_id}/images/{image_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id

Responses

200

GET /admin/api/unstable/products/{product_id}/images.json

Get all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-unstable>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
since_id		query		Restrict results to after the specified ID
fields		query		comma-separated list of fields to include in the response

Responses

200

POST /admin/api/unstable/products/{product_id}/images.json

Create a new product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-unstable>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id

Responses

200

GET /admin/api/unstable/products/{product_id}/images/count.json

Get a count of all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-unstable>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
since_id		query		Restrict results to after the specified ID

Responses

200

GET /admin/api/unstable/products/{product_id}/images/{image_id}.json

Get a single product image by id

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-unstable>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id
fields		query		comma-separated list of fields to include in the response

Responses

200

PUT /admin/api/unstable/products/{product_id}/images/{image_id}.json

Modify an existing product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-unstable>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id

Responses

200

DELETE /admin/api/unstable/products/{product_id}/images/{image_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-unstable>

Parameters

Name	Type	In	Required	Description
product_id	string	path	required	product_id
image_id	string	path	required	image_id

Responses

200

GET /admin/api/2020-01/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-2020-01>

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to show. (default: 50, maximum: 250)
ids		query		Show only the smart collections specified by a comma-separated list of IDs. Restrict results to after the specified ID.
since_id		query		
title		query		Show smart collections with the specified title.
product_id		query		Show smart collections that includes the specified product.
handle		query		Filter results by smart collection handle.
updated_at_min		query		Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-01/smart_collections.json

Creates a new smart collection using the specified rules.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-2020-01>

Responses

200

GET /admin/api/2020-01/smart_collections/count.json

Retrieves a count of smart collections

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-2020-01>

Parameters

Name	Type	In	Required	Description
title		query		Show smart collections with the specified title.
product_id		query		Show smart collections that include the specified product.
updated_at_min		query		Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.

Responses

200

GET /admin/api/2020-01/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-2020-01>

Parameters

Name	Type	In	Required	Description
smart_collection_id fields	string	path query	required	smart_collection_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-01/smart_collections/{smart_collection_id}.json

Updates an existing smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-2020-01>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

DELETE /admin/api/2020-01/smart_collections/{smart_collection_id}.json

Removes a smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

PUT /admin/api/2020-01/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-2020-01>

Parameters

Name	Type	In	Required	Description
smart_collection_id products	string	path query	required	smart_collection_id An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order		query		The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	integer	query		products[]

Responses

200

GET /admin/api/2020-04/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-2020-04>

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to show. (default: 50, maximum: 250)
ids		query		Show only the smart collections specified by a comma-separated list of IDs.
since_id		query		Restrict results to after the specified ID.
title		query		Show smart collections with the specified title.
product_id		query		Show smart collections that includes the specified product.
handle		query		Filter results by smart collection handle.
updated_at_min		query		Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only

fields

query

unpublished smart collections. any: Show all smart collections.
Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-04/smart_collections.json

Creates a new smart collection using the specified rules.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-2020-04>

Responses

200

GET

/admin/api/2020-04/smart_collections/count.json

Retrieves a count of smart collections

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-2020-04>

Parameters

Name	Type	In	Required	Description
title		query		Show smart collections with the specified title.
product_id		query		Show smart collections that include the specified product.
updated_at_min		query		Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.

Responses

200

GET

/admin/api/2020-04/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-2020-04>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-04/smart_collections/{smart_collection_id}.json

Updates an existing smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-2020-04>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

DELETE

/admin/api/2020-04/smart_collections/{smart_collection_id}.json

Removes a smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

PUT /admin/api/2020-04/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-2020-04>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id
products		query		An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order		query		The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	integer	query		products[]

Responses

200

GET /admin/api/2020-07/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-2020-07>

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to show. (default: 50, maximum: 250)
ids		query		Show only the smart collections specified by a comma-separated list of IDs.
since_id		query		Restrict results to after the specified ID.
title		query		Show smart collections with the specified title.
product_id		query		Show smart collections that includes the specified product.
handle		query		Filter results by smart collection handle.
updated_at_min		query		Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-07/smart_collections.json

Creates a new smart collection using the specified rules.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-2020-07>

Responses

200

GET /admin/api/2020-07/smart_collections/count.json

Retrieves a count of smart collections

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-2020-07>

Parameters

Name	Type	In	Required	Description
title		query		Show smart collections with the specified title.
product_id		query		Show smart collections that include the specified product.
updated_at_min		query		Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)

published_status

query

Filter results based on the published status of smart collections. (default: any)
published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.

Responses

200

GET /admin/api/2020-07/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-2020-07

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-07/smart_collections/{smart_collection_id}.json

Updates an existing smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-2020-07

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

DELETE /admin/api/2020-07/smart_collections/{smart_collection_id}.json

Removes a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-2020-07

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

PUT /admin/api/2020-07/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-2020-07

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id
products		query		An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order		query		The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	integer	query		products[]

Responses

200

GET /admin/api/2020-10/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-2020-10

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

limit	query	The number of results to show. (default: 50, maximum: 250)
ids	query	Show only the smart collections specified by a comma-separated list of IDs.
since_id	query	Restrict results to after the specified ID.
title	query	Show smart collections with the specified title.
product_id	query	Show smart collections that includes the specified product.
handle	query	Filter results by smart collection handle.
updated_at_min	query	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	query	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	query	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	query	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status	query	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.
fields	query	Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-10/smart_collections.json

Creates a new smart collection using the specified rules.
<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-2020-10>

Responses

200

GET

/admin/api/2020-10/smart_collections/count.json

Retrieves a count of smart collections
<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-2020-10>

Parameters

Name	Type	In	Required	Description
title		query		Show smart collections with the specified title.
product_id		query		Show smart collections that include the specified product.
updated_at_min		query		Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.

Responses

200

GET

/admin/api/2020-10/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection
<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-2020-10>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-10/smart_collections/{smart_collection_id}.json

Updates an existing smart collection
<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-2020-10>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

DELETE /admin/api/2020-10/smart_collections/{smart_collection_id}.json

Removes a smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

PUT /admin/api/2020-10/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-2020-10>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id
products		query		An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order		query		The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	integer	query		products[]

Responses

200

GET /admin/api/2021-01/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-2021-01>

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to show. (default: 50, maximum: 250)
ids		query		Show only the smart collections specified by a comma-separated list of IDs.
since_id		query		Restrict results to after the specified ID.
title		query		Show smart collections with the specified title.
product_id		query		Show smart collections that includes the specified product.
handle		query		Filter results by smart collection handle.
updated_at_min		query		Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2021-01/smart_collections.json

Creates a new smart collection using the specified rules.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-2021-01>

Responses

200

GET /admin/api/2021-01/smart_collections/count.json

Retrieves a count of smart collections

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-2021-01

Parameters

Name	Type	In	Required	Description
title		query		Show smart collections with the specified title.
product_id		query		Show smart collections that include the specified product.
updated_at_min		query		Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.

Responses

200

GET /admin/api/2021-01/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-2021-01

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2021-01/smart_collections/{smart_collection_id}.json

Updates an existing smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-2021-01

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

DELETE /admin/api/2021-01/smart_collections/{smart_collection_id}.json

Removes a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-2021-01

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

PUT /admin/api/2021-01/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-2021-01

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id
products		query		An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order		query		The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	integer	query		products[]

Responses

200

GET

/admin/api/unstable/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-unstable

Parameters

Name	Type	In	Required	Description
limit		query		The number of results to show. (default: 50, maximum: 250)
ids		query		Show only the smart collections specified by a comma-separated list of IDs.
since_id		query		Restrict results to after the specified ID.
title		query		Show smart collections with the specified title.
product_id		query		Show smart collections that includes the specified product.
handle		query		Filter results by smart collection handle.
updated_at_min		query		Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/unstable/smart_collections.json

Creates a new smart collection using the specified rules.

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-unstable

Responses

200

GET

/admin/api/unstable/smart_collections/count.json

Retrieves a count of smart collections

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-unstable

Parameters

Name	Type	In	Required	Description
title		query		Show smart collections with the specified title.
product_id		query		Show smart collections that include the specified product.
updated_at_min		query		Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max		query		Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min		query		Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max		query		Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status		query		Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.

Responses

200

GET

/admin/api/unstable/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-unstable

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/unstable/smart_collections/{smart_collection_id}.json

Updates an existing smart collection
<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-unstable>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

DELETE

/admin/api/unstable/smart_collections/{smart_collection_id}.json

Removes a smart collection
<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-unstable>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id

Responses

200

PUT

/admin/api/unstable/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection
<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-unstable>

Parameters

Name	Type	In	Required	Description
smart_collection_id	string	path	required	smart_collection_id
products		query		An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order		query		The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	integer	query		products[]

Responses

200

POST

/admin/api/2020-01/checkouts/{token}/complete.json

Completes a checkout
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-2020-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET

/admin/api/2020-01/checkouts/{token}.json

Retrieves a checkout
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-2020-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

PUT /admin/api/2020-01/checkouts/{token}.json

Modifies an existing checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-2020-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2020-01/checkouts/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-2020-01

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

POST /admin/api/2020-04/checkouts/{token}/complete.json

Completes a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-2020-04>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2020-04/checkouts/{token}.json

Retrieves a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-2020-04>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

PUT /admin/api/2020-04/checkouts/{token}.json

Modifies an existing checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-2020-04>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2020-04/checkouts/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-2020-04

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

POST /admin/api/2020-07/checkouts/{token}/complete.json

Completes a checkout
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-2020-07>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2020-07/checkouts/{token}.json

Retrieves a checkout
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-2020-07>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

PUT /admin/api/2020-07/checkouts/{token}.json

Modifies an existing checkout
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-2020-07>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2020-07/checkouts/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-2020-07

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

POST /admin/api/2020-10/checkouts/{token}/complete.json

Completes a checkout
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-2020-10>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2020-10/checkouts/{token}.json

Retrieves a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-2020-10>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

PUT /admin/api/2020-10/checkouts/{token}.json

Modifies an existing checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-2020-10>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2020-10/checkouts/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-2020-10

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

POST /admin/api/2021-01/checkouts/{token}/complete.json

Completes a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-2021-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2021-01/checkouts/{token}.json

Retrieves a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-2021-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

PUT /admin/api/2021-01/checkouts/{token}.json

Modifies an existing checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-2021-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2021-01/checkouts/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-2021-01

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

POST /admin/api/unstable/checkouts/{token}/complete.json

Completes a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-unstable>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/unstable/checkouts/{token}.json

Retrieves a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-unstable>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

PUT /admin/api/unstable/checkouts/{token}.json

Modifies an existing checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-unstable>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/unstable/checkouts/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-unstable

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2020-01/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-2020-01>

Parameters

Name	Type	In	Required	Description
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET /admin/api/2020-01/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-2020-01

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET /admin/api/2020-01/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-2020-01>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

PUT /admin/api/2020-01/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-2020-01>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

DELETE /admin/api/2020-01/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

GET /admin/api/2020-04/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-2020-04>

Parameters

Name	Type	In	Required	Description
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET /admin/api/2020-04/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-2020-04

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET /admin/api/2020-04/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-2020-04>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

PUT /admin/api/2020-04/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-2020-04>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

DELETE /admin/api/2020-04/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

GET /admin/api/2020-07/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-2020-07>

Parameters

Name	Type	In	Required	Description
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

GET

/admin/api/2020-07/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-2020-07

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET

/admin/api/2020-07/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-2020-07

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

PUT

/admin/api/2020-07/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-2020-07

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

DELETE

/admin/api/2020-07/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-2020-07

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

GET

/admin/api/2020-10/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-2020-10

Parameters

Name	Type	In	Required	Description
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET

/admin/api/2020-10/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-2020-10

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET /admin/api/2020-10/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-2020-10

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

PUT /admin/api/2020-10/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-2020-10

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

DELETE /admin/api/2020-10/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-2020-10

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

GET /admin/api/2021-01/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-2021-01

Parameters

Name	Type	In	Required	Description
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET /admin/api/2021-01/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-2021-01

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET

/admin/api/2021-01/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-2021-01>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

PUT

/admin/api/2021-01/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-2021-01>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

DELETE

/admin/api/2021-01/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

GET

/admin/api/unstable/collection_listings.json

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-unstable>

Parameters

Name	Type	In	Required	Description
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET

/admin/api/unstable/collection_listings/{collection_listing_id}/product_ids.json

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-unstable

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET

/admin/api/unstable/collection_listings/{collection_listing_id}.json

Retrieve a specific collection listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-unstable>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

PUT

/admin/api/unstable/collection_listings/{collection_listing_id}.json

Create a collection listing to publish a collection to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-unstable>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

DELETE

/admin/api/unstable/collection_listings/{collection_listing_id}.json

Delete a collection listing to unpublish a collection from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-unstable>

Parameters

Name	Type	In	Required	Description
collection_listing_id	string	path	required	collection_listing_id

Responses

200

GET

/admin/api/2020-01/checkouts/{token}/payments.json

Retrieves a list of payments on a particular checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-2020-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

POST

/admin/api/2020-01/checkouts/{token}/payments.json

Creates a payment on a checkout using the session ID returned by the card vault

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-2020-01

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
amount required		query		The amount of the payment.
request_details required		query		The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.
session_id required		query		A session ID provided by the card vault when creating a payment session.
unique_token required		query		A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Responses

200

GET

/admin/api/2020-01/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-2020-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
payment_id	string	path	required	payment_id

Responses

200

GET

/admin/api/2020-01/checkouts/{token}/payments/count.json

Counts the number of payments attempted on a checkout
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-2020-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET

/admin/api/2020-04/checkouts/{token}/payments.json

Retrieves a list of payments on a particular checkout
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-2020-04>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

POST

/admin/api/2020-04/checkouts/{token}/payments.json

Creates a payment on a checkout using the session ID returned by the card vault
https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-2020-04

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
amount	required	query		The amount of the payment.
request_details	required	query		The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.
session_id	required	query		A session ID provided by the card vault when creating a payment session.
unique_token	required	query		A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Responses

200

GET

/admin/api/2020-04/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-2020-04>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
payment_id	string	path	required	payment_id

Responses

200

GET

/admin/api/2020-04/checkouts/{token}/payments/count.json

Counts the number of payments attempted on a checkout
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-2020-04>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2020-07/checkouts/{token}/payments.json

Retrieves a list of payments on a particular checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-2020-07>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

POST /admin/api/2020-07/checkouts/{token}/payments.json

Creates a payment on a checkout using the session ID returned by the card vault

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-2020-07

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
amount required		query		The amount of the payment.
request_details required		query		The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.
session_id required		query		A session ID provided by the card vault when creating a payment session.
unique_token required		query		A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Responses

200

GET /admin/api/2020-07/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-2020-07>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
payment_id	string	path	required	payment_id

Responses

200

GET /admin/api/2020-07/checkouts/{token}/payments/count.json

Counts the number of payments attempted on a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-2020-07>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2020-10/checkouts/{token}/payments.json

Retrieves a list of payments on a particular checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-2020-10>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

POST /admin/api/2020-10/checkouts/{token}/payments.json

Creates a payment on a checkout using the session ID returned by the card vault

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-2020-10

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
amount required		query		The amount of the payment.
request_details required		query		The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.
session_id required		query		A session ID provided by the card vault when creating a payment session.
unique_token required		query		A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Responses

200

GET /admin/api/2020-10/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-2020-10>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
payment_id	string	path	required	payment_id

Responses

200

GET /admin/api/2020-10/checkouts/{token}/payments/count.json

Counts the number of payments attempted on a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-2020-10>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/2021-01/checkouts/{token}/payments.json

Retrieves a list of payments on a particular checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-2021-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

POST /admin/api/2021-01/checkouts/{token}/payments.json

Creates a payment on a checkout using the session ID returned by the card vault

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-2021-01

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
amount required		query		The amount of the payment.
request_details required		query		The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.
session_id required		query		A session ID provided by the card vault when creating a payment session.
unique_token required		query		A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Responses

200

GET /admin/api/2021-01/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-2021-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
payment_id	string	path	required	payment_id

Responses

200

GET /admin/api/2021-01/checkouts/{token}/payments/count.json

Counts the number of payments attempted on a checkout
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-2021-01>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET /admin/api/unstable/checkouts/{token}/payments.json

Retrieves a list of payments on a particular checkout
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-unstable>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

POST /admin/api/unstable/checkouts/{token}/payments.json

Creates a payment on a checkout using the session ID returned by the card vault
https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-unstable

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
amount required		query		The amount of the payment.
request_details required		query		The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.
session_id required		query		A session ID provided by the card vault when creating a payment session.
unique_token required		query		A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Responses

GET

/admin/api/unstable/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-unstable>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token
payment_id	string	path	required	payment_id

Responses

200

GET

/admin/api/unstable/checkouts/{token}/payments/count.json

Counts the number of payments attempted on a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-unstable>

Parameters

Name	Type	In	Required	Description
token	string	path	required	token

Responses

200

GET

/admin/api/2020-01/product_listings.json

Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#index-2020-01>

Parameters

Name	Type	In	Required	Description
product_ids		query		A comma-separated list of product ids
limit		query		Amount of results (default: 50, maximum: 1000)
collection_id		query		Filter by products belonging to a particular collection
updated_at_min		query		Filter by products last updated after a certain date and time (formatted in ISO 8601)
handle		query		Filter by product handle

Responses

200

GET

/admin/api/2020-01/product_listings/product_ids.json

Retrieve product_ids that are published to your app. Maximum 1,000 results per page.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#product_ids-2020-01

Parameters

Name	Type	In	Required	Description
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET

/admin/api/2020-01/product_listings/count.json

Retrieve a count of products that are published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#count-2020-01>

Responses

200

GET

/admin/api/2020-01/product_listings/{product_listing_id}.json

Retrieve a specific product listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#show-2020-01>

Parameters

Name	Type	In	Required	Description
product_listing_id	string	path	required	product_listing_id

Responses

200

PUT

/admin/api/2020-01/product_listings/{product_listing_id}.json

Create a product listing to publish a product to your app
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#create-2020-01>

Parameters

Name	Type	In	Required	Description
product_listing_id	string	path	required	product_listing_id

Responses

200

DELETE

/admin/api/2020-01/product_listings/{product_listing_id}.json

Delete a product listing to unpublish a product from your app
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
product_listing_id	string	path	required	product_listing_id

Responses

200

GET

/admin/api/2020-04/product_listings.json

Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#index-2020-04>

Parameters

Name	Type	In	Required	Description
product_ids		query		A comma-separated list of product ids
limit		query		Amount of results (default: 50, maximum: 1000)
collection_id		query		Filter by products belonging to a particular collection
updated_at_min		query		Filter by products last updated after a certain date and time (formatted in ISO 8601)
handle		query		Filter by product handle

Responses

200

GET

/admin/api/2020-04/product_listings/product_ids.json

Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#product_ids-2020-04

Parameters

Name	Type	In	Required	Description
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET

/admin/api/2020-04/product_listings/count.json

Retrieve a count of products that are published to your app
<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#count-2020-04>

Responses

200

GET /admin/api/2020-04/product_listings/{product_listing_id}.json

Retrieve a specific product listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#show-2020-04>

Parameters

Name	Type	In	Required	Description
product_listing_id	string	path	required	product_listing_id

Responses

200

PUT /admin/api/2020-04/product_listings/{product_listing_id}.json

Create a product listing to publish a product to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#create-2020-04>

Parameters

Name	Type	In	Required	Description
product_listing_id	string	path	required	product_listing_id

Responses

200

DELETE /admin/api/2020-04/product_listings/{product_listing_id}.json

Delete a product listing to unpublish a product from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
product_listing_id	string	path	required	product_listing_id

Responses

200

GET /admin/api/2020-07/product_listings.json

Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#index-2020-07>

Parameters

Name	Type	In	Required	Description
product_ids		query		A comma-separated list of product ids
limit		query		Amount of results (default: 50, maximum: 1000)
collection_id		query		Filter by products belonging to a particular collection
updated_at_min		query		Filter by products last updated after a certain date and time (formatted in ISO 8601)
handle		query		Filter by product handle

Responses

200

GET /admin/api/2020-07/product_listings/product_ids.json

Retrieve product_ids that are published to your app. Maximum 1,000 results per page.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#product_ids-2020-07

Parameters

Name	Type	In	Required	Description
limit		query		Amount of results (default: 50, maximum: 1000)

Responses

200

GET /admin/api/2020-07/product_listings/count.json

Retrieve a count of products that are published to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#count-2020-07

Responses

200

GET /admin/api/2020-07/product_listings/{product_listing_id}.json

Retrieve a specific product listing that is published to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#show-2020-07

Parameters

Name	Type	In	Required	Description
product_listing_id	string	path	required	product_listing_id

Responses

200

PUT /admin/api/2020-07/product_listings/{product_listing_id}.json

Create a product listing to publish a product to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#create-2020-07

Parameters

Name	Type	In	Required	Description
product_listing_id	string	path	required	product_listing_id

Responses

200

DELETE /admin/api/2020-07/product_listings/{product_listing_id}.json

Delete a product listing to unpublish a product from your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#destroy-2020-07

Parameters

Name	Type	In	Required	Description
product_listing_id	string	path	required	product_listing_id

Responses

200

GET /admin/api/2020-01/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-2020-01

Parameters

Name	Type	In	Required	Description
assignment_status		query		The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items. The IDs of the assigned locations of the fulfillment orders that should be returned. location_ids[]
location_ids		query		
location_ids[]	integer	query		

Responses

200

GET /admin/api/2020-04/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-2020-04

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

assignment_status		query	The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items. The IDs of the assigned locations of the fulfillment orders that should be returned. location_ids[]
location_ids		query	
location_ids[]	integer	query	

Responses

200

GET /admin/api/2020-07/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-2020-07>

Parameters

Name	Type	In	Required	Description
assignment_status		query		The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items. The IDs of the assigned locations of the fulfillment orders that should be returned. location_ids[]
location_ids		query		
location_ids[]	integer	query		

Responses

200

GET /admin/api/2020-10/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-2020-10>

Parameters

Name	Type	In	Required	Description
assignment_status		query		The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items. The IDs of the assigned locations of the fulfillment orders that should be returned. location_ids[]
location_ids		query		
location_ids[]	integer	query		

Responses

200

GET /admin/api/2021-01/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-2021-01>

Parameters

Name	Type	In	Required	Description
assignment_status		query		The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items. The IDs of the assigned locations of the fulfillment orders that should be returned. location_ids[]
location_ids		query		
location_ids[]	integer	query		

Responses

200

GET /admin/api/unstable/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-unstable>

Parameters

Name	Type	In	Required	Description
assignment_status		query		The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items. The IDs of the assigned locations of the fulfillment orders that should be returned. location_ids[]
location_ids		query		
location_ids[]	integer	query		

Responses

200

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Sends a cancellation request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for the cancellation request.

Responses

200

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for accepting the cancellation request.

Responses

200

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for rejecting the cancellation request.

Responses

200

POST /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Sends a cancellation request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for the cancellation request.

Responses

POST

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for accepting the cancellation request.

Responses

200

POST

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for rejecting the cancellation request.

Responses

200

POST

/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Sends a cancellation request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-2020-07>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for the cancellation request.

Responses

200

POST

/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-2020-07>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for accepting the cancellation request.

Responses

200

POST

/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-2020-07>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for rejecting the cancellation request.

Responses

200

POST

/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Sends a cancellation request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for the cancellation request.

Responses

200

POST

/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for accepting the cancellation request.

Responses

200

POST

/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for rejecting the cancellation request.

Responses

200

POST

/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Sends a cancellation request to the fulfillment service of a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-2021-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for the cancellation request.

Responses

200

POST

/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-2021-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for accepting the cancellation request.

Responses

200

POST

/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-2021-01>

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for rejecting the cancellation request.
---------------------------------	--------	---------------	----------	--

Responses

200

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Sends a cancellation request to the fulfillment service of a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for the cancellation request.

Responses

200

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for accepting the cancellation request.

Responses

200

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for rejecting the cancellation request.

Responses

200

GET /admin/api/2020-01/carrier_services.json

Retrieves a list of carrier services
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-2020-01>

Responses

200

POST /admin/api/2020-01/carrier_services.json

Creates a carrier service
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-2020-01>

Responses

200

GET /admin/api/2020-01/carrier_services/{carrier_service_id}.json

Retrieves a single carrier service by its ID
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-2020-01>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

PUT

/admin/api/2020-01/carrier_services/{carrier_service_id}.json

Updates a carrier service. Only the app that creates a carrier service can update it.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-2020-01>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

DELETE

/admin/api/2020-01/carrier_services/{carrier_service_id}.json

Deletes a carrier service
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

GET

/admin/api/2020-04/carrier_services.json

Retrieves a list of carrier services
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-2020-04>

Responses

200

POST

/admin/api/2020-04/carrier_services.json

Creates a carrier service
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-2020-04>

Responses

200

GET

/admin/api/2020-04/carrier_services/{carrier_service_id}.json

Retrieves a single carrier service by its ID
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-2020-04>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

PUT

/admin/api/2020-04/carrier_services/{carrier_service_id}.json

Updates a carrier service. Only the app that creates a carrier service can update it.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-2020-04>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

DELETE

/admin/api/2020-04/carrier_services/{carrier_service_id}.json

Deletes a carrier service

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

GET /admin/api/2020-07/carrier_services.json

Retrieves a list of carrier services

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-2020-07>

Responses

200

POST /admin/api/2020-07/carrier_services.json

Creates a carrier service

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-2020-07>

Responses

200

GET /admin/api/2020-07/carrier_services/{carrier_service_id}.json

Retrieves a single carrier service by its ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-2020-07>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

PUT /admin/api/2020-07/carrier_services/{carrier_service_id}.json

Updates a carrier service. Only the app that creates a carrier service can update it.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-2020-07>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

DELETE /admin/api/2020-07/carrier_services/{carrier_service_id}.json

Deletes a carrier service

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-2020-07>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

GET /admin/api/2020-10/carrier_services.json

Retrieves a list of carrier services

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-2020-10>

Responses

POST /admin/api/2020-10/carrier_services.json

Creates a carrier service
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-2020-10>

Responses

200

GET /admin/api/2020-10/carrier_services/{carrier_service_id}.json

Retrieves a single carrier service by its ID
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-2020-10>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

PUT /admin/api/2020-10/carrier_services/{carrier_service_id}.json

Updates a carrier service. Only the app that creates a carrier service can update it.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-2020-10>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

DELETE /admin/api/2020-10/carrier_services/{carrier_service_id}.json

Deletes a carrier service
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

GET /admin/api/2021-01/carrier_services.json

Retrieves a list of carrier services
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-2021-01>

Responses

200

POST /admin/api/2021-01/carrier_services.json

Creates a carrier service
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-2021-01>

Responses

200

GET /admin/api/2021-01/carrier_services/{carrier_service_id}.json

Retrieves a single carrier service by its ID
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-2021-01>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

PUT /admin/api/2021-01/carrier_services/{carrier_service_id}.json

Updates a carrier service. Only the app that creates a carrier service can update it.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-2021-01>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

DELETE /admin/api/2021-01/carrier_services/{carrier_service_id}.json

Deletes a carrier service

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

GET /admin/api/unstable/carrier_services.json

Retrieves a list of carrier services

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-unstable>

Responses

200

POST /admin/api/unstable/carrier_services.json

Creates a carrier service

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-unstable>

Responses

200

GET /admin/api/unstable/carrier_services/{carrier_service_id}.json

Retrieves a single carrier service by its ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-unstable>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

PUT /admin/api/unstable/carrier_services/{carrier_service_id}.json

Updates a carrier service. Only the app that creates a carrier service can update it.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-unstable>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

DELETE

/admin/api/unstable/carrier_services/{carrier_service_id}.json

Deletes a carrier service

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-unstable>

Parameters

Name	Type	In	Required	Description
carrier_service_id	string	path	required	carrier_service_id

Responses

200

GET

/admin/api/2020-01/orders/{order_id}/fulfillments.json

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#index-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_max		query		Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min		query		Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields		query		A comma-separated list of fields to include in the response.
limit		query		Limit the amount of results. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
updated_at_max		query		Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST

/admin/api/2020-01/orders/{order_id}/fulfillments.json

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#create-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET

/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#indexV2-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
fulfillment_order_id		query		The ID of the fulfillment order that is associated with the fulfillments.

Responses

200

GET

/admin/api/2020-01/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_min		query		Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).

Responses

200

GET /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fields		query		Comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST /admin/api/2020-01/fulfillments.json

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-2020-01>

Responses

200

POST /admin/api/2020-01/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-2020-01

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#complete-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

POST

/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancel-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-01/fulfillments/{fulfillment_id}/cancel.json

Cancels a fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancelV2-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET

/admin/api/2020-04/orders/{order_id}/fulfillments.json

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#index-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_max		query		Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min		query		Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields		query		A comma-separated list of fields to include in the response.
limit		query		Limit the amount of results. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
updated_at_max		query		Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST

/admin/api/2020-04/orders/{order_id}/fulfillments.json

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#create-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#indexV2-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
fulfillment_order_id		query		The ID of the fulfillment order that is associated with the fulfillments.

Responses

200

GET

/admin/api/2020-04/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_min		query		Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).

Responses

200

GET

/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fields		query		Comma-separated list of fields to include in the response.

Responses

200

PUT

/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-04/fulfillments.json

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-2020-04>

Responses

POST

/admin/api/2020-04/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-2020-04

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#complete-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancel-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-04/fulfillments/{fulfillment_id}/cancel.json

Cancels a fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancelV2-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET

/admin/api/2020-07/orders/{order_id}/fulfillments.json

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_max		query		Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min		query		Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields		query		A comma-separated list of fields to include in the response.
limit		query		Limit the amount of results. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
updated_at_max		query		Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST /admin/api/2020-07/orders/{order_id}/fulfillments.json

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#create-2020-07

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#indexV2-2020-07

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
fulfillment_order_id		query		The ID of the fulfillment order that is associated with the fulfillments.

Responses

200

GET /admin/api/2020-07/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-2020-07

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_min		query		Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).

Responses

200

GET /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-2020-07

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fields		query		Comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-2020-07>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST /admin/api/2020-07/fulfillments.json

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-2020-07>

Responses

200

POST /admin/api/2020-07/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-2020-07

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#complete-2020-07>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-2020-07>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST /admin/api/2020-07/fulfillments/{fulfillment_id}/cancel.json

Cancels a fulfillment.

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET /admin/api/2020-10/orders/{order_id}/fulfillments.json

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_max	query			Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min	query			Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields	query			A comma-separated list of fields to include in the response.
limit	query			Limit the amount of results. (default: 50, maximum: 250)
since_id	query			Restrict results to after the specified ID.
updated_at_max	query			Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	query			Show fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST /admin/api/2020-10/orders/{order_id}/fulfillments.json

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
fulfillment_order_id	query			The ID of the fulfillment order that is associated with the fulfillments.

Responses

200

GET

/admin/api/2020-10/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-2020-10

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_min		query		Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).

Responses

200

GET

/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-2020-10

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fields		query		Comma-separated list of fields to include in the response.

Responses

200

PUT

/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-2020-10

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-10/fulfillments.json

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-2020-10

Responses

200

POST

/admin/api/2020-10/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-2020-10

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-2020-10

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancel-2020-10

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2020-10/fulfillments/{fulfillment_id}/cancel.json

Cancels a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancelV2-2020-10

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET

/admin/api/2021-01/orders/{order_id}/fulfillments.json

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#index-2021-01

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_max		query		Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min		query		Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields		query		A comma-separated list of fields to include in the response.
limit		query		Limit the amount of results. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
updated_at_max		query		Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST

/admin/api/2021-01/orders/{order_id}/fulfillments.json

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#create-2021-01

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#indexV2-2021-01

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
fulfillment_order_id		query		The ID of the fulfillment order that is associated with the fulfillments.

Responses

200

GET /admin/api/2021-01/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-2021-01

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_min		query		Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).

Responses

200

GET /admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-2021-01

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fields		query		Comma-separated list of fields to include in the response.

Responses

200

PUT /admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-2021-01

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2021-01/fulfillments.json

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-2021-01>

Responses

200

POST

/admin/api/2021-01/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-2021-01

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#complete-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancel-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/2021-01/fulfillments/{fulfillment_id}/cancel.json

Cancels a fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancelV2-2021-01>

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET /admin/api/unstable/orders/{order_id}/fulfillments.json

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#index-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_max		query		Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min		query		Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields		query		A comma-separated list of fields to include in the response.
limit		query		Limit the amount of results. (default: 50, maximum: 250)
since_id		query		Restrict results to after the specified ID.
updated_at_max		query		Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Show fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).

Responses

200

POST /admin/api/unstable/orders/{order_id}/fulfillments.json

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#create-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

Responses

200

GET /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#indexV2-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
fulfillment_order_id		query		The ID of the fulfillment order that is associated with the fulfillments.

Responses

200

GET /admin/api/unstable/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
created_at_min		query		Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max		query		Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min		query		Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max		query		Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).

Responses

200

GET

/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fields		query		Comma-separated list of fields to include in the response.

Responses

200

PUT

/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/unstable/fulfillments.json

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-unstable>

Responses

200

POST

/admin/api/unstable/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-unstable

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#complete-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST

/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST /admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancel-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

POST /admin/api/unstable/fulfillments/{fulfillment_id}/cancel.json

Cancels a fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancelV2-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Retrieves a list of fulfillment events for a specific fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fulfillment_id		query		The ID of the fulfillment that's associated with the fulfillment event.
order_id		query		The ID of the order that's associated with the fulfillment event.

Responses

200

POST /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Creates a fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Retrieves a specific fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id

event_id

query

The ID of the fulfillment event.

Responses

200

DELETE

/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Deletes a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-2020-01

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id

Responses

200

GET

/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Retrieves a list of fulfillment events for a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-2020-04

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fulfillment_id		query		The ID of the fulfillment that's associated with the fulfillment event.
order_id		query		The ID of the order that's associated with the fulfillment event.

Responses

200

POST

/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Creates a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-2020-04

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET

/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Retrieves a specific fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-2020-04

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id
event_id		query		The ID of the fulfillment event.

Responses

200

DELETE

/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Deletes a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-2020-04

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id

fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id

Responses

200

GET /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Retrieves a list of fulfillment events for a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-2020-07

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fulfillment_id		query		The ID of the fulfillment that's associated with the fulfillment event.
order_id		query		The ID of the order that's associated with the fulfillment event.

Responses

200

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Creates a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-2020-07

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Retrieves a specific fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-2020-07

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id
event_id		query		The ID of the fulfillment event.

Responses

200

DELETE /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Deletes a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-2020-07

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id

Responses

200

GET /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Retrieves a list of fulfillment events for a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-2020-10

Parameters

Name	Type	In	Required	Description
------	------	----	----------	-------------

order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fulfillment_id		query		The ID of the fulfillment that's associated with the fulfillment event.
order_id		query		The ID of the order that's associated with the fulfillment event.

Responses

200

POST

/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Creates a fulfillment event
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET

/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Retrieves a specific fulfillment event
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id
event_id		query		The ID of the fulfillment event.

Responses

200

DELETE

/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Deletes a fulfillment event
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id

Responses

200

GET

/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Retrieves a list of fulfillment events for a specific fulfillment
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fulfillment_id		query		The ID of the fulfillment that's associated with the fulfillment event.
order_id		query		The ID of the order that's associated with the fulfillment event.

Responses

200

POST

/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Creates a fulfillment event
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET /admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Retrieves a specific fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id
event_id		query		The ID of the fulfillment event.

Responses

200

DELETE /admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Deletes a fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id

Responses

200

GET /admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Retrieves a list of fulfillment events for a specific fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
fulfillment_id		query		The ID of the fulfillment that's associated with the fulfillment event.
order_id		query		The ID of the order that's associated with the fulfillment event.

Responses

200

POST /admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Creates a fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id

Responses

200

GET /admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Retrieves a specific fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id
event_id		query		The ID of the fulfillment event.

Responses

200

DELETE /admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Deletes a fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
fulfillment_id	string	path	required	fulfillment_id
event_id	string	path	required	event_id

Responses

200

GET /admin/api/2020-01/orders/{order_id}/fulfillment_orders.json

Retrieves a list of fulfillment orders for a specific order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#index-2020-01>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
order_id		query		The ID of the order that is associated with the fulfillment orders.

Responses

200

GET /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}.json

Retrieves a specific fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#show-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancel.json

Marks a fulfillment order as cancelled.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#cancel-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#close-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for marking the fulfillment order as incomplete.

Responses

200

POST

/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#move-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
new_location_id		query		The id of the location to which the fulfillment order will be moved.

Responses

200

GET

/admin/api/2020-04/orders/{order_id}/fulfillment_orders.json

Retrieves a list of fulfillment orders for a specific order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#index-2020-04>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
order_id		query		The ID of the order that is associated with the fulfillment orders.

Responses

200

GET

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}.json

Retrieves a specific fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#show-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancel.json

Marks a fulfillment order as cancelled.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#cancel-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#close-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for marking the fulfillment order as incomplete.

Responses

200

POST

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.

Parameters

Name	Type	In	Required	Description
fulfillment_order_id new_location_id	string	path query	required	fulfillment_order_id The id of the location to which the fulfillment order will be moved.

Responses

200

GET

/admin/api/2020-07/orders/{order_id}/fulfillment_orders.json

Retrieves a list of fulfillment orders for a specific order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#index-2020-07

Parameters

Name	Type	In	Required	Description
order_id order_id	string	path query	required	order_id The ID of the order that is associated with the fulfillment orders.

Responses

200

GET

/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}.json

Retrieves a specific fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#show-2020-07

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST

/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancel.json

Marks a fulfillment order as cancelled.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#cancel-2020-07

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST

/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#close-2020-07

Parameters

Name	Type	In	Required	Description
fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for marking the fulfillment order as incomplete.

Responses

200

POST

/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#move-2020-07

Parameters

Name	Type	In	Required	Description
fulfillment_order_id new_location_id	string	path query	required	fulfillment_order_id The id of the location to which the fulfillment order will be moved.

Responses

200

GET /admin/api/2020-10/orders/{order_id}/fulfillment_orders.json

Retrieves a list of fulfillment orders for a specific order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#index-2020-10>

Parameters

Name	Type	In	Required	Description
order_id order_id	string	path query	required	order_id The ID of the order that is associated with the fulfillment orders.

Responses

200

GET /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}.json

Retrieves a specific fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#show-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancel.json

Marks a fulfillment order as cancelled.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#cancel-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#close-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for marking the fulfillment order as incomplete.

Responses

200

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#move-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id new_location_id	string	path query	required	fulfillment_order_id The id of the location to which the fulfillment order will be moved.

Responses

200

GET /admin/api/2021-01/orders/{order_id}/fulfillment_orders.json

Retrieves a list of fulfillment orders for a specific order.

Parameters

Name	Type	In	Required	Description
order_id order_id	string	path query	required	order_id The ID of the order that is associated with the fulfillment orders.

Responses

200

GET /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}.json

Retrieves a specific fulfillment order.

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancel.json

Marks a fulfillment order as cancelled.

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

Parameters

Name	Type	In	Required	Description
fulfillment_order_id message	string	path query	required	fulfillment_order_id An optional reason for marking the fulfillment order as incomplete.

Responses

200

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.

Parameters

Name	Type	In	Required	Description
fulfillment_order_id new_location_id	string	path query	required	fulfillment_order_id The id of the location to which the fulfillment order will be moved.

Responses

200

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/open.json

Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST

/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/reschedule.json

Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#reschedule-2021-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

GET

/admin/api/unstable/orders/{order_id}/fulfillment_orders.json

Retrieves a list of fulfillment orders for a specific order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#index-unstable>

Parameters

Name	Type	In	Required	Description
order_id	string	path	required	order_id
order_id		query		The ID of the order that is associated with the fulfillment orders.

Responses

200

GET

/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}.json

Retrieves a specific fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#show-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST

/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancel.json

Marks a fulfillment order as cancelled.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#cancel-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST

/admin/api/unstable/fulfillment_orders/release_hold.json

Releases the fulfillment order holds for a specific order. Fulfillment orders are created with an ON_HOLD status if the channel that created the order has a fulfillment hold policy.
https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#release_hold-unstable

Parameters

Name	Type	In	Required	Description
order_id		query		The ID of the order that is associated to the fulfillment orders.

Responses

200

POST

/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#close-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for marking the fulfillment order as incomplete.

Responses

200

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#move-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
new_location_id		query		The id of the location to which the fulfillment order will be moved.

Responses

200

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/open.json

Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#open-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/reschedule.json

Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#reschedule-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id

Responses

200

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional message for the fulfillment request.
fulfillment_order_line_items		query		The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Responses

200

POST /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for accepting the fulfillment request.

Responses

200

POST

/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for rejecting the fulfillment request.

Responses

200

POST

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional message for the fulfillment request.
fulfillment_order_line_items		query		The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Responses

200

POST

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for accepting the fulfillment request.

Responses

200

POST

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for rejecting the fulfillment request.

Responses

200

POST

/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.
<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-2020-07>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional message for the fulfillment request.
fulfillment_order_line_items		query		The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Responses

POST

/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-2020-07>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for accepting the fulfillment request.

Responses

200

POST

/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-2020-07>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for rejecting the fulfillment request.

Responses

200

POST

/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional message for the fulfillment request.
fulfillment_order_line_items		query		The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Responses

200

POST

/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for accepting the fulfillment request.

Responses

200

POST

/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for rejecting the fulfillment request.

Responses

200

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-2021-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional message for the fulfillment request.
fulfillment_order_line_items		query		The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Responses

200

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-2021-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for accepting the fulfillment request.

Responses

200

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-2021-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for rejecting the fulfillment request.

Responses

200

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional message for the fulfillment request.
fulfillment_order_line_items		query		The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Responses

200

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for accepting the fulfillment request.

Responses

200

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
message		query		An optional reason for rejecting the fulfillment request.

Responses

200

GET /fetch_tracking_numbers

Get tracking numbers for orders

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#fetch-tracking-numbers>

Parameters

Name	Type	In	Required	Description
order_names		query		The fulfillment names we require tracking numbers for (i.e. #1001.1)
shop		query		The shop's myshopify url

Responses

200

GET /fetch_stock

Get inventory levels

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#fetch-stock>

Parameters

Name	Type	In	Required	Description
max_retries		query		The maximum amount of times Shopify will send the request for inventory levels.
shop		query		The shop's myshopify url.
sku		query		The SKU for the Product Variant we need stock levels for.
timestamp		query		The Unix timestamp from when the inventory request was made.

Responses

200

GET /admin/api/2020-01/fulfillment_services.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-2020-01>

Parameters

Name	Type	In	Required	Description
scope		query		current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses

200

POST /admin/api/2020-01/fulfillment_services.json

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE"

https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-2020-01>

Responses

200

GET /admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

PUT /admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

DELETE /admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

GET /admin/api/2020-04/fulfillment_services.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-2020-04>

Parameters

Name	Type	In	Required	Description
scope		query		current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses

200

POST /admin/api/2020-04/fulfillment_services.json

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H "Accept:application/json" -H "Content-Type:application/json" -H "X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-2020-04>

Responses

200

GET /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

PUT /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

DELETE

/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-2020-04

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

GET

/admin/api/2020-07/fulfillment_services.json

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-2020-07

Parameters

Name	Type	In	Required	Description
scope		query		current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses

200

POST

/admin/api/2020-07/fulfillment_services.json

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE"
https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.
https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-2020-07

Responses

200

GET

/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-2020-07

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

PUT

/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-2020-07

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

DELETE

/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-2020-07

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

GET /admin/api/2020-10/fulfillment_services.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-2020-10>

Parameters

Name	Type	In	Required	Description
scope		query		current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses

200

POST /admin/api/2020-10/fulfillment_services.json

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-2020-10>

Responses

200

GET /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

PUT /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

DELETE /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

GET /admin/api/2021-01/fulfillment_services.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-2021-01>

Parameters

Name	Type	In	Required	Description
scope		query		current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses

200

POST /admin/api/2021-01/fulfillment_services.json

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-2021-01

Responses

200

GET /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-2021-01

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

PUT /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-2021-01

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

DELETE /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-2021-01

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

GET /admin/api/unstable/fulfillment_services.json

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-unstable

Parameters

Name	Type	In	Required	Description
scope		query		current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses

200

POST /admin/api/unstable/fulfillment_services.json

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-unstable

Responses

200

GET /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-unstable

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

PUT /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

DELETE /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_service_id	string	path	required	fulfillment_service_id

Responses

200

GET /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-2020-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
fulfillment_order_id		query		The ID of the fulfillment order.

Responses

200

GET /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-2020-04>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
fulfillment_order_id		query		The ID of the fulfillment order.

Responses

200

GET /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-2020-07>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id	string	path	required	fulfillment_order_id
fulfillment_order_id		query		The ID of the fulfillment order.

Responses

200

GET /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-2020-10>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id fulfillment_order_id	string	path query	required	fulfillment_order_id The ID of the fulfillment order.

Responses

200

GET /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-2021-01>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id fulfillment_order_id	string	path query	required	fulfillment_order_id The ID of the fulfillment order.

Responses

200

GET /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-unstable>

Parameters

Name	Type	In	Required	Description
fulfillment_order_id fulfillment_order_id	string	path query	required	fulfillment_order_id The ID of the fulfillment order.

Responses

200

GET /admin/api/2020-01/shopify_payments/balance.json

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-2020-01

Responses

200

GET /admin/api/2020-04/shopify_payments/balance.json

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-2020-04

Responses

200

GET /admin/api/2020-07/shopify_payments/balance.json

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-2020-07

Responses

200

GET /admin/api/2020-10/shopify_payments/balance.json

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-2020-10

Responses

200

GET /admin/api/2021-01/shopify_payments/balance.json

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-2021-01

Responses

200

GET /admin/api/unstable/shopify_payments/balance.json

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-unstable

Responses

200

GET /admin/api/2020-01/shopify_payments/disputes.json

Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/dispute#index-2020-01

Parameters

Name	Type	In	Required	Description
since_id		query		Return only disputes after the specified ID.
last_id		query		Return only disputes before the specified ID.
status		query		Return only disputes with the specified status.
initiated_at		query		Return only disputes with the specified initiated_at date (ISO 8601 format).

Responses

200

GET /admin/api/2020-01/shopify_payments/disputes/{dispute_id}.json

Retrieves a single dispute by ID.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/dispute#show-2020-01

Parameters

Name	Type	In	Required	Description
dispute_id	string	path	required	dispute_id

Responses

200

GET /admin/api/2020-04/shopify_payments/disputes.json

Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/dispute#index-2020-04

Parameters

Name	Type	In	Required	Description
since_id		query		Return only disputes after the specified ID.
last_id		query		Return only disputes before the specified ID.
status		query		Return only disputes with the specified status.
initiated_at		query		Return only disputes with the specified initiated_at date (ISO 8601 format).

Responses

200

GET /admin/api/2020-01/shopify_payments/payouts.json

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#index-2020-01

Parameters

Name	Type	In	Required	Description
since_id		query		Filter the response to payouts made after the specified ID.

last_id	query	Filter the response to payouts made before the specified ID.
date_min	query	Filter the response to payouts made inclusively after the specified date.
date_max	query	Filter the response to payouts made inclusively before the specified date.
date	query	Filter the response to payouts made on the specified date.
status	query	Filter the response to payouts made with the specified status.

Responses

200

GET /admin/api/2020-01/shopify_payments/payouts/{payout_id}.json

Retrieves a single payout by id.
https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#show-2020-01

Parameters

Name	Type	In	Required	Description
payout_id	string	path	required	payout_id

Responses

200

GET /admin/api/2020-04/shopify_payments/payouts.json

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#index-2020-04

Parameters

Name	Type	In	Required	Description
since_id		query		Filter the response to payouts made after the specified ID.
last_id		query		Filter the response to payouts made before the specified ID.
date_min		query		Filter the response to payouts made inclusively after the specified date.
date_max		query		Filter the response to payouts made inclusively before the specified date.
date		query		Filter the response to payouts made on the specified date.
status		query		Filter the response to payouts made with the specified status.

Responses

200

GET /admin/api/2020-04/shopify_payments/payouts/{payout_id}.json

Retrieves a single payout by id.
https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#show-2020-04

Parameters

Name	Type	In	Required	Description
payout_id	string	path	required	payout_id

Responses

200

GET /admin/api/2020-07/shopify_payments/payouts.json

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#index-2020-07

Parameters

Name	Type	In	Required	Description
since_id		query		Filter the response to payouts made after the specified ID.
last_id		query		Filter the response to payouts made before the specified ID.
date_min		query		Filter the response to payouts made inclusively after the specified date.
date_max		query		Filter the response to payouts made inclusively before the specified date.
date		query		Filter the response to payouts made on the specified date.
status		query		Filter the response to payouts made with the specified status.

Responses

200

GET /admin/api/2020-07/shopify_payments/payouts/{payout_id}.json

Retrieves a single payout by id.

Parameters

Name	Type	In	Required	Description
payout_id	string	path	required	payout_id

Responses

200

GET /admin/api/2020-10/shopify_payments/payouts.json

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

Parameters

Name	Type	In	Required	Description
since_id		query		Filter the response to payouts made after the specified ID.
last_id		query		Filter the response to payouts made before the specified ID.
date_min		query		Filter the response to payouts made inclusively after the specified date.
date_max		query		Filter the response to payouts made inclusively before the specified date.
date		query		Filter the response to payouts made on the specified date.
status		query		Filter the response to payouts made with the specified status.

Responses

200

GET /admin/api/2020-10/shopify_payments/payouts/{payout_id}.json

Retrieves a single payout by id.

Parameters

Name	Type	In	Required	Description
payout_id	string	path	required	payout_id

Responses

200

GET /admin/api/2021-01/shopify_payments/payouts.json

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

Parameters

Name	Type	In	Required	Description
since_id		query		Filter the response to payouts made after the specified ID.
last_id		query		Filter the response to payouts made before the specified ID.
date_min		query		Filter the response to payouts made inclusively after the specified date.
date_max		query		Filter the response to payouts made inclusively before the specified date.
date		query		Filter the response to payouts made on the specified date.
status		query		Filter the response to payouts made with the specified status.

Responses

200

GET /admin/api/2021-01/shopify_payments/payouts/{payout_id}.json

Retrieves a single payout by id.

Parameters

Name	Type	In	Required	Description
payout_id	string	path	required	payout_id

Responses

200

GET /admin/api/unstable/shopify_payments/payouts.json

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#index-unstable

Parameters

Name	Type	In	Required	Description
since_id		query		Filter the response to payouts made after the specified ID.
last_id		query		Filter the response to payouts made before the specified ID.
date_min		query		Filter the response to payouts made inclusively after the specified date.
date_max		query		Filter the response to payouts made inclusively before the specified date.
date		query		Filter the response to payouts made on the specified date.
status		query		Filter the response to payouts made with the specified status.

Responses

200

GET /admin/api/unstable/shopify_payments/payouts/{payout_id}.json

Retrieves a single payout by id.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#show-unstable

Parameters

Name	Type	In	Required	Description
payout_id	string	path	required	payout_id

Responses

200

GET /admin/api/2020-01/shopify_payments/balance/transactions.json

Retrieves a list of all balance transactions ordered by processing time, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/transaction#index-2020-01

Parameters

Name	Type	In	Required	Description
since_id		query		Filter response to transactions exclusively after the specified ID.
last_id		query		Filter response to transactions exclusively before the specified ID.
test		query		Filter response to transactions placed in test mode.
payout_id		query		Filter response to transactions paid out in the specified payout.
payout_status		query		Filter response to transactions with the specified payout status.

Responses

200

GET /admin/api/2020-01/countries.json

Retrieves a list of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-2020-01>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-01/countries.json

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-2020-01>

Responses

200

GET /admin/api/2020-01/countries/count.json

Retrieves a count of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-2020-01>

Responses

200

GET

/admin/api/2020-01/countries/{country_id}.json

Retrieves a specific county.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-2020-01>

Parameters

Name	Type	In	Required	Description
country_id fields	string	path query	required	country_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-01/countries/{country_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-2020-01>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

DELETE

/admin/api/2020-01/countries/{country_id}.json

Deletes a country.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-2020-01>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET

/admin/api/2020-04/countries.json

Retrieves a list of countries.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-2020-04>

Parameters

Name	Type	In	Required	Description
since_id fields		query query		Restrict results to after the specified ID. Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-04/countries.json

Caution As of version 2020-10, the tax field is deprecated. Creates a country.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-2020-04>

Responses

200

GET

/admin/api/2020-04/countries/count.json

Retrieves a count of countries.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-2020-04>

Responses

200

GET /admin/api/2020-04/countries/{country_id}.json

Retrieves a specific county.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-2020-04>

Parameters

Name	Type	In	Required	Description
country_id fields	string	path query	required	country_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-04/countries/{country_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-2020-04>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

DELETE /admin/api/2020-04/countries/{country_id}.json

Deletes a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-2020-04>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET /admin/api/2020-07/countries.json

Retrieves a list of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-2020-07>

Parameters

Name	Type	In	Required	Description
since_id fields		query query		Restrict results to after the specified ID. Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2020-07/countries.json

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-2020-07>

Responses

200

GET /admin/api/2020-07/countries/count.json

Retrieves a count of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-2020-07>

Responses

200

GET /admin/api/2020-07/countries/{country_id}.json

Retrieves a specific county.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-2020-07

Parameters

Name	Type	In	Required	Description
country_id fields	string	path query	required	country_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-07/countries/{country_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-2020-07

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

DELETE

/admin/api/2020-07/countries/{country_id}.json

Deletes a country.
https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-2020-07

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET

/admin/api/2020-10/countries.json

Retrieves a list of countries.
https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-2020-10

Parameters

Name	Type	In	Required	Description
since_id fields		query query		Restrict results to after the specified ID. Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/2020-10/countries.json

Caution As of version 2020-10, the tax field is deprecated. Creates a country.
https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-2020-10

Responses

200

GET

/admin/api/2020-10/countries/count.json

Retrieves a count of countries.
https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-2020-10

Responses

200

GET

/admin/api/2020-10/countries/{country_id}.json

Retrieves a specific county.
https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-2020-10

Parameters

Name	Type	In	Required	Description
country_id fields	string	path query	required	country_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-10/countries/{country_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-2020-10>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

DELETE /admin/api/2020-10/countries/{country_id}.json

Deletes a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-2020-10>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET /admin/api/2021-01/countries.json

Retrieves a list of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-2021-01>

Parameters

Name	Type	In	Required	Description
since_id fields		query query		Restrict results to after the specified ID. Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST /admin/api/2021-01/countries.json

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-2021-01>

Responses

200

GET /admin/api/2021-01/countries/count.json

Retrieves a count of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-2021-01>

Responses

200

GET /admin/api/2021-01/countries/{country_id}.json

Retrieves a specific county.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-2021-01>

Parameters

Name	Type	In	Required	Description
country_id fields	string	path query	required	country_id Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2021-01/countries/{country_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-2021-01>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

DELETE

/admin/api/2021-01/countries/{country_id}.json

Deletes a country.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-2021-01>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET

/admin/api/unstable/countries.json

Retrieves a list of countries.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-unstable>

Parameters

Name	Type	In	Required	Description
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

POST

/admin/api/unstable/countries.json

Caution As of version 2020-10, the tax field is deprecated. Creates a country.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-unstable>

Responses

200

GET

/admin/api/unstable/countries/count.json

Retrieves a count of countries.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-unstable>

Responses

200

GET

/admin/api/unstable/countries/{country_id}.json

Retrieves a specific county.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-unstable>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/unstable/countries/{country_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-unstable>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

DELETE /admin/api/unstable/countries/{country_id}.json

Deletes a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-unstable>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET /admin/api/2020-01/currencies.json

Retrieves a list of currencies enabled on a shop

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-2020-01>

Responses

200

GET /admin/api/2020-04/currencies.json

Retrieves a list of currencies enabled on a shop

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-2020-04>

Responses

200

GET /admin/api/2020-07/currencies.json

Retrieves a list of currencies enabled on a shop

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-2020-07>

Responses

200

GET /admin/api/2020-10/currencies.json

Retrieves a list of currencies enabled on a shop

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-2020-10>

Responses

200

GET /admin/api/2021-01/currencies.json

Retrieves a list of currencies enabled on a shop

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-2021-01>

Responses

200

GET /admin/api/unstable/currencies.json

Retrieves a list of currencies enabled on a shop

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-unstable>

Responses

200

GET /admin/api/2020-01/policies.json

Retrieves a list of the shop's policies
https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-2020-01

Responses

200

GET /admin/api/2020-04/policies.json

Retrieves a list of the shop's policies
https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-2020-04

Responses

200

GET /admin/api/2020-07/policies.json

Retrieves a list of the shop's policies
https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-2020-07

Responses

200

GET /admin/api/2020-10/policies.json

Retrieves a list of the shop's policies
https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-2020-10

Responses

200

GET /admin/api/2021-01/policies.json

Retrieves a list of the shop's policies
https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-2021-01

Responses

200

GET /admin/api/unstable/policies.json

Retrieves a list of the shop's policies
https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-unstable

Responses

200

GET /admin/api/2020-01/countries/{country_id}/provinces.json

Retrieves a list of provinces
https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-2020-01

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of fields names.

Responses

200

GET /admin/api/2020-01/countries/{country_id}/provinces/count.json

Retrieves a count of provinces for a country
https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-2020-01

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET /admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json

Retrieves a single province for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-2020-01>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-2020-01>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id

Responses

200

GET /admin/api/2020-04/countries/{country_id}/provinces.json

Retrieves a list of provinces

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-2020-04>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of fields names.

Responses

200

GET /admin/api/2020-04/countries/{country_id}/provinces/count.json

Retrieves a count of provinces for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-2020-04>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET /admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json

Retrieves a single province for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-2020-04>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id

fields

query

Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-2020-04>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id

Responses

200

GET /admin/api/2020-07/countries/{country_id}/provinces.json

Retrieves a list of provinces
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-2020-07>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of fields names.

Responses

200

GET /admin/api/2020-07/countries/{country_id}/provinces/count.json

Retrieves a count of provinces for a country
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-2020-07>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET /admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json

Retrieves a single province for a country
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-2020-07>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-2020-07>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id

Responses

GET

/admin/api/2020-10/countries/{country_id}/provinces.json

Retrieves a list of provinces

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-2020-10>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of fields names.

Responses

200

GET

/admin/api/2020-10/countries/{country_id}/provinces/count.json

Retrieves a count of provinces for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-2020-10>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET

/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json

Retrieves a single province for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-2020-10>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-2020-10>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id

Responses

200

GET

/admin/api/2021-01/countries/{country_id}/provinces.json

Retrieves a list of provinces

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-2021-01>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of fields names.

Responses

200

GET /admin/api/2021-01/countries/{country_id}/provinces/count.json

Retrieves a count of provinces for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-2021-01>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET /admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json

Retrieves a single province for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-2021-01>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT /admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-2021-01>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id

Responses

200

GET /admin/api/unstable/countries/{country_id}/provinces.json

Retrieves a list of provinces

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-unstable>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
since_id		query		Restrict results to after the specified ID.
fields		query		Show only certain fields, specified by a comma-separated list of fields names.

Responses

200

GET /admin/api/unstable/countries/{country_id}/provinces/count.json

Retrieves a count of provinces for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-unstable>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id

Responses

200

GET /admin/api/unstable/countries/{country_id}/provinces/{province_id}.json

Retrieves a single province for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-unstable>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id
fields		query		Show only certain fields, specified by a comma-separated list of field names.

Responses

200

PUT

/admin/api/unstable/countries/{country_id}/provinces/{province_id}.json

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-unstable>

Parameters

Name	Type	In	Required	Description
country_id	string	path	required	country_id
province_id	string	path	required	province_id

Responses

200

GET

/admin/api/2020-01/shipping_zones.json

Get a list of all shipping zones
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-2020-01>

Parameters

Name	Type	In	Required	Description
fields		query		comma-separated list of fields to include in the response

Responses

200

GET

/admin/api/2020-04/shipping_zones.json

Get a list of all shipping zones
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-2020-04>

Parameters

Name	Type	In	Required	Description
fields		query		comma-separated list of fields to include in the response

Responses

200

GET

/admin/api/2020-07/shipping_zones.json

Get a list of all shipping zones
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-2020-07>

Parameters

Name	Type	In	Required	Description
fields		query		comma-separated list of fields to include in the response

Responses

200

GET

/admin/api/2020-10/shipping_zones.json

Get a list of all shipping zones
<https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-2020-10>

Parameters

Name	Type	In	Required	Description
fields		query		comma-separated list of fields to include in the response

Responses

200

GET

/admin/api/2021-01/shipping_zones.json

Get a list of all shipping zones

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-2021-01

Parameters

Name	Type	In	Required	Description
fields		query		comma-separated list of fields to include in the response

Responses

200

GET

/admin/api/unstable/shipping_zones.json

Get a list of all shipping zones

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-unstable

Parameters

Name	Type	In	Required	Description
fields		query		comma-separated list of fields to include in the response

Responses

200

GET

/admin/api/2020-01/shop.json

Retrieves the shop's configuration

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-2020-01

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET

/admin/api/2020-04/shop.json

Retrieves the shop's configuration

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-2020-04

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET

/admin/api/2020-07/shop.json

Retrieves the shop's configuration

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-2020-07

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET

/admin/api/2020-10/shop.json

Retrieves the shop's configuration

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-2020-10

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET /admin/api/2021-01/shop.json

Retrieves the shop's configuration

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-2021-01>

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET /admin/api/unstable/shop.json

Retrieves the shop's configuration

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-unstable>

Parameters

Name	Type	In	Required	Description
fields		query		A comma-separated list of fields to include in the response.

Responses

200

GET /admin/api/2020-01/tender_transactions.json

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/tendertransaction#index-2020-01>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Retrieve only transactions after the specified ID.
processed_at_min		query		Show tender transactions processed_at or after the specified date.
processed_at_max		query		Show tender transactions processed_at or before the specified date.
processed_at		query		Show tender transactions processed at the specified date.
order		query		Show tender transactions ordered by processed_at in ascending or descending order.

Responses

200

GET /admin/api/2020-04/tender_transactions.json

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/tendertransaction#index-2020-04>

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Retrieve only transactions after the specified ID.
processed_at_min		query		Show tender transactions processed_at or after the specified date.
processed_at_max		query		Show tender transactions processed_at or before the specified date.
processed_at		query		Show tender transactions processed at the specified date.
order		query		Show tender transactions ordered by processed_at in ascending or descending order.

Responses

200

GET /admin/api/2020-07/tender_transactions.json

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Retrieve only transactions after the specified ID.
processed_at_min		query		Show tender transactions processed_at or after the specified date.
processed_at_max		query		Show tender transactions processed_at or before the specified date.
processed_at		query		Show tender transactions processed at the specified date.
order		query		Show tender transactions ordered by processed_at in ascending or descending order.

Responses

200

GET /admin/api/2020-10/tender_transactions.json

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/tendertransaction#index-2020-10

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Retrieve only transactions after the specified ID.
processed_at_min		query		Show tender transactions processed_at or after the specified date.
processed_at_max		query		Show tender transactions processed_at or before the specified date.
processed_at		query		Show tender transactions processed at the specified date.
order		query		Show tender transactions ordered by processed_at in ascending or descending order.

Responses

200

GET /admin/api/2021-01/tender_transactions.json

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/tendertransaction#index-2021-01

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Retrieve only transactions after the specified ID.
processed_at_min		query		Show tender transactions processed_at or after the specified date.
processed_at_max		query		Show tender transactions processed_at or before the specified date.
processed_at		query		Show tender transactions processed at the specified date.
order		query		Show tender transactions ordered by processed_at in ascending or descending order.

Responses

200

GET /admin/api/unstable/tender_transactions.json

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/tendertransaction#index-unstable

Parameters

Name	Type	In	Required	Description
limit		query		The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id		query		Retrieve only transactions after the specified ID.
processed_at_min		query		Show tender transactions processed_at or after the specified date.
processed_at_max		query		Show tender transactions processed_at or before the specified date.
processed_at		query		Show tender transactions processed at the specified date.
order		query		Show tender transactions ordered by processed_at in ascending or descending order.

Responses

200

Schemas

