

Shopify Admin API

REST API Reference

The REST Admin API lets you build apps and other integrations for the Shopify admin.

Version 2020-10

Revisions

Date	Version	Author	Description
2024-06-01	1.0.0		
2024-06-15	1.1.0		
2024-07-01	1.2.0		

Summary

[OpenAPI](#) JSON:

Table of Contents

abandoned-checkouts

GET	/admin/api/2020-01/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-04/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-07/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-10/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2021-01/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/unstable/checkouts/count.json	Retrieves a count of checkouts from the past 90 days

access

GET	/admin/oauth/access_scopes.json	Retrieves a list of access scopes associated to the access token.
GET	/admin/api/2020-01/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-01/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-01/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2020-04/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-04/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-04/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2020-07/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-07/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-07/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2020-10/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-10/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-10/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2021-01/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2021-01/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2021-01/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/unstable/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/unstable/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/unstable/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token

access/accessscope

GET	/admin/oauth/access_scopes.json	Retrieves a list of access scopes associated to the access token.
---------------------	---	---

access/storefrontaccesstoken

GET	/admin/api/2020-01/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-01/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-01/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2020-04/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-04/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-04/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2020-07/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-07/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-07/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2020-10/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-10/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-10/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2021-01/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2021-01/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2021-01/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/unstable/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/unstable/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/unstable/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token

accessscope

GET	/admin/oauth/access_scopes.json	Retrieves a list of access scopes associated to the access token.
-----	---	---

analytics

GET	/admin/api/2020-01/reports.json	Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/reports.json	Creates a new report
GET	/admin/api/2020-01/reports/{report_id}.json	Retrieves a single report created by your app
PUT	/admin/api/2020-01/reports/{report_id}.json	Updates a report
DELETE	/admin/api/2020-01/reports/{report_id}.json	Deletes a report
GET	/admin/api/2020-04/reports.json	Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/reports.json	Creates a new report

GET	/admin/api/2020-04/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2020-04/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-04/reports/{report_id}.json Deletes a report
GET	/admin/api/2020-07/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/reports.json Creates a new report
GET	/admin/api/2020-07/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2020-07/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-07/reports/{report_id}.json Deletes a report
GET	/admin/api/2020-10/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/reports.json Creates a new report
GET	/admin/api/2020-10/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2020-10/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-10/reports/{report_id}.json Deletes a report
GET	/admin/api/2021-01/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/reports.json Creates a new report
GET	/admin/api/2021-01/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2021-01/reports/{report_id}.json Updates a report
DELETE	/admin/api/2021-01/reports/{report_id}.json Deletes a report
GET	/admin/api/unstable/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/reports.json Creates a new report
GET	/admin/api/unstable/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/unstable/reports/{report_id}.json Updates a report
DELETE	/admin/api/unstable/reports/{report_id}.json Deletes a report

analytics/report

GET	/admin/api/2020-01/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/reports.json Creates a new report
GET	/admin/api/2020-01/reports/{report_id}.json

PUT	Retrieves a single report created by your app /admin/api/2020-01/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-01/reports/{report_id}.json Deletes a report
GET	/admin/api/2020-04/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/reports.json Creates a new report
GET	/admin/api/2020-04/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2020-04/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-04/reports/{report_id}.json Deletes a report
GET	/admin/api/2020-07/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/reports.json Creates a new report
GET	/admin/api/2020-07/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2020-07/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-07/reports/{report_id}.json Deletes a report
GET	/admin/api/2020-10/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/reports.json Creates a new report
GET	/admin/api/2020-10/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2020-10/reports/{report_id}.json Updates a report
DELETE	/admin/api/2020-10/reports/{report_id}.json Deletes a report
GET	/admin/api/2021-01/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/reports.json Creates a new report
GET	/admin/api/2021-01/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2021-01/reports/{report_id}.json Updates a report
DELETE	/admin/api/2021-01/reports/{report_id}.json Deletes a report
GET	/admin/api/unstable/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/reports.json Creates a new report
GET	/admin/api/unstable/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/unstable/reports/{report_id}.json Updates a report

DELETE /admin/api/unstable/reports/{report_id}.json
Deletes a report

applicationcharge

GET /admin/api/2020-01/application_charges.json
Retrieves a list of application charges

POST /admin/api/2020-01/application_charges.json
Creates an application charge

GET /admin/api/2020-01/application_charges/{application_charge_id}.json
Retrieves an application charge

POST /admin/api/2020-01/application_charges/{application_charge_id}/activate.json
Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

GET /admin/api/2020-04/application_charges.json
Retrieves a list of application charges

POST /admin/api/2020-04/application_charges.json
Creates an application charge

GET /admin/api/2020-04/application_charges/{application_charge_id}.json
Retrieves an application charge

POST /admin/api/2020-04/application_charges/{application_charge_id}/activate.json
Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

GET /admin/api/2020-07/application_charges.json
Retrieves a list of application charges

POST /admin/api/2020-07/application_charges.json
Creates an application charge

GET /admin/api/2020-07/application_charges/{application_charge_id}.json
Retrieves an application charge

POST /admin/api/2020-07/application_charges/{application_charge_id}/activate.json
Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

GET /admin/api/2020-10/application_charges.json
Retrieves a list of application charges

POST /admin/api/2020-10/application_charges.json
Creates an application charge

GET /admin/api/2020-10/application_charges/{application_charge_id}.json
Retrieves an application charge

POST /admin/api/2020-10/application_charges/{application_charge_id}/activate.json
Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

GET /admin/api/2021-01/application_charges.json
Retrieves a list of application charges

POST /admin/api/2021-01/application_charges.json
Creates an application charge

GET /admin/api/2021-01/application_charges/{application_charge_id}.json
Retrieves an application charge

GET /admin/api/unstable/application_charges.json
Retrieves a list of application charges

POST /admin/api/unstable/application_charges.json
Creates an application charge

GET /admin/api/unstable/application_charges/{application_charge_id}.json
Retrieves an application charge

applicationcredit

GET /admin/api/2020-01/application_credits.json
Retrieves all application credits

POST /admin/api/2020-01/application_credits.json
Creates an application credit

GET /admin/api/2020-01/application_credits/{application_credit_id}.json
Retrieves a single application credit

GET /admin/api/2020-04/application_credits.json

POST	/admin/api/2020-04/application_credits.json Retrieves all application credits Creates an application credit
GET	/admin/api/2020-04/application_credits/{application_credit_id}.json Retrieves a single application credit
GET	/admin/api/2020-07/application_credits.json Retrieves all application credits
POST	/admin/api/2020-07/application_credits.json Creates an application credit
GET	/admin/api/2020-07/application_credits/{application_credit_id}.json Retrieves a single application credit
GET	/admin/api/2020-10/application_credits.json Retrieves all application credits
POST	/admin/api/2020-10/application_credits.json Creates an application credit
GET	/admin/api/2020-10/application_credits/{application_credit_id}.json Retrieves a single application credit
GET	/admin/api/2021-01/application_credits.json Retrieves all application credits
POST	/admin/api/2021-01/application_credits.json Creates an application credit
GET	/admin/api/2021-01/application_credits/{application_credit_id}.json Retrieves a single application credit
GET	/admin/api/unstable/application_credits.json Retrieves all application credits
POST	/admin/api/unstable/application_credits.json Creates an application credit
GET	/admin/api/unstable/application_credits/{application_credit_id}.json Retrieves a single application credit

article

GET	/admin/api/2020-01/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-01/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-01/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-01/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-04/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-04/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json Updates an article

DELETE	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json	Deletes an article
GET	/admin/api/2020-04/articles/authors.json	Retrieves a list all of article authors
GET	/admin/api/2020-04/articles/tags.json	Retrieves a list of all the tags
GET	/admin/api/2020-07/blogs/{blog_id}/articles.json	Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/blogs/{blog_id}/articles.json	Creates an article for a blog
GET	/admin/api/2020-07/blogs/{blog_id}/articles/count.json	Retrieves a count of all articles from a blog
GET	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json	Retrieves a single article
PUT	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json	Updates an article
DELETE	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json	Deletes an article
GET	/admin/api/2020-07/articles/authors.json	Retrieves a list all of article authors
GET	/admin/api/2020-07/articles/tags.json	Retrieves a list of all the tags
GET	/admin/api/2020-10/blogs/{blog_id}/articles.json	Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/blogs/{blog_id}/articles.json	Creates an article for a blog
GET	/admin/api/2020-10/blogs/{blog_id}/articles/count.json	Retrieves a count of all articles from a blog
GET	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json	Retrieves a single article
PUT	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json	Updates an article
DELETE	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json	Deletes an article
GET	/admin/api/2020-10/articles/authors.json	Retrieves a list all of article authors
GET	/admin/api/2020-10/articles/tags.json	Retrieves a list of all the tags
GET	/admin/api/2021-01/blogs/{blog_id}/articles.json	Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/blogs/{blog_id}/articles.json	Creates an article for a blog
GET	/admin/api/2021-01/blogs/{blog_id}/articles/count.json	Retrieves a count of all articles from a blog
GET	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json	Retrieves a single article
PUT	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json	Updates an article
DELETE	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json	Deletes an article
GET	/admin/api/2021-01/articles/authors.json	Retrieves a list all of article authors
GET	/admin/api/2021-01/articles/tags.json	Retrieves a list of all the tags
GET	/admin/api/unstable/blogs/{blog_id}/articles.json	

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/blogs/{blog_id}/articles.json

Creates an article for a blog

GET /admin/api/unstable/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

GET /admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article

PUT /admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Updates an article

DELETE /admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

GET </admin/api/unstable/articles/authors.json>

Retrieves a list all of article authors

GET </admin/api/unstable/articles/tags.json>

Retrieves a list of all the tags

asset

GET /admin/api/2020-01/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see Asset properties.

PUT /admin/api/2020-01/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

DELETE /admin/api/2020-01/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET /admin/api/2020-04/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see Asset properties.

PUT /admin/api/2020-04/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

DELETE /admin/api/2020-04/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET /admin/api/2020-07/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see Asset properties.

PUT /admin/api/2020-07/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

DELETE /admin/api/2020-07/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET /admin/api/2020-10/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see Asset properties.

PUT /admin/api/2020-10/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

DELETE /admin/api/2020-10/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET /admin/api/2021-01/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see Asset properties.

PUT /admin/api/2021-01/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

DELETE /admin/api/2021-01/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET /admin/api/unstable/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see Asset properties.

PUT /admin/api/unstable/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

DELETE /admin/api/unstable/themes/{theme_id}/assets.json

Deletes an asset from a theme.

assignedfulfillmentorder

GET /admin/api/2020-01/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.

GET /admin/api/2020-04/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.

GET /admin/api/2020-07/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.

GET /admin/api/2020-10/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.

GET /admin/api/2021-01/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.

GET /admin/api/unstable/assigned_fulfillment_orders.json

Retrieves a list of fulfillment orders on a shop for a specific app.

balance

GET /admin/api/2020-01/shopify_payments/balance.json

Retrieves the account's current balance.

GET /admin/api/2020-04/shopify_payments/balance.json

Retrieves the account's current balance.

GET /admin/api/2020-07/shopify_payments/balance.json

Retrieves the account's current balance.

GET /admin/api/2020-10/shopify_payments/balance.json

Retrieves the account's current balance.

GET /admin/api/2021-01/shopify_payments/balance.json

Retrieves the account's current balance.

GET /admin/api/unstable/shopify_payments/balance.json

Retrieves the account's current balance.

billing

GET /admin/api/2020-01/application_charges.json

Retrieves a list of application charges

POST /admin/api/2020-01/application_charges.json

Creates an application charge

GET /admin/api/2020-01/application_charges/{application_charge_id}.json

Retrieves an application charge

POST /admin/api/2020-01/application_charges/{application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

GET /admin/api/2020-04/application_charges.json

Retrieves a list of application charges

POST /admin/api/2020-04/application_charges.json

Creates an application charge

GET /admin/api/2020-04/application_charges/{application_charge_id}.json

Retrieves an application charge

POST /admin/api/2020-04/application_charges/{application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.

GET /admin/api/2020-07/application_charges.json

Retrieves a list of application charges

POST /admin/api/2020-07/application_charges.json

Creates an application charge

GET /admin/api/2020-07/application_charges/{application_charge_id}.json

Retrieves an application charge

POST	/admin/api/2020-07/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-10/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2020-10/application_charges.json	Creates an application charge
GET	/admin/api/2020-10/application_charges/{application_charge_id}.json	Retrieves an application charge
POST	/admin/api/2020-10/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2021-01/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2021-01/application_charges.json	Creates an application charge
GET	/admin/api/2021-01/application_charges/{application_charge_id}.json	Retrieves an application charge
GET	/admin/api/unstable/application_charges.json	Retrieves a list of application charges
POST	/admin/api/unstable/application_charges.json	Creates an application charge
GET	/admin/api/unstable/application_charges/{application_charge_id}.json	Retrieves an application charge
GET	/admin/api/2020-01/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-01/application_credits.json	Creates an application credit
GET	/admin/api/2020-01/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-04/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-04/application_credits.json	Creates an application credit
GET	/admin/api/2020-04/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-07/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-07/application_credits.json	Creates an application credit
GET	/admin/api/2020-07/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-10/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-10/application_credits.json	Creates an application credit
GET	/admin/api/2020-10/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2021-01/application_credits.json	Retrieves all application credits
POST	/admin/api/2021-01/application_credits.json	Creates an application credit
GET	/admin/api/2021-01/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/unstable/application_credits.json	Retrieves all application credits
POST	/admin/api/unstable/application_credits.json	Creates an application credit
GET	/admin/api/unstable/application_credits/{application_credit_id}.json	Retrieves a single application credit

GET	/admin/api/2020-01/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/2020-01/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
POST	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-04/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/2020-04/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
POST	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-07/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/2020-07/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
POST	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-10/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/2020-10/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge
GET	/admin/api/2021-01/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/2021-01/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
PUT	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/customize.json

GET	/admin/api/unstable/recurring_application_charges.json	Updates the capped amount of an active recurring application charge
		Retrieves a list of recurring application charges
POST	/admin/api/unstable/recurring_application_charges.json	Creates a recurring application charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json	Retrieves a single charge
DELETE	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json	Cancels a recurring application charge
PUT	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/customize.json	Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Retrieves a list of usage charges
POST	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Creates a usage charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json	Retrieves a single charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Retrieves a list of usage charges
POST	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Creates a usage charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json	Retrieves a single charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Retrieves a list of usage charges
POST	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Creates a usage charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json	Retrieves a single charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Retrieves a list of usage charges
POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Creates a usage charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json	Retrieves a single charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Retrieves a list of usage charges
POST	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Creates a usage charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json	Retrieves a single charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Retrieves a list of usage charges
POST	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Creates a usage charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json	Retrieves a single charge

billing/applicationcharge

GET	/admin/api/2020-01/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2020-01/application_charges.json	Creates an application charge
GET	/admin/api/2020-01/application_charges/{application_charge_id}.json	Retrieves an application charge
POST	/admin/api/2020-01/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-04/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2020-04/application_charges.json	

GET	/admin/api/2020-04/application_charges/{application_charge_id}.json	Creates an application charge
		Retrieves an application charge
POST	/admin/api/2020-04/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-07/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2020-07/application_charges.json	Creates an application charge
GET	/admin/api/2020-07/application_charges/{application_charge_id}.json	Retrieves an application charge
POST	/admin/api/2020-07/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-10/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2020-10/application_charges.json	Creates an application charge
GET	/admin/api/2020-10/application_charges/{application_charge_id}.json	Retrieves an application charge
POST	/admin/api/2020-10/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2021-01/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2021-01/application_charges.json	Creates an application charge
GET	/admin/api/2021-01/application_charges/{application_charge_id}.json	Retrieves an application charge
GET	/admin/api/unstable/application_charges.json	Retrieves a list of application charges
POST	/admin/api/unstable/application_charges.json	Creates an application charge
GET	/admin/api/unstable/application_charges/{application_charge_id}.json	Retrieves an application charge

billing/applicationcredit

GET	/admin/api/2020-01/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-01/application_credits.json	Creates an application credit
GET	/admin/api/2020-01/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-04/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-04/application_credits.json	Creates an application credit
GET	/admin/api/2020-04/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-07/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-07/application_credits.json	Creates an application credit
GET	/admin/api/2020-07/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/2020-10/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-10/application_credits.json	Creates an application credit
GET	/admin/api/2020-10/application_credits/{application_credit_id}.json	

GET	/admin/api/2021-01/application_credits.json	Retrieves a single application credit
		Retrieves all application credits
POST	/admin/api/2021-01/application_credits.json	Creates an application credit
GET	/admin/api/2021-01/application_credits/{application_credit_id}.json	Retrieves a single application credit
GET	/admin/api/unstable/application_credits.json	Retrieves all application credits
POST	/admin/api/unstable/application_credits.json	Creates an application credit
GET	/admin/api/unstable/application_credits/{application_credit_id}.json	Retrieves a single application credit

billing/recurringapplicationcharge

GET	/admin/api/2020-01/recurring_application_charges.json	Retrieves a list of recurring application charges
POST	/admin/api/2020-01/recurring_application_charges.json	Creates a recurring application charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json	Retrieves a single charge
DELETE	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json	Cancels a recurring application charge
POST	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/customize.json	Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-04/recurring_application_charges.json	Retrieves a list of recurring application charges
POST	/admin/api/2020-04/recurring_application_charges.json	Creates a recurring application charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json	Retrieves a single charge
DELETE	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json	Cancels a recurring application charge
POST	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/customize.json	Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-07/recurring_application_charges.json	Retrieves a list of recurring application charges
POST	/admin/api/2020-07/recurring_application_charges.json	Creates a recurring application charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json	Retrieves a single charge
DELETE	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json	Cancels a recurring application charge
POST	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/customize.json	Updates the capped amount of an active recurring application charge
GET	/admin/api/2020-10/recurring_application_charges.json	Retrieves a list of recurring application charges
POST	/admin/api/2020-10/recurring_application_charges.json	Creates a recurring application charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json	Retrieves a single charge
DELETE	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json	

	Cancels a recurring application charge
POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/activate.json Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
PUT	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge
GET	/admin/api/2021-01/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/2021-01/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
PUT	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge
GET	/admin/api/unstable/recurring_application_charges.json Retrieves a list of recurring application charges
POST	/admin/api/unstable/recurring_application_charges.json Creates a recurring application charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json Retrieves a single charge
DELETE	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json Cancels a recurring application charge
PUT	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/customize.json Updates the capped amount of an active recurring application charge

billing/usagecharge

GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

GET [Creates a usage charge](#)
[/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json](#)
Retrieves a single charge

blog

GET [/admin/api/2020-01/blogs.json](#)
Retrieve a list of all blogs. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST [/admin/api/2020-01/blogs.json](#)
Create a new blog

GET [/admin/api/2020-01/blogs/count.json](#)
Get a count of all blogs

GET [/admin/api/2020-01/blogs/{blog_id}.json](#)
Get a single blog by its ID

PUT [/admin/api/2020-01/blogs/{blog_id}.json](#)
Update a blog

DELETE [/admin/api/2020-01/blogs/{blog_id}.json](#)
Delete a blog

cancellationrequest

POST [/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

carrierservice

GET [/admin/api/2020-01/carrier_services.json](#)
Retrieves a list of carrier services

POST /admin/api/2020-01/carrier_services.json
Creates a carrier service

GET /admin/api/2020-01/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-01/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-01/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2020-04/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2020-04/carrier_services.json
Creates a carrier service

GET /admin/api/2020-04/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-04/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-04/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2020-07/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2020-07/carrier_services.json
Creates a carrier service

GET /admin/api/2020-07/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-07/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-07/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2020-10/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2020-10/carrier_services.json
Creates a carrier service

GET /admin/api/2020-10/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-10/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-10/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2021-01/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2021-01/carrier_services.json
Creates a carrier service

GET /admin/api/2021-01/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2021-01/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2021-01/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/unstable/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/unstable/carrier_services.json
Creates a carrier service

GET /admin/api/unstable/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/unstable/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/unstable/carrier_services/{carrier_service_id}.json
Deletes a carrier service

checkout

POST	/admin/api/2020-01/checkouts.json Creates a checkout
POST	/admin/api/2020-04/checkouts.json Creates a checkout
POST	/admin/api/2020-07/checkouts.json Creates a checkout
POST	/admin/api/2020-10/checkouts.json Creates a checkout
POST	/admin/api/2021-01/checkouts.json Creates a checkout
POST	/admin/api/unstable/checkouts.json Creates a checkout
POST	/admin/api/2020-01/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-01/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-01/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-01/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-04/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-04/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-04/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-04/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-07/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-07/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-07/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-07/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-10/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-10/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-10/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-10/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2021-01/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2021-01/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2021-01/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2021-01/checkouts/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

POST </admin/api/unstable/checkout/{token}/complete.json>

Completes a checkout

GET </admin/api/unstable/checkout/{token}.json>

Retrieves a checkout

PUT </admin/api/unstable/checkout/{token}.json>

Modifies an existing checkout

GET /admin/api/unstable/checkout/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

collect

GET </admin/api/2020-01/collects.json>

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/collects.json>

Adds a product to a custom collection.

GET /admin/api/2020-01/collects/{collect_id}.json

Retrieves a specific collect by its ID.

DELETE /admin/api/2020-01/collects/{collect_id}.json

Removes a product from a collection.

GET </admin/api/2020-01/collects/count.json>

Retrieves a count of collects.

GET </admin/api/2020-04/collects.json>

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-04/collects.json>

Adds a product to a custom collection.

GET /admin/api/2020-04/collects/{collect_id}.json

Retrieves a specific collect by its ID.

DELETE /admin/api/2020-04/collects/{collect_id}.json

Removes a product from a collection.

GET </admin/api/2020-04/collects/count.json>

Retrieves a count of collects.

GET </admin/api/2020-07/collects.json>

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-07/collects.json>

Adds a product to a custom collection.

GET /admin/api/2020-07/collects/{collect_id}.json

Retrieves a specific collect by its ID.

DELETE /admin/api/2020-07/collects/{collect_id}.json

Removes a product from a collection.

GET </admin/api/2020-07/collects/count.json>

Retrieves a count of collects.

GET </admin/api/2020-10/collects.json>

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-10/collects.json>

Adds a product to a custom collection.

GET /admin/api/2020-10/collects/{collect_id}.json

Retrieves a specific collect by its ID.

DELETE /admin/api/2020-10/collects/{collect_id}.json

Removes a product from a collection.

GET </admin/api/2020-10/collects/count.json>

GET	/admin/api/2021-01/collects.json Retrieves a count of collects.
POST	/admin/api/2021-01/collects.json Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/collects/{collect_id}.json Adds a product to a custom collection.
DELETE	/admin/api/2021-01/collects/{collect_id}.json Retrieves a specific collect by its ID.
GET	/admin/api/2021-01/collects/count.json Removes a product from a collection.
GET	/admin/api/unstable/collects.json Retrieves a count of collects.
POST	/admin/api/unstable/collects.json Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/collects/{collect_id}.json Adds a product to a custom collection.
DELETE	/admin/api/unstable/collects/{collect_id}.json Retrieves a specific collect by its ID.
GET	/admin/api/unstable/collects/count.json Removes a product from a collection.
GET	/admin/api/unstable/collects/count.json Retrieves a count of collects.

collection

GET	/admin/api/2020-01/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2020-01/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-04/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2020-04/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-07/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2020-07/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-10/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2020-10/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2021-01/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2021-01/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/unstable/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/unstable/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

collectionlisting

[illegible]

PUT	/admin/api/2021-01/collection_listings/{collection_listing_id}.json Retrieve a specific collection listing that is published to your app
DELETE	/admin/api/2021-01/collection_listings/{collection_listing_id}.json Create a collection listing to publish a collection to your app
GET	/admin/api/unstable/collection_listings.json Delete a collection listing to unpublish a collection from your app
GET	/admin/api/unstable/collection_listings/{collection_listing_id}/product_ids.json Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/collection_listings/{collection_listing_id}/product_ids.json Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/collection_listings/{collection_listing_id}.json Retrieve a specific collection listing that is published to your app
PUT	/admin/api/unstable/collection_listings/{collection_listing_id}.json Create a collection listing to publish a collection to your app
DELETE	/admin/api/unstable/collection_listings/{collection_listing_id}.json Delete a collection listing to unpublish a collection from your app

comment

GET	/admin/api/2020-01/comments.json Retrieves a list of comments. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/comments.json Creates a comment for an article
GET	/admin/api/2020-01/comments/count.json Retrieves a count of comments
GET	/admin/api/2020-01/comments/{comment_id}.json Retrieves a single comment by its ID
PUT	/admin/api/2020-01/comments/{comment_id}.json Updates a comment of an article
POST	/admin/api/2020-01/comments/{comment_id}/spam.json Marks a comment as spam
POST	/admin/api/2020-01/comments/{comment_id}/not_spam.json Marks a comment as not spam
POST	/admin/api/2020-01/comments/{comment_id}/approve.json Approves a comment
POST	/admin/api/2020-01/comments/{comment_id}/remove.json Removes a comment
POST	/admin/api/2020-01/comments/{comment_id}/restore.json Restores a previously removed comment

country

GET	/admin/api/2020-01/countries.json Retrieves a list of countries.
POST	/admin/api/2020-01/countries.json Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-01/countries/count.json Retrieves a count of countries.
GET	/admin/api/2020-01/countries/{country_id}.json Retrieves a specific county.
PUT	/admin/api/2020-01/countries/{country_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-01/countries/{country_id}.json Deletes a country.
GET	/admin/api/2020-04/countries.json Retrieves a list of countries.
POST	/admin/api/2020-04/countries.json Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-04/countries/count.json

GET	/admin/api/2020-04/countries/{country_id}.json	Retrieves a count of countries.
PUT	/admin/api/2020-04/countries/{country_id}.json	Retrieves a specific county.
DELETE	/admin/api/2020-04/countries/{country_id}.json	Deletes a country.
GET	/admin/api/2020-07/countries.json	Retrieves a list of countries.
POST	/admin/api/2020-07/countries.json	Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-07/countries/count.json	Retrieves a count of countries.
GET	/admin/api/2020-07/countries/{country_id}.json	Retrieves a specific county.
PUT	/admin/api/2020-07/countries/{country_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-07/countries/{country_id}.json	Deletes a country.
GET	/admin/api/2020-10/countries.json	Retrieves a list of countries.
POST	/admin/api/2020-10/countries.json	Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-10/countries/count.json	Retrieves a count of countries.
GET	/admin/api/2020-10/countries/{country_id}.json	Retrieves a specific county.
PUT	/admin/api/2020-10/countries/{country_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-10/countries/{country_id}.json	Deletes a country.
GET	/admin/api/2021-01/countries.json	Retrieves a list of countries.
POST	/admin/api/2021-01/countries.json	Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2021-01/countries/count.json	Retrieves a count of countries.
GET	/admin/api/2021-01/countries/{country_id}.json	Retrieves a specific county.
PUT	/admin/api/2021-01/countries/{country_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2021-01/countries/{country_id}.json	Deletes a country.
GET	/admin/api/unstable/countries.json	Retrieves a list of countries.
POST	/admin/api/unstable/countries.json	Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/unstable/countries/count.json	Retrieves a count of countries.
GET	/admin/api/unstable/countries/{country_id}.json	Retrieves a specific county.
PUT	/admin/api/unstable/countries/{country_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/unstable/countries/{country_id}.json	Deletes a country.

currency

GET	/admin/api/2020-01/currencies.json	Retrieves a list of currencies enabled on a shop
GET	/admin/api/2020-04/currencies.json	

GET	/admin/api/2020-07/currencies.json Retrieves a list of currencies enabled on a shop
GET	/admin/api/2020-10/currencies.json Retrieves a list of currencies enabled on a shop
GET	/admin/api/2021-01/currencies.json Retrieves a list of currencies enabled on a shop
GET	/admin/api/unstable/currencies.json Retrieves a list of currencies enabled on a shop

customcollection

GET	/admin/api/2020-01/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/custom_collections.json Creates a custom collection
GET	/admin/api/2020-01/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-01/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-01/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-01/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2020-04/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/custom_collections.json Creates a custom collection
GET	/admin/api/2020-04/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-04/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-04/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-04/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2020-07/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/custom_collections.json Creates a custom collection
GET	/admin/api/2020-07/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-07/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-07/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-07/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2020-10/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/custom_collections.json Creates a custom collection
GET	/admin/api/2020-10/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-10/custom_collections/{custom_collection_id}.json

PUT	Retrieves a single custom collection /admin/api/2020-10/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2021-01/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/custom_collections.json Creates a custom collection
GET	/admin/api/2021-01/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/unstable/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/custom_collections.json Creates a custom collection
GET	/admin/api/unstable/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/unstable/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/unstable/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/unstable/custom_collections/{custom_collection_id}.json Deletes a custom collection

customer

GET	/admin/api/2020-01/customers.json Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customers.json Creates a customer.
GET	/admin/api/2020-01/customers/search.json Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/customers/{customer_id}.json Retrieves a single customer.
PUT	/admin/api/2020-01/customers/{customer_id}.json Updates a customer.
DELETE	/admin/api/2020-01/customers/{customer_id}.json Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-01/customers/{customer_id}/account_activation_url.json Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-01/customers/{customer_id}/send_invite.json Sends an account invite to a customer.
GET	/admin/api/2020-01/customers/count.json Retrieves a count of all customers.
GET	/admin/api/2020-01/customers/{customer_id}/orders.json Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

GET	/admin/api/2020-04/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customers.json	Creates a customer.
GET	/admin/api/2020-04/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/2020-04/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/2020-04/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-04/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-04/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/2020-04/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2020-04/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-07/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customers.json	Creates a customer.
GET	/admin/api/2020-07/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/2020-07/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/2020-07/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-07/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-07/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/2020-07/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2020-07/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-10/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customers.json	Creates a customer.
GET	/admin/api/2020-10/customers/search.json	

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-10/customers/{customer_id}.json

Retrieves a single customer.

PUT /admin/api/2020-10/customers/{customer_id}.json

Updates a customer.

DELETE /admin/api/2020-10/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.

POST /admin/api/2020-10/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

POST /admin/api/2020-10/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

GET </admin/api/2020-10/customers/count.json>

Retrieves a count of all customers.

GET /admin/api/2020-10/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

GET </admin/api/2021-01/customers.json>

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2021-01/customers.json>

Creates a customer.

GET </admin/api/2021-01/customers/search.json>

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2021-01/customers/{customer_id}.json

Retrieves a single customer.

PUT /admin/api/2021-01/customers/{customer_id}.json

Updates a customer.

DELETE /admin/api/2021-01/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.

POST /admin/api/2021-01/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

POST /admin/api/2021-01/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

GET </admin/api/2021-01/customers/count.json>

Retrieves a count of all customers.

GET /admin/api/2021-01/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

GET </admin/api/unstable/customers.json>

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/unstable/customers.json>

Creates a customer.

GET </admin/api/unstable/customers/search.json>

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/unstable/customers/{customer_id}.json

Retrieves a single customer.

PUT /admin/api/unstable/customers/{customer_id}.json

Updates a customer.

DELETE	/admin/api/unstable/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/unstable/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/unstable/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/unstable/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/unstable/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

customer-address

GET	/admin/api/2020-01/customers/{customer_id}/addresses.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customers/{customer_id}/addresses.json	Creates a new address for a customer.
GET	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json	Retrieves details a single customer address.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json	Updates an existing customer address.
DELETE	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json	Removes an address from a customer's address list.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/set.json	Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}/default.json	Sets the default address for a customer.
GET	/admin/api/2020-04/customers/{customer_id}/addresses.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customers/{customer_id}/addresses.json	Creates a new address for a customer.
GET	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json	Retrieves details a single customer address.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json	Updates an existing customer address.
DELETE	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json	Removes an address from a customer's address list.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/set.json	Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}/default.json	Sets the default address for a customer.
GET	/admin/api/2020-07/customers/{customer_id}/addresses.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customers/{customer_id}/addresses.json	Creates a new address for a customer.
GET	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json	Retrieves details a single customer address.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json	Updates an existing customer address.
DELETE	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json	Removes an address from a customer's address list.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/set.json	Performs bulk operations for multiple customer addresses.

PUT	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2020-10/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2021-01/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/unstable/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.

customers

GET	/admin/api/2020-01/customers.json Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customers.json Creates a customer.
GET	/admin/api/2020-01/customers/search.json Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/customers/{customer_id}.json

PUT	Retrieves a single customer. /admin/api/2020-01/customers/{customer_id}.json Updates a customer.
DELETE	/admin/api/2020-01/customers/{customer_id}.json Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-01/customers/{customer_id}/account_activation_url.json Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-01/customers/{customer_id}/send_invite.json Sends an account invite to a customer.
GET	/admin/api/2020-01/customers/count.json Retrieves a count of all customers.
GET	/admin/api/2020-01/customers/{customer_id}/orders.json Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-04/customers.json Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customers.json Creates a customer.
GET	/admin/api/2020-04/customers/search.json Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/customers/{customer_id}.json Retrieves a single customer.
PUT	/admin/api/2020-04/customers/{customer_id}.json Updates a customer.
DELETE	/admin/api/2020-04/customers/{customer_id}.json Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-04/customers/{customer_id}/account_activation_url.json Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-04/customers/{customer_id}/send_invite.json Sends an account invite to a customer.
GET	/admin/api/2020-04/customers/count.json Retrieves a count of all customers.
GET	/admin/api/2020-04/customers/{customer_id}/orders.json Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-07/customers.json Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customers.json Creates a customer.
GET	/admin/api/2020-07/customers/search.json Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/customers/{customer_id}.json Retrieves a single customer.
PUT	/admin/api/2020-07/customers/{customer_id}.json Updates a customer.
DELETE	/admin/api/2020-07/customers/{customer_id}.json Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-07/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

POST /admin/api/2020-07/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

GET </admin/api/2020-07/customers/count.json>

Retrieves a count of all customers.

GET /admin/api/2020-07/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

GET </admin/api/2020-10/customers.json>

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-10/customers.json>

Creates a customer.

GET </admin/api/2020-10/customers/search.json>

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-10/customers/{customer_id}.json

Retrieves a single customer.

PUT /admin/api/2020-10/customers/{customer_id}.json

Updates a customer.

DELETE /admin/api/2020-10/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.

POST /admin/api/2020-10/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

POST /admin/api/2020-10/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

GET </admin/api/2020-10/customers/count.json>

Retrieves a count of all customers.

GET /admin/api/2020-10/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

GET </admin/api/2021-01/customers.json>

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2021-01/customers.json>

Creates a customer.

GET </admin/api/2021-01/customers/search.json>

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2021-01/customers/{customer_id}.json

Retrieves a single customer.

PUT /admin/api/2021-01/customers/{customer_id}.json

Updates a customer.

DELETE /admin/api/2021-01/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.

POST /admin/api/2021-01/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

POST /admin/api/2021-01/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

GET </admin/api/2021-01/customers/count.json>

Retrieves a count of all customers.

GET	/admin/api/2021-01/customers/{customer_id}/orders.json	Retrieves a count of all customers.
GET	/admin/api/unstable/customers.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
POST	/admin/api/unstable/customers.json	Creates a customer.
GET	/admin/api/unstable/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/unstable/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/unstable/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/unstable/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/unstable/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/unstable/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/unstable/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-01/customers/{customer_id}/addresses.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customers/{customer_id}/addresses.json	Creates a new address for a customer.
GET	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json	Retrieves details a single customer address.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json	Updates an existing customer address.
DELETE	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json	Removes an address from a customer's address list.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/set.json	Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}/default.json	Sets the default address for a customer.
GET	/admin/api/2020-04/customers/{customer_id}/addresses.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customers/{customer_id}/addresses.json	Creates a new address for a customer.
GET	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json	Retrieves details a single customer address.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json	Updates an existing customer address.
DELETE	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json	Removes an address from a customer's address list.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/set.json	Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}/default.json	

	Sets the default address for a customer.
GET	/admin/api/2020-07/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2020-10/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2021-01/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/unstable/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/set.json

PUT	Performs bulk operations for multiple customer addresses. /admin/api/unstable/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2020-01/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/2020-01/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json Updates a customer saved search.
DELETE	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-04/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/2020-04/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json Updates a customer saved search.
DELETE	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-07/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/2020-07/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json Updates a customer saved search.
DELETE	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json

DELETE	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json Updates a customer saved search.
DELETE	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.
GET	/admin/api/unstable/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/unstable/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json Updates a customer saved search.
DELETE	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.

customers/customer

GET	/admin/api/2020-01/customers.json Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customers.json Creates a customer.
GET	/admin/api/2020-01/customers/search.json Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/customers/{customer_id}.json Retrieves a single customer.
PUT	/admin/api/2020-01/customers/{customer_id}.json Updates a customer.
DELETE	/admin/api/2020-01/customers/{customer_id}.json Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-01/customers/{customer_id}/account_activation_url.json Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-01/customers/{customer_id}/send_invite.json Sends an account invite to a customer.

GET	/admin/api/2020-01/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2020-01/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-04/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customers.json	Creates a customer.
GET	/admin/api/2020-04/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/2020-04/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/2020-04/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-04/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-04/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/2020-04/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2020-04/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-07/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customers.json	Creates a customer.
GET	/admin/api/2020-07/customers/search.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/customers/{customer_id}.json	Retrieves a single customer.
PUT	/admin/api/2020-07/customers/{customer_id}.json	Updates a customer.
DELETE	/admin/api/2020-07/customers/{customer_id}.json	Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/2020-07/customers/{customer_id}/account_activation_url.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/2020-07/customers/{customer_id}/send_invite.json	Sends an account invite to a customer.
GET	/admin/api/2020-07/customers/count.json	Retrieves a count of all customers.
GET	/admin/api/2020-07/customers/{customer_id}/orders.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
GET	/admin/api/2020-10/customers.json	

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-10/customers.json>

Creates a customer.

GET </admin/api/2020-10/customers/search.json>

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-10/customers/{customer_id}.json

Retrieves a single customer.

PUT /admin/api/2020-10/customers/{customer_id}.json

Updates a customer.

DELETE /admin/api/2020-10/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.

POST /admin/api/2020-10/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

POST /admin/api/2020-10/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

GET </admin/api/2020-10/customers/count.json>

Retrieves a count of all customers.

GET /admin/api/2020-10/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

GET </admin/api/2021-01/customers.json>

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2021-01/customers.json>

Creates a customer.

GET </admin/api/2021-01/customers/search.json>

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2021-01/customers/{customer_id}.json

Retrieves a single customer.

PUT /admin/api/2021-01/customers/{customer_id}.json

Updates a customer.

DELETE /admin/api/2021-01/customers/{customer_id}.json

Deletes a customer. A customer can't be deleted if they have existing orders.

POST /admin/api/2021-01/customers/{customer_id}/account_activation_url.json

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

POST /admin/api/2021-01/customers/{customer_id}/send_invite.json

Sends an account invite to a customer.

GET </admin/api/2021-01/customers/count.json>

Retrieves a count of all customers.

GET /admin/api/2021-01/customers/{customer_id}/orders.json

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

GET </admin/api/unstable/customers.json>

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/unstable/customers.json>

Creates a customer.

GET </admin/api/unstable/customers/search.json>

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests

	to paginated REST Admin API endpoints.
GET	/admin/api/unstable/customers/{customer_id}.json Retrieves a single customer.
PUT	/admin/api/unstable/customers/{customer_id}.json Updates a customer.
DELETE	/admin/api/unstable/customers/{customer_id}.json Deletes a customer. A customer can't be deleted if they have existing orders.
POST	/admin/api/unstable/customers/{customer_id}/account_activation_url.json Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
POST	/admin/api/unstable/customers/{customer_id}/send_invite.json Sends an account invite to a customer.
GET	/admin/api/unstable/customers/count.json Retrieves a count of all customers.
GET	/admin/api/unstable/customers/{customer_id}/orders.json Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

customers/customer-address

GET	/admin/api/2020-01/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2020-04/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-04/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2020-07/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json

	Updates an existing customer address.
DELETE	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2020-10/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2021-01/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/unstable/customers/{customer_id}/addresses.json Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/customers/{customer_id}/addresses.json Creates a new address for a customer.
GET	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Retrieves details a single customer address.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Updates an existing customer address.
DELETE	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json Removes an address from a customer's address list.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.

customers/customersavedsearch

GET	/admin/api/2020-01/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/customer_saved_searches.json

	Creates a customer saved search.
GET	/admin/api/2020-01/customer_saved_searches/count.json
	Retrieves a count of all customer saved searches.
GET	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json
	Retrieves a single customer saved search.
PUT	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json
	Updates a customer saved search.
DELETE	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json
	Deletes a customer saved search.
GET	/admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}/customers.json
	Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-04/customer_saved_searches.json
	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/customer_saved_searches.json
	Creates a customer saved search.
GET	/admin/api/2020-04/customer_saved_searches/count.json
	Retrieves a count of all customer saved searches.
GET	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json
	Retrieves a single customer saved search.
PUT	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json
	Updates a customer saved search.
DELETE	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json
	Deletes a customer saved search.
GET	/admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}/customers.json
	Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-07/customer_saved_searches.json
	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customer_saved_searches.json
	Creates a customer saved search.
GET	/admin/api/2020-07/customer_saved_searches/count.json
	Retrieves a count of all customer saved searches.
GET	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json
	Retrieves a single customer saved search.
PUT	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json
	Updates a customer saved search.
DELETE	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json
	Deletes a customer saved search.
GET	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}/customers.json
	Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches.json
	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customer_saved_searches.json
	Creates a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/count.json
	Retrieves a count of all customer saved searches.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json
	Retrieves a single customer saved search.
PUT	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json
	Updates a customer saved search.
DELETE	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json
	Deletes a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}/customers.json
	Retrieves all customers returned by a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches.json
	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to

paginated REST Admin API endpoints.

POST /admin/api/2021-01/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/2021-01/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

GET /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

PUT /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

DELETE /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

GET /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

GET /admin/api/unstable/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/unstable/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

GET /admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

PUT /admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

DELETE /admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

GET /admin/api/unstable/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

customersavedsearch

GET /admin/api/2020-01/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/2020-01/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

GET /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

PUT /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

DELETE /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

GET /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

GET /admin/api/2020-04/customer_saved_searches.json

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/customer_saved_searches.json

Creates a customer saved search.

GET /admin/api/2020-04/customer_saved_searches/count.json

Retrieves a count of all customer saved searches.

GET /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Retrieves a single customer saved search.

PUT /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Updates a customer saved search.

DELETE /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Deletes a customer saved search.

GET /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}/customers.json

GET	/admin/api/2020-07/customer_saved_searches.json	Retrieves all customers returned by a customer saved search.
		Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/customer_saved_searches.json	Creates a customer saved search.
GET	/admin/api/2020-07/customer_saved_searches/count.json	Retrieves a count of all customer saved searches.
GET	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a single customer saved search.
PUT	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json	Updates a customer saved search.
DELETE	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json	Deletes a customer saved search.
GET	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}/customers.json	Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches.json	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customer_saved_searches.json	Creates a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/count.json	Retrieves a count of all customer saved searches.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a single customer saved search.
PUT	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json	Updates a customer saved search.
DELETE	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json	Deletes a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}/customers.json	Retrieves all customers returned by a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches.json	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/customer_saved_searches.json	Creates a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches/count.json	Retrieves a count of all customer saved searches.
GET	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a single customer saved search.
PUT	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json	Updates a customer saved search.
DELETE	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json	Deletes a customer saved search.
GET	/admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}/customers.json	Retrieves all customers returned by a customer saved search.
GET	/admin/api/unstable/customer_saved_searches.json	Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/customer_saved_searches.json	Creates a customer saved search.
GET	/admin/api/unstable/customer_saved_searches/count.json	Retrieves a count of all customer saved searches.
GET	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json	Retrieves a single customer saved search.
PUT	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json	Updates a customer saved search.
DELETE	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json	

Deletes a customer saved search.

GET /admin/api/unstable/customer_saved_searches/{customer_saved_search_id}/customers.json

Retrieves all customers returned by a customer saved search.

deprecated_api_calls

GET /admin/api/2021-01/deprecated_api_calls.json

Retrieves a list of deprecated API calls made by the authenticated private app in the past 30 days.

GET /admin/api/unstable/deprecated_api_calls.json

Retrieves a list of deprecated API calls made by the authenticated private app in the past 30 days.

discountcode

GET /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

GET /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

PUT /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

DELETE /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

GET /admin/api/2020-01/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2020-01/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

GET /admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

GET /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

GET /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

PUT /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

DELETE /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

GET /admin/api/2020-04/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2020-04/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

GET	/admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json	Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json	Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json	Creates a discount code
GET	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Retrieves a single discount code
PUT	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Updates an existing discount code
DELETE	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Deletes a discount code
GET	/admin/api/2020-07/discount_codes/lookup.json	Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-07/price_rules/{price_rule_id}/batch.json	Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}.json	Retrieves a discount code creation job
GET	/admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json	Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json	Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json	Creates a discount code
GET	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Retrieves a single discount code
PUT	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Updates an existing discount code
DELETE	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json	Deletes a discount code
GET	/admin/api/2020-10/discount_codes/lookup.json	Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-10/price_rules/{price_rule_id}/batch.json	Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}.json	Retrieves a discount code creation job
GET	/admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json	Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json	Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json	

	Creates a discount code
GET	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/2021-01/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2021-01/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}.json Retrieves a discount code creation job
GET	/admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/unstable/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/unstable/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}.json Retrieves a discount code creation job
GET	/admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

discounts

GET	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

	Deletes a discount code
GET	/admin/api/2020-01/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-01/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}.json Retrieves a discount code creation job
GET	/admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/2020-04/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-04/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}.json Retrieves a discount code creation job
GET	/admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/2020-07/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-07/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of

discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

GET /admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

GET /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

GET /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

PUT /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

DELETE /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

GET /admin/api/2020-10/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2020-10/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

GET /admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

GET /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json

Creates a discount code

GET /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Retrieves a single discount code

PUT /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Updates an existing discount code

DELETE /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Deletes a discount code

GET /admin/api/2021-01/discount_codes/lookup.json

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

POST /admin/api/2021-01/price_rules/{price_rule_id}/batch.json

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

GET /admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}.json

Retrieves a discount code creation job

GET /admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

GET	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/unstable/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/unstable/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}.json Retrieves a discount code creation job
GET	/admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

discounts/discountcode

GET	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/2020-01/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-01/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}.json Retrieves a discount code creation job
GET	/admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json Creates a discount code

GET	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/2020-04/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-04/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}.json Retrieves a discount code creation job
GET	/admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/2020-07/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-07/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}.json Retrieves a discount code creation job
GET	/admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/2020-10/discount_codes/lookup.json

	Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-10/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}.json Retrieves a discount code creation job
GET	/admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/2021-01/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2021-01/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}.json Retrieves a discount code creation job
GET	/admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/unstable/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/unstable/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies

when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

[GET](#) [/admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}.json](#)

Retrieves a discount code creation job

[GET](#) [/admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json](#)

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

dispute

[GET](#) [/admin/api/2020-01/shopify_payments/disputes.json](#)

Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-01/shopify_payments/disputes/{dispute_id}.json](#)

Retrieves a single dispute by ID.

[GET](#) [/admin/api/2020-04/shopify_payments/disputes.json](#)

Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

event

[GET](#) [/admin/api/2020-01/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-01/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-01/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2020-04/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-04/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-04/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2020-07/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-07/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-07/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2020-10/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-10/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-10/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2021-01/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2021-01/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2021-01/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/unstable/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/unstable/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/unstable/events/count.json](#)

Retrieves a count of events

events

[GET](#) [/admin/api/2020-01/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-01/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-01/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2020-04/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-04/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-04/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2020-07/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-07/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-07/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2020-10/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-10/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2020-10/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2021-01/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2021-01/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/2021-01/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/unstable/events.json](#)

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/unstable/events/{event_id}.json](#)

Retrieves a single event by its ID

[GET](#) [/admin/api/unstable/events/count.json](#)

Retrieves a count of events

[GET](#) [/admin/api/2020-01/webhooks.json](#)

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-01/webhooks.json](#)

Create a new webhook subscription by specifying both an address and a topic

[GET](#) [/admin/api/2020-01/webhooks/count.json](#)

Retrieves a count of existing webhook subscriptions

[GET](#) [/admin/api/2020-01/webhooks/{webhook_id}.json](#)

Retrieves a single webhook subscription

PUT	/admin/api/2020-01/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-01/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/2020-04/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-04/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-04/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2020-04/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-04/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/2020-07/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-07/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-07/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2020-07/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-07/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/2020-10/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-10/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-10/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2020-10/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-10/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/2021-01/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2021-01/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/2021-01/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2021-01/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2021-01/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/unstable/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/webhooks.json Create a new webhook subscription by specifying both an address and a topic

GET	/admin/api/unstable/webhooks/count.json	Retrieves a count of existing webhook subscriptions
GET	/admin/api/unstable/webhooks/{webhook_id}.json	Retrieves a single webhook subscription
PUT	/admin/api/unstable/webhooks/{webhook_id}.json	Update a webhook subscription's topic or address URIs
DELETE	/admin/api/unstable/webhooks/{webhook_id}.json	Delete a webhook subscription

events/event

GET	/admin/api/2020-01/events.json	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/events/{event_id}.json	Retrieves a single event by its ID
GET	/admin/api/2020-01/events/count.json	Retrieves a count of events
GET	/admin/api/2020-04/events.json	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/events/{event_id}.json	Retrieves a single event by its ID
GET	/admin/api/2020-04/events/count.json	Retrieves a count of events
GET	/admin/api/2020-07/events.json	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/events/{event_id}.json	Retrieves a single event by its ID
GET	/admin/api/2020-07/events/count.json	Retrieves a count of events
GET	/admin/api/2020-10/events.json	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/events/{event_id}.json	Retrieves a single event by its ID
GET	/admin/api/2020-10/events/count.json	Retrieves a count of events
GET	/admin/api/2021-01/events.json	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/events/{event_id}.json	Retrieves a single event by its ID
GET	/admin/api/2021-01/events/count.json	Retrieves a count of events
GET	/admin/api/unstable/events.json	Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/events/{event_id}.json	Retrieves a single event by its ID
GET	/admin/api/unstable/events/count.json	Retrieves a count of events

events/webhook

GET	/admin/api/2020-01/webhooks.json	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
---------------------	--	---

POST	/admin/api/2020-01/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-01/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-01/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2020-01/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-01/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/2020-04/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-04/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-04/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2020-04/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-04/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/2020-07/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-07/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-07/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2020-07/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-07/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/2020-10/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-10/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/2020-10/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2020-10/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-10/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/2021-01/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2021-01/webhooks/count.json Retrieves a count of existing webhook subscriptions
GET	/admin/api/2021-01/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2021-01/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2021-01/webhooks/{webhook_id}.json

GET	Delete a webhook subscription /admin/api/unstable/webhooks.json
	Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/webhooks.json
	Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/unstable/webhooks/count.json
	Retrieves a count of existing webhook subscriptions
GET	/admin/api/unstable/webhooks/{webhook_id}.json
	Retrieves a single webhook subscription
PUT	/admin/api/unstable/webhooks/{webhook_id}.json
	Update a webhook subscription's topic or address URIs
DELETE	/admin/api/unstable/webhooks/{webhook_id}.json
	Delete a webhook subscription

fulfillment

GET	/admin/api/2020-01/orders/{order_id}/fulfillments.json
	Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/fulfillments.json
	Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json
	Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/count.json
	Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json
	Retrieve a specific fulfillment
PUT	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json
	Update information associated with a fulfillment
POST	/admin/api/2020-01/fulfillments.json
	Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-01/fulfillments/{fulfillment_id}/update_tracking.json
	Updates the tracking information for a fulfillment.
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json
	Mark a fulfillment as complete
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json
	Mark a fulfillment as open
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json
	Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-01/fulfillments/{fulfillment_id}/cancel.json
	Cancels a fulfillment.
GET	/admin/api/2020-04/orders/{order_id}/fulfillments.json
	Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/fulfillments.json
	Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and

partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

GET /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

GET /admin/api/2020-04/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

GET /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

PUT /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

POST </admin/api/2020-04/fulfillments.json>

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

POST /admin/api/2020-04/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

POST /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

POST /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

POST /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

POST /admin/api/2020-04/fulfillments/{fulfillment_id}/cancel.json

Cancels a fulfillment.

GET /admin/api/2020-07/orders/{order_id}/fulfillments.json

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/orders/{order_id}/fulfillments.json

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

GET /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

GET /admin/api/2020-07/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

GET /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

PUT /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

POST </admin/api/2020-07/fulfillments.json>

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

POST /admin/api/2020-07/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-07/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-10/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2021-01/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json

PUT	Retrieve a specific fulfillment /admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2021-01/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/unstable/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/unstable/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/unstable/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/unstable/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/unstable/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.

fulfillmentevent

GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Deletes a fulfillment event
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Retrieves a list of fulfillment events for a specific fulfillment
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Creates a fulfillment event
DELETE	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Retrieves a specific fulfillment event
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Deletes a fulfillment event
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Retrieves a list of fulfillment events for a specific fulfillment
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Creates a fulfillment event
DELETE	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Retrieves a specific fulfillment event
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Deletes a fulfillment event
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Retrieves a list of fulfillment events for a specific fulfillment
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Creates a fulfillment event
DELETE	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Retrieves a specific fulfillment event
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Deletes a fulfillment event
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Retrieves a list of fulfillment events for a specific fulfillment
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Creates a fulfillment event
DELETE	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Retrieves a specific fulfillment event
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Deletes a fulfillment event
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json	Retrieves a list of fulfillment events for a specific fulfillment
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Creates a fulfillment event
DELETE	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json	Retrieves a specific fulfillment event

fulfillmentorder

GET	/admin/api/2020-01/orders/{order_id}/fulfillment_orders.json	Retrieves a list of fulfillment orders for a specific order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}.json	Retrieves a specific fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancel.json	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/close.json	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/move.json	Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-04/orders/{order_id}/fulfillment_orders.json	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}.json	Retrieves a specific fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancel.json	Marks a fulfillment order as cancelled.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/close.json	

	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-07/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-10/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2021-01/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/open.json Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/reschedule.json Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.
GET	/admin/api/unstable/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/unstable/fulfillment_orders/release_hold.json Releases the fulfillment order holds for a specific order. Fulfillment orders are created with an ON_HOLD status if the channel that created the order has a fulfillment hold policy.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/open.json Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/reschedule.json Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.

fulfillmentrequest

POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

fulfillmentservice

GET	/fetch_tracking_numbers Get tracking numbers for orders
GET	/fetch_stock Get inventory levels
GET	/admin/api/2020-01/fulfillment_services.json
POST	/admin/api/2020-01/fulfillment_services.json To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.
GET	/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json
PUT	/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json
DELETE	/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json
GET	/admin/api/2020-04/fulfillment_services.json
POST	/admin/api/2020-04/fulfillment_services.json To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.
GET	/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

PUT /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

DELETE /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

GET /admin/api/2020-07/fulfillment_services.json

POST /admin/api/2020-07/fulfillment_services.json

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET /admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

PUT /admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

DELETE /admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

GET /admin/api/2020-10/fulfillment_services.json

POST /admin/api/2020-10/fulfillment_services.json

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

PUT /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

DELETE /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

GET /admin/api/2021-01/fulfillment_services.json

POST /admin/api/2021-01/fulfillment_services.json

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

PUT /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

DELETE /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

GET /admin/api/unstable/fulfillment_services.json

POST /admin/api/unstable/fulfillment_services.json

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json

PUT /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json

DELETE /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json

giftcard

GET /admin/api/2020-01/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/gift_cards.json

Creates a gift card

GET /admin/api/2020-01/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

PUT /admin/api/2020-01/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

GET /admin/api/2020-01/gift_cards/count.json

Retrieves a count of gift cards

POST /admin/api/2020-01/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

GET /admin/api/2020-01/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET	/admin/api/2020-04/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/gift_cards.json	Creates a gift card
GET	/admin/api/2020-04/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2020-04/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-04/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2020-04/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-04/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/gift_cards.json	Creates a gift card
GET	/admin/api/2020-07/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2020-07/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-07/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2020-07/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-07/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/gift_cards.json	Creates a gift card
GET	/admin/api/2020-10/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2020-10/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-10/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2020-10/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-10/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/gift_cards.json	

GET	/admin/api/2021-01/gift_cards/{gift_card_id}.json	Creates a gift card
PUT	/admin/api/2021-01/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
GET	/admin/api/2021-01/gift_cards/count.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
POST	/admin/api/2021-01/gift_cards/{gift_card_id}/disable.json	Retrieves a count of gift cards
GET	/admin/api/2021-01/gift_cards/search.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/unstable/gift_cards.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/gift_cards/{gift_card_id}.json	Creates a gift card
PUT	/admin/api/unstable/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
GET	/admin/api/unstable/gift_cards/count.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
POST	/admin/api/unstable/gift_cards/{gift_card_id}/disable.json	Retrieves a count of gift cards
GET	/admin/api/unstable/gift_cards/search.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/unstable/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

inventory

GET	/admin/api/2020-01/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-01/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-04/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-04/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-07/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-07/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-10/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET	/admin/api/2020-10/inventory_items/{inventory_item_id}.json Retrieves a single inventory item by ID
PUT	/admin/api/2020-10/inventory_items/{inventory_item_id}.json Updates an existing inventory item
GET	/admin/api/2021-01/inventory_items.json Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/inventory_items/{inventory_item_id}.json Retrieves a single inventory item by ID
PUT	/admin/api/2021-01/inventory_items/{inventory_item_id}.json Updates an existing inventory item
GET	/admin/api/unstable/inventory_items.json Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/inventory_items/{inventory_item_id}.json Retrieves a single inventory item by ID
PUT	/admin/api/unstable/inventory_items/{inventory_item_id}.json Updates an existing inventory item
GET	/admin/api/2020-01/inventory_levels.json Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-01/inventory_levels.json Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-01/inventory_levels/adjust.json Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2020-01/inventory_levels/connect.json Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2020-01/inventory_levels/set.json Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/2020-04/inventory_levels.json Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-04/inventory_levels.json Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-04/inventory_levels/adjust.json Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2020-04/inventory_levels/connect.json Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2020-04/inventory_levels/set.json Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/2020-07/inventory_levels.json Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-07/inventory_levels.json Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-07/inventory_levels/adjust.json Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2020-07/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-07/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2020-10/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2020-10/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-10/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-10/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-10/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2021-01/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2021-01/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2021-01/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2021-01/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2021-01/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/unstable/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/unstable/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/unstable/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/unstable/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/unstable/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET </admin/api/2020-01/locations.json>

Retrieves a list of locations

GET /admin/api/2020-01/locations/{location_id}.json

Retrieves a single location by its ID

GET </admin/api/2020-01/locations/count.json>

Retrieves a count of locations

GET /admin/api/2020-01/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET	/admin/api/2020-04/locations.json	Retrieves a list of locations
GET	/admin/api/2020-04/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2020-04/locations/count.json	Retrieves a count of locations
GET	/admin/api/2020-04/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/locations.json	Retrieves a list of locations
GET	/admin/api/2020-07/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2020-07/locations/count.json	Retrieves a count of locations
GET	/admin/api/2020-07/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/locations.json	Retrieves a list of locations
GET	/admin/api/2020-10/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2020-10/locations/count.json	Retrieves a count of locations
GET	/admin/api/2020-10/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/locations.json	Retrieves a list of locations
GET	/admin/api/2021-01/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/2021-01/locations/count.json	Retrieves a count of locations
GET	/admin/api/2021-01/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/locations.json	Retrieves a list of locations
GET	/admin/api/unstable/locations/{location_id}.json	Retrieves a single location by its ID
GET	/admin/api/unstable/locations/count.json	Retrieves a count of locations
GET	/admin/api/unstable/locations/{location_id}/inventory_levels.json	Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

inventory/inventoryitem

GET	/admin/api/2020-01/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/inventory_items/{inventory_item_id}.json	Retrieves a single inventory item by ID
PUT	/admin/api/2020-01/inventory_items/{inventory_item_id}.json	Updates an existing inventory item
GET	/admin/api/2020-04/inventory_items.json	Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET	/admin/api/2020-04/inventory_items/{inventory_item_id}.json Retrieves a single inventory item by ID
PUT	/admin/api/2020-04/inventory_items/{inventory_item_id}.json Updates an existing inventory item
GET	/admin/api/2020-07/inventory_items.json Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/inventory_items/{inventory_item_id}.json Retrieves a single inventory item by ID
PUT	/admin/api/2020-07/inventory_items/{inventory_item_id}.json Updates an existing inventory item
GET	/admin/api/2020-10/inventory_items.json Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/inventory_items/{inventory_item_id}.json Retrieves a single inventory item by ID
PUT	/admin/api/2020-10/inventory_items/{inventory_item_id}.json Updates an existing inventory item
GET	/admin/api/2021-01/inventory_items.json Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/inventory_items/{inventory_item_id}.json Retrieves a single inventory item by ID
PUT	/admin/api/2021-01/inventory_items/{inventory_item_id}.json Updates an existing inventory item
GET	/admin/api/unstable/inventory_items.json Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/inventory_items/{inventory_item_id}.json Retrieves a single inventory item by ID
PUT	/admin/api/unstable/inventory_items/{inventory_item_id}.json Updates an existing inventory item

inventory/inventorylevel

GET	/admin/api/2020-01/inventory_levels.json Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-01/inventory_levels.json Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-01/inventory_levels/adjust.json Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2020-01/inventory_levels/connect.json Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2020-01/inventory_levels/set.json Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/2020-04/inventory_levels.json Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-04/inventory_levels.json Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-04/inventory_levels/adjust.json Adjusts the inventory level of an inventory item at a single location

POST	/admin/api/2020-04/inventory_levels/connect.json Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2020-04/inventory_levels/set.json Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/2020-07/inventory_levels.json Retrieves a list of inventory levels. You must include <code>inventory_item_ids</code> , <code>location_ids</code> , or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-07/inventory_levels.json Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-07/inventory_levels/adjust.json Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2020-07/inventory_levels/connect.json Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2020-07/inventory_levels/set.json Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/2020-10/inventory_levels.json Retrieves a list of inventory levels. You must include <code>inventory_item_ids</code> , <code>location_ids</code> , or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-10/inventory_levels.json Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-10/inventory_levels/adjust.json Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2020-10/inventory_levels/connect.json Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2020-10/inventory_levels/set.json Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/2021-01/inventory_levels.json Retrieves a list of inventory levels. You must include <code>inventory_item_ids</code> , <code>location_ids</code> , or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2021-01/inventory_levels.json Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2021-01/inventory_levels/adjust.json Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2021-01/inventory_levels/connect.json Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2021-01/inventory_levels/set.json Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/unstable/inventory_levels.json Retrieves a list of inventory levels. You must include <code>inventory_item_ids</code> , <code>location_ids</code> , or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/unstable/inventory_levels.json Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/unstable/inventory_levels/adjust.json

- POST** [/admin/api/unstable/inventory_levels/connect.json](#)
Adjusts the inventory level of an inventory item at a single location
Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
- POST** [/admin/api/unstable/inventory_levels/set.json](#)
Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

inventory/location

- GET** [/admin/api/2020-01/locations.json](#)
Retrieves a list of locations
- GET** [/admin/api/2020-01/locations/{location_id}.json](#)
Retrieves a single location by its ID
- GET** [/admin/api/2020-01/locations/count.json](#)
Retrieves a count of locations
- GET** [/admin/api/2020-01/locations/{location_id}/inventory_levels.json](#)
Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- GET** [/admin/api/2020-04/locations.json](#)
Retrieves a list of locations
- GET** [/admin/api/2020-04/locations/{location_id}.json](#)
Retrieves a single location by its ID
- GET** [/admin/api/2020-04/locations/count.json](#)
Retrieves a count of locations
- GET** [/admin/api/2020-04/locations/{location_id}/inventory_levels.json](#)
Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- GET** [/admin/api/2020-07/locations.json](#)
Retrieves a list of locations
- GET** [/admin/api/2020-07/locations/{location_id}.json](#)
Retrieves a single location by its ID
- GET** [/admin/api/2020-07/locations/count.json](#)
Retrieves a count of locations
- GET** [/admin/api/2020-07/locations/{location_id}/inventory_levels.json](#)
Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- GET** [/admin/api/2020-10/locations.json](#)
Retrieves a list of locations
- GET** [/admin/api/2020-10/locations/{location_id}.json](#)
Retrieves a single location by its ID
- GET** [/admin/api/2020-10/locations/count.json](#)
Retrieves a count of locations
- GET** [/admin/api/2020-10/locations/{location_id}/inventory_levels.json](#)
Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- GET** [/admin/api/2021-01/locations.json](#)
Retrieves a list of locations
- GET** [/admin/api/2021-01/locations/{location_id}.json](#)
Retrieves a single location by its ID
- GET** [/admin/api/2021-01/locations/count.json](#)
Retrieves a count of locations
- GET** [/admin/api/2021-01/locations/{location_id}/inventory_levels.json](#)
Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- GET** [/admin/api/unstable/locations.json](#)
Retrieves a list of locations
- GET** [/admin/api/unstable/locations/{location_id}.json](#)
Retrieves a single location by its ID

- [GET](#) </admin/api/unstable/locations/count.json>
Retrieves a count of locations
- [GET](#) /admin/api/unstable/locations/{location_id}/inventory_levels.json
Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

inventoryitem

- [GET](#) /admin/api/2020-01/inventory_items.json
Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/2020-01/inventory_items/{inventory_item_id}.json
Retrieves a single inventory item by ID
- [PUT](#) /admin/api/2020-01/inventory_items/{inventory_item_id}.json
Updates an existing inventory item
- [GET](#) /admin/api/2020-04/inventory_items.json
Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/2020-04/inventory_items/{inventory_item_id}.json
Retrieves a single inventory item by ID
- [PUT](#) /admin/api/2020-04/inventory_items/{inventory_item_id}.json
Updates an existing inventory item
- [GET](#) /admin/api/2020-07/inventory_items.json
Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/2020-07/inventory_items/{inventory_item_id}.json
Retrieves a single inventory item by ID
- [PUT](#) /admin/api/2020-07/inventory_items/{inventory_item_id}.json
Updates an existing inventory item
- [GET](#) /admin/api/2020-10/inventory_items.json
Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/2020-10/inventory_items/{inventory_item_id}.json
Retrieves a single inventory item by ID
- [PUT](#) /admin/api/2020-10/inventory_items/{inventory_item_id}.json
Updates an existing inventory item
- [GET](#) /admin/api/2021-01/inventory_items.json
Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/2021-01/inventory_items/{inventory_item_id}.json
Retrieves a single inventory item by ID
- [PUT](#) /admin/api/2021-01/inventory_items/{inventory_item_id}.json
Updates an existing inventory item
- [GET](#) /admin/api/unstable/inventory_items.json
Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/unstable/inventory_items/{inventory_item_id}.json
Retrieves a single inventory item by ID
- [PUT](#) /admin/api/unstable/inventory_items/{inventory_item_id}.json
Updates an existing inventory item

inventorylevel

- [GET](#) /admin/api/2020-01/inventory_levels.json
Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [DELETE](#) /admin/api/2020-01/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-01/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-01/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-01/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2020-04/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2020-04/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-04/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-04/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-04/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2020-07/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2020-07/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-07/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-07/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-07/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2020-10/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE /admin/api/2020-10/inventory_levels.json

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

POST /admin/api/2020-10/inventory_levels/adjust.json

Adjusts the inventory level of an inventory item at a single location

POST /admin/api/2020-10/inventory_levels/connect.json

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

POST /admin/api/2020-10/inventory_levels/set.json

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

GET /admin/api/2021-01/inventory_levels.json

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

DELETE	/admin/api/2021-01/inventory_levels.json	Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2021-01/inventory_levels/adjust.json	Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2021-01/inventory_levels/connect.json	Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2021-01/inventory_levels/set.json	Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/unstable/inventory_levels.json	Retrieves a list of inventory levels. You must include <code>inventory_item_ids</code> , <code>location_ids</code> , or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/unstable/inventory_levels.json	Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/unstable/inventory_levels/adjust.json	Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/unstable/inventory_levels/connect.json	Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/unstable/inventory_levels/set.json	Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

latest_api_version

GET	/admin/oauth/access_scopes.json	Retrieves a list of access scopes associated to the access token.
GET	/admin/api/2020-10/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-10/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-10/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2020-10/reports.json	Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/reports.json	Creates a new report
GET	/admin/api/2020-10/reports/{report_id}.json	Retrieves a single report created by your app
PUT	/admin/api/2020-10/reports/{report_id}.json	Updates a report
DELETE	/admin/api/2020-10/reports/{report_id}.json	Deletes a report
GET	/admin/api/2020-10/application_charges.json	Retrieves a list of application charges
POST	/admin/api/2020-10/application_charges.json	Creates an application charge
GET	/admin/api/2020-10/application_charges/{application_charge_id}.json	Retrieves an application charge
POST	/admin/api/2020-10/application_charges/{application_charge_id}/activate.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-10/application_credits.json	Retrieves all application credits
POST	/admin/api/2020-10/application_credits.json	

GET	/admin/api/2020-10/application_credits/{application_credit_id}.json	Creates an application credit
GET	/admin/api/2020-10/recurring_application_charges.json	Retrieves a single application credit
POST	/admin/api/2020-10/recurring_application_charges.json	Retrieves a list of recurring application charges
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json	Creates a recurring application charge
DELETE	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json	Retrieves a single charge
POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/activate.json	Cancels a recurring application charge
PUT	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/customize.json	Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Updates the capped amount of an active recurring application charge
POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json	Retrieves a list of usage charges
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json	Creates a usage charge
GET	/admin/api/2020-10/customers.json	Retrieves a single charge
POST	/admin/api/2020-10/customers.json	Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/customers/search.json	Creates a customer.
PUT	/admin/api/2020-10/customers/{customer_id}.json	Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-10/customers/{customer_id}.json	Retrieves a single customer.
POST	/admin/api/2020-10/customers/{customer_id}/account_activation_url.json	Updates a customer.
POST	/admin/api/2020-10/customers/{customer_id}/send_invite.json	Deletes a customer. A customer can't be deleted if they have existing orders.
GET	/admin/api/2020-10/customers/{customer_id}/orders.json	Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.
GET	/admin/api/2020-10/customers/{customer_id}/addresses.json	Sends an account invite to a customer.
POST	/admin/api/2020-10/customers/{customer_id}/addresses.json	Retrieves a count of all customers.
GET	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json	Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json	Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json	Creates a new address for a customer.
		Retrieves details a single customer address.
		Updates an existing customer address.
		Removes an address from a customer's address list.

PUT	/admin/api/2020-10/customers/{customer_id}/addresses/set.json Performs bulk operations for multiple customer addresses.
PUT	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}/default.json Sets the default address for a customer.
GET	/admin/api/2020-10/customer_saved_searches.json Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/customer_saved_searches.json Creates a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/count.json Retrieves a count of all customer saved searches.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json Retrieves a single customer saved search.
PUT	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json Updates a customer saved search.
DELETE	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json Deletes a customer saved search.
GET	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}/customers.json Retrieves all customers returned by a customer saved search.
GET	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json Creates a discount code
GET	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Retrieves a single discount code
PUT	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Updates an existing discount code
DELETE	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json Deletes a discount code
GET	/admin/api/2020-10/discount_codes/lookup.json Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.
POST	/admin/api/2020-10/price_rules/{price_rule_id}/batch.json Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"
GET	/admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}.json Retrieves a discount code creation job
GET	/admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.
GET	/admin/api/2020-10/events.json Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/events/{event_id}.json Retrieves a single event by its ID
GET	/admin/api/2020-10/events/count.json Retrieves a count of events
GET	/admin/api/2020-10/webhooks.json Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/webhooks.json Create a new webhook subscription by specifying both an address and a topic
GET	/admin/api/2020-10/webhooks/count.json Retrieves a count of existing webhook subscriptions

GET	/admin/api/2020-10/webhooks/{webhook_id}.json Retrieves a single webhook subscription
PUT	/admin/api/2020-10/webhooks/{webhook_id}.json Update a webhook subscription's topic or address URIs
DELETE	/admin/api/2020-10/webhooks/{webhook_id}.json Delete a webhook subscription
GET	/admin/api/2020-10/inventory_items.json Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/inventory_items/{inventory_item_id}.json Retrieves a single inventory item by ID
PUT	/admin/api/2020-10/inventory_items/{inventory_item_id}.json Updates an existing inventory item
GET	/admin/api/2020-10/inventory_levels.json Retrieves a list of inventory levels. You must include inventory_item_ids, location_ids, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
DELETE	/admin/api/2020-10/inventory_levels.json Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.
POST	/admin/api/2020-10/inventory_levels/adjust.json Adjusts the inventory level of an inventory item at a single location
POST	/admin/api/2020-10/inventory_levels/connect.json Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
POST	/admin/api/2020-10/inventory_levels/set.json Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.
GET	/admin/api/2020-10/locations.json Retrieves a list of locations
GET	/admin/api/2020-10/locations/{location_id}.json Retrieves a single location by its ID
GET	/admin/api/2020-10/locations/count.json Retrieves a count of locations
GET	/admin/api/2020-10/locations/{location_id}/inventory_levels.json Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/metafields.json Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/2020-10/metafields.json Creates a new metafield for a resource.
GET	/admin/api/2020-10/metafields/count.json Retrieves a count of a resource's metafields.
GET	/admin/api/2020-10/metafields/{metafield_id}.json Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/2020-10/metafields/{metafield_id}.json Updates a metafield.
DELETE	/admin/api/2020-10/metafields/{metafield_id}.json Deletes a metafield by its ID.
GET	/admin/api/2020-10/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-10/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article

PUT	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-10/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-10/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-10/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties .
PUT	/admin/api/2020-10/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-10/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-10/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the <code>page</code> parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints .
POST	/admin/api/2020-10/redirects.json Creates a redirect. When you provide a full URL as the value of the <code>path</code> property, it will be saved as an absolute path without the domain. For example, <code>"path": "http://www.johns-apparel.com/springwear"</code> will be saved as <code>"path": "springwear"</code> .
GET	/admin/api/2020-10/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2020-10/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2020-10/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2020-10/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2020-10/script_tags.json Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the <code>page</code> parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints .
POST	/admin/api/2020-10/script_tags.json Creates a new script tag
GET	/admin/api/2020-10/script_tags/count.json Retrieves a count of all script tags
GET	/admin/api/2020-10/script_tags/{script_tag_id}.json Retrieves a single script tag
PUT	/admin/api/2020-10/script_tags/{script_tag_id}.json Updates a script tag
DELETE	/admin/api/2020-10/script_tags/{script_tag_id}.json Deletes a script tag
GET	/admin/api/2020-10/themes.json Retrieves a list of themes.
POST	/admin/api/2020-10/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include <code>"role": "main"</code> in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-10/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-10/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-10/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2020-10/checkouts/count.json Retrieves a count of checkouts from the past 90 days
POST	/admin/api/2020-10/checkouts.json Creates a checkout

GET	/admin/api/2020-10/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/risks.json	Creates an order risk for an order
GET	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
PUT	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-10/orders/{order_id}/refunds.json	Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/refunds.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-10/orders/{order_id}/refunds/{refund_id}.json	Retrieves a specific refund.
POST	/admin/api/2020-10/orders/{order_id}/refunds/calculate.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.
GET	/admin/api/2020-10/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/gift_cards.json	Creates a gift card
GET	/admin/api/2020-10/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2020-10/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-10/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2020-10/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-10/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/users.json	Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/users/{user_id}.json	Retrieves a single user
GET	/admin/api/2020-10/users/current.json	Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-10/collects.json	Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/collects.json	

GET	/admin/api/2020-10/collects/{collect_id}.json Adds a product to a custom collection. Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-10/collects/{collect_id}.json Removes a product from a collection.
GET	/admin/api/2020-10/collects/count.json Retrieves a count of collects.
GET	/admin/api/2020-10/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2020-10/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-10/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/custom_collections.json Creates a custom collection
GET	/admin/api/2020-10/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2020-10/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-10/products/count.json Retrieves a count of products.
GET	/admin/api/2020-10/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2020-10/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-10/products/{product_id}.json Deletes a product.
GET	/admin/api/2020-10/products/{product_id}/images.json Get all product images
POST	/admin/api/2020-10/products/{product_id}/images.json Create a new product image
GET	/admin/api/2020-10/products/{product_id}/images/count.json Get a count of all product images
GET	/admin/api/2020-10/products/{product_id}/images/{image_id}.json Get a single product image by id
PUT	/admin/api/2020-10/products/{product_id}/images/{image_id}.json Modify an existing product image
DELETE	/admin/api/2020-10/products/{product_id}/images/{image_id}.json
GET	/admin/api/2020-10/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/smart_collections.json Creates a new smart collection using the specified rules.

GET	/admin/api/2020-10/smart_collections/count.json	Retrieves a count of smart collections
GET	/admin/api/2020-10/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
PUT	/admin/api/2020-10/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
DELETE	/admin/api/2020-10/smart_collections/{smart_collection_id}.json	Removes a smart collection
PUT	/admin/api/2020-10/smart_collections/{smart_collection_id}/order.json	Updates the ordering type of products in a smart collection
POST	/admin/api/2020-10/checkouts/{token}/complete.json	Completes a checkout
GET	/admin/api/2020-10/checkouts/{token}.json	Retrieves a checkout
PUT	/admin/api/2020-10/checkouts/{token}.json	Modifies an existing checkout
GET	/admin/api/2020-10/checkouts/{token}/shipping_rates.json	Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
GET	/admin/api/2020-10/collection_listings.json	Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/collection_listings/{collection_listing_id}/product_ids.json	Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/collection_listings/{collection_listing_id}.json	Retrieve a specific collection listing that is published to your app
PUT	/admin/api/2020-10/collection_listings/{collection_listing_id}.json	Create a collection listing to publish a collection to your app
DELETE	/admin/api/2020-10/collection_listings/{collection_listing_id}.json	Delete a collection listing to unpublish a collection from your app
GET	/admin/api/2020-10/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-10/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-10/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-10/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-10/assigned_fulfillment_orders.json	Retrieves a list of fulfillment orders on a shop for a specific app.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json	Sends a cancellation request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json	Accepts a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json	Rejects a cancellation request sent to a fulfillment service for a fulfillment order.
GET	/admin/api/2020-10/carrier_services.json	Retrieves a list of carrier services
POST	/admin/api/2020-10/carrier_services.json	Creates a carrier service
GET	/admin/api/2020-10/carrier_services/{carrier_service_id}.json	Retrieves a single carrier service by its ID
PUT	/admin/api/2020-10/carrier_services/{carrier_service_id}.json	Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/2020-10/carrier_services/{carrier_service_id}.json	Deletes a carrier service
GET	/admin/api/2020-10/orders/{order_id}/fulfillments.json	

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/orders/{order_id}/fulfillments.json

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

GET /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

GET /admin/api/2020-10/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

GET /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

PUT /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

POST </admin/api/2020-10/fulfillments.json>

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

POST /admin/api/2020-10/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

POST /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

POST /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

POST /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

POST /admin/api/2020-10/fulfillments/{fulfillment_id}/cancel.json

Cancels a fulfillment.

GET /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Retrieves a list of fulfillment events for a specific fulfillment

POST /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Creates a fulfillment event

GET /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Retrieves a specific fulfillment event

DELETE /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Deletes a fulfillment event

GET /admin/api/2020-10/orders/{order_id}/fulfillment_orders.json

Retrieves a list of fulfillment orders for a specific order.

GET /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}.json

Retrieves a specific fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancel.json

Marks a fulfillment order as cancelled.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/close.json

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/move.json

Moves a fulfillment order from one merchant managed location to another merchant managed location.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Sends a fulfillment request to the fulfillment service of a fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

GET	/admin/api/2020-10/fulfillment_services.json
POST	/admin/api/2020-10/fulfillment_services.json To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.
GET	/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json
PUT	/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json
DELETE	/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/2020-10/shopify_payments/balance.json Retrieves the account's current balance.
GET	/admin/api/2020-10/shopify_payments/payouts.json Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/shopify_payments/payouts/{payout_id}.json Retrieves a single payout by id.
GET	/admin/api/2020-10/countries.json Retrieves a list of countries.
POST	/admin/api/2020-10/countries.json Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-10/countries/count.json Retrieves a count of countries.
GET	/admin/api/2020-10/countries/{country_id}.json Retrieves a specific county.
PUT	/admin/api/2020-10/countries/{country_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-10/countries/{country_id}.json Deletes a country.
GET	/admin/api/2020-10/currencies.json Retrieves a list of currencies enabled on a shop
GET	/admin/api/2020-10/policies.json Retrieves a list of the shop's policies
GET	/admin/api/2020-10/countries/{country_id}/provinces.json Retrieves a list of provinces
GET	/admin/api/2020-10/countries/{country_id}/provinces/count.json Retrieves a count of provinces for a country
GET	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json Retrieves a single province for a country
PUT	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-10/shipping_zones.json Get a list of all shipping zones
GET	/admin/api/2020-10/shop.json Retrieves the shop's configuration
GET	/admin/api/2020-10/tender_transactions.json Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

location

GET	/admin/api/2020-01/locations.json Retrieves a list of locations
GET	/admin/api/2020-01/locations/{location_id}.json Retrieves a single location by its ID
GET	/admin/api/2020-01/locations/count.json Retrieves a count of locations
GET	/admin/api/2020-01/locations/{location_id}/inventory_levels.json

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET /admin/api/2020-04/locations.json](#)

Retrieves a list of locations

[GET /admin/api/2020-04/locations/{location_id}.json](#)

Retrieves a single location by its ID

[GET /admin/api/2020-04/locations/count.json](#)

Retrieves a count of locations

[GET /admin/api/2020-04/locations/{location_id}/inventory_levels.json](#)

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET /admin/api/2020-07/locations.json](#)

Retrieves a list of locations

[GET /admin/api/2020-07/locations/{location_id}.json](#)

Retrieves a single location by its ID

[GET /admin/api/2020-07/locations/count.json](#)

Retrieves a count of locations

[GET /admin/api/2020-07/locations/{location_id}/inventory_levels.json](#)

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET /admin/api/2020-10/locations.json](#)

Retrieves a list of locations

[GET /admin/api/2020-10/locations/{location_id}.json](#)

Retrieves a single location by its ID

[GET /admin/api/2020-10/locations/count.json](#)

Retrieves a count of locations

[GET /admin/api/2020-10/locations/{location_id}/inventory_levels.json](#)

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET /admin/api/2021-01/locations.json](#)

Retrieves a list of locations

[GET /admin/api/2021-01/locations/{location_id}.json](#)

Retrieves a single location by its ID

[GET /admin/api/2021-01/locations/count.json](#)

Retrieves a count of locations

[GET /admin/api/2021-01/locations/{location_id}/inventory_levels.json](#)

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET /admin/api/unstable/locations.json](#)

Retrieves a list of locations

[GET /admin/api/unstable/locations/{location_id}.json](#)

Retrieves a single location by its ID

[GET /admin/api/unstable/locations/count.json](#)

Retrieves a count of locations

[GET /admin/api/unstable/locations/{location_id}/inventory_levels.json](#)

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

locationsformove

[GET /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json	Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

metafield

GET	/admin/api/2020-01/metafields.json	Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/2020-01/metafields.json	Creates a new metafield for a resource.
GET	/admin/api/2020-01/metafields/count.json	Retrieves a count of a resource's metafields.
GET	/admin/api/2020-01/metafields/{metafield_id}.json	Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/2020-01/metafields/{metafield_id}.json	Updates a metafield.
DELETE	/admin/api/2020-01/metafields/{metafield_id}.json	Deletes a metafield by its ID.
GET	/admin/api/2020-04/metafields.json	Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/2020-04/metafields.json	Creates a new metafield for a resource.
GET	/admin/api/2020-04/metafields/count.json	Retrieves a count of a resource's metafields.
GET	/admin/api/2020-04/metafields/{metafield_id}.json	Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/2020-04/metafields/{metafield_id}.json	Updates a metafield.
DELETE	/admin/api/2020-04/metafields/{metafield_id}.json	Deletes a metafield by its ID.
GET	/admin/api/2020-07/metafields.json	Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/2020-07/metafields.json	Creates a new metafield for a resource.
GET	/admin/api/2020-07/metafields/count.json	Retrieves a count of a resource's metafields.
GET	/admin/api/2020-07/metafields/{metafield_id}.json	Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/2020-07/metafields/{metafield_id}.json	Updates a metafield.
DELETE	/admin/api/2020-07/metafields/{metafield_id}.json	Deletes a metafield by its ID.
GET	/admin/api/2020-10/metafields.json	Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/2020-10/metafields.json	Creates a new metafield for a resource.
GET	/admin/api/2020-10/metafields/count.json	Retrieves a count of a resource's metafields.
GET	/admin/api/2020-10/metafields/{metafield_id}.json	Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/2020-10/metafields/{metafield_id}.json	Updates a metafield.
DELETE	/admin/api/2020-10/metafields/{metafield_id}.json	Deletes a metafield by its ID.
GET	/admin/api/2021-01/metafields.json	Retrieves a list of metafields that belong to a Product Image resource.

POST	/admin/api/2021-01/metafields.json Creates a new metafield for a resource.
GET	/admin/api/2021-01/metafields/count.json Retrieves a count of a resource's metafields.
GET	/admin/api/2021-01/metafields/{metafield_id}.json Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/2021-01/metafields/{metafield_id}.json Updates a metafield.
DELETE	/admin/api/2021-01/metafields/{metafield_id}.json Deletes a metafield by its ID.
GET	/admin/api/unstable/metafields.json Retrieves a list of metafields that belong to a Product Image resource.
POST	/admin/api/unstable/metafields.json Creates a new metafield for a resource.
GET	/admin/api/unstable/metafields/count.json Retrieves a count of a resource's metafields.
GET	/admin/api/unstable/metafields/{metafield_id}.json Retrieves a single metafield from a resource by its ID.
PUT	/admin/api/unstable/metafields/{metafield_id}.json Updates a metafield.
DELETE	/admin/api/unstable/metafields/{metafield_id}.json Deletes a metafield by its ID.

online-store

GET	/admin/api/2020-01/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-01/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-01/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-01/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-04/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-04/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-04/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-04/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-07/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/blogs/{blog_id}/articles.json

Creates an article for a blog

GET /admin/api/2020-07/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

GET /admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article

PUT /admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json

Updates an article

DELETE /admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

GET </admin/api/2020-07/articles/authors.json>

Retrieves a list all of article authors

GET </admin/api/2020-07/articles/tags.json>

Retrieves a list of all the tags

GET /admin/api/2020-10/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/blogs/{blog_id}/articles.json

Creates an article for a blog

GET /admin/api/2020-10/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

GET /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article

PUT /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Updates an article

DELETE /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

GET </admin/api/2020-10/articles/authors.json>

Retrieves a list all of article authors

GET </admin/api/2020-10/articles/tags.json>

Retrieves a list of all the tags

GET /admin/api/2021-01/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/blogs/{blog_id}/articles.json

Creates an article for a blog

GET /admin/api/2021-01/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

GET /admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article

PUT /admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json

Updates an article

DELETE /admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

GET </admin/api/2021-01/articles/authors.json>

Retrieves a list all of article authors

GET </admin/api/2021-01/articles/tags.json>

Retrieves a list of all the tags

GET /admin/api/unstable/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/blogs/{blog_id}/articles.json

Creates an article for a blog

GET /admin/api/unstable/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

GET /admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

PUT	Retrieves a single article /admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/unstable/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/unstable/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-01/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-01/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-01/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-04/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-04/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-04/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-07/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-07/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-07/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-10/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2020-10/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2020-10/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2021-01/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/2021-01/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/2021-01/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/unstable/themes/{theme_id}/assets.json Retrieves a single asset for a theme by its key. To retrieve a single asset, include <code>asset[key]=#{asset_key}</code> as a request parameter. For example, to retrieve the asset with a key of <code>templates/index.liquid</code> , the request might be <code>/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid</code> . For more information on the key property, see Asset properties.
PUT	/admin/api/unstable/themes/{theme_id}/assets.json Creates or updates an asset for a theme. In the PUT request, you can include the <code>src</code> or <code>source_key</code> property to create the asset from an existing file.
DELETE	/admin/api/unstable/themes/{theme_id}/assets.json Deletes an asset from a theme.
GET	/admin/api/2020-01/blogs.json

Retrieve a list of all blogs. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/blogs.json>

Create a new blog

GET </admin/api/2020-01/blogs/count.json>

Get a count of all blogs

GET /admin/api/2020-01/blogs/{blog_id}.json

Get a single blog by its ID

PUT /admin/api/2020-01/blogs/{blog_id}.json

Update a blog

DELETE /admin/api/2020-01/blogs/{blog_id}.json

Delete a blog

GET </admin/api/2020-01/comments.json>

Retrieves a list of comments. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/comments.json>

Creates a comment for an article

GET </admin/api/2020-01/comments/count.json>

Retrieves a count of comments

GET /admin/api/2020-01/comments/{comment_id}.json

Retrieves a single comment by its ID

PUT /admin/api/2020-01/comments/{comment_id}.json

Updates a comment of an article

POST /admin/api/2020-01/comments/{comment_id}/spam.json

Marks a comment as spam

POST /admin/api/2020-01/comments/{comment_id}/not_spam.json

Marks a comment as not spam

POST /admin/api/2020-01/comments/{comment_id}/approve.json

Approves a comment

POST /admin/api/2020-01/comments/{comment_id}/remove.json

Removes a comment

POST /admin/api/2020-01/comments/{comment_id}/restore.json

Restores a previously removed comment

GET </admin/api/2020-01/redirects.json>

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/redirects.json>

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

GET </admin/api/2020-01/redirects/count.json>

Retrieves a count of URL redirects

GET /admin/api/2020-01/redirects/{redirect_id}.json

Retrieves a single redirect

PUT /admin/api/2020-01/redirects/{redirect_id}.json

Updates an existing redirect

DELETE /admin/api/2020-01/redirects/{redirect_id}.json

Deletes a redirect

GET </admin/api/2020-04/redirects.json>

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-04/redirects.json>

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

GET </admin/api/2020-04/redirects/count.json>

Retrieves a count of URL redirects

GET /admin/api/2020-04/redirects/{redirect_id}.json

Retrieves a single redirect

PUT /admin/api/2020-04/redirects/{redirect_id}.json

Updates an existing redirect

DELETE	/admin/api/2020-04/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2020-07/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-07/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2020-07/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2020-07/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2020-07/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2020-10/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-10/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2020-10/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2020-10/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2020-10/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2021-01/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2021-01/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2021-01/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2021-01/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2021-01/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/unstable/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/unstable/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/unstable/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/unstable/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/unstable/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/2020-01/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/script_tags.json

Creates a new script tag

GET /admin/api/2020-01/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-01/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-01/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-01/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2020-04/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/script_tags.json

Creates a new script tag

GET /admin/api/2020-04/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-04/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-04/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-04/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2020-07/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/script_tags.json

Creates a new script tag

GET /admin/api/2020-07/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-07/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-07/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-07/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2020-10/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/script_tags.json

Creates a new script tag

GET /admin/api/2020-10/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-10/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-10/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-10/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2021-01/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/script_tags.json

Creates a new script tag

GET /admin/api/2021-01/script_tags/count.json

Retrieves a count of all script tags

GET	/admin/api/2021-01/script_tags/{script_tag_id}.json Retrieves a single script tag
PUT	/admin/api/2021-01/script_tags/{script_tag_id}.json Updates a script tag
DELETE	/admin/api/2021-01/script_tags/{script_tag_id}.json Deletes a script tag
GET	/admin/api/unstable/script_tags.json Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/script_tags.json Creates a new script tag
GET	/admin/api/unstable/script_tags/count.json Retrieves a count of all script tags
GET	/admin/api/unstable/script_tags/{script_tag_id}.json Retrieves a single script tag
PUT	/admin/api/unstable/script_tags/{script_tag_id}.json Updates a script tag
DELETE	/admin/api/unstable/script_tags/{script_tag_id}.json Deletes a script tag
GET	/admin/api/2020-01/themes.json Retrieves a list of themes.
POST	/admin/api/2020-01/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-01/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-01/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-01/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2020-04/themes.json Retrieves a list of themes.
POST	/admin/api/2020-04/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-04/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-04/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-04/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2020-07/themes.json Retrieves a list of themes.
POST	/admin/api/2020-07/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-07/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-07/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-07/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2020-10/themes.json Retrieves a list of themes.
POST	/admin/api/2020-10/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

GET	/admin/api/2020-10/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-10/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-10/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2021-01/themes.json Retrieves a list of themes.
POST	/admin/api/2021-01/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2021-01/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2021-01/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2021-01/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/unstable/themes.json Retrieves a list of themes.
POST	/admin/api/unstable/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/unstable/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/unstable/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/unstable/themes/{theme_id}.json Deletes a theme.

online-store/article

GET	/admin/api/2020-01/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-01/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-01/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-01/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-04/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-04/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json Updates an article

DELETE	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-04/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-04/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-07/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-07/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-07/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-07/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2020-10/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2020-10/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2020-10/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2020-10/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/2021-01/blogs/{blog_id}/articles.json Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/blogs/{blog_id}/articles.json Creates an article for a blog
GET	/admin/api/2021-01/blogs/{blog_id}/articles/count.json Retrieves a count of all articles from a blog
GET	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json Retrieves a single article
PUT	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json Updates an article
DELETE	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json Deletes an article
GET	/admin/api/2021-01/articles/authors.json Retrieves a list all of article authors
GET	/admin/api/2021-01/articles/tags.json Retrieves a list of all the tags
GET	/admin/api/unstable/blogs/{blog_id}/articles.json

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/blogs/{blog_id}/articles.json

Creates an article for a blog

GET /admin/api/unstable/blogs/{blog_id}/articles/count.json

Retrieves a count of all articles from a blog

GET /admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Retrieves a single article

PUT /admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Updates an article

DELETE /admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Deletes an article

GET </admin/api/unstable/articles/authors.json>

Retrieves a list all of article authors

GET </admin/api/unstable/articles/tags.json>

Retrieves a list of all the tags

online-store/asset

GET /admin/api/2020-01/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.

PUT /admin/api/2020-01/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

DELETE /admin/api/2020-01/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET /admin/api/2020-04/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.

PUT /admin/api/2020-04/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

DELETE /admin/api/2020-04/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET /admin/api/2020-07/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.

PUT /admin/api/2020-07/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

DELETE /admin/api/2020-07/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET /admin/api/2020-10/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.

PUT /admin/api/2020-10/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

DELETE /admin/api/2020-10/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET /admin/api/2021-01/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include asset[key]=#{asset_key} as a request parameter. For example, to retrieve the asset with a key of templates/index.liquid, the request might be /admin/themes/828155753/assets.json?asset[key]=templates/index.liquid. For more information on the key property, see Asset properties.

PUT /admin/api/2021-01/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the src or source_key property to create the asset from an existing file.

DELETE /admin/api/2021-01/themes/{theme_id}/assets.json

Deletes an asset from a theme.

GET /admin/api/unstable/themes/{theme_id}/assets.json

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see Asset properties.

PUT /admin/api/unstable/themes/{theme_id}/assets.json

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

DELETE /admin/api/unstable/themes/{theme_id}/assets.json

Deletes an asset from a theme.

online-store/blog

GET </admin/api/2020-01/blogs.json>

Retrieve a list of all blogs. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/blogs.json>

Create a new blog

GET </admin/api/2020-01/blogs/count.json>

Get a count of all blogs

GET /admin/api/2020-01/blogs/{blog_id}.json

Get a single blog by its ID

PUT /admin/api/2020-01/blogs/{blog_id}.json

Update a blog

DELETE /admin/api/2020-01/blogs/{blog_id}.json

Delete a blog

online-store/comment

GET </admin/api/2020-01/comments.json>

Retrieves a list of comments. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/comments.json>

Creates a comment for an article

GET </admin/api/2020-01/comments/count.json>

Retrieves a count of comments

GET /admin/api/2020-01/comments/{comment_id}.json

Retrieves a single comment by its ID

PUT /admin/api/2020-01/comments/{comment_id}.json

Updates a comment of an article

POST /admin/api/2020-01/comments/{comment_id}/spam.json

Marks a comment as spam

POST /admin/api/2020-01/comments/{comment_id}/not_spam.json

Marks a comment as not spam

POST /admin/api/2020-01/comments/{comment_id}/approve.json

Approves a comment

POST /admin/api/2020-01/comments/{comment_id}/remove.json

Removes a comment

POST /admin/api/2020-01/comments/{comment_id}/restore.json

Restores a previously removed comment

online-store/redirect

GET </admin/api/2020-01/redirects.json>

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/redirects.json>

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

GET </admin/api/2020-01/redirects/count.json>

Retrieves a count of URL redirects

GET /admin/api/2020-01/redirects/{redirect_id}.json

Retrieves a single redirect

PUT /admin/api/2020-01/redirects/{redirect_id}.json

Updates an existing redirect

DELETE	/admin/api/2020-01/redirects/{redirect_id}.json
	Deletes a redirect
GET	/admin/api/2020-04/redirects.json
	Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/redirects.json
	Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-04/redirects/count.json
	Retrieves a count of URL redirects
GET	/admin/api/2020-04/redirects/{redirect_id}.json
	Retrieves a single redirect
PUT	/admin/api/2020-04/redirects/{redirect_id}.json
	Updates an existing redirect
DELETE	/admin/api/2020-04/redirects/{redirect_id}.json
	Deletes a redirect
GET	/admin/api/2020-07/redirects.json
	Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/redirects.json
	Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-07/redirects/count.json
	Retrieves a count of URL redirects
GET	/admin/api/2020-07/redirects/{redirect_id}.json
	Retrieves a single redirect
PUT	/admin/api/2020-07/redirects/{redirect_id}.json
	Updates an existing redirect
DELETE	/admin/api/2020-07/redirects/{redirect_id}.json
	Deletes a redirect
GET	/admin/api/2020-10/redirects.json
	Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/redirects.json
	Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2020-10/redirects/count.json
	Retrieves a count of URL redirects
GET	/admin/api/2020-10/redirects/{redirect_id}.json
	Retrieves a single redirect
PUT	/admin/api/2020-10/redirects/{redirect_id}.json
	Updates an existing redirect
DELETE	/admin/api/2020-10/redirects/{redirect_id}.json
	Deletes a redirect
GET	/admin/api/2021-01/redirects.json
	Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/redirects.json
	Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2021-01/redirects/count.json
	Retrieves a count of URL redirects
GET	/admin/api/2021-01/redirects/{redirect_id}.json
	Retrieves a single redirect
PUT	/admin/api/2021-01/redirects/{redirect_id}.json
	Updates an existing redirect
DELETE	/admin/api/2021-01/redirects/{redirect_id}.json
	Deletes a redirect
GET	/admin/api/unstable/redirects.json

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/unstable/redirects.json>

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

GET </admin/api/unstable/redirects/count.json>

Retrieves a count of URL redirects

GET /admin/api/unstable/redirects/{redirect_id}.json

Retrieves a single redirect

PUT /admin/api/unstable/redirects/{redirect_id}.json

Updates an existing redirect

DELETE /admin/api/unstable/redirects/{redirect_id}.json

Deletes a redirect

online-store/scripttag

GET /admin/api/2020-01/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/script_tags.json

Creates a new script tag

GET /admin/api/2020-01/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-01/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-01/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-01/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2020-04/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/script_tags.json

Creates a new script tag

GET /admin/api/2020-04/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-04/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-04/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-04/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2020-07/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/script_tags.json

Creates a new script tag

GET /admin/api/2020-07/script_tags/count.json

Retrieves a count of all script tags

GET /admin/api/2020-07/script_tags/{script_tag_id}.json

Retrieves a single script tag

PUT /admin/api/2020-07/script_tags/{script_tag_id}.json

Updates a script tag

DELETE /admin/api/2020-07/script_tags/{script_tag_id}.json

Deletes a script tag

GET /admin/api/2020-10/script_tags.json

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/script_tags.json

GET	/admin/api/2020-10/script_tags/count.json	Creates a new script tag
GET	/admin/api/2020-10/script_tags/{script_tag_id}.json	Retrieves a count of all script tags
PUT	/admin/api/2020-10/script_tags/{script_tag_id}.json	Retrieves a single script tag
DELETE	/admin/api/2020-10/script_tags/{script_tag_id}.json	Updates a script tag
GET	/admin/api/2021-01/script_tags.json	Deletes a script tag
POST	/admin/api/2021-01/script_tags.json	Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/script_tags/count.json	Creates a new script tag
GET	/admin/api/2021-01/script_tags/{script_tag_id}.json	Retrieves a count of all script tags
PUT	/admin/api/2021-01/script_tags/{script_tag_id}.json	Retrieves a single script tag
DELETE	/admin/api/2021-01/script_tags/{script_tag_id}.json	Updates a script tag
GET	/admin/api/unstable/script_tags.json	Deletes a script tag
POST	/admin/api/unstable/script_tags.json	Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/script_tags/count.json	Creates a new script tag
GET	/admin/api/unstable/script_tags/{script_tag_id}.json	Retrieves a count of all script tags
PUT	/admin/api/unstable/script_tags/{script_tag_id}.json	Retrieves a single script tag
DELETE	/admin/api/unstable/script_tags/{script_tag_id}.json	Updates a script tag

online-store/theme

GET	/admin/api/2020-01/themes.json	Retrieves a list of themes.
POST	/admin/api/2020-01/themes.json	Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-01/themes/{theme_id}.json	Retrieves a single theme.
PUT	/admin/api/2020-01/themes/{theme_id}.json	Updates an existing theme.
DELETE	/admin/api/2020-01/themes/{theme_id}.json	Deletes a theme.
GET	/admin/api/2020-04/themes.json	Retrieves a list of themes.
POST	/admin/api/2020-04/themes.json	Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-04/themes/{theme_id}.json	Retrieves a single theme.
PUT	/admin/api/2020-04/themes/{theme_id}.json	Updates an existing theme.
DELETE	/admin/api/2020-04/themes/{theme_id}.json	

GET	/admin/api/2020-07/themes.json Deletes a theme.
POST	/admin/api/2020-07/themes.json Retrieves a list of themes.
GET	/admin/api/2020-07/themes/{theme_id}.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
PUT	/admin/api/2020-07/themes/{theme_id}.json Retrieves a single theme.
DELETE	/admin/api/2020-07/themes/{theme_id}.json Updates an existing theme.
GET	/admin/api/2020-10/themes.json Deletes a theme.
POST	/admin/api/2020-10/themes.json Retrieves a list of themes.
GET	/admin/api/2020-10/themes/{theme_id}.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
PUT	/admin/api/2020-10/themes/{theme_id}.json Retrieves a single theme.
DELETE	/admin/api/2020-10/themes/{theme_id}.json Updates an existing theme.
GET	/admin/api/2021-01/themes.json Deletes a theme.
POST	/admin/api/2021-01/themes.json Retrieves a list of themes.
GET	/admin/api/2021-01/themes/{theme_id}.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
PUT	/admin/api/2021-01/themes/{theme_id}.json Retrieves a single theme.
DELETE	/admin/api/2021-01/themes/{theme_id}.json Updates an existing theme.
GET	/admin/api/unstable/themes.json Deletes a theme.
POST	/admin/api/unstable/themes.json Retrieves a list of themes.
GET	/admin/api/unstable/themes/{theme_id}.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
PUT	/admin/api/unstable/themes/{theme_id}.json Retrieves a single theme.
DELETE	/admin/api/unstable/themes/{theme_id}.json Updates an existing theme.
	Deletes a theme.

order

GET	/admin/api/2020-01/orders.json Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders.json Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: <code>inventory_behaviour</code> : The behaviour to use when updating inventory. (default: <code>bypass</code>) <code>bypass</code> : Do not claim inventory. <code>decrement_ignoring_policy</code> : Ignore the product's inventory policy and claim inventory. <code>decrement_obeying_policy</code> : Follow the product's inventory policy and claim inventory, if possible. <code>send_receipt</code> : Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when <code>send_receipt</code> is set to <code>false</code> , then you need to disable the Storefront API from the private app's page in the Shopify admin. <code>send_fulfillment_receipt</code> : Whether to send a shipping confirmation to the customer. Note If you are including <code>shipping_address</code> or <code>billing_address</code> , make sure to pass both <code>first_name</code> and <code>last_name</code> . Otherwise both these addresses will be

ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.

GET /admin/api/2020-01/orders/{order_id}.json

Retrieves a specific order

PUT /admin/api/2020-01/orders/{order_id}.json

Updates an order

DELETE /admin/api/2020-01/orders/{order_id}.json

Deletes an order. Orders that interact with an online gateway can't be deleted.

GET </admin/api/2020-01/orders/count.json>

Retrieves an order count

POST /admin/api/2020-01/orders/{order_id}/close.json

Closes an order

POST /admin/api/2020-01/orders/{order_id}/open.json

Re-opens a closed order

POST /admin/api/2020-01/orders/{order_id}/cancel.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.

GET </admin/api/2020-04/orders.json>

Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-04/orders.json>

Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: `inventory_behaviour`: The behaviour to use when updating inventory. (default: `bypass`) `bypass`: Do not claim inventory. `decrement_ignoring_policy`: Ignore the product's inventory policy and claim inventory. `decrement_obeying_policy`: Follow the product's inventory policy and claim inventory, if possible. `send_receipt`: Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when `send_receipt` is set to `false`, then you need to disable the Storefront API from the private app's page in the Shopify admin. `send_fulfillment_receipt`: Whether to send a shipping confirmation to the customer. Note If you are including `shipping_address` or `billing_address`, make sure to pass both `first_name` and `last_name`. Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.

GET /admin/api/2020-04/orders/{order_id}.json

Retrieves a specific order

PUT /admin/api/2020-04/orders/{order_id}.json

Updates an order

DELETE /admin/api/2020-04/orders/{order_id}.json

Deletes an order. Orders that interact with an online gateway can't be deleted.

GET </admin/api/2020-04/orders/count.json>

Retrieves an order count

POST /admin/api/2020-04/orders/{order_id}/close.json

Closes an order

POST /admin/api/2020-04/orders/{order_id}/open.json

Re-opens a closed order

POST /admin/api/2020-04/orders/{order_id}/cancel.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.

GET </admin/api/2020-07/orders.json>

Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

order-risk

GET /admin/api/2020-01/orders/{order_id}/risks.json

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/orders/{order_id}/risks.json

Creates an order risk for an order

GET /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Retrieves a single order risk by its ID

PUT /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Updates an order risk Note You cannot modify an order risk that was created by another application.

DELETE /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

GET	/admin/api/2020-04/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/risks.json	Creates an order risk for an order
GET	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
PUT	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-07/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/orders/{order_id}/risks.json	Creates an order risk for an order
GET	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
PUT	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-10/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/risks.json	Creates an order risk for an order
GET	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
PUT	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2021-01/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/orders/{order_id}/risks.json	Creates an order risk for an order
GET	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
PUT	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/unstable/orders/{order_id}/risks.json	Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/orders/{order_id}/risks.json	Creates an order risk for an order
GET	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json	Retrieves a single order risk by its ID
PUT	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json	Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json	Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

orders

[GET](#) [/admin/api/2020-01/checkouts/count.json](#)

GET	/admin/api/2020-04/checkouts/count.json Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-07/checkouts/count.json Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-10/checkouts/count.json Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2021-01/checkouts/count.json Retrieves a count of checkouts from the past 90 days
GET	/admin/api/unstable/checkouts/count.json Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-01/orders.json Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders.json Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: <code>inventory_behaviour</code> : The behaviour to use when updating inventory. (default: <code>bypass</code>) <code>bypass</code> : Do not claim inventory. <code>decrement_ignoring_policy</code> : Ignore the product's inventory policy and claim inventory. <code>decrement_obeying_policy</code> : Follow the product's inventory policy and claim inventory, if possible. <code>send_receipt</code> : Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when <code>send_receipt</code> is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. <code>send_fulfillment_receipt</code> : Whether to send a shipping confirmation to the customer. Note If you are including <code>shipping_address</code> or <code>billing_address</code> , make sure to pass both <code>first_name</code> and <code>last_name</code> . Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.
GET	/admin/api/2020-01/orders/{order_id}.json Retrieves a specific order
PUT	/admin/api/2020-01/orders/{order_id}.json Updates an order
DELETE	/admin/api/2020-01/orders/{order_id}.json Deletes an order. Orders that interact with an online gateway can't be deleted.
GET	/admin/api/2020-01/orders/count.json Retrieves an order count
POST	/admin/api/2020-01/orders/{order_id}/close.json Closes an order
POST	/admin/api/2020-01/orders/{order_id}/open.json Re-opens a closed order
POST	/admin/api/2020-01/orders/{order_id}/cancel.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.
GET	/admin/api/2020-04/orders.json Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders.json Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: <code>inventory_behaviour</code> : The behaviour to use when updating inventory. (default: <code>bypass</code>) <code>bypass</code> : Do not claim inventory. <code>decrement_ignoring_policy</code> : Ignore the product's inventory policy and claim inventory. <code>decrement_obeying_policy</code> : Follow the product's inventory policy and claim inventory, if possible. <code>send_receipt</code> : Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when <code>send_receipt</code> is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. <code>send_fulfillment_receipt</code> : Whether to send a shipping confirmation to the customer. Note If you are including <code>shipping_address</code> or <code>billing_address</code> , make sure to pass both <code>first_name</code> and <code>last_name</code> . Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.
GET	/admin/api/2020-04/orders/{order_id}.json Retrieves a specific order
PUT	/admin/api/2020-04/orders/{order_id}.json Updates an order
DELETE	/admin/api/2020-04/orders/{order_id}.json Deletes an order. Orders that interact with an online gateway can't be deleted.
GET	/admin/api/2020-04/orders/count.json Retrieves an order count
POST	/admin/api/2020-04/orders/{order_id}/close.json Closes an order

POST	/admin/api/2020-04/orders/{order_id}/open.json Re-opens a closed order
POST	/admin/api/2020-04/orders/{order_id}/cancel.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.
GET	/admin/api/2020-07/orders.json Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-04/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-07/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-10/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2021-01/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/orders/{order_id}/risks.json Creates an order risk for an order

GET	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/unstable/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-01/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-01/orders/{order_id}/refunds/{refund_id}.json Retrieves a specific refund.
POST	/admin/api/2020-01/orders/{order_id}/refunds/calculate.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind" : "refund" for the refund to be accepted.
GET	/admin/api/2020-04/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-04/orders/{order_id}/refunds/{refund_id}.json Retrieves a specific refund.
POST	/admin/api/2020-04/orders/{order_id}/refunds/calculate.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind" : "refund" for the refund to be accepted.
GET	/admin/api/2020-07/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-07/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2020-07/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2020-10/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2020-10/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2020-10/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2021-01/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2021-01/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2021-01/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/unstable/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/unstable/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/unstable/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/unstable/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

orders/abandoned-checkouts

GET	/admin/api/2020-01/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-04/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-07/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2020-10/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/2021-01/checkouts/count.json	Retrieves a count of checkouts from the past 90 days
GET	/admin/api/unstable/checkouts/count.json	Retrieves a count of checkouts from the past 90 days

orders/order

GET	/admin/api/2020-01/orders.json	Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders.json	Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: <code>inventory_behaviour</code> : The behaviour to use when updating inventory. (default: <code>bypass</code>) <code>bypass</code> : Do not claim inventory. <code>decrement_ignoring_policy</code> : Ignore the product's inventory policy and claim inventory. <code>decrement_obeying_policy</code> : Follow the product's inventory policy and claim inventory, if possible. <code>send_receipt</code> : Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when <code>send_receipt</code> is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. <code>send_fulfillment_receipt</code> : Whether to send a shipping confirmation to the customer. Note If you are including <code>shipping_address</code> or <code>billing_address</code> , make sure to pass both <code>first_name</code> and <code>last_name</code> . Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.
GET	/admin/api/2020-01/orders/{order_id}.json	Retrieves a specific order
PUT	/admin/api/2020-01/orders/{order_id}.json	Updates an order
DELETE	/admin/api/2020-01/orders/{order_id}.json	Deletes an order. Orders that interact with an online gateway can't be deleted.
GET	/admin/api/2020-01/orders/count.json	Retrieves an order count
POST	/admin/api/2020-01/orders/{order_id}/close.json	Closes an order
POST	/admin/api/2020-01/orders/{order_id}/open.json	Re-opens a closed order
POST	/admin/api/2020-01/orders/{order_id}/cancel.json	Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.
GET	/admin/api/2020-04/orders.json	Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders.json	Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request: <code>inventory_behaviour</code> : The behaviour to use when updating inventory. (default: <code>bypass</code>) <code>bypass</code> : Do not claim inventory. <code>decrement_ignoring_policy</code> : Ignore the product's inventory policy and claim inventory. <code>decrement_obeying_policy</code> : Follow the product's inventory policy and claim inventory, if possible. <code>send_receipt</code> : Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when <code>send_receipt</code> is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin. <code>send_fulfillment_receipt</code> : Whether to send a shipping confirmation to the customer. Note If you are including <code>shipping_address</code> or <code>billing_address</code> , make sure to pass both <code>first_name</code> and <code>last_name</code> . Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.
GET	/admin/api/2020-04/orders/{order_id}.json	Retrieves a specific order
PUT	/admin/api/2020-04/orders/{order_id}.json	Updates an order
DELETE	/admin/api/2020-04/orders/{order_id}.json	

GET	/admin/api/2020-04/orders/count.json Deletes an order. Orders that interact with an online gateway can't be deleted. Retrieves an order count
POST	/admin/api/2020-04/orders/{order_id}/close.json Closes an order
POST	/admin/api/2020-04/orders/{order_id}/open.json Re-opens a closed order
POST	/admin/api/2020-04/orders/{order_id}/cancel.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Cancels an order. Orders that have a fulfillment object can't be canceled.
GET	/admin/api/2020-07/orders.json Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

orders/order-risk

GET	/admin/api/2020-01/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-04/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-07/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
GET	/admin/api/2020-10/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/risks.json Creates an order risk for an order
GET	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
PUT	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
DELETE	/admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json

GET	/admin/api/2021-01/orders/{order_id}/risks.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
POST	/admin/api/2021-01/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json Creates an order risk for an order
PUT	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
DELETE	/admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
GET	/admin/api/unstable/orders/{order_id}/risks.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.
POST	/admin/api/unstable/orders/{order_id}/risks.json Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json Creates an order risk for an order
PUT	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json Retrieves a single order risk by its ID
DELETE	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json Updates an order risk Note You cannot modify an order risk that was created by another application.
	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

orders/refund

GET	/admin/api/2020-01/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-01/orders/{order_id}/refunds/{refund_id}.json Retrieves a specific refund.
POST	/admin/api/2020-01/orders/{order_id}/refunds/calculate.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.
GET	/admin/api/2020-04/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-04/orders/{order_id}/refunds/{refund_id}.json Retrieves a specific refund.
POST	/admin/api/2020-04/orders/{order_id}/refunds/calculate.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.

GET	/admin/api/2020-07/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-07/orders/{order_id}/refunds/{refund_id}.json Retrieves a specific refund.
POST	/admin/api/2020-07/orders/{order_id}/refunds/calculate.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind" : "refund" for the refund to be accepted.
GET	/admin/api/2020-10/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-10/orders/{order_id}/refunds/{refund_id}.json Retrieves a specific refund.
POST	/admin/api/2020-10/orders/{order_id}/refunds/calculate.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind" : "refund" for the refund to be accepted.
GET	/admin/api/2021-01/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2021-01/orders/{order_id}/refunds/{refund_id}.json Retrieves a specific refund.
POST	/admin/api/2021-01/orders/{order_id}/refunds/calculate.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind" : "refund" for the refund to be accepted.
GET	/admin/api/unstable/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/unstable/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/unstable/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

payment

GET </admin/api/2020-01/checkouts/{token}/payments.json>

Retrieves a list of payments on a particular checkout

POST </admin/api/2020-01/checkouts/{token}/payments.json>

Creates a payment on a checkout using the session ID returned by the card vault

GET /admin/api/2020-01/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

GET </admin/api/2020-01/checkouts/{token}/payments/count.json>

Counts the number of payments attempted on a checkout

GET </admin/api/2020-04/checkouts/{token}/payments.json>

Retrieves a list of payments on a particular checkout

POST </admin/api/2020-04/checkouts/{token}/payments.json>

Creates a payment on a checkout using the session ID returned by the card vault

GET /admin/api/2020-04/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

GET </admin/api/2020-04/checkouts/{token}/payments/count.json>

Counts the number of payments attempted on a checkout

GET </admin/api/2020-07/checkouts/{token}/payments.json>

Retrieves a list of payments on a particular checkout

POST </admin/api/2020-07/checkouts/{token}/payments.json>

Creates a payment on a checkout using the session ID returned by the card vault

GET /admin/api/2020-07/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

GET </admin/api/2020-07/checkouts/{token}/payments/count.json>

Counts the number of payments attempted on a checkout

GET </admin/api/2020-10/checkouts/{token}/payments.json>

Retrieves a list of payments on a particular checkout

POST </admin/api/2020-10/checkouts/{token}/payments.json>

Creates a payment on a checkout using the session ID returned by the card vault

GET /admin/api/2020-10/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

GET </admin/api/2020-10/checkouts/{token}/payments/count.json>

Counts the number of payments attempted on a checkout

GET </admin/api/2021-01/checkouts/{token}/payments.json>

Retrieves a list of payments on a particular checkout

POST </admin/api/2021-01/checkouts/{token}/payments.json>

Creates a payment on a checkout using the session ID returned by the card vault

GET /admin/api/2021-01/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

GET </admin/api/2021-01/checkouts/{token}/payments/count.json>

Counts the number of payments attempted on a checkout

GET </admin/api/unstable/checkouts/{token}/payments.json>

Retrieves a list of payments on a particular checkout

POST </admin/api/unstable/checkouts/{token}/payments.json>

Creates a payment on a checkout using the session ID returned by the card vault

GET /admin/api/unstable/checkouts/{token}/payments/{payment_id}.json

Retrieves the payment information for an existing payment

GET </admin/api/unstable/checkouts/{token}/payments/count.json>

Counts the number of payments attempted on a checkout

payout

GET	/admin/api/2020-01/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2020-04/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2020-07/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2020-10/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2021-01/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/unstable/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.

plus

GET	/admin/api/2020-01/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/gift_cards.json	Creates a gift card
GET	/admin/api/2020-01/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2020-01/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-01/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2020-01/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-01/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/gift_cards.json	Creates a gift card
GET	/admin/api/2020-04/gift_cards/{gift_card_id}.json	

PUT	Retrieves a single gift card by its ID /admin/api/2020-04/gift_cards/{gift_card_id}.json
	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-04/gift_cards/count.json
	Retrieves a count of gift cards
POST	/admin/api/2020-04/gift_cards/{gift_card_id}/disable.json
	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-04/gift_cards/search.json
	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/gift_cards.json
	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/gift_cards.json
	Creates a gift card
GET	/admin/api/2020-07/gift_cards/{gift_card_id}.json
	Retrieves a single gift card by its ID
PUT	/admin/api/2020-07/gift_cards/{gift_card_id}.json
	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-07/gift_cards/count.json
	Retrieves a count of gift cards
POST	/admin/api/2020-07/gift_cards/{gift_card_id}/disable.json
	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-07/gift_cards/search.json
	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/gift_cards.json
	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/gift_cards.json
	Creates a gift card
GET	/admin/api/2020-10/gift_cards/{gift_card_id}.json
	Retrieves a single gift card by its ID
PUT	/admin/api/2020-10/gift_cards/{gift_card_id}.json
	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-10/gift_cards/count.json
	Retrieves a count of gift cards
POST	/admin/api/2020-10/gift_cards/{gift_card_id}/disable.json
	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-10/gift_cards/search.json
	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/gift_cards.json
	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/gift_cards.json
	Creates a gift card
GET	/admin/api/2021-01/gift_cards/{gift_card_id}.json
	Retrieves a single gift card by its ID
PUT	/admin/api/2021-01/gift_cards/{gift_card_id}.json
	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2021-01/gift_cards/count.json

POST	Retrieves a count of gift cards /admin/api/2021-01/gift_cards/{gift_card_id}/disable.json Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2021-01/gift_cards/search.json Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/gift_cards.json Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/gift_cards.json Creates a gift card
GET	/admin/api/unstable/gift_cards/{gift_card_id}.json Retrieves a single gift card by its ID
PUT	/admin/api/unstable/gift_cards/{gift_card_id}.json Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/unstable/gift_cards/count.json Retrieves a count of gift cards
POST	/admin/api/unstable/gift_cards/{gift_card_id}/disable.json Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/unstable/gift_cards/search.json Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/users/{user_id}.json Retrieves a single user
GET	/admin/api/2020-01/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-04/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/users/{user_id}.json Retrieves a single user
GET	/admin/api/2020-04/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-07/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/users/{user_id}.json Retrieves a single user
GET	/admin/api/2020-07/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-10/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/users/{user_id}.json Retrieves a single user
GET	/admin/api/2020-10/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2021-01/users.json

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2021-01/users/{user_id}.json

Retrieves a single user

GET </admin/api/2021-01/users/current.json>

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

GET </admin/api/unstable/users.json>

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/unstable/users/{user_id}.json

Retrieves a single user

GET </admin/api/unstable/users/current.json>

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

plus/giftcard

GET /admin/api/2020-01/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/gift_cards.json

Creates a gift card

GET /admin/api/2020-01/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

PUT /admin/api/2020-01/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

GET /admin/api/2020-01/gift_cards/count.json

Retrieves a count of gift cards

POST /admin/api/2020-01/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

GET /admin/api/2020-01/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-04/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/gift_cards.json

Creates a gift card

GET /admin/api/2020-04/gift_cards/{gift_card_id}.json

Retrieves a single gift card by its ID

PUT /admin/api/2020-04/gift_cards/{gift_card_id}.json

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

GET /admin/api/2020-04/gift_cards/count.json

Retrieves a count of gift cards

POST /admin/api/2020-04/gift_cards/{gift_card_id}/disable.json

Disables a gift card. Disabling a gift card can't be undone.

GET /admin/api/2020-04/gift_cards/search.json

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-07/gift_cards.json

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/gift_cards.json

Creates a gift card

GET	/admin/api/2020-07/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2020-07/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-07/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2020-07/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-07/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/gift_cards.json	Creates a gift card
GET	/admin/api/2020-10/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2020-10/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2020-10/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2020-10/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2020-10/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/gift_cards.json	Creates a gift card
GET	/admin/api/2021-01/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/2021-01/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.
GET	/admin/api/2021-01/gift_cards/count.json	Retrieves a count of gift cards
POST	/admin/api/2021-01/gift_cards/{gift_card_id}/disable.json	Disables a gift card. Disabling a gift card can't be undone.
GET	/admin/api/2021-01/gift_cards/search.json	Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/gift_cards.json	Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/gift_cards.json	Creates a gift card
GET	/admin/api/unstable/gift_cards/{gift_card_id}.json	Retrieves a single gift card by its ID
PUT	/admin/api/unstable/gift_cards/{gift_card_id}.json	Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

- [GET](#) /admin/api/unstable/gift_cards/count.json
Retrieves a count of gift cards
- [POST](#) /admin/api/unstable/gift_cards/{gift_card_id}/disable.json
Disables a gift card. Disabling a gift card can't be undone.
- [GET](#) /admin/api/unstable/gift_cards/search.json
Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

plus/user

- [GET](#) </admin/api/2020-01/users.json>
Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/2020-01/users/{user_id}.json
Retrieves a single user
- [GET](#) </admin/api/2020-01/users/current.json>
Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
- [GET](#) </admin/api/2020-04/users.json>
Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/2020-04/users/{user_id}.json
Retrieves a single user
- [GET](#) </admin/api/2020-04/users/current.json>
Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
- [GET](#) </admin/api/2020-07/users.json>
Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/2020-07/users/{user_id}.json
Retrieves a single user
- [GET](#) </admin/api/2020-07/users/current.json>
Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
- [GET](#) </admin/api/2020-10/users.json>
Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/2020-10/users/{user_id}.json
Retrieves a single user
- [GET](#) </admin/api/2020-10/users/current.json>
Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
- [GET](#) </admin/api/2021-01/users.json>
Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/2021-01/users/{user_id}.json
Retrieves a single user
- [GET](#) </admin/api/2021-01/users/current.json>
Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
- [GET](#) </admin/api/unstable/users.json>
Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [GET](#) /admin/api/unstable/users/{user_id}.json
Retrieves a single user
- [GET](#) </admin/api/unstable/users/current.json>
Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

policy

- [GET](#) </admin/api/2020-01/policies.json>
Retrieves a list of the shop's policies
- [GET](#) </admin/api/2020-04/policies.json>
Retrieves a list of the shop's policies
- [GET](#) </admin/api/2020-07/policies.json>
Retrieves a list of the shop's policies
- [GET](#) </admin/api/2020-10/policies.json>
Retrieves a list of the shop's policies
- [GET](#) </admin/api/2021-01/policies.json>
Retrieves a list of the shop's policies
- [GET](#) </admin/api/unstable/policies.json>
Retrieves a list of the shop's policies

product

- [GET](#) </admin/api/2020-01/products.json>
Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [POST](#) </admin/api/2020-01/products.json>
Creates a new product. If you want to set the product's SEO information, then you can use the following properties:
metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag.
metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
- [GET](#) </admin/api/2020-01/products/count.json>
Retrieves a count of products.
- [GET](#) /admin/api/2020-01/products/{product_id}.json
Retrieves a single product.
- [PUT](#) /admin/api/2020-01/products/{product_id}.json
Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
- [DELETE](#) /admin/api/2020-01/products/{product_id}.json
Deletes a product.
- [GET](#) </admin/api/2020-04/products.json>
Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [POST](#) </admin/api/2020-04/products.json>
Creates a new product. If you want to set the product's SEO information, then you can use the following properties:
metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag.
metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
- [GET](#) </admin/api/2020-04/products/count.json>
Retrieves a count of products.
- [GET](#) /admin/api/2020-04/products/{product_id}.json
Retrieves a single product.
- [PUT](#) /admin/api/2020-04/products/{product_id}.json
Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
- [DELETE](#) /admin/api/2020-04/products/{product_id}.json
Deletes a product.
- [GET](#) </admin/api/2020-07/products.json>
Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- [POST](#) </admin/api/2020-07/products.json>
Creates a new product. If you want to set the product's SEO information, then you can use the following properties:
metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag.
metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
- [GET](#) </admin/api/2020-07/products/count.json>

GET	Retrieves a count of products. /admin/api/2020-07/products/{product_id}.json
PUT	Retrieves a single product. /admin/api/2020-07/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-07/products/{product_id}.json Deletes a product.
GET	/admin/api/2020-10/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-10/products/count.json Retrieves a count of products.
GET	/admin/api/2020-10/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2020-10/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-10/products/{product_id}.json Deletes a product.
GET	/admin/api/2021-01/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2021-01/products/count.json Retrieves a count of products.
GET	/admin/api/2021-01/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2021-01/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2021-01/products/{product_id}.json Deletes a product.
GET	/admin/api/unstable/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/unstable/products/count.json Retrieves a count of products.
GET	/admin/api/unstable/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/unstable/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta

name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

DELETE /admin/api/unstable/products/{product_id}.json

Deletes a product.

product-image

GET /admin/api/2020-01/products/{product_id}/images.json

Get all product images

POST /admin/api/2020-01/products/{product_id}/images.json

Create a new product image

GET /admin/api/2020-01/products/{product_id}/images/count.json

Get a count of all product images

GET /admin/api/2020-01/products/{product_id}/images/{image_id}.json

Get a single product image by id

PUT /admin/api/2020-01/products/{product_id}/images/{image_id}.json

Modify an existing product image

DELETE /admin/api/2020-01/products/{product_id}/images/{image_id}.json

GET /admin/api/2020-04/products/{product_id}/images.json

Get all product images

POST /admin/api/2020-04/products/{product_id}/images.json

Create a new product image

GET /admin/api/2020-04/products/{product_id}/images/count.json

Get a count of all product images

GET /admin/api/2020-04/products/{product_id}/images/{image_id}.json

Get a single product image by id

PUT /admin/api/2020-04/products/{product_id}/images/{image_id}.json

Modify an existing product image

DELETE /admin/api/2020-04/products/{product_id}/images/{image_id}.json

GET /admin/api/2020-07/products/{product_id}/images.json

Get all product images

POST /admin/api/2020-07/products/{product_id}/images.json

Create a new product image

GET /admin/api/2020-07/products/{product_id}/images/count.json

Get a count of all product images

GET /admin/api/2020-07/products/{product_id}/images/{image_id}.json

Get a single product image by id

PUT /admin/api/2020-07/products/{product_id}/images/{image_id}.json

Modify an existing product image

DELETE /admin/api/2020-07/products/{product_id}/images/{image_id}.json

GET /admin/api/2020-10/products/{product_id}/images.json

Get all product images

POST /admin/api/2020-10/products/{product_id}/images.json

Create a new product image

GET /admin/api/2020-10/products/{product_id}/images/count.json

Get a count of all product images

GET /admin/api/2020-10/products/{product_id}/images/{image_id}.json

Get a single product image by id

PUT /admin/api/2020-10/products/{product_id}/images/{image_id}.json

Modify an existing product image

DELETE /admin/api/2020-10/products/{product_id}/images/{image_id}.json

GET /admin/api/2021-01/products/{product_id}/images.json

Get all product images

POST /admin/api/2021-01/products/{product_id}/images.json

Create a new product image

GET /admin/api/2021-01/products/{product_id}/images/count.json

Get a count of all product images

GET /admin/api/2021-01/products/{product_id}/images/{image_id}.json

Get a single product image by id

PUT /admin/api/2021-01/products/{product_id}/images/{image_id}.json

Modify an existing product image

DELETE /admin/api/2021-01/products/{product_id}/images/{image_id}.json

GET /admin/api/unstable/products/{product_id}/images.json
Get all product images

POST /admin/api/unstable/products/{product_id}/images.json
Create a new product image

GET /admin/api/unstable/products/{product_id}/images/count.json
Get a count of all product images

GET /admin/api/unstable/products/{product_id}/images/{image_id}.json
Get a single product image by id

PUT /admin/api/unstable/products/{product_id}/images/{image_id}.json
Modify an existing product image

DELETE /admin/api/unstable/products/{product_id}/images/{image_id}.json

productlisting

GET /admin/api/2020-01/product_listings.json
Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-01/product_listings/product_ids.json
Retrieve product_ids that are published to your app. Maximum 1,000 results per page.

GET /admin/api/2020-01/product_listings/count.json
Retrieve a count of products that are published to your app

GET /admin/api/2020-01/product_listings/{product_listing_id}.json
Retrieve a specific product listing that is published to your app

PUT /admin/api/2020-01/product_listings/{product_listing_id}.json
Create a product listing to publish a product to your app

DELETE /admin/api/2020-01/product_listings/{product_listing_id}.json
Delete a product listing to unpublish a product from your app

GET /admin/api/2020-04/product_listings.json
Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-04/product_listings/product_ids.json
Retrieve product_ids that are published to your app. Maximum 1,000 results per page.

GET /admin/api/2020-04/product_listings/count.json
Retrieve a count of products that are published to your app

GET /admin/api/2020-04/product_listings/{product_listing_id}.json
Retrieve a specific product listing that is published to your app

PUT /admin/api/2020-04/product_listings/{product_listing_id}.json
Create a product listing to publish a product to your app

DELETE /admin/api/2020-04/product_listings/{product_listing_id}.json
Delete a product listing to unpublish a product from your app

GET /admin/api/2020-07/product_listings.json
Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-07/product_listings/product_ids.json
Retrieve product_ids that are published to your app. Maximum 1,000 results per page.

GET /admin/api/2020-07/product_listings/count.json
Retrieve a count of products that are published to your app

GET /admin/api/2020-07/product_listings/{product_listing_id}.json
Retrieve a specific product listing that is published to your app

PUT /admin/api/2020-07/product_listings/{product_listing_id}.json
Create a product listing to publish a product to your app

DELETE /admin/api/2020-07/product_listings/{product_listing_id}.json
Delete a product listing to unpublish a product from your app

products

GET </admin/api/2020-01/collects.json>
Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST	/admin/api/2020-01/collects.json	Adds a product to a custom collection.
GET	/admin/api/2020-01/collects/{collect_id}.json	Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-01/collects/{collect_id}.json	Removes a product from a collection.
GET	/admin/api/2020-01/collects/count.json	Retrieves a count of collects.
GET	/admin/api/2020-04/collects.json	Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/collects.json	Adds a product to a custom collection.
GET	/admin/api/2020-04/collects/{collect_id}.json	Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-04/collects/{collect_id}.json	Removes a product from a collection.
GET	/admin/api/2020-04/collects/count.json	Retrieves a count of collects.
GET	/admin/api/2020-07/collects.json	Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/collects.json	Adds a product to a custom collection.
GET	/admin/api/2020-07/collects/{collect_id}.json	Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-07/collects/{collect_id}.json	Removes a product from a collection.
GET	/admin/api/2020-07/collects/count.json	Retrieves a count of collects.
GET	/admin/api/2020-10/collects.json	Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/collects.json	Adds a product to a custom collection.
GET	/admin/api/2020-10/collects/{collect_id}.json	Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-10/collects/{collect_id}.json	Removes a product from a collection.
GET	/admin/api/2020-10/collects/count.json	Retrieves a count of collects.
GET	/admin/api/2021-01/collects.json	Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/collects.json	Adds a product to a custom collection.
GET	/admin/api/2021-01/collects/{collect_id}.json	Retrieves a specific collect by its ID.
DELETE	/admin/api/2021-01/collects/{collect_id}.json	Removes a product from a collection.
GET	/admin/api/2021-01/collects/count.json	Retrieves a count of collects.
GET	/admin/api/unstable/collects.json	Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/collects.json	Adds a product to a custom collection.

GET	/admin/api/unstable/collects/{collect_id}.json Retrieves a specific collect by its ID.
DELETE	/admin/api/unstable/collects/{collect_id}.json Removes a product from a collection.
GET	/admin/api/unstable/collects/count.json Retrieves a count of collects.
GET	/admin/api/2020-01/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2020-01/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-04/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2020-04/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-07/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2020-07/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-10/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2020-10/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2021-01/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/2021-01/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/unstable/collections/{collection_id}.json Retrieves a single collection
GET	/admin/api/unstable/collections/{collection_id}/products.json Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.
GET	/admin/api/2020-01/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/custom_collections.json Creates a custom collection
GET	/admin/api/2020-01/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-01/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-01/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-01/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2020-04/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/custom_collections.json Creates a custom collection
GET	/admin/api/2020-04/custom_collections/count.json Retrieves a count of custom collections

GET	/admin/api/2020-04/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-04/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-04/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2020-07/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/custom_collections.json Creates a custom collection
GET	/admin/api/2020-07/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-07/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-07/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-07/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2020-10/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/custom_collections.json Creates a custom collection
GET	/admin/api/2020-10/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2021-01/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/custom_collections.json Creates a custom collection
GET	/admin/api/2021-01/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/unstable/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/custom_collections.json Creates a custom collection
GET	/admin/api/unstable/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/unstable/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/unstable/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/unstable/custom_collections/{custom_collection_id}.json Deletes a custom collection

GET	/admin/api/2020-01/products.json	Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/products.json	Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-01/products/count.json	Retrieves a count of products.
GET	/admin/api/2020-01/products/{product_id}.json	Retrieves a single product.
PUT	/admin/api/2020-01/products/{product_id}.json	Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-01/products/{product_id}.json	Deletes a product.
GET	/admin/api/2020-04/products.json	Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/products.json	Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-04/products/count.json	Retrieves a count of products.
GET	/admin/api/2020-04/products/{product_id}.json	Retrieves a single product.
PUT	/admin/api/2020-04/products/{product_id}.json	Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-04/products/{product_id}.json	Deletes a product.
GET	/admin/api/2020-07/products.json	Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/products.json	Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-07/products/count.json	Retrieves a count of products.
GET	/admin/api/2020-07/products/{product_id}.json	Retrieves a single product.
PUT	/admin/api/2020-07/products/{product_id}.json	Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-07/products/{product_id}.json	Deletes a product.
GET	/admin/api/2020-10/products.json	Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/products.json	Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag.

metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

GET </admin/api/2020-10/products/count.json>

Retrieves a count of products.

GET /admin/api/2020-10/products/{product_id}.json

Retrieves a single product.

PUT /admin/api/2020-10/products/{product_id}.json

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

DELETE /admin/api/2020-10/products/{product_id}.json

Deletes a product.

GET </admin/api/2021-01/products.json>

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2021-01/products.json>

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

GET </admin/api/2021-01/products/count.json>

Retrieves a count of products.

GET /admin/api/2021-01/products/{product_id}.json

Retrieves a single product.

PUT /admin/api/2021-01/products/{product_id}.json

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

DELETE /admin/api/2021-01/products/{product_id}.json

Deletes a product.

GET </admin/api/unstable/products.json>

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/unstable/products.json>

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

GET </admin/api/unstable/products/count.json>

Retrieves a count of products.

GET /admin/api/unstable/products/{product_id}.json

Retrieves a single product.

PUT /admin/api/unstable/products/{product_id}.json

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

DELETE /admin/api/unstable/products/{product_id}.json

Deletes a product.

GET /admin/api/2020-01/products/{product_id}/images.json

Get all product images

POST /admin/api/2020-01/products/{product_id}/images.json

Create a new product image

GET /admin/api/2020-01/products/{product_id}/images/count.json

Get a count of all product images

GET /admin/api/2020-01/products/{product_id}/images/{image_id}.json

Get a single product image by id

PUT /admin/api/2020-01/products/{product_id}/images/{image_id}.json

Modify an existing product image

DELETE /admin/api/2020-01/products/{product_id}/images/{image_id}.json

GET /admin/api/2020-04/products/{product_id}/images.json

POST	/admin/api/2020-04/products/{product_id}/images.json Get all product images
GET	/admin/api/2020-04/products/{product_id}/images/count.json Create a new product image
GET	/admin/api/2020-04/products/{product_id}/images/{image_id}.json Get a count of all product images
PUT	/admin/api/2020-04/products/{product_id}/images/{image_id}.json Get a single product image by id
DELETE	/admin/api/2020-04/products/{product_id}/images/{image_id}.json Modify an existing product image
GET	/admin/api/2020-07/products/{product_id}/images.json Get all product images
POST	/admin/api/2020-07/products/{product_id}/images.json Create a new product image
GET	/admin/api/2020-07/products/{product_id}/images/count.json Get a count of all product images
GET	/admin/api/2020-07/products/{product_id}/images/{image_id}.json Get a single product image by id
PUT	/admin/api/2020-07/products/{product_id}/images/{image_id}.json Modify an existing product image
DELETE	/admin/api/2020-07/products/{product_id}/images/{image_id}.json
GET	/admin/api/2020-10/products/{product_id}/images.json Get all product images
POST	/admin/api/2020-10/products/{product_id}/images.json Create a new product image
GET	/admin/api/2020-10/products/{product_id}/images/count.json Get a count of all product images
GET	/admin/api/2020-10/products/{product_id}/images/{image_id}.json Get a single product image by id
PUT	/admin/api/2020-10/products/{product_id}/images/{image_id}.json Modify an existing product image
DELETE	/admin/api/2020-10/products/{product_id}/images/{image_id}.json
GET	/admin/api/2021-01/products/{product_id}/images.json Get all product images
POST	/admin/api/2021-01/products/{product_id}/images.json Create a new product image
GET	/admin/api/2021-01/products/{product_id}/images/count.json Get a count of all product images
GET	/admin/api/2021-01/products/{product_id}/images/{image_id}.json Get a single product image by id
PUT	/admin/api/2021-01/products/{product_id}/images/{image_id}.json Modify an existing product image
DELETE	/admin/api/2021-01/products/{product_id}/images/{image_id}.json
GET	/admin/api/unstable/products/{product_id}/images.json Get all product images
POST	/admin/api/unstable/products/{product_id}/images.json Create a new product image
GET	/admin/api/unstable/products/{product_id}/images/count.json Get a count of all product images
GET	/admin/api/unstable/products/{product_id}/images/{image_id}.json Get a single product image by id
PUT	/admin/api/unstable/products/{product_id}/images/{image_id}.json Modify an existing product image
DELETE	/admin/api/unstable/products/{product_id}/images/{image_id}.json
GET	/admin/api/2020-01/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/2020-01/smart_collections/count.json

GET	/admin/api/2020-01/smart_collections/{smart_collection_id}.json	Retrieves a count of smart collections
PUT	/admin/api/2020-01/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
DELETE	/admin/api/2020-01/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
PUT	/admin/api/2020-01/smart_collections/{smart_collection_id}/order.json	Removes a smart collection
GET	/admin/api/2020-04/smart_collections.json	Updates the ordering type of products in a smart collection
POST	/admin/api/2020-04/smart_collections.json	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/smart_collections/count.json	Creates a new smart collection using the specified rules.
GET	/admin/api/2020-04/smart_collections/{smart_collection_id}.json	Retrieves a count of smart collections
PUT	/admin/api/2020-04/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
DELETE	/admin/api/2020-04/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
PUT	/admin/api/2020-04/smart_collections/{smart_collection_id}/order.json	Removes a smart collection
GET	/admin/api/2020-07/smart_collections.json	Updates the ordering type of products in a smart collection
POST	/admin/api/2020-07/smart_collections.json	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/smart_collections/count.json	Creates a new smart collection using the specified rules.
GET	/admin/api/2020-07/smart_collections/{smart_collection_id}.json	Retrieves a count of smart collections
PUT	/admin/api/2020-07/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
DELETE	/admin/api/2020-07/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
PUT	/admin/api/2020-07/smart_collections/{smart_collection_id}/order.json	Removes a smart collection
GET	/admin/api/2020-10/smart_collections.json	Updates the ordering type of products in a smart collection
POST	/admin/api/2020-10/smart_collections.json	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/smart_collections/count.json	Creates a new smart collection using the specified rules.
GET	/admin/api/2020-10/smart_collections/{smart_collection_id}.json	Retrieves a count of smart collections
PUT	/admin/api/2020-10/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
DELETE	/admin/api/2020-10/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
PUT	/admin/api/2020-10/smart_collections/{smart_collection_id}/order.json	Removes a smart collection
GET	/admin/api/2021-01/smart_collections.json	Updates the ordering type of products in a smart collection
POST	/admin/api/2021-01/smart_collections.json	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/smart_collections/count.json	Creates a new smart collection using the specified rules.
		Retrieves a count of smart collections

GET	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/2021-01/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection
GET	/admin/api/unstable/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/unstable/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/unstable/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/unstable/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/unstable/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/unstable/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection

products/collect

GET	/admin/api/2020-01/collects.json Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/collects.json Adds a product to a custom collection.
GET	/admin/api/2020-01/collects/{collect_id}.json Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-01/collects/{collect_id}.json Removes a product from a collection.
GET	/admin/api/2020-01/collects/count.json Retrieves a count of collects.
GET	/admin/api/2020-04/collects.json Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/collects.json Adds a product to a custom collection.
GET	/admin/api/2020-04/collects/{collect_id}.json Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-04/collects/{collect_id}.json Removes a product from a collection.
GET	/admin/api/2020-04/collects/count.json Retrieves a count of collects.
GET	/admin/api/2020-07/collects.json Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/collects.json Adds a product to a custom collection.
GET	/admin/api/2020-07/collects/{collect_id}.json Retrieves a specific collect by its ID.
DELETE	/admin/api/2020-07/collects/{collect_id}.json Removes a product from a collection.
GET	/admin/api/2020-07/collects/count.json Retrieves a count of collects.
GET	/admin/api/2020-10/collects.json

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-10/collects.json>

Adds a product to a custom collection.

GET /admin/api/2020-10/collects/{collect_id}.json

Retrieves a specific collect by its ID.

DELETE /admin/api/2020-10/collects/{collect_id}.json

Removes a product from a collection.

GET </admin/api/2020-10/collects/count.json>

Retrieves a count of collects.

GET </admin/api/2021-01/collects.json>

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2021-01/collects.json>

Adds a product to a custom collection.

GET /admin/api/2021-01/collects/{collect_id}.json

Retrieves a specific collect by its ID.

DELETE /admin/api/2021-01/collects/{collect_id}.json

Removes a product from a collection.

GET </admin/api/2021-01/collects/count.json>

Retrieves a count of collects.

GET </admin/api/unstable/collects.json>

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/unstable/collects.json>

Adds a product to a custom collection.

GET /admin/api/unstable/collects/{collect_id}.json

Retrieves a specific collect by its ID.

DELETE /admin/api/unstable/collects/{collect_id}.json

Removes a product from a collection.

GET </admin/api/unstable/collects/count.json>

Retrieves a count of collects.

products/collection

GET /admin/api/2020-01/collections/{collection_id}.json

Retrieves a single collection

GET /admin/api/2020-01/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

GET /admin/api/2020-04/collections/{collection_id}.json

Retrieves a single collection

GET /admin/api/2020-04/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

GET /admin/api/2020-07/collections/{collection_id}.json

Retrieves a single collection

GET /admin/api/2020-07/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

GET /admin/api/2020-10/collections/{collection_id}.json

Retrieves a single collection

GET /admin/api/2020-10/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

GET /admin/api/2021-01/collections/{collection_id}.json

Retrieves a single collection

GET /admin/api/2021-01/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

GET /admin/api/unstable/collections/{collection_id}.json

Retrieves a single collection

GET /admin/api/unstable/collections/{collection_id}/products.json

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

products/customcollection

GET /admin/api/2020-01/custom_collections.json

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/custom_collections.json

Creates a custom collection

GET /admin/api/2020-01/custom_collections/count.json

Retrieves a count of custom collections

GET /admin/api/2020-01/custom_collections/{custom_collection_id}.json

Retrieves a single custom collection

PUT /admin/api/2020-01/custom_collections/{custom_collection_id}.json

Updates an existing custom collection

DELETE /admin/api/2020-01/custom_collections/{custom_collection_id}.json

Deletes a custom collection

GET /admin/api/2020-04/custom_collections.json

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/custom_collections.json

Creates a custom collection

GET /admin/api/2020-04/custom_collections/count.json

Retrieves a count of custom collections

GET /admin/api/2020-04/custom_collections/{custom_collection_id}.json

Retrieves a single custom collection

PUT /admin/api/2020-04/custom_collections/{custom_collection_id}.json

Updates an existing custom collection

DELETE /admin/api/2020-04/custom_collections/{custom_collection_id}.json

Deletes a custom collection

GET /admin/api/2020-07/custom_collections.json

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/custom_collections.json

Creates a custom collection

GET /admin/api/2020-07/custom_collections/count.json

Retrieves a count of custom collections

GET /admin/api/2020-07/custom_collections/{custom_collection_id}.json

Retrieves a single custom collection

PUT /admin/api/2020-07/custom_collections/{custom_collection_id}.json

Updates an existing custom collection

DELETE /admin/api/2020-07/custom_collections/{custom_collection_id}.json

Deletes a custom collection

GET /admin/api/2020-10/custom_collections.json

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/custom_collections.json

Creates a custom collection

GET /admin/api/2020-10/custom_collections/count.json

Retrieves a count of custom collections

GET /admin/api/2020-10/custom_collections/{custom_collection_id}.json

Retrieves a single custom collection

PUT	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2020-10/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/2021-01/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/custom_collections.json Creates a custom collection
GET	/admin/api/2021-01/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/2021-01/custom_collections/{custom_collection_id}.json Deletes a custom collection
GET	/admin/api/unstable/custom_collections.json Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/custom_collections.json Creates a custom collection
GET	/admin/api/unstable/custom_collections/count.json Retrieves a count of custom collections
GET	/admin/api/unstable/custom_collections/{custom_collection_id}.json Retrieves a single custom collection
PUT	/admin/api/unstable/custom_collections/{custom_collection_id}.json Updates an existing custom collection
DELETE	/admin/api/unstable/custom_collections/{custom_collection_id}.json Deletes a custom collection

products/product

GET	/admin/api/2020-01/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-01/products/count.json Retrieves a count of products.
GET	/admin/api/2020-01/products/{product_id}.json Retrieves a single product.
PUT	/admin/api/2020-01/products/{product_id}.json Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-01/products/{product_id}.json Deletes a product.
GET	/admin/api/2020-04/products.json Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/products.json Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-04/products/count.json

GET	/admin/api/2020-04/products/{product_id}.json	Retrieves a count of products.
PUT	/admin/api/2020-04/products/{product_id}.json	Retrieves a single product.
DELETE	/admin/api/2020-04/products/{product_id}.json	Deletes a product.
GET	/admin/api/2020-07/products.json	Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/products.json	Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-07/products/count.json	Retrieves a count of products.
GET	/admin/api/2020-07/products/{product_id}.json	Retrieves a single product.
PUT	/admin/api/2020-07/products/{product_id}.json	Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-07/products/{product_id}.json	Deletes a product.
GET	/admin/api/2020-10/products.json	Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/products.json	Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2020-10/products/count.json	Retrieves a count of products.
GET	/admin/api/2020-10/products/{product_id}.json	Retrieves a single product.
PUT	/admin/api/2020-10/products/{product_id}.json	Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
DELETE	/admin/api/2020-10/products/{product_id}.json	Deletes a product.
GET	/admin/api/2021-01/products.json	Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/products.json	Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.
GET	/admin/api/2021-01/products/count.json	Retrieves a count of products.
GET	/admin/api/2021-01/products/{product_id}.json	Retrieves a single product.
PUT	/admin/api/2021-01/products/{product_id}.json	Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta

name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

DELETE /admin/api/2021-01/products/{product_id}.json

Deletes a product.

GET </admin/api/unstable/products.json>

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/unstable/products.json>

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

GET </admin/api/unstable/products/count.json>

Retrieves a count of products.

GET /admin/api/unstable/products/{product_id}.json

Retrieves a single product.

PUT /admin/api/unstable/products/{product_id}.json

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

DELETE /admin/api/unstable/products/{product_id}.json

Deletes a product.

products/product-image

GET /admin/api/2020-01/products/{product_id}/images.json

Get all product images

POST /admin/api/2020-01/products/{product_id}/images.json

Create a new product image

GET /admin/api/2020-01/products/{product_id}/images/count.json

Get a count of all product images

GET /admin/api/2020-01/products/{product_id}/images/{image_id}.json

Get a single product image by id

PUT /admin/api/2020-01/products/{product_id}/images/{image_id}.json

Modify an existing product image

DELETE /admin/api/2020-01/products/{product_id}/images/{image_id}.json

GET /admin/api/2020-04/products/{product_id}/images.json

Get all product images

POST /admin/api/2020-04/products/{product_id}/images.json

Create a new product image

GET /admin/api/2020-04/products/{product_id}/images/count.json

Get a count of all product images

GET /admin/api/2020-04/products/{product_id}/images/{image_id}.json

Get a single product image by id

PUT /admin/api/2020-04/products/{product_id}/images/{image_id}.json

Modify an existing product image

DELETE /admin/api/2020-04/products/{product_id}/images/{image_id}.json

GET /admin/api/2020-07/products/{product_id}/images.json

Get all product images

POST /admin/api/2020-07/products/{product_id}/images.json

Create a new product image

GET /admin/api/2020-07/products/{product_id}/images/count.json

Get a count of all product images

GET /admin/api/2020-07/products/{product_id}/images/{image_id}.json

Get a single product image by id

PUT /admin/api/2020-07/products/{product_id}/images/{image_id}.json

Modify an existing product image

DELETE /admin/api/2020-07/products/{product_id}/images/{image_id}.json

GET /admin/api/2020-10/products/{product_id}/images.json

Get all product images

POST /admin/api/2020-10/products/{product_id}/images.json

GET	/admin/api/2020-10/products/{product_id}/images/count.json	Create a new product image Get a count of all product images
GET	/admin/api/2020-10/products/{product_id}/images/{image_id}.json	Get a single product image by id
PUT	/admin/api/2020-10/products/{product_id}/images/{image_id}.json	Modify an existing product image
DELETE	/admin/api/2020-10/products/{product_id}/images/{image_id}.json	
GET	/admin/api/2021-01/products/{product_id}/images.json	Get all product images
POST	/admin/api/2021-01/products/{product_id}/images.json	Create a new product image
GET	/admin/api/2021-01/products/{product_id}/images/count.json	Get a count of all product images
GET	/admin/api/2021-01/products/{product_id}/images/{image_id}.json	Get a single product image by id
PUT	/admin/api/2021-01/products/{product_id}/images/{image_id}.json	Modify an existing product image
DELETE	/admin/api/2021-01/products/{product_id}/images/{image_id}.json	
GET	/admin/api/unstable/products/{product_id}/images.json	Get all product images
POST	/admin/api/unstable/products/{product_id}/images.json	Create a new product image
GET	/admin/api/unstable/products/{product_id}/images/count.json	Get a count of all product images
GET	/admin/api/unstable/products/{product_id}/images/{image_id}.json	Get a single product image by id
PUT	/admin/api/unstable/products/{product_id}/images/{image_id}.json	Modify an existing product image
DELETE	/admin/api/unstable/products/{product_id}/images/{image_id}.json	

products/smartcollection

GET	/admin/api/2020-01/smart_collections.json	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/smart_collections.json	Creates a new smart collection using the specified rules.
GET	/admin/api/2020-01/smart_collections/count.json	Retrieves a count of smart collections
GET	/admin/api/2020-01/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
PUT	/admin/api/2020-01/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
DELETE	/admin/api/2020-01/smart_collections/{smart_collection_id}.json	Removes a smart collection
PUT	/admin/api/2020-01/smart_collections/{smart_collection_id}/order.json	Updates the ordering type of products in a smart collection
GET	/admin/api/2020-04/smart_collections.json	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/smart_collections.json	Creates a new smart collection using the specified rules.
GET	/admin/api/2020-04/smart_collections/count.json	Retrieves a count of smart collections
GET	/admin/api/2020-04/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
PUT	/admin/api/2020-04/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
DELETE	/admin/api/2020-04/smart_collections/{smart_collection_id}.json	Removes a smart collection
PUT	/admin/api/2020-04/smart_collections/{smart_collection_id}/order.json	

GET	/admin/api/2020-07/smart_collections.json	Updates the ordering type of products in a smart collection
		Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/smart_collections.json	Creates a new smart collection using the specified rules.
GET	/admin/api/2020-07/smart_collections/count.json	Retrieves a count of smart collections
GET	/admin/api/2020-07/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
PUT	/admin/api/2020-07/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
DELETE	/admin/api/2020-07/smart_collections/{smart_collection_id}.json	Removes a smart collection
PUT	/admin/api/2020-07/smart_collections/{smart_collection_id}/order.json	Updates the ordering type of products in a smart collection
GET	/admin/api/2020-10/smart_collections.json	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/smart_collections.json	Creates a new smart collection using the specified rules.
GET	/admin/api/2020-10/smart_collections/count.json	Retrieves a count of smart collections
GET	/admin/api/2020-10/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
PUT	/admin/api/2020-10/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
DELETE	/admin/api/2020-10/smart_collections/{smart_collection_id}.json	Removes a smart collection
PUT	/admin/api/2020-10/smart_collections/{smart_collection_id}/order.json	Updates the ordering type of products in a smart collection
GET	/admin/api/2021-01/smart_collections.json	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/smart_collections.json	Creates a new smart collection using the specified rules.
GET	/admin/api/2021-01/smart_collections/count.json	Retrieves a count of smart collections
GET	/admin/api/2021-01/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
PUT	/admin/api/2021-01/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
DELETE	/admin/api/2021-01/smart_collections/{smart_collection_id}.json	Removes a smart collection
PUT	/admin/api/2021-01/smart_collections/{smart_collection_id}/order.json	Updates the ordering type of products in a smart collection
GET	/admin/api/unstable/smart_collections.json	Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/smart_collections.json	Creates a new smart collection using the specified rules.
GET	/admin/api/unstable/smart_collections/count.json	Retrieves a count of smart collections
GET	/admin/api/unstable/smart_collections/{smart_collection_id}.json	Retrieves a single smart collection
PUT	/admin/api/unstable/smart_collections/{smart_collection_id}.json	Updates an existing smart collection
DELETE	/admin/api/unstable/smart_collections/{smart_collection_id}.json	Removes a smart collection
PUT	/admin/api/unstable/smart_collections/{smart_collection_id}/order.json	Updates the ordering type of products in a smart collection

province

GET	/admin/api/2020-01/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2020-01/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-04/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2020-04/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-07/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2020-07/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2020-10/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2020-10/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2021-01/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2021-01/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/unstable/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/unstable/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/unstable/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/unstable/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

recurringapplicationcharge

GET	/admin/api/2020-01/recurring_application_charges.json	Retrieves a list of recurring application charges
POST	/admin/api/2020-01/recurring_application_charges.json	Creates a recurring application charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json	Retrieves a single charge
DELETE	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json	Cancels a recurring application charge
POST	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/activate.json	

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

PUT /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

GET /admin/api/2020-04/recurring_application_charges.json

Retrieves a list of recurring application charges

POST /admin/api/2020-04/recurring_application_charges.json

Creates a recurring application charge

GET /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

DELETE /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

POST /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

PUT /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

GET /admin/api/2020-07/recurring_application_charges.json

Retrieves a list of recurring application charges

POST /admin/api/2020-07/recurring_application_charges.json

Creates a recurring application charge

GET /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

DELETE /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

POST /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

PUT /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

GET /admin/api/2020-10/recurring_application_charges.json

Retrieves a list of recurring application charges

POST /admin/api/2020-10/recurring_application_charges.json

Creates a recurring application charge

GET /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

DELETE /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

POST /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/activate.json

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

PUT /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

GET /admin/api/2021-01/recurring_application_charges.json

Retrieves a list of recurring application charges

POST /admin/api/2021-01/recurring_application_charges.json

Creates a recurring application charge

GET /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

DELETE /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

PUT /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/customize.json

Updates the capped amount of an active recurring application charge

GET /admin/api/unstable/recurring_application_charges.json

Retrieves a list of recurring application charges

POST /admin/api/unstable/recurring_application_charges.json

Creates a recurring application charge

GET /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json

Retrieves a single charge

DELETE /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json

Cancels a recurring application charge

PUT /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/customize.json
Updates the capped amount of an active recurring application charge

redirect

GET </admin/api/2020-01/redirects.json>
Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-01/redirects.json>
Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

GET </admin/api/2020-01/redirects/count.json>
Retrieves a count of URL redirects

GET /admin/api/2020-01/redirects/{redirect_id}.json
Retrieves a single redirect

PUT /admin/api/2020-01/redirects/{redirect_id}.json
Updates an existing redirect

DELETE /admin/api/2020-01/redirects/{redirect_id}.json
Deletes a redirect

GET </admin/api/2020-04/redirects.json>
Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-04/redirects.json>
Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

GET </admin/api/2020-04/redirects/count.json>
Retrieves a count of URL redirects

GET /admin/api/2020-04/redirects/{redirect_id}.json
Retrieves a single redirect

PUT /admin/api/2020-04/redirects/{redirect_id}.json
Updates an existing redirect

DELETE /admin/api/2020-04/redirects/{redirect_id}.json
Deletes a redirect

GET </admin/api/2020-07/redirects.json>
Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-07/redirects.json>
Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

GET </admin/api/2020-07/redirects/count.json>
Retrieves a count of URL redirects

GET /admin/api/2020-07/redirects/{redirect_id}.json
Retrieves a single redirect

PUT /admin/api/2020-07/redirects/{redirect_id}.json
Updates an existing redirect

DELETE /admin/api/2020-07/redirects/{redirect_id}.json
Deletes a redirect

GET </admin/api/2020-10/redirects.json>
Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-10/redirects.json>
Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

GET </admin/api/2020-10/redirects/count.json>
Retrieves a count of URL redirects

GET /admin/api/2020-10/redirects/{redirect_id}.json
Retrieves a single redirect

PUT /admin/api/2020-10/redirects/{redirect_id}.json
Updates an existing redirect

DELETE /admin/api/2020-10/redirects/{redirect_id}.json

GET	/admin/api/2021-01/redirects.json Deletes a redirect Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/2021-01/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/2021-01/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/2021-01/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/2021-01/redirects/{redirect_id}.json Deletes a redirect
GET	/admin/api/unstable/redirects.json Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/redirects.json Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".
GET	/admin/api/unstable/redirects/count.json Retrieves a count of URL redirects
GET	/admin/api/unstable/redirects/{redirect_id}.json Retrieves a single redirect
PUT	/admin/api/unstable/redirects/{redirect_id}.json Updates an existing redirect
DELETE	/admin/api/unstable/redirects/{redirect_id}.json Deletes a redirect

refund

GET	/admin/api/2020-01/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-01/orders/{order_id}/refunds/{refund_id}.json Retrieves a specific refund.
POST	/admin/api/2020-01/orders/{order_id}/refunds/calculate.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind": "refund" for the refund to be accepted.
GET	/admin/api/2020-04/orders/{order_id}/refunds.json Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/refunds.json Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
GET	/admin/api/2020-04/orders/{order_id}/refunds/{refund_id}.json Retrieves a specific refund.
POST	/admin/api/2020-04/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2020-07/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2020-07/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2020-07/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2020-10/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-10/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2020-10/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2020-10/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/2021-01/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2021-01/orders/{order_id}/refunds.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

GET /admin/api/2021-01/orders/{order_id}/refunds/{refund_id}.json

Retrieves a specific refund.

POST /admin/api/2021-01/orders/{order_id}/refunds/calculate.json

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must be changed to "kind": "refund" for the refund to be accepted.

GET /admin/api/unstable/orders/{order_id}/refunds.json

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

- POST** /admin/api/unstable/orders/{order_id}/refunds.json
 Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.
- GET** /admin/api/unstable/orders/{order_id}/refunds/{refund_id}.json
 Retrieves a specific refund.
- POST** /admin/api/unstable/orders/{order_id}/refunds/calculate.json
 Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind": "refund" for the refund to be accepted.

report

- GET** </admin/api/2020-01/reports.json>
 Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- POST** </admin/api/2020-01/reports.json>
 Creates a new report
- GET** /admin/api/2020-01/reports/{report_id}.json
 Retrieves a single report created by your app
- PUT** /admin/api/2020-01/reports/{report_id}.json
 Updates a report
- DELETE** /admin/api/2020-01/reports/{report_id}.json
 Deletes a report
- GET** </admin/api/2020-04/reports.json>
 Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- POST** </admin/api/2020-04/reports.json>
 Creates a new report
- GET** /admin/api/2020-04/reports/{report_id}.json
 Retrieves a single report created by your app
- PUT** /admin/api/2020-04/reports/{report_id}.json
 Updates a report
- DELETE** /admin/api/2020-04/reports/{report_id}.json
 Deletes a report
- GET** </admin/api/2020-07/reports.json>
 Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- POST** </admin/api/2020-07/reports.json>
 Creates a new report
- GET** /admin/api/2020-07/reports/{report_id}.json
 Retrieves a single report created by your app
- PUT** /admin/api/2020-07/reports/{report_id}.json
 Updates a report
- DELETE** /admin/api/2020-07/reports/{report_id}.json
 Deletes a report
- GET** </admin/api/2020-10/reports.json>
 Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
- POST** </admin/api/2020-10/reports.json>
 Creates a new report
- GET** /admin/api/2020-10/reports/{report_id}.json
 Retrieves a single report created by your app
- PUT** /admin/api/2020-10/reports/{report_id}.json
 Updates a report
- DELETE** /admin/api/2020-10/reports/{report_id}.json

GET	/admin/api/2021-01/reports.json Deletes a report
POST	/admin/api/2021-01/reports.json Creates a new report
GET	/admin/api/2021-01/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/2021-01/reports/{report_id}.json Updates a report
DELETE	/admin/api/2021-01/reports/{report_id}.json Deletes a report
GET	/admin/api/unstable/reports.json Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/reports.json Creates a new report
GET	/admin/api/unstable/reports/{report_id}.json Retrieves a single report created by your app
PUT	/admin/api/unstable/reports/{report_id}.json Updates a report
DELETE	/admin/api/unstable/reports/{report_id}.json Deletes a report

sales-channels

POST	/admin/api/2020-01/checkouts.json Creates a checkout
POST	/admin/api/2020-04/checkouts.json Creates a checkout
POST	/admin/api/2020-07/checkouts.json Creates a checkout
POST	/admin/api/2020-10/checkouts.json Creates a checkout
POST	/admin/api/2021-01/checkouts.json Creates a checkout
POST	/admin/api/unstable/checkouts.json Creates a checkout
POST	/admin/api/2020-01/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-01/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-01/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-01/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-04/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-04/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-04/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-04/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-07/checkouts/{token}/complete.json Completes a checkout

GET	/admin/api/2020-07/checkouts/{token}.json
	Retrieves a checkout
PUT	/admin/api/2020-07/checkouts/{token}.json
	Modifies an existing checkout
GET	/admin/api/2020-07/checkouts/{token}/shipping_rates.json
	Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-10/checkouts/{token}/complete.json
	Completes a checkout
GET	/admin/api/2020-10/checkouts/{token}.json
	Retrieves a checkout
PUT	/admin/api/2020-10/checkouts/{token}.json
	Modifies an existing checkout
GET	/admin/api/2020-10/checkouts/{token}/shipping_rates.json
	Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2021-01/checkouts/{token}/complete.json
	Completes a checkout
GET	/admin/api/2021-01/checkouts/{token}.json
	Retrieves a checkout
PUT	/admin/api/2021-01/checkouts/{token}.json
	Modifies an existing checkout
GET	/admin/api/2021-01/checkouts/{token}/shipping_rates.json
	Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/unstable/checkouts/{token}/complete.json
	Completes a checkout
GET	/admin/api/unstable/checkouts/{token}.json
	Retrieves a checkout
PUT	/admin/api/unstable/checkouts/{token}.json
	Modifies an existing checkout
GET	/admin/api/unstable/checkouts/{token}/shipping_rates.json
	Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
GET	/admin/api/2020-01/collection_listings.json
	Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/collection_listings/{collection_listing_id}/product_ids.json
	Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/collection_listings/{collection_listing_id}.json
	Retrieve a specific collection listing that is published to your app
PUT	/admin/api/2020-01/collection_listings/{collection_listing_id}.json
	Create a collection listing to publish a collection to your app
DELETE	/admin/api/2020-01/collection_listings/{collection_listing_id}.json
	Delete a collection listing to unpublish a collection from your app
GET	/admin/api/2020-04/collection_listings.json
	Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/collection_listings/{collection_listing_id}/product_ids.json
	Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/collection_listings/{collection_listing_id}.json

PUT	Retrieve a specific collection listing that is published to your app /admin/api/2020-04/collection_listings/{collection_listing_id}.json Create a collection listing to publish a collection to your app
DELETE	/admin/api/2020-04/collection_listings/{collection_listing_id}.json Delete a collection listing to unpublish a collection from your app
GET	/admin/api/2020-07/collection_listings.json Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/collection_listings/{collection_listing_id}/product_ids.json Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/collection_listings/{collection_listing_id}.json Retrieve a specific collection listing that is published to your app
PUT	/admin/api/2020-07/collection_listings/{collection_listing_id}.json Create a collection listing to publish a collection to your app
DELETE	/admin/api/2020-07/collection_listings/{collection_listing_id}.json Delete a collection listing to unpublish a collection from your app
GET	/admin/api/2020-10/collection_listings.json Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/collection_listings/{collection_listing_id}/product_ids.json Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/collection_listings/{collection_listing_id}.json Retrieve a specific collection listing that is published to your app
PUT	/admin/api/2020-10/collection_listings/{collection_listing_id}.json Create a collection listing to publish a collection to your app
DELETE	/admin/api/2020-10/collection_listings/{collection_listing_id}.json Delete a collection listing to unpublish a collection from your app
GET	/admin/api/2021-01/collection_listings.json Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/collection_listings/{collection_listing_id}/product_ids.json Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/collection_listings/{collection_listing_id}.json Retrieve a specific collection listing that is published to your app
PUT	/admin/api/2021-01/collection_listings/{collection_listing_id}.json Create a collection listing to publish a collection to your app
DELETE	/admin/api/2021-01/collection_listings/{collection_listing_id}.json Delete a collection listing to unpublish a collection from your app
GET	/admin/api/unstable/collection_listings.json Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/collection_listings/{collection_listing_id}/product_ids.json Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/collection_listings/{collection_listing_id}.json Retrieve a specific collection listing that is published to your app
PUT	/admin/api/unstable/collection_listings/{collection_listing_id}.json Create a collection listing to publish a collection to your app
DELETE	/admin/api/unstable/collection_listings/{collection_listing_id}.json Delete a collection listing to unpublish a collection from your app
GET	/admin/api/2020-01/checkouts/{token}/payments.json Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-01/checkouts/{token}/payments.json

GET	/admin/api/2020-01/checkouts/{token}/payments/{payment_id}.json	Creates a payment on a checkout using the session ID returned by the card vault
		Retrieves the payment information for an existing payment
GET	/admin/api/2020-01/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-04/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-04/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-04/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-04/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-07/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-07/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-07/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-07/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-10/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-10/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-10/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-10/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2021-01/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2021-01/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2021-01/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2021-01/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/unstable/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/unstable/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/unstable/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/unstable/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-01/product_listings.json	Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/product_listings/product_ids.json	Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-01/product_listings/count.json	Retrieve a count of products that are published to your app
GET	/admin/api/2020-01/product_listings/{product_listing_id}.json	Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-01/product_listings/{product_listing_id}.json	Create a product listing to publish a product to your app
DELETE	/admin/api/2020-01/product_listings/{product_listing_id}.json	Delete a product listing to unpublish a product from your app
GET	/admin/api/2020-04/product_listings.json	

Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-04/product_listings/product_ids.json

Retrieve product_ids that are published to your app. Maximum 1,000 results per page.

GET /admin/api/2020-04/product_listings/count.json

Retrieve a count of products that are published to your app

GET /admin/api/2020-04/product_listings/{product_listing_id}.json

Retrieve a specific product listing that is published to your app

PUT /admin/api/2020-04/product_listings/{product_listing_id}.json

Create a product listing to publish a product to your app

DELETE /admin/api/2020-04/product_listings/{product_listing_id}.json

Delete a product listing to unpublish a product from your app

GET /admin/api/2020-07/product_listings.json

Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-07/product_listings/product_ids.json

Retrieve product_ids that are published to your app. Maximum 1,000 results per page.

GET /admin/api/2020-07/product_listings/count.json

Retrieve a count of products that are published to your app

GET /admin/api/2020-07/product_listings/{product_listing_id}.json

Retrieve a specific product listing that is published to your app

PUT /admin/api/2020-07/product_listings/{product_listing_id}.json

Create a product listing to publish a product to your app

DELETE /admin/api/2020-07/product_listings/{product_listing_id}.json

Delete a product listing to unpublish a product from your app

sales-channels/checkout

POST </admin/api/2020-01/checkouts.json>

Creates a checkout

POST </admin/api/2020-04/checkouts.json>

Creates a checkout

POST </admin/api/2020-07/checkouts.json>

Creates a checkout

POST </admin/api/2020-10/checkouts.json>

Creates a checkout

POST </admin/api/2021-01/checkouts.json>

Creates a checkout

POST </admin/api/unstable/checkouts.json>

Creates a checkout

POST </admin/api/2020-01/checkouts/{token}/complete.json>

Completes a checkout

GET </admin/api/2020-01/checkouts/{token}.json>

Retrieves a checkout

PUT </admin/api/2020-01/checkouts/{token}.json>

Modifies an existing checkout

GET /admin/api/2020-01/checkouts/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

POST </admin/api/2020-04/checkouts/{token}/complete.json>

Completes a checkout

GET </admin/api/2020-04/checkouts/{token}.json>

Retrieves a checkout

PUT </admin/api/2020-04/checkouts/{token}.json>

Modifies an existing checkout

GET /admin/api/2020-04/checkouts/{token}/shipping_rates.json

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

POST	/admin/api/2020-07/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-07/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-07/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-07/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2020-10/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2020-10/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2020-10/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2020-10/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/2021-01/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/2021-01/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/2021-01/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/2021-01/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.
POST	/admin/api/unstable/checkouts/{token}/complete.json Completes a checkout
GET	/admin/api/unstable/checkouts/{token}.json Retrieves a checkout
PUT	/admin/api/unstable/checkouts/{token}.json Modifies an existing checkout
GET	/admin/api/unstable/checkouts/{token}/shipping_rates.json Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

sales-channels/collectionlisting

GET	/admin/api/2020-01/collection_listings.json Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/collection_listings/{collection_listing_id}/product_ids.json Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/collection_listings/{collection_listing_id}.json Retrieve a specific collection listing that is published to your app
PUT	/admin/api/2020-01/collection_listings/{collection_listing_id}.json Create a collection listing to publish a collection to your app
DELETE	/admin/api/2020-01/collection_listings/{collection_listing_id}.json Delete a collection listing to unpublish a collection from your app
GET	/admin/api/2020-04/collection_listings.json Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/collection_listings/{collection_listing_id}/product_ids.json

sales-channels/payment

GET	/admin/api/2020-01/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-01/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-01/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-01/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-04/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-04/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-04/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-04/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-07/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-07/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-07/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-07/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2020-10/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2020-10/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2020-10/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2020-10/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/2021-01/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/2021-01/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/2021-01/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/2021-01/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout
GET	/admin/api/unstable/checkouts/{token}/payments.json	Retrieves a list of payments on a particular checkout
POST	/admin/api/unstable/checkouts/{token}/payments.json	Creates a payment on a checkout using the session ID returned by the card vault
GET	/admin/api/unstable/checkouts/{token}/payments/{payment_id}.json	Retrieves the payment information for an existing payment
GET	/admin/api/unstable/checkouts/{token}/payments/count.json	Counts the number of payments attempted on a checkout

sales-channels/productlisting

GET	/admin/api/2020-01/product_listings.json	Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/product_listings/product_ids.json	Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-01/product_listings/count.json	Retrieve a count of products that are published to your app
GET	/admin/api/2020-01/product_listings/{product_listing_id}.json	

PUT	/admin/api/2020-01/product_listings/{product_listing_id}.json Retrieve a specific product listing that is published to your app
DELETE	/admin/api/2020-01/product_listings/{product_listing_id}.json Delete a product listing to unpublish a product from your app
GET	/admin/api/2020-04/product_listings.json Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/product_listings/product_ids.json Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-04/product_listings/count.json Retrieve a count of products that are published to your app
GET	/admin/api/2020-04/product_listings/{product_listing_id}.json Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-04/product_listings/{product_listing_id}.json Create a product listing to publish a product to your app
DELETE	/admin/api/2020-04/product_listings/{product_listing_id}.json Delete a product listing to unpublish a product from your app
GET	/admin/api/2020-07/product_listings.json Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/product_listings/product_ids.json Retrieve product_ids that are published to your app. Maximum 1,000 results per page.
GET	/admin/api/2020-07/product_listings/count.json Retrieve a count of products that are published to your app
GET	/admin/api/2020-07/product_listings/{product_listing_id}.json Retrieve a specific product listing that is published to your app
PUT	/admin/api/2020-07/product_listings/{product_listing_id}.json Create a product listing to publish a product to your app
DELETE	/admin/api/2020-07/product_listings/{product_listing_id}.json Delete a product listing to unpublish a product from your app

scripttag

GET	/admin/api/2020-01/script_tags.json Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/script_tags.json Creates a new script tag
GET	/admin/api/2020-01/script_tags/count.json Retrieves a count of all script tags
GET	/admin/api/2020-01/script_tags/{script_tag_id}.json Retrieves a single script tag
PUT	/admin/api/2020-01/script_tags/{script_tag_id}.json Updates a script tag
DELETE	/admin/api/2020-01/script_tags/{script_tag_id}.json Deletes a script tag
GET	/admin/api/2020-04/script_tags.json Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/script_tags.json Creates a new script tag
GET	/admin/api/2020-04/script_tags/count.json Retrieves a count of all script tags
GET	/admin/api/2020-04/script_tags/{script_tag_id}.json Retrieves a single script tag
PUT	/admin/api/2020-04/script_tags/{script_tag_id}.json Updates a script tag
DELETE	/admin/api/2020-04/script_tags/{script_tag_id}.json

GET	/admin/api/2020-07/script_tags.json Deletes a script tag
	Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/script_tags.json Creates a new script tag
GET	/admin/api/2020-07/script_tags/count.json Retrieves a count of all script tags
GET	/admin/api/2020-07/script_tags/{script_tag_id}.json Retrieves a single script tag
PUT	/admin/api/2020-07/script_tags/{script_tag_id}.json Updates a script tag
DELETE	/admin/api/2020-07/script_tags/{script_tag_id}.json Deletes a script tag
GET	/admin/api/2020-10/script_tags.json Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/script_tags.json Creates a new script tag
GET	/admin/api/2020-10/script_tags/count.json Retrieves a count of all script tags
GET	/admin/api/2020-10/script_tags/{script_tag_id}.json Retrieves a single script tag
PUT	/admin/api/2020-10/script_tags/{script_tag_id}.json Updates a script tag
DELETE	/admin/api/2020-10/script_tags/{script_tag_id}.json Deletes a script tag
GET	/admin/api/2021-01/script_tags.json Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/script_tags.json Creates a new script tag
GET	/admin/api/2021-01/script_tags/count.json Retrieves a count of all script tags
GET	/admin/api/2021-01/script_tags/{script_tag_id}.json Retrieves a single script tag
PUT	/admin/api/2021-01/script_tags/{script_tag_id}.json Updates a script tag
DELETE	/admin/api/2021-01/script_tags/{script_tag_id}.json Deletes a script tag
GET	/admin/api/unstable/script_tags.json Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/script_tags.json Creates a new script tag
GET	/admin/api/unstable/script_tags/count.json Retrieves a count of all script tags
GET	/admin/api/unstable/script_tags/{script_tag_id}.json Retrieves a single script tag
PUT	/admin/api/unstable/script_tags/{script_tag_id}.json Updates a script tag
DELETE	/admin/api/unstable/script_tags/{script_tag_id}.json Deletes a script tag

shipping-and-fulfillment

GET	/admin/api/2020-01/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.
GET	/admin/api/2020-04/assigned_fulfillment_orders.json

GET [/admin/api/2020-07/assigned_fulfillment_orders.json](#)
Retrieves a list of fulfillment orders on a shop for a specific app.

GET [/admin/api/2020-10/assigned_fulfillment_orders.json](#)
Retrieves a list of fulfillment orders on a shop for a specific app.

GET [/admin/api/2021-01/assigned_fulfillment_orders.json](#)
Retrieves a list of fulfillment orders on a shop for a specific app.

GET [/admin/api/unstable/assigned_fulfillment_orders.json](#)
Retrieves a list of fulfillment orders on a shop for a specific app.

POST [/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json](#)
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json](#)
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST [/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json](#)
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

GET [/admin/api/2020-01/carrier_services.json](#)
Retrieves a list of carrier services

POST [/admin/api/2020-01/carrier_services.json](#)
Creates a carrier service

GET [/admin/api/2020-01/carrier_services/{carrier_service_id}.json](#)
Retrieves a single carrier service by its ID

PUT [/admin/api/2020-01/carrier_services/{carrier_service_id}.json](#)
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE [/admin/api/2020-01/carrier_services/{carrier_service_id}.json](#)
Deletes a carrier service

GET [/admin/api/2020-04/carrier_services.json](#)
Retrieves a list of carrier services

POST [/admin/api/2020-04/carrier_services.json](#)
Creates a carrier service

GET [/admin/api/2020-04/carrier_services/{carrier_service_id}.json](#)

PUT	Retrieves a single carrier service by its ID /admin/api/2020-04/carrier_services/{carrier_service_id}.json
	Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/2020-04/carrier_services/{carrier_service_id}.json Deletes a carrier service
GET	/admin/api/2020-07/carrier_services.json Retrieves a list of carrier services
POST	/admin/api/2020-07/carrier_services.json Creates a carrier service
GET	/admin/api/2020-07/carrier_services/{carrier_service_id}.json Retrieves a single carrier service by its ID
PUT	/admin/api/2020-07/carrier_services/{carrier_service_id}.json Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/2020-07/carrier_services/{carrier_service_id}.json Deletes a carrier service
GET	/admin/api/2020-10/carrier_services.json Retrieves a list of carrier services
POST	/admin/api/2020-10/carrier_services.json Creates a carrier service
GET	/admin/api/2020-10/carrier_services/{carrier_service_id}.json Retrieves a single carrier service by its ID
PUT	/admin/api/2020-10/carrier_services/{carrier_service_id}.json Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/2020-10/carrier_services/{carrier_service_id}.json Deletes a carrier service
GET	/admin/api/2021-01/carrier_services.json Retrieves a list of carrier services
POST	/admin/api/2021-01/carrier_services.json Creates a carrier service
GET	/admin/api/2021-01/carrier_services/{carrier_service_id}.json Retrieves a single carrier service by its ID
PUT	/admin/api/2021-01/carrier_services/{carrier_service_id}.json Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/2021-01/carrier_services/{carrier_service_id}.json Deletes a carrier service
GET	/admin/api/unstable/carrier_services.json Retrieves a list of carrier services
POST	/admin/api/unstable/carrier_services.json Creates a carrier service
GET	/admin/api/unstable/carrier_services/{carrier_service_id}.json Retrieves a single carrier service by its ID
PUT	/admin/api/unstable/carrier_services/{carrier_service_id}.json Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/unstable/carrier_services/{carrier_service_id}.json Deletes a carrier service
GET	/admin/api/2020-01/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

GET	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-01/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-01/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-01/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-04/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-04/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-04/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-04/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-07/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST	/admin/api/2020-07/orders/{order_id}/fulfillments.json	Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillments.json	Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/count.json	Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json	Retrieve a specific fulfillment
PUT	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json	Update information associated with a fulfillment
POST	/admin/api/2020-07/fulfillments.json	Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-07/fulfillments/{fulfillment_id}/update_tracking.json	Updates the tracking information for a fulfillment.
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json	Mark a fulfillment as complete
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/open.json	Mark a fulfillment as open
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json	Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-07/fulfillments/{fulfillment_id}/cancel.json	Cancels a fulfillment.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments.json	Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/fulfillments.json	Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillments.json	Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/count.json	Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json	Retrieve a specific fulfillment
PUT	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json	Update information associated with a fulfillment
POST	/admin/api/2020-10/fulfillments.json	Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/update_tracking.json	Updates the tracking information for a fulfillment.

POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2021-01/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2021-01/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/unstable/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

GET	/admin/api/unstable/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/unstable/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/unstable/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/unstable/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event

GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2020-01/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-04/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-07/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-10/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2021-01/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/move.json	Moves a fulfillment order from one merchant managed location to another merchant managed location.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/open.json	Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/reschedule.json	Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.
GET	/admin/api/unstable/orders/{order_id}/fulfillment_orders.json	Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}.json	Retrieves a specific fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancel.json	Marks a fulfillment order as cancelled.
POST	/admin/api/unstable/fulfillment_orders/release_hold.json	Releases the fulfillment order holds for a specific order. Fulfillment orders are created with an ON_HOLD status if the channel that created the order has a fulfillment hold policy.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/close.json	Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/move.json	Moves a fulfillment order from one merchant managed location to another merchant managed location.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/open.json	Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/reschedule.json	Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json
Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

GET /fetch_tracking_numbers
Get tracking numbers for orders

GET /fetch_stock
Get inventory levels

GET /admin/api/2020-01/fulfillment_services.json

POST /admin/api/2020-01/fulfillment_services.json
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET /admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json

PUT /admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json

DELETE /admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json

GET /admin/api/2020-04/fulfillment_services.json

POST /admin/api/2020-04/fulfillment_services.json
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

PUT /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

DELETE /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

GET /admin/api/2020-07/fulfillment_services.json

POST /admin/api/2020-07/fulfillment_services.json
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET /admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

PUT /admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

DELETE /admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

GET /admin/api/2020-10/fulfillment_services.json

POST /admin/api/2020-10/fulfillment_services.json
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

PUT /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

DELETE /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

GET /admin/api/2021-01/fulfillment_services.json

POST /admin/api/2021-01/fulfillment_services.json
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

PUT /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

DELETE /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

GET /admin/api/unstable/fulfillment_services.json

POST /admin/api/unstable/fulfillment_services.json
To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

GET /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json

PUT	/admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json
DELETE	/admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json
GET	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

shipping-and-fulfillment/assignedfulfillmentorder

GET	/admin/api/2020-01/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.
GET	/admin/api/2020-04/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.
GET	/admin/api/2020-07/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.
GET	/admin/api/2020-10/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.
GET	/admin/api/2021-01/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.
GET	/admin/api/unstable/assigned_fulfillment_orders.json Retrieves a list of fulfillment orders on a shop for a specific app.

shipping-and-fulfillment/cancellationrequest

POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json Sends a cancellation request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json Accepts a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json Rejects a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json Sends a cancellation request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json Accepts a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json Rejects a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json Sends a cancellation request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json Accepts a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json Rejects a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json Sends a cancellation request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json Accepts a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json Rejects a cancellation request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json Sends a cancellation request to the fulfillment service of a fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json
Sends a cancellation request to the fulfillment service of a fulfillment order.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json
Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

POST /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json
Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

shipping-and-fulfillment/carrierservice

GET /admin/api/2020-01/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2020-01/carrier_services.json
Creates a carrier service

GET /admin/api/2020-01/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-01/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-01/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2020-04/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2020-04/carrier_services.json
Creates a carrier service

GET /admin/api/2020-04/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-04/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-04/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2020-07/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2020-07/carrier_services.json
Creates a carrier service

GET /admin/api/2020-07/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-07/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-07/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2020-10/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2020-10/carrier_services.json
Creates a carrier service

GET /admin/api/2020-10/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2020-10/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE /admin/api/2020-10/carrier_services/{carrier_service_id}.json
Deletes a carrier service

GET /admin/api/2021-01/carrier_services.json
Retrieves a list of carrier services

POST /admin/api/2021-01/carrier_services.json
Creates a carrier service

GET /admin/api/2021-01/carrier_services/{carrier_service_id}.json
Retrieves a single carrier service by its ID

PUT /admin/api/2021-01/carrier_services/{carrier_service_id}.json
Updates a carrier service. Only the app that creates a carrier service can update it.

DELETE	/admin/api/2021-01/carrier_services/{carrier_service_id}.json Deletes a carrier service
GET	/admin/api/unstable/carrier_services.json Retrieves a list of carrier services
POST	/admin/api/unstable/carrier_services.json Creates a carrier service
GET	/admin/api/unstable/carrier_services/{carrier_service_id}.json Retrieves a single carrier service by its ID
PUT	/admin/api/unstable/carrier_services/{carrier_service_id}.json Updates a carrier service. Only the app that creates a carrier service can update it.
DELETE	/admin/api/unstable/carrier_services/{carrier_service_id}.json Deletes a carrier service

shipping-and-fulfillment/fulfillment

GET	/admin/api/2020-01/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-01/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-01/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-01/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-01/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-04/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-04/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using

this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

GET /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

GET /admin/api/2020-04/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

GET /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

PUT /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

POST </admin/api/2020-04/fulfillments.json>

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

POST /admin/api/2020-04/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

POST /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

POST /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

POST /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

POST /admin/api/2020-04/fulfillments/{fulfillment_id}/cancel.json

Cancels a fulfillment.

GET /admin/api/2020-07/orders/{order_id}/fulfillments.json

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-07/orders/{order_id}/fulfillments.json

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

GET /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Retrieves fulfillments associated with a fulfillment order.

GET /admin/api/2020-07/orders/{order_id}/fulfillments/count.json

Retrieves a count of fulfillments associated with a specific order

GET /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json

Retrieve a specific fulfillment

PUT /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json

Update information associated with a fulfillment

POST </admin/api/2020-07/fulfillments.json>

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

POST /admin/api/2020-07/fulfillments/{fulfillment_id}/update_tracking.json

Updates the tracking information for a fulfillment.

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Mark a fulfillment as complete

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Mark a fulfillment as open

POST /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Cancel a fulfillment for a specific order ID

POST	/admin/api/2020-07/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/2020-10/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2020-10/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/2021-01/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json

POST	/admin/api/2021-01/fulfillments.json Update information associated with a fulfillment Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/2021-01/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.
GET	/admin/api/unstable/orders/{order_id}/fulfillments.json Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/orders/{order_id}/fulfillments.json Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillments.json Retrieves fulfillments associated with a fulfillment order.
GET	/admin/api/unstable/orders/{order_id}/fulfillments/count.json Retrieves a count of fulfillments associated with a specific order
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json Retrieve a specific fulfillment
PUT	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json Update information associated with a fulfillment
POST	/admin/api/unstable/fulfillments.json Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.
POST	/admin/api/unstable/fulfillments/{fulfillment_id}/update_tracking.json Updates the tracking information for a fulfillment.
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json Mark a fulfillment as complete
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/open.json Mark a fulfillment as open
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json Cancel a fulfillment for a specific order ID
POST	/admin/api/unstable/fulfillments/{fulfillment_id}/cancel.json Cancels a fulfillment.

shipping-and-fulfillment/fulfillmentevent

GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

POST	Retrieves a list of fulfillment events for a specific fulfillment /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Retrieves a list of fulfillment events for a specific fulfillment
POST	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json Creates a fulfillment event
GET	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Retrieves a specific fulfillment event
DELETE	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json Deletes a fulfillment event

shipping-and-fulfillment/fulfillmentorder

GET	/admin/api/2020-01/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-04/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-07/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2020-10/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
GET	/admin/api/2021-01/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/open.json Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/reschedule.json Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.
GET	/admin/api/unstable/orders/{order_id}/fulfillment_orders.json Retrieves a list of fulfillment orders for a specific order.
GET	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}.json Retrieves a specific fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancel.json Marks a fulfillment order as cancelled.
POST	/admin/api/unstable/fulfillment_orders/release_hold.json Releases the fulfillment order holds for a specific order. Fulfillment orders are created with an ON_HOLD status if the channel that created the order has a fulfillment hold policy.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/close.json Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/move.json Moves a fulfillment order from one merchant managed location to another merchant managed location.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/open.json Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/reschedule.json Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.

shipping-and-fulfillment/fulfillmentrequest

POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json	Sends a fulfillment request to the fulfillment service of a fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json	Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.
POST	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json	Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

shipping-and-fulfillment/fulfillmentservice

GET	/fetch_tracking_numbers	Get tracking numbers for orders
GET	/fetch_stock	Get inventory levels
GET	/admin/api/2020-01/fulfillment_services.json	
POST	/admin/api/2020-01/fulfillment_services.json	To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.
GET	/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json	
PUT	/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json	
DELETE	/admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json	
GET	/admin/api/2020-04/fulfillment_services.json	
POST	/admin/api/2020-04/fulfillment_services.json	To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.
GET	/admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json	

[PUT /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json](#)

[DELETE /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json](#)

[GET /admin/api/2020-07/fulfillment_services.json](#)

[POST /admin/api/2020-07/fulfillment_services.json](#)

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

[GET /admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json](#)

[PUT /admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json](#)

[DELETE /admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json](#)

[GET /admin/api/2020-10/fulfillment_services.json](#)

[POST /admin/api/2020-10/fulfillment_services.json](#)

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

[GET /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)

[PUT /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)

[DELETE /admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json](#)

[GET /admin/api/2021-01/fulfillment_services.json](#)

[POST /admin/api/2021-01/fulfillment_services.json](#)

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

[GET /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)

[PUT /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)

[DELETE /admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json](#)

[GET /admin/api/unstable/fulfillment_services.json](#)

[POST /admin/api/unstable/fulfillment_services.json](#)

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

[GET /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)

[PUT /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)

[DELETE /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json](#)

shipping-and-fulfillment/locationsformove

[GET /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

[GET /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json](#)

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

shippingzone

GET	/admin/api/2020-01/shipping_zones.json
	Get a list of all shipping zones
GET	/admin/api/2020-04/shipping_zones.json
	Get a list of all shipping zones
GET	/admin/api/2020-07/shipping_zones.json
	Get a list of all shipping zones
GET	/admin/api/2020-10/shipping_zones.json
	Get a list of all shipping zones
GET	/admin/api/2021-01/shipping_zones.json
	Get a list of all shipping zones
GET	/admin/api/unstable/shipping_zones.json
	Get a list of all shipping zones

shop

GET	/admin/api/2020-01/shop.json
	Retrieves the shop's configuration
GET	/admin/api/2020-04/shop.json
	Retrieves the shop's configuration
GET	/admin/api/2020-07/shop.json
	Retrieves the shop's configuration
GET	/admin/api/2020-10/shop.json
	Retrieves the shop's configuration
GET	/admin/api/2021-01/shop.json
	Retrieves the shop's configuration
GET	/admin/api/unstable/shop.json
	Retrieves the shop's configuration

shopify_payments

GET	/admin/api/2020-01/shopify_payments/balance.json
	Retrieves the account's current balance.
GET	/admin/api/2020-04/shopify_payments/balance.json
	Retrieves the account's current balance.
GET	/admin/api/2020-07/shopify_payments/balance.json
	Retrieves the account's current balance.
GET	/admin/api/2020-10/shopify_payments/balance.json
	Retrieves the account's current balance.
GET	/admin/api/2021-01/shopify_payments/balance.json
	Retrieves the account's current balance.
GET	/admin/api/unstable/shopify_payments/balance.json
	Retrieves the account's current balance.
GET	/admin/api/2020-01/shopify_payments/disputes.json
	Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/shopify_payments/disputes/{dispute_id}.json
	Retrieves a single dispute by ID.
GET	/admin/api/2020-04/shopify_payments/disputes.json
	Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/shopify_payments/payouts.json
	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/shopify_payments/payouts/{payout_id}.json
	Retrieves a single payout by id.
GET	/admin/api/2020-04/shopify_payments/payouts.json
	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/shopify_payments/payouts/{payout_id}.json
	Retrieves a single payout by id.

GET	/admin/api/2020-07/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2020-10/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2021-01/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/unstable/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2020-01/shopify_payments/balance/transactions.json	Retrieves a list of all balance transactions ordered by processing time, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

shopify_payments/balance

GET	/admin/api/2020-01/shopify_payments/balance.json	Retrieves the account's current balance.
GET	/admin/api/2020-04/shopify_payments/balance.json	Retrieves the account's current balance.
GET	/admin/api/2020-07/shopify_payments/balance.json	Retrieves the account's current balance.
GET	/admin/api/2020-10/shopify_payments/balance.json	Retrieves the account's current balance.
GET	/admin/api/2021-01/shopify_payments/balance.json	Retrieves the account's current balance.
GET	/admin/api/unstable/shopify_payments/balance.json	Retrieves the account's current balance.

shopify_payments/dispute

GET	/admin/api/2020-01/shopify_payments/disputes.json	Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/shopify_payments/disputes/{dispute_id}.json	Retrieves a single dispute by ID.
GET	/admin/api/2020-04/shopify_payments/disputes.json	Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

shopify_payments/payout

GET	/admin/api/2020-01/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/shopify_payments/payouts/{payout_id}.json	Retrieves a single payout by id.
GET	/admin/api/2020-04/shopify_payments/payouts.json	Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-04/shopify_payments/payouts/{payout_id}.json

Retrieves a single payout by id.

GET /admin/api/2020-07/shopify_payments/payouts.json

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-07/shopify_payments/payouts/{payout_id}.json

Retrieves a single payout by id.

GET /admin/api/2020-10/shopify_payments/payouts.json

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2020-10/shopify_payments/payouts/{payout_id}.json

Retrieves a single payout by id.

GET /admin/api/2021-01/shopify_payments/payouts.json

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/2021-01/shopify_payments/payouts/{payout_id}.json

Retrieves a single payout by id.

GET /admin/api/unstable/shopify_payments/payouts.json

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

GET /admin/api/unstable/shopify_payments/payouts/{payout_id}.json

Retrieves a single payout by id.

shopify_payments/transaction

GET /admin/api/2020-01/shopify_payments/balance/transactions.json

Retrieves a list of all balance transactions ordered by processing time, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

smartcollection

GET /admin/api/2020-01/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-01/smart_collections.json

Creates a new smart collection using the specified rules.

GET /admin/api/2020-01/smart_collections/count.json

Retrieves a count of smart collections

GET /admin/api/2020-01/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection

PUT /admin/api/2020-01/smart_collections/{smart_collection_id}.json

Updates an existing smart collection

DELETE /admin/api/2020-01/smart_collections/{smart_collection_id}.json

Removes a smart collection

PUT /admin/api/2020-01/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection

GET /admin/api/2020-04/smart_collections.json

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST /admin/api/2020-04/smart_collections.json

Creates a new smart collection using the specified rules.

GET /admin/api/2020-04/smart_collections/count.json

Retrieves a count of smart collections

GET /admin/api/2020-04/smart_collections/{smart_collection_id}.json

Retrieves a single smart collection

PUT /admin/api/2020-04/smart_collections/{smart_collection_id}.json

Updates an existing smart collection

DELETE /admin/api/2020-04/smart_collections/{smart_collection_id}.json

Removes a smart collection

PUT	/admin/api/2020-04/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection
GET	/admin/api/2020-07/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-07/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/2020-07/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/2020-07/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/2020-07/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/2020-07/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/2020-07/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection
GET	/admin/api/2020-10/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2020-10/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/2020-10/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/2020-10/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/2020-10/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/2020-10/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/2020-10/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection
GET	/admin/api/2021-01/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/2021-01/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/2021-01/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/2021-01/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/2021-01/smart_collections/{smart_collection_id}/order.json Updates the ordering type of products in a smart collection
GET	/admin/api/unstable/smart_collections.json Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
POST	/admin/api/unstable/smart_collections.json Creates a new smart collection using the specified rules.
GET	/admin/api/unstable/smart_collections/count.json Retrieves a count of smart collections
GET	/admin/api/unstable/smart_collections/{smart_collection_id}.json Retrieves a single smart collection
PUT	/admin/api/unstable/smart_collections/{smart_collection_id}.json Updates an existing smart collection
DELETE	/admin/api/unstable/smart_collections/{smart_collection_id}.json Removes a smart collection
PUT	/admin/api/unstable/smart_collections/{smart_collection_id}/order.json

Updates the ordering type of products in a smart collection

store-properties

GET	/admin/api/2020-01/countries.json	Retrieves a list of countries.
POST	/admin/api/2020-01/countries.json	Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-01/countries/count.json	Retrieves a count of countries.
GET	/admin/api/2020-01/countries/{country_id}.json	Retrieves a specific county.
PUT	/admin/api/2020-01/countries/{country_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-01/countries/{country_id}.json	Deletes a country.
GET	/admin/api/2020-04/countries.json	Retrieves a list of countries.
POST	/admin/api/2020-04/countries.json	Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-04/countries/count.json	Retrieves a count of countries.
GET	/admin/api/2020-04/countries/{country_id}.json	Retrieves a specific county.
PUT	/admin/api/2020-04/countries/{country_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-04/countries/{country_id}.json	Deletes a country.
GET	/admin/api/2020-07/countries.json	Retrieves a list of countries.
POST	/admin/api/2020-07/countries.json	Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-07/countries/count.json	Retrieves a count of countries.
GET	/admin/api/2020-07/countries/{country_id}.json	Retrieves a specific county.
PUT	/admin/api/2020-07/countries/{country_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-07/countries/{country_id}.json	Deletes a country.
GET	/admin/api/2020-10/countries.json	Retrieves a list of countries.
POST	/admin/api/2020-10/countries.json	Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2020-10/countries/count.json	Retrieves a count of countries.
GET	/admin/api/2020-10/countries/{country_id}.json	Retrieves a specific county.
PUT	/admin/api/2020-10/countries/{country_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
DELETE	/admin/api/2020-10/countries/{country_id}.json	Deletes a country.
GET	/admin/api/2021-01/countries.json	Retrieves a list of countries.
POST	/admin/api/2021-01/countries.json	Caution As of version 2020-10, the tax field is deprecated. Creates a country.
GET	/admin/api/2021-01/countries/count.json	Retrieves a count of countries.
GET	/admin/api/2021-01/countries/{country_id}.json	Retrieves a specific county.
PUT	/admin/api/2021-01/countries/{country_id}.json	

DELETE /admin/api/2021-01/countries/{country_id}.json
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.
Deletes a country.

GET </admin/api/unstable/countries.json>
Retrieves a list of countries.

POST </admin/api/unstable/countries.json>
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET </admin/api/unstable/countries/count.json>
Retrieves a count of countries.

GET /admin/api/unstable/countries/{country_id}.json
Retrieves a specific county.

PUT /admin/api/unstable/countries/{country_id}.json
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE /admin/api/unstable/countries/{country_id}.json
Deletes a country.

GET </admin/api/2020-01/currencies.json>
Retrieves a list of currencies enabled on a shop

GET </admin/api/2020-04/currencies.json>
Retrieves a list of currencies enabled on a shop

GET </admin/api/2020-07/currencies.json>
Retrieves a list of currencies enabled on a shop

GET </admin/api/2020-10/currencies.json>
Retrieves a list of currencies enabled on a shop

GET </admin/api/2021-01/currencies.json>
Retrieves a list of currencies enabled on a shop

GET </admin/api/unstable/currencies.json>
Retrieves a list of currencies enabled on a shop

GET </admin/api/2020-01/policies.json>
Retrieves a list of the shop's policies

GET </admin/api/2020-04/policies.json>
Retrieves a list of the shop's policies

GET </admin/api/2020-07/policies.json>
Retrieves a list of the shop's policies

GET </admin/api/2020-10/policies.json>
Retrieves a list of the shop's policies

GET </admin/api/2021-01/policies.json>
Retrieves a list of the shop's policies

GET </admin/api/unstable/policies.json>
Retrieves a list of the shop's policies

GET /admin/api/2020-01/countries/{country_id}/provinces.json
Retrieves a list of provinces

GET /admin/api/2020-01/countries/{country_id}/provinces/count.json
Retrieves a count of provinces for a country

GET /admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json
Retrieves a single province for a country

PUT /admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json
Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

GET /admin/api/2020-04/countries/{country_id}/provinces.json
Retrieves a list of provinces

GET /admin/api/2020-04/countries/{country_id}/provinces/count.json
Retrieves a count of provinces for a country

GET /admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json
Retrieves a single province for a country

PUT /admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json
Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

GET /admin/api/2020-07/countries/{country_id}/provinces.json
Retrieves a list of provinces

GET /admin/api/2020-07/countries/{country_id}/provinces/count.json
Retrieves a count of provinces for a country

GET /admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json

Retrieves a single province for a country
PUT /admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json
 Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

GET /admin/api/2020-10/countries/{country_id}/provinces.json
 Retrieves a list of provinces

GET /admin/api/2020-10/countries/{country_id}/provinces/count.json
 Retrieves a count of provinces for a country

GET /admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json
 Retrieves a single province for a country

PUT /admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json
 Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

GET /admin/api/2021-01/countries/{country_id}/provinces.json
 Retrieves a list of provinces

GET /admin/api/2021-01/countries/{country_id}/provinces/count.json
 Retrieves a count of provinces for a country

GET /admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json
 Retrieves a single province for a country

PUT /admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json
 Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

GET /admin/api/unstable/countries/{country_id}/provinces.json
 Retrieves a list of provinces

GET /admin/api/unstable/countries/{country_id}/provinces/count.json
 Retrieves a count of provinces for a country

GET /admin/api/unstable/countries/{country_id}/provinces/{province_id}.json
 Retrieves a single province for a country

PUT /admin/api/unstable/countries/{country_id}/provinces/{province_id}.json
 Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

GET /admin/api/2020-01/shipping_zones.json
 Get a list of all shipping zones

GET /admin/api/2020-04/shipping_zones.json
 Get a list of all shipping zones

GET /admin/api/2020-07/shipping_zones.json
 Get a list of all shipping zones

GET /admin/api/2020-10/shipping_zones.json
 Get a list of all shipping zones

GET /admin/api/2021-01/shipping_zones.json
 Get a list of all shipping zones

GET /admin/api/unstable/shipping_zones.json
 Get a list of all shipping zones

GET </admin/api/2020-01/shop.json>
 Retrieves the shop's configuration

GET </admin/api/2020-04/shop.json>
 Retrieves the shop's configuration

GET </admin/api/2020-07/shop.json>
 Retrieves the shop's configuration

GET </admin/api/2020-10/shop.json>
 Retrieves the shop's configuration

GET </admin/api/2021-01/shop.json>
 Retrieves the shop's configuration

GET </admin/api/unstable/shop.json>
 Retrieves the shop's configuration

store-properties/country

GET </admin/api/2020-01/countries.json>
 Retrieves a list of countries.

POST </admin/api/2020-01/countries.json>
 Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET </admin/api/2020-01/countries/count.json>
 Retrieves a count of countries.

GET /admin/api/2020-01/countries/{country_id}.json

PUT [/admin/api/2020-01/countries/{country_id}.json](#)
Retrieves a specific county.
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE [/admin/api/2020-01/countries/{country_id}.json](#)
Deletes a country.

GET [/admin/api/2020-04/countries.json](#)
Retrieves a list of countries.

POST [/admin/api/2020-04/countries.json](#)
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET [/admin/api/2020-04/countries/count.json](#)
Retrieves a count of countries.

GET [/admin/api/2020-04/countries/{country_id}.json](#)
Retrieves a specific county.

PUT [/admin/api/2020-04/countries/{country_id}.json](#)
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE [/admin/api/2020-04/countries/{country_id}.json](#)
Deletes a country.

GET [/admin/api/2020-07/countries.json](#)
Retrieves a list of countries.

POST [/admin/api/2020-07/countries.json](#)
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET [/admin/api/2020-07/countries/count.json](#)
Retrieves a count of countries.

GET [/admin/api/2020-07/countries/{country_id}.json](#)
Retrieves a specific county.

PUT [/admin/api/2020-07/countries/{country_id}.json](#)
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE [/admin/api/2020-07/countries/{country_id}.json](#)
Deletes a country.

GET [/admin/api/2020-10/countries.json](#)
Retrieves a list of countries.

POST [/admin/api/2020-10/countries.json](#)
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET [/admin/api/2020-10/countries/count.json](#)
Retrieves a count of countries.

GET [/admin/api/2020-10/countries/{country_id}.json](#)
Retrieves a specific county.

PUT [/admin/api/2020-10/countries/{country_id}.json](#)
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE [/admin/api/2020-10/countries/{country_id}.json](#)
Deletes a country.

GET [/admin/api/2021-01/countries.json](#)
Retrieves a list of countries.

POST [/admin/api/2021-01/countries.json](#)
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET [/admin/api/2021-01/countries/count.json](#)
Retrieves a count of countries.

GET [/admin/api/2021-01/countries/{country_id}.json](#)
Retrieves a specific county.

PUT [/admin/api/2021-01/countries/{country_id}.json](#)
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE [/admin/api/2021-01/countries/{country_id}.json](#)
Deletes a country.

GET [/admin/api/unstable/countries.json](#)
Retrieves a list of countries.

POST [/admin/api/unstable/countries.json](#)
Caution As of version 2020-10, the tax field is deprecated. Creates a country.

GET [/admin/api/unstable/countries/count.json](#)
Retrieves a count of countries.

GET [/admin/api/unstable/countries/{country_id}.json](#)

PUT [/admin/api/unstable/countries/{country_id}.json](#)
Retrieves a specific county.
Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

DELETE [/admin/api/unstable/countries/{country_id}.json](#)
Deletes a country.

store-properties/currency

GET [/admin/api/2020-01/currencies.json](#)
Retrieves a list of currencies enabled on a shop

GET [/admin/api/2020-04/currencies.json](#)
Retrieves a list of currencies enabled on a shop

GET [/admin/api/2020-07/currencies.json](#)
Retrieves a list of currencies enabled on a shop

GET [/admin/api/2020-10/currencies.json](#)
Retrieves a list of currencies enabled on a shop

GET [/admin/api/2021-01/currencies.json](#)
Retrieves a list of currencies enabled on a shop

GET [/admin/api/unstable/currencies.json](#)
Retrieves a list of currencies enabled on a shop

store-properties/policy

GET [/admin/api/2020-01/policies.json](#)
Retrieves a list of the shop's policies

GET [/admin/api/2020-04/policies.json](#)
Retrieves a list of the shop's policies

GET [/admin/api/2020-07/policies.json](#)
Retrieves a list of the shop's policies

GET [/admin/api/2020-10/policies.json](#)
Retrieves a list of the shop's policies

GET [/admin/api/2021-01/policies.json](#)
Retrieves a list of the shop's policies

GET [/admin/api/unstable/policies.json](#)
Retrieves a list of the shop's policies

store-properties/province

GET [/admin/api/2020-01/countries/{country_id}/provinces.json](#)
Retrieves a list of provinces

GET [/admin/api/2020-01/countries/{country_id}/provinces/count.json](#)
Retrieves a count of provinces for a country

GET [/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json](#)
Retrieves a single province for a country

PUT [/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json](#)
Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

GET [/admin/api/2020-04/countries/{country_id}/provinces.json](#)
Retrieves a list of provinces

GET [/admin/api/2020-04/countries/{country_id}/provinces/count.json](#)
Retrieves a count of provinces for a country

GET [/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json](#)
Retrieves a single province for a country

PUT [/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json](#)
Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

GET [/admin/api/2020-07/countries/{country_id}/provinces.json](#)
Retrieves a list of provinces

GET [/admin/api/2020-07/countries/{country_id}/provinces/count.json](#)
Retrieves a count of provinces for a country

GET [/admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json](#)
Retrieves a single province for a country

PUT [/admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json](#)
Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

GET [/admin/api/2020-10/countries/{country_id}/provinces.json](#)
Retrieves a list of provinces

GET	/admin/api/2020-10/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/2021-01/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/2021-01/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.
GET	/admin/api/unstable/countries/{country_id}/provinces.json	Retrieves a list of provinces
GET	/admin/api/unstable/countries/{country_id}/provinces/count.json	Retrieves a count of provinces for a country
GET	/admin/api/unstable/countries/{country_id}/provinces/{province_id}.json	Retrieves a single province for a country
PUT	/admin/api/unstable/countries/{country_id}/provinces/{province_id}.json	Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

store-properties/shippingzone

GET	/admin/api/2020-01/shipping_zones.json	Get a list of all shipping zones
GET	/admin/api/2020-04/shipping_zones.json	Get a list of all shipping zones
GET	/admin/api/2020-07/shipping_zones.json	Get a list of all shipping zones
GET	/admin/api/2020-10/shipping_zones.json	Get a list of all shipping zones
GET	/admin/api/2021-01/shipping_zones.json	Get a list of all shipping zones
GET	/admin/api/unstable/shipping_zones.json	Get a list of all shipping zones

store-properties/shop

GET	/admin/api/2020-01/shop.json	Retrieves the shop's configuration
GET	/admin/api/2020-04/shop.json	Retrieves the shop's configuration
GET	/admin/api/2020-07/shop.json	Retrieves the shop's configuration
GET	/admin/api/2020-10/shop.json	Retrieves the shop's configuration
GET	/admin/api/2021-01/shop.json	Retrieves the shop's configuration
GET	/admin/api/unstable/shop.json	Retrieves the shop's configuration

storefrontaccesstoken

GET	/admin/api/2020-01/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-01/storefront_access_tokens.json	Creates a new storefront access token
DELETE	/admin/api/2020-01/storefront_access_tokens/{storefront_access_token_id}.json	Deletes an existing storefront access token
GET	/admin/api/2020-04/storefront_access_tokens.json	Retrieves a list of storefront access tokens that have been issued

POST	/admin/api/2020-04/storefront_access_tokens.json Creates a new storefront access token
DELETE	/admin/api/2020-04/storefront_access_tokens/{storefront_access_token_id}.json Deletes an existing storefront access token
GET	/admin/api/2020-07/storefront_access_tokens.json Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-07/storefront_access_tokens.json Creates a new storefront access token
DELETE	/admin/api/2020-07/storefront_access_tokens/{storefront_access_token_id}.json Deletes an existing storefront access token
GET	/admin/api/2020-10/storefront_access_tokens.json Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2020-10/storefront_access_tokens.json Creates a new storefront access token
DELETE	/admin/api/2020-10/storefront_access_tokens/{storefront_access_token_id}.json Deletes an existing storefront access token
GET	/admin/api/2021-01/storefront_access_tokens.json Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/2021-01/storefront_access_tokens.json Creates a new storefront access token
DELETE	/admin/api/2021-01/storefront_access_tokens/{storefront_access_token_id}.json Deletes an existing storefront access token
GET	/admin/api/unstable/storefront_access_tokens.json Retrieves a list of storefront access tokens that have been issued
POST	/admin/api/unstable/storefront_access_tokens.json Creates a new storefront access token
DELETE	/admin/api/unstable/storefront_access_tokens/{storefront_access_token_id}.json Deletes an existing storefront access token

tendertransaction

GET	/admin/api/2020-01/tender_transactions.json Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/tender_transactions.json Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-07/tender_transactions.json Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-10/tender_transactions.json Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2021-01/tender_transactions.json Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/unstable/tender_transactions.json Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

theme

GET	/admin/api/2020-01/themes.json Retrieves a list of themes.
POST	/admin/api/2020-01/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-01/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-01/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-01/themes/{theme_id}.json Deletes a theme.

GET	/admin/api/2020-04/themes.json Retrieves a list of themes.
POST	/admin/api/2020-04/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-04/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-04/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-04/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2020-07/themes.json Retrieves a list of themes.
POST	/admin/api/2020-07/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-07/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-07/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-07/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2020-10/themes.json Retrieves a list of themes.
POST	/admin/api/2020-10/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2020-10/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2020-10/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2020-10/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/2021-01/themes.json Retrieves a list of themes.
POST	/admin/api/2021-01/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/2021-01/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/2021-01/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/2021-01/themes/{theme_id}.json Deletes a theme.
GET	/admin/api/unstable/themes.json Retrieves a list of themes.
POST	/admin/api/unstable/themes.json Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.
GET	/admin/api/unstable/themes/{theme_id}.json Retrieves a single theme.
PUT	/admin/api/unstable/themes/{theme_id}.json Updates an existing theme.
DELETE	/admin/api/unstable/themes/{theme_id}.json Deletes a theme.

transaction

GET	/admin/api/2020-01/shopify_payments/balance/transactions.json
---------------------	---

Retrieves a list of all balance transactions ordered by processing time, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

usagecharge

GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Retrieves a list of usage charges
POST	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json Creates a usage charge
GET	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json Retrieves a single charge

user

GET	/admin/api/2020-01/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-01/users/{user_id}.json Retrieves a single user
GET	/admin/api/2020-01/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-04/users.json Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.
GET	/admin/api/2020-04/users/{user_id}.json Retrieves a single user
GET	/admin/api/2020-04/users/current.json Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.
GET	/admin/api/2020-07/users.json

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-07/users/{user_id}.json](#)

Retrieves a single user

[GET](#) [/admin/api/2020-07/users/current.json](#)

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

[GET](#) [/admin/api/2020-10/users.json](#)

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2020-10/users/{user_id}.json](#)

Retrieves a single user

[GET](#) [/admin/api/2020-10/users/current.json](#)

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

[GET](#) [/admin/api/2021-01/users.json](#)

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/2021-01/users/{user_id}.json](#)

Retrieves a single user

[GET](#) [/admin/api/2021-01/users/current.json](#)

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

[GET](#) [/admin/api/unstable/users.json](#)

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

[GET](#) [/admin/api/unstable/users/{user_id}.json](#)

Retrieves a single user

[GET](#) [/admin/api/unstable/users/current.json](#)

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

webhook

[GET](#) [/admin/api/2020-01/webhooks.json](#)

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-01/webhooks.json](#)

Create a new webhook subscription by specifying both an address and a topic

[GET](#) [/admin/api/2020-01/webhooks/count.json](#)

Retrieves a count of existing webhook subscriptions

[GET](#) [/admin/api/2020-01/webhooks/{webhook_id}.json](#)

Retrieves a single webhook subscription

[PUT](#) [/admin/api/2020-01/webhooks/{webhook_id}.json](#)

Update a webhook subscription's topic or address URIs

[DELETE](#) [/admin/api/2020-01/webhooks/{webhook_id}.json](#)

Delete a webhook subscription

[GET](#) [/admin/api/2020-04/webhooks.json](#)

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

[POST](#) [/admin/api/2020-04/webhooks.json](#)

Create a new webhook subscription by specifying both an address and a topic

[GET](#) [/admin/api/2020-04/webhooks/count.json](#)

Retrieves a count of existing webhook subscriptions

[GET](#) [/admin/api/2020-04/webhooks/{webhook_id}.json](#)

Retrieves a single webhook subscription

[PUT](#) [/admin/api/2020-04/webhooks/{webhook_id}.json](#)

Update a webhook subscription's topic or address URIs

[DELETE](#) [/admin/api/2020-04/webhooks/{webhook_id}.json](#)

Delete a webhook subscription

[GET](#) [/admin/api/2020-07/webhooks.json](#)

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-07/webhooks.json>

Create a new webhook subscription by specifying both an address and a topic

GET </admin/api/2020-07/webhooks/count.json>

Retrieves a count of existing webhook subscriptions

GET /admin/api/2020-07/webhooks/{webhook_id}.json

Retrieves a single webhook subscription

PUT /admin/api/2020-07/webhooks/{webhook_id}.json

Update a webhook subscription's topic or address URIs

DELETE /admin/api/2020-07/webhooks/{webhook_id}.json

Delete a webhook subscription

GET </admin/api/2020-10/webhooks.json>

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2020-10/webhooks.json>

Create a new webhook subscription by specifying both an address and a topic

GET </admin/api/2020-10/webhooks/count.json>

Retrieves a count of existing webhook subscriptions

GET /admin/api/2020-10/webhooks/{webhook_id}.json

Retrieves a single webhook subscription

PUT /admin/api/2020-10/webhooks/{webhook_id}.json

Update a webhook subscription's topic or address URIs

DELETE /admin/api/2020-10/webhooks/{webhook_id}.json

Delete a webhook subscription

GET </admin/api/2021-01/webhooks.json>

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/2021-01/webhooks.json>

Create a new webhook subscription by specifying both an address and a topic

GET </admin/api/2021-01/webhooks/count.json>

Retrieves a count of existing webhook subscriptions

GET /admin/api/2021-01/webhooks/{webhook_id}.json

Retrieves a single webhook subscription

PUT /admin/api/2021-01/webhooks/{webhook_id}.json

Update a webhook subscription's topic or address URIs

DELETE /admin/api/2021-01/webhooks/{webhook_id}.json

Delete a webhook subscription

GET </admin/api/unstable/webhooks.json>

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

POST </admin/api/unstable/webhooks.json>

Create a new webhook subscription by specifying both an address and a topic

GET </admin/api/unstable/webhooks/count.json>

Retrieves a count of existing webhook subscriptions

GET /admin/api/unstable/webhooks/{webhook_id}.json

Retrieves a single webhook subscription

PUT /admin/api/unstable/webhooks/{webhook_id}.json

Update a webhook subscription's topic or address URIs

DELETE /admin/api/unstable/webhooks/{webhook_id}.json

Delete a webhook subscription

REST Api

Retrieves a list of access scopes associated to the access token.

<https://shopify.dev/docs/admin-api/rest/reference/access/accessscope#index-2020-10>

Method GET
Path /admin/oauth/access_scopes.json

Responses

Response 200 No description available

Retrieves a list of storefront access tokens that have been issued

<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-2020-01>

Method GET
Path /admin/api/2020-01/storefront_access_tokens.json

Responses

Response 200 No description available

Creates a new storefront access token

<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-2020-01>

Method POST
Path /admin/api/2020-01/storefront_access_tokens.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Deletes an existing storefront access token

<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-2020-01>

Method DELETE
Path /admin/api/2020-01/storefront_access_tokens/{storefront_access_token_id}.json

Parameters

Parameter	About	Description
storefront_access_token_id	Required	storefront_access_token_id

Responses

Response 200 No description available

Retrieves a list of storefront access tokens that have been issued

<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-2020-04>

Method GET
Path /admin/api/2020-04/storefront_access_tokens.json

Responses

Response 200 No description available

Creates a new storefront access token

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-2020-04

Method POST
Path /admin/api/2020-04/storefront_access_tokens.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes an existing storefront access token

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-2020-04

Method DELETE
Path /admin/api/2020-04/storefront_access_tokens/{storefront_access_token_id}.json

Parameters

Parameter	About	Description
storefront_access_token_id	Required	storefront_access_token_id

Responses

Response 200 No description available

Retrieves a list of storefront access tokens that have been issued

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-2020-07

Method GET
Path /admin/api/2020-07/storefront_access_tokens.json

Responses

Response 200 No description available

Creates a new storefront access token

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-2020-07

Method POST
Path /admin/api/2020-07/storefront_access_tokens.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes an existing storefront access token

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-2020-07

Method DELETE
Path /admin/api/2020-07/storefront_access_tokens/{storefront_access_token_id}.json

Parameters

Parameter	About	Description
storefront_access_token_id	Required	storefront_access_token_id

Responses

Response 200 No description available

Retrieves a list of storefront access tokens that have been issued

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-2020-10

Method GET
Path /admin/api/2020-10/storefront_access_tokens.json

Responses

Response 200 No description available

Creates a new storefront access token

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-2020-10

Method POST
Path /admin/api/2020-10/storefront_access_tokens.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Deletes an existing storefront access token

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-2020-10

Method DELETE
Path /admin/api/2020-10/storefront_access_tokens/{storefront_access_token_id}.json

Parameters

Parameter	About	Description
storefront_access_token_id	Required	storefront_access_token_id

Responses

Response 200 No description available

Retrieves a list of storefront access tokens that have been issued

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-2021-01

Method GET
Path /admin/api/2021-01/storefront_access_tokens.json

Responses

Response 200 No description available

Creates a new storefront access token

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-2021-01

Method POST
Path /admin/api/2021-01/storefront_access_tokens.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes an existing storefront access token

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-2021-01

Method DELETE
Path /admin/api/2021-01/storefront_access_tokens/{storefront_access_token_id}.json

Parameters

Parameter	About	Description
storefront_access_token_id	Required	storefront_access_token_id

Responses

Response 200 No description available

Retrieves a list of storefront access tokens that have been issued

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#index-unstable

Method GET
Path /admin/api/unstable/storefront_access_tokens.json

Responses

Response 200 No description available

Creates a new storefront access token

https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#create-unstable

Method POST
Path /admin/api/unstable/storefront_access_tokens.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes an existing storefront access token

<https://shopify.dev/docs/admin-api/rest/reference/access/storefrontaccesstoken#destroy-unstable>

Method DELETE
Path /admin/api/unstable/storefront_access_tokens/{storefront_access_token_id}.json

Parameters

Parameter	About	Description
storefront_access_token_id	Required	storefront_access_token_id

Responses

Response 200 No description available

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-2020-01>

Method GET
Path /admin/api/2020-01/reports.json

Parameters

Parameter	About	Description
ids	Optional	A comma-separated list of report IDs.
limit	Optional	The amount of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_min	Optional	Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates a new report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-2020-01>

Method POST
Path /admin/api/2020-01/reports.json

Parameters

Parameter	About	Description
name	Optional	The name of the report. Maximum length: 255 characters.
shopify_ql	Optional	The ShopifyQL the report will query.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined Example: <pre>null</pre>

Responses

Response 200 No description available

Retrieves a single report created by your app

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-2020-01>

Method GET
Path /admin/api/2020-01/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Updates a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-2020-01>

Method	PUT
Path	/admin/api/2020-01/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Deletes a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-2020-01>

Method	DELETE
Path	/admin/api/2020-01/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-2020-04>

Method	GET
Path	/admin/api/2020-04/reports.json

Parameters

Parameter	About	Description
ids	Optional	A comma-separated list of report IDs.
limit	Optional	The amount of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_min	Optional	Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a new report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-2020-04>

Method	POST
Path	/admin/api/2020-04/reports.json

Parameters

Parameter	About	Description
name	Optional	The name of the report. Maximum length: 255 characters.
shopify_ql	Optional	The ShopifyQL the report will query.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single report created by your app

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-2020-04>

Method	GET
Path	/admin/api/2020-04/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Updates a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-2020-04>

Method	PUT
Path	/admin/api/2020-04/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Deletes a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-2020-04>

Method DELETE
Path /admin/api/2020-04/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-2020-07>

Method GET
Path /admin/api/2020-07/reports.json

Parameters

Parameter	About	Description
ids	Optional	A comma-separated list of report IDs.
limit	Optional	The amount of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_min	Optional	Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a new report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-2020-07>

Method POST
Path /admin/api/2020-07/reports.json

Parameters

Parameter	About	Description
name	Optional	The name of the report. Maximum length: 255 characters.
shopify_ql	Optional	The ShopifyQL the report will query.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single report created by your app

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-2020-07>

Method GET
Path /admin/api/2020-07/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Updates a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-2020-07>

Method	PUT
Path	/admin/api/2020-07/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Deletes a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-2020-07>

Method	DELETE
Path	/admin/api/2020-07/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-2020-10>

Method	GET
Path	/admin/api/2020-10/reports.json

Parameters

Parameter	About	Description
ids	Optional	A comma-separated list of report IDs.
limit	Optional	The amount of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_min	Optional	Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a new report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-2020-10>

Method	POST
Path	/admin/api/2020-10/reports.json

Parameters

Parameter	About	Description
name	Optional	The name of the report. Maximum length: 255 characters.
shopify_ql	Optional	The ShopifyQL the report will query.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single report created by your app

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-2020-10>

Method	GET
Path	/admin/api/2020-10/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Updates a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-2020-10>

Method	PUT
Path	/admin/api/2020-10/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Deletes a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-2020-10>

Method DELETE
Path /admin/api/2020-10/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-2021-01>

Method GET
Path /admin/api/2021-01/reports.json

Parameters

Parameter	About	Description
ids	Optional	A comma-separated list of report IDs.
limit	Optional	The amount of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_min	Optional	Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a new report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-2021-01>

Method POST
Path /admin/api/2021-01/reports.json

Parameters

Parameter	About	Description
name	Optional	The name of the report. Maximum length: 255 characters.
shopify_ql	Optional	The ShopifyQL the report will query.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single report created by your app

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-2021-01>

Method GET
Path /admin/api/2021-01/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Updates a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-2021-01>

Method	PUT
Path	/admin/api/2021-01/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Deletes a report

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-2021-01>

Method	DELETE
Path	/admin/api/2021-01/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of reports. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/analytics/report#index-unstable>

Method	GET
Path	/admin/api/unstable/reports.json

Parameters

Parameter	About	Description
ids	Optional	A comma-separated list of report IDs.
limit	Optional	The amount of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_min	Optional	Show reports last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show reports last updated before date. (format: 2014-04-25T16:15:47-04:00)
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a new report

https://shopify.dev/docs/admin-api/rest/reference/analytics/report#create-unstable

Method	POST
Path	/admin/api/unstable/reports.json

Parameters

Parameter	About	Description
name	Optional	The name of the report. Maximum length: 255 characters.
shopify_ql	Optional	The ShopifyQL the report will query.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single report created by your app

https://shopify.dev/docs/admin-api/rest/reference/analytics/report#show-unstable

Method	GET
Path	/admin/api/unstable/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Updates a report

https://shopify.dev/docs/admin-api/rest/reference/analytics/report#update-unstable

Method	PUT
Path	/admin/api/unstable/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Deletes a report

https://shopify.dev/docs/admin-api/rest/reference/analytics/report#destroy-unstable

Method DELETE
Path /admin/api/unstable/reports/{report_id}.json

Parameters

Parameter	About	Description
report_id	Required	report_id

Responses

Response 200 No description available

Retrieves a list of application charges

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-2020-01

Method GET
Path /admin/api/2020-01/application_charges.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates an application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-2020-01

Method POST
Path /admin/api/2020-01/application_charges.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves an application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-2020-01

Method GET
Path /admin/api/2020-01/application_charges/{application_charge_id}.json

Parameters

Parameter	About	Description
application_charge_id	Required	application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant."

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#activate-2020-01

Method POST
Path /admin/api/2020-01/application_charges/{application_charge_id}/activate.json

Parameters

Parameter	About	Description
application_charge_id	Required	application_charge_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a list of application charges

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-2020-04

Method GET
Path /admin/api/2020-04/application_charges.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates an application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-2020-04

Method POST
Path /admin/api/2020-04/application_charges.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves an application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-2020-04

Method GET
Path /admin/api/2020-04/application_charges/{application_charge_id}.json

Parameters

Parameter	About	Description
application_charge_id	Required	application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant."

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#activate-2020-04>

Method	POST
Path	/admin/api/2020-04/application_charges/{application_charge_id}/activate.json

Parameters

Parameter	About	Description
application_charge_id	Required	application_charge_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-2020-07>

Method	GET
Path	/admin/api/2020-07/application_charges.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-2020-07>

Method	POST
Path	/admin/api/2020-07/application_charges.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-2020-07>

Method GET
Path /admin/api/2020-07/application_charges/{application_charge_id}.json

Parameters

Parameter	About	Description
application_charge_id	Required	application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant."

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#activate-2020-07>

Method POST
Path /admin/api/2020-07/application_charges/{application_charge_id}/activate.json

Parameters

Parameter	About	Description
application_charge_id	Required	application_charge_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-2020-10>

Method GET
Path /admin/api/2020-10/application_charges.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-2020-10>

Method POST
Path /admin/api/2020-10/application_charges.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-2020-10>

Method GET
Path /admin/api/2020-10/application_charges/{application_charge_id}.json

Parameters

Parameter	About	Description
application_charge_id	Required	application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. "Activates an accepted application charge. One-time charges are now immediately activated when approved by a merchant."

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#activate-2020-10>

Method POST
Path /admin/api/2020-10/application_charges/{application_charge_id}/activate.json

Parameters

Parameter	About	Description
application_charge_id	Required	application_charge_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-2021-01>

Method GET
Path /admin/api/2021-01/application_charges.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses	
Response	200 No description available

Creates an application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-2021-01

Method	POST
Path	/admin/api/2021-01/application_charges.json

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses	
Response	200 No description available

Retrieves an application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-2021-01

Method	GET
Path	/admin/api/2021-01/application_charges/{application_charge_id}.json

Parameters		
Parameter	About	Description
application_charge_id	Required	application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses	
Response	200 No description available

Retrieves a list of application charges

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#index-unstable

Method	GET
Path	/admin/api/unstable/application_charges.json

Parameters		
Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses	
Response	200 No description available

Creates an application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#create-unstable

Method	POST
Path	/admin/api/unstable/application_charges.json

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

null

Responses

Response 200 No description available

Retrieves an application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcharge#show-unstable>

Method GET
Path /admin/api/unstable/application_charges/{application_charge_id}.json

Parameters

Parameter	About	Description
application_charge_id fields	Required Optional	application_charge_id A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Retrieves all application credits

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-2020-01>

Method GET
Path /admin/api/2020-01/application_credits.json

Parameters

Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates an application credit

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-2020-01>

Method POST
Path /admin/api/2020-01/application_credits.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

null

Responses

Response 200 No description available

Retrieves a single application credit

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-2020-01>

Method GET
Path /admin/api/2020-01/application_credits/{application_credit_id}.json

Parameters

Parameter	About	Description
application_credit_id fields	Required Optional	application_credit_id A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Retrieves all application credits

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-2020-04>

Method	GET
Path	/admin/api/2020-04/application_credits.json

Parameters

Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates an application credit

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-2020-04>

Method	POST
Path	/admin/api/2020-04/application_credits.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single application credit

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-2020-04>

Method	GET
Path	/admin/api/2020-04/application_credits/{application_credit_id}.json

Parameters

Parameter	About	Description
application_credit_id	Required	application_credit_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Retrieves all application credits

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-2020-07>

Method	GET
Path	/admin/api/2020-07/application_credits.json

Parameters

Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates an application credit

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-2020-07

Method POST
Path /admin/api/2020-07/application_credits.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a single application credit

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-2020-07

Method GET
Path /admin/api/2020-07/application_credits/{application_credit_id}.json

Parameters

Parameter	About	Description
application_credit_id	Required	application_credit_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Retrieves all application credits

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-2020-10

Method GET
Path /admin/api/2020-10/application_credits.json

Parameters

Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates an application credit

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-2020-10

Method POST
Path /admin/api/2020-10/application_credits.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a single application credit

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-2020-10

Method	GET	
Path	/admin/api/2020-10/application_credits/{application_credit_id}.json	
Parameters		
Parameter	About	Description
application_credit_id	Required	application_credit_id
fields	Optional	A comma-separated list of fields to include in the response.
Responses		
Response	200 No description available	

Retrieves all application credits

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-2021-01

Method	GET	
Path	/admin/api/2021-01/application_credits.json	
Parameters		
Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.
Responses		
Response	200 No description available	

Creates an application credit

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-2021-01

Method	POST
Path	/admin/api/2021-01/application_credits.json
Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>
Responses	
Response	200 No description available

Retrieves a single application credit

https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-2021-01

Method	GET	
Path	/admin/api/2021-01/application_credits/{application_credit_id}.json	
Parameters		
Parameter	About	Description
application_credit_id	Required	application_credit_id
fields	Optional	A comma-separated list of fields to include in the response.
Responses		
Response	200 No description available	

Retrieves all application credits

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#index-unstable>

Method GET
Path /admin/api/unstable/application_credits.json

Parameters

Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates an application credit

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#create-unstable>

Method POST
Path /admin/api/unstable/application_credits.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves a single application credit

<https://shopify.dev/docs/admin-api/rest/reference/billing/applicationcredit#show-unstable>

Method GET
Path /admin/api/unstable/application_credits/{application_credit_id}.json

Parameters

Parameter	About	Description
application_credit_id	Required	application_credit_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Retrieves a list of recurring application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-2020-01>

Method GET
Path /admin/api/2020-01/recurring_application_charges.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-2020-01>

Method POST
Path /admin/api/2020-01/recurring_application_charges.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-2020-01>

Method GET
Path /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Cancels a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-2020-01>

Method DELETE
Path /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Responses

Response 200 No description available

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#activate-2020-01>

Method POST
Path /admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/activate.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Request Body

Required No
Description No description available
Content-type application/json

Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Updates the capped amount of an active recurring application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-2020-01

Method	PUT
Path	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/customize.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
recurring_application_charge[capped_amount]	Optional	recurring_application_charge[capped_amount]

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of recurring application charges

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-2020-04

Method	GET
Path	/admin/api/2020-04/recurring_application_charges.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a recurring application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-2020-04

Method	POST
Path	/admin/api/2020-04/recurring_application_charges.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single charge

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-2020-04

Method	GET
Path	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Cancels a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-2020-04>

Method	DELETE
Path	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Responses

Response	200 No description available
----------	------------------------------

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#activate-2020-04>

Method	POST
Path	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/activate.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Updates the capped amount of an active recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-2020-04>

Method	PUT
Path	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/customize.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
recurring_application_charge[capped_amount]	Optional	recurring_application_charge[capped_amount]

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of recurring application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-2020-07>

Method	GET
Path	/admin/api/2020-07/recurring_application_charges.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-2020-07>

Method	POST
Path	/admin/api/2020-07/recurring_application_charges.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-2020-07>

Method	GET
Path	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Cancels a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-2020-07>

Method	DELETE
Path	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Responses

Response	200 No description available
----------	------------------------------

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#activate-2020-07>

Method	POST
Path	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/activate.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Updates the capped amount of an active recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-2020-07>

Method	PUT
Path	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/customize.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
recurring_application_charge[capped_amount]	Optional	recurring_application_charge[capped_amount]

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of recurring application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-2020-10>

Method	GET
Path	/admin/api/2020-10/recurring_application_charges.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-2020-10>

Method POST
Path /admin/api/2020-10/recurring_application_charges.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-2020-10>

Method GET
Path /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Cancels a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-2020-10>

Method DELETE
Path /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Responses

Response 200 No description available

Caution This endpoint is no longer required and is deprecated as of API version 2021-01. Activates a previously accepted recurring application charge. Recurring charges are now immediately activated when approved by a merchant.

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#activate-2020-10>

Method POST
Path /admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/activate.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Request Body

Required No
Description No description available
Content-type application/json

Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Updates the capped amount of an active recurring application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-2020-10

Method	PUT
Path	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/customize.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
recurring_application_charge[capped_amount]	Optional	recurring_application_charge[capped_amount]

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of recurring application charges

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-2021-01

Method	GET
Path	/admin/api/2021-01/recurring_application_charges.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a recurring application charge

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-2021-01

Method	POST
Path	/admin/api/2021-01/recurring_application_charges.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single charge

https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-2021-01

Method	GET
Path	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Cancels a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-2021-01>

Method	DELETE
Path	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields		

Responses

Response	200 No description available
----------	------------------------------

Updates the capped amount of an active recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-2021-01>

Method	PUT
Path	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/customize.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
recurring_application_charge[capped_amount]	Optional	recurring_application_charge[capped_amount]
fields		

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of recurring application charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#index-unstable>

Method	GET
Path	/admin/api/unstable/recurring_application_charges.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#create-unstable>

Method	POST
Path	/admin/api/unstable/recurring_application_charges.json

Request Body

Required	No
----------	----

Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#show-unstable>

Method	GET
Path	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
-----------------	------------------------------

Cancels a recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#destroy-unstable>

Method	DELETE
Path	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Responses

Response	200 No description available
-----------------	------------------------------

Updates the capped amount of an active recurring application charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/recurringapplicationcharge#customize-unstable>

Method	PUT
Path	/admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/customize.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
recurring_application_charge[capped_amount]	Optional	recurring_application_charge[capped_amount]

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of usage charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-2020-01>

Method	GET
Path	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a usage charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-2020-01>

Method	POST
Path	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields		

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-2020-01>

Method	GET
Path	/admin/api/2020-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
usage_charge_id	Required	usage_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of usage charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-2020-04>

Method	GET
Path	/admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates a usage charge

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-2020-04

Method POST
Path /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

Retrieves a single charge

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-2020-04

Method GET
Path /admin/api/2020-04/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
usage_charge_id	Required	usage_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Retrieves a list of usage charges

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-2020-07

Method GET
Path /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates a usage charge

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-2020-07

Method POST
Path /admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-2020-07>

Method	GET
Path	/admin/api/2020-07/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
usage_charge_id	Required	usage_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of usage charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-2020-10>

Method	GET
Path	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a usage charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-2020-10>

Method	POST
Path	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Request Body

Required	No
----------	----

Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-2020-10>

Method	GET
Path	/admin/api/2020-10/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
usage_charge_id	Required	usage_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of usage charges

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-2021-01>

Method	GET
Path	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
-----------------	------------------------------

Creates a usage charge

<https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-2021-01>

Method	POST
Path	/admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a single charge

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-2021-01

Method GET
Path /admin/api/2021-01/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
usage_charge_id	Required	usage_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Retrieves a list of usage charges

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#index-unstable

Method GET
Path /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates a usage charge

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#create-unstable

Method POST
Path /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response 200 No description available

Retrieves a single charge

https://shopify.dev/docs/admin-api/rest/reference/billing/usagecharge#show-unstable

Method GET
Path /admin/api/unstable/recurring_application_charges/{recurring_application_charge_id}/usage_charges/{usage_charge_id}.json

Parameters

Parameter	About	Description
recurring_application_charge_id	Required	recurring_application_charge_id
usage_charge_id	Required	usage_charge_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-2020-01>

Method	GET
Path	/admin/api/2020-01/customers.json

Parameters

Parameter	About	Description
ids	Optional	Restrict results to customers specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to those after the specified ID.
created_at_min	Optional	Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Creates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-2020-01>

Method	POST
Path	/admin/api/2020-01/customers.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-2020-01>

Method	GET
Path	/admin/api/2020-01/customers/search.json

Parameters

Parameter	About	Description
order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
query	Optional	Text to search for in the shop's customer data.
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-2020-01>

Method	GET
Path	/admin/api/2020-01/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-2020-01>

Method	PUT
Path	/admin/api/2020-01/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Deletes a customer. A customer can't be deleted if they have existing orders.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-2020-01>

Method	DELETE
Path	/admin/api/2020-01/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response	200 No description available
----------	------------------------------

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-2020-01

Method POST
Path /admin/api/2020-01/customers/{customer_id}/account_activation_url.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Sends an account invite to a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-2020-01

Method POST
Path /admin/api/2020-01/customers/{customer_id}/send_invite.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of all customers.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-2020-01>

Method GET
Path /admin/api/2020-01/customers/count.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-2020-01>

Method GET
Path /admin/api/2020-01/customers/{customer_id}/orders.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response 200 No description available

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-2020-04>

Method GET
Path /admin/api/2020-04/customers.json

Parameters

Parameter	About	Description
ids	Optional	Restrict results to customers specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to those after the specified ID.
created_at_min	Optional	Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-2020-04>

Method POST
Path /admin/api/2020-04/customers.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the

response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-2020-04

Method GET
Path /admin/api/2020-04/customers/search.json

Parameters

Parameter	About	Description
order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
query	Optional	Text to search for in the shop's customer data.
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a single customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-2020-04

Method GET
Path /admin/api/2020-04/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-2020-04

Method PUT
Path /admin/api/2020-04/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Deletes a customer. A customer can't be deleted if they have existing orders.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-2020-04

Method DELETE
Path /admin/api/2020-04/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response 200 No description available

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-2020-04

Method POST
Path /admin/api/2020-04/customers/{customer_id}/account_activation_url.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Sends an account invite to a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-2020-04

Method POST
Path /admin/api/2020-04/customers/{customer_id}/send_invite.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves a count of all customers.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-2020-04>

Method GET
Path /admin/api/2020-04/customers/count.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-2020-04>

Method	GET
Path	/admin/api/2020-04/customers/{customer_id}/orders.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-2020-07>

Method	GET
Path	/admin/api/2020-07/customers.json

Parameters

Parameter	About	Description
ids	Optional	Restrict results to customers specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to those after the specified ID.
created_at_min	Optional	Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Creates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-2020-07>

Method	POST
Path	/admin/api/2020-07/customers.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-2020-07

Method GET
Path /admin/api/2020-07/customers/search.json

Parameters

Parameter	About	Description
order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
query	Optional	Text to search for in the shop's customer data.
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a single customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-2020-07

Method GET
Path /admin/api/2020-07/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-2020-07

Method PUT
Path /admin/api/2020-07/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Deletes a customer. A customer can't be deleted if they have existing orders.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-2020-07

Method DELETE
Path /admin/api/2020-07/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response	200 No description available
----------	------------------------------

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-2020-07

Method	POST
Path	/admin/api/2020-07/customers/{customer_id}/account_activation_url.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Sends an account invite to a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-2020-07

Method	POST
Path	/admin/api/2020-07/customers/{customer_id}/send_invite.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of all customers.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-2020-07>

Method GET
Path /admin/api/2020-07/customers/count.json

Responses

Response 200 No description available

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-2020-07>

Method GET
Path /admin/api/2020-07/customers/{customer_id}/orders.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response 200 No description available

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-2020-10>

Method GET
Path /admin/api/2020-10/customers.json

Parameters

Parameter	About	Description
ids	Optional	Restrict results to customers specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to those after the specified ID.
created_at_min	Optional	Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-2020-10>

Method POST
Path /admin/api/2020-10/customers.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-2020-10>

Method	GET
Path	/admin/api/2020-10/customers/search.json

Parameters

Parameter	About	Description
order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
query	Optional	Text to search for in the shop's customer data.
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-2020-10>

Method	GET
Path	/admin/api/2020-10/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-2020-10>

Method	PUT
Path	/admin/api/2020-10/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Deletes a customer. A customer can't be deleted if they have existing orders.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-2020-10>

Method DELETE
Path /admin/api/2020-10/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response 200 No description available

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-2020-10

Method POST
Path /admin/api/2020-10/customers/{customer_id}/account_activation_url.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Sends an account invite to a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-2020-10

Method POST
Path /admin/api/2020-10/customers/{customer_id}/send_invite.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of all customers.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-2020-10>

Method GET
Path /admin/api/2020-10/customers/count.json

Responses

Response 200 No description available

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-2020-10>

Method GET
Path /admin/api/2020-10/customers/{customer_id}/orders.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response 200 No description available

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-2021-01>

Method GET
Path /admin/api/2021-01/customers.json

Parameters

Parameter	About	Description
ids	Optional	Restrict results to customers specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to those after the specified ID.
created_at_min	Optional	Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-2021-01>

Method POST
Path /admin/api/2021-01/customers.json

Request Body

Required	No
Description	No description available
Content-type	application/json

Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-2021-01

Method	GET
Path	/admin/api/2021-01/customers/search.json

Parameters

Parameter	About	Description
order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
query	Optional	Text to search for in the shop's customer data.
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-2021-01

Method	GET
Path	/admin/api/2021-01/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-2021-01

Method	PUT
Path	/admin/api/2021-01/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Deletes a customer. A customer can't be deleted if they have existing orders.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-2021-01>

Method DELETE
Path /admin/api/2021-01/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response	200 No description available
----------	------------------------------

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-2021-01

Method POST
Path /admin/api/2021-01/customers/{customer_id}/account_activation_url.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Sends an account invite to a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-2021-01

Method POST
Path /admin/api/2021-01/customers/{customer_id}/send_invite.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of all customers.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-2021-01>

Method	GET
Path	/admin/api/2021-01/customers/count.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-2021-01>

Method	GET
Path	/admin/api/2021-01/customers/{customer_id}/orders.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of customers. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#index-unstable>

Method	GET
Path	/admin/api/unstable/customers.json

Parameters

Parameter	About	Description
ids	Optional	Restrict results to customers specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to those after the specified ID.
created_at_min	Optional	Show customers created after a specified date.(format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show customers created before a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show customers last updated after a specified date.(format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show customers last updated before a specified date.(format: 2014-04-25T16:15:47-04:00)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Creates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#create-unstable>

Method	POST
Path	/admin/api/unstable/customers.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Searches for customers that match a supplied query. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#search-unstable>

Method	GET
Path	/admin/api/unstable/customers/search.json

Parameters

Parameter	About	Description
order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
query	Optional	Text to search for in the shop's customer data.
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#show-unstable>

Method	GET
Path	/admin/api/unstable/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#update-unstable>

Method	PUT
Path	/admin/api/unstable/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

null

Responses

Response	200 No description available
----------	------------------------------

Deletes a customer. A customer can't be deleted if they have existing orders.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#destroy-unstable>

Method	DELETE
Path	/admin/api/unstable/customers/{customer_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response	200 No description available
----------	------------------------------

Generate an account activation URL for a customer whose account is not yet enabled. This is useful when you've imported a large number of customers and want to send them activation emails all at once. Using this approach, you'll need to generate and send the activation emails yourself. The account activation URL generated by this endpoint is for one-time use and will expire after 30 days. If you make a new POST request to this endpoint, then a new URL will be generated. The new URL will be again valid for 30 days, but the previous URL will no longer be valid.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#account_activation_url-unstable

Method	POST
Path	/admin/api/unstable/customers/{customer_id}/account_activation_url.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

null

Responses

Response	200 No description available
----------	------------------------------

Sends an account invite to a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer#send_invite-unstable

Method	POST
Path	/admin/api/unstable/customers/{customer_id}/send_invite.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required Description	No
Content-type	No description available
Schema for application/json	application/json
	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of all customers.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#count-unstable>

Method	GET
Path	/admin/api/unstable/customers/count.json

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves all orders belonging to a customer. The query string parameters that are available to the Order resource are also available to this endpoint.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer#orders-unstable>

Method	GET
Path	/admin/api/unstable/customers/{customer_id}/orders.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-2020-01>

Method	GET
Path	/admin/api/2020-01/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response	200 No description available
-----------------	------------------------------

Creates a new address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-2020-01>

Method	POST
Path	/admin/api/2020-01/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Retrieves details a single customer address.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-2020-01

Method	GET
Path	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response	200 No description available
----------	------------------------------

Updates an existing customer address.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-2020-01

Method	PUT
Path	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Removes an address from a customer’s address list.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-2020-01

Method	DELETE
Path	/admin/api/2020-01/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response	200 No description available
----------	------------------------------

Performs bulk operations for multiple customer addresses.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-2020-01>

Method PUT
Path /admin/api/2020-01/customers/{customer_id}/addresses/set.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_ids[]	Optional	address_ids[]
operation	Optional	operation

Responses

Response 200 No description available

Sets the default address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-2020-01>

Method PUT
Path /admin/api/2020-01/customers/{customer_id}/addresses/{address_id}/default.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response 200 No description available

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-2020-04>

Method GET
Path /admin/api/2020-04/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response 200 No description available

Creates a new address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-2020-04>

Method POST
Path /admin/api/2020-04/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

null

Responses

Response 200 No description available

Retrieves details a single customer address.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-2020-04>

Method GET
Path /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response 200 No description available

Updates an existing customer address.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-2020-04>

Method PUT
Path /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

null

Responses

Response 200 No description available

Removes an address from a customer's address list.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-2020-04>

Method DELETE
Path /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response 200 No description available

Performs bulk operations for multiple customer addresses.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-2020-04>

Method PUT

Path /admin/api/2020-04/customers/{customer_id}/addresses/set.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_ids[]	Optional	address_ids[]
operation	Optional	operation

Responses

Response 200 No description available

Sets the default address for a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-2020-04

Method PUT
Path /admin/api/2020-04/customers/{customer_id}/addresses/{address_id}/default.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response 200 No description available

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-2020-07

Method GET
Path /admin/api/2020-07/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response 200 No description available

Creates a new address for a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-2020-07

Method POST
Path /admin/api/2020-07/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves details a single customer address.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-2020-07

Method GET
Path /admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response 200 No description available

Updates an existing customer address.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-2020-07

Method PUT
Path /admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Removes an address from a customer's address list.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-2020-07

Method DELETE
Path /admin/api/2020-07/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response 200 No description available

Performs bulk operations for multiple customer addresses.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-2020-07

Method PUT
Path /admin/api/2020-07/customers/{customer_id}/addresses/set.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_ids[]	Optional	address_ids[]
operation	Optional	operation

Responses

Response	200 No description available
----------	------------------------------

Sets the default address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-2020-07>

Method	PUT
Path	/admin/api/2020-07/customers/{customer_id}/addresses/{address_id}/default.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-2020-10>

Method	GET
Path	/admin/api/2020-10/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response	200 No description available
----------	------------------------------

Creates a new address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-2020-10>

Method	POST
Path	/admin/api/2020-10/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Retrieves details a single customer address.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-2020-10

Method GET
Path /admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response 200 No description available

Updates an existing customer address.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-2020-10

Method PUT
Path /admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Removes an address from a customer's address list.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-2020-10

Method DELETE
Path /admin/api/2020-10/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response 200 No description available

Performs bulk operations for multiple customer addresses.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-2020-10

Method PUT
Path /admin/api/2020-10/customers/{customer_id}/addresses/set.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_ids[]	Optional	address_ids[]
operation	Optional	operation

Responses

Response	200 No description available
----------	------------------------------

Sets the default address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-2020-10>

Method	PUT
Path	/admin/api/2020-10/customers/{customer_id}/addresses/{address_id}/default.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-2021-01>

Method	GET
Path	/admin/api/2021-01/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response	200 No description available
----------	------------------------------

Creates a new address for a customer.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-2021-01>

Method	POST
Path	/admin/api/2021-01/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves details a single customer address.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-2021-01>

Method	GET
--------	-----

Path	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json	
Parameters		
Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id
Responses		
Response	200 No description available	

Updates an existing customer address.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-2021-01

Method	PUT	
Path	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json	
Parameters		
Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
	Example:	
	null	
Responses		
Response	200 No description available	

Removes an address from a customer's address list.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-2021-01

Method	DELETE	
Path	/admin/api/2021-01/customers/{customer_id}/addresses/{address_id}.json	
Parameters		
Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id
Responses		
Response	200 No description available	

Performs bulk operations for multiple customer addresses.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-2021-01

Method	PUT	
Path	/admin/api/2021-01/customers/{customer_id}/addresses/set.json	
Parameters		
Parameter	About	Description
customer_id	Required	customer_id
address_ids[]	Optional	address_ids[]
operation	Optional	operation
Responses		
Response	200 No description available	

Sets the default address for a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-2021-01

Method PUT
Path /admin/api/2021-01/customers/{customer_id}/addresses/{address_id}/default.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response 200 No description available

Retrieves a list of addresses for a customer. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#index-unstable

Method GET
Path /admin/api/unstable/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Responses

Response 200 No description available

Creates a new address for a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#create-unstable

Method POST
Path /admin/api/unstable/customers/{customer_id}/addresses.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

Retrieves details a single customer address.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#show-unstable

Method GET
Path /admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
-----------	-------	-------------

customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response	200 No description available
----------	------------------------------

Updates an existing customer address.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#update-unstable

Method	PUT
Path	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Removes an address from a customer’s address list.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#destroy-unstable

Method	DELETE
Path	/admin/api/unstable/customers/{customer_id}/addresses/{address_id}.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response	200 No description available
----------	------------------------------

Performs bulk operations for multiple customer addresses.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#set-unstable

Method	PUT
Path	/admin/api/unstable/customers/{customer_id}/addresses/set.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_ids[]	Optional	address_ids[]
operation	Optional	operation

Responses

Response	200 No description available
----------	------------------------------

Sets the default address for a customer.

https://shopify.dev/docs/admin-api/rest/reference/customers/customer-address#default-unstable

Method PUT
Path /admin/api/unstable/customers/{customer_id}/addresses/{address_id}/default.json

Parameters

Parameter	About	Description
customer_id	Required	customer_id
address_id	Required	address_id

Responses

Response 200 No description available

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-2020-01>

Method GET
Path /admin/api/2020-01/customer_saved_searches.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-2020-01>

Method POST
Path /admin/api/2020-01/customer_saved_searches.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of all customer saved searches.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-2020-01>

Method GET
Path /admin/api/2020-01/customer_saved_searches/count.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID

Responses

Response 200 No description available

Retrieves a single customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-2020-01

Method GET
Path /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates a customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-2020-01

Method PUT
Path /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Deletes a customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-2020-01

Method DELETE
Path /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Responses

Response 200 No description available

Retrieves all customers returned by a customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-2020-01

Method GET
Path /admin/api/2020-01/customer_saved_searches/{customer_saved_search_id}/customers.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-2020-04>

Method	GET
Path	/admin/api/2020-04/customer_saved_searches.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Creates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-2020-04>

Method	POST
Path	/admin/api/2020-04/customer_saved_searches.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of all customer saved searches.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-2020-04>

Method	GET
Path	/admin/api/2020-04/customer_saved_searches/count.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-2020-04>

Method	GET
---------------	-----

Path /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-2020-04>

Method PUT
Path /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Deletes a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-2020-04>

Method DELETE
Path /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Responses

Response 200 No description available

Retrieves all customers returned by a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-2020-04>

Method GET
Path /admin/api/2020-04/customer_saved_searches/{customer_saved_search_id}/customers.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id
order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-2020-07>

Method GET
Path /admin/api/2020-07/customer_saved_searches.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-2020-07>

Method POST
Path /admin/api/2020-07/customer_saved_searches.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

Retrieves a count of all customer saved searches.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-2020-07>

Method GET
Path /admin/api/2020-07/customer_saved_searches/count.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID

Responses

Response 200 No description available

Retrieves a single customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-2020-07>

Method GET
Path /admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
-----------	-------	-------------

customer_saved_search_id	Required	customer_saved_search_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates a customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-2020-07

Method	PUT
Path	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Deletes a customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-2020-07

Method	DELETE
Path	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves all customers returned by a customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-2020-07

Method	GET
Path	/admin/api/2020-07/customer_saved_searches/{customer_saved_search_id}/customers.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id
order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-2020-10>

Method GET
Path /admin/api/2020-10/customer_saved_searches.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-2020-10>

Method POST
Path /admin/api/2020-10/customer_saved_searches.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

Retrieves a count of all customer saved searches.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-2020-10>

Method GET
Path /admin/api/2020-10/customer_saved_searches/count.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID

Responses

Response 200 No description available

Retrieves a single customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-2020-10>

Method GET
Path /admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-2020-10>

Method	PUT
Path	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Deletes a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-2020-10>

Method	DELETE
Path	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves all customers returned by a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-2020-10>

Method	GET
Path	/admin/api/2020-10/customer_saved_searches/{customer_saved_search_id}/customers.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id
order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response

header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-2021-01>

Method GET
Path /admin/api/2021-01/customer_saved_searches.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-2021-01>

Method POST
Path /admin/api/2021-01/customer_saved_searches.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a count of all customer saved searches.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-2021-01>

Method GET
Path /admin/api/2021-01/customer_saved_searches/count.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID

Responses

Response 200 No description available

Retrieves a single customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-2021-01>

Method GET
Path /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-2021-01>

Method PUT
Path /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Deletes a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-2021-01>

Method DELETE
Path /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Responses

Response 200 No description available

Retrieves all customers returned by a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-2021-01>

Method GET
Path /admin/api/2021-01/customer_saved_searches/{customer_saved_search_id}/customers.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id
order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a list of customer saved searches. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#index-unstable>

Method GET
Path /admin/api/unstable/customer_saved_searches.json

Parameters		
Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
Responses		
Response	200 No description available	

Creates a customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#create-unstable

Method	POST
Path	/admin/api/unstable/customer_saved_searches.json
Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses	
Response	200 No description available

Retrieves a count of all customer saved searches.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#count-unstable

Method	GET	
Path	/admin/api/unstable/customer_saved_searches/count.json	
Parameters		
Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID

Responses	
Response	200 No description available

Retrieves a single customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#show-unstable

Method

Path

GET

/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses	
Response	200 No description available

Updates a customer saved search.

https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#update-unstable

Method	PUT
Path	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Deletes a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#destroy-unstable>

Method	DELETE
Path	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves all customers returned by a customer saved search.

<https://shopify.dev/docs/admin-api/rest/reference/customers/customersavedsearch#other-unstable>

Method	GET
Path	/admin/api/unstable/customer_saved_searches/{customer_saved_search_id}/customers.json

Parameters

Parameter	About	Description
customer_saved_search_id	Required	customer_saved_search_id
order	Optional	Set the field and direction by which to order results. (default: last_order_date DESC)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of deprecated API calls made by the authenticated private app in the past 30 days.

https://shopify.dev/docs/admin-api/rest/reference/deprecated_api_calls#index-2021-01

Method	GET
Path	/admin/api/2021-01/deprecated_api_calls.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of deprecated API calls made by the authenticated private app in the past 30 days.

https://shopify.dev/docs/admin-api/rest/reference/deprecated_api_calls#index-unstable

Method GET
Path /admin/api/unstable/deprecated_api_calls.json

Responses

Response 200 No description available

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-2020-01>

Method GET
Path /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Responses

Response 200 No description available

Creates a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-2020-01>

Method POST
Path /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a single discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-2020-01>

Method GET
Path /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses

Response 200 No description available

Updates an existing discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-2020-01

Method PUT
Path /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Deletes a discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-2020-01

Method DELETE
Path /admin/api/2020-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-2020-01

Method GET
Path /admin/api/2020-01/discount_codes/lookup.json

Parameters

Parameter	About	Description
code	Optional	code

Responses

Response	200 No description available
----------	------------------------------

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job

has finished. **codes_count**: The number of discount codes to create. **imported_count**: The number of discount codes created successfully. **failed_count**: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. **logs**: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-2020-01

Method POST
Path /admin/api/2020-01/price_rules/{price_rule_id}/batch.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a discount code creation job

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-2020-01

Method GET
Path /admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response 200 No description available

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-2020-01

Method GET
Path /admin/api/2020-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response 200 No description available

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-2020-04

Method GET
Path /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Responses

Response 200 No description available

Creates a discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-2020-04

Method POST
Path /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a single discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-2020-04

Method GET
Path /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses

Response 200 No description available

Updates an existing discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-2020-04

Method PUT
Path /admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
-----------	-------	-------------

price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Deletes a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-2020-04>

Method	DELETE
Path	/admin/api/2020-04/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-2020-04>

Method	GET
Path	/admin/api/2020-04/discount_codes/lookup.json

Parameters

Parameter	About	Description
code	Optional	code

Responses

Response	200 No description available
----------	------------------------------

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses:

"Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-2020-04

Method POST
Path /admin/api/2020-04/price_rules/{price_rule_id}/batch.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a discount code creation job

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-2020-04

Method GET
Path /admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response 200 No description available

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-2020-04

Method GET
Path /admin/api/2020-04/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response 200 No description available

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-2020-07

Method GET
Path /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Responses

Response 200 No description available

Creates a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-2020-07>

Method POST
Path /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a single discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-2020-07>

Method GET
Path /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses

Response 200 No description available

Updates an existing discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-2020-07>

Method PUT
Path /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Request Body

Required	No
Description	No description available
Content-type	application/json

Schema for application/json

Type: undefined

Example:

null

Responses

Response 200 No description available

Deletes a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-2020-07>

Method DELETE
Path /admin/api/2020-07/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses

Response 200 No description available

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-2020-07>

Method GET
Path /admin/api/2020-07/discount_codes/lookup.json

Parameters

Parameter	About	Description
code	Optional	code

Responses

Response 200 No description available

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-2020-07

Method POST
Path /admin/api/2020-07/price_rules/{price_rule_id}/batch.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre> null </pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a discount code creation job

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-2020-07

Method	GET
Path	/admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-2020-07

Method	GET
Path	/admin/api/2020-07/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response	200 No description available
----------	------------------------------

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-2020-10>

Method	GET
Path	/admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Responses

Response 200 No description available

Creates a discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-2020-10

Method POST
Path /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a single discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-2020-10

Method GET
Path /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses

Response 200 No description available

Updates an existing discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-2020-10

Method PUT
Path /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-2020-10>

Method DELETE
Path /admin/api/2020-10/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses

Response 200 No description available

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-2020-10>

Method GET
Path /admin/api/2020-10/discount_codes/lookup.json

Parameters

Parameter	About	Description
code	Optional	code

Responses

Response 200 No description available

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-2020-10

Method POST
Path /admin/api/2020-10/price_rules/{price_rule_id}/batch.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

null

Responses

Response 200 No description available

Retrieves a discount code creation job

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-2020-10

Method GET
Path /admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response 200 No description available

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-2020-10

Method GET
Path /admin/api/2020-10/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response 200 No description available

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-2021-01>

Method GET
Path /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Responses

Response 200 No description available

Creates a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-2021-01>

Method POST
Path /admin/api/2021-01/price_rules/{price_rule_id}/discount_codes.json

Parameters		
Parameter	About	Description
price_rule_id	Required	price_rule_id
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
	Example:	
	null	

Responses	
Response	200 No description available

Retrieves a single discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-2021-01

Method	GET
Path	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters		
Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses	
Response	200 No description available

Updates an existing discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-2021-01

Method	PUT
Path	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters		
Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses	
Response	200 No description available

Deletes a discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-2021-01

Method	DELETE
Path	/admin/api/2021-01/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters		
Parameter	About	Description

price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-2021-01

Method	GET
Path	/admin/api/2021-01/discount_codes/lookup.json

Parameters

Parameter	About	Description
code	Optional	code

Responses

Response	200 No description available
----------	------------------------------

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-2021-01

Method	POST
Path	/admin/api/2021-01/price_rules/{price_rule_id}/batch.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a discount code creation job

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-2021-01

Method GET
Path /admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response 200 No description available

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-2021-01

Method GET
Path /admin/api/2021-01/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response 200 No description available

Retrieve a list of discount codes. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#index-unstable>

Method GET
Path /admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Responses

Response 200 No description available

Creates a discount code

<https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#create-unstable>

Method POST
Path /admin/api/unstable/price_rules/{price_rule_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Request Body

Required No
Description No description available

Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#show-unstable

Method	GET
Path	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses

Response	200 No description available
-----------------	------------------------------

Updates an existing discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#update-unstable

Method	PUT
Path	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Deletes a discount code

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#destroy-unstable

Method	DELETE
Path	/admin/api/unstable/price_rules/{price_rule_id}/discount_codes/{discount_code_id}.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
discount_code_id	Required	discount_code_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves the location of a discount code. The discount code's location is returned in the location header, not in the DiscountCode object itself. Depending on your HTTP client, the location of the discount code might follow the location header automatically.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#lookup-unstable

Method GET
Path /admin/api/unstable/discount_codes/lookup.json

Parameters

Parameter	About	Description
code	Optional	code

Responses

Response 200 No description available

Creates a discount code creation job. The batch endpoint can be used to asynchronously create up to 100 discount codes in a single request. It enqueues and returns a discount_code_creation object that can be monitored for completion. Response fields that are specific to the batch endpoint include: status: The state of the discount code creation job. Possible values are: queued: The job is acknowledged, but not started. running: The job is in process. completed: The job has finished. codes_count: The number of discount codes to create. imported_count: The number of discount codes created successfully. failed_count: The number of discount codes that were not created successfully. Unsuccessful attempts will retry up to three times. logs: A report that specifies when no discount codes were created because the provided data was invalid. Example responses: "Price rule target selection can't be blank" "Price rule allocation method can't be blank"

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_create-unstable

Method POST
Path /admin/api/unstable/price_rules/{price_rule_id}/batch.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a discount code creation job

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_show-unstable

Method GET
Path /admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}.json

Parameters

Parameter	About	Description
-----------	-------	-------------

price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of discount codes for a discount code creation job. Discount codes that have been successfully created include a populated id field. Discount codes that encountered errors during the creation process include a populated errors field.

https://shopify.dev/docs/admin-api/rest/reference/discounts/discountcode#batch_discount_codes_index-unstable

Method	GET
Path	/admin/api/unstable/price_rules/{price_rule_id}/batch/{batch_id}/discount_codes.json

Parameters

Parameter	About	Description
price_rule_id	Required	price_rule_id
batch_id	Required	batch_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/event#index-2020-01>

Method	GET
Path	/admin/api/2020-01/events.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
since_id	Optional	Show only results after the specified ID.
created_at_min	Optional	Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
filter	Optional	Show events specified in this filter.
verb	Optional	Show events of a certain type.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single event by its ID

<https://shopify.dev/docs/admin-api/rest/reference/events/event#show-2020-01>

Method	GET
Path	/admin/api/2020-01/events/{event_id}.json

Parameters

Parameter	About	Description
event_id	Required	event_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of events

<https://shopify.dev/docs/admin-api/rest/reference/events/event#count-2020-01>

Method GET
Path /admin/api/2020-01/events/count.json

Parameters

Parameter	About	Description
created_at_min	Optional	Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

Response 200 No description available

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/event#index-2020-04>

Method GET
Path /admin/api/2020-04/events.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
since_id	Optional	Show only results after the specified ID.
created_at_min	Optional	Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
filter	Optional	Show events specified in this filter.
verb	Optional	Show events of a certain type.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a single event by its ID

<https://shopify.dev/docs/admin-api/rest/reference/events/event#show-2020-04>

Method GET
Path /admin/api/2020-04/events/{event_id}.json

Parameters

Parameter	About	Description
event_id	Required	event_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a count of events

<https://shopify.dev/docs/admin-api/rest/reference/events/event#count-2020-04>

Method GET
Path /admin/api/2020-04/events/count.json

Parameters

Parameter	About	Description
-----------	-------	-------------

created_at_min	Optional	Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/event#index-2020-07>

Method	GET
Path	/admin/api/2020-07/events.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
since_id	Optional	Show only results after the specified ID.
created_at_min	Optional	Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
filter	Optional	Show events specified in this filter.
verb	Optional	Show events of a certain type.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single event by its ID

<https://shopify.dev/docs/admin-api/rest/reference/events/event#show-2020-07>

Method	GET
Path	/admin/api/2020-07/events/{event_id}.json

Parameters

Parameter	About	Description
event_id	Required	event_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of events

<https://shopify.dev/docs/admin-api/rest/reference/events/event#count-2020-07>

Method	GET
Path	/admin/api/2020-07/events/count.json

Parameters

Parameter	About	Description
created_at_min	Optional	Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/event#index-2020-10>

Method GET
Path /admin/api/2020-10/events.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
since_id	Optional	Show only results after the specified ID.
created_at_min	Optional	Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
filter	Optional	Show events specified in this filter.
verb	Optional	Show events of a certain type.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a single event by its ID

<https://shopify.dev/docs/admin-api/rest/reference/events/event#show-2020-10>

Method GET
Path /admin/api/2020-10/events/{event_id}.json

Parameters

Parameter	About	Description
event_id	Required	event_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a count of events

<https://shopify.dev/docs/admin-api/rest/reference/events/event#count-2020-10>

Method GET
Path /admin/api/2020-10/events/count.json

Parameters

Parameter	About	Description
created_at_min	Optional	Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

Response 200 No description available

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/event#index-2021-01>

Method GET

Path /admin/api/2021-01/events.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
since_id	Optional	Show only results after the specified ID.
created_at_min	Optional	Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
filter	Optional	Show events specified in this filter.
verb	Optional	Show events of a certain type.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a single event by its ID

<https://shopify.dev/docs/admin-api/rest/reference/events/event#show-2021-01>

Method GET
Path /admin/api/2021-01/events/{event_id}.json

Parameters

Parameter	About	Description
event_id	Required	event_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a count of events

<https://shopify.dev/docs/admin-api/rest/reference/events/event#count-2021-01>

Method GET
Path /admin/api/2021-01/events/count.json

Parameters

Parameter	About	Description
created_at_min	Optional	Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

Response 200 No description available

Retrieves a list of events. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/events/event#index-unstable>

Method GET
Path /admin/api/unstable/events.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
since_id	Optional	Show only results after the specified ID.
created_at_min	Optional	Show events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)

created_at_max	Optional	Show events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)
filter	Optional	Show events specified in this filter.
verb	Optional	Show events of a certain type.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single event by its ID

<https://shopify.dev/docs/admin-api/rest/reference/events/event#show-unstable>

Method	GET
Path	/admin/api/unstable/events/{event_id}.json

Parameters

Parameter	About	Description
event_id	Required	event_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of events

<https://shopify.dev/docs/admin-api/rest/reference/events/event#count-unstable>

Method	GET
Path	/admin/api/unstable/events/count.json

Parameters

Parameter	About	Description
created_at_min	Optional	Count only events created at or after this date and time. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Count only events created at or before this date and time. (format: 2014-04-25T16:15:47-04:00)

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-2020-01>

Method	GET
Path	/admin/api/2020-01/webhooks.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max	Optional	Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit	Optional	Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id	Optional	Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
updated_at_min	Optional	Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).

updated_at_max	Optional	Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).
----------------	----------	--

Responses

Response	200 No description available
----------	------------------------------

Create a new webhook subscription by specifying both an address and a topic

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-2020-01

Method	POST
Path	/admin/api/2020-01/webhooks.json

Parameters

Parameter	About	Description
format	Optional	Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of existing webhook subscriptions

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-2020-01

Method	GET
Path	/admin/api/2020-01/webhooks/count.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single webhook subscription

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-2020-01

Method	GET
Path	/admin/api/2020-01/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.

Responses

Response	200 No description available
----------	------------------------------

Update a webhook subscription's topic or address URIs

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-2020-01>

Method PUT
Path /admin/api/2020-01/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined Example: <pre>null</pre>

Responses

Response 200 No description available

Delete a webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-2020-01>

Method DELETE
Path /admin/api/2020-01/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Responses

Response 200 No description available

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-2020-04>

Method GET
Path /admin/api/2020-04/webhooks.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max	Optional	Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit	Optional	Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id	Optional	Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
updated_at_min	Optional	Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).

Responses

Response 200 No description available

Create a new webhook subscription by specifying both an address and a topic

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-2020-04

Method POST
Path /admin/api/2020-04/webhooks.json

Parameters

Parameter	About	Description
format	Optional	Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of existing webhook subscriptions

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-2020-04

Method GET
Path /admin/api/2020-04/webhooks/count.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single webhook subscription

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-2020-04

Method GET
Path /admin/api/2020-04/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.

Responses

Response	200 No description available
----------	------------------------------

Update a webhook subscription's topic or address URIs

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-2020-04

Method PUT
Path /admin/api/2020-04/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Delete a webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-2020-04>

Method	DELETE
Path	/admin/api/2020-04/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-2020-07>

Method	GET
Path	/admin/api/2020-07/webhooks.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max	Optional	Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit	Optional	Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id	Optional	Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
updated_at_min	Optional	Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).

Responses

Response	200 No description available
----------	------------------------------

Create a new webhook subscription by specifying both an address and a topic

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-2020-07>

Method	POST
Path	/admin/api/2020-07/webhooks.json

Parameters

Parameter	About	Description
format	Optional	Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of existing webhook subscriptions

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-2020-07>

Method	GET
Path	/admin/api/2020-07/webhooks/count.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-2020-07>

Method	GET
Path	/admin/api/2020-07/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.

Responses

Response	200 No description available
-----------------	------------------------------

Update a webhook subscription's topic or address URIs

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-2020-07>

Method	PUT
Path	/admin/api/2020-07/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

null

Responses

Response 200 No description available

Delete a webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-2020-07>

Method DELETE
Path /admin/api/2020-07/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Responses

Response 200 No description available

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-2020-10>

Method GET
Path /admin/api/2020-10/webhooks.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max	Optional	Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit	Optional	Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id	Optional	Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
updated_at_min	Optional	Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).

Responses

Response 200 No description available

Create a new webhook subscription by specifying both an address and a topic

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-2020-10>

Method POST
Path /admin/api/2020-10/webhooks.json

Parameters

Parameter	About	Description
format	Optional	Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Request Body

Required	No
Description	No description available

Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of existing webhook subscriptions

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-2020-10

Method	GET
Path	/admin/api/2020-10/webhooks/count.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single webhook subscription

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-2020-10

Method	GET
Path	/admin/api/2020-10/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.

Responses

Response	200 No description available
-----------------	------------------------------

Update a webhook subscription's topic or address URIs

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-2020-10

Method	PUT
Path	/admin/api/2020-10/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Delete a webhook subscription

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-2020-10>

Method DELETE
Path /admin/api/2020-10/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Responses

Response 200 No description available

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-2021-01>

Method GET
Path /admin/api/2021-01/webhooks.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max	Optional	Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit	Optional	Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id	Optional	Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
updated_at_min	Optional	Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).

Responses

Response 200 No description available

Create a new webhook subscription by specifying both an address and a topic

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-2021-01>

Method POST
Path /admin/api/2021-01/webhooks.json

Parameters

Parameter	About	Description
format	Optional	Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of existing webhook subscriptions

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-2021-01

Method GET
Path /admin/api/2021-01/webhooks/count.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>

Responses

Response 200 No description available

Retrieves a single webhook subscription

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-2021-01

Method GET
Path /admin/api/2021-01/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.

Responses

Response 200 No description available

Update a webhook subscription's topic or address URIs

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-2021-01

Method PUT
Path /admin/api/2021-01/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Delete a webhook subscription

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-2021-01

Method DELETE
Path /admin/api/2021-01/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of webhooks. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#index-unstable>

Method	GET
Path	/admin/api/unstable/webhooks.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
created_at_max	Optional	Retrieve webhook subscriptions that were created before a given date and time (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Retrieve webhook subscriptions that were created after a given date and time (format: 2014-04-25T16:15:47-04:00).
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.
limit	Optional	Maximum number of webhook subscriptions that should be returned. Setting this parameter outside the maximum range will return an error. (default: 50, maximum: 250)
since_id	Optional	Restrict the returned list to webhook subscriptions whose id is greater than the specified since_id.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>
updated_at_min	Optional	Retrieve webhooks that were updated before a given date and time (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Retrieve webhooks that were updated after a given date and time (format: 2014-04-25T16:15:47-04:00).

Responses

Response	200 No description available
----------	------------------------------

Create a new webhook subscription by specifying both an address and a topic

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#create-unstable>

Method	POST
Path	/admin/api/unstable/webhooks.json

Parameters

Parameter	About	Description
format	Optional	Use this parameter to select the data format for the payload. Valid values are json and xml. (default: json)

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of existing webhook subscriptions

<https://shopify.dev/docs/admin-api/rest/reference/events/webhook#count-unstable>

Method	GET
--------	-----

Path /admin/api/unstable/webhooks/count.json

Parameters

Parameter	About	Description
address	Optional	Retrieve webhook subscriptions that send the POST request to this URI.
topic	Optional	Show webhook subscriptions with a given topic. For a list of valid values, refer to the topic property.>

Responses

Response 200 No description available

Retrieves a single webhook subscription

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#show-unstable

Method GET
Path /admin/api/unstable/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id
fields	Optional	Comma-separated list of the properties you want returned for each item in the result list. Use this parameter to restrict the returned list of items to only those properties you specify.

Responses

Response 200 No description available

Update a webhook subscription's topic or address URIs

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#update-unstable

Method PUT
Path /admin/api/unstable/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Delete a webhook subscription

https://shopify.dev/docs/admin-api/rest/reference/events/webhook#destroy-unstable

Method DELETE
Path /admin/api/unstable/webhooks/{webhook_id}.json

Parameters

Parameter	About	Description
webhook_id	Required	webhook_id

Responses

Response 200 No description available

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-2020-01

Method GET
Path /admin/api/2020-01/inventory_items.json

Parameters

Parameter	About	Description
ids required	Optional	Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
ids	Optional	ids

Responses

Response 200 No description available

Retrieves a single inventory item by ID

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-2020-01

Method GET
Path /admin/api/2020-01/inventory_items/{inventory_item_id}.json

Parameters

Parameter	About	Description
inventory_item_id	Required	inventory_item_id

Responses

Response 200 No description available

Updates an existing inventory item

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-2020-01

Method PUT
Path /admin/api/2020-01/inventory_items/{inventory_item_id}.json

Parameters

Parameter	About	Description
inventory_item_id	Required	inventory_item_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-2020-04

Method	GET	
Path	/admin/api/2020-04/inventory_items.json	
Parameters		
Parameter	About	Description
ids required	Optional	Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
ids	Optional	ids
Responses		
Response	200 No description available	

Retrieves a single inventory item by ID

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-2020-04

Method	GET	
Path	/admin/api/2020-04/inventory_items/{inventory_item_id}.json	
Parameters		
Parameter	About	Description
inventory_item_id	Required	inventory_item_id
Responses		
Response	200 No description available	

Updates an existing inventory item

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-2020-04

Method	PUT	
Path	/admin/api/2020-04/inventory_items/{inventory_item_id}.json	
Parameters		
Parameter	About	Description
inventory_item_id	Required	inventory_item_id
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
	Example:	
	null	
Responses		
Response	200 No description available	

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-2020-07

Method	GET	
Path	/admin/api/2020-07/inventory_items.json	
Parameters		
Parameter	About	Description
ids required	Optional	Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)

limit ids	Optional Optional	The maximum number of results to show. (default: 50, maximum: 250) ids
--------------	----------------------	---

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single inventory item by ID

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-2020-07

Method	GET
Path	/admin/api/2020-07/inventory_items/{inventory_item_id}.json

Parameters

Parameter	About	Description
inventory_item_id	Required	inventory_item_id

Responses

Response	200 No description available
----------	------------------------------

Updates an existing inventory item

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-2020-07

Method	PUT
Path	/admin/api/2020-07/inventory_items/{inventory_item_id}.json

Parameters

Parameter	About	Description
inventory_item_id	Required	inventory_item_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-2020-10

Method	GET
Path	/admin/api/2020-10/inventory_items.json

Parameters

Parameter	About	Description
ids required	Optional	Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)
limit ids	Optional Optional	The maximum number of results to show. (default: 50, maximum: 250) ids

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single inventory item by ID

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-2020-10

Method GET
Path /admin/api/2020-10/inventory_items/{inventory_item_id}.json

Parameters

Parameter	About	Description
inventory_item_id	Required	inventory_item_id

Responses

Response 200 No description available

Updates an existing inventory item

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-2020-10

Method PUT
Path /admin/api/2020-10/inventory_items/{inventory_item_id}.json

Parameters

Parameter	About	Description
inventory_item_id	Required	inventory_item_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-2021-01

Method GET
Path /admin/api/2021-01/inventory_items.json

Parameters

Parameter	About	Description
ids required	Optional	Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
ids	Optional	ids

Responses

Response 200 No description available

Retrieves a single inventory item by ID

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-2021-01

Method GET
Path /admin/api/2021-01/inventory_items/{inventory_item_id}.json

Parameters

Parameter	About	Description
inventory_item_id	Required	inventory_item_id

Responses

Response	200 No description available
----------	------------------------------

Updates an existing inventory item

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-2021-01>

Method	PUT
Path	/admin/api/2021-01/inventory_items/{inventory_item_id}.json

Parameters

Parameter	About	Description
inventory_item_id	Required	inventory_item_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of inventory items. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#index-unstable>

Method	GET
Path	/admin/api/unstable/inventory_items.json

Parameters

Parameter	About	Description
ids required	Optional	Show only inventory items specified by a comma-separated list of IDs. (maximum: 100)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
ids	Optional	ids

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single inventory item by ID

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#show-unstable>

Method	GET
Path	/admin/api/unstable/inventory_items/{inventory_item_id}.json

Parameters

Parameter	About	Description
inventory_item_id	Required	inventory_item_id

Responses

Response	200 No description available
----------	------------------------------

Updates an existing inventory item

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventoryitem#update-unstable>

Method PUT
Path /admin/api/unstable/inventory_items/{inventory_item_id}.json

Parameters

Parameter	About	Description
inventory_item_id	Required	inventory_item_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined Example: <pre>null</pre>

Responses

Response 200 No description available

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-2020-01>

Method GET
Path /admin/api/2020-01/inventory_levels.json

Parameters

Parameter	About	Description
inventory_item_ids	Optional	A comma-separated list of inventory item IDs. (maximum: 50)
location_ids	Optional	A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
updated_at_min	Optional	Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

Response 200 No description available

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-2020-01>

Method DELETE
Path /admin/api/2020-01/inventory_levels.json

Parameters

Parameter	About	Description
inventory_item_id	Optional	The ID for the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
inventory_item_id	Optional	inventory_item_id
location_id	Optional	location_id

Responses

Response	200 No description available
----------	------------------------------

Adjusts the inventory level of an inventory item at a single location

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#adjust-2020-01>

Method	POST
Path	/admin/api/2020-01/inventory_levels/adjust.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID of the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available_adjustment required	Optional	The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3 decreases the current available quantity by 3.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#connect-2020-01>

Method	POST
Path	/admin/api/2020-01/inventory_levels/connect.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID of the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
relocate_if_necessary	Optional	Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-2020-01>

Method POST
Path /admin/api/2020-01/inventory_levels/set.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID for the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available required	Optional	Sets the available inventory quantity.
disconnect_if_necessary	Optional	Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-2020-04>

Method GET
Path /admin/api/2020-04/inventory_levels.json

Parameters

Parameter	About	Description
inventory_item_ids	Optional	A comma-separated list of inventory item IDs. (maximum: 50)
location_ids	Optional	A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
updated_at_min	Optional	Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

Response 200 No description available

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-2020-04>

Method DELETE

Path /admin/api/2020-04/inventory_levels.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID for the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
inventory_item_id	Optional	inventory_item_id
location_id	Optional	location_id

Responses

Response 200 No description available

Adjusts the inventory level of an inventory item at a single location

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#adjust-2020-04>

Method POST
Path /admin/api/2020-04/inventory_levels/adjust.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID of the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available_adjustment required	Optional	The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3 decreases the current available quantity by 3.

Request Body

Required No
Description No description available
Content-type application/json
Schema for Type: undefined
application/json Example:

```
null
```

Responses

Response 200 No description available

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#connect-2020-04>

Method POST
Path /admin/api/2020-04/inventory_levels/connect.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID of the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
relocate_if_necessary	Optional	Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required No
Description No description available
Content-type application/json
Schema for Type: undefined
application/json

Example:

```
null
```

Responses

Response 200 No description available

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-2020-04>

Method POST
Path /admin/api/2020-04/inventory_levels/set.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID for the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available required	Optional	Sets the available inventory quantity.
disconnect_if_necessary	Optional	Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-2020-07>

Method GET
Path /admin/api/2020-07/inventory_levels.json

Parameters

Parameter	About	Description
inventory_item_ids	Optional	A comma-separated list of inventory item IDs. (maximum: 50)
location_ids	Optional	A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
updated_at_min	Optional	Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

Response 200 No description available

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-2020-07

Method DELETE
Path /admin/api/2020-07/inventory_levels.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID for the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
inventory_item_id location_id	Optional Optional	inventory_item_id location_id

Responses

Response 200 No description available

Adjusts the inventory level of an inventory item at a single location

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#adjust-2020-07

Method POST
Path /admin/api/2020-07/inventory_levels/adjust.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID of the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available_adjustment required	Optional	The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3decreases the current available quantity by 3.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response 200 No description available

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#connect-2020-07

Method POST
Path /admin/api/2020-07/inventory_levels/connect.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID of the inventory item.

location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
relocate_if_necessary	Optional	Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
-----------------	------------------------------

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-2020-07>

Method	POST
Path	/admin/api/2020-07/inventory_levels/set.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID for the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available required	Optional	Sets the available inventory quantity.
disconnect_if_necessary	Optional	Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-2020-10>

Method	GET
Path	/admin/api/2020-10/inventory_levels.json

Parameters

Parameter	About	Description
inventory_item_ids	Optional	A comma-separated list of inventory item IDs. (maximum: 50)

location_ids	Optional	A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
updated_at_min	Optional	Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

Response	200 No description available
-----------------	------------------------------

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-2020-10>

Method	DELETE
Path	/admin/api/2020-10/inventory_levels.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID for the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
inventory_item_id	Optional	inventory_item_id
location_id	Optional	location_id

Responses

Response	200 No description available
-----------------	------------------------------

Adjusts the inventory level of an inventory item at a single location

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#adjust-2020-10>

Method	POST
Path	/admin/api/2020-10/inventory_levels/adjust.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID of the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available_adjustment required	Optional	The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3 decreases the current available quantity by 3.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
-----------------	------------------------------

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#connect-2020-10>

Method POST
Path /admin/api/2020-10/inventory_levels/connect.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID of the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
relocate_if_necessary	Optional	Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-2020-10>

Method POST
Path /admin/api/2020-10/inventory_levels/set.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID for the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available required	Optional	Sets the available inventory quantity.
disconnect_if_necessary	Optional	Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response

header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-2021-01>

Method GET
Path /admin/api/2021-01/inventory_levels.json

Parameters

Parameter	About	Description
inventory_item_ids	Optional	A comma-separated list of inventory item IDs. (maximum: 50)
location_ids	Optional	A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
updated_at_min	Optional	Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

Response 200 No description available

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-2021-01>

Method DELETE
Path /admin/api/2021-01/inventory_levels.json

Parameters

Parameter	About	Description
inventory_item_id	Optional	The ID for the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
inventory_item_id	Optional	inventory_item_id
location_id	Optional	location_id

Responses

Response 200 No description available

Adjusts the inventory level of an inventory item at a single location

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#adjust-2021-01>

Method POST
Path /admin/api/2021-01/inventory_levels/adjust.json

Parameters

Parameter	About	Description
inventory_item_id	Optional	The ID of the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available_adjustment required	Optional	The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3decreases the current available quantity by 3.

Request Body

Required No
Description No description available
Content-type application/json
Schema for Type: undefined
application/json Example:

null

Responses

Response	200 No description available
----------	------------------------------

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#connect-2021-01>

Method	POST
Path	/admin/api/2021-01/inventory_levels/connect.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID of the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
relocate_if_necessary	Optional	Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-2021-01>

Method	POST
Path	/admin/api/2021-01/inventory_levels/set.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID for the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available required	Optional	Sets the available inventory quantity.
disconnect_if_necessary	Optional	Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Retrieves a list of inventory levels. You must include `inventory_item_ids`, `location_ids`, or both as filter parameters. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the `page` parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#index-unstable>

Method GET
Path /admin/api/unstable/inventory_levels.json

Parameters

Parameter	About	Description
<code>inventory_item_ids</code>	Optional	A comma-separated list of inventory item IDs. (maximum: 50)
<code>location_ids</code>	Optional	A comma-separated list of location IDs. To find the ID of a location, use the Location resource. (maximum: 50)
<code>limit</code>	Optional	The maximum number of results to show. (default: 50, maximum: 250)
<code>updated_at_min</code>	Optional	Show inventory levels updated at or after date (format: 2019-03-19T01:21:44-04:00).

Responses

Response 200 No description available

Deletes an inventory level of an inventory item at a location. Deleting an inventory level for an inventory item removes that item from the specified location. Every inventory item must have at least one inventory level. To move inventory to another location, first connect the inventory item to another location, and then delete the previous inventory level.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#destroy-unstable>

Method DELETE
Path /admin/api/unstable/inventory_levels.json

Parameters

Parameter	About	Description
<code>inventory_item_id</code>	Optional	The ID for the inventory item.
<code>location_id required</code>	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
<code>inventory_item_id</code>	Optional	<code>inventory_item_id</code>
<code>location_id</code>	Optional	<code>location_id</code>

Responses

Response 200 No description available

Adjusts the inventory level of an inventory item at a single location

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#adjust-unstable>

Method POST
Path /admin/api/unstable/inventory_levels/adjust.json

Parameters

Parameter	About	Description
<code>inventory_item_id</code>	Optional	The ID of the inventory item.
<code>location_id required</code>	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
<code>available_adjustment required</code>	Optional	The amount to adjust the available inventory quantity. Send negative values to subtract from the current available quantity. For example, "available_adjustment": 2 increases the current available quantity by 2, and "available_adjustment": -3 decreases the current available quantity by 3.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Connects an inventory item to a location by creating an inventory level at that location. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#connect-unstable>

Method POST
Path /admin/api/unstable/inventory_levels/connect.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID of the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
relocate_if_necessary	Optional	Whether inventory for any previously connected locations will be relocated. This property is ignored when no fulfillment service location is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Sets the inventory level for an inventory item at a location. If the specified location is not connected, it will be automatically connected first. When connecting inventory items to locations, it's important to understand the rules around fulfillment service locations.

<https://shopify.dev/docs/admin-api/rest/reference/inventory/inventorylevel#set-unstable>

Method POST
Path /admin/api/unstable/inventory_levels/set.json

Parameters

Parameter	About	Description
inventory_item_id required	Optional	The ID for the inventory item.
location_id required	Optional	The ID of the location that the inventory level belongs to. To find the ID of the location, use the Location resource.
available required	Optional	Sets the available inventory quantity.
disconnect_if_necessary	Optional	Whether inventory for any previously connected locations will be set to 0 and the locations disconnected. This property is ignored when no fulfillment service is involved. For more information, see Inventory levels and fulfillment service locations. (default: false)

Request Body

Required Description	No
Content-type	No description available
Schema for application/json	application/json
	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of locations

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-2020-01

Method	GET
Path	/admin/api/2020-01/locations.json

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single location by its ID

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-2020-01

Method	GET
Path	/admin/api/2020-01/locations/{location_id}.json

Parameters

Parameter	About	Description
location_id	Required	location_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of locations

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-2020-01

Method	GET
Path	/admin/api/2020-01/locations/count.json

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-2020-01

Method	GET
Path	/admin/api/2020-01/locations/{location_id}/inventory_levels.json

Parameters

Parameter	About	Description
location_id	Required	location_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of locations

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-2020-04

Method GET
Path /admin/api/2020-04/locations.json

Responses

Response 200 No description available

Retrieves a single location by its ID

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-2020-04

Method GET
Path /admin/api/2020-04/locations/{location_id}.json

Parameters

Parameter	About	Description
location_id	Required	location_id

Responses

Response 200 No description available

Retrieves a count of locations

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-2020-04

Method GET
Path /admin/api/2020-04/locations/count.json

Responses

Response 200 No description available

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-2020-04

Method GET
Path /admin/api/2020-04/locations/{location_id}/inventory_levels.json

Parameters

Parameter	About	Description
location_id	Required	location_id

Responses

Response 200 No description available

Retrieves a list of locations

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-2020-07

Method GET
Path /admin/api/2020-07/locations.json

Responses

Response 200 No description available

Retrieves a single location by its ID

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-2020-07>

Method GET
Path /admin/api/2020-07/locations/{location_id}.json

Parameters

Parameter	About	Description
location_id	Required	location_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of locations

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-2020-07>

Method GET
Path /admin/api/2020-07/locations/count.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-2020-07

Method GET
Path /admin/api/2020-07/locations/{location_id}/inventory_levels.json

Parameters

Parameter	About	Description
location_id	Required	location_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of locations

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-2020-10>

Method GET
Path /admin/api/2020-10/locations.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single location by its ID

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-2020-10>

Method GET
Path /admin/api/2020-10/locations/{location_id}.json

Parameters

Parameter	About	Description
location_id	Required	location_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of locations

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-2020-10>

Method GET
Path /admin/api/2020-10/locations/count.json

Responses

Response 200 No description available

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-2020-10

Method GET
Path /admin/api/2020-10/locations/{location_id}/inventory_levels.json

Parameters

Parameter	About	Description
location_id	Required	location_id

Responses

Response 200 No description available

Retrieves a list of locations

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-2021-01>

Method GET
Path /admin/api/2021-01/locations.json

Responses

Response 200 No description available

Retrieves a single location by its ID

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-2021-01>

Method GET
Path /admin/api/2021-01/locations/{location_id}.json

Parameters

Parameter	About	Description
location_id	Required	location_id

Responses

Response 200 No description available

Retrieves a count of locations

<https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-2021-01>

Method GET
Path /admin/api/2021-01/locations/count.json

Responses

Response 200 No description available

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-2021-01

Method GET
Path /admin/api/2021-01/locations/{location_id}/inventory_levels.json

Parameters

Parameter	About	Description
location_id	Required	location_id

Responses

Response 200 No description available

Retrieves a list of locations

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#index-unstable

Method GET
Path /admin/api/unstable/locations.json

Responses

Response 200 No description available

Retrieves a single location by its ID

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#show-unstable

Method GET
Path /admin/api/unstable/locations/{location_id}.json

Parameters

Parameter	About	Description
location_id	Required	location_id

Responses

Response 200 No description available

Retrieves a count of locations

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#count-unstable

Method GET
Path /admin/api/unstable/locations/count.json

Responses

Response 200 No description available

Retrieves a list of inventory levels for a location. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/inventory/location#inventory_levels-unstable

Method GET
Path /admin/api/unstable/locations/{location_id}/inventory_levels.json

Parameters

Parameter	About	Description
-----------	-------	-------------

location_id Required location_id

Responses

Response 200 No description available

Retrieves a list of metafields that belong to a Product Image resource.

https://shopify.dev/docs/admin-api/rest/reference/metafield#index-2020-01

Method GET
Path /admin/api/2020-01/metafields.json

Parameters

Parameter	About	Description
metafield[owner_id]	Optional	metafield[owner_id]
metafield[owner_resource]	Optional	metafield[owner_resource]
]		

Responses

Response 200 No description available

Creates a new metafield for a resource.

https://shopify.dev/docs/admin-api/rest/reference/metafield#create-2020-01

Method POST
Path /admin/api/2020-01/metafields.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for Type: undefined
application/json Example:

null

Responses

Response 200 No description available

Retrieves a count of a resource's metafields.

https://shopify.dev/docs/admin-api/rest/reference/metafield#count-2020-01

Method GET
Path /admin/api/2020-01/metafields/count.json

Responses

Response 200 No description available

Retrieves a single metafield from a resource by its ID.

https://shopify.dev/docs/admin-api/rest/reference/metafield#show-2020-01

Method GET
Path /admin/api/2020-01/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates a metafield.

https://shopify.dev/docs/admin-api/rest/reference/metafield#update-2020-01

Method PUT
Path /admin/api/2020-01/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Deletes a metafield by its ID.

https://shopify.dev/docs/admin-api/rest/reference/metafield#destroy-2020-01

Method DELETE
Path /admin/api/2020-01/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Responses

Response 200 No description available

Retrieves a list of metafields that belong to a Product Image resource.

https://shopify.dev/docs/admin-api/rest/reference/metafield#index-2020-04

Method GET
Path /admin/api/2020-04/metafields.json

Parameters

Parameter	About	Description
metafield[owner_id]	Optional	metafield[owner_id]
metafield[owner_resource]	Optional	metafield[owner_resource]
]		

Responses

Response 200 No description available

Creates a new metafield for a resource.

https://shopify.dev/docs/admin-api/rest/reference/metafield#create-2020-04

Method POST
Path /admin/api/2020-04/metafields.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

null

Responses

Response 200 No description available

Retrieves a count of a resource's metafields.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#count-2020-04>

Method GET
Path /admin/api/2020-04/metafields/count.json

Responses

Response 200 No description available

Retrieves a single metafield from a resource by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#show-2020-04>

Method GET
Path /admin/api/2020-04/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates a metafield.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#update-2020-04>

Method PUT
Path /admin/api/2020-04/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

null

Responses

Response 200 No description available

Deletes a metafield by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#destroy-2020-04>

Method DELETE
Path /admin/api/2020-04/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Responses

Response 200 No description available

Retrieves a list of metafields that belong to a Product Image resource.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#index-2020-07>

Method GET
Path /admin/api/2020-07/metafields.json

Parameters

Parameter	About	Description
metafield[owner_id]	Optional	metafield[owner_id]
metafield[owner_resource]	Optional	metafield[owner_resource]
]		

Responses

Response 200 No description available

Creates a new metafield for a resource.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#create-2020-07>

Method POST
Path /admin/api/2020-07/metafields.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a count of a resource's metafields.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#count-2020-07>

Method GET
Path /admin/api/2020-07/metafields/count.json

Responses

Response 200 No description available

Retrieves a single metafield from a resource by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#show-2020-07>

Method GET
Path /admin/api/2020-07/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates a metafield.

https://shopify.dev/docs/admin-api/rest/reference/metafield#update-2020-07

Method PUT
Path /admin/api/2020-07/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Deletes a metafield by its ID.

https://shopify.dev/docs/admin-api/rest/reference/metafield#destroy-2020-07

Method DELETE
Path /admin/api/2020-07/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Responses

Response 200 No description available

Retrieves a list of metafields that belong to a Product Image resource.

https://shopify.dev/docs/admin-api/rest/reference/metafield#index-2020-10

Method GET
Path /admin/api/2020-10/metafields.json

Parameters

Parameter	About	Description
metafield[owner_id]	Optional	metafield[owner_id]
metafield[owner_resource]	Optional	metafield[owner_resource]
]		

Responses

Response 200 No description available

Creates a new metafield for a resource.

https://shopify.dev/docs/admin-api/rest/reference/metafield#create-2020-10

Method POST
Path /admin/api/2020-10/metafields.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

null

Responses

Response 200 No description available

Retrieves a count of a resource's metafields.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#count-2020-10>

Method GET
Path /admin/api/2020-10/metafields/count.json

Responses

Response 200 No description available

Retrieves a single metafield from a resource by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#show-2020-10>

Method GET
Path /admin/api/2020-10/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates a metafield.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#update-2020-10>

Method PUT
Path /admin/api/2020-10/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

null

Responses

Response 200 No description available

Deletes a metafield by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#destroy-2020-10>

Method DELETE
Path /admin/api/2020-10/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Responses

Response 200 No description available

Retrieves a list of metafields that belong to a Product Image resource.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#index-2021-01>

Method GET
Path /admin/api/2021-01/metafields.json

Parameters

Parameter	About	Description
metafield[owner_id]	Optional	metafield[owner_id]
metafield[owner_resource]	Optional	metafield[owner_resource]
]		

Responses

Response 200 No description available

Creates a new metafield for a resource.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#create-2021-01>

Method POST
Path /admin/api/2021-01/metafields.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a count of a resource's metafields.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#count-2021-01>

Method GET
Path /admin/api/2021-01/metafields/count.json

Responses

Response 200 No description available

Retrieves a single metafield from a resource by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#show-2021-01>

Method GET
Path /admin/api/2021-01/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates a metafield.

https://shopify.dev/docs/admin-api/rest/reference/metafield#update-2021-01

Method PUT
Path /admin/api/2021-01/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Deletes a metafield by its ID.

https://shopify.dev/docs/admin-api/rest/reference/metafield#destroy-2021-01

Method DELETE
Path /admin/api/2021-01/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Responses

Response 200 No description available

Retrieves a list of metafields that belong to a Product Image resource.

https://shopify.dev/docs/admin-api/rest/reference/metafield#index-unstable

Method GET
Path /admin/api/unstable/metafields.json

Parameters

Parameter	About	Description
metafield[owner_id]	Optional	metafield[owner_id]
metafield[owner_resource]	Optional	metafield[owner_resource]
]		

Responses

Response 200 No description available

Creates a new metafield for a resource.

https://shopify.dev/docs/admin-api/rest/reference/metafield#create-unstable

Method POST
Path /admin/api/unstable/metafields.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of a resource's metafields.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#count-unstable>

Method	GET
Path	/admin/api/unstable/metafields/count.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single metafield from a resource by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#show-unstable>

Method	GET
Path	/admin/api/unstable/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates a metafield.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#update-unstable>

Method	PUT
Path	/admin/api/unstable/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Deletes a metafield by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/metafield#destroy-unstable>

Method	DELETE
Path	/admin/api/unstable/metafields/{metafield_id}.json

Parameters

Parameter	About	Description
metafield_id	Required	metafield_id

Responses

Response 200 No description available

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-2020-01>

Method GET
Path /admin/api/2020-01/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle	Optional	Retrieve an article with a specific handle.
tag	Optional	Filter articles with a specific tag.
author	Optional	Filter articles by article author.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates an article for a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-2020-01>

Method POST
Path /admin/api/2020-01/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined Example: <pre>null</pre>

Responses

Response 200 No description available

Retrieves a count of all articles from a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#count-2020-01>

Method GET
Path /admin/api/2020-01/blogs/{blog_id}/articles/count.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
created_at_min	Optional	Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#show-2020-01>

Method	GET
Path	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Updates an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#update-2020-01>

Method	PUT
Path	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
-----------------	------------------------------

Deletes an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#destroy-2020-01>

Method	DELETE
Path	/admin/api/2020-01/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list all of article authors

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#authors-2020-01>

Method	GET
Path	/admin/api/2020-01/articles/authors.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of all the tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#tags-2020-01>

Method	GET
Path	/admin/api/2020-01/articles/tags.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of tags to retrieve.
popular	Optional	A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-2020-04>

Method	GET
Path	/admin/api/2020-04/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle	Optional	Retrieve an article with a specific handle.
tag	Optional	Filter articles with a specific tag.
author	Optional	Filter articles by article author.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Creates an article for a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-2020-04>

Method	POST
--------	------

Path /admin/api/2020-04/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a count of all articles from a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#count-2020-04>

Method GET
Path /admin/api/2020-04/blogs/{blog_id}/articles/count.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
created_at_min	Optional	Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

Response 200 No description available

Retrieves a single article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#show-2020-04>

Method GET
Path /admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#update-2020-04>

Method PUT
Path /admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
-----------	-------	-------------

blog_id	Required	blog_id
article_id	Required	article_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
-----------------	------------------------------

Deletes an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#destroy-2020-04>

Method	DELETE
Path	/admin/api/2020-04/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list all of article authors

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#authors-2020-04>

Method	GET
Path	/admin/api/2020-04/articles/authors.json

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of all the tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#tags-2020-04>

Method	GET
Path	/admin/api/2020-04/articles/tags.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of tags to retrieve.
popular	Optional	A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-2020-07>

Method	GET
---------------	-----

Path /admin/api/2020-07/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle	Optional	Retrieve an article with a specific handle.
tag	Optional	Filter articles with a specific tag.
author	Optional	Filter articles by article author.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates an article for a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-2020-07>

Method POST
Path /admin/api/2020-07/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of all articles from a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#count-2020-07>

Method GET
Path /admin/api/2020-07/blogs/{blog_id}/articles/count.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
created_at_min	Optional	Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

Response 200 No description available

Retrieves a single article

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#show-2020-07

Method GET
Path /admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an article

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#update-2020-07

Method PUT
Path /admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Deletes an article

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#destroy-2020-07

Method DELETE
Path /admin/api/2020-07/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id

Responses

Response 200 No description available

Retrieves a list all of article authors

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#authors-2020-07

Method GET
Path /admin/api/2020-07/articles/authors.json

Responses

Response 200 No description available

Retrieves a list of all the tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#tags-2020-07>

Method GET
Path /admin/api/2020-07/articles/tags.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of tags to retrieve.
popular	Optional	A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

Response 200 No description available

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-2020-10>

Method GET
Path /admin/api/2020-10/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle	Optional	Retrieve an article with a specific handle.
tag	Optional	Filter articles with a specific tag.
author	Optional	Filter articles by article author.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates an article for a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-2020-10>

Method POST
Path /admin/api/2020-10/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of all articles from a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#count-2020-10>

Method GET
Path /admin/api/2020-10/blogs/{blog_id}/articles/count.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
created_at_min	Optional	Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

Response 200 No description available

Retrieves a single article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#show-2020-10>

Method GET
Path /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#update-2020-10>

Method PUT
Path /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Deletes an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#destroy-2020-10>

Method DELETE
Path /admin/api/2020-10/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id

Responses

Response 200 No description available

Retrieves a list all of article authors

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#authors-2020-10>

Method GET
Path /admin/api/2020-10/articles/authors.json

Responses

Response 200 No description available

Retrieves a list of all the tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#tags-2020-10>

Method GET
Path /admin/api/2020-10/articles/tags.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of tags to retrieve.
popular	Optional	A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

Response 200 No description available

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-2021-01>

Method GET
Path /admin/api/2021-01/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle	Optional	Retrieve an article with a specific handle.
tag	Optional	Filter articles with a specific tag.

author fields	Optional Optional	Filter articles by article author. Show only certain fields, specified by a comma-separated list of field names.
----------------------	----------------------	---

Responses

Response	200 No description available
-----------------	------------------------------

Creates an article for a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-2021-01>

Method	POST
Path	/admin/api/2021-01/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined Example: null

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of all articles from a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#count-2021-01>

Method	GET
Path	/admin/api/2021-01/blogs/{blog_id}/articles/count.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
created_at_min	Optional	Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#show-2021-01>

Method	GET
Path	/admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an article

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#update-2021-01

Method PUT
Path /admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes an article

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#destroy-2021-01

Method DELETE
Path /admin/api/2021-01/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id

Responses

Response 200 No description available

Retrieves a list all of article authors

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#authors-2021-01

Method GET
Path /admin/api/2021-01/articles/authors.json

Responses

Response 200 No description available

Retrieves a list of all the tags

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#tags-2021-01

Method GET
Path /admin/api/2021-01/articles/tags.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of tags to retrieve.
popular	Optional	A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

Retrieves a list of all articles from a blog. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#index-unstable>

Method GET
Path /admin/api/unstable/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Show articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Retrieve results based on their published status. (default: any) published: Show only published articles. unpublished: Show only unpublished articles. any: Show articles of any published status.
handle	Optional	Retrieve an article with a specific handle.
tag	Optional	Filter articles with a specific tag.
author	Optional	Filter articles by article author.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates an article for a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#create-unstable>

Method POST
Path /admin/api/unstable/blogs/{blog_id}/articles.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves a count of all articles from a blog

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#count-unstable>

Method GET
Path /admin/api/unstable/blogs/{blog_id}/articles/count.json

Parameters

Parameter	About	Description
-----------	-------	-------------

blog_id	Required	blog_id
created_at_min	Optional	Count articles created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count articles created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count articles last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count articles last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count articles published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count articles published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count articles with a given published status. (default: any) published: Count only published articles. unpublished: Count only unpublished articles. any: Count all articles.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single article

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#show-unstable

Method	GET
Path	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates an article

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#update-unstable

Method	PUT
Path	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Deletes an article

https://shopify.dev/docs/admin-api/rest/reference/online-store/article#destroy-unstable

Method	DELETE
Path	/admin/api/unstable/blogs/{blog_id}/articles/{article_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
article_id	Required	article_id

Responses

Response 200 No description available

Retrieves a list all of article authors

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#authors-unstable>

Method GET
Path /admin/api/unstable/articles/authors.json

Responses

Response 200 No description available

Retrieves a list of all the tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/article#tags-unstable>

Method GET
Path /admin/api/unstable/articles/tags.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of tags to retrieve.
popular	Optional	A flag for ordering retrieved tags. If present in the request, then the results will be ordered by popularity, starting with the most popular tag.

Responses

Response 200 No description available

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see [Asset properties](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-2020-01>

Method GET
Path /admin/api/2020-01/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names
asset[key]	Optional	asset[key]

Responses

Response 200 No description available

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-2020-01>

Method PUT
Path /admin/api/2020-01/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
src	Optional	The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key	Optional	The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Deletes an asset from a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-2020-01>

Method DELETE
Path /admin/api/2020-01/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
asset[key]	Optional	asset[key]

Responses

Response 200 No description available

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see [Asset properties](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-2020-04>

Method GET
Path /admin/api/2020-04/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names
asset[key]	Optional	asset[key]

Responses

Response 200 No description available

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-2020-04>

Method PUT
Path /admin/api/2020-04/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
src	Optional	The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key	Optional	The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Request Body

Required Description	No
Content-type	No description available
Schema for application/json	application/json
	Type: undefined
	Example:
	<code>null</code>

Responses

Response	200 No description available
----------	------------------------------

Deletes an asset from a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-2020-04>

Method	DELETE
Path	/admin/api/2020-04/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
asset[key]	Optional	asset[key]

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see [Asset properties](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-2020-07>

Method	GET
Path	/admin/api/2020-07/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names
asset[key]	Optional	asset[key]

Responses

Response	200 No description available
----------	------------------------------

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-2020-07>

Method	PUT
Path	/admin/api/2020-07/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
src	Optional	The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key	Optional	The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Request Body

Required	No
----------	----

Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Deletes an asset from a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-2020-07>

Method	DELETE
Path	/admin/api/2020-07/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
asset[key]	Optional	asset[key]

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see [Asset properties](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-2020-10>

Method	GET
Path	/admin/api/2020-10/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names
asset[key]	Optional	asset[key]

Responses

Response	200 No description available
-----------------	------------------------------

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-2020-10>

Method	PUT
Path	/admin/api/2020-10/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
src	Optional	The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key	Optional	The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Request Body

Required	No
Description	No description available

Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Deletes an asset from a theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-2020-10>

Method	DELETE
Path	/admin/api/2020-10/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
asset[key]	Optional	asset[key]

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see [Asset properties](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-2021-01>

Method	GET
Path	/admin/api/2021-01/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names
asset[key]	Optional	asset[key]

Responses

Response	200 No description available
----------	------------------------------

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-2021-01>

Method	PUT
Path	/admin/api/2021-01/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
src	Optional	The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key	Optional	The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Request Body

Required	No
Description	No description available
Content-type	application/json

Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Deletes an asset from a theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-2021-01

Method	DELETE
Path	/admin/api/2021-01/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
asset[key]	Optional	asset[key]

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single asset for a theme by its key. To retrieve a single asset, include `asset[key]=#{asset_key}` as a request parameter. For example, to retrieve the asset with a key of `templates/index.liquid`, the request might be `/admin/themes/828155753/assets.json?asset[key]=templates/index.liquid`. For more information on the key property, see [Asset properties](#).

https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#show-unstable

Method	GET
Path	/admin/api/unstable/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names
asset[key]	Optional	asset[key]

Responses

Response	200 No description available
----------	------------------------------

Creates or updates an asset for a theme. In the PUT request, you can include the `src` or `source_key` property to create the asset from an existing file.

https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#update-unstable

Method	PUT
Path	/admin/api/unstable/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
src	Optional	The source URL of an image. Include in the body of the PUT request to upload the image to Shopify.
source_key	Optional	The path within the theme to an existing asset. Include in the body of the PUT request to create a duplicate asset.

Request Body

Required	No
Description	No description available
Content-type	application/json

Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Deletes an asset from a theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/asset#destroy-unstable

Method	DELETE
Path	/admin/api/unstable/themes/{theme_id}/assets.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
asset[key]	Optional	asset[key]

Responses

Response	200 No description available
----------	------------------------------

Retrieve a list of all blogs. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#index-2020-01

Method	GET
Path	/admin/api/2020-01/blogs.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID
handle	Optional	Filter by blog handle
fields	Optional	comma-separated list of fields to include in the response

Responses

Response	200 No description available
----------	------------------------------

Create a new blog

https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#create-2020-01

Method	POST
Path	/admin/api/2020-01/blogs.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Get a count of all blogs

https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#count-2020-01

Method GET
Path /admin/api/2020-01/blogs/count.json

Responses

Response 200 No description available

Get a single blog by its ID

https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#show-2020-01

Method GET
Path /admin/api/2020-01/blogs/{blog_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id
fields	Optional	comma-separated list of fields to include in the response

Responses

Response 200 No description available

Update a blog

https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#update-2020-01

Method PUT
Path /admin/api/2020-01/blogs/{blog_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

Delete a blog

https://shopify.dev/docs/admin-api/rest/reference/online-store/blog#destroy-2020-01

Method DELETE
Path /admin/api/2020-01/blogs/{blog_id}.json

Parameters

Parameter	About	Description
blog_id	Required	blog_id

Responses

Response 200 No description available

Retrieves a list of comments. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header.

Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#index-2020-01

Method GET
Path /admin/api/2020-01/comments.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show comments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Show comments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show comments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show comments last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show comments published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show comments published before date (format: 2014-04-25T16:15:47-04:00).
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
published_status	Optional	Filter results by their published status. (default: any) published: Show only published comments. unpublished: Show only unpublished comments. any: Show comments of any published status.
status	Optional	Filter results by their status. pending: Show only pending comments. published: Show only published comments. unapproved: Show only unapproved comments.
article_id	Optional	article_id
blog_id	Optional	blog_id

Responses

Response 200 No description available

Creates a comment for an article

https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#create-2020-01

Method POST
Path /admin/api/2020-01/comments.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response 200 No description available

Retrieves a count of comments

https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#count-2020-01

Method GET
Path /admin/api/2020-01/comments/count.json

Parameters

Parameter	About	Description
created_at_min	Optional	Count comments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count comments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count comments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count comments last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count comments published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count comments published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Retrieve a count of comments with a given published status. (default: any) published: Count only published comments. unpublished: Count only unpublished comments. any: Count comments of any published status.
status	Optional	Retrieve a count of comments with a given status. pending: Count pending comments. published: Count published comments. unapproved: Count

article_id	Optional	unapproved comments.
blog_id	Optional	article_id blog_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single comment by its ID

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#show-2020-01>

Method	GET
Path	/admin/api/2020-01/comments/{comment_id}.json

Parameters

Parameter	About	Description
comment_id	Required	comment_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Updates a comment of an article

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#update-2020-01>

Method	PUT
Path	/admin/api/2020-01/comments/{comment_id}.json

Parameters

Parameter	About	Description
comment_id	Required	comment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
-----------------	------------------------------

Marks a comment as spam

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#spam-2020-01>

Method	POST
Path	/admin/api/2020-01/comments/{comment_id}/spam.json

Parameters

Parameter	About	Description
comment_id	Required	comment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

Marks a comment as not spam

https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#not_spam-2020-01

Method POST
Path /admin/api/2020-01/comments/{comment_id}/not_spam.json

Parameters

Parameter	About	Description
comment_id	Required	comment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Approves a comment

https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#approve-2020-01

Method POST
Path /admin/api/2020-01/comments/{comment_id}/approve.json

Parameters

Parameter	About	Description
comment_id	Required	comment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Removes a comment

https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#remove-2020-01

Method POST
Path /admin/api/2020-01/comments/{comment_id}/remove.json

Parameters

Parameter	About	Description
comment_id	Required	comment_id

Request Body

Required	No
Description	No description available
Content-type	application/json

Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Restores a previously removed comment

<https://shopify.dev/docs/admin-api/rest/reference/online-store/comment#restore-2020-01>

Method	POST
Path	/admin/api/2020-01/comments/{comment_id}/restore.json

Parameters

Parameter	About	Description
comment_id	Required	comment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-2020-01>

Method	GET
Path	/admin/api/2020-01/redirects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
path	Optional	Show redirects with a given path.
target	Optional	Show redirects with a given target.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-2020-01>

Method	POST
Path	/admin/api/2020-01/redirects.json

Request Body

Required	No
Description	No description available

Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of URL redirects

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-2020-01

Method	GET
Path	/admin/api/2020-01/redirects/count.json

Parameters

Parameter	About	Description
path	Optional	Count redirects with given path.
target	Optional	Count redirects with given target.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-2020-01

Method	GET
Path	/admin/api/2020-01/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates an existing redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-2020-01

Method	PUT
Path	/admin/api/2020-01/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Deletes a redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-2020-01>

Method DELETE
Path /admin/api/2020-01/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Responses

Response 200 No description available

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-2020-04>

Method GET
Path /admin/api/2020-04/redirects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
path	Optional	Show redirects with a given path.
target	Optional	Show redirects with a given target.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-2020-04>

Method POST
Path /admin/api/2020-04/redirects.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves a count of URL redirects

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-2020-04>

Method GET
Path /admin/api/2020-04/redirects/count.json

Parameters

Parameter	About	Description
path	Optional	Count redirects with given path.
target	Optional	Count redirects with given target.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-2020-04>

Method	GET
Path	/admin/api/2020-04/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates an existing redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-2020-04>

Method	PUT
Path	/admin/api/2020-04/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Deletes a redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-2020-04>

Method	DELETE
Path	/admin/api/2020-04/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-2020-07>

Method	GET
--------	-----

Path /admin/api/2020-07/redirects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
path	Optional	Show redirects with a given path.
target	Optional	Show redirects with a given target.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-2020-07

Method POST
Path /admin/api/2020-07/redirects.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a count of URL redirects

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-2020-07

Method GET
Path /admin/api/2020-07/redirects/count.json

Parameters

Parameter	About	Description
path	Optional	Count redirects with given path.
target	Optional	Count redirects with given target.

Responses

Response 200 No description available

Retrieves a single redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-2020-07

Method GET
Path /admin/api/2020-07/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an existing redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-2020-07>

Method PUT
Path /admin/api/2020-07/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined Example: <pre>null</pre>

Responses

Response 200 No description available

Deletes a redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-2020-07>

Method DELETE
Path /admin/api/2020-07/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Responses

Response 200 No description available

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-2020-10>

Method GET
Path /admin/api/2020-10/redirects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
path	Optional	Show redirects with a given path.
target	Optional	Show redirects with a given target.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-2020-10>

Method POST
Path /admin/api/2020-10/redirects.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of URL redirects

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-2020-10>

Method GET
Path /admin/api/2020-10/redirects/count.json

Parameters

Parameter	About	Description
path	Optional	Count redirects with given path.
target	Optional	Count redirects with given target.

Responses

Response 200 No description available

Retrieves a single redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-2020-10>

Method GET
Path /admin/api/2020-10/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an existing redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-2020-10>

Method PUT
Path /admin/api/2020-10/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Deletes a redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-2020-10>

Method	DELETE
Path	/admin/api/2020-10/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of URL redirects. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-2021-01>

Method	GET
Path	/admin/api/2021-01/redirects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
path	Optional	Show redirects with a given path.
target	Optional	Show redirects with a given target.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-2021-01>

Method	POST
Path	/admin/api/2021-01/redirects.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of URL redirects

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-2021-01>

Method GET
Path /admin/api/2021-01/redirects/count.json

Parameters

Parameter	About	Description
path	Optional	Count redirects with given path.
target	Optional	Count redirects with given target.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-2021-01

Method GET
Path /admin/api/2021-01/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates an existing redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-2021-01

Method PUT
Path /admin/api/2021-01/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Deletes a redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-2021-01

Method DELETE
Path /admin/api/2021-01/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of URL redirects. **Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.**

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#index-unstable

Method GET
Path /admin/api/unstable/redirects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
path	Optional	Show redirects with a given path.
target	Optional	Show redirects with a given target.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a redirect. When you provide a full URL as the value of the path property, it will be saved as an absolute path without the domain. For example, "path": "http://www.johns-apparel.com/springwear" will be saved as "path": "springwear".

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#create-unstable

Method POST
Path /admin/api/unstable/redirects.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a count of URL redirects

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#count-unstable

Method GET
Path /admin/api/unstable/redirects/count.json

Parameters

Parameter	About	Description
path	Optional	Count redirects with given path.
target	Optional	Count redirects with given target.

Responses

Response 200 No description available

Retrieves a single redirect

https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#show-unstable

Method GET
Path /admin/api/unstable/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Updates an existing redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#update-unstable>

Method	PUT
Path	/admin/api/unstable/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
-----------------	------------------------------

Deletes a redirect

<https://shopify.dev/docs/admin-api/rest/reference/online-store/redirect#destroy-unstable>

Method	DELETE
Path	/admin/api/unstable/redirects/{redirect_id}.json

Parameters

Parameter	About	Description
redirect_id	Required	redirect_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-2020-01>

Method	GET
Path	/admin/api/2020-01/script_tags.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)
src	Optional	Show script tags with this URL.
fields	Optional	A comma-separated list of fields to include in the response.

Responses	
Response	200 No description available

Creates a new script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-2020-01

Method	POST
Path	/admin/api/2020-01/script_tags.json

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses	
Response	200 No description available

Retrieves a count of all script tags

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-2020-01

Method	GET
Path	/admin/api/2020-01/script_tags/count.json

Parameters		
Parameter	About	Description
src	Optional	Count only script tags with a given URL.

Responses	
Response	200 No description available

Retrieves a single script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-2020-01

Method	GET
Path	/admin/api/2020-01/script_tags/{script_tag_id}.json

Parameters		
Parameter	About	Description
script_tag_id	Required	script_tag_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses	
Response	200 No description available

Updates a script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-2020-01

Method	PUT
Path	/admin/api/2020-01/script_tags/{script_tag_id}.json

Parameters		
Parameter	About	Description
script_tag_id	Required	script_tag_id

Request Body	
Required	No

Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Deletes a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-2020-01>

Method	DELETE
Path	/admin/api/2020-01/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-2020-04>

Method	GET
Path	/admin/api/2020-04/script_tags.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)
src	Optional	Show script tags with this URL.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
-----------------	------------------------------

Creates a new script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-2020-04>

Method	POST
Path	/admin/api/2020-04/script_tags.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a count of all script tags

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-2020-04

Method GET
Path /admin/api/2020-04/script_tags/count.json

Parameters

Parameter	About	Description
src	Optional	Count only script tags with a given URL.

Responses

Response 200 No description available

Retrieves a single script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-2020-04

Method GET
Path /admin/api/2020-04/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Updates a script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-2020-04

Method PUT
Path /admin/api/2020-04/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes a script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-2020-04

Method DELETE
Path /admin/api/2020-04/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id

Responses

Response 200 No description available

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-2020-07>

Method GET
Path /admin/api/2020-07/script_tags.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)
src	Optional	Show script tags with this URL.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates a new script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-2020-07>

Method POST
Path /admin/api/2020-07/script_tags.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of all script tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-2020-07>

Method GET
Path /admin/api/2020-07/script_tags/count.json

Parameters

Parameter	About	Description
src	Optional	Count only script tags with a given URL.

Responses

Response 200 No description available

Retrieves a single script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-2020-07>

Method GET
Path /admin/api/2020-07/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Updates a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-2020-07>

Method PUT
Path /admin/api/2020-07/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Deletes a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-2020-07>

Method DELETE
Path /admin/api/2020-07/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id

Responses

Response 200 No description available

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-2020-10>

Method GET
Path /admin/api/2020-10/script_tags.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)

updated_at_min	Optional	Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)
src	Optional	Show script tags with this URL.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a new script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-2020-10>

Method	POST
Path	/admin/api/2020-10/script_tags.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of all script tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-2020-10>

Method	GET
Path	/admin/api/2020-10/script_tags/count.json

Parameters

Parameter	About	Description
src	Optional	Count only script tags with a given URL.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-2020-10>

Method	GET
Path	/admin/api/2020-10/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Updates a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-2020-10>

Method	PUT
Path	/admin/api/2020-10/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
-----------	-------	-------------

script_tag_id Required **script_tag_id**

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Deletes a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-2020-10>

Method DELETE
Path /admin/api/2020-10/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id

Responses

Response 200 No description available

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-2021-01>

Method GET
Path /admin/api/2021-01/script_tags.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)
src	Optional	Show script tags with this URL.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Creates a new script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-2021-01>

Method POST
Path /admin/api/2021-01/script_tags.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of all script tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-2021-01>

Method	GET
Path	/admin/api/2021-01/script_tags/count.json

Parameters

Parameter	About	Description
src	Optional	Count only script tags with a given URL.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-2021-01>

Method	GET
Path	/admin/api/2021-01/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Updates a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-2021-01>

Method	PUT
Path	/admin/api/2021-01/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Deletes a script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-2021-01>

Method	DELETE
Path	/admin/api/2021-01/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of all script tags. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#index-unstable>

Method	GET
Path	/admin/api/unstable/script_tags.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to return. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Show script tags created after this date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show script tags created before this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show script tags last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show script tags last updated before this date. (format: 2014-04-25T16:15:47-04:00)
src	Optional	Show script tags with this URL.
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Creates a new script tag

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#create-unstable>

Method	POST
Path	/admin/api/unstable/script_tags.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of all script tags

<https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#count-unstable>

Method	GET
Path	/admin/api/unstable/script_tags/count.json

Parameters

Parameter	About	Description
src	Optional	Count only script tags with a given URL.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#show-unstable

Method GET
Path /admin/api/unstable/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Updates a script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#update-unstable

Method PUT
Path /admin/api/unstable/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

Deletes a script tag

https://shopify.dev/docs/admin-api/rest/reference/online-store/scripttag#destroy-unstable

Method DELETE
Path /admin/api/unstable/script_tags/{script_tag_id}.json

Parameters

Parameter	About	Description
script_tag_id	Required	script_tag_id

Responses

Response 200 No description available

Retrieves a list of themes.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-2020-01

Method GET
Path /admin/api/2020-01/themes.json

Parameters

Parameter	About	Description
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-2020-01

Method POST
Path /admin/api/2020-01/themes.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a single theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-2020-01

Method GET
Path /admin/api/2020-01/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an existing theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-2020-01

Method PUT
Path /admin/api/2020-01/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes a theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-2020-01

Method DELETE
Path /admin/api/2020-01/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of themes.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-2020-04>

Method GET
Path /admin/api/2020-04/themes.json

Parameters

Parameter	About	Description
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-2020-04>

Method POST
Path /admin/api/2020-04/themes.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-2020-04>

Method GET
Path /admin/api/2020-04/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates an existing theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-2020-04

Method PUT
Path /admin/api/2020-04/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

Deletes a theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-2020-04

Method DELETE
Path /admin/api/2020-04/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Responses

Response 200 No description available

Retrieves a list of themes.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-2020-07

Method GET
Path /admin/api/2020-07/themes.json

Parameters

Parameter	About	Description
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-2020-07

Method POST
Path /admin/api/2020-07/themes.json

Request Body

Required No

Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-2020-07

Method	GET
Path	/admin/api/2020-07/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Updates an existing theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-2020-07

Method	PUT
Path	/admin/api/2020-07/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Deletes a theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-2020-07

Method	DELETE
Path	/admin/api/2020-07/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of themes.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-2020-10>

Method GET
Path /admin/api/2020-10/themes.json

Parameters

Parameter	About	Description
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-2020-10>

Method POST
Path /admin/api/2020-10/themes.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves a single theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-2020-10>

Method GET
Path /admin/api/2020-10/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an existing theme.

<https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-2020-10>

Method PUT
Path /admin/api/2020-10/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Request Body

Required	No
Description	No description available

Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Deletes a theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-2020-10

Method	DELETE
Path	/admin/api/2020-10/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of themes.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-2021-01

Method	GET
Path	/admin/api/2021-01/themes.json

Parameters

Parameter	About	Description
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-2021-01

Method	POST
Path	/admin/api/2021-01/themes.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-2021-01

Method GET
Path /admin/api/2021-01/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an existing theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-2021-01

Method PUT
Path /admin/api/2021-01/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes a theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-2021-01

Method DELETE
Path /admin/api/2021-01/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Responses

Response 200 No description available

Retrieves a list of themes.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#index-unstable

Method GET
Path /admin/api/unstable/themes.json

Parameters

Parameter	About	Description
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a theme by providing the public URL of a ZIP file that contains the theme. A new theme is always unpublished by default. To publish a theme when you create it, include "role": "main" in the POST request. The theme will be published only after all of its files have been extracted and stored by Shopify, which might take a couple of minutes.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#create-unstable

Method POST
Path /admin/api/unstable/themes.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a single theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#show-unstable

Method GET
Path /admin/api/unstable/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an existing theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#update-unstable

Method PUT
Path /admin/api/unstable/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes a theme.

https://shopify.dev/docs/admin-api/rest/reference/online-store/theme#destroy-unstable

Method DELETE
Path /admin/api/unstable/themes/{theme_id}.json

Parameters

Parameter	About	Description
theme_id	Required	theme_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of checkouts from the past 90 days

<https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-2020-01>

Method GET
Path /admin/api/2020-01/checkouts/count.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status	Optional	Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

Response	200 No description available
----------	------------------------------

Creates a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-2020-01>

Method POST
Path /admin/api/2020-01/checkouts.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of checkouts from the past 90 days

<https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-2020-04>

Method GET
Path /admin/api/2020-04/checkouts/count.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)

created_at_max	Optional	Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status	Optional	Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

Response	200 No description available
-----------------	------------------------------

Creates a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-2020-04>

Method	POST
Path	/admin/api/2020-04/checkouts.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of checkouts from the past 90 days

<https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-2020-07>

Method	GET
Path	/admin/api/2020-07/checkouts/count.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status	Optional	Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

Response	200 No description available
-----------------	------------------------------

Creates a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-2020-07>

Method	POST
Path	/admin/api/2020-07/checkouts.json

Request Body

Required	No
Description	No description available
Content-type	application/json

Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of checkouts from the past 90 days

https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-2020-10

Method	GET
Path	/admin/api/2020-10/checkouts/count.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status	Optional	Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

Response	200 No description available
----------	------------------------------

Creates a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-2020-10

Method	POST
Path	/admin/api/2020-10/checkouts.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of checkouts from the past 90 days

https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-2021-01

Method	GET
Path	/admin/api/2021-01/checkouts/count.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)

updated_at_min	Optional	Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status	Optional	Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

Response	200 No description available
----------	------------------------------

Creates a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-2021-01

Method	POST
Path	/admin/api/2021-01/checkouts.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of checkouts from the past 90 days

https://shopify.dev/docs/admin-api/rest/reference/orders/abandoned-checkouts#count-unstable

Method	GET
Path	/admin/api/unstable/checkouts/count.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
created_at_min	Optional	Count checkouts created after the specified date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Count checkouts created before the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Count checkouts last updated after the specified date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Count checkouts last updated before the specified date. (format: 2014-04-25T16:15:47-04:00)
status	Optional	Count checkouts with a given status. (default: open) open: Count only open abandoned checkouts. closed: Count only closed abandoned checkouts.

Responses

Response	200 No description available
----------	------------------------------

Creates a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#create-unstable

Method	POST
Path	/admin/api/unstable/checkouts.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

Responses

Response 200 No description available

Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#index-2020-01>

Method GET
Path /admin/api/2020-01/orders.json

Parameters

Parameter	About	Description
ids	Optional	Retrieve only orders specified by a comma-separated list of order IDs.
limit	Optional	The maximum number of results to show on a page. (default: 50, maximum: 250)
since_id	Optional	Show orders after the specified ID.
created_at_min	Optional	Show orders created at or after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Show orders created at or before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show orders last updated at or after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show orders last updated at or before date (format: 2014-04-25T16:15:47-04:00).
processed_at_min	Optional	Show orders imported at or after date (format: 2014-04-25T16:15:47-04:00).
processed_at_max	Optional	Show orders imported at or before date (format: 2014-04-25T16:15:47-04:00).
attribution_app_id	Optional	Show orders attributed to a certain app, specified by the app ID. Set as current to show orders for the app currently consuming the API.
status	Optional	Filter orders by their status. (default: open) open: Show only open orders. closed: Show only closed orders. cancelled: Show only canceled orders. any: Show orders of any status, including archived orders.
financial_status	Optional	Filter orders by their financial status. (default: any) authorized: Show only authorized orders pending: Show only pending orders paid: Show only paid orders partially_paid: Show only partially paid orders refunded: Show only refunded orders voided: Show only voided orders partially_refunded: Show only partially refunded orders any: Show orders of any financial status. unpaid: Show authorized and partially paid orders.
fulfillment_status	Optional	Filter orders by their fulfillment status. (default: any) shipped: Show orders that have been shipped. Returns orders with fulfillment_status of fulfilled. partial: Show partially shipped orders. unshipped: Show orders that have not yet been shipped. Returns orders with fulfillment_status of null. any: Show orders of any fulfillment status. unfulfilled: Returns orders with fulfillment_status of null or partial.
fields	Optional	Retrieve only certain fields, specified by a comma-separated list of fields names.

Responses

Response 200 No description available

Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request:
inventory_behaviour: The behaviour to use when updating inventory. (default: bypass)
bypass: Do not claim inventory.
decrement_ignoring_policy: Ignore the product's inventory policy and claim inventory.
decrement_obeying_policy: Follow the product's inventory policy and claim inventory, if possible.
send_receipt: Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when send_receipt is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin.
send_fulfillment_receipt: Whether to send a shipping confirmation to the customer. Note If you are including shipping_address or billing_address, make sure to pass both first_name and last_name. Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.

https://shopify.dev/docs/admin-api/rest/reference/orders/order#create-2020-01

Method POST
Path /admin/api/2020-01/orders.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a specific order

https://shopify.dev/docs/admin-api/rest/reference/orders/order#show-2020-01

Method GET
Path /admin/api/2020-01/orders/{order_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fields	Optional	Retrieve only certain fields, specified by a comma-separated list of fields names.

Responses

Response 200 No description available

Updates an order

https://shopify.dev/docs/admin-api/rest/reference/orders/order#update-2020-01

Method PUT
Path /admin/api/2020-01/orders/{order_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes an order. Orders that interact with an online gateway can't be deleted.

https://shopify.dev/docs/admin-api/rest/reference/orders/order#destroy-2020-01

Method DELETE
Path /admin/api/2020-01/orders/{order_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves an order count

https://shopify.dev/docs/admin-api/rest/reference/orders/order#count-2020-01

Method	GET
Path	/admin/api/2020-01/orders/count.json

Parameters

Parameter	About	Description
created_at_min	Optional	Count orders created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count orders created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count orders last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count orders last updated before date (format: 2014-04-25T16:15:47-04:00).
status	Optional	Count orders of a given status. (default: open) open: Count open orders. closed: Count closed orders. any: Count orders of any status.
financial_status	Optional	Count orders of a given financial status. (default: any) authorized: Count authorized orders. pending: Count pending orders. paid: Count paid orders. refunded: Count refunded orders. voided: Count voided orders. any: Count orders of any financial status.
fulfillment_status	Optional	Filter orders by their fulfillment status. (default: any) shipped: Show orders that have been shipped. Returns orders with fulfillment_status of fulfilled. partial: Show partially shipped orders. unshipped: Show orders that have not yet been shipped. Returns orders with fulfillment_status of null. any: Show orders of any fulfillment status. unfulfilled: Returns orders with fulfillment_status of null or partial.

Responses

Response	200 No description available
----------	------------------------------

Closes an order

https://shopify.dev/docs/admin-api/rest/reference/orders/order#close-2020-01

Method	POST
Path	/admin/api/2020-01/orders/{order_id}/close.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Re-opens a closed order

https://shopify.dev/docs/admin-api/rest/reference/orders/order#open-2020-01

Method	POST
Path	/admin/api/2020-01/orders/{order_id}/open.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
----------	----

Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<code>null</code>

Responses

Response	200 No description available
-----------------	------------------------------

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see [Migrating to support multiple currencies](#). Cancels an order. Orders that have a fulfillment object can't be canceled.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#cancel-2020-01>

Method	POST
Path	/admin/api/2020-01/orders/{order_id}/cancel.json

Parameters

Parameter	About	Description
order_id	Required	order_id
amount	Optional	The amount to refund. If set, Shopify attempts to void or refund the payment, depending on its status. Shopify refunds through a manual gateway in cases where the original transaction was not made in Shopify. Refunds through a manual gateway are recorded as a refund on Shopify, but the customer is not refunded.
currency	Optional	The currency of the refund that's issued when the order is canceled. Required for multi-currency orders whenever the amount property is provided.
restock deprecated	Optional	Whether to restock refunded items back to your store's inventory. (default: false)
reason	Optional	The reason for the order cancellation. Valid values: customer, inventory, fraud, declined, and other.) (default: other)
email	Optional	Whether to send an email to the customer notifying them of the cancellation. (default: false)
refund	Optional	The refund transactions to perform. Required for some more complex refund situations. For more information, see the Refund API.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<code>null</code>

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#index-2020-04>

Method	GET
Path	/admin/api/2020-04/orders.json

Parameters

Parameter	About	Description
ids	Optional	Retrieve only orders specified by a comma-separated list of order IDs.
limit	Optional	The maximum number of results to show on a page. (default: 50, maximum: 250)
since_id	Optional	Show orders after the specified ID.
created_at_min	Optional	Show orders created at or after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Show orders created at or before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show orders last updated at or after date (format: 2014-04-25T16:15:47-04:00).

updated_at_max	Optional	Show orders last updated at or before date (format: 2014-04-25T16:15:47-04:00).
processed_at_min	Optional	Show orders imported at or after date (format: 2014-04-25T16:15:47-04:00).
processed_at_max	Optional	Show orders imported at or before date (format: 2014-04-25T16:15:47-04:00).
attribution_app_id	Optional	Show orders attributed to a certain app, specified by the app ID. Set as current to show orders for the app currently consuming the API.
status	Optional	Filter orders by their status. (default: open) open: Show only open orders. closed: Show only closed orders. cancelled: Show only canceled orders. any: Show orders of any status, including archived orders.
financial_status	Optional	Filter orders by their financial status. (default: any) authorized: Show only authorized orders pending: Show only pending orders paid: Show only paid orders partially_paid: Show only partially paid orders refunded: Show only refunded orders voided: Show only voided orders partially_refunded: Show only partially refunded orders any: Show orders of any financial status. unpaid: Show authorized and partially paid orders.
fulfillment_status	Optional	Filter orders by their fulfillment status. (default: any) shipped: Show orders that have been shipped. Returns orders with fulfillment_status of fulfilled. partial: Show partially shipped orders. unshipped: Show orders that have not yet been shipped. Returns orders with fulfillment_status of null. any: Show orders of any fulfillment status. unfulfilled: Returns orders with fulfillment_status of null or partial.
fields	Optional	Retrieve only certain fields, specified by a comma-separated list of fields names.

Responses

Response	200 No description available
----------	------------------------------

Creates an order. By default, product inventory is not claimed. When you create an order, you can include the following option parameters in the body of the request:

- inventory_behaviour:** The behaviour to use when updating inventory. (default: bypass)
- bypass:** Do not claim inventory.
- decrement_ignoring_policy:** Ignore the product's inventory policy and claim inventory.
- decrement_obeying_policy:** Follow the product's inventory policy and claim inventory, if possible.
- send_receipt:** Whether to send an order confirmation to the customer. Note If you're working on a private app and order confirmations are still being sent to the customer when send_receipt is set to false, then you need to disable the Storefront API from the private app's page in the Shopify admin.
- send_fulfillment_receipt:** Whether to send a shipping confirmation to the customer. Note If you are including shipping_address or billing_address, make sure to pass both first_name and last_name. Otherwise both these addresses will be ignored. If you're using this endpoint with a trial or Partner development store, then you can create no more than 5 new orders per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#create-2020-04>

Method	POST
Path	/admin/api/2020-04/orders.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a specific order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#show-2020-04>

Method	GET
Path	/admin/api/2020-04/orders/{order_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fields	Optional	Retrieve only certain fields, specified by a comma-separated list of fields names.

Responses

Response	200 No description available
-----------------	------------------------------

Updates an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#update-2020-04>

Method	PUT
Path	/admin/api/2020-04/orders/{order_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
-----------------	------------------------------

Deletes an order. Orders that interact with an online gateway can't be deleted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#destroy-2020-04>

Method	DELETE
Path	/admin/api/2020-04/orders/{order_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves an order count

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#count-2020-04>

Method	GET
Path	/admin/api/2020-04/orders/count.json

Parameters

Parameter	About	Description
created_at_min	Optional	Count orders created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count orders created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count orders last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count orders last updated before date (format: 2014-04-25T16:15:47-04:00).
status	Optional	Count orders of a given status. (default: open) open: Count open orders. closed: Count closed orders. any: Count orders of any status.
financial_status	Optional	Count orders of a given financial status. (default: any) authorized: Count authorized orders. pending: Count pending orders. paid: Count paid orders. refunded: Count refunded orders. voided: Count voided orders. any: Count orders of any financial status.
fulfillment_status	Optional	Filter orders by their fulfillment status. (default: any) shipped: Show orders that have been shipped. Returns orders with fulfillment_status of fulfilled. partial: Show partially shipped orders. unshipped: Show orders that have not yet been shipped. Returns orders with

fulfillment_status of null. any: Show orders of any fulfillment status. unfulfilled: Returns orders with fulfillment_status of null or partial.

Responses

Response	200 No description available
----------	------------------------------

Closes an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#close-2020-04>

Method	POST
Path	/admin/api/2020-04/orders/{order_id}/close.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Re-opens a closed order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#open-2020-04>

Method	POST
Path	/admin/api/2020-04/orders/{order_id}/open.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see [Migrating to support multiple currencies](#). Cancels an order. Orders that have a fulfillment object can't be canceled.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#cancel-2020-04>

Method	POST
Path	/admin/api/2020-04/orders/{order_id}/cancel.json

Parameters

Parameter	About	Description
-----------	-------	-------------

order_id	Optional	Required	order_id
amount	Optional	The amount to refund. If set, Shopify attempts to void or refund the payment, depending on its status. Shopify refunds through a manual gateway in cases where the original transaction was not made in Shopify. Refunds through a manual gateway are recorded as a refund on Shopify, but the customer is not refunded.	
currency	Optional	The currency of the refund that's issued when the order is canceled. Required for multi-currency orders whenever the amount property is provided.	
restock deprecated reason	Optional	Optional	Whether to restock refunded items back to your store's inventory. (default: false)
email	Optional	The reason for the order cancellation. Valid values: customer, inventory, fraud, declined, and other.) (default: other)	
refund	Optional	Optional	Whether to send an email to the customer notifying them of the cancellation. (default: false)
		The refund transactions to perform. Required for some more complex refund situations. For more information, see the Refund API.	

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<code>null</code>

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of orders. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order#index-2020-07>

Method	GET
Path	/admin/api/2020-07/orders.json

Parameters

Parameter	About	Description
ids	Optional	Retrieve only orders specified by a comma-separated list of order IDs.
limit	Optional	The maximum number of results to show on a page. (default: 50, maximum: 250)
since_id	Optional	Show orders after the specified ID.
created_at_min	Optional	Show orders created at or after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Show orders created at or before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show orders last updated at or after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show orders last updated at or before date (format: 2014-04-25T16:15:47-04:00).
processed_at_min	Optional	Show orders imported at or after date (format: 2014-04-25T16:15:47-04:00).
processed_at_max	Optional	Show orders imported at or before date (format: 2014-04-25T16:15:47-04:00).
attribution_app_id	Optional	Show orders attributed to a certain app, specified by the app ID. Set as current to show orders for the app currently consuming the API.
status	Optional	Filter orders by their status. (default: open) open: Show only open orders. closed: Show only closed orders. cancelled: Show only canceled orders. any: Show orders of any status, including archived orders.
financial_status	Optional	Filter orders by their financial status. (default: any) authorized: Show only authorized orders pending: Show only pending orders paid: Show only paid orders partially_paid: Show only partially paid orders refunded: Show only refunded orders voided: Show only voided orders partially_refunded: Show only partially refunded orders any: Show orders of any financial status. unpaid: Show authorized and partially paid orders.
fulfillment_status	Optional	Filter orders by their fulfillment status. (default: any) shipped: Show orders that have been shipped. Returns orders with fulfillment_status of fulfilled. partial: Show partially shipped orders. unshipped: Show orders that have not yet been shipped. Returns orders with fulfillment_status of null. any: Show orders of any fulfillment status. unfulfilled: Returns orders with fulfillment_status of null or partial.
fields	Optional	Retrieve only certain fields, specified by a comma-separated list of fields names.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response

header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-2020-01>

Method GET
Path /admin/api/2020-01/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Responses

Response 200 No description available

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-2020-01>

Method POST
Path /admin/api/2020-01/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-2020-01>

Method GET
Path /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response 200 No description available

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-2020-01>

Method PUT
Path /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-2020-01>

Method DELETE
Path /admin/api/2020-01/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response 200 No description available

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-2020-04>

Method GET
Path /admin/api/2020-04/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Responses

Response 200 No description available

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-2020-04>

Method POST
Path /admin/api/2020-04/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-2020-04>

Method	GET
Path	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response	200 No description available
----------	------------------------------

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-2020-04>

Method	PUT
Path	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-2020-04>

Method	DELETE
Path	/admin/api/2020-04/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response

header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-2020-07>

Method GET
Path /admin/api/2020-07/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Responses

Response 200 No description available

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-2020-07>

Method POST
Path /admin/api/2020-07/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-2020-07>

Method GET
Path /admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response 200 No description available

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-2020-07>

Method PUT
Path /admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-2020-07>

Method DELETE
Path /admin/api/2020-07/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response 200 No description available

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-2020-10>

Method GET
Path /admin/api/2020-10/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Responses

Response 200 No description available

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-2020-10>

Method POST
Path /admin/api/2020-10/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-2020-10>

Method GET
Path /admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response 200 No description available

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-2020-10>

Method PUT
Path /admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response 200 No description available

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-2020-10>

Method DELETE
Path /admin/api/2020-10/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response 200 No description available

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response

header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-2021-01>

Method GET
Path /admin/api/2021-01/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Responses

Response 200 No description available

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-2021-01>

Method POST
Path /admin/api/2021-01/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-2021-01>

Method GET
Path /admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response 200 No description available

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-2021-01>

Method PUT
Path /admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-2021-01>

Method DELETE
Path /admin/api/2021-01/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response 200 No description available

Retrieves a list of all order risks for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#index-unstable>

Method GET
Path /admin/api/unstable/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Responses

Response 200 No description available

Creates an order risk for an order

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#create-unstable>

Method POST
Path /admin/api/unstable/orders/{order_id}/risks.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```


Responses

Response	200 No description available
----------	------------------------------

Retrieves a single order risk by its ID

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#show-unstable>

Method	GET
Path	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response	200 No description available
----------	------------------------------

Updates an order risk Note You cannot modify an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#update-unstable>

Method	PUT
Path	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Deletes an order risk for an order Note You cannot delete an order risk that was created by another application.

<https://shopify.dev/docs/admin-api/rest/reference/orders/order-risk#destroy-unstable>

Method	DELETE
Path	/admin/api/unstable/orders/{order_id}/risks/{risk_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
risk_id	Required	risk_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header.

Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-2020-01>

Method GET
Path /admin/api/2020-01/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response 200 No description available

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see [Migrating to support multiple currencies](#). Creates a refund. Use the [calculate](#) endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-2020-01>

Method POST
Path /admin/api/2020-01/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
restock deprecated	Optional	Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.
notify	Optional	Whether to send a refund notification to the customer.
note	Optional	An optional note attached to a refund.
discrepancy_reason	Optional	An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.
transactions	Optional	A list of transactions to process as refunds.
currency	Optional	The three-letter code (ISO 4217 format) for the currency used for the refund.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

Retrieves a specific refund.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-2020-01>

Method GET
Path /admin/api/2020-01/orders/{order_id}/refunds/{refund_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
refund_id	Required	refund_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response 200 No description available

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see [Migrating to support multiple currencies](#). Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the [calculate](#) endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-2020-01>

Method POST
Path /admin/api/2020-01/orders/{order_id}/refunds/calculate.json

Parameters

Parameter	About	Description
order_id	Required	order_id
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.
currency	Optional	The three-letter code (ISO 4217 format) for the currency used for the refund. Note: Required whenever the shipping amount property is provided.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of refunds for an order. **Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.**

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-2020-04>

Method GET
Path /admin/api/2020-04/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response 200 No description available

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see [Migrating to support multiple currencies](#). **Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.**

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-2020-04>

Method POST
Path /admin/api/2020-04/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
restock deprecated	Optional	Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.
notify	Optional	Whether to send a refund notification to the customer.
note	Optional	An optional note attached to a refund.
discrepancy_reason	Optional	An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.
transactions	Optional	A list of transactions to process as refunds.
currency	Optional	The three-letter code (ISO 4217 format) for the currency used for the refund.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

Retrieves a specific refund.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-2020-04>

Method GET
Path /admin/api/2020-04/orders/{order_id}/refunds/{refund_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
refund_id	Required	refund_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response 200 No description available

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see [Migrating to support multiple currencies](#). Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the [calculate](#) endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-2020-04>

Method POST
Path /admin/api/2020-04/orders/{order_id}/refunds/calculate.json

Parameters

Parameter	About	Description
order_id	Required	order_id
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.
currency	Optional	The three-letter code (ISO 4217 format) for the currency used for the refund. Note: Required whenever the shipping amount property is provided.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-2020-07>

Method GET
Path /admin/api/2020-07/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response 200 No description available

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-2020-07>

Method POST
Path /admin/api/2020-07/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
restock deprecated	Optional	Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.
notify	Optional	Whether to send a refund notification to the customer.
note	Optional	An optional note attached to a refund.
discrepancy_reason	Optional	An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.
transactions	Optional	A list of transactions to process as refunds.
currency	Optional	The three-letter code (ISO 4217 format) for the currency used for the refund.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

null

Responses

Response 200 No description available

Retrieves a specific refund.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-2020-07>

Method GET
Path /admin/api/2020-07/orders/{order_id}/refunds/{refund_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
refund_id	Required	refund_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response 200 No description available

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see [Migrating to support multiple currencies](#). Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the [calculate](#) endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-2020-07>

Method POST
Path /admin/api/2020-07/orders/{order_id}/refunds/calculate.json

Parameters

Parameter	About	Description
order_id	Required	order_id
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.
currency	Optional	The three-letter code (ISO 4217 format) for the currency used for the refund. Note: Required whenever the shipping amount property is provided.

Request Body

Required No
Description No description available
Content-type application/json

Schema for application/json

Type: undefined

Example:

null

Responses

Response 200 No description available

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-2020-10>

Method GET
Path /admin/api/2020-10/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response 200 No description available

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-2020-10>

Method POST
Path /admin/api/2020-10/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
restock deprecated	Optional	Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.
notify	Optional	Whether to send a refund notification to the customer.
note	Optional	An optional note attached to a refund.
discrepancy_reason	Optional	An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.
transactions	Optional	A list of transactions to process as refunds.
currency	Optional	The three-letter code (ISO 4217 format) for the currency used for the refund.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre> null </pre>

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a specific refund.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-2020-10>

Method	GET
Path	/admin/api/2020-10/orders/{order_id}/refunds/{refund_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
refund_id	Required	refund_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response	200 No description available
-----------------	------------------------------

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see [Migrating to support multiple currencies](#). Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the calculate endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-2020-10>

Method	POST
Path	/admin/api/2020-10/orders/{order_id}/refunds/calculate.json

Parameters

Parameter	About	Description
order_id	Required	order_id
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.
currency	Optional	The three-letter code (ISO 4217 format) for the currency used for the refund. Note: Required whenever the shipping amount property is provided.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-2021-01>

Method GET
Path /admin/api/2021-01/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response 200 No description available

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-2021-01>

Method POST
Path /admin/api/2021-01/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
restock deprecated	Optional	Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.
notify	Optional	Whether to send a refund notification to the customer.
note	Optional	An optional note attached to a refund.
discrepancy_reason	Optional	An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.

transactions	Optional	A list of transactions to process as refunds.
currency	Optional	The three-letter code (ISO 4217 format) for the currency used for the refund.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a specific refund.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-2021-01>

Method	GET
Path	/admin/api/2021-01/orders/{order_id}/refunds/{refund_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
refund_id	Required	refund_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response	200 No description available
-----------------	------------------------------

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see [Migrating to support multiple currencies](#). Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the [calculate](#) endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-2021-01>

Method	POST
Path	/admin/api/2021-01/orders/{order_id}/refunds/calculate.json

Parameters

Parameter	About	Description
order_id	Required	order_id
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value

of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.

currency Optional The three-letter code (ISO 4217 format) for the currency used for the refund. Note: Required whenever the shipping amount property is provided.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of refunds for an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#index-unstable>

Method GET
Path /admin/api/unstable/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response 200 No description available

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see Migrating to support multiple currencies. Creates a refund. Use the calculate endpoint to produce the transactions to submit. Note When you use this endpoint with a Partner development store or a trial store, you can create only five refunds per minute.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#create-unstable>

Method POST
Path /admin/api/unstable/orders/{order_id}/refunds.json

Parameters

Parameter	About	Description
order_id	Required	order_id
restock deprecated	Optional	Whether to add the line items back to the store inventory. Use restock_type for refund line items instead.
notify	Optional	Whether to send a refund notification to the customer.
note	Optional	An optional note attached to a refund.
discrepancy_reason	Optional	An optional comment that explains a discrepancy between calculated and actual refund amounts. Used to populate the reason property of the resulting order adjustment object attached to the refund. Valid values: restock, damage, customer, and other.
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line item affects inventory levels. Valid values: no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will

decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. This is required when the value of restock_type is return or cancel. If the item is not already stocked at the location, then the item is connected to the location. An error is returned when the item is connected to a fulfillment service location and a different location is provided.

transactions
currency

Optional
Optional

A list of transactions to process as refunds.
The three-letter code (ISO 4217 format) for the currency used for the refund.

Request Body

Required
Description
Content-type
Schema for
application/json

No
No description available
application/json
Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a specific refund.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#show-unstable>

Method GET
Path /admin/api/unstable/orders/{order_id}/refunds/{refund_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
refund_id	Required	refund_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
in_shop_currency	Optional	Show amounts in the shop currency for the underlying transaction. (default: false)

Responses

Response 200 No description available

Caution For multi-currency orders, the currency property is required whenever the amount property is provided. For more information, see [Migrating to support multiple currencies](#). Calculates refund transactions based on line items and shipping. When you want to create a refund, you should first use the [calculate](#) endpoint to generate accurate refund transactions. Specify the line items that are being refunded, their quantity and restock instructions, and whether you intend to refund shipping costs. If the restock instructions can't be met—for example, because you try to return more items than have been fulfilled—then the endpoint returns modified restock instructions. You can then use the response in the body of the request to create the actual refund. The response includes a transactions object with "kind": "suggested_refund", which must to be changed to "kind" : "refund" for the refund to be accepted.

<https://shopify.dev/docs/admin-api/rest/reference/orders/refund#calculate-unstable>

Method POST
Path /admin/api/unstable/orders/{order_id}/refunds/calculate.json

Parameters

Parameter	About	Description
order_id	Required	order_id
shipping	Optional	Specify how much shipping to refund. It has the following properties: full_refund: Whether to refund all remaining shipping. amount: Set a specific amount to refund for shipping. Takes precedence over full_refund.
refund_line_items	Optional	A list of line item IDs, quantities to refund, and restock instructions. Each entry has the following properties: line_item_id: The ID of a line item to refund. quantity: The quantity to refund. restock_type: How this refund line

item affects inventory levels. Valid values:

no_restock: Refunding these items won't affect inventory. cancel: The items have not yet been fulfilled. The canceled quantity will be added back to the available count. The number of fulfillable units for this line item will decrease. return: The items were already delivered but will be returned to the merchant. The returned quantity will be added back to the available count. The number of fulfillable units for this line item will remain unchanged. location_id: The ID of the location where the items should be restocked. If location_id is not provided and the value of restock_type is return or cancel, then the endpoint returns a suitable location ID. already_stocked: Whether the item is already stocked at the location. If this is false, then creating the refund will connect the item to the location and start stocking it there.

currency Optional The three-letter code (ISO 4217 format) for the currency used for the refund. Note: Required whenever the shipping amount property is provided.

Request Body

Required No
Description No description available
Content-type application/json
Schema for Type: undefined
application/json Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#index-2020-01>

Method GET
Path /admin/api/2020-01/gift_cards.json

Parameters

Parameter	About	Description
status	Optional	Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a gift card

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-2020-01>

Method POST
Path /admin/api/2020-01/gift_cards.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for Type: undefined
application/json Example:

```
null
```

Responses

Response 200 No description available

Retrieves a single gift card by its ID

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-2020-01

Method GET
Path /admin/api/2020-01/gift_cards/{gift_card_id}.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Responses

Response 200 No description available

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-2020-01

Method PUT
Path /admin/api/2020-01/gift_cards/{gift_card_id}.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a count of gift cards

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-2020-01

Method GET
Path /admin/api/2020-01/gift_cards/count.json

Parameters

Parameter	About	Description
status	Optional	Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses

Response 200 No description available

Disables a gift card. Disabling a gift card can't be undone.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-2020-01

Method POST
Path /admin/api/2020-01/gift_cards/{gift_card_id}/disable.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body

Required Description Content-type Schema for application/json	No No description available application/json Type: undefined Example: null
--	---

Responses

Response	200 No description available
-----------------	------------------------------

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-2020-01>

Method	GET
Path	/admin/api/2020-01/gift_cards/search.json

Parameters

Parameter	About	Description
order	Optional	The field and direction to order results by. (default: disabled_at DESC)
query	Optional	The text to search for.
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#index-2020-04>

Method	GET
Path	/admin/api/2020-04/gift_cards.json

Parameters

Parameter	About	Description
status	Optional	Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Creates a gift card

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-2020-04>

Method	POST
Path	/admin/api/2020-04/gift_cards.json

Request Body

Required	No
-----------------	----

Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single gift card by its ID

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-2020-04>

Method	GET
Path	/admin/api/2020-04/gift_cards/{gift_card_id}.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Responses

Response	200 No description available
-----------------	------------------------------

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-2020-04>

Method	PUT
Path	/admin/api/2020-04/gift_cards/{gift_card_id}.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of gift cards

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-2020-04>

Method	GET
Path	/admin/api/2020-04/gift_cards/count.json

Parameters

Parameter	About	Description
status	Optional	Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses

Response	200 No description available
-----------------	------------------------------

Disables a gift card. Disabling a gift card can't be undone.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-2020-04>

Method POST
Path /admin/api/2020-04/gift_cards/{gift_card_id}/disable.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-2020-04>

Method GET
Path /admin/api/2020-04/gift_cards/search.json

Parameters

Parameter	About	Description
order	Optional	The field and direction to order results by. (default: disabled_at DESC)
query	Optional	The text to search for.
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#index-2020-07>

Method GET
Path /admin/api/2020-07/gift_cards.json

Parameters

Parameter	About	Description
status	Optional	Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses	
Response	200 No description available

Creates a gift card

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-2020-07>

Method	POST
Path	/admin/api/2020-07/gift_cards.json

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses	
Response	200 No description available

Retrieves a single gift card by its ID

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-2020-07>

Method	GET
Path	/admin/api/2020-07/gift_cards/{gift_card_id}.json

Parameters		
Parameter	About	Description
gift_card_id	Required	gift_card_id

Responses	
Response	200 No description available

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-2020-07>

Method	PUT
Path	/admin/api/2020-07/gift_cards/{gift_card_id}.json

Parameters		
Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses	
Response	200 No description available

Retrieves a count of gift cards

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-2020-07>

Method GET
Path /admin/api/2020-07/gift_cards/count.json

Parameters

Parameter	About	Description
status	Optional	Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses

Response 200 No description available

Disables a gift card. Disabling a gift card can't be undone.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-2020-07>

Method POST
Path /admin/api/2020-07/gift_cards/{gift_card_id}/disable.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-2020-07>

Method GET
Path /admin/api/2020-07/gift_cards/search.json

Parameters

Parameter	About	Description
order	Optional	The field and direction to order results by. (default: disabled_at DESC)
query	Optional	The text to search for.
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#index-2020-10>

Method GET
Path /admin/api/2020-10/gift_cards.json

Parameters

Parameter	About	Description
status	Optional	Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a gift card

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-2020-10>

Method POST
Path /admin/api/2020-10/gift_cards.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves a single gift card by its ID

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-2020-10>

Method GET
Path /admin/api/2020-10/gift_cards/{gift_card_id}.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Responses

Response 200 No description available

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-2020-10>

Method PUT
Path /admin/api/2020-10/gift_cards/{gift_card_id}.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of gift cards

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-2020-10>

Method	GET
Path	/admin/api/2020-10/gift_cards/count.json

Parameters

Parameter	About	Description
status	Optional	Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses

Response	200 No description available
----------	------------------------------

Disables a gift card. Disabling a gift card can't be undone.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-2020-10>

Method	POST
Path	/admin/api/2020-10/gift_cards/{gift_card_id}/disable.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-2020-10>

Method	GET
Path	/admin/api/2020-10/gift_cards/search.json

Parameters

Parameter	About	Description
order	Optional	The field and direction to order results by. (default: disabled_at DESC)
query	Optional	The text to search for.
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#index-2021-01>

Method GET
Path /admin/api/2021-01/gift_cards.json

Parameters

Parameter	About	Description
status	Optional	Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a gift card

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-2021-01>

Method POST
Path /admin/api/2021-01/gift_cards.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a single gift card by its ID

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-2021-01>

Method GET
Path /admin/api/2021-01/gift_cards/{gift_card_id}.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Responses

Response 200 No description available

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-2021-01>

Method PUT

Path /admin/api/2021-01/gift_cards/{gift_card_id}.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves a count of gift cards

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-2021-01>

Method GET
Path /admin/api/2021-01/gift_cards/count.json

Parameters

Parameter	About	Description
status	Optional	Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses

Response 200 No description available

Disables a gift card. Disabling a gift card can't be undone.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-2021-01>

Method POST
Path /admin/api/2021-01/gift_cards/{gift_card_id}/disable.json

Parameters

Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header.

Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-2021-01

Method GET
Path /admin/api/2021-01/gift_cards/search.json

Parameters

Parameter	About	Description
order	Optional	The field and direction to order results by. (default: disabled_at DESC)
query	Optional	The text to search for.
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a list of gift cards. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#index-unstable

Method GET
Path /admin/api/unstable/gift_cards.json

Parameters

Parameter	About	Description
status	Optional	Retrieve gift cards with a given status. Valid values: enabled: Restrict results to only enabled gift cards disabled: Restrict results to only disabled gift cards
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a gift card

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#create-unstable

Method POST
Path /admin/api/unstable/gift_cards.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a single gift card by its ID

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#show-unstable

Method GET
Path /admin/api/unstable/gift_cards/{gift_card_id}.json

Parameters		
Parameter	About	Description
gift_card_id	Required	gift_card_id
Responses		
Response	200 No description available	

Updates an existing gift card. The gift card's balance can't be changed via the API. You can change only the expiry date, note, and template suffix.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#update-unstable

Method	PUT
Path	/admin/api/unstable/gift_cards/{gift_card_id}.json

Parameters		
Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses	
Response	200 No description available

Retrieves a count of gift cards

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#count-unstable

Method	GET
Path	/admin/api/unstable/gift_cards/count.json

Parameters		
Parameter	About	Description
status	Optional	Count gift cards with a given status. Valid values: enabled: Count only enabled gift cards disabled: Count only disabled gift cards

Responses	
Response	200 No description available

Disables a gift card. Disabling a gift card can't be undone.

https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#disable-unstable

Method	POST
Path	/admin/api/unstable/gift_cards/{gift_card_id}/disable.json

Parameters		
Parameter	About	Description
gift_card_id	Required	gift_card_id

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Searches for gift cards that match a supplied query. The following fields are indexed by search: created_at updated_at disabled_at balance initial_value amount_spent email last_characters Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/giftcard#search-unstable>

Method GET
Path /admin/api/unstable/gift_cards/search.json

Parameters

Parameter	About	Description
order	Optional	The field and direction to order results by. (default: disabled_at DESC)
query	Optional	The text to search for.
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-2020-01>

Method GET
Path /admin/api/2020-01/users.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info	Optional	A unique ID used to access a certain page of results.

Responses

Response 200 No description available

Retrieves a single user

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-2020-01>

Method GET
Path /admin/api/2020-01/users/{user_id}.json

Parameters

Parameter	About	Description
user_id	Required	user_id

Responses

Response 200 No description available

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token

was created for a specific user of the shop.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-2020-01>

Method GET
Path /admin/api/2020-01/users/current.json

Responses

Response 200 No description available

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-2020-04>

Method GET
Path /admin/api/2020-04/users.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info	Optional	A unique ID used to access a certain page of results.

Responses

Response 200 No description available

Retrieves a single user

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-2020-04>

Method GET
Path /admin/api/2020-04/users/{user_id}.json

Parameters

Parameter	About	Description
user_id	Required	user_id

Responses

Response 200 No description available

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-2020-04>

Method GET
Path /admin/api/2020-04/users/current.json

Responses

Response 200 No description available

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-2020-07>

Method GET
Path /admin/api/2020-07/users.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info	Optional	A unique ID used to access a certain page of results.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single user

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-2020-07>

Method	GET
Path	/admin/api/2020-07/users/{user_id}.json

Parameters

Parameter	About	Description
user_id	Required	user_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-2020-07>

Method	GET
Path	/admin/api/2020-07/users/current.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-2020-10>

Method	GET
Path	/admin/api/2020-10/users.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info	Optional	A unique ID used to access a certain page of results.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single user

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-2020-10>

Method	GET
Path	/admin/api/2020-10/users/{user_id}.json

Parameters

Parameter	About	Description
user_id	Required	user_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-2020-10>

Method	GET
Path	/admin/api/2020-10/users/current.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-2021-01>

Method	GET
Path	/admin/api/2021-01/users.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info	Optional	A unique ID used to access a certain page of results.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single user

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-2021-01>

Method	GET
Path	/admin/api/2021-01/users/{user_id}.json

Parameters

Parameter	About	Description
user_id	Required	user_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-2021-01>

Method	GET
Path	/admin/api/2021-01/users/current.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of all users. Note: As of version 2021-01, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#index-unstable>

Method GET
Path /admin/api/unstable/users.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show on a page. (default: 50, maximum: 250)
page_info	Optional	A unique ID used to access a certain page of results.

Responses

Response 200 No description available

Retrieves a single user

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#show-unstable>

Method GET
Path /admin/api/unstable/users/{user_id}.json

Parameters

Parameter	About	Description
user_id	Required	user_id

Responses

Response 200 No description available

Retrieves information about the user account associated with the access token used to make this API request. This request works only when the access token was created for a specific user of the shop.

<https://shopify.dev/docs/admin-api/rest/reference/plus/user#current-unstable>

Method GET
Path /admin/api/unstable/users/current.json

Responses

Response 200 No description available

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-2020-01>

Method GET
Path /admin/api/2020-01/collects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Adds a product to a custom collection.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-2020-01

Method POST
Path /admin/api/2020-01/collects.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a specific collect by its ID.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-2020-01

Method GET
Path /admin/api/2020-01/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Removes a product from a collection.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-2020-01

Method DELETE
Path /admin/api/2020-01/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id

Responses

Response 200 No description available

Retrieves a count of collects.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#count-2020-01

Method GET
Path /admin/api/2020-01/collects/count.json

Parameters

Parameter	About	Description
collection_id	Optional	collection_id

Responses

Response 200 No description available

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the

page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-2020-04

Method GET
Path /admin/api/2020-04/collects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Adds a product to a custom collection.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-2020-04

Method POST
Path /admin/api/2020-04/collects.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a specific collect by its ID.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-2020-04

Method GET
Path /admin/api/2020-04/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Removes a product from a collection.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-2020-04

Method DELETE
Path /admin/api/2020-04/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id

Responses

Response 200 No description available

Retrieves a count of collects.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#count-2020-04>

Method GET
Path /admin/api/2020-04/collects/count.json

Parameters

Parameter	About	Description
collection_id	Optional	collection_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-2020-07>

Method GET
Path /admin/api/2020-07/collects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Adds a product to a custom collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-2020-07>

Method POST
Path /admin/api/2020-07/collects.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a specific collect by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-2020-07>

Method GET
Path /admin/api/2020-07/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Removes a product from a collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-2020-07>

Method DELETE
Path /admin/api/2020-07/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id

Responses

Response 200 No description available

Retrieves a count of collects.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#count-2020-07>

Method GET
Path /admin/api/2020-07/collects/count.json

Parameters

Parameter	About	Description
collection_id	Optional	collection_id

Responses

Response 200 No description available

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-2020-10>

Method GET
Path /admin/api/2020-10/collects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Adds a product to a custom collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-2020-10>

Method POST
Path /admin/api/2020-10/collects.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a specific collect by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-2020-10>

Method	GET
Path	/admin/api/2020-10/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Removes a product from a collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-2020-10>

Method	DELETE
Path	/admin/api/2020-10/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of collects.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#count-2020-10>

Method	GET
Path	/admin/api/2020-10/collects/count.json

Parameters

Parameter	About	Description
collection_id	Optional	collection_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-2021-01>

Method	GET
Path	/admin/api/2021-01/collects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Adds a product to a custom collection.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-2021-01

Method POST
Path /admin/api/2021-01/collects.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for Type: undefined
application/json Example:

```
null
```

Responses

Response 200 No description available

Retrieves a specific collect by its ID.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-2021-01

Method GET
Path /admin/api/2021-01/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Removes a product from a collection.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-2021-01

Method DELETE
Path /admin/api/2021-01/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id

Responses

Response 200 No description available

Retrieves a count of collects.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#count-2021-01

Method GET
Path /admin/api/2021-01/collects/count.json

Parameters

Parameter	About	Description
collection_id	Optional	collection_id

Responses

Response 200 No description available

Retrieves a list of collects. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#index-unstable>

Method GET
Path /admin/api/unstable/collects.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to show. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Adds a product to a custom collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#create-unstable>

Method POST
Path /admin/api/unstable/collects.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

Retrieves a specific collect by its ID.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#show-unstable>

Method GET
Path /admin/api/unstable/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Removes a product from a collection.

<https://shopify.dev/docs/admin-api/rest/reference/products/collect#destroy-unstable>

Method DELETE
Path /admin/api/unstable/collects/{collect_id}.json

Parameters

Parameter	About	Description
collect_id	Required	collect_id

Responses

Response 200 No description available

Retrieves a count of collects.

https://shopify.dev/docs/admin-api/rest/reference/products/collect#count-unstable

Method GET
Path /admin/api/unstable/collects/count.json

Parameters

Parameter	About	Description
collection_id	Optional	collection_id

Responses

Response 200 No description available

Retrieves a single collection

https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-2020-01

Method GET
Path /admin/api/2020-01/collections/{collection_id}.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-2020-01

Method GET
Path /admin/api/2020-01/collections/{collection_id}/products.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
limit	Optional	The number of products to retrieve. (default: 50, maximum: 250)

Responses

Response 200 No description available

Retrieves a single collection

https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-2020-04

Method GET
Path /admin/api/2020-04/collections/{collection_id}.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response

200 No description available

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-2020-04>

Method GET
Path /admin/api/2020-04/collections/{collection_id}/products.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
limit	Optional	The number of products to retrieve. (default: 50, maximum: 250)

Responses

Response 200 No description available

Retrieves a single collection

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-2020-07>

Method GET
Path /admin/api/2020-07/collections/{collection_id}.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-2020-07>

Method GET
Path /admin/api/2020-07/collections/{collection_id}/products.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
limit	Optional	The number of products to retrieve. (default: 50, maximum: 250)

Responses

Response 200 No description available

Retrieves a single collection

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-2020-10>

Method GET
Path /admin/api/2020-10/collections/{collection_id}.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-2020-10>

Method	GET
Path	/admin/api/2020-10/collections/{collection_id}/products.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
limit	Optional	The number of products to retrieve. (default: 50, maximum: 250)

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single collection

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-2021-01>

Method	GET
Path	/admin/api/2021-01/collections/{collection_id}.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-2021-01>

Method	GET
Path	/admin/api/2021-01/collections/{collection_id}/products.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
limit	Optional	The number of products to retrieve. (default: 50, maximum: 250)

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single collection

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#show-unstable>

Method GET
Path /admin/api/unstable/collections/{collection_id}.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Retrieve a list of products belonging to a collection. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.. The products returned are sorted by the collection's sort order.

<https://shopify.dev/docs/admin-api/rest/reference/products/collection#products-unstable>

Method GET
Path /admin/api/unstable/collections/{collection_id}/products.json

Parameters

Parameter	About	Description
collection_id	Required	collection_id
limit	Optional	The number of products to retrieve. (default: 50, maximum: 250)

Responses

Response 200 No description available

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-2020-01>

Method GET
Path /admin/api/2020-01/custom_collections.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
ids	Optional	Show only collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show custom collections with a given title.
product_id	Optional	Show custom collections that include a given product.
handle	Optional	Filter by custom collection handle.
updated_at_min	Optional	Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Show custom collections with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a custom collection

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-2020-01

Method POST
Path /admin/api/2020-01/custom_collections.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of custom collections

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-2020-01

Method GET
Path /admin/api/2020-01/custom_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Count custom collections with given title.
product_id	Optional	Count custom collections that include a given product.
updated_at_min	Optional	Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.

Responses

Response 200 No description available

Retrieves a single custom collection

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-2020-01

Method GET
Path /admin/api/2020-01/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an existing custom collection

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-2020-01

Method PUT
Path /admin/api/2020-01/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
-----------	-------	-------------

custom_collection_id Required custom_collection_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Deletes a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-2020-01>

Method DELETE
Path /admin/api/2020-01/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id

Responses

Response 200 No description available

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-2020-04>

Method GET
Path /admin/api/2020-04/custom_collections.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
ids	Optional	Show only collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show custom collections with a given title.
product_id	Optional	Show custom collections that include a given product.
handle	Optional	Filter by custom collection handle.
updated_at_min	Optional	Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Show custom collections with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-2020-04>

Method POST
Path /admin/api/2020-04/custom_collections.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of custom collections

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-2020-04

Method	GET
Path	/admin/api/2020-04/custom_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Count custom collections with given title.
product_id	Optional	Count custom collections that include a given product.
updated_at_min	Optional	Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single custom collection

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-2020-04

Method	GET
Path	/admin/api/2020-04/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates an existing custom collection

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-2020-04

Method	PUT
Path	/admin/api/2020-04/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id

Request Body

Required	No
Description	No description available
Content-type	application/json

Schema for
application/json

Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Deletes a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-2020-04>

Method	DELETE
Path	/admin/api/2020-04/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-2020-07>

Method	GET
Path	/admin/api/2020-07/custom_collections.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
ids	Optional	Show only collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show custom collections with a given title.
product_id	Optional	Show custom collections that include a given product.
handle	Optional	Filter by custom collection handle.
updated_at_min	Optional	Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Show custom collections with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Creates a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-2020-07>

Method	POST
Path	/admin/api/2020-07/custom_collections.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of custom collections

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-2020-07>

Method	GET
Path	/admin/api/2020-07/custom_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Count custom collections with given title.
product_id	Optional	Count custom collections that include a given product.
updated_at_min	Optional	Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-2020-07>

Method	GET
Path	/admin/api/2020-07/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates an existing custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-2020-07>

Method	PUT
Path	/admin/api/2020-07/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Deletes a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-2020-07>

Method DELETE
Path /admin/api/2020-07/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id

Responses

Response 200 No description available

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-2020-10>

Method GET
Path /admin/api/2020-10/custom_collections.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
ids	Optional	Show only collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show custom collections with a given title.
product_id	Optional	Show custom collections that include a given product.
handle	Optional	Filter by custom collection handle.
updated_at_min	Optional	Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Show custom collections with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-2020-10>

Method POST
Path /admin/api/2020-10/custom_collections.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of custom collections

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-2020-10

Method GET
Path /admin/api/2020-10/custom_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Count custom collections with given title.
product_id	Optional	Count custom collections that include a given product.
updated_at_min	Optional	Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.

Responses

Response 200 No description available

Retrieves a single custom collection

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-2020-10

Method GET
Path /admin/api/2020-10/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an existing custom collection

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-2020-10

Method PUT
Path /admin/api/2020-10/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Deletes a custom collection

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-2020-10

Method DELETE
Path /admin/api/2020-10/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-2021-01>

Method	GET
Path	/admin/api/2021-01/custom_collections.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
ids	Optional	Show only collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show custom collections with a given title.
product_id	Optional	Show custom collections that include a given product.
handle	Optional	Filter by custom collection handle.
updated_at_min	Optional	Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Show custom collections with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Creates a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-2021-01>

Method	POST
Path	/admin/api/2021-01/custom_collections.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of custom collections

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-2021-01>

Method	GET
Path	/admin/api/2021-01/custom_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Count custom collections with given title.
product_id	Optional	Count custom collections that include a given product.
updated_at_min	Optional	Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-2021-01>

Method	GET
Path	/admin/api/2021-01/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Updates an existing custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-2021-01>

Method	PUT
Path	/admin/api/2021-01/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
-----------------	------------------------------

Deletes a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-2021-01>

Method	DELETE
Path	/admin/api/2021-01/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id

Responses

Retrieves a list of custom collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#index-unstable>

Method GET
Path /admin/api/unstable/custom_collections.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
ids	Optional	Show only collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show custom collections with a given title.
product_id	Optional	Show custom collections that include a given product.
handle	Optional	Filter by custom collection handle.
updated_at_min	Optional	Show custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Show custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).
published_at_min	Optional	Show custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Show custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Show custom collections with a given published status. (default: any) published: Show only published custom collections. unpublished: Show only unpublished custom collections. any: Show custom collections of any published status.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a custom collection

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#create-unstable>

Method POST
Path /admin/api/unstable/custom_collections.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of custom collections

<https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#count-unstable>

Method GET
Path /admin/api/unstable/custom_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Count custom collections with given title.
product_id	Optional	Count custom collections that include a given product.
updated_at_min	Optional	Count custom collections last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count custom collections last updated before date (format: 2014-04-25T16:15:47-04:00).

published_at_min	Optional	Count custom collections published after date (format: 2014-04-25T16:15:47-04:00).
published_at_max	Optional	Count custom collections published before date (format: 2014-04-25T16:15:47-04:00).
published_status	Optional	Count custom collections with a given published status. (default: any) published: Count only published custom collections. unpublished: Count only unpublished custom collections. any: Count custom collections of any published status.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single custom collection

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#show-unstable

Method	GET
Path	/admin/api/unstable/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates an existing custom collection

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#update-unstable

Method	PUT
Path	/admin/api/unstable/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Deletes a custom collection

https://shopify.dev/docs/admin-api/rest/reference/products/customcollection#destroy-unstable

Method	DELETE
Path	/admin/api/unstable/custom_collections/{custom_collection_id}.json

Parameters

Parameter	About	Description
custom_collection_id	Required	custom_collection_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the

page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/products/product#index-2020-01>

Method GET
Path /admin/api/2020-01/products.json

Parameters

Parameter	About	Description
ids	Optional	Return only products specified by a comma-separated list of product IDs.
limit	Optional	Return up to this many results per page. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Filter results by product title.
vendor	Optional	Filter results by product vendor.
handle	Optional	Filter results by product handle.
product_type	Optional	Filter results by product type.
status	Optional	Return products by their status. (default: active) active: Show only active products. archived: Show only archived products. draft: Show only draft products.
collection_id	Optional	Filter results by product collection ID.
created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
presentment_currencies	Optional	Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

Response 200 No description available

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: **metafields_global_title_tag**: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. **metafields_global_description_tag**: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#create-2020-01>

Method POST
Path /admin/api/2020-01/products.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a count of products.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#count-2020-01>

Method GET
Path /admin/api/2020-01/products/count.json

Parameters

Parameter	About	Description
vendor	Optional	Filter results by product vendor.
product_type	Optional	Filter results by product type.
collection_id	Optional	Filter results by collection ID.
created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#show-2020-01>

Method	GET
Path	/admin/api/2020-01/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties:

metafields_global_title_tag: The name of the product used for SEO purposes.

Generally added to the <meta name='title'> tag.
metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#update-2020-01>

Method	PUT
Path	/admin/api/2020-01/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Deletes a product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-2020-01>

Method	DELETE
--------	--------

Path /admin/api/2020-01/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Responses

Response 200 No description available

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#index-2020-04>

Method GET
Path /admin/api/2020-04/products.json

Parameters

Parameter	About	Description
ids	Optional	Return only products specified by a comma-separated list of product IDs.
limit	Optional	Return up to this many results per page. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Filter results by product title.
vendor	Optional	Filter results by product vendor.
handle	Optional	Filter results by product handle.
product_type	Optional	Filter results by product type.
status	Optional	Return products by their status. (default: active) active: Show only active products. archived: Show only archived products. draft: Show only draft products.
collection_id	Optional	Filter results by product collection ID.
created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
presentment_currencies	Optional	Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

Response 200 No description available

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#create-2020-04>

Method POST
Path /admin/api/2020-04/products.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves a count of products.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#count-2020-04>

Method GET
Path /admin/api/2020-04/products/count.json

Parameters

Parameter	About	Description
vendor	Optional	Filter results by product vendor.
product_type	Optional	Filter results by product type.
collection_id	Optional	Filter results by collection ID.
created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

Response 200 No description available

Retrieves a single product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#show-2020-04>

Method GET
Path /admin/api/2020-04/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties:

metafields_global_title_tag: The name of the product used for SEO purposes.

Generally added to the <meta name='title'> tag.

metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#update-2020-04>

Method PUT
Path /admin/api/2020-04/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

null

Responses

Response 200 No description available

Deletes a product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-2020-04>

Method DELETE
Path /admin/api/2020-04/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Responses

Response 200 No description available

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#index-2020-07>

Method GET
Path /admin/api/2020-07/products.json

Parameters

Parameter	About	Description
ids	Optional	Return only products specified by a comma-separated list of product IDs.
limit	Optional	Return up to this many results per page. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Filter results by product title.
vendor	Optional	Filter results by product vendor.
handle	Optional	Filter results by product handle.
product_type	Optional	Filter results by product type.
status	Optional	Return products by their status. (default: active) active: Show only active products. archived: Show only archived products. draft: Show only draft products.
collection_id	Optional	Filter results by product collection ID.
created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
presentment_currencies	Optional	Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

Response 200 No description available

Creates a new product. If you want to set the product's SEO information, then you can use the following properties:
metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag.
metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#create-2020-07>

Method POST
Path /admin/api/2020-07/products.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of products.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#count-2020-07>

Method GET
Path /admin/api/2020-07/products/count.json

Parameters

Parameter	About	Description
vendor	Optional	Filter results by product vendor.
product_type	Optional	Filter results by product type.
collection_id	Optional	Filter results by collection ID.
created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

Response 200 No description available

Retrieves a single product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#show-2020-07>

Method GET
Path /admin/api/2020-07/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties:

metafields_global_title_tag: The name of the product used for SEO purposes.

metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#update-2020-07>

Method PUT
Path /admin/api/2020-07/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Deletes a product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-2020-07>

Method DELETE
Path /admin/api/2020-07/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Responses

Response 200 No description available

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#index-2020-10>

Method GET
Path /admin/api/2020-10/products.json

Parameters

Parameter	About	Description
ids	Optional	Return only products specified by a comma-separated list of product IDs.
limit	Optional	Return up to this many results per page. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Filter results by product title.
vendor	Optional	Filter results by product vendor.
handle	Optional	Filter results by product handle.
product_type	Optional	Filter results by product type.
status	Optional	Return products by their status. (default: active) active: Show only active products. archived: Show only archived products. draft: Show only draft products.
collection_id	Optional	Filter results by product collection ID.
created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
presentment_currencies	Optional	Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

Response	200 No description available
----------	------------------------------

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: **metafields_global_title_tag:** The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. **metafields_global_description_tag:** A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#create-2020-10>

Method	POST
Path	/admin/api/2020-10/products.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of products.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#count-2020-10>

Method	GET
Path	/admin/api/2020-10/products/count.json

Parameters

Parameter	About	Description
vendor	Optional	Filter results by product vendor.
product_type	Optional	Filter results by product type.
collection_id	Optional	Filter results by collection ID.
created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#show-2020-10>

Method	GET
Path	/admin/api/2020-10/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties:

metafields_global_title_tag: The name of the product used for SEO purposes.

metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the `<meta name='description'>` tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#update-2020-10>

Method PUT
Path /admin/api/2020-10/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Deletes a product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-2020-10>

Method DELETE
Path /admin/api/2020-10/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Responses

Response 200 No description available

Retrieves a list of products. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#index-2021-01>

Method GET
Path /admin/api/2021-01/products.json

Parameters

Parameter	About	Description
ids	Optional	Return only products specified by a comma-separated list of product IDs.
limit	Optional	Return up to this many results per page. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Filter results by product title.
vendor	Optional	Filter results by product vendor.
handle	Optional	Filter results by product handle.
product_type	Optional	Filter results by product type.
status	Optional	Return products by their status. (default: active) active: Show only active products. archived: Show only archived products. draft: Show only draft products.
collection_id	Optional	Filter results by product collection ID.

created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
presentment_currencies	Optional	Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

Response	200 No description available
-----------------	------------------------------

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: **metafields_global_title_tag:** The name of the product used for SEO purposes. Generally added to the `<meta name='title'>` tag. **metafields_global_description_tag:** A description of the product used for SEO purposes. Generally added to the `<meta name='description'>` tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#create-2021-01>

Method	POST
Path	/admin/api/2021-01/products.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

```
null
```

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of products.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#count-2021-01>

Method	GET
Path	/admin/api/2021-01/products/count.json

Parameters

Parameter	About	Description
vendor	Optional	Filter results by product vendor.
product_type	Optional	Filter results by product type.
collection_id	Optional	Filter results by collection ID.
created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#show-2021-01>

Method GET
Path /admin/api/2021-01/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties:
metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag.
metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#update-2021-01>

Method PUT
Path /admin/api/2021-01/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Deletes a product.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-2021-01>

Method DELETE
Path /admin/api/2021-01/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Responses

Response 200 No description available

Retrieves a list of products. **Note:** As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#index-unstable>

Method GET
Path /admin/api/unstable/products.json

Parameters

Parameter	About	Description
ids	Optional	Return only products specified by a comma-separated list of product IDs.
limit	Optional	Return up to this many results per page. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Filter results by product title.
vendor	Optional	Filter results by product vendor.
handle	Optional	Filter results by product handle.
product_type	Optional	Filter results by product type.
status	Optional	Return products by their status. (default: active) active: Show only active products. archived: Show only archived products. draft: Show only draft products.
collection_id	Optional	Filter results by product collection ID.
created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.
presentment_currencies	Optional	Return presentment prices in only certain currencies, specified by a comma-separated list of ISO 4217 currency codes.

Responses

Response	200 No description available
----------	------------------------------

Creates a new product. If you want to set the product's SEO information, then you can use the following properties: **metafields_global_title_tag:** The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag. **metafields_global_description_tag:** A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#create-unstable>

Method	POST
Path	/admin/api/unstable/products.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of products.

<https://shopify.dev/docs/admin-api/rest/reference/products/product#count-unstable>

Method	GET
Path	/admin/api/unstable/products/count.json

Parameters

Parameter	About	Description
vendor	Optional	Filter results by product vendor.
product_type	Optional	Filter results by product type.
collection_id	Optional	Filter results by collection ID.
created_at_min	Optional	Show products created after date. (format: 2014-04-25T16:15:47-04:00)
created_at_max	Optional	Show products created before date. (format: 2014-04-25T16:15:47-04:00)
updated_at_min	Optional	Show products last updated after date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show products last updated before date. (format: 2014-04-25T16:15:47-04:00)

published_at_min	Optional	Show products published after date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show products published before date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Return products by their published status (default: any) published: Show only published products. unpublished: Show only unpublished products. any: Show all products.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single product.

https://shopify.dev/docs/admin-api/rest/reference/products/product#show-unstable

Method	GET
Path	/admin/api/unstable/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Updates a product and its variants and images. If you want to update the product's SEO information, then you can use the following properties:
metafields_global_title_tag: The name of the product used for SEO purposes. Generally added to the <meta name='title'> tag.
metafields_global_description_tag: A description of the product used for SEO purposes. Generally added to the <meta name='description'> tag.

https://shopify.dev/docs/admin-api/rest/reference/products/product#update-unstable

Method	PUT
Path	/admin/api/unstable/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Deletes a product.

https://shopify.dev/docs/admin-api/rest/reference/products/product#destroy-unstable

Method	DELETE
Path	/admin/api/unstable/products/{product_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Responses

Response 200 No description available

Get all product images

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-2020-01

Method GET
Path /admin/api/2020-01/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID
fields	Optional	comma-separated list of fields to include in the response

Responses

Response 200 No description available

Create a new product image

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-2020-01

Method POST
Path /admin/api/2020-01/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Get a count of all product images

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-2020-01

Method GET
Path /admin/api/2020-01/products/{product_id}/images/count.json

Parameters

Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID

Responses

Response 200 No description available

Get a single product image by id

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-2020-01

Method GET
Path /admin/api/2020-01/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id
fields	Optional	comma-separated list of fields to include in the response

Responses

Response	200 No description available
----------	------------------------------

Modify an existing product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-2020-01>

Method	PUT
Path	/admin/api/2020-01/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-2020-01>

Method	DELETE
Path	/admin/api/2020-01/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Responses

Response	200 No description available
----------	------------------------------

Get all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-2020-04>

Method	GET
Path	/admin/api/2020-04/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID
fields	Optional	comma-separated list of fields to include in the response

Responses

Response	200 No description available
----------	------------------------------

Create a new product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-2020-04>

Method POST
Path /admin/api/2020-04/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Get a count of all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-2020-04>

Method GET
Path /admin/api/2020-04/products/{product_id}/images/count.json

Parameters

Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID

Responses

Response	200 No description available
----------	------------------------------

Get a single product image by id

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-2020-04>

Method GET
Path /admin/api/2020-04/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id
fields	Optional	comma-separated list of fields to include in the response

Responses

Response	200 No description available
----------	------------------------------

Modify an existing product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-2020-04>

Method PUT
Path /admin/api/2020-04/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Request Body

Required	No
Description	No description available

Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-2020-04

Method	DELETE
Path	/admin/api/2020-04/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Responses

Response	200 No description available
-----------------	------------------------------

Get all product images

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-2020-07

Method	GET
Path	/admin/api/2020-07/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID
fields	Optional	comma-separated list of fields to include in the response

Responses

Response	200 No description available
-----------------	------------------------------

Create a new product image

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-2020-07

Method	POST
Path	/admin/api/2020-07/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Get a count of all product images

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-2020-07

Method GET
Path /admin/api/2020-07/products/{product_id}/images/count.json

Parameters

Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID

Responses

Response 200 No description available

Get a single product image by id

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-2020-07

Method GET
Path /admin/api/2020-07/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id
fields	Optional	comma-separated list of fields to include in the response

Responses

Response 200 No description available

Modify an existing product image

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-2020-07

Method PUT
Path /admin/api/2020-07/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-2020-07

Method DELETE
Path /admin/api/2020-07/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Responses

Response 200 No description available

Get all product images

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-2020-10

Method GET
Path /admin/api/2020-10/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID
fields	Optional	comma-separated list of fields to include in the response

Responses

Response 200 No description available

Create a new product image

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-2020-10

Method POST
Path /admin/api/2020-10/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Get a count of all product images

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-2020-10

Method GET
Path /admin/api/2020-10/products/{product_id}/images/count.json

Parameters

Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID

Responses

Response 200 No description available

Get a single product image by id

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-2020-10

Method GET
Path /admin/api/2020-10/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id
fields	Optional	comma-separated list of fields to include in the response

Responses

Response 200 No description available

Modify an existing product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-2020-10>

Method PUT
Path /admin/api/2020-10/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-2020-10>

Method DELETE
Path /admin/api/2020-10/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Responses

Response 200 No description available

Get all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-2021-01>

Method GET
Path /admin/api/2021-01/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID
fields	Optional	comma-separated list of fields to include in the response

Responses

Response 200 No description available

Create a new product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-2021-01>

Method POST
Path /admin/api/2021-01/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre> null </pre>

Responses	
Response	200 No description available

Get a count of all product images

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-2021-01

Method	GET
Path	/admin/api/2021-01/products/{product_id}/images/count.json

Parameters		
Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID

Responses	
Response	200 No description available

Get a single product image by id

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-2021-01

Method	GET
Path	/admin/api/2021-01/products/{product_id}/images/{image_id}.json

Parameters		
Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id
fields	Optional	comma-separated list of fields to include in the response

Responses	
Response	200 No description available

Modify an existing product image

https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-2021-01

Method	PUT
Path	/admin/api/2021-01/products/{product_id}/images/{image_id}.json

Parameters		
Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response 200 No description available

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-2021-01>

Method DELETE
Path /admin/api/2021-01/products/{product_id}/images/{image_id}.json

Parameters

Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Responses

Response 200 No description available

Get all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#index-unstable>

Method GET
Path /admin/api/unstable/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID
fields	Optional	comma-separated list of fields to include in the response

Responses

Response 200 No description available

Create a new product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#create-unstable>

Method POST
Path /admin/api/unstable/products/{product_id}/images.json

Parameters

Parameter	About	Description
product_id	Required	product_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Get a count of all product images

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#count-unstable>

Method GET
Path /admin/api/unstable/products/{product_id}/images/count.json

Parameters		
Parameter	About	Description
product_id	Required	product_id
since_id	Optional	Restrict results to after the specified ID
Responses		
Response	200 No description available	

Get a single product image by id

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#show-unstable>

Method	GET
Path	/admin/api/unstable/products/{product_id}/images/{image_id}.json

Parameters		
Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id
fields	Optional	comma-separated list of fields to include in the response

Responses		
Response	200 No description available	

Modify an existing product image

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#update-unstable>

Method	PUT
Path	/admin/api/unstable/products/{product_id}/images/{image_id}.json

Parameters		
Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses		
Response	200 No description available	

<https://shopify.dev/docs/admin-api/rest/reference/products/product-image#destroy-unstable>

Method	DELETE
Path	/admin/api/unstable/products/{product_id}/images/{image_id}.json

Parameters		
Parameter	About	Description
product_id	Required	product_id
image_id	Required	image_id

Responses		
Response	200 No description available	

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-2020-01>

Method GET
Path /admin/api/2020-01/smart_collections.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
ids	Optional	Show only the smart collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that includes the specified product.
handle	Optional	Filter results by smart collection handle.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a new smart collection using the specified rules.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-2020-01>

Method POST
Path /admin/api/2020-01/smart_collections.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of smart collections

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-2020-01>

Method GET
Path /admin/api/2020-01/smart_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that include the specified product.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)

published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.
-------------------------	----------	---

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-2020-01

Method	GET
Path	/admin/api/2020-01/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates an existing smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-2020-01

Method	PUT
Path	/admin/api/2020-01/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Removes a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-2020-01

Method	DELETE
Path	/admin/api/2020-01/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Responses

Response	200 No description available
----------	------------------------------

Updates the ordering type of products in a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-2020-01

Method	PUT
Path	/admin/api/2020-01/smart_collections/{smart_collection_id}/order.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
products	Optional	An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order	Optional	The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	Optional	products[]

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-2020-04>

Method	GET
Path	/admin/api/2020-04/smart_collections.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
ids	Optional	Show only the smart collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that includes the specified product.
handle	Optional	Filter results by smart collection handle.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Creates a new smart collection using the specified rules.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-2020-04>

Method	POST
Path	/admin/api/2020-04/smart_collections.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves a count of smart collections

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-2020-04>

Method GET
Path /admin/api/2020-04/smart_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that include the specified product.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.

Responses

Response 200 No description available

Retrieves a single smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-2020-04>

Method GET
Path /admin/api/2020-04/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an existing smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-2020-04>

Method PUT
Path /admin/api/2020-04/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Removes a smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-2020-04>

Method DELETE
Path /admin/api/2020-04/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Responses

Response 200 No description available

Updates the ordering type of products in a smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-2020-04>

Method PUT
Path /admin/api/2020-04/smart_collections/{smart_collection_id}/order.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
products	Optional	An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order	Optional	The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	Optional	products[]

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-2020-07>

Method GET
Path /admin/api/2020-07/smart_collections.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
ids	Optional	Show only the smart collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that includes the specified product.
handle	Optional	Filter results by smart collection handle.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart

fields Optional collections. any: Show all smart collections.
Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a new smart collection using the specified rules.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-2020-07>

Method POST
Path /admin/api/2020-07/smart_collections.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of smart collections

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-2020-07>

Method GET
Path /admin/api/2020-07/smart_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that include the specified product.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.

Responses

Response 200 No description available

Retrieves a single smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-2020-07>

Method GET
Path /admin/api/2020-07/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an existing smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-2020-07

Method PUT
Path /admin/api/2020-07/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Removes a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-2020-07

Method DELETE
Path /admin/api/2020-07/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Responses

Response 200 No description available

Updates the ordering type of products in a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-2020-07

Method PUT
Path /admin/api/2020-07/smart_collections/{smart_collection_id}/order.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
products	Optional	An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order	Optional	The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	Optional	products[]

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-2020-10>

Method GET
Path /admin/api/2020-10/smart_collections.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
ids	Optional	Show only the smart collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that includes the specified product.
handle	Optional	Filter results by smart collection handle.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Creates a new smart collection using the specified rules.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-2020-10>

Method POST
Path /admin/api/2020-10/smart_collections.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of smart collections

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-2020-10>

Method GET
Path /admin/api/2020-10/smart_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that include the specified product.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)

published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.
-------------------------	----------	---

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-2020-10

Method	GET
Path	/admin/api/2020-10/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates an existing smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-2020-10

Method	PUT
Path	/admin/api/2020-10/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Removes a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-2020-10

Method	DELETE
Path	/admin/api/2020-10/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Responses

Response	200 No description available
----------	------------------------------

Updates the ordering type of products in a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-2020-10

Method	PUT
Path	/admin/api/2020-10/smart_collections/{smart_collection_id}/order.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
products	Optional	An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order	Optional	The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	Optional	products[]

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-2021-01>

Method	GET
Path	/admin/api/2021-01/smart_collections.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
ids	Optional	Show only the smart collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that includes the specified product.
handle	Optional	Filter results by smart collection handle.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Creates a new smart collection using the specified rules.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-2021-01>

Method	POST
Path	/admin/api/2021-01/smart_collections.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response 200 No description available

Retrieves a count of smart collections

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-2021-01>

Method GET
Path /admin/api/2021-01/smart_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that include the specified product.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.

Responses

Response 200 No description available

Retrieves a single smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-2021-01>

Method GET
Path /admin/api/2021-01/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Updates an existing smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-2021-01>

Method PUT
Path /admin/api/2021-01/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Removes a smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-2021-01>

Method DELETE
Path /admin/api/2021-01/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Responses

Response 200 No description available

Updates the ordering type of products in a smart collection

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-2021-01>

Method PUT
Path /admin/api/2021-01/smart_collections/{smart_collection_id}/order.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
products	Optional	An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order	Optional	The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	Optional	products[]

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of smart collections. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#index-unstable>

Method GET
Path /admin/api/unstable/smart_collections.json

Parameters

Parameter	About	Description
limit	Optional	The number of results to show. (default: 50, maximum: 250)
ids	Optional	Show only the smart collections specified by a comma-separated list of IDs.
since_id	Optional	Restrict results to after the specified ID.
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that includes the specified product.
handle	Optional	Filter results by smart collection handle.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart

fields	Optional	collections. any: Show all smart collections. Show only certain fields, specified by a comma-separated list of field names.
--------	----------	--

Responses

Response	200 No description available
----------	------------------------------

Creates a new smart collection using the specified rules.

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#create-unstable

Method	POST
Path	/admin/api/unstable/smart_collections.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of smart collections

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#count-unstable

Method	GET
Path	/admin/api/unstable/smart_collections/count.json

Parameters

Parameter	About	Description
title	Optional	Show smart collections with the specified title.
product_id	Optional	Show smart collections that include the specified product.
updated_at_min	Optional	Show smart collections last updated after this date. (format: 2014-04-25T16:15:47-04:00)
updated_at_max	Optional	Show smart collections last updated before this date. (format: 2014-04-25T16:15:47-04:00)
published_at_min	Optional	Show smart collections published after this date. (format: 2014-04-25T16:15:47-04:00)
published_at_max	Optional	Show smart collections published before this date. (format: 2014-04-25T16:15:47-04:00)
published_status	Optional	Filter results based on the published status of smart collections. (default: any) published: Show only published smart collections. unpublished: Show only unpublished smart collections. any: Show all smart collections.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#show-unstable

Method	GET
Path	/admin/api/unstable/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Updates an existing smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#update-unstable

Method PUT
Path /admin/api/unstable/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Removes a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#destroy-unstable

Method DELETE
Path /admin/api/unstable/smart_collections/{smart_collection_id}.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id

Responses

Response 200 No description available

Updates the ordering type of products in a smart collection

https://shopify.dev/docs/admin-api/rest/reference/products/smartcollection#order-unstable

Method PUT
Path /admin/api/unstable/smart_collections/{smart_collection_id}/order.json

Parameters

Parameter	About	Description
smart_collection_id	Required	smart_collection_id
products	Optional	An array of product IDs, in the order that you want them to appear at the top of the collection. When products is specified but empty, any previously sorted products are cleared.
sort_order	Optional	The type of sorting to apply. Valid values are listed in the Properties section above. (default: (current value))
products[]	Optional	products[]

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Completes a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-2020-01

Method POST
Path /admin/api/2020-01/checkouts/{token}/complete.json

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-2020-01

Method GET
Path /admin/api/2020-01/checkouts/{token}.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Modifies an existing checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-2020-01

Method PUT
Path /admin/api/2020-01/checkouts/{token}.json

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price

in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-2020-01

Method GET
Path /admin/api/2020-01/checkouts/{token}/shipping_rates.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Completes a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-2020-04>

Method POST
Path /admin/api/2020-04/checkouts/{token}/complete.json

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-2020-04>

Method GET
Path /admin/api/2020-04/checkouts/{token}.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Modifies an existing checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-2020-04>

Method PUT
Path /admin/api/2020-04/checkouts/{token}.json

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required Description Content-type Schema for application/json	No No description available application/json Type: undefined Example: null
---	--

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-2020-04

Method Path	GET /admin/api/2020-04/checkouts/{token}/shipping_rates.json
-------------	---

Parameters

Parameter	About	Description
token	Required	token

Responses

Response	200 No description available
----------	------------------------------

Completes a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-2020-07

Method Path	POST /admin/api/2020-07/checkouts/{token}/complete.json
-------------	--

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required Description Content-type Schema for application/json	No No description available application/json Type: undefined Example: null
---	--

Responses

Response	200 No description available
----------	------------------------------

Retrieves a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-2020-07

Method Path	GET /admin/api/2020-07/checkouts/{token}.json
-------------	--

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Modifies an existing checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-2020-07>

Method PUT
Path /admin/api/2020-07/checkouts/{token}.json

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-2020-07

Method GET
Path /admin/api/2020-07/checkouts/{token}/shipping_rates.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Completes a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-2020-10>

Method POST
Path /admin/api/2020-10/checkouts/{token}/complete.json

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-2020-10

Method	GET
Path	/admin/api/2020-10/checkouts/{token}.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response	200 No description available
----------	------------------------------

Modifies an existing checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-2020-10

Method	PUT
Path	/admin/api/2020-10/checkouts/{token}.json

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-2020-10

Method	GET
Path	/admin/api/2020-10/checkouts/{token}/shipping_rates.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response	200 No description available
----------	------------------------------

Completes a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-2021-01

Method POST
Path /admin/api/2021-01/checkouts/{token}/complete.json

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-2021-01

Method GET
Path /admin/api/2021-01/checkouts/{token}.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Modifies an existing checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-2021-01

Method PUT
Path /admin/api/2021-01/checkouts/{token}.json

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price

in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-2021-01

Method GET
Path /admin/api/2021-01/checkouts/{token}/shipping_rates.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Completes a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#complete-unstable>

Method POST
Path /admin/api/unstable/checkouts/{token}/complete.json

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#show-unstable>

Method GET
Path /admin/api/unstable/checkouts/{token}.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Modifies an existing checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#update-unstable>

Method PUT
Path /admin/api/unstable/checkouts/{token}.json

Parameters

Parameter	About	Description
token	Required	token

Request Body

Required Description
Content-type
Schema for application/json

No
No description available
application/json
Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a list of available shipping rates for the specified checkout. Implementers need to poll this endpoint until rates become available. Each shipping rate contains the checkout's new subtotal price, total tax, and total price in the event that this shipping rate is selected. This can be used to update the UI without performing further API requests. To apply a shipping rate, update the checkout's shipping line with the handle of the selected rate.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/checkout#shipping_rates-unstable

Method GET
Path /admin/api/unstable/checkouts/{token}/shipping_rates.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-2020-01>

Method GET
Path /admin/api/2020-01/collection_listings.json

Parameters

Parameter	About	Description
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response 200 No description available

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-2020-01

Method GET
Path /admin/api/2020-01/collection_listings/{collection_listing_id}/product_ids.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response	200 No description available
----------	------------------------------

Retrieve a specific collection listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-2020-01>

Method	GET
Path	/admin/api/2020-01/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response	200 No description available
----------	------------------------------

Create a collection listing to publish a collection to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-2020-01>

Method	PUT
Path	/admin/api/2020-01/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Delete a collection listing to unpublish a collection from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-2020-01>

Method	DELETE
Path	/admin/api/2020-01/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response	200 No description available
----------	------------------------------

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-2020-04>

Method	GET
Path	/admin/api/2020-04/collection_listings.json

Parameters

Parameter	About	Description
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response	200 No description available
----------	------------------------------

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-2020-04

Method	GET
Path	/admin/api/2020-04/collection_listings/{collection_listing_id}/product_ids.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response	200 No description available
----------	------------------------------

Retrieve a specific collection listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-2020-04>

Method	GET
Path	/admin/api/2020-04/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response	200 No description available
----------	------------------------------

Create a collection listing to publish a collection to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-2020-04>

Method	PUT
Path	/admin/api/2020-04/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Delete a collection listing to unpublish a collection from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-2020-04>

Method DELETE
Path /admin/api/2020-04/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response 200 No description available

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-2020-07>

Method GET
Path /admin/api/2020-07/collection_listings.json

Parameters

Parameter	About	Description
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response 200 No description available

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-2020-07

Method GET
Path /admin/api/2020-07/collection_listings/{collection_listing_id}/product_ids.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response 200 No description available

Retrieve a specific collection listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-2020-07>

Method GET
Path /admin/api/2020-07/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response 200 No description available

Create a collection listing to publish a collection to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-2020-07>

Method PUT
Path /admin/api/2020-07/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Delete a collection listing to unpublish a collection from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-2020-07>

Method DELETE
Path /admin/api/2020-07/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response 200 No description available

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-2020-10>

Method GET
Path /admin/api/2020-10/collection_listings.json

Parameters

Parameter	About	Description
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response 200 No description available

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-2020-10

Method GET
Path /admin/api/2020-10/collection_listings/{collection_listing_id}/product_ids.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response	200 No description available
----------	------------------------------

Retrieve a specific collection listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-2020-10>

Method	GET
Path	/admin/api/2020-10/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response	200 No description available
----------	------------------------------

Create a collection listing to publish a collection to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-2020-10>

Method	PUT
Path	/admin/api/2020-10/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Delete a collection listing to unpublish a collection from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-2020-10>

Method	DELETE
Path	/admin/api/2020-10/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response	200 No description available
----------	------------------------------

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in

the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-2021-01

Method GET
Path /admin/api/2021-01/collection_listings.json

Parameters

Parameter	About	Description
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response 200 No description available

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-2021-01

Method GET
Path /admin/api/2021-01/collection_listings/{collection_listing_id}/product_ids.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response 200 No description available

Retrieve a specific collection listing that is published to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-2021-01

Method GET
Path /admin/api/2021-01/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response 200 No description available

Create a collection listing to publish a collection to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-2021-01

Method PUT
Path /admin/api/2021-01/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for Type: undefined
application/json Example:

null

Responses

Response 200 No description available

Delete a collection listing to unpublish a collection from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-2021-01>

Method DELETE
Path /admin/api/2021-01/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response 200 No description available

Retrieve collection listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#index-unstable>

Method GET
Path /admin/api/unstable/collection_listings.json

Parameters

Parameter	About	Description
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response 200 No description available

Retrieve product_ids that are published to a collection_id. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#product_ids-unstable

Method GET
Path /admin/api/unstable/collection_listings/{collection_listing_id}/product_ids.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response 200 No description available

Retrieve a specific collection listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#show-unstable>

Method GET
Path /admin/api/unstable/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response	200 No description available
----------	------------------------------

Create a collection listing to publish a collection to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#create-unstable>

Method PUT
Path /admin/api/unstable/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
 Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Delete a collection listing to unpublish a collection from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/collectionlisting#destroy-unstable>

Method DELETE
Path /admin/api/unstable/collection_listings/{collection_listing_id}.json

Parameters

Parameter	About	Description
collection_listing_id	Required	collection_listing_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of payments on a particular checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-2020-01>

Method GET
Path /admin/api/2020-01/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response	200 No description available
----------	------------------------------

Creates a payment on a checkout using the session ID returned by the card vault

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-2020-01

Method POST
Path /admin/api/2020-01/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token
amount required	Optional	The amount of the payment.
request_details required	Optional	The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.
session_id required	Optional	A session ID provided by the card vault when creating a payment session.
unique_token required	Optional	A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Retrieves the payment information for an existing payment

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-2020-01>

Method	GET
Path	/admin/api/2020-01/checkouts/{token}/payments/{payment_id}.json

Parameters

Parameter	About	Description
token	Required	token
payment_id	Required	payment_id

Responses

Response	200 No description available
----------	------------------------------

Counts the number of payments attempted on a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-2020-01>

Method	GET
Path	/admin/api/2020-01/checkouts/{token}/payments/count.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of payments on a particular checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-2020-04>

Method	GET
Path	/admin/api/2020-04/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Creates a payment on a checkout using the session ID returned by the card vault

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-2020-04

Method POST
Path /admin/api/2020-04/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token
amount required	Optional	The amount of the payment.
request_details required	Optional	The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.
session_id required	Optional	A session ID provided by the card vault when creating a payment session.
unique_token required	Optional	A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves the payment information for an existing payment

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-2020-04

Method GET
Path /admin/api/2020-04/checkouts/{token}/payments/{payment_id}.json

Parameters

Parameter	About	Description
token	Required	token
payment_id	Required	payment_id

Responses

Response 200 No description available

Counts the number of payments attempted on a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-2020-04

Method GET
Path /admin/api/2020-04/checkouts/{token}/payments/count.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Retrieves a list of payments on a particular checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-2020-07

Method GET
Path /admin/api/2020-07/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Creates a payment on a checkout using the session ID returned by the card vault

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-2020-07

Method POST
Path /admin/api/2020-07/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token
amount required	Optional	The amount of the payment.
request_details required	Optional	The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.
session_id required	Optional	A session ID provided by the card vault when creating a payment session.
unique_token required	Optional	A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves the payment information for an existing payment

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-2020-07>

Method GET
Path /admin/api/2020-07/checkouts/{token}/payments/{payment_id}.json

Parameters

Parameter	About	Description
token	Required	token
payment_id	Required	payment_id

Responses

Response 200 No description available

Counts the number of payments attempted on a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-2020-07>

Method GET
Path /admin/api/2020-07/checkouts/{token}/payments/count.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of payments on a particular checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-2020-10>

Method	GET
Path	/admin/api/2020-10/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response	200 No description available
----------	------------------------------

Creates a payment on a checkout using the session ID returned by the card vault

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-2020-10

Method	POST
Path	/admin/api/2020-10/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token
amount required	Optional	The amount of the payment.
request_detailsOptional required	The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.	
session_id required	Optional	A session ID provided by the card vault when creating a payment session.
unique_token required	Optional	A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves the payment information for an existing payment

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-2020-10>

Method	GET
Path	/admin/api/2020-10/checkouts/{token}/payments/{payment_id}.json

Parameters

Parameter	About	Description
token	Required	token
payment_id	Required	payment_id

Responses

Response	200 No description available
----------	------------------------------

Counts the number of payments attempted on a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-2020-10

Method GET
Path /admin/api/2020-10/checkouts/{token}/payments/count.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Retrieves a list of payments on a particular checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-2021-01

Method GET
Path /admin/api/2021-01/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Creates a payment on a checkout using the session ID returned by the card vault

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-2021-01

Method POST
Path /admin/api/2021-01/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token
amount required	Optional	The amount of the payment.
request_detailsOptional required		The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.
session_id required	Optional	A session ID provided by the card vault when creating a payment session.
unique_token required	Optional	A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves the payment information for an existing payment

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-2021-01

Method GET
Path /admin/api/2021-01/checkouts/{token}/payments/{payment_id}.json

Parameters

Parameter	About	Description
-----------	-------	-------------

token	Required	token
payment_id	Required	payment_id

Responses

Response	200 No description available
----------	------------------------------

Counts the number of payments attempted on a checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-2021-01

Method	GET
Path	/admin/api/2021-01/checkouts/{token}/payments/count.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of payments on a particular checkout

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#index-unstable

Method	GET
Path	/admin/api/unstable/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response	200 No description available
----------	------------------------------

Creates a payment on a checkout using the session ID returned by the card vault

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#create_payment-unstable

Method	POST
Path	/admin/api/unstable/checkouts/{token}/payments.json

Parameters

Parameter	About	Description
token	Required	token
amount	Optional	The amount of the payment.
request_details	Optional	The details of the request, including the following attributes: ip_address: The IP address of the customer. accept_language: The language preferences of the customer, in the same format as a standard Accept-Language request header. user_agent: The user agent string for the customer's device.
session_id	Optional	A session ID provided by the card vault when creating a payment session.
unique_token	Optional	A unique idempotency token generated by your app. This can be any value, but must be unique across all payment requests.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:

null

Responses

Response	200 No description available
----------	------------------------------

Retrieves the payment information for an existing payment

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#show-unstable>

Method GET
Path /admin/api/unstable/checkouts/{token}/payments/{payment_id}.json

Parameters

Parameter	About	Description
token	Required	token
payment_id	Required	payment_id

Responses

Response 200 No description available

Counts the number of payments attempted on a checkout

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/payment#count-unstable>

Method GET
Path /admin/api/unstable/checkouts/{token}/payments/count.json

Parameters

Parameter	About	Description
token	Required	token

Responses

Response 200 No description available

Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#index-2020-01>

Method GET
Path /admin/api/2020-01/product_listings.json

Parameters

Parameter	About	Description
product_ids	Optional	A comma-separated list of product ids
limit	Optional	Amount of results (default: 50, maximum: 1000)
collection_id	Optional	Filter by products belonging to a particular collection
updated_at_min	Optional	Filter by products last updated after a certain date and time (formatted in ISO 8601)
handle	Optional	Filter by product handle

Responses

Response 200 No description available

Retrieve product_ids that are published to your app. Maximum 1,000 results per page.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#product_ids-2020-01

Method GET
Path /admin/api/2020-01/product_listings/product_ids.json

Parameters

Parameter	About	Description
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response 200 No description available

Retrieve a count of products that are published to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#count-2020-01

Method GET
Path /admin/api/2020-01/product_listings/count.json

Responses

Response 200 No description available

Retrieve a specific product listing that is published to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#show-2020-01

Method GET
Path /admin/api/2020-01/product_listings/{product_listing_id}.json

Parameters

Parameter	About	Description
product_listing_id	Required	product_listing_id

Responses

Response 200 No description available

Create a product listing to publish a product to your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#create-2020-01

Method PUT
Path /admin/api/2020-01/product_listings/{product_listing_id}.json

Parameters

Parameter	About	Description
product_listing_id	Required	product_listing_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Delete a product listing to unpublish a product from your app

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#destroy-2020-01

Method DELETE
Path /admin/api/2020-01/product_listings/{product_listing_id}.json

Parameters

Parameter	About	Description
product_listing_id	Required	product_listing_id

Responses

Response 200 No description available

Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the

response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#index-2020-04>

Method GET
Path /admin/api/2020-04/product_listings.json

Parameters

Parameter	About	Description
product_ids	Optional	A comma-separated list of product ids
limit	Optional	Amount of results (default: 50, maximum: 1000)
collection_id	Optional	Filter by products belonging to a particular collection
updated_at_min	Optional	Filter by products last updated after a certain date and time (formatted in ISO 8601)
handle	Optional	Filter by product handle

Responses

Response 200 No description available

Retrieve product_ids that are published to your app. Maximum 1,000 results per page.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#product_ids-2020-04

Method GET
Path /admin/api/2020-04/product_listings/product_ids.json

Parameters

Parameter	About	Description
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response 200 No description available

Retrieve a count of products that are published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#count-2020-04>

Method GET
Path /admin/api/2020-04/product_listings/count.json

Responses

Response 200 No description available

Retrieve a specific product listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#show-2020-04>

Method GET
Path /admin/api/2020-04/product_listings/{product_listing_id}.json

Parameters

Parameter	About	Description
product_listing_id	Required	product_listing_id

Responses

Response 200 No description available

Create a product listing to publish a product to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#create-2020-04>

Method PUT
Path /admin/api/2020-04/product_listings/{product_listing_id}.json

Parameters

Parameter	About	Description
product_listing_id	Required	product_listing_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Delete a product listing to unpublish a product from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#destroy-2020-04>

Method	DELETE
Path	/admin/api/2020-04/product_listings/{product_listing_id}.json

Parameters

Parameter	About	Description
product_listing_id	Required	product_listing_id

Responses

Response	200 No description available
----------	------------------------------

Retrieve product listings that are published to your app. Note: As of version 2019-07, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#index-2020-07>

Method	GET
Path	/admin/api/2020-07/product_listings.json

Parameters

Parameter	About	Description
product_ids	Optional	A comma-separated list of product ids
limit	Optional	Amount of results (default: 50, maximum: 1000)
collection_id	Optional	Filter by products belonging to a particular collection
updated_at_min	Optional	Filter by products last updated after a certain date and time (formatted in ISO 8601)
handle	Optional	Filter by product handle

Responses

Response	200 No description available
----------	------------------------------

Retrieve product_ids that are published to your app. Maximum 1,000 results per page.

https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#product_ids-2020-07

Method	GET
Path	/admin/api/2020-07/product_listings/product_ids.json

Parameters

Parameter	About	Description
limit	Optional	Amount of results (default: 50, maximum: 1000)

Responses

Response	200 No description available
----------	------------------------------

Retrieve a count of products that are published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#count-2020-07>

Method	GET
Path	/admin/api/2020-07/product_listings/count.json

Responses

Response	200 No description available
----------	------------------------------

Retrieve a specific product listing that is published to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#show-2020-07>

Method	GET
Path	/admin/api/2020-07/product_listings/{product_listing_id}.json

Parameters

Parameter	About	Description
product_listing_id	Required	product_listing_id

Responses

Response	200 No description available
----------	------------------------------

Create a product listing to publish a product to your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#create-2020-07>

Method	PUT
Path	/admin/api/2020-07/product_listings/{product_listing_id}.json

Parameters

Parameter	About	Description
product_listing_id	Required	product_listing_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Delete a product listing to unpublish a product from your app

<https://shopify.dev/docs/admin-api/rest/reference/sales-channels/productlisting#destroy-2020-07>

Method	DELETE
Path	/admin/api/2020-07/product_listings/{product_listing_id}.json

Parameters

Parameter	About	Description
product_listing_id	Required	product_listing_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of fulfillment orders on a shop for a specific app.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-2020-01>

Method GET
Path /admin/api/2020-01/assigned_fulfillment_orders.json

Parameters

Parameter	About	Description
assignment_status	Optional	The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items.
location_ids	Optional	The IDs of the assigned locations of the fulfillment orders that should be returned.
location_ids[]	Optional	location_ids[]

Responses

Response 200 No description available

Retrieves a list of fulfillment orders on a shop for a specific app.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-2020-04>

Method GET
Path /admin/api/2020-04/assigned_fulfillment_orders.json

Parameters

Parameter	About	Description
assignment_status	Optional	The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items.
location_ids	Optional	The IDs of the assigned locations of the fulfillment orders that should be returned.
location_ids[]	Optional	location_ids[]

Responses

Response 200 No description available

Retrieves a list of fulfillment orders on a shop for a specific app.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-2020-07>

Method GET
Path /admin/api/2020-07/assigned_fulfillment_orders.json

Parameters

Parameter	About	Description
assignment_status	Optional	The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items.
location_ids	Optional	The IDs of the assigned locations of the fulfillment orders that should be returned.
location_ids[]	Optional	location_ids[]

Responses

Response 200 No description available

Retrieves a list of fulfillment orders on a shop for a specific app.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-2020-10>

Method GET
Path /admin/api/2020-10/assigned_fulfillment_orders.json

Parameters

Parameter	About	Description
assignment_status	Optional	The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items.
location_ids	Optional	The IDs of the assigned locations of the fulfillment orders that should be returned.
location_ids[]	Optional	location_ids[]

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of fulfillment orders on a shop for a specific app.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-2021-01>

Method	GET
Path	/admin/api/2021-01/assigned_fulfillment_orders.json

Parameters

Parameter	About	Description
assignment_status	Optional	The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items.
location_ids	Optional	The IDs of the assigned locations of the fulfillment orders that should be returned.
location_ids[]	Optional	location_ids[]

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of fulfillment orders on a shop for a specific app.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/assignedfulfillmentorder#index-unstable>

Method	GET
Path	/admin/api/unstable/assigned_fulfillment_orders.json

Parameters

Parameter	About	Description
assignment_status	Optional	The assignment status of the fulfillment orders that should be returned: cancellation_requested: Fulfillment orders for which the merchant has requested cancellation of the previously accepted fulfillment request. fulfillment_requested: Fulfillment orders for which the merchant has requested fulfillment. fulfillment_accepted: Fulfillment orders for which the merchant's fulfillment request has been accepted. Any number of fulfillments can be created on these fulfillment orders to completely fulfill the requested items.
location_ids	Optional	The IDs of the assigned locations of the fulfillment orders that should be returned.
location_ids[]	Optional	location_ids[]

Responses

Response	200 No description available
----------	------------------------------

Sends a cancellation request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-2020-01>

Method	POST
Path	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json

Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-2020-01>

Method	POST
Path	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for accepting the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-2020-01>

Method	POST
Path	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Sends a cancellation request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-2020-04>

Method	POST
Path	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for the cancellation request.
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
	Example:	
	null	
Responses		
Response	200 No description available	

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-2020-04>

Method

Path

POST

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for accepting the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-2020-04>

Method

Path

POST

/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Sends a cancellation request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-2020-07>

Method POST
Path /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-2020-07>

Method POST
Path /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for accepting the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-2020-07>

Method POST
Path /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response 200 No description available

Sends a cancellation request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-2020-10>

Method POST
Path /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for the cancellation request.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-2020-10>

Method POST
Path /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for accepting the cancellation request.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-2020-10>

Method POST
Path /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the cancellation request.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Sends a cancellation request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-2021-01>

Method POST
Path /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for the cancellation request.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-2021-01>

Method POST
Path /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for accepting the cancellation request.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-2021-01>

Method POST

Path /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Sends a cancellation request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#create-unstable>

Method POST
Path /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Accepts a cancellation request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#accept-unstable>

Method POST
Path /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for accepting the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Rejects a cancellation request sent to a fulfillment service for a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/cancellationrequest#reject-unstable

Method POST
Path /admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancellation_request/reject.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the cancellation request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a list of carrier services

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-2020-01

Method GET
Path /admin/api/2020-01/carrier_services.json

Responses

Response 200 No description available

Creates a carrier service

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-2020-01

Method POST
Path /admin/api/2020-01/carrier_services.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a single carrier service by its ID

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-2020-01

Method GET
Path /admin/api/2020-01/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses

Response	200 No description available
----------	------------------------------

Updates a carrier service. Only the app that creates a carrier service can update it.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-2020-01>

Method	PUT
Path	/admin/api/2020-01/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Deletes a carrier service

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-2020-01>

Method	DELETE
Path	/admin/api/2020-01/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of carrier services

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-2020-04>

Method	GET
Path	/admin/api/2020-04/carrier_services.json

Responses

Response	200 No description available
----------	------------------------------

Creates a carrier service

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-2020-04>

Method	POST
Path	/admin/api/2020-04/carrier_services.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single carrier service by its ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-2020-04>

Method	GET
Path	/admin/api/2020-04/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses

Response	200 No description available
----------	------------------------------

Updates a carrier service. Only the app that creates a carrier service can update it.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-2020-04>

Method	PUT
Path	/admin/api/2020-04/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Deletes a carrier service

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-2020-04>

Method	DELETE
Path	/admin/api/2020-04/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of carrier services

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-2020-07>

Method	GET
Path	/admin/api/2020-07/carrier_services.json

Responses

Response	200 No description available
----------	------------------------------

Creates a carrier service

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-2020-07

Method POST
Path /admin/api/2020-07/carrier_services.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a single carrier service by its ID

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-2020-07

Method GET
Path /admin/api/2020-07/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses

Response 200 No description available

Updates a carrier service. Only the app that creates a carrier service can update it.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-2020-07

Method PUT
Path /admin/api/2020-07/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Deletes a carrier service

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-2020-07

Method DELETE
Path /admin/api/2020-07/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses	
Response	200 No description available

Retrieves a list of carrier services

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-2020-10

Method	GET
Path	/admin/api/2020-10/carrier_services.json

Responses	
Response	200 No description available

Creates a carrier service

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-2020-10

Method	POST
Path	/admin/api/2020-10/carrier_services.json

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses	
Response	200 No description available

Retrieves a single carrier service by its ID

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-2020-10

Method	GET
Path	/admin/api/2020-10/carrier_services/{carrier_service_id}.json

Parameters		
Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses	
Response	200 No description available

Updates a carrier service. Only the app that creates a carrier service can update it.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-2020-10

Method	PUT
Path	/admin/api/2020-10/carrier_services/{carrier_service_id}.json

Parameters		
Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Deletes a carrier service

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-2020-10

Method	DELETE
Path	/admin/api/2020-10/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of carrier services

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-2021-01

Method	GET
Path	/admin/api/2021-01/carrier_services.json

Responses

Response	200 No description available
----------	------------------------------

Creates a carrier service

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-2021-01

Method	POST
Path	/admin/api/2021-01/carrier_services.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single carrier service by its ID

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-2021-01

Method	GET
Path	/admin/api/2021-01/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses

Response	200 No description available
----------	------------------------------

Updates a carrier service. Only the app that creates a carrier service can update it.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-2021-01

Method PUT
Path /admin/api/2021-01/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Deletes a carrier service

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-2021-01

Method DELETE
Path /admin/api/2021-01/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of carrier services

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#index-unstable

Method GET
Path /admin/api/unstable/carrier_services.json

Responses

Response	200 No description available
----------	------------------------------

Creates a carrier service

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#create-unstable

Method POST
Path /admin/api/unstable/carrier_services.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single carrier service by its ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#show-unstable>

Method GET
Path /admin/api/unstable/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses

Response 200 No description available

Updates a carrier service. Only the app that creates a carrier service can update it.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#update-unstable>

Method PUT
Path /admin/api/unstable/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Deletes a carrier service

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/carrierservice#destroy-unstable>

Method DELETE
Path /admin/api/unstable/carrier_services/{carrier_service_id}.json

Parameters

Parameter	About	Description
carrier_service_id	Required	carrier_service_id

Responses

Response 200 No description available

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#index-2020-01>

Method GET
Path /admin/api/2020-01/orders/{order_id}/fulfillments.json

Parameters

Parameter	About	Description
order_id	Required	order_id

created_at_max	Optional	Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields	Optional	A comma-separated list of fields to include in the response.
limit	Optional	Limit the amount of results. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_max	Optional	Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).

Responses

Response	200 No description available
----------	------------------------------

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the **tracking_company** and **tracking_numbers** fields, and Shopify will generate the **tracking_url** for you. If you're creating a fulfillment for an unsupported carrier (not in the **tracking_company** list), then send the **tracking_company**, **tracking_numbers**, and **tracking_urls** fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#create-2020-01>

Method	POST
Path	/admin/api/2020-01/orders/{order_id}/fulfillments.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves fulfillments associated with a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#indexV2-2020-01>

Method

Path

GET

/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order that is associated with the fulfillments.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of fulfillments associated with a specific order

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-2020-01>

Method	GET	
Path	/admin/api/2020-01/orders/{order_id}/fulfillments/count.json	
Parameters		
Parameter	About	Description
order_id	Required	order_id
created_at_min	Optional	Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
Responses		
Response	200 No description available	

Retrieve a specific fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-2020-01>

Method	GET	
Path	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json	
Parameters		
Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fields	Optional	Comma-separated list of fields to include in the response.
Responses		
Response	200 No description available	

Update information associated with a fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-2020-01>

Method

Path

PUT
/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-2020-01

Method POST
Path /admin/api/2020-01/fulfillments.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-2020-01

Method POST
Path /admin/api/2020-01/fulfillments/{fulfillment_id}/update_tracking.json

Parameters

Parameter	About	Description
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Mark a fulfillment as complete

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#complete-2020-01

Method POST
Path /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	


```
null
```

Responses

Response	200 No description available
----------	------------------------------

Mark a fulfillment as open

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-2020-01>

Method	POST
Path	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Cancel a fulfillment for a specific order ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancel-2020-01>

Method	POST
Path	/admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Cancels a fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancelV2-2020-01>

Method	POST
Path	/admin/api/2020-01/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<code>null</code>

Responses

Response	200 No description available
----------	------------------------------

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#index-2020-04>

Method	GET
Path	/admin/api/2020-04/orders/{order_id}/fulfillments.json

Parameters

Parameter	About	Description
order_id	Required	order_id
created_at_max	Optional	Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields	Optional	A comma-separated list of fields to include in the response.
limit	Optional	Limit the amount of results. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_max	Optional	Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).

Responses

Response	200 No description available
----------	------------------------------

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#create-2020-04>

Method POST
Path /admin/api/2020-04/orders/{order_id}/fulfillments.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined Example: null

Responses

Response 200 No description available

Retrieves fulfillments associated with a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#indexV2-2020-04>

Method GET
Path /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order that is associated with the fulfillments.

Responses

Response 200 No description available

Retrieves a count of fulfillments associated with a specific order

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-2020-04>

Method GET
Path /admin/api/2020-04/orders/{order_id}/fulfillments/count.json

Parameters

Parameter	About	Description
order_id	Required	order_id
created_at_min	Optional	Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).

Responses

Response 200 No description available

Retrieve a specific fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-2020-04>

Method GET
Path /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fields	Optional	Comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Update information associated with a fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-2020-04>

Method PUT
Path /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response 200 No description available

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-2020-04>

Method POST
Path /admin/api/2020-04/fulfillments.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response 200 No description available

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-2020-04

Method POST
Path /admin/api/2020-04/fulfillments/{fulfillment_id}/update_tracking.json

Parameters

Parameter	About	Description
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Mark a fulfillment as complete

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#complete-2020-04>

Method	POST
Path	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Mark a fulfillment as open

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-2020-04>

Method	POST
Path	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Cancel a fulfillment for a specific order ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancel-2020-04>

Method	POST
Path	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Cancels a fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancelV2-2020-04>

Method POST
Path /admin/api/2020-04/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
fulfillment_id	Required	fulfillment_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#index-2020-07>

Method GET
Path /admin/api/2020-07/orders/{order_id}/fulfillments.json

Parameters

Parameter	About	Description
order_id	Required	order_id
created_at_max	Optional	Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields	Optional	A comma-separated list of fields to include in the response.
limit	Optional	Limit the amount of results. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_max	Optional	Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).

Responses

Response 200 No description available

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will

be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#create-2020-07>

Method POST
Path /admin/api/2020-07/orders/{order_id}/fulfillments.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Retrieves fulfillments associated with a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#indexV2-2020-07>

Method GET
Path /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order that is associated with the fulfillments.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of fulfillments associated with a specific order

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-2020-07>

Method	GET	
Path	/admin/api/2020-07/orders/{order_id}/fulfillments/count.json	
Parameters		
Parameter	About	Description
order_id	Required	order_id
created_at_min	Optional	Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
Responses		
Response	200 No description available	

Retrieve a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-2020-07

Method	GET
Path	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fields	Optional	Comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Update information associated with a fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-2020-07

Method	PUT	
Path	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}.json	
Parameters		
Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
	Example:	
	<pre>null</pre>	
Responses		
Response	200 No description available	

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-2020-07

Method	POST
Path	/admin/api/2020-07/fulfillments.json
Request Body	
Required	No
Description	No description available
Content-type	application/json

Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-2020-07

Method	POST
Path	/admin/api/2020-07/fulfillments/{fulfillment_id}/update_tracking.json

Parameters

Parameter	About	Description
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Mark a fulfillment as complete

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#complete-2020-07

Method	POST
Path	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Mark a fulfillment as open

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-2020-07

Method	POST
Path	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Parameters

Parameter	About	Description
-----------	-------	-------------

order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Cancel a fulfillment for a specific order ID

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancel-2020-07

Method	POST
Path	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Cancels a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancelV2-2020-07

Method	POST
Path	/admin/api/2020-07/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#index-2020-10>

Method GET
Path /admin/api/2020-10/orders/{order_id}/fulfillments.json

Parameters

Parameter	About	Description
order_id	Required	order_id
created_at_max	Optional	Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields	Optional	A comma-separated list of fields to include in the response.
limit	Optional	Limit the amount of results. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_max	Optional	Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).

Responses

Response 200 No description available

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#create-2020-10>

Method POST
Path /admin/api/2020-10/orders/{order_id}/fulfillments.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required No
Description No description available
Content-type application/json

Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves fulfillments associated with a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#indexV2-2020-10

Method	GET
Path	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order that is associated with the fulfillments.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of fulfillments associated with a specific order

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-2020-10

Method	GET
Path	/admin/api/2020-10/orders/{order_id}/fulfillments/count.json

Parameters

Parameter	About	Description
order_id	Required	order_id
created_at_min	Optional	Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).

Responses

Response	200 No description available
----------	------------------------------

Retrieve a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-2020-10

Method	GET
Path	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fields	Optional	Comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Update information associated with a fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-2020-10

Method	PUT
Path	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-2020-10>

Method	POST
Path	/admin/api/2020-10/fulfillments.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-2020-10

Method	POST
Path	/admin/api/2020-10/fulfillments/{fulfillment_id}/update_tracking.json

Parameters

Parameter	About	Description
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Mark a fulfillment as complete

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#complete-2020-10>

Method	POST
Path	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Mark a fulfillment as open

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-2020-10>

Method	POST
Path	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Cancel a fulfillment for a specific order ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancel-2020-10>

Method	POST
Path	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Cancels a fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancelV2-2020-10>

Method POST
Path /admin/api/2020-10/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
fulfillment_id	Required	fulfillment_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#index-2021-01>

Method GET
Path /admin/api/2021-01/orders/{order_id}/fulfillments.json

Parameters

Parameter	About	Description
order_id	Required	order_id
created_at_max	Optional	Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields	Optional	A comma-separated list of fields to include in the response.
limit	Optional	Limit the amount of results. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_max	Optional	Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Show fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).

Responses

Response 200 No description available

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If

you're creating a fulfillment for a supported carrier, then you can send the `tracking_company` and `tracking_numbers` fields, and Shopify will generate the `tracking_url` for you. If you're creating a fulfillment for an unsupported carrier (not in the `tracking_company` list), then send the `tracking_company`, `tracking_numbers`, and `tracking_urls` fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#create-2021-01

Method	POST	
Path	/admin/api/2021-01/orders/{order_id}/fulfillments.json	
Parameters		
Parameter	About	Description
order_id	Required	order_id
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
	Example:	
	null	
Responses		
Response	200 No description available	

Retrieves fulfillments associated with a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#indexV2-2021-01

Method	GET	
Path	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillments.json	
Parameters		
Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order that is associated with the fulfillments.
Responses		
Response	200 No description available	

Retrieves a count of fulfillments associated with a specific order

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-2021-01

Method	GET	
Path	/admin/api/2021-01/orders/{order_id}/fulfillments/count.json	
Parameters		
Parameter	About	Description
order_id	Required	order_id
created_at_min	Optional	Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).
Responses		
Response	200 No description available	

Retrieve a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-2021-01

Method GET
Path /admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fields	Optional	Comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Update information associated with a fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-2021-01

Method PUT
Path /admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required Description Content-type Schema for application/json	No No description available application/json Type: undefined Example: null
--	--

Responses

Response 200 No description available

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-2021-01

Method POST
Path /admin/api/2021-01/fulfillments.json

Request Body

Required Description Content-type Schema for application/json	No No description available application/json Type: undefined Example: null
--	--

Responses

Response 200 No description available

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-2021-01

Method POST
Path /admin/api/2021-01/fulfillments/{fulfillment_id}/update_tracking.json

Parameters		
Parameter	About	Description
fulfillment_id	Required	fulfillment_id
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
	Example:	
	null	
Responses		
Response	200 No description available	

Mark a fulfillment as complete

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#complete-2021-01

Method	POST	
Path	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json	
Parameters		
Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
	Example:	
	null	
Responses		
Response	200 No description available	

Mark a fulfillment as open

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-2021-01

Method	POST	
Path	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/open.json	
Parameters		
Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
	Example:	
	null	
Responses		
Response	200 No description available	

Cancel a fulfillment for a specific order ID

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancel-2021-01>

Method POST
Path /admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Cancel a fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancelV2-2021-01>

Method POST
Path /admin/api/2021-01/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves fulfillments associated with an order. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#index-unstable>

Method GET
Path /admin/api/unstable/orders/{order_id}/fulfillments.json

Parameters

Parameter	About	Description
order_id	Required	order_id
created_at_max	Optional	Show fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
created_at_min	Optional	Show fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
fields	Optional	A comma-separated list of fields to include in the response.
limit	Optional	Limit the amount of results. (default: 50, maximum: 250)
since_id	Optional	Restrict results to after the specified ID.
updated_at_max	Optional	Show fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).

Responses

Response	200 No description available
----------	------------------------------

Create a fulfillment for the specified order and line items. The fulfillment's status depends on the line items in the order: If the line items in the fulfillment use a manual or custom fulfillment service, then the status of the returned fulfillment will be set immediately. If the line items use an external fulfillment service, then they will be queued for fulfillment and the status will be set to pending until the external fulfillment service has been invoked. A fulfillment might then transition to open, which implies it is being processed by the service, before transitioning to success when the items have shipped. If you don't specify line item IDs, then all unfulfilled and partially fulfilled line items for the order will be fulfilled. However, if an order is refunded or if any of its individual line items are refunded, then the order can't be fulfilled. All line items being fulfilled must have the same fulfillment service. Note If you are using this endpoint with a Partner development store or a trial store, then you can create no more than 5 new fulfillments per minute. About tracking urls If you're creating a fulfillment for a supported carrier, then you can send the tracking_company and tracking_numbers fields, and Shopify will generate the tracking_url for you. If you're creating a fulfillment for an unsupported carrier (not in the tracking_company list), then send the tracking_company, tracking_numbers, and tracking_urls fields. Note If you send an unsupported carrier without a tracking URL, then Shopify will still try to generate a valid tracking URL by using pattern matching on the tracking number. However, Shopify does not validate the tracking URL, so you should make sure that your tracking URL is correct for the order and fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#create-unstable

Method	POST
Path	/admin/api/unstable/orders/{order_id}/fulfillments.json

Parameters

Parameter	About	Description
order_id	Required	order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Retrieves fulfillments associated with a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#indexV2-unstable

Method	GET
Path	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillments.json

Parameters

Parameter	About	Description
-----------	-------	-------------

fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order that is associated with the fulfillments.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of fulfillments associated with a specific order

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#count-unstable

Method	GET
Path	/admin/api/unstable/orders/{order_id}/fulfillments/count.json

Parameters

Parameter	About	Description
order_id	Required	order_id
created_at_min	Optional	Count fulfillments created after date (format: 2014-04-25T16:15:47-04:00).
created_at_max	Optional	Count fulfillments created before date (format: 2014-04-25T16:15:47-04:00).
updated_at_min	Optional	Count fulfillments last updated after date (format: 2014-04-25T16:15:47-04:00).
updated_at_max	Optional	Count fulfillments last updated before date (format: 2014-04-25T16:15:47-04:00).

Responses

Response	200 No description available
----------	------------------------------

Retrieve a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#show-unstable

Method	GET
Path	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fields	Optional	Comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Update information associated with a fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update-unstable

Method	PUT
Path	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Creates a fulfillment for one or many fulfillment orders. The fulfillment orders are associated with the same order and are assigned to the same location.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#createV2-unstable

Method POST
Path /admin/api/unstable/fulfillments.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Updates the tracking information for a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#update_tracking-unstable

Method POST
Path /admin/api/unstable/fulfillments/{fulfillment_id}/update_tracking.json

Parameters

Parameter	About	Description
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Mark a fulfillment as complete

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#complete-unstable

Method POST
Path /admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/complete.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Mark a fulfillment as open

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#open-unstable

Method POST
Path /admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/open.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Cancel a fulfillment for a specific order ID

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancel-unstable

Method POST
Path /admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Cancels a fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillment#cancelV2-unstable

Method POST
Path /admin/api/unstable/fulfillments/{fulfillment_id}/cancel.json

Parameters

Parameter	About	Description
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a list of fulfillment events for a specific fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-2020-01>

Method GET
Path /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fulfillment_id	Optional	The ID of the fulfillment that's associated with the fulfillment event.
order_id	Optional	The ID of the order that's associated with the fulfillment event.

Responses

Response 200 No description available

Creates a fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-2020-01>

Method POST
Path /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response 200 No description available

Retrieves a specific fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-2020-01>

Method GET
Path /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
event_id	Required	event_id
event_id	Optional	The ID of the fulfillment event.

Responses

Response 200 No description available

Deletes a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-2020-01

Method DELETE
Path /admin/api/2020-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
event_id	Required	event_id

Responses

Response 200 No description available

Retrieves a list of fulfillment events for a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-2020-04

Method GET
Path /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fulfillment_id	Optional	The ID of the fulfillment that's associated with the fulfillment event.
order_id	Optional	The ID of the order that's associated with the fulfillment event.

Responses

Response 200 No description available

Creates a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-2020-04

Method POST
Path /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a specific fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-2020-04

Method GET
Path /admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

event_id	Required	event_id
event_id	Optional	The ID of the fulfillment event.

Responses

Response	200 No description available
----------	------------------------------

Deletes a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-2020-04

Method	DELETE
Path	/admin/api/2020-04/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
event_id	Required	event_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of fulfillment events for a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-2020-07

Method	GET
Path	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fulfillment_id	Optional	The ID of the fulfillment that's associated with the fulfillment event.
order_id	Optional	The ID of the order that's associated with the fulfillment event.

Responses

Response	200 No description available
----------	------------------------------

Creates a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-2020-07

Method	POST
Path	/admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a specific fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-2020-07

Method GET
Path /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
event_id	Required	event_id
event_id	Optional	The ID of the fulfillment event.

Responses

Response 200 No description available

Deletes a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-2020-07

Method DELETE
Path /admin/api/2020-07/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
event_id	Required	event_id

Responses

Response 200 No description available

Retrieves a list of fulfillment events for a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-2020-10

Method GET
Path /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fulfillment_id	Optional	The ID of the fulfillment that's associated with the fulfillment event.
order_id	Optional	The ID of the order that's associated with the fulfillment event.

Responses

Response 200 No description available

Creates a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-2020-10

Method POST
Path /admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
----------	------------------------------

Retrieves a specific fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-2020-10>

Method	GET
Path	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
event_id	Required	event_id
event_id	Optional	The ID of the fulfillment event.

Responses

Response	200 No description available
----------	------------------------------

Deletes a fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-2020-10>

Method	DELETE
Path	/admin/api/2020-10/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
event_id	Required	event_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of fulfillment events for a specific fulfillment

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-2021-01>

Method	GET
Path	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fulfillment_id	Optional	The ID of the fulfillment that's associated with the fulfillment event.
order_id	Optional	The ID of the order that's associated with the fulfillment event.

Responses

Response	200 No description available
----------	------------------------------

Creates a fulfillment event

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-2021-01>

Method	POST
Path	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters

Parameter	About	Description
order_id	Required	order_id

fulfillment_id	Required	fulfillment_id
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
	Example:	
		<code>null</code>

Responses	
Response	200 No description available

Retrieves a specific fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-2021-01	
Method	GET
Path	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters		
Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
event_id	Required	event_id
event_id	Optional	The ID of the fulfillment event.

Responses	
Response	200 No description available

Deletes a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-2021-01	
Method	DELETE
Path	/admin/api/2021-01/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters		
Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
event_id	Required	event_id

Responses	
Response	200 No description available

Retrieves a list of fulfillment events for a specific fulfillment

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#index-unstable	
Method	GET
Path	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters		
Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
fulfillment_id	Optional	The ID of the fulfillment that's associated with the fulfillment event.
order_id	Optional	The ID of the order that's associated with the fulfillment event.

Responses	
Response	200 No description available

Creates a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#create-unstable

Method	POST
Path	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a specific fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#show-unstable

Method	GET
Path	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
event_id	Required	event_id
event_id	Optional	The ID of the fulfillment event.

Responses

Response	200 No description available
----------	------------------------------

Deletes a fulfillment event

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentevent#destroy-unstable

Method	DELETE
Path	/admin/api/unstable/orders/{order_id}/fulfillments/{fulfillment_id}/events/{event_id}.json

Parameters

Parameter	About	Description
order_id	Required	order_id
fulfillment_id	Required	fulfillment_id
event_id	Required	event_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of fulfillment orders for a specific order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#index-2020-01

Method	GET
Path	/admin/api/2020-01/orders/{order_id}/fulfillment_orders.json

Parameters

Parameter	About	Description
-----------	-------	-------------

order_id	Required	order_id
order_id	Optional	The ID of the order that is associated with the fulfillment orders.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a specific fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#show-2020-01

Method	GET
Path	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Responses

Response	200 No description available
----------	------------------------------

Marks a fulfillment order as cancelled.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#cancel-2020-01

Method	POST
Path	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/cancel.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#close-2020-01

Method	POST
Path	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/close.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for marking the fulfillment order as incomplete.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response 200 No description available

Moves a fulfillment order from one merchant managed location to another merchant managed location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#move-2020-01>

Method POST
Path /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/move.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
new_location_id	Optional	The id of the location to which the fulfillment order will be moved.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves a list of fulfillment orders for a specific order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#index-2020-04>

Method GET
Path /admin/api/2020-04/orders/{order_id}/fulfillment_orders.json

Parameters

Parameter	About	Description
order_id	Required	order_id
order_id	Optional	The ID of the order that is associated with the fulfillment orders.

Responses

Response 200 No description available

Retrieves a specific fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#show-2020-04>

Method GET
Path /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Responses

Response 200 No description available

Marks a fulfillment order as cancelled.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#cancel-2020-04>

Method POST
Path /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/cancel.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#close-2020-04>

Method	POST
Path	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/close.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for marking the fulfillment order as incomplete.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Moves a fulfillment order from one merchant managed location to another merchant managed location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#move-2020-04>

Method	POST
Path	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/move.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
new_location_id	Optional	The id of the location to which the fulfillment order will be moved.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of fulfillment orders for a specific order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#index-2020-07

Method	GET
Path	/admin/api/2020-07/orders/{order_id}/fulfillment_orders.json

Parameters

Parameter	About	Description
order_id	Required	order_id
order_id	Optional	The ID of the order that is associated with the fulfillment orders.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a specific fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#show-2020-07

Method	GET
Path	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Responses

Response	200 No description available
----------	------------------------------

Marks a fulfillment order as cancelled.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#cancel-2020-07

Method	POST
Path	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/cancel.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#close-2020-07

Method	POST
Path	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/close.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for marking the fulfillment order as incomplete.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Moves a fulfillment order from one merchant managed location to another merchant managed location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#move-2020-07>

Method	POST
Path	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/move.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
new_location_id	Optional	The id of the location to which the fulfillment order will be moved.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of fulfillment orders for a specific order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#index-2020-10>

Method	GET
Path	/admin/api/2020-10/orders/{order_id}/fulfillment_orders.json

Parameters

Parameter	About	Description
order_id	Required	order_id
order_id	Optional	The ID of the order that is associated with the fulfillment orders.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a specific fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#show-2020-10>

Method	GET
Path	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Responses

Response	200 No description available
----------	------------------------------

Marks a fulfillment order as cancelled.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#cancel-2020-10>

Method	POST
Path	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/cancel.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#close-2020-10>

Method	POST
Path	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/close.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for marking the fulfillment order as incomplete.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Moves a fulfillment order from one merchant managed location to another merchant managed location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#move-2020-10>

Method	POST
Path	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/move.json

Parameters		
Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
new_location_id	Optional	The id of the location to which the fulfillment order will be moved.
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
Example:		<pre>null</pre>

Responses	
Response	200 No description available

Retrieves a list of fulfillment orders for a specific order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#index-2021-01	
Method	GET
Path	/admin/api/2021-01/orders/{order_id}/fulfillment_orders.json

Parameters		
Parameter	About	Description
order_id	Required	order_id
order_id	Optional	The ID of the order that is associated with the fulfillment orders.

Responses	
Response	200 No description available

Retrieves a specific fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#show-2021-01	
Method	GET
Path	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}.json

Parameters		
Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Responses	
Response	200 No description available

Marks a fulfillment order as cancelled.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#cancel-2021-01	
Method	POST
Path	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/cancel.json

Parameters		
Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Request Body	
Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#close-2021-01>

Method	POST
Path	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/close.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for marking the fulfillment order as incomplete.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Moves a fulfillment order from one merchant managed location to another merchant managed location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#move-2021-01>

Method	POST
Path	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/move.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
new_location_id	Optional	The id of the location to which the fulfillment order will be moved.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#open-2021-01>

Method	POST
Path	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/open.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#reschedule-2021-01>

Method	POST
Path	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/reschedule.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of fulfillment orders for a specific order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#index-unstable>

Method	GET
Path	/admin/api/unstable/orders/{order_id}/fulfillment_orders.json

Parameters

Parameter	About	Description
order_id	Required	order_id
order_id	Optional	The ID of the order that is associated with the fulfillment orders.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a specific fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#show-unstable>

Method	GET
Path	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Responses

Response	200 No description available
----------	------------------------------

Marks a fulfillment order as cancelled.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#cancel-unstable>

Method	POST
Path	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/cancel.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Releases the fulfillment order holds for a specific order. Fulfillment orders are created with an ON_HOLD status if the channel that created the order has a fulfillment hold policy.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#release_hold-unstable

Method	POST
Path	/admin/api/unstable/fulfillment_orders/release_hold.json

Parameters

Parameter	About	Description
order_id	Optional	The ID of the order that is associated to the fulfillment orders.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Marks an in progress fulfillment order as incomplete, indicating the fulfillment service is unable to ship any remaining items and intends to close the fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#close-unstable>

Method	POST
Path	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/close.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for marking the fulfillment order as incomplete.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Moves a fulfillment order from one merchant managed location to another merchant managed location.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#move-unstable>

Method	POST
Path	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/move.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
new_location_id	Optional	The id of the location to which the fulfillment order will be moved.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Marks a scheduled fulfillment order as ready for fulfillment. This endpoint allows merchants to work on a scheduled fulfillment order before its expected fulfill_at datetime.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#open-unstable>

Method	POST
Path	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/open.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

Updates the fulfill_at time of a scheduled fulfillment order. This endpoint is used to manage the time a scheduled fulfillment order will be marked as ready for fulfillment.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentorder#reschedule-unstable

Method	POST
Path	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/reschedule.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Sends a fulfillment request to the fulfillment service of a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-2020-01

Method	POST
Path	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional message for the fulfillment request.
fulfillment_order_line_items	Optional	The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response	200 No description available
----------	------------------------------

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-2020-01

Method	POST
Path	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id

message	Optional	An optional reason for accepting the fulfillment request.
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
Example:		<pre>null</pre>

Responses		
Response	200	No description available

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-2020-01>

Method	POST
Path	/admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Parameters		
Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the fulfillment request.

Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
Example:		<pre>null</pre>

Responses		
Response	200	No description available

Sends a fulfillment request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-2020-04>

Method	POST
Path	/admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Parameters		
Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional message for the fulfillment request.
fulfillment_order_line_items	Optional	The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
Example:		<pre>null</pre>

Responses		
Response	200	No description available

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-2020-04

Method POST
Path /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for accepting the fulfillment request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-2020-04

Method POST
Path /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the fulfillment request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Sends a fulfillment request to the fulfillment service of a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-2020-07

Method POST
Path /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional message for the fulfillment request.
fulfillment_order_line_items	Optional	The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Request Body

Required	No
Description	No description available
Content-type	application/json

Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-2020-07>

Method	POST
Path	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for accepting the fulfillment request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-2020-07>

Method	POST
Path	/admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the fulfillment request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Sends a fulfillment request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-2020-10>

Method	POST
Path	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional message for the fulfillment request.
fulfillment_order_line_items	Optional	The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
-----------------	------------------------------

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-2020-10>

Method	POST
Path	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for accepting the fulfillment request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
-----------------	------------------------------

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-2020-10>

Method	POST
Path	/admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the fulfillment request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
-----------------	------------------------------

Sends a fulfillment request to the fulfillment service of a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-2021-01>

Method POST
Path /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional message for the fulfillment request.
fulfillment_order_line_items	Optional	The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-2021-01>

Method POST
Path /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for accepting the fulfillment request.

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-2021-01>

Method POST
Path /admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the fulfillment request.

Request Body

Required No
Description No description available
Content-type application/json

Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Sends a fulfillment request to the fulfillment service of a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#create-unstable

Method	POST
Path	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional message for the fulfillment request.
fulfillment_order_line_items	Optional	The fulfillment order line items to be requested for fulfillment. If left blank, all line items of the fulfillment order are requested for fulfillment.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Accepts a fulfillment request sent to a fulfillment service for a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#accept-unstable

Method	POST
Path	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/accept.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for accepting the fulfillment request.

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	null

Responses

Response	200 No description available
----------	------------------------------

Rejects a fulfillment request sent to a fulfillment service for a fulfillment order.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentrequest#reject-unstable

Method	POST
Path	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/fulfillment_request/reject.json

Parameters		
Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
message	Optional	An optional reason for rejecting the fulfillment request.
Request Body		
Required	No	
Description	No description available	
Content-type	application/json	
Schema for application/json	Type: undefined	
	Example:	
	null	

Responses	
Response	200 No description available

Get tracking numbers for orders

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#fetch-tracking-numbers

Method	GET
Path	/fetch_tracking_numbers

Parameters		
Parameter	About	Description
order_names	Optional	The fulfillment names we require tracking numbers for (i.e. #1001.1)
shop	Optional	The shop's myshopify url

Responses	
Response	200 No description available

Get inventory levels

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#fetch-stock

Method	GET
Path	/fetch_stock

Parameters		
Parameter	About	Description
max_retries	Optional	The maximum amount of times Shopify will send the request for inventory levels.
shop	Optional	The shop's myshopify url.
sku	Optional	The SKU for the Product Variant we need stock levels for.
timestamp	Optional	The Unix timestamp from when the inventory request was made.

Responses	
Response	200 No description available

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-2020-01

Method	GET
Path	/admin/api/2020-01/fulfillment_services.json

Parameters		
Parameter	About	Description
scope	Optional	current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses	
Response	200 No description available

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-2020-01

Method POST
Path /admin/api/2020-01/fulfillment_services.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-2020-01

Method GET
Path /admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response 200 No description available

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-2020-01

Method PUT
Path /admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-2020-01

Method DELETE
Path /admin/api/2020-01/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response 200 No description available

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-2020-04>

Method GET
Path /admin/api/2020-04/fulfillment_services.json

Parameters

Parameter	About	Description
scope	Optional	current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses

Response 200 No description available

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-2020-04>

Method POST
Path /admin/api/2020-04/fulfillment_services.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-2020-04>

Method GET
Path /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response 200 No description available

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-2020-04>

Method PUT
Path /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined Example: null

Responses

Response 200 No description available

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-2020-04>

Method DELETE
Path /admin/api/2020-04/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response 200 No description available

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-2020-07>

Method GET
Path /admin/api/2020-07/fulfillment_services.json

Parameters

Parameter	About	Description
scope	Optional	current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses

Response 200 No description available

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy `curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE"`
`https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services` Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and `https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services` is replaced by the authorized shop's URL.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-2020-07>

Method POST
Path /admin/api/2020-07/fulfillment_services.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<code>null</code>

Responses

Response	200 No description available
-----------------	------------------------------

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-2020-07

Method	GET
Path	/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response	200 No description available
-----------------	------------------------------

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-2020-07

Method	PUT
Path	/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<code>null</code>

Responses

Response	200 No description available
-----------------	------------------------------

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-2020-07

Method	DELETE
Path	/admin/api/2020-07/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response	200 No description available
-----------------	------------------------------

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-2020-10

Method	GET
Path	/admin/api/2020-10/fulfillment_services.json

Parameters

Parameter	About	Description
scope	Optional	current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses

Response	200 No description available
----------	------------------------------

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE" https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services is replaced by the authorized shop's URL.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-2020-10>

Method	POST
Path	/admin/api/2020-10/fulfillment_services.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-2020-10>

Method	GET
Path	/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response	200 No description available
----------	------------------------------

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-2020-10>

Method	PUT
Path	/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-2020-10>

Method	DELETE
Path	/admin/api/2020-10/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response	200 No description available
----------	------------------------------

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-2021-01>

Method	GET
Path	/admin/api/2021-01/fulfillment_services.json

Parameters

Parameter	About	Description
scope	Optional	current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses

Response	200 No description available
----------	------------------------------

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy `curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE"` `https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services` Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify and `https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services` is replaced by the authorized shop's URL.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-2021-01>

Method	POST
Path	/admin/api/2021-01/fulfillment_services.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined

Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-2021-01>

Method	GET
Path	/admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response	200 No description available
----------	------------------------------

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-2021-01>

Method	PUT
Path	/admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response	200 No description available
----------	------------------------------

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-2021-01>

Method	DELETE
Path	/admin/api/2021-01/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response	200 No description available
----------	------------------------------

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#index-unstable>

Method	GET
Path	/admin/api/unstable/fulfillment_services.json

Parameters

Parameter	About	Description
scope	Optional	current_client: Returns fulfillment providers that have been created by the app sending the request (default) all: Returns all the fulfillment providers

Responses

Response	200 No description available
----------	------------------------------

To create a fulfillment service, you can also use a cURL request that uses that fulfillment_service.json payload: Copy `curl -X POST -d @fulfillment_service.json -H"Accept:application/json" -H"Content-Type:application/json" -H"X-Shopify-Access-Token:THE_TOKEN_GOES_HERE"`
`https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services` Where THE_TOKEN_GOES_HERE is replaced by the OAuth token given to you by Shopify

and `https://AUTHORIZED_SHOP.myshopify.com/admin/fulfillment_services` is replaced by the authorized shop's URL.

`https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#create-unstable`

Method POST
Path /admin/api/unstable/fulfillment_services.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

`https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#show-unstable`

Method GET
Path /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response 200 No description available

`https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#update-unstable`

Method PUT
Path /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

`https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/fulfillmentservice#destroy-unstable`

Method DELETE
Path /admin/api/unstable/fulfillment_services/{fulfillment_service_id}.json

Parameters

Parameter	About	Description
fulfillment_service_id	Required	fulfillment_service_id

Responses

Response 200 No description available

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-2020-01

Method GET
Path /admin/api/2020-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order.

Responses

Response 200 No description available

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-2020-04

Method GET
Path /admin/api/2020-04/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order.

Responses

Response 200 No description available

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-2020-07

Method GET
Path /admin/api/2020-07/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order.

Responses

Response 200 No description available

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-2020-10

Method GET
Path /admin/api/2020-10/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-2021-01>

Method	GET
Path	/admin/api/2021-01/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of locations that a fulfillment order can potentially move to. The resulting list is sorted alphabetically in ascending order by location name.

<https://shopify.dev/docs/admin-api/rest/reference/shipping-and-fulfillment/locationsformove#index-unstable>

Method	GET
Path	/admin/api/unstable/fulfillment_orders/{fulfillment_order_id}/locations_for_move.json

Parameters

Parameter	About	Description
fulfillment_order_id	Required	fulfillment_order_id
fulfillment_order_id	Optional	The ID of the fulfillment order.

Responses

Response	200 No description available
----------	------------------------------

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-2020-01

Method	GET
Path	/admin/api/2020-01/shopify_payments/balance.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-2020-04

Method	GET
Path	/admin/api/2020-04/shopify_payments/balance.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-2020-07

Method	GET
Path	/admin/api/2020-07/shopify_payments/balance.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-2020-10

Method GET
Path /admin/api/2020-10/shopify_payments/balance.json

Responses

Response 200 No description available

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-2021-01

Method GET
Path /admin/api/2021-01/shopify_payments/balance.json

Responses

Response 200 No description available

Retrieves the account's current balance.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/balance#show-unstable

Method GET
Path /admin/api/unstable/shopify_payments/balance.json

Responses

Response 200 No description available

Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/dispute#index-2020-01

Method GET
Path /admin/api/2020-01/shopify_payments/disputes.json

Parameters

Parameter	About	Description
since_id	Optional	Return only disputes after the specified ID.
last_id	Optional	Return only disputes before the specified ID.
status	Optional	Return only disputes with the specified status.
initiated_at	Optional	Return only disputes with the specified initiated_at date (ISO 8601 format).

Responses

Response 200 No description available

Retrieves a single dispute by ID.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/dispute#show-2020-01

Method GET
Path /admin/api/2020-01/shopify_payments/disputes/{dispute_id}.json

Parameters

Parameter	About	Description
dispute_id	Required	dispute_id

Responses

Response 200 No description available

Retrieve all disputes ordered by initiated_at date and time (ISO 8601 format), with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/dispute#index-2020-04

Method GET
Path /admin/api/2020-04/shopify_payments/disputes.json

Parameters

Parameter	About	Description
since_id	Optional	Return only disputes after the specified ID.
last_id	Optional	Return only disputes before the specified ID.
status	Optional	Return only disputes with the specified status.
initiated_at	Optional	Return only disputes with the specified initiated_at date (ISO 8601 format).

Responses

Response 200 No description available

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#index-2020-01

Method GET
Path /admin/api/2020-01/shopify_payments/payouts.json

Parameters

Parameter	About	Description
since_id	Optional	Filter the response to payouts made after the specified ID.
last_id	Optional	Filter the response to payouts made before the specified ID.
date_min	Optional	Filter the response to payouts made inclusively after the specified date.
date_max	Optional	Filter the response to payouts made inclusively before the specified date.
date	Optional	Filter the response to payouts made on the specified date.
status	Optional	Filter the response to payouts made with the specified status.

Responses

Response 200 No description available

Retrieves a single payout by id.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#show-2020-01

Method GET
Path /admin/api/2020-01/shopify_payments/payouts/{payout_id}.json

Parameters

Parameter	About	Description
payout_id	Required	payout_id

Responses

Response 200 No description available

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will

return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#index-2020-04

Method GET
Path /admin/api/2020-04/shopify_payments/payouts.json

Parameters

Parameter	About	Description
since_id	Optional	Filter the response to payouts made after the specified ID.
last_id	Optional	Filter the response to payouts made before the specified ID.
date_min	Optional	Filter the response to payouts made inclusively after the specified date.
date_max	Optional	Filter the response to payouts made inclusively before the specified date.
date	Optional	Filter the response to payouts made on the specified date.
status	Optional	Filter the response to payouts made with the specified status.

Responses

Response 200 No description available

Retrieves a single payout by id.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#show-2020-04

Method GET
Path /admin/api/2020-04/shopify_payments/payouts/{payout_id}.json

Parameters

Parameter	About	Description
payout_id	Required	payout_id

Responses

Response 200 No description available

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see [Making requests to paginated REST Admin API endpoints](#).

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#index-2020-07

Method GET
Path /admin/api/2020-07/shopify_payments/payouts.json

Parameters

Parameter	About	Description
since_id	Optional	Filter the response to payouts made after the specified ID.
last_id	Optional	Filter the response to payouts made before the specified ID.
date_min	Optional	Filter the response to payouts made inclusively after the specified date.
date_max	Optional	Filter the response to payouts made inclusively before the specified date.
date	Optional	Filter the response to payouts made on the specified date.
status	Optional	Filter the response to payouts made with the specified status.

Responses

Response 200 No description available

Retrieves a single payout by id.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#show-2020-07

Method GET
Path /admin/api/2020-07/shopify_payments/payouts/{payout_id}.json

Parameters

Parameter	About	Description
payout_id	Required	payout_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#index-2020-10

Method	GET
Path	/admin/api/2020-10/shopify_payments/payouts.json

Parameters

Parameter	About	Description
since_id	Optional	Filter the response to payouts made after the specified ID.
last_id	Optional	Filter the response to payouts made before the specified ID.
date_min	Optional	Filter the response to payouts made inclusively after the specified date.
date_max	Optional	Filter the response to payouts made inclusively before the specified date.
date	Optional	Filter the response to payouts made on the specified date.
status	Optional	Filter the response to payouts made with the specified status.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single payout by id.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#show-2020-10

Method	GET
Path	/admin/api/2020-10/shopify_payments/payouts/{payout_id}.json

Parameters

Parameter	About	Description
payout_id	Required	payout_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#index-2021-01

Method	GET
Path	/admin/api/2021-01/shopify_payments/payouts.json

Parameters

Parameter	About	Description
since_id	Optional	Filter the response to payouts made after the specified ID.
last_id	Optional	Filter the response to payouts made before the specified ID.
date_min	Optional	Filter the response to payouts made inclusively after the specified date.
date_max	Optional	Filter the response to payouts made inclusively before the specified date.
date	Optional	Filter the response to payouts made on the specified date.
status	Optional	Filter the response to payouts made with the specified status.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single payout by id.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#show-2021-01

Method	GET
Path	/admin/api/2021-01/shopify_payments/payouts/{payout_id}.json

Parameters

Parameter	About	Description
payout_id	Required	payout_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of all payouts ordered by payout date, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#index-unstable

Method	GET
Path	/admin/api/unstable/shopify_payments/payouts.json

Parameters

Parameter	About	Description
since_id	Optional	Filter the response to payouts made after the specified ID.
last_id	Optional	Filter the response to payouts made before the specified ID.
date_min	Optional	Filter the response to payouts made inclusively after the specified date.
date_max	Optional	Filter the response to payouts made inclusively before the specified date.
date	Optional	Filter the response to payouts made on the specified date.
status	Optional	Filter the response to payouts made with the specified status.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single payout by id.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/payout#show-unstable

Method	GET
Path	/admin/api/unstable/shopify_payments/payouts/{payout_id}.json

Parameters

Parameter	About	Description
payout_id	Required	payout_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of all balance transactions ordered by processing time, with the most recent being first. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. Sending the page parameter will return an error. To learn more, see Making requests to paginated REST Admin API endpoints.

https://shopify.dev/docs/admin-api/rest/reference/shopify_payments/transaction#index-2020-01

Method GET
Path /admin/api/2020-01/shopify_payments/balance/transactions.json

Parameters

Parameter	About	Description
since_id	Optional	Filter response to transactions exclusively after the specified ID.
last_id	Optional	Filter response to transactions exclusively before the specified ID.
test	Optional	Filter response to transactions placed in test mode.
payout_id	Optional	Filter response to transactions paid out in the specified payout.
payout_status	Optional	Filter response to transactions with the specified payout status.

Responses

Response 200 No description available

Retrieves a list of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-2020-01>

Method GET
Path /admin/api/2020-01/countries.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-2020-01>

Method POST
Path /admin/api/2020-01/countries.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-2020-01>

Method GET
Path /admin/api/2020-01/countries/count.json

Responses

Response 200 No description available

Retrieves a specific county.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-2020-01>

Method GET
Path /admin/api/2020-01/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-2020-01>

Method	PUT
Path	/admin/api/2020-01/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Deletes a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-2020-01>

Method	DELETE
Path	/admin/api/2020-01/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-2020-04>

Method	GET
Path	/admin/api/2020-04/countries.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-2020-04>

Method POST
Path /admin/api/2020-04/countries.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-2020-04>

Method GET
Path /admin/api/2020-04/countries/count.json

Responses

Response 200 No description available

Retrieves a specific county.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-2020-04>

Method GET
Path /admin/api/2020-04/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-2020-04>

Method PUT
Path /admin/api/2020-04/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Deletes a country.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-2020-04

Method DELETE
Path /admin/api/2020-04/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of countries.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-2020-07

Method GET
Path /admin/api/2020-07/countries.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-2020-07

Method POST
Path /admin/api/2020-07/countries.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of countries.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-2020-07

Method GET
Path /admin/api/2020-07/countries/count.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a specific county.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-2020-07

Method GET
Path /admin/api/2020-07/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-2020-07>

Method PUT
Path /admin/api/2020-07/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined
 Example:

```
null
```

Responses

Response	200 No description available
----------	------------------------------

Deletes a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-2020-07>

Method DELETE
Path /admin/api/2020-07/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-2020-10>

Method GET
Path /admin/api/2020-10/countries.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-2020-10>

Method POST
Path /admin/api/2020-10/countries.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-2020-10>

Method GET
Path /admin/api/2020-10/countries/count.json

Responses

Response 200 No description available

Retrieves a specific county.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-2020-10>

Method GET
Path /admin/api/2020-10/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-2020-10>

Method PUT
Path /admin/api/2020-10/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Deletes a country.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-2020-10

Method DELETE
Path /admin/api/2020-10/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response 200 No description available

Retrieves a list of countries.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-2021-01

Method GET
Path /admin/api/2021-01/countries.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-2021-01

Method POST
Path /admin/api/2021-01/countries.json

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Retrieves a count of countries.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-2021-01

Method GET
Path /admin/api/2021-01/countries/count.json

Responses

Response 200 No description available

Retrieves a specific county.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-2021-01

Method GET
Path /admin/api/2021-01/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-2021-01>

Method PUT
Path /admin/api/2021-01/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Deletes a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-2021-01>

Method DELETE
Path /admin/api/2021-01/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#index-unstable>

Method GET
Path /admin/api/unstable/countries.json

Parameters

Parameter	About	Description
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Caution As of version 2020-10, the tax field is deprecated. Creates a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#create-unstable>

Method POST
Path /admin/api/unstable/countries.json

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Retrieves a count of countries.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#count-unstable>

Method GET
Path /admin/api/unstable/countries/count.json

Responses

Response 200 No description available

Retrieves a specific county.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#show-unstable>

Method GET
Path /admin/api/unstable/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Caution As of version 2020-10, the tax field is deprecated. Updates an existing country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#update-unstable>

Method PUT
Path /admin/api/unstable/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Request Body

Required No
Description No description available
Content-type application/json
Schema for application/json Type: undefined

Example:

```
null
```

Responses

Response 200 No description available

Deletes a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/country#destroy-unstable>

Method DELETE
Path /admin/api/unstable/countries/{country_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of currencies enabled on a shop

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-2020-01>

Method GET
Path /admin/api/2020-01/currencies.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of currencies enabled on a shop

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-2020-04>

Method GET
Path /admin/api/2020-04/currencies.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of currencies enabled on a shop

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-2020-07>

Method GET
Path /admin/api/2020-07/currencies.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of currencies enabled on a shop

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-2020-10>

Method GET
Path /admin/api/2020-10/currencies.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of currencies enabled on a shop

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-2021-01>

Method GET
Path /admin/api/2021-01/currencies.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of currencies enabled on a shop

https://shopify.dev/docs/admin-api/rest/reference/store-properties/currency#index-unstable

Method GET
Path /admin/api/unstable/currencies.json

Responses

Response 200 No description available

Retrieves a list of the shop's policies

https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-2020-01

Method GET
Path /admin/api/2020-01/policies.json

Responses

Response 200 No description available

Retrieves a list of the shop's policies

https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-2020-04

Method GET
Path /admin/api/2020-04/policies.json

Responses

Response 200 No description available

Retrieves a list of the shop's policies

https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-2020-07

Method GET
Path /admin/api/2020-07/policies.json

Responses

Response 200 No description available

Retrieves a list of the shop's policies

https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-2020-10

Method GET
Path /admin/api/2020-10/policies.json

Responses

Response 200 No description available

Retrieves a list of the shop's policies

https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-2021-01

Method GET
Path /admin/api/2021-01/policies.json

Responses

Response 200 No description available

Retrieves a list of the shop's policies

https://shopify.dev/docs/admin-api/rest/reference/store-properties/policy#index-unstable

Method GET
Path /admin/api/unstable/policies.json

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of provinces

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-2020-01>

Method	GET
Path	/admin/api/2020-01/countries/{country_id}/provinces.json

Parameters

Parameter	About	Description
country_id	Required	country_id
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of fields names.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of provinces for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-2020-01>

Method	GET
Path	/admin/api/2020-01/countries/{country_id}/provinces/count.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single province for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-2020-01>

Method	GET
Path	/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-2020-01>

Method	PUT
Path	/admin/api/2020-01/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id

Request Body

Required	No
----------	----

Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a list of provinces

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-2020-04	
Method	GET
Path	/admin/api/2020-04/countries/{country_id}/provinces.json

Parameters

Parameter	About	Description
country_id	Required	country_id
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of fields names.

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a count of provinces for a country

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-2020-04	
Method	GET
Path	/admin/api/2020-04/countries/{country_id}/provinces/count.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response	200 No description available
-----------------	------------------------------

Retrieves a single province for a country

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-2020-04	
Method	GET
Path	/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
-----------------	------------------------------

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-2020-04	
Method	PUT
Path	/admin/api/2020-04/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	<pre>null</pre>

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of provinces

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-2020-07>

Method	GET
Path	/admin/api/2020-07/countries/{country_id}/provinces.json

Parameters

Parameter	About	Description
country_id	Required	country_id
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of fields names.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a count of provinces for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-2020-07>

Method	GET
Path	/admin/api/2020-07/countries/{country_id}/provinces/count.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response	200 No description available
----------	------------------------------

Retrieves a single province for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-2020-07>

Method	GET
Path	/admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response	200 No description available
----------	------------------------------

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-2020-07

Method PUT
Path /admin/api/2020-07/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response 200 No description available

Retrieves a list of provinces

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-2020-10

Method GET
Path /admin/api/2020-10/countries/{country_id}/provinces.json

Parameters

Parameter	About	Description
country_id	Required	country_id
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of fields names.

Responses

Response 200 No description available

Retrieves a count of provinces for a country

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-2020-10

Method GET
Path /admin/api/2020-10/countries/{country_id}/provinces/count.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response 200 No description available

Retrieves a single province for a country

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-2020-10

Method GET
Path /admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id

fields

Optional

Show only certain fields, specified by a comma-separated list of field names.

Responses

Response

200 No description available

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-2020-10

Method

PUT

Path

/admin/api/2020-10/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
	Example:
	null

Responses

Response

200 No description available

Retrieves a list of provinces

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-2021-01

Method

GET

Path

/admin/api/2021-01/countries/{country_id}/provinces.json

Parameters

Parameter	About	Description
country_id	Required	country_id
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of fields names.

Responses

Response

200 No description available

Retrieves a count of provinces for a country

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-2021-01

Method

GET

Path

/admin/api/2021-01/countries/{country_id}/provinces/count.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response

200 No description available

Retrieves a single province for a country

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-2021-01

Method GET
Path /admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-2021-01>

Method PUT
Path /admin/api/2021-01/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
<pre>null</pre>	

Responses

Response 200 No description available

Retrieves a list of provinces

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#index-unstable>

Method GET
Path /admin/api/unstable/countries/{country_id}/provinces.json

Parameters

Parameter	About	Description
country_id	Required	country_id
since_id	Optional	Restrict results to after the specified ID.
fields	Optional	Show only certain fields, specified by a comma-separated list of fields names.

Responses

Response 200 No description available

Retrieves a count of provinces for a country

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#count-unstable>

Method GET
Path /admin/api/unstable/countries/{country_id}/provinces/count.json

Parameters

Parameter	About	Description
country_id	Required	country_id

Responses

Response 200 No description available

Retrieves a single province for a country

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#show-unstable

Method GET
Path /admin/api/unstable/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id
fields	Optional	Show only certain fields, specified by a comma-separated list of field names.

Responses

Response 200 No description available

Caution As of version 2020-10, the tax field is deprecated. Updates an existing province for a country.

https://shopify.dev/docs/admin-api/rest/reference/store-properties/province#update-unstable

Method PUT
Path /admin/api/unstable/countries/{country_id}/provinces/{province_id}.json

Parameters

Parameter	About	Description
country_id	Required	country_id
province_id	Required	province_id

Request Body

Required	No
Description	No description available
Content-type	application/json
Schema for application/json	Type: undefined
Example:	
null	

Responses

Response 200 No description available

Get a list of all shipping zones

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-2020-01

Method GET
Path /admin/api/2020-01/shipping_zones.json

Parameters

Parameter	About	Description
fields	Optional	comma-separated list of fields to include in the response

Responses

Response 200 No description available

Get a list of all shipping zones

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-2020-04

Method GET
Path /admin/api/2020-04/shipping_zones.json

Parameters

Parameter	About	Description
fields	Optional	comma-separated list of fields to include in the response

Responses

Response	200 No description available
----------	------------------------------

Get a list of all shipping zones

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-2020-07

Method	GET
Path	/admin/api/2020-07/shipping_zones.json

Parameters

Parameter	About	Description
fields	Optional	comma-separated list of fields to include in the response

Responses

Response	200 No description available
----------	------------------------------

Get a list of all shipping zones

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-2020-10

Method	GET
Path	/admin/api/2020-10/shipping_zones.json

Parameters

Parameter	About	Description
fields	Optional	comma-separated list of fields to include in the response

Responses

Response	200 No description available
----------	------------------------------

Get a list of all shipping zones

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-2021-01

Method	GET
Path	/admin/api/2021-01/shipping_zones.json

Parameters

Parameter	About	Description
fields	Optional	comma-separated list of fields to include in the response

Responses

Response	200 No description available
----------	------------------------------

Get a list of all shipping zones

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shippingzone#index-unstable

Method	GET
Path	/admin/api/unstable/shipping_zones.json

Parameters

Parameter	About	Description
fields	Optional	comma-separated list of fields to include in the response

Responses

Response	200 No description available
----------	------------------------------

Retrieves the shop's configuration

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-2020-01

Method GET
Path /admin/api/2020-01/shop.json

Parameters

Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Retrieves the shop's configuration

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-2020-04

Method GET
Path /admin/api/2020-04/shop.json

Parameters

Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Retrieves the shop's configuration

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-2020-07

Method GET
Path /admin/api/2020-07/shop.json

Parameters

Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Retrieves the shop's configuration

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-2020-10

Method GET
Path /admin/api/2020-10/shop.json

Parameters

Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response 200 No description available

Retrieves the shop's configuration

https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-2021-01

Method GET
Path /admin/api/2021-01/shop.json

Parameters

Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Retrieves the shop's configuration

<https://shopify.dev/docs/admin-api/rest/reference/store-properties/shop#show-unstable>

Method	GET
Path	/admin/api/unstable/shop.json

Parameters

Parameter	About	Description
fields	Optional	A comma-separated list of fields to include in the response.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/tendertransaction#index-2020-01>

Method	GET
Path	/admin/api/2020-01/tender_transactions.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Retrieve only transactions after the specified ID.
processed_at_min	Optional	Show tender transactions processed_at or after the specified date.
processed_at_max	Optional	Show tender transactions processed_at or before the specified date.
processed_at	Optional	Show tender transactions processed at the specified date.
order	Optional	Show tender transactions ordered by processed_at in ascending or descending order.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/tendertransaction#index-2020-04>

Method	GET
Path	/admin/api/2020-04/tender_transactions.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Retrieve only transactions after the specified ID.
processed_at_min	Optional	Show tender transactions processed_at or after the specified date.
processed_at_max	Optional	Show tender transactions processed_at or before the specified date.
processed_at	Optional	Show tender transactions processed at the specified date.
order	Optional	Show tender transactions ordered by processed_at in ascending or descending order.

Responses

Response	200 No description available
----------	------------------------------

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/tendertransaction#index-2020-07>

Method GET
Path /admin/api/2020-07/tender_transactions.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Retrieve only transactions after the specified ID.
processed_at_min	Optional	Show tender transactions processed_at or after the specified date.
processed_at_max	Optional	Show tender transactions processed_at or before the specified date.
processed_at	Optional	Show tender transactions processed at the specified date.
order	Optional	Show tender transactions ordered by processed_at in ascending or descending order.

Responses

Response 200 No description available

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/tendertransaction#index-2020-10>

Method GET
Path /admin/api/2020-10/tender_transactions.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Retrieve only transactions after the specified ID.
processed_at_min	Optional	Show tender transactions processed_at or after the specified date.
processed_at_max	Optional	Show tender transactions processed_at or before the specified date.
processed_at	Optional	Show tender transactions processed at the specified date.
order	Optional	Show tender transactions ordered by processed_at in ascending or descending order.

Responses

Response 200 No description available

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/tendertransaction#index-2021-01>

Method GET
Path /admin/api/2021-01/tender_transactions.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Retrieve only transactions after the specified ID.
processed_at_min	Optional	Show tender transactions processed_at or after the specified date.
processed_at_max	Optional	Show tender transactions processed_at or before the specified date.
processed_at	Optional	Show tender transactions processed at the specified date.
order	Optional	Show tender transactions ordered by processed_at in ascending or descending order.

Responses

Response 200 No description available

Retrieves a list of tender transactions. Note: As of version 2019-10, this endpoint implements pagination by using links that are provided in the response header. To learn more, see Making requests to paginated REST Admin API endpoints.

<https://shopify.dev/docs/admin-api/rest/reference/tendertransaction#index-unstable>

Method GET
Path /admin/api/unstable/tender_transactions.json

Parameters

Parameter	About	Description
limit	Optional	The maximum number of results to retrieve. (default: 50, maximum: 250)
since_id	Optional	Retrieve only transactions after the specified ID.
processed_at_min	Optional	Show tender transactions processed_at or after the specified date.
processed_at_max	Optional	Show tender transactions processed_at or before the specified date.
processed_at	Optional	Show tender transactions processed at the specified date.
order	Optional	Show tender transactions ordered by processed_at in ascending or descending order.

Responses

Response 200 No description available

