

1Password Connect

REST API Reference

REST API interface for 1Password Connect.

Version 1.5.7

Revisions

Date	Version	Author	Description
2024-06-01	1.0.0		
2024-06-15	1.1.0		
2024-07-01	1.2.0		

Summary

[OpenAPI JSON](https://api.apis.guru/v2/specs/1password.local/connect/1.5.7/openapi.json): `https://api.apis.guru/v2/specs/1password.local/connect/1.5.7/openapi.json`

Table of Contents

Activity

Access API Request Activity

[GET](#) [/activity](#)
Retrieve a list of API Requests that have been made.

Files

[GET](#) [/vaults/{vaultUuid}/items/{itemUuid}/files](#)
Get all the files inside an Item

[GET](#) [/vaults/{vaultUuid}/items/{itemUuid}/files/{fileUuid}](#)
Get the details of a File

[GET](#) [/vaults/{vaultUuid}/items/{itemUuid}/files/{fileUuid}/content](#)
Get the content of a File

Health

[GET](#) [/health](#)
Get state of the server and its dependencies.

[GET](#) [/heartbeat](#)
Ping the server for liveness

Items

Access and manage items inside 1Password Vaults

[GET](#) [/vaults/{vaultUuid}/items](#)
Get all items for inside a Vault

[POST](#) [/vaults/{vaultUuid}/items](#)
Create a new Item

[GET](#) [/vaults/{vaultUuid}/items/{itemUuid}](#)
Get the details of an Item

[PUT](#) [/vaults/{vaultUuid}/items/{itemUuid}](#)
Update an Item

[DELETE](#) [/vaults/{vaultUuid}/items/{itemUuid}](#)
Delete an Item

[PATCH](#) [/vaults/{vaultUuid}/items/{itemUuid}](#)
Update a subset of Item attributes

Metrics

[GET](#) [/metrics](#)
Query server for exposed Prometheus metrics

Vaults

Access 1Password Vaults

[GET](#) [/vaults](#)
Get all Vaults

[GET](#) [/vaults/{vaultUuid}](#)
Get Vault details and metadata

REST Api

Retrieve a list of API Requests that have been made.

Security	ConnectToken
Method	GET
Path	/activity

Parameters

Parameter	Description
limit	Optional, How many API Events should be retrieved in a single request. <pre>{ "default": 50, "example": 10 }</pre>
offset	Optional, How far into the collection of API Events should the response start <pre>{ "default": 0, "example": 50 }</pre>

Responses

Response	200 OK
- application/json	(Array of following) See referenced schema APIRequest
Response	401 Invalid or missing token
- application/json	See referenced schema ErrorResponse

Get state of the server and its dependencies.

Method	GET
Path	/health

Responses

Response	200 OK
- application/json	Type: object
Properties	
Name	Description
dependencies	array See referenced schema ServiceDependency
name	Required , string
version	Required , string , The Connect server's version

Ping the server for liveness

Method	GET
Path	/heartbeat

Responses

Response	200 OK
- text/plain	Type: string
Example:	
<pre>"."</pre>	

Query server for exposed Prometheus metrics

See Prometheus documentation for a complete data model.

Method	GET
Path	/metrics

Responses

Response
- text/plain

200 Successfully returned Prometheus metrics
Type: string

Example:

```
"# HELP go_gc_duration_seconds A summary of the pause duration of garbage collection cycles.\n# TYPE go_gc_duration_seconds summary\nngo_gc_duration_seconds{quantile=\"0\"} 2.9153e-05\nngo_gc_duration_seconds{quantile=\"0.25\"} 6.2832e-05\nngo_gc_duration_seconds{quantile=\"0.5\"} 9.7187e-05\nngo_gc_duration_seconds{quantile=\"0.75\"} 0.000112967\nngo_gc_duration_seconds{quantile=\"1\"} 0.000215819\nngo_gc_duration_seconds_sum 0.001376862\nngo_gc_duration_seconds_count 14\n"
```

Get all Vaults

Security Method Path
ConnectToken
GET
/vaults

Parameters

Parameter	Description
filter	Optional, Filter the Vault collection based on Vault name using SCIM eq filter

```
{  
  "example": "name eq \"Some Vault Name\""  
}
```

Responses

Response - application/json	200 OK (Array of following) See referenced schema Vault
Response - application/json	401 Invalid or missing token See referenced schema ErrorResponse

Get Vault details and metadata

Security Method Path
ConnectToken
GET
/vaults/{vaultUuid}

Parameters

Parameter	Description
vaultUuid	Required, The UUID of the Vault to fetch Items from

```
{  
  "pattern": "^\\[da-z]{26}$"  
}
```

Responses

Response - application/json	200 OK See referenced schema Vault
Response - application/json	401 Invalid or missing token See referenced schema ErrorResponse
Response - application/json	403 Unauthorized access See referenced schema ErrorResponse
Response - application/json	404 Vault not found See referenced schema ErrorResponse

Get all items for inside a Vault

Security Method Path
ConnectToken
GET
/vaults/{vaultUuid}/items

Parameters

Parameter	Description
vaultUuid	Required, The UUID of the Vault to fetch Items from

```
{  
  "pattern": "^\\[da-z]{26}$"  
}
```

filter	Optional, Filter the Item collection based on Item name using SCIM eq filter
--------	--

```
{  
  "example": "title eq \"Some Item Name\""  
}
```

Responses

Response	200 OK
- application/json	(Array of following) See referenced schema Item
Response	401 Invalid or missing token
- application/json	See referenced schema ErrorResponse
Response	404 Vault not found
- application/json	See referenced schema ErrorResponse

Create a new Item

Security	ConnectToken
Method	POST
Path	/vaults/{vaultUuid}/items

Parameters

Parameter	Description
vaultUuid	Required , The UUID of the Vault to create an Item in <pre>{ "pattern": "[\\da-z]{26}" }</pre>

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema FullItem

Responses

Response	200 OK
- application/json	See referenced schema FullItem
Response	400 Unable to create item due to invalid input
- application/json	See referenced schema ErrorResponse
Response	401 Invalid or missing token
- application/json	See referenced schema ErrorResponse
Response	403 Unauthorized access
- application/json	See referenced schema ErrorResponse
Response	404 Item not found
- application/json	See referenced schema ErrorResponse

Get the details of an Item

Security	ConnectToken
Method	GET
Path	/vaults/{vaultUuid}/items/{itemUuid}

Parameters

Parameter	Description
vaultUuid	Required , The UUID of the Vault to fetch Item from <pre>{ "pattern": "[\\da-z]{26}" }</pre>
itemUuid	Required , The UUID of the Item to fetch <pre>{ "pattern": "[\\da-z]{26}" }</pre>

Responses

Response	200 OK
- application/json	See referenced schema FullItem
Response	401 Invalid or missing token
- application/json	See referenced schema ErrorResponse
Response	403 Unauthorized access
- application/json	See referenced schema ErrorResponse
Response	404 Item not found
- application/json	See referenced schema ErrorResponse

Update an Item

Security	ConnectToken
Method	PUT
Path	/vaults/{vaultUuid}/items/{itemUuid}

Parameters

Parameter	Description
vaultUuid	Required, The UUID of the Item's Vault <pre>{ "pattern": "^\\da-z]{26}\$" }</pre>
itemUuid	Required, The UUID of the Item to update <pre>{ "pattern": "^\\da-z]{26}\$" }</pre>

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema FullItem

Responses

Response	200 OK
- application/json	See referenced schema FullItem
Response	400 Unable to create item due to invalid input
- application/json	See referenced schema ErrorResponse
Response	401 Invalid or missing token
- application/json	See referenced schema ErrorResponse
Response	403 Unauthorized access
- application/json	See referenced schema ErrorResponse
Response	404 Item not found
- application/json	See referenced schema ErrorResponse

Delete an Item

Security	ConnectToken
Method	DELETE
Path	/vaults/{vaultUuid}/items/{itemUuid}

Parameters

Parameter	Description
vaultUuid	Required, The UUID of the Vault the item is in <pre>{ "pattern": "^\\da-z]{26}\$" }</pre>
itemUuid	Required, The UUID of the Item to update <pre>{ "pattern": "^\\da-z]{26}\$" }</pre>

Responses

Response	204 Successfully deleted an item
Response	401 Invalid or missing token
- application/json	See referenced schema ErrorResponse
Response	403 Unauthorized access
- application/json	See referenced schema ErrorResponse
Response	404 Item not found
- application/json	See referenced schema ErrorResponse

Update a subset of Item attributes

Applies a modified [RFC6902 JSON Patch](https://tools.ietf.org/html/rfc6902) document to an Item or ItemField. This endpoint only supports `add`, `remove` and `replace` operations. When modifying a specific ItemField, the ItemField's ID in the `path` attribute of the operation object: `/fields/{fieldId}`

Security	ConnectToken
Method	PATCH

Path /vaults/{vaultUuid}/items/{itemUuid}

Parameters

Parameter	Description
vaultUuid	Required , The UUID of the Vault the item is in <pre>{ "pattern": "^[\\da-z]{26}\$" }</pre>
itemUuid	Required , The UUID of the Item to update <pre>{ "pattern": "^[\\da-z]{26}\$" }</pre>

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema Patch

Responses

Response	200 OK - Item updated. If no Patch operations were provided, Item is unmodified.
- application/json	See referenced schema FullItem
Response	401 Invalid or missing token
- application/json	See referenced schema ErrorResponse
Response	403 Unauthorized access
- application/json	See referenced schema ErrorResponse
Response	404 Item not found
- application/json	See referenced schema ErrorResponse

Get all the files inside an Item

Security	ConnectToken
Method	GET
Path	/vaults/{vaultUuid}/items/{itemUuid}/files

Parameters

Parameter	Description
vaultUuid	Required , The UUID of the Vault to fetch Items from <pre>{ "format": "uuid" }</pre>
itemUuid	Required , The UUID of the Item to fetch files from <pre>{ "format": "uuid" }</pre>
inline_files	Optional, Tells server to return the base64-encoded file contents in the response. <pre>{ "example": true }</pre>

Responses

Response	200 OK
- application/json	(Array of following) See referenced schema File
Response	401 Invalid or missing token
- application/json	See referenced schema ErrorResponse
Response	404 Item not found
- application/json	See referenced schema ErrorResponse
Response	413 File content too large to display
- application/json	See referenced schema ErrorResponse

Get the details of a File

Security	ConnectToken
Method	GET
Path	/vaults/{vaultUuid}/items/{itemUuid}/files/{fileUuid}

Parameters

Parameter	Description
vaultUuid	Required , The UUID of the Vault to fetch Item from <pre>{ "format": "uuid" }</pre>
itemUuid	Required , The UUID of the Item to fetch File from <pre>{ "format": "uuid" }</pre>
fileUuid	Required , The UUID of the File to fetch <pre>{ "format": "uuid" }</pre>
inline_files	Optional, Tells server to return the base64-encoded file contents in the response. <pre>{ "example": true }</pre>

Responses

Response	200 OK
- application/json	See referenced schema File
Response	401 Invalid or missing token
- application/json	See referenced schema ErrorResponse
Response	403 Unauthorized access
- application/json	See referenced schema ErrorResponse
Response	404 File not found
- application/json	See referenced schema ErrorResponse
Response	413 File content too large to display
- application/json	See referenced schema ErrorResponse

Get the content of a File

Security	ConnectToken
Method	GET
Path	/vaults/{vaultUuid}/items/{itemUuid}/files/{fileUuid}/content

Responses

Response	200 Success
- application/octet-stream	Type: string Example: <pre>"string"</pre>
Response	401 Invalid or missing token
- application/json	See referenced schema ErrorResponse
Response	404 File not found
- application/json	See referenced schema ErrorResponse

Schemas

APIRequest

Type: object

Example:

```
{
  "action": "READ",
  "actor": {
    "account": "string",
    "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
    "jti": "string",
    "requestIp": "string",
    "userAgent": "string"
  },
  "requestId": "d385ab22-0f51-4b97-9ecd-b8ff3fd4fcb6",
  "resource": {
    "item": {
      "id": "string"
    },
    "itemVersion": 0,
    "type": "ITEM",
    "vault": {
      "id": "string"
    }
  },
  "result": "SUCCESS",
  "timestamp": "2019-08-24T14:15:22Z"
}
```

Properties

Name	Description														
action	string <pre>{ "enum": ["READ", "CREATE", "UPDATE", "DELETE"] }</pre>														
actor	object Sub-properties <table><tr><th>Name</th><th>Description</th></tr><tr><td>account</td><td>string</td></tr><tr><td>id</td><td>string (format: uuid)</td></tr><tr><td>jti</td><td>string</td></tr><tr><td>requestIp</td><td>string</td></tr><tr><td>userAgent</td><td>string</td></tr></table>	Name	Description	account	string	id	string (format: uuid)	jti	string	requestIp	string	userAgent	string		
Name	Description														
account	string														
id	string (format: uuid)														
jti	string														
requestIp	string														
userAgent	string														
requestId	string (format: uuid), The unique id used to identify a single request.														
resource	object Sub-properties <table><tr><th>Name</th><th>Description</th></tr><tr><td>item</td><td> object Sub-properties <table><tr><th>Name</th><th>Description</th></tr><tr><td>id</td><td> string <pre>{ "pattern": "^[\\da-z]{26}\$" }</pre> </td></tr></table> </td></tr><tr><td>itemVersion</td><td>integer</td></tr><tr><td>type</td><td> string <pre>{ "enum": ["ITEM", "VAULT"] }</pre> </td></tr><tr><td>vault</td><td> object </td></tr></table>	Name	Description	item	object Sub-properties <table><tr><th>Name</th><th>Description</th></tr><tr><td>id</td><td> string <pre>{ "pattern": "^[\\da-z]{26}\$" }</pre> </td></tr></table>	Name	Description	id	string <pre>{ "pattern": "^[\\da-z]{26}\$" }</pre>	itemVersion	integer	type	string <pre>{ "enum": ["ITEM", "VAULT"] }</pre>	vault	object
Name	Description														
item	object Sub-properties <table><tr><th>Name</th><th>Description</th></tr><tr><td>id</td><td> string <pre>{ "pattern": "^[\\da-z]{26}\$" }</pre> </td></tr></table>	Name	Description	id	string <pre>{ "pattern": "^[\\da-z]{26}\$" }</pre>										
Name	Description														
id	string <pre>{ "pattern": "^[\\da-z]{26}\$" }</pre>														
itemVersion	integer														
type	string <pre>{ "enum": ["ITEM", "VAULT"] }</pre>														
vault	object														

Sub-properties

Name

id

Description

string

```
{
  "pattern": "^\\da-z]{26}$"
}
```

result

string

```
{
  "enum": [
    "SUCCESS",
    "DENY"
  ]
}
```

timestamp

string (format: date-time), The time at which the request was processed by the server.

```
{
  "format": "date-time",
  "readOnly": true
}
```

ErrorResponse

Type: object

Example:

```
{
  "message": "string",
  "status": 0
}
```

Properties

Name

Description

message

string , A message detailing the error

status

integer , HTTP Status Code

Field

Type: object

Properties

Name

Description

entropy

number , For fields with a purpose of PASSWORD this is the entropy of the value

```
{
  "readOnly": true
}
```

generate

boolean , If value is not present then a new value should be generated for this field

```
{
  "default": false
}
```

id

Required, string

label

string

purpose

string , Some item types, Login and Password, have fields used for autofill. This property indicates that purpose and is required for some item types.

```
{
  "enum": [
    "",
    "USERNAME",
    "PASSWORD",
    "NOTES"
  ]
}
```

recipe

, The recipe is used in conjunction with the "generate" property to set the character set used to generate a new secure value

See referenced schema [GeneratorRecipe](#)

section

object

Sub-properties

Name

Description

	id string
type	Required string <pre>{ "default": "STRING", "enum": ["STRING", "EMAIL", "CONCEALED", "URL", "TOTP", "DATE", "MONTH_YEAR", "MENU"] }</pre>
value	string

File

Type: object

Example:

```
{
  "content": "VGh1IGZ1dHVyZSB1ZWxvbmdzIHRvIHRoZSBjdXJpb3VzLgo=",
  "content_path": "v1/vaults/ionaiwtdvgclrixbt6ztpqcxnq/items/p7eflcy7f5mk7vg6zrzf5rjjyu/files/6r65pjq33banznomn7q22sj44e/content",
  "id": "6r65pjq33banznomn7q22sj44e",
  "name": "foo.txt",
  "size": 35
}
```

Properties

Name	Description				
content	string (format: byte), Base64-encoded contents of the file. Only set if size <= OP_MAX_INLINE_FILE_SIZE_KB kb and inline_files is set to true.				
content_path	string , Path of the Connect API that can be used to download the contents of this file. <pre>{ "readOnly": true }</pre>				
id	string , ID of the file				
name	string , Name of the file				
section	object , For files that are in a section, this field describes the section. Sub-properties <table><tr><th>Name</th><th>Description</th></tr><tr><td>id</td><td>string</td></tr></table>	Name	Description	id	string
Name	Description				
id	string				
size	integer , Size in bytes of the file				

FullItem

Type: undefined

GeneratorRecipe

Type: object

Example:

```
{
  "characterSets": [
    "LETTERS"
  ],
  "excludeCharacters": "abc1",
  "length": 32
}
```

Properties

Name	Description
characterSets	array <pre>{ "items": { "enum": ["LETTERS", "DIGITS", "SYMBOLS"], "type": "string" }, "maximum": 3, "minimum": 0, }</pre>

```
    "uniqueItems": true
  }
```

See referenced schema [Items of characterSets](#)

excludeCharacters

string , List of all characters that should be excluded from generated passwords.

```
{
  "example": "abc1"
}
```

length

integer , Length of the generated value

```
{
  "default": 32,
  "maximum": 64,
  "minimum": 1
}
```

Item

Type: object

Example:

```
{
  "category": "LOGIN",
  "createdAt": "2019-08-24T14:15:22Z",
  "favorite": false,
  "id": "string",
  "lastEditedBy": "string",
  "state": "ARCHIVED",
  "tags": [
    "string"
  ],
  "title": "string",
  "updatedAt": "2019-08-24T14:15:22Z",
  "urls": [
    {
      "href": "https://example.com",
      "primary": true
    },
    {
      "href": "https://example.org"
    }
  ],
  "vault": {
    "id": "string"
  },
  "version": 0
}
```

Properties

Name	Description
category	Required , string <pre>{ "enum": ["LOGIN", "PASSWORD", "API_CREDENTIAL", "SERVER", "DATABASE", "CREDIT_CARD", "MEMBERSHIP", "PASSPORT", "SOFTWARE_LICENSE", "OUTDOOR_LICENSE", "SECURE_NOTE", "WIRELESS_ROUTER", "BANK_ACCOUNT", "DRIVER_LICENSE", "IDENTITY", "REWARD_PROGRAM", "DOCUMENT", "EMAIL_ACCOUNT", "SOCIAL_SECURITY_NUMBER", "MEDICAL_RECORD", "SSH_KEY", "CUSTOM"] }</pre>
createdAt	string (format: date-time) <pre>{ "format": "date-time", "readOnly": true }</pre>
favorite	boolean <pre>{ "default": false }</pre>
id	string <pre>{ "pattern": "^[\\da-z]{26}\$" }</pre>

	<pre> }</pre>				
lastEditedBy	string <pre> { "readOnly": true }</pre>				
state	string <pre> { "enum": ["ARCHIVED", "DELETED"], "readOnly": true }</pre>				
tags	array See referenced schema Items of tags				
title	string				
updatedAt	string (format: date-time) <pre> { "format": "date-time", "readOnly": true }</pre>				
urls	array <pre> { "example": [{ "href": "https://example.com", "primary": true }, { "href": "https://example.org" }], "items": { "properties": { "href": { "format": "url", "type": "string" }, "label": { "type": "string" }, "primary": { "type": "boolean" } }, "required": ["href"], "type": "object" } }</pre> See referenced schema Items of urls				
vault	Required, object <pre> { "properties": { "id": { "pattern": "^[\\da-z]{26}\$", "type": "string" } }, "required": ["id"] }</pre> Sub-properties <table> <tr> <th>Name</th><th>Description</th></tr> <tr> <td>id</td><td> Required, string <pre> { "pattern": "^[\\da-z]{26}\$" }</pre> </td></tr> </table>	Name	Description	id	Required , string <pre> { "pattern": "^[\\da-z]{26}\$" }</pre>
Name	Description				
id	Required , string <pre> { "pattern": "^[\\da-z]{26}\$" }</pre>				
version	integer				
(Array of following) Type: object Example: <pre> { "op": "add", "path": "/fields/06gnn2b95example10q91512p5/label", }</pre>					

```
"value": {}
}
```

Properties

Name	Description
op	Required , string <pre>{ "enum": ["add", "remove", "replace"] }</pre>
path	Required , string , An RFC6901 JSON Pointer pointing to the Item document, an Item Attribute, and Item Field by Field ID, or an Item Field Attribute <pre>{ "example": "/fields/06gnn2b95example10q91512p5/label1" }</pre>
value	object

ServiceDependency

Type: object

Example:

```
{
  "message": "string",
  "service": "string",
  "status": "string"
}
```

Properties

Name	Description
message	string , Human-readable message for explaining the current state.
service	string
status	string

Vault

Type: object

Example:

```
{
  "attributeVersion": 0,
  "contentVersion": 0,
  "createdAt": "2019-08-24T14:15:22Z",
  "description": "string",
  "id": "string",
  "items": 0,
  "name": "string",
  "type": "USER_CREATED",
  "updatedAt": "2019-08-24T14:15:22Z"
}
```

Properties

Name	Description
attributeVersion	integer , The vault version
contentVersion	integer , The version of the vault contents
createdAt	string (format: date-time) <pre>{ "format": "date-time", "readOnly": true }</pre>
description	string
id	string <pre>{ "pattern": "^[\\da-z]{26}\$" }</pre>
items	integer , Number of active items in the vault
name	string
type	string <pre>{ "enum": [</pre>


```
"USER_CREATED",
"PERSONAL",
"EVERYONE",
"TRANSFER"
]
```

updatedAt

string (format: date-time)

```
{
  "format": "date-time",
  "readOnly": true
}
```

GeneratorRecipe_characterSets

Type: string

Example:

```
"LETTERS"
```

Item_tags

Type: string

Example:

```
"string"
```

Item_urls

Type: object

Example:

```
{
  "href": "string",
  "label": "string",
  "primary": true
}
```

Properties

Name	Description
href	Required , string (format: url)
label	string
primary	boolean

