

Configuration API

REST API Reference

The Configuration API enables you to create a platform where you can onboard your users as account holders and create balance accounts, cards, and business accounts. ## Authentication Your Adyen contact will provide your API credential and an API key. To connect to the API, add an `X-API-Key` header with the API key as the value, for example: `` curl -H "Content-Type: application/json" \ -H "X-API-Key: YOUR\_API\_KEY" \ ... `` Alternatively, you can use the username and password to connect to the API using basic authentication. For example: `` curl -H "Content-Type: application/json" \ -U "ws@BalancePlatform.YOUR\_BALANCE\_PLATFORM":"YOUR\_WS\_PASSWORD" \ ... `` ## Versioning The Configuration API supports [versioning](https://docs.adyen.com/development-resources/versioning) using a version suffix in the endpoint URL. This suffix has the following format: "vXX", where XX is the version number. For example: `` https://balanceplatform-api-test.adyen.com/bcl/v2/accountHolders `` ## Going live When going live, your Adyen contact will provide your API credential for the live environment. You can then use the API key or the username and password to send requests to `https://balanceplatform-api-live.adyen.com/bcl/v2`.

Revisions

Date	Version	Author	Description
2024-06-01	1.0.0		
2024-06-15	1.1.0		
2024-07-01	1.2.0		

Summary

[OpenAPI JSON](https://api.apis.guru/v2/specs/adyen.com/BalancePlatformService/2/openapi.json): <https://api.apis.guru/v2/specs/adyen.com/BalancePlatformService/2/openapi.json>

Table of Contents

Account holders

- [POST](#) </accountHolders>
Create an account holder
- [GET](#) </accountHolders/{id}>
Get an account holder
- [PATCH](#) </accountHolders/{id}>
Update an account holder
- [GET](#) </accountHolders/{id}/balanceAccounts>
Get all balance accounts of an account holder

Balance accounts

- [POST](#) </balanceAccounts>
Create a balance account
- [GET](#) </balanceAccounts/{balanceAccountId}/sweeps>
Get all sweeps for a balance account
- [POST](#) </balanceAccounts/{balanceAccountId}/sweeps>
Create a sweep
- [GET](#) </balanceAccounts/{balanceAccountId}/sweeps/{sweepId}>
Get a sweep
- [DELETE](#) </balanceAccounts/{balanceAccountId}/sweeps/{sweepId}>
Delete a sweep
- [PATCH](#) </balanceAccounts/{balanceAccountId}/sweeps/{sweepId}>
Update a sweep
- [GET](#) </balanceAccounts/{id}>
Get a balance account
- [PATCH](#) </balanceAccounts/{id}>
Update a balance account
- [GET](#) </balanceAccounts/{id}/paymentInstruments>
Get all payment instruments for a balance account

Bank account validation

- [POST](#) </validateBankAccountIdentification>
Validate a bank account

Grant accounts

- [GET](#) </grantAccounts/{id}>
Get a grant account

Grant offers

- [GET](#) </grantOffers>
Get all available grant offers
- [GET](#) </grantOffers/{grantOfferId}>
Get a grant offer

Payment instrument groups

- [POST](#) </paymentInstrumentGroups>
Create a payment instrument group
- [GET](#) </paymentInstrumentGroups/{id}>
Get a payment instrument group
- [GET](#) </paymentInstrumentGroups/{id}/transactionRules>
Get all transaction rules for a payment instrument group

Payment instruments

- [POST](#) </paymentInstruments>
Create a payment instrument
- [GET](#) </paymentInstruments/{id}>

PATCH	Get a payment instrument /paymentInstruments/{id} Update a payment instrument
GET	/paymentInstruments/{id}/reveal Get the PAN of a payment instrument
GET	/paymentInstruments/{id}/transactionRules Get all transaction rules for a payment instrument

Platform

GET	/balancePlatforms/{id} Get a balance platform
GET	/balancePlatforms/{id}/accountHolders Get all account holders under a balance platform

Transaction rules

POST	/transactionRules Create a transaction rule
GET	/transactionRules/{transactionRuleId} Get a transaction rule
DELETE	/transactionRules/{transactionRuleId} Delete a transaction rule
PATCH	/transactionRules/{transactionRuleId} Update a transaction rule

REST Api

Create an account holder

Creates an account holder linked to a [legal entity](https://docs.adyen.com/api-explorer/#!/legalentity/latest/post/legalEntities).

Security	BasicAuth ApiKeyAuth
Method	POST
Path	/accountHolders

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema AccountHolderInfo

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema AccountHolder
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get an account holder

Returns an account holder.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/accountHolders/{id}

Parameters

Parameter	Description
id	Required , The unique identifier of the account holder.

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema AccountHolder
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Update an account holder

Updates an account holder. When updating an account holder resource, if a parameter is not provided in the request, it is left unchanged.

Security	BasicAuth ApiKeyAuth
Method	PATCH
Path	/accountHolders/{id}

Parameters

Parameter	Description
id	Required , The unique identifier of the account holder.

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema AccountHolder

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema AccountHolder
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get all balance accounts of an account holder

Returns a paginated list of the balance accounts associated with an account holder. To fetch multiple pages, use the query parameters. For example, to limit the page to 5 balance accounts and skip the first 10, use `/accountHolders/{id}/balanceAccounts?limit=5&offset=10`.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/accountHolders/{id}/balanceAccounts

Parameters

Parameter	Description
id	Required , The unique identifier of the account holder.
offset	Optional, The number of items that you want to skip. <pre>{ "format": "int32" }</pre>
limit	Optional, The number of items returned per page, maximum 100 items. By default, the response returns 10 items per page. <pre>{ "format": "int32" }</pre>

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema PaginatedBalanceAccountsResponse
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Create a balance account

Creates a balance account that holds the funds of the associated account holder.

Security	BasicAuth ApiKeyAuth
Method	POST
Path	/balanceAccounts

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema BalanceAccountInfo

Responses

Response - application/json	200 OK - the request has succeeded. See referenced schema BalanceAccount
Response - application/json	400 Bad Request - a problem reading or understanding the request. See referenced schema RestServiceError
Response - application/json	401 Unauthorized - authentication required. See referenced schema RestServiceError
Response - application/json	403 Forbidden - insufficient permissions to process the request. See referenced schema RestServiceError
Response - application/json	422 Unprocessable Entity - a request validation error. See referenced schema RestServiceError
Response - application/json	500 Internal Server Error - the server could not process the request. See referenced schema RestServiceError

Get all sweeps for a balance account

Returns a list of the sweeps configured for a balance account. To fetch multiple pages, use the query parameters. For example, to limit the page to 5 sweeps and to skip the first 10, use `/balanceAccounts/{balanceAccountId}/sweeps?limit=5&offset=10`.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/balanceAccounts/{balanceAccountId}/sweeps

Parameters

Parameter	Description
balanceAccountId	Required , The unique identifier of the balance account.
offset	Optional, The number of items that you want to skip. <pre>{ "format": "int32" }</pre>
limit	Optional, The number of items returned per page, maximum 100 items. By default, the response returns 10 items per page. <pre>{ "format": "int32" }</pre>

Responses

Response - application/json	200 OK - the request has succeeded. See referenced schema BalanceSweepConfigurationsResponse
Response - application/json	400 Bad Request - a problem reading or understanding the request. See referenced schema RestServiceError
Response - application/json	401 Unauthorized - authentication required. See referenced schema RestServiceError
Response - application/json	403 Forbidden - insufficient permissions to process the request. See referenced schema RestServiceError
Response - application/json	422 Unprocessable Entity - a request validation error. See referenced schema RestServiceError
Response - application/json	500 Internal Server Error - the server could not process the request. See referenced schema RestServiceError

Create a sweep

Creates a sweep that results in moving funds from or to a balance account. A sweep pulls in or pushes out funds based on a defined schedule, amount, currency, and a source or a destination.

Security	BasicAuth ApiKeyAuth
Method	POST
Path	/balanceAccounts/{balanceAccountId}/sweeps

Parameters

Parameter	Description
balanceAccountId	Required , The unique identifier of the balance account.

Request Body

Required	No
Description	No description available
Content-type - Schema	application/json See referenced schema SweepConfigurationV2

Responses

Response	200 OK - the request has succeeded.
-----------------	-------------------------------------

- application/json Response	See referenced schema SweepConfigurationV2
- application/json Response	400 Bad Request - a problem reading or understanding the request. See referenced schema RestServiceError
- application/json Response	401 Unauthorized - authentication required. See referenced schema RestServiceError
- application/json Response	403 Forbidden - insufficient permissions to process the request. See referenced schema RestServiceError
- application/json Response	422 Unprocessable Entity - a request validation error. See referenced schema RestServiceError
- application/json Response	500 Internal Server Error - the server could not process the request. See referenced schema RestServiceError

Get a sweep

Returns a sweep.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/balanceAccounts/{balanceAccountId}/sweeps/{sweepId}

Parameters

Parameter	Description
balanceAccountId	Required , The unique identifier of the balance account.
sweepId	Required , The unique identifier of the sweep.

Responses

Response	200 OK - the request has succeeded.
- application/json Response	See referenced schema SweepConfigurationV2
- application/json Response	400 Bad Request - a problem reading or understanding the request. See referenced schema RestServiceError
- application/json Response	401 Unauthorized - authentication required. See referenced schema RestServiceError
- application/json Response	403 Forbidden - insufficient permissions to process the request. See referenced schema RestServiceError
- application/json Response	422 Unprocessable Entity - a request validation error. See referenced schema RestServiceError
- application/json Response	500 Internal Server Error - the server could not process the request. See referenced schema RestServiceError

Delete a sweep

Deletes a sweep for a balance account.

Security	BasicAuth ApiKeyAuth
Method	DELETE
Path	/balanceAccounts/{balanceAccountId}/sweeps/{sweepId}

Parameters

Parameter	Description
balanceAccountId	Required , The unique identifier of the balance account.
sweepId	Required , The unique identifier of the sweep.

Responses

Response	204 No Content - the request has been successfully processed, but there is no additional content.
Response	400 Bad Request - a problem reading or understanding the request. See referenced schema RestServiceError
- application/json Response	401 Unauthorized - authentication required. See referenced schema RestServiceError
- application/json Response	403 Forbidden - insufficient permissions to process the request. See referenced schema RestServiceError
- application/json Response	422 Unprocessable Entity - a request validation error. See referenced schema RestServiceError
- application/json Response	500 Internal Server Error - the server could not process the request. See referenced schema RestServiceError

Update a sweep

Updates a sweep. When updating a sweep resource, note that if a request parameter is not provided, the parameter is left unchanged.

Security	BasicAuth ApiKeyAuth
-----------------	----------------------

Method	PATCH
Path	/balanceAccounts/{balanceAccountId}/sweeps/{sweepId}

Parameters

Parameter	Description
balanceAccountId	Required , The unique identifier of the balance account.
sweepId	Required , The unique identifier of the sweep.

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema SweepConfigurationV2

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema SweepConfigurationV2
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get a balance account

Returns a balance account and its balances for the default currency and other currencies with a non-zero balance.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/balanceAccounts/{id}

Parameters

Parameter	Description
id	Required , The unique identifier of the balance account.

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema BalanceAccount
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Update a balance account

Updates a balance account.

Security	BasicAuth ApiKeyAuth
Method	PATCH
Path	/balanceAccounts/{id}

Parameters

Parameter	Description
id	Required , The unique identifier of the balance account.

Request Body

Required	No
Description	No description available

Content-type application/json
- Schema See referenced schema [BalanceAccountUpdateRequest](#)

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema BalanceAccount
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get all payment instruments for a balance account

Returns a paginated list of the payment instruments associated with a balance account. To fetch multiple pages, use the query parameters. For example, to limit the page to 3 payment instruments and to skip the first 6, use `/balanceAccounts/{id}/paymentInstruments?limit=3&offset=6`.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/balanceAccounts/{id}/paymentInstruments

Parameters

Parameter	Description
id	Required , The unique identifier of the balance account.
offset	Optional, The number of items that you want to skip. <pre>{ "format": "int32" }</pre>
limit	Optional, The number of items returned per page, maximum 100 items. By default, the response returns 10 items per page. <pre>{ "format": "int32" }</pre>

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema PaginatedPaymentInstrumentsResponse
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get a balance platform

Returns a balance platform.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/balancePlatforms/{id}

Parameters

Parameter	Description
id	Required , The unique identifier of the balance platform.

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema BalancePlatform
Response	400 Bad Request - a problem reading or understanding the request.

- application/json Response	See referenced schema RestServiceError 401 Unauthorized - authentication required.
- application/json Response	See referenced schema RestServiceError 403 Forbidden - insufficient permissions to process the request.
- application/json Response	See referenced schema RestServiceError 422 Unprocessable Entity - a request validation error.
- application/json Response	See referenced schema RestServiceError 500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get all account holders under a balance platform

Returns a paginated list of all the account holders that belong to the balance platform. To fetch multiple pages, use the query parameters. For example, to limit the page to 5 account holders and to skip the first 20, use `/balancePlatforms/{id}/accountHolders?limit=5&offset=20`.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/balancePlatforms/{id}/accountHolders

Parameters

Parameter	Description
id	Required , The unique identifier of the balance platform.
offset	Optional, The number of items that you want to skip. <pre>{ "format": "int32" }</pre>
limit	Optional, The number of items returned per page, maximum 100 items. By default, the response returns 10 items per page. <pre>{ "format": "int32" }</pre>

Responses

Response	200 OK - the request has succeeded.
- application/json Response	See referenced schema PaginatedAccountHoldersResponse
Response	400 Bad Request - a problem reading or understanding the request.
- application/json Response	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json Response	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json Response	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json Response	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get a grant account

Returns the details of the [grant account](https://docs.adyen.com/marketplaces-and-platforms/capital#grant-account).

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/grantAccounts/{id}

Parameters

Parameter	Description
id	Required , The unique identifier of the grant account.

Responses

Response	200 OK - the request has succeeded.
- application/json Response	See referenced schema CapitalGrantAccount
Response	400 Bad Request - a problem reading or understanding the request.
- application/json Response	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json Response	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json Response	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json Response	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get all available grant offers

Returns a list of all [grant offers](https://docs.adyen.com/marketplaces-and-platforms/capital#grant-offers) available for `accountHolderId` specified as a query parameter.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/grantOffers

Parameters

Parameter	Description
accountHolderId	Required , The unique identifier of the grant account.

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema GrantOffers
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get a grant offer

Returns the details of a single grant offer.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/grantOffers/{grantOfferId}

Parameters

Parameter	Description
grantOfferId	Required , The unique identifier of the grant offer.

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema GrantOffer
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Create a payment instrument group

Creates a payment instrument group to associate and group payment instrument resources together. You can apply a transaction rule to a payment instrument group.

Security	BasicAuth ApiKeyAuth
Method	POST
Path	/paymentInstrumentGroups

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema PaymentInstrumentGroupInfo

Responses

Response	200 OK - the request has succeeded.
----------	-------------------------------------

- application/json Response	See referenced schema PaymentInstrumentGroup
- application/json Response	400 Bad Request - a problem reading or understanding the request.
- application/json Response	See referenced schema RestServiceError
- application/json Response	401 Unauthorized - authentication required.
- application/json Response	See referenced schema RestServiceError
- application/json Response	403 Forbidden - insufficient permissions to process the request.
- application/json Response	See referenced schema RestServiceError
- application/json Response	422 Unprocessable Entity - a request validation error.
- application/json Response	See referenced schema RestServiceError
- application/json Response	500 Internal Server Error - the server could not process the request.
- application/json Response	See referenced schema RestServiceError

Get a payment instrument group

Returns the details of a payment instrument group.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/paymentInstrumentGroups/{id}

Parameters

Parameter	Description
id	Required , The unique identifier of the payment instrument group.

Responses

Response	200 OK - the request has succeeded.
- application/json Response	See referenced schema PaymentInstrumentGroup
Response	400 Bad Request - a problem reading or understanding the request.
- application/json Response	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json Response	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json Response	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json Response	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json Response	See referenced schema RestServiceError

Get all transaction rules for a payment instrument group

Returns a list of all the transaction rules associated with a payment instrument group.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/paymentInstrumentGroups/{id}/transactionRules

Parameters

Parameter	Description
id	Required , The unique identifier of the payment instrument group.

Responses

Response	200 OK - the request has succeeded.
- application/json Response	See referenced schema TransactionRulesResponse
Response	400 Bad Request - a problem reading or understanding the request.
- application/json Response	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json Response	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json Response	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json Response	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json Response	See referenced schema RestServiceError

Create a payment instrument

Creates a payment instrument to issue a physical card, a virtual card, or a business account to your user. For more information, refer to [Issue cards](https://docs.adyen.com/issuing/create-cards) or [Issue business accounts](https://docs.adyen.com/marketplaces-and-platforms/business-accounts).

Security	BasicAuth ApiKeyAuth
Method	POST
Path	/paymentInstruments

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema PaymentInstrumentInfo

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema PaymentInstrument
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get a payment instrument

Returns the details of a payment instrument.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/paymentInstruments/{id}

Parameters

Parameter	Description
id	Required , The unique identifier of the payment instrument.

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema PaymentInstrument
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Update a payment instrument

Updates a payment instrument. Once a payment instrument is already active, you can only update its status. However, for cards created with ****inactive**** status, you can still update the balance account associated with the card.

Security	BasicAuth ApiKeyAuth
Method	PATCH
Path	/paymentInstruments/{id}

Parameters

Parameter	Description
id	Required , The unique identifier of the payment instrument.

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema PaymentInstrumentUpdateRequest

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema UpdatePaymentInstrument
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get the PAN of a payment instrument

Returns the primary account number (PAN) of a payment instrument. To make this request, your API credential must have the following [role] (<https://docs.adyen.com/issuing/manage-access/api-credentials-web-service#api-permissions>): * Balance Platform BCL PCI role

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/paymentInstruments/{id}/reveal

Parameters

Parameter	Description
id	Required , The unique identifier of the payment instrument.

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema PaymentInstrumentRevealInfo
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get all transaction rules for a payment instrument

Returns a list of transaction rules associated with a payment instrument.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/paymentInstruments/{id}/transactionRules

Parameters

Parameter	Description
id	Required , The unique identifier of the payment instrument.

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema TransactionRulesResponse
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Create a transaction rule

Creates a [transaction rule](<https://docs.adyen.com/issuing/transaction-rules>). When your user makes a transaction with their Adyen-issued card, the transaction is allowed or declined based on the conditions and outcome defined in the transaction rule. You can apply the

transaction rule to several cards, such as all the cards in your platform, or to a specific card. For use cases, see [examples] (<https://docs.adyen.com/issuing/transaction-rules/examples>).

Security	BasicAuth ApiKeyAuth
Method	POST
Path	/transactionRules

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema TransactionRuleInfo

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema TransactionRule
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Get a transaction rule

Returns the details of a transaction rule.

Security	BasicAuth ApiKeyAuth
Method	GET
Path	/transactionRules/{transactionRuleId}

Parameters

Parameter	Description
transactionRuleId	Required , The unique identifier of the transaction rule.

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema TransactionRuleResponse
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError
Response	401 Unauthorized - authentication required.
- application/json	See referenced schema RestServiceError
Response	403 Forbidden - insufficient permissions to process the request.
- application/json	See referenced schema RestServiceError
Response	422 Unprocessable Entity - a request validation error.
- application/json	See referenced schema RestServiceError
Response	500 Internal Server Error - the server could not process the request.
- application/json	See referenced schema RestServiceError

Delete a transaction rule

Deletes a transaction rule.

Security	BasicAuth ApiKeyAuth
Method	DELETE
Path	/transactionRules/{transactionRuleId}

Parameters

Parameter	Description
transactionRuleId	Required , The unique identifier of the transaction rule.

Responses

Response	200 OK - the request has succeeded.
- application/json	See referenced schema TransactionRule
Response	400 Bad Request - a problem reading or understanding the request.
- application/json	See referenced schema RestServiceError

Response - application/json	401 Unauthorized - authentication required. See referenced schema RestServiceError
Response - application/json	403 Forbidden - insufficient permissions to process the request. See referenced schema RestServiceError
Response - application/json	422 Unprocessable Entity - a request validation error. See referenced schema RestServiceError
Response - application/json	500 Internal Server Error - the server could not process the request. See referenced schema RestServiceError

Update a transaction rule

Updates a transaction rule. * To update only the status of a transaction rule, send only the `status` parameter. All other parameters not provided in the request are left unchanged. * When updating any other parameter, you need to send all existing resource parameters. If you omit a parameter in the request, that parameter is removed from the resource.

Security	BasicAuth ApiKeyAuth
Method	PATCH
Path	/transactionRules/{transactionRuleId}

Parameters

Parameter	Description
transactionRuleId	Required , The unique identifier of the transaction rule.

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema TransactionRuleInfo

Responses

Response - application/json	200 OK - the request has succeeded. See referenced schema TransactionRule
Response - application/json	400 Bad Request - a problem reading or understanding the request. See referenced schema RestServiceError
Response - application/json	401 Unauthorized - authentication required. See referenced schema RestServiceError
Response - application/json	403 Forbidden - insufficient permissions to process the request. See referenced schema RestServiceError
Response - application/json	422 Unprocessable Entity - a request validation error. See referenced schema RestServiceError
Response - application/json	500 Internal Server Error - the server could not process the request. See referenced schema RestServiceError

Validate a bank account

Validates bank account identification details. You can use this endpoint to validate bank account details before you [make a transfer] (<https://docs.adyen.com/api-explorer/transfers/latest/post/transfers>) or [create a transfer instrument] (<https://docs.adyen.com/api-explorer/legalentity/latest/post/transferInstruments>).

Security	BasicAuth ApiKeyAuth
Method	POST
Path	/validateBankAccountIdentification

Request Body

Required	No
Description	No description available
Content-type	application/json
- Schema	See referenced schema BankAccountIdentificationValidationRequest

Responses

Response - application/json	200 OK - the request has succeeded. See referenced schema Void
Response - application/json	401 Unauthorized - authentication required. See referenced schema RestServiceError
Response - application/json	403 Forbidden - insufficient permissions to process the request. See referenced schema RestServiceError
Response - application/json	422 Unprocessable Entity - a request validation error. See referenced schema RestServiceError
Response - application/json	500 Internal Server Error - the server could not process the request. See referenced schema RestServiceError

Schemas

AULocalAccountIdentification

Type: object

Example:

```
{
  "accountNumber": "string",
  "bsbCode": "string",
  "type": "auLocal"
}
```

Properties

Name	Description
accountNumber	Required , string , The bank account number, without separators or whitespace. <pre>{ "maxLength": 9, "minLength": 5 }</pre>
bsbCode	Required , string , The 6-digit Bank State Branch (BSB) code , without separators or whitespace. <pre>{ "maxLength": 6, "minLength": 6 }</pre>
type	Required , string , auLocal <pre>{ "default": "auLocal", "enum": ["auLocal"] }</pre>

AccountHolder

Type: object

Properties

Name	Description
balancePlatform	string , The unique identifier of the balance platform to which the account holder belongs. Required in the request if your API credentials can be used for multiple balance platforms.
capabilities	object , Contains key-value pairs that specify the actions that an account holder can do in your platform. The key is a capability required for your integration. For example, issueCard for Issuing. The value is an object containing the settings for the capability. <pre>{ "additionalProperties": { "\$ref": "#/components/schemas/AccountHolderCapability" } }</pre>
contactDetails	See referenced schema ContactDetails <pre>{ "deprecated": true }</pre>
description	string , Your description for the account holder, maximum 300 characters. <pre>{ "maxLength": 300 }</pre>
id	Required , string , The unique identifier of the account holder. <pre>{ "readOnly": true }</pre>
legalEntityId	Required , string , The unique identifier of the legal entity associated with the account holder. Adyen performs a verification process against the legal entity of the account holder.
primaryBalanceAccount	string , The ID of the account holder's primary balance account. By default, this is set to the first balance account that you create for the account holder. To assign a different balance account, send a PATCH request.
reference	string , Your reference for the account holder, maximum 150 characters. <pre>{ "maxLength": 150 }</pre>

```
}
```

status

string , The status of the account holder. Possible values: * **active**: The account holder is active. This is the default status when creating an account holder. * **inactive (Deprecated)**: The account holder is temporarily inactive due to missing KYC details. You can set the account back to active by providing the missing KYC details. * **suspended**: The account holder is permanently deactivated by Adyen. This action cannot be undone. * **closed**: The account holder is permanently deactivated by you. This action cannot be undone.

```
{
  "enum": [
    "active",
    "closed",
    "inactive",
    "suspended"
  ]
}
```

timeZone

string , The [time zone](#) of the account holder. For example, **Europe/Amsterdam**. Defaults to the time zone of the balance platform if no time zone is set. For possible values, see the [list of time zone codes](#).

verificationDeadlines

array , List of verification deadlines and the capabilities that will be disallowed if verification errors are not resolved.

```
{
  "items": {
    "$ref": "#/components/schemas/VerificationDeadline"
  },
  "readOnly": true,
  "x-addedInVersion": "2"
}
```

See referenced schema [VerificationDeadline](#)

AccountHolderCapability

Type: object

Properties

Name	Description
allowed	boolean , Indicates whether the capability is allowed. Adyen sets this to true if the verification is successful and the account holder is permitted to use the capability. <pre>{ "readOnly": true }</pre>
allowedLevel	string , The capability level that is allowed for the account holder. Possible values: notApplicable , low , medium , high . <pre>{ "enum": ["high", "low", "medium", "notApplicable"], "readOnly": true }</pre>
allowedSettings	See referenced schema JSONObject <pre>{ "readOnly": true }</pre>
enabled	boolean , Indicates whether the capability is enabled. If false , the capability is temporarily disabled for the account holder.
problems	array , Contains verification errors and the actions that you can take to resolve them. <pre>{ "items": { "\$ref": "#/components/schemas/CapabilityProblem" }, "readOnly": true }</pre> See referenced schema CapabilityProblem
requested	boolean , Indicates whether the capability is requested. To check whether the account holder is permitted to use the capability, refer to the <code>allowed</code> field.
requestedLevel	string , The requested level of the capability. Some capabilities, such as those used in card issuing , have different levels. Levels increase the capability, but also require additional checks and increased monitoring. Possible values: notApplicable , low , medium , high . <pre>{ "enum": ["high", "low", "medium", "notApplicable"] }</pre>

```
"notApplicable"
]
}
```

requestedSettings

See referenced schema [JSONObject](#)

```
{
  "readOnly": true
}
```

transferInstruments

array , Contains the status of the transfer instruments associated with this capability.

See referenced schema [AccountSupportingEntityCapability](#)

verificationStatus

string , The status of the verification checks for the capability. Possible values: * **pending**: Adyen is running the verification. * **invalid**: The verification failed. Check if the `errors` array contains more information. * **valid**: The verification has been successfully completed. * **rejected**: Adyen has verified the information, but found reasons to not allow the capability.

```
{
  "enum": [
    "invalid",
    "pending",
    "rejected",
    "valid"
  ],
  "readOnly": true
}
```

AccountHolderInfo

Type: object

Properties

Name	Description
balancePlatform	string , The unique identifier of the balance platform to which the account holder belongs. Required in the request if your API credentials can be used for multiple balance platforms.
capabilities	object , Contains key-value pairs that specify the actions that an account holder can do in your platform. The key is a capability required for your integration. For example, issueCard for Issuing. The value is an object containing the settings for the capability. <pre>{ "additionalProperties": { "\$ref": "#/components/schemas/AccountHolderCapability" } }</pre>
contactDetails	See referenced schema ContactDetails <pre>{ "deprecated": true }</pre>
description	string , Your description for the account holder, maximum 300 characters. <pre>{ "maxLength": 300 }</pre>
legalEntityId	Required , string , The unique identifier of the legal entity associated with the account holder. Adyen performs a verification process against the legal entity of the account holder.
reference	string , Your reference for the account holder, maximum 150 characters. <pre>{ "maxLength": 150 }</pre>
timeZone	string , The time zone of the account holder. For example, Europe/Amsterdam . Defaults to the time zone of the balance platform if no time zone is set. For possible values, see the list of time zone codes .

AccountSupportingEntityCapability

Type: object

Example:

```
{
  "allowed": true,
  "allowedLevel": "high",
  "enabled": true,
  "id": "string",
  "requested": true,
  "requestedLevel": "high",
  "verificationStatus": "invalid"
}
```

Properties

Name	Description
allowed	boolean , Indicates whether the supporting entity capability is allowed. Adyen sets this to true if the verification is successful and the account holder is permitted to use the capability. <pre>{ "readOnly": true }</pre>
allowedLevel	string , The capability level that is allowed for the account holder. Possible values: notApplicable , low , medium , high . <pre>{ "enum": ["high", "low", "medium", "notApplicable"], "readOnly": true }</pre>
enabled	boolean , Indicates whether the capability is enabled. If false , the capability is temporarily disabled for the account holder.
id	string , The ID of the supporting entity. <pre>{ "readOnly": true }</pre>
requested	boolean , Indicates whether the capability is requested. To check whether the account holder is permitted to use the capability, refer to the <code>allowed</code> field.
requestedLevel	string , The requested level of the capability. Some capabilities, such as those used in card issuing , have different levels. Levels increase the capability, but also require additional checks and increased monitoring. Possible values: notApplicable , low , medium , high . <pre>{ "enum": ["high", "low", "medium", "notApplicable"] }</pre>
verificationStatus	string , The status of the verification checks for the supporting entity capability. Possible values: * pending : Adyen is running the verification. * invalid : The verification failed. Check if the <code>errors</code> array contains more information. * valid : The verification has been successfully completed. * rejected : Adyen has verified the information, but found reasons to not allow the capability. <pre>{ "enum": ["invalid", "pending", "rejected", "valid"], "readOnly": true }</pre>

ActiveNetworkTokensRestriction

Type: object

Example:

```
{
  "operation": "string",
  "value": 0
}
```

Properties

Name	Description
operation	Required , string , Defines how the condition must be evaluated.
value	integer (format: int32), The number of tokens.

AdditionalBankIdentification

Type: object

Example:

```
{
  "code": "string",
  "type": "gbSortCode"
}
```

Properties

Name	Description
code	string , The value of the additional bank identification.
type	string , The type of additional bank identification, depending on the country. Possible values: * gbSortCode : The 6-digit UK sort code , without separators or spaces * usRoutingNumber : The 9-digit routing number , without separators or spaces. <pre>{ "enum": ["gbSortCode", "usRoutingNumber"] }</pre>

Address

Type: object

Example:

```
{
  "city": "string",
  "country": "string",
  "houseNumberOrName": "string",
  "postalCode": "string",
  "stateOrProvince": "string",
  "street": "string"
}
```

Properties

Name	Description
city	Required , string , The name of the city. Maximum length: 3000 characters. <pre>{ "maxLength": 3000 }</pre>
country	Required , string , The two-character ISO-3166-1 alpha-2 country code. For example, US . > If you don't know the country or are not collecting the country from the shopper, provide <code>country</code> as <code>ZZ</code> .
houseNumberOrName	Required , string , The number or name of the house. Maximum length: 3000 characters. <pre>{ "maxLength": 3000 }</pre>
postalCode	Required , string , A maximum of five digits for an address in the US, or a maximum of ten characters for an address in all other countries.
stateOrProvince	string , The two-character ISO 3166-2 state or province code. For example, CA in the US or ON in Canada. > Required for the US and Canada.
street	Required , string , The name of the street. Maximum length: 3000 characters. > The house number should not be included in this field; it should be separately provided via <code>houseNumberOrName</code> . <pre>{ "maxLength": 3000 }</pre>

Address-2

Type: object

Example:

```
{
  "city": "string",
  "country": "string",
  "line1": "string",
  "line2": "string",
  "line3": "string",
  "postalCode": "string",
  "stateOrProvince": "string"
}
```

Properties

Name	Description
city	string , The name of the city.
country	Required , string , The two-character ISO-3166-1 alpha-2 country code. For example, US . >If you don't know the country or are not collecting the country from the shopper, provide <code>country</code> as <code>ZZ</code> .
line1	string , First line of the address.
line2	string , Second line of the address.
line3	string , Third line of the address.

postalCode	string , The postal code. Maximum length: * 5 digits for an address in the US. * 10 characters for an address in all other countries.
stateOrProvince	string , The two-letterISO 3166-2 state or province code. For example, CA in the US or ON in Canada. > Required for the US and Canada.

Amount

Type: object

Example:

```
{
  "currency": "str",
  "value": 0
}
```

Properties

Name	Description
currency	Required , string , The three-character ISO currency code . <pre>{ "maxLength": 3, "minLength": 3 }</pre>
value	Required , integer (format: int64), The amount of the transaction, in minor units .

Authentication

Type: object

Properties

Name	Description
email	string , The email address where the one-time password (OTP) is sent.
password	string , The password used for 3D Secure password-based authentication. The value must be between 1 to 30 characters and must only contain the following supported characters. * Characters between a-z , A-Z , and 0-9 * Special characters: äöüßÄÖÜ+~*/ç%()=?!~#"',:;&àùôâôûáúó <pre>{ "maxLength": 30, "minLength": 1 }</pre>
phone	See referenced schema Phone

Balance

Type: object

Example:

```
{
  "available": 0,
  "balance": 0,
  "currency": "string",
  "reserved": 0
}
```

Properties

Name	Description
available	Required , integer (format: int64), The remaining amount available for spending.
balance	Required , integer (format: int64), The total amount in the balance.
currency	Required , string , The three-character ISO currency code of the balance.
reserved	Required , integer (format: int64), The amount reserved for payments that have been authorised, but have not been captured yet.

BalanceAccount

Type: object

Properties

Name	Description
accountHolderId	Required , string , The unique identifier of the account holder associated with the balance account.
balances	array , List of balances with the amount and currency. See referenced schema Balance

defaultCurrencyCode	string , The default three-character ISO currency code of the balance account. The default value is EUR .
description	string , A human-readable description of the balance account, maximum 300 characters. You can use this parameter to distinguish between multiple balance accounts under an account holder. <pre>{ "maxLength": 300 }</pre>
id	Required , string , The unique identifier of the balance account.
reference	string , Your reference for the balance account, maximum 150 characters. <pre>{ "maxLength": 150 }</pre>
status	string , The status of the balance account, set to active by default. <pre>{ "enum": ["active", "closed", "inactive", "suspended"] }</pre>
timeZone	string , The time zone of the balance account. For example, Europe/Amsterdam . Defaults to the time zone of the account holder if no time zone is set. For possible values, see the list of time zone codes .

BalanceAccountBase

Type: object

Example:

```
{
  "accountHolderId": "string",
  "defaultCurrencyCode": "string",
  "description": "string",
  "id": "string",
  "reference": "string",
  "status": "active",
  "timeZone": "string"
}
```

Properties

Name	Description
accountHolderId	Required , string , The unique identifier of the account holder associated with the balance account.
defaultCurrencyCode	string , The default three-character ISO currency code of the balance account. The default value is EUR .
description	string , A human-readable description of the balance account, maximum 300 characters. You can use this parameter to distinguish between multiple balance accounts under an account holder. <pre>{ "maxLength": 300 }</pre>
id	Required , string , The unique identifier of the balance account.
reference	string , Your reference for the balance account, maximum 150 characters. <pre>{ "maxLength": 150 }</pre>
status	string , The status of the balance account, set to active by default. <pre>{ "enum": ["active", "closed", "inactive", "suspended"] }</pre>
timeZone	string , The time zone of the balance account. For example, Europe/Amsterdam . Defaults to the time zone of the account holder if no time zone is set. For possible values, see the list of time zone codes .

BalanceAccountInfo

Type: object

Example:

```
{
  "accountHolderId": "string",
  "defaultCurrencyCode": "string",
  "description": "string",
  "reference": "string",
}
```

```
"timeZone": "string"
}
```

Properties

Name	Description
accountHolderId	Required , string , The unique identifier of the account holder associated with the balance account.
defaultCurrencyCode	string , The default three-character ISO currency code of the balance account. The default value is EUR .
description	string , A human-readable description of the balance account, maximum 300 characters. You can use this parameter to distinguish between multiple balance accounts under an account holder. <pre>{ "maxLength": 300 }</pre>
reference	string , Your reference for the balance account, maximum 150 characters. <pre>{ "maxLength": 150 }</pre>
timeZone	string , The time zone of the balance account. For example, Europe/Amsterdam . Defaults to the time zone of the account holder if no time zone is set. For possible values, see the list of time zone codes .

BalanceAccountUpdateRequest

Type: object

Example:

```
{
  "accountHolderId": "string",
  "defaultCurrencyCode": "string",
  "description": "string",
  "reference": "string",
  "status": "active",
  "timeZone": "string"
}
```

Properties

Name	Description
accountHolderId	string , The unique identifier of the account holder associated with the balance account.
defaultCurrencyCode	string , The default currency code of this balance account, in three-character ISO currency code format. The default value is EUR .
description	string , A human-readable description of the balance account, maximum 300 characters. You can use this parameter to distinguish between multiple balance accounts under an account holder. <pre>{ "maxLength": 300 }</pre>
reference	string , Your reference to the balance account, maximum 150 characters. <pre>{ "maxLength": 150 }</pre>
status	string , The status of the balance account. Payment instruments linked to the balance account can only be used if the balance account status is active . Possible values: active , inactive , closed , suspended . <pre>{ "enum": ["active", "closed", "inactive", "suspended"] }</pre>
timeZone	string , The time zone of the balance account. For example, Europe/Amsterdam . Defaults to the time zone of the account holder if no time zone is set. For possible values, see the list of time zone codes .

BalancePlatform

Type: object

Example:

```
{
  "description": "string",
  "id": "string",
  "status": "string"
}
```

Properties

Name	Description
------	-------------

description	string , Your description of the balance platform, maximum 300 characters. <pre>{ "maxLength": 300 }</pre>
id	Required , string , The unique identifier of the balance platform.
status	string , The status of the balance platform. Possible values: Active , Inactive , Closed , Suspended .

BalanceSweepConfigurationsResponse

Type: object

Properties

Name	Description
hasNext	Required , boolean , Indicates whether there are more items on the next page.
hasPrevious	Required , boolean , Indicates whether there are more items on the previous page.
sweeps	Required , array , List of sweeps associated with the balance account. See referenced schema SweepConfigurationV2

BankAccountIdentificationValidationRequest

Type: object

Properties

Name	Description
accountIdentification	Required , undefined , Bank account identification. <pre>{ "oneOf": [{ "\$ref": "#/components/schemas/AULocalAccountIdentification" }, { "\$ref": "#/components/schemas/CALocalAccountIdentification" }, { "\$ref": "#/components/schemas/CZLocalAccountIdentification" }, { "\$ref": "#/components/schemas/HULocalAccountIdentification" }, { "\$ref": "#/components/schemas/IbanAccountIdentification" }, { "\$ref": "#/components/schemas/NOLocalAccountIdentification" }, { "\$ref": "#/components/schemas/NumberAndBicAccountIdentification" }, { "\$ref": "#/components/schemas/PLLocalAccountIdentification" }, { "\$ref": "#/components/schemas/SELocalAccountIdentification" }, { "\$ref": "#/components/schemas/SGLocalAccountIdentification" }, { "\$ref": "#/components/schemas/UKLocalAccountIdentification" }, { "\$ref": "#/components/schemas/USLocalAccountIdentification" }] }</pre>

BrandVariantsRestriction

Type: object

Example:

<pre>{ "operation": "string", "value": ["string"] }</pre>

Properties

Name	Description
operation	Required , string , Defines how the condition must be evaluated.
value	array , List of card brand variants. Possible values: - mc, mccredit, mccommercialcredit_b2b, mcdebit, mcbusinessdebit, mcbusinessworlddebit, mcprepaid, mcmaestro - visa, visacredit, visadebit,

visaprepaid. You can specify a rule for a generic variant. For example, to create a rule for all Mastercard payment instruments, use **mc**. The rule is applied to all payment instruments under **mc**, such as **mcbusinessdebit** and **mcdebit**.
See referenced schema [Items of value](#)

BulkAddress

Type: object

Example:

```
{
  "city": "string",
  "company": "string",
  "country": "string",
  "email": "string",
  "houseNumberOrName": "string",
  "mobile": "string",
  "postalCode": "string",
  "stateOrProvince": "string",
  "street": "string"
}
```

Properties

Name	Description
city	string , The name of the city.
company	string , The name of the company.
country	Required , string , The two-character ISO-3166-1 alpha-2 country code. For example, US .
email	string , The email address.
houseNumberOrName	string , The house number or name.
mobile	string , The full telephone number.
postalCode	string , The postal code. Maximum length: * 5 digits for addresses in the US. * 10 characters for all other countries.
stateOrProvince	string , The two-letter ISO 3166-2 state or province code. Maximum length: 2 characters for addresses in the US.
street	string , The streetname of the house.

CALocalAccountIdentification

Type: object

Example:

```
{
  "accountNumber": "string",
  "accountType": "checking",
  "institutionNumber": "str",
  "transitNumber": "strin",
  "type": "caLocal"
}
```

Properties

Name	Description
accountNumber	Required , string , The 5- to 12-digit bank account number, without separators or whitespace. <pre>{ "maxLength": 12, "minLength": 5 }</pre>
accountType	string , The bank account type. Possible values: checking or savings . Defaults to checking . <pre>{ "default": "checking", "enum": ["checking", "savings"] }</pre>
institutionNumber	Required , string , The 3-digit institution number, without separators or whitespace. <pre>{ "maxLength": 3, "minLength": 3 }</pre>
transitNumber	Required , string , The 5-digit transit number, without separators or whitespace. <pre>{ "maxLength": 5, "minLength": 5 }</pre>
type	

Required, string , **caLocal**

```
{
  "default": "caLocal",
  "enum": [
    "caLocal"
  ]
}
```

CZLocalAccountIdentification

Type: object

Example:

```
{
  "accountNumber": "string",
  "bankCode": "stri",
  "type": "czLocal"
}
```

Properties

Name	Description
accountNumber	Required , string , The 2- to 16-digit bank account number (Číslo účtu) in the following format: - The optional prefix (předčísí). - The required second part (základní část) which must be at least two non-zero digits. Examples: - 19-123457 (with prefix) - 123457 (without prefix) - 000019-0000123457 (with prefix, normalized) - 000000-0000123457 (without prefix, normalized) <pre>{ "maxLength": 17, "minLength": 2 }</pre>
bankCode	Required , string , The 4-digit bank code (Kód banky), without separators or whitespace. <pre>{ "maxLength": 4, "minLength": 4 }</pre>
type	Required , string , czLocal <pre>{ "default": "czLocal", "enum": ["czLocal"] }</pre>

CapabilityProblem

Type: object

Example:

```
{}
```

CapitalBalance

Type: object

Example:

```
{
  "currency": "string",
  "fee": 0,
  "principal": 0,
  "total": 0
}
```

Properties

Name	Description
currency	Required , string , The three-character ISO currency code .
fee	Required , integer (format: int64), Fee amount.
principal	Required , integer (format: int64), Principal amount.
total	Required , integer (format: int64), Total amount. A sum of principal amount and fee amount.

CapitalGrantAccount

Type: object

Properties

Name	Description
balances	array , The balances of the grant account. See referenced schema CapitalBalance

fundingBalanceAccountId	string , The unique identifier of the balance account used to fund the grant.
id	string , The identifier of the grant account.
limits	array , The limits of the grant account. See referenced schema GrantLimit

Card

Type: object

Properties

Name	Description
authentication	See referenced schema Authentication
bin	string , The bank identification number (BIN) of the card number.
brand	Required , string , The brand of the physical or the virtual card. Possible values: visa , mc .
brandVariant	Required , string , The brand variant of the physical or the virtual card. >Contact your Adyen Implementation Manager to get the values that are relevant to your integration. Examples: visadebit , mcprepaid .
cardholderName	Required , string , The name of the cardholder. Maximum length: 26 characters. <pre>{ "maxLength": 26 }</pre>
configuration	See referenced schema CardConfiguration
cvc	string , The CVC2 value of the card. > The CVC2 is not sent by default. This is only returned in the POST response for single-use virtual cards.
deliveryContact	See referenced schema DeliveryContact <pre>{ "x-addedInVersion": "2" }</pre>
expiration	See referenced schema Expiry
formFactor	Required , string , The form factor of the card. Possible values: virtual , physical . <pre>{ "enum": ["physical", "unknown", "virtual"] }</pre>
lastFour	string , Last last four digits of the card number.
number	Required , string , The primary account number (PAN) of the card. > The PAN is masked by default and returned only for single-use virtual cards. <pre>{ "readOnly": true }</pre>

CardConfiguration

Type: object

Properties

Name	Description
activation	string , Overrides the activation label design ID defined in the <code>configurationProfileId</code> . The activation label is attached to the card and contains the activation instructions.
activationUrl	string , Your app's URL, if you want to activate cards through your app. For example, my-app://ref1236a7d . A QR code is created based on this URL, and is included in the carrier. Before you use this field, reach out to your Adyen contact to set up the QR code process. Maximum length: 255 characters. <pre>{ "maxLength": 255 }</pre>
bulkAddress	

	See referenced schema BulkAddress
cardImageId	string , The ID of the card image. This is the image that will be printed on the full front of the card.
carrier	string , Overrides the carrier design ID defined in the <code>configurationProfileId</code> . The carrier is the letter or packaging to which the card is attached.
carrierImageId	string , The ID of the carrier image. This is the image that will be printed on the letter to which the card is attached.
configurationProfileId	Required , string , The ID of the card configuration profile that contains the settings of the card. For example, the envelope and PIN mailer designs or the logistics company handling the shipment. All the settings in the profile are applied to the card, unless you provide other fields to override them. For example, send the <code>shipmentMethod</code> to override the logistics company defined in the card configuration profile.
currency	string , The three-letter ISO-4217 currency code of the card. For example, EUR .
envelope	string , Overrides the envelope design ID defined in the <code>configurationProfileId</code> .
insert	string , Overrides the insert design ID defined in the <code>configurationProfileId</code> . An insert is any additional material, such as marketing materials, that are shipped together with the card.
language	string , The two-letter ISO-639-1 language code of the card. For example, en .
logoImageId	string , The ID of the logo image. This is the image that will be printed on the partial front of the card, such as a logo on the upper right corner.
pinMailer	string , Overrides the PIN mailer design ID defined in the <code>configurationProfileId</code> . The PIN mailer is the letter on which the PIN is printed.
shipmentMethod	string , Overrides the logistics company defined in the <code>configurationProfileId</code> .

CardInfo

Type: object

Properties

Name	Description
authentication	See referenced schema Authentication
brand	Required , string , The brand of the physical or the virtual card. Possible values: visa , mc .
brandVariant	Required , string , The brand variant of the physical or the virtual card. >Contact your Adyen Implementation Manager to get the values that are relevant to your integration. Examples: visadebit , mcprepaid .
cardholderName	Required , string , The name of the cardholder. Maximum length: 26 characters. <pre>{ "maxLength": 26 }</pre>
configuration	See referenced schema CardConfiguration
deliveryContact	See referenced schema DeliveryContact <pre>{ "x-addedInVersion": "2" }</pre>
formFactor	Required , string , The form factor of the card. Possible values: virtual , physical . <pre>{ "enum": ["physical", "unknown", "virtual"] }</pre>

ContactDetails

Type: object

Properties

Name	Description
address	Required , See referenced schema Address

email	Required , string , The email address of the account holder.
phone	Required , See referenced schema Phone
webAddress	string , The URL of the account holder's website.

CountriesRestriction

Type: object

Example:

```
{
  "operation": "string",
  "value": [
    "string"
  ]
}
```

Properties

Name	Description
operation	Required , string , Defines how the condition must be evaluated.
value	array , List of two-character ISO 3166-1 alpha-2 country codes. See referenced schema Items of value

CronSweepSchedule

Type: object

Example:

```
{
  "cronExpression": "string",
  "type": "daily"
}
```

Properties

Name	Description
cronExpression	Required , string , A cron expression that is used to set the sweep schedule. The schedule uses the time zone of the balance account. For example, 30 17 * * MON schedules a sweep every Monday at 17:30. The expression must have five values separated by a single space in the following order: * Minute: 0-59 * Hour: 0-23 * Day of the month: 1-31 * Month: 1-12 or JAN-DEC * Day of the week: 0-7 (0 and 7 are Sunday) or MON-SUN . The following non-standard characters are supported: *, L, #, W and /. See crontab.guru for more examples.
type	string , The schedule type. Possible values: * cron : push out funds based on a cron expression. * daily : push out funds daily at 07:00 AM CET. * weekly : push out funds every Monday at 07:00 AM CET. * monthly : push out funds every first of the month at 07:00 AM CET. * balance : pull in funds instantly if the balance is less than or equal to the triggerAmount. You can only use this for sweeps of type pull and when the source is a merchantAccount OR transferInstrument.

```
{
  "enum": [
    "daily",
    "weekly",
    "monthly",
    "balance",
    "cron"
  ]
}
```

DayOfWeekRestriction

Type: object

Example:

```
{
  "operation": "string",
  "value": [
    "friday"
  ]
}
```

Properties

Name	Description
operation	Required , string , Defines how the condition must be evaluated.
value	array , List of days of the week. Possible values: monday , tuesday , wednesday , thursday , friday , saturday , sunday . See referenced schema Items of value

DeliveryContact

Type: object

Properties

Name	Description
address	Required, See referenced schema Address-2
email	string , The email address of the contact.
fullPhoneNumber	string , The full phone number of the contact provided as a single string. It will be handled as a landline phone. Examples: "0031 6 11 22 33 44", "+316/1122-3344", "(0031) 611223344"
name	Required, See referenced schema Name
phoneNumber	 See referenced schema PhoneNumber
webAddress	string , The URL of the contact's website.

DifferentCurrenciesRestriction

Type: object

Example:

```
{
  "operation": "string",
  "value": true
}
```

Properties

Name	Description
operation	Required, string , Defines how the condition must be evaluated.
value	boolean , Checks the currency of the payment against the currency of the payment instrument. Possible values: - true : The currency of the payment is different from the currency of the payment instrument. - false : The currencies are the same.

Duration

Type: object

Example:

```
{
  "unit": "days",
  "value": 0
}
```

Properties

Name	Description
unit	string , The unit of time. You can only use minutes and hours if the <code>interval.type</code> is sliding . Possible values: minutes , hours , days , weeks , or months <pre>{ "enum": ["days", "hours", "minutes", "months", "weeks"] }</pre>
value	integer (format: int32), The length of time by the unit. For example, 5 days. The maximum duration is 90 days or an equivalent in other units. For example, 3 months.

EntryModesRestriction

Type: object

Example:

```
{
  "operation": "string",
  "value": [
    "barcode"
  ]
}
```

Properties

Name	Description
------	-------------

operation	Required , string , Defines how the condition must be evaluated.
value	array , List of point-of-sale entry modes. Possible values: barcode , chip , cof , contactless , magstripe , manual , ocr , server . See referenced schema Items of value

Expiry

Type: object
Example:
<pre>{ "month": "string", "year": "string" }</pre>

Properties

Name	Description
month	string , The month in which the card will expire.
year	string , The year in which the card will expire.

Fee

Type: object

Properties

Name	Description
amount	Required, See referenced schema Amount

GrantLimit

Type: object

Properties

Name	Description
amount	See referenced schema Amount

GrantOffer

Type: object

Properties	
Name	Description
accountHolderId	Required , string , The identifier of the account holder to which the grant is offered.
amount	 See referenced schema Amount
contractType	string , The contract type of the grant offer. Possible value: cashAdvance , loan . <pre>{ "enum": ["cashAdvance", "loan"] }</pre>
expiresAt	 See referenced schema LocalDateTime
fee	 See referenced schema Fee
id	string , The unique identifier of the grant offer.
repayment	 See referenced schema Repayment
startsAt	 See referenced schema LocalDateTime

GrantOffers

Type: object

Properties

Name	Description
grantOffers	Required , array , A list of available grant offers. See referenced schema GrantOffer

HULocalAccountIdentification

Type: object

Example:

```
{
  "accountNumber": "stringstringstringstring",
  "type": "huLocal"
}
```

Properties

Name	Description
accountNumber	Required , string , The 24-digit bank account number, without separators or whitespace. <pre>{ "maxLength": 24, "minLength": 24 }</pre>
type	Required , string , huLocal <pre>{ "default": "huLocal", "enum": ["huLocal"] }</pre>

IbanAccountIdentification

Type: object

Example:

```
{
  "iban": "string",
  "type": "iban"
}
```

Properties

Name	Description
iban	Required , string , The international bank account number as defined in the ISO-13616 standard.
type	Required , string , iban <pre>{ "default": "iban", "enum": ["iban"] }</pre>

InternationalTransactionRestriction

Type: object

Example:

```
{
  "operation": "string",
  "value": true
}
```

Properties

Name	Description
operation	Required , string , Defines how the condition must be evaluated.
value	boolean , Boolean indicating whether transaction is an international transaction. Possible values: - true : The transaction is an international transaction. - false : The transaction is a domestic transaction.

InvalidField

Type: object

Example:

```
{
  "message": "string",
  "name": "string",
  "value": "string"
}
```

Properties

Name	Description
message	Required , string , Description of the validation error.
name	Required , string , The field that has an invalid value.
value	Required , string , The invalid value.

JSONObject

Type: object

Properties

Name	Description
paths	array See referenced schema JSONPath
rootPath	See referenced schema JSONPath

JSONPath

Type: object

Example:

```
{
  "content": [
    "string"
  ]
}
```

Properties

Name	Description
content	array See referenced schema Items of content

LocalDateTime

Type: object

Example:

```
{}
```

MatchingTransactionsRestriction

Type: object

Example:

```
{
  "operation": "string",
  "value": 0
}
```

Properties

Name	Description
operation	Required , string , Defines how the condition must be evaluated.
value	integer (format: int32), The number of transactions.

MccsRestriction

Type: object

Example:

```
{
  "operation": "string",
  "value": [
    "string"
  ]
}
```

Properties

Name	Description
operation	

Required, string , Defines how the condition must be evaluated.

value
array , List of merchant category codes (MCCs).
See referenced schema [Items of value](#)

MerchantAcquirerPair

Type: object

Example:

```
{
  "acquirerId": "string",
  "merchantId": "string"
}
```

Properties

Name	Description
acquirerId	string , The acquirer ID.
merchantId	string , The merchant identification number (MID).

MerchantNamesRestriction

Type: object

Properties

Name	Description
operation	Required , string , Defines how the condition must be evaluated.
value	array See referenced schema StringMatch

MerchantsRestriction

Type: object

Properties

Name	Description
operation	Required , string , Defines how the condition must be evaluated.
value	array , List of merchant ID and acquirer ID pairs. See referenced schema MerchantAcquirerPair

NOLocalAccountIdentification

Type: object

Example:

```
{
  "accountNumber": "stringstrin",
  "type": "noLocal"
}
```

Properties

Name	Description
accountNumber	Required , string , The 11-digit bank account number, without separators or whitespace. <pre>{ "maxLength": 11, "minLength": 11 }</pre>
type	Required , string , noLocal <pre>{ "default": "noLocal", "enum": ["noLocal"] }</pre>

Name

Type: object

Example:

```
{
  "firstName": "string",
  "lastName": "string"
}
```

Properties

Name	Description
firstName	Required , string , The first name.
lastName	Required , string , The last name.

NumberAndBicAccountIdentification

Type: object

Properties

Name	Description
accountNumber	Required , string , The bank account number, without separators or whitespace. The length and format depends on the bank or country. <pre>{ "maxLength": 34 }</pre>
additionalBankIdentification	See referenced schema AdditionalBankIdentification
bic	Required , string , The bank's 8- or 11-character BIC or SWIFT code. <pre>{ "maxLength": 11, "minLength": 8 }</pre>
type	Required , string , numberAndBic <pre>{ "default": "numberAndBic", "enum": ["numberAndBic"] }</pre>

PLLocalAccountIdentification

Type: object

Example:

```
{
  "accountNumber": "stringstringstringstringst",
  "type": "plLocal"
}
```

Properties

Name	Description
accountNumber	Required , string , The 26-digit bank account number (Numer rachunku), without separators or whitespace. <pre>{ "maxLength": 26, "minLength": 26 }</pre>
type	Required , string , plLocal <pre>{ "default": "plLocal", "enum": ["plLocal"] }</pre>

PaginatedAccountHoldersResponse

Type: object

Properties

Name	Description
accountHolders	Required , array , List of account holders. See referenced schema AccountHolder
hasNext	Required , boolean , Indicates whether there are more items on the next page.
hasPrevious	Required , boolean , Indicates whether there are more items on the previous page.

PaginatedBalanceAccountsResponse

Type: object

Properties

Name	Description
balanceAccounts	Required , array , List of balance accounts. See referenced schema BalanceAccountBase
hasNext	Required , boolean , Indicates whether there are more items on the next page.
hasPrevious	Required , boolean , Indicates whether there are more items on the previous page.

PaginatedPaymentInstrumentsResponse

Type: object

Properties

Name	Description
hasNext	Required , boolean , Indicates whether there are more items on the next page.
hasPrevious	Required , boolean , Indicates whether there are more items on the previous page.
paymentInstruments	Required , array , List of payment instruments associated with the balance account. See referenced schema PaymentInstrument

PaymentInstrument

Type: object

Properties

Name	Description
balanceAccountId	Required , string , The unique identifier of the balance account associated with the payment instrument.
bankAccount	undefined , Contains the business account details. Returned when you create a payment instrument with type bankAccount .

```
{
  "oneOf": [
    {
      "$ref": "#/components/schemas/IbanAccountIdentification"
    },
    {
      "$ref": "#/components/schemas/USLocalAccountIdentification"
    }
  ]
}
```

card

See referenced schema [Card](#)

description

string , Your description for the payment instrument, maximum 300 characters.

```
{
  "maxLength": 300
}
```

id

Required, string , The unique identifier of the payment instrument.

issuingCountryCode

Required, string , The two-character [ISO 3166-1 alpha-2](#) country code where the payment instrument is issued. For example, **NL** or **US**.

paymentInstrumentGroupId string , The unique identifier of the [payment instrument group](#) to which the payment instrument belongs.

reference

string , Your reference for the payment instrument, maximum 150 characters.

```
{
  "maxLength": 150
}
```

status

string , The status of the payment instrument. If a status is not specified when creating a payment instrument, it is set to **active** by default. However, there can be exceptions for cards based on the `card.formFactor` and the `issuingCountryCode`. For example, when issuing physical cards in the US, the default status is **inactive**. Possible values: * **active**: The payment instrument is active and can be used to make payments. * **inactive**: The payment instrument is inactive and cannot be used to make payments. * **suspended**: The payment instrument is suspended, either because it was stolen or lost. * **closed**: The payment instrument is permanently closed. This action cannot be undone.

```
{
  "enum": [
    "active",
    "closed",
    "inactive",
    "suspended"
  ],
  "x-enum": [
    {
      "description": "The payment instrument is active and can be used to make payments.",
      "value": "active"
    },
    {
      "description": "The payment instrument is inactive and cannot be used to make payments.",

```

```
    "value": "inactive"
  },
  {
    "description": "The payment instrument is suspended. Either because it was stolen or lost.",
    "value": "suspended"
  },
  {
    "description": "The payment instrument is permanently closed. This action cannot be undone.",
    "value": "closed"
  }
]
```

statusReason string , The reason for updating the status of the payment instrument. Possible values: **lost**, **stolen**, **damaged**, **suspectedFraud**, **expired**, **endOfLife**, **accountClosure**, **other**. If the reason is **other**, you must also send the **statusComment** parameter describing the status change.

```
{
  "enum": [
    "accountClosure",
    "damaged",
    "endOfLife",
    "expired",
    "lost",
    "other",
    "stolen",
    "suspectedFraud"
  ],
  "x-addedInVersion": "2"
}
```

type **Required**, string , Type of payment instrument. Possible value: **card**, **bankAccount**.

```
{
  "enum": [
    "bankAccount",
    "card"
  ]
}
```

PaymentInstrumentGroup

Type: object

Example:

```
{
  "balancePlatform": "string",
  "description": "string",
  "id": "string",
  "properties": {
    "property1": "string",
    "property2": "string"
  },
  "reference": "string",
  "txVariant": "string"
}
```

Properties

Name	Description
balancePlatform	Required , string , The unique identifier of the balance platform to which the payment instrument group belongs.
description	string , Your description for the payment instrument group, maximum 300 characters. <pre>{ "maxLength": 300 }</pre>
id	string , The unique identifier of the payment instrument group.
properties	object , Properties of the payment instrument group. <pre>{ "additionalProperties": { "type": "string" } }</pre>
reference	string , Your reference for the payment instrument group, maximum 150 characters. <pre>{ "maxLength": 150 }</pre>
txVariant	Required , string , The tx variant of the payment instrument group.

PaymentInstrumentGroupInfo

Type: object

Example:

```
{
  "balancePlatform": "string",
  "description": "string",
  "properties": {
```

```

    "property1": "string",
    "property2": "string"
  },
  "reference": "string",
  "txVariant": "string"
}

```

Properties

Name	Description
balancePlatform	Required , string , The unique identifier of the balance platform to which the payment instrument group belongs.
description	string , Your description for the payment instrument group, maximum 300 characters. <pre> { "maxLength": 300 } </pre>
properties	object , Properties of the payment instrument group. <pre> { "additionalProperties": { "type": "string" } } </pre>
reference	string , Your reference for the payment instrument group, maximum 150 characters. <pre> { "maxLength": 150 } </pre>
txVariant	Required , string , The tx variant of the payment instrument group.

PaymentInstrumentInfo

Type: object

Properties

Name	Description
balanceAccountId	Required , string , The unique identifier of the balance account associated with the payment instrument.
card	See referenced schema CardInfo
description	string , Your description for the payment instrument, maximum 300 characters. <pre> { "maxLength": 300 } </pre>
issuingCountryCode	Required , string , The two-character ISO 3166-1 alpha-2 country code where the payment instrument is issued. For example, NL or US .
paymentInstrumentGroupId	string , The unique identifier of the payment instrument group to which the payment instrument belongs.
reference	string , Your reference for the payment instrument, maximum 150 characters. <pre> { "maxLength": 150 } </pre>
status	string , The status of the payment instrument. If a status is not specified when creating a payment instrument, it is set to active by default. However, there can be exceptions for cards based on the <code>card.formFactor</code> and the <code>issuingCountryCode</code> . For example, when issuing physical cards in the US, the default status is inactive . Possible values: * active : The payment instrument is active and can be used to make payments. * inactive : The payment instrument is inactive and cannot be used to make payments. * suspended : The payment instrument is suspended, either because it was stolen or lost. * closed : The payment instrument is permanently closed. This action cannot be undone. <pre> { "enum": ["active", "closed", "inactive", "suspended"], "x-enum": [{ "description": "The payment instrument is active and can be used to make payments.", "value": "active" }, { "description": "The payment instrument is inactive and cannot be used to make payments.", "value": "inactive" }, { "description": "The payment instrument is suspended. Either because it was stolen or lost.", "value": "suspended" }, { </pre>

```

    "description": "The payment instrument is permanently closed. This action cannot be undone.",
    "value": "closed"
  }
}
}

```

statusReason

string , The reason for updating the status of the payment instrument. Possible values: **lost**, **stolen**, **damaged**, **suspectedFraud**, **expired**, **endOfLife**, **accountClosure**, **other**. If the reason is **other**, you must also send the statusComment parameter describing the status change.

```

{
  "enum": [
    "accountClosure",
    "damaged",
    "endOfLife",
    "expired",
    "lost",
    "other",
    "stolen",
    "suspectedFraud"
  ],
  "x-addedInVersion": "2"
}

```

type

Required, string , Type of payment instrument. Possible value: **card**, **bankAccount**.

```

{
  "enum": [
    "bankAccount",
    "card"
  ]
}

```

PaymentInstrumentRevealInfo

Type: object

Properties

Name	Description
cvc	Required , string , The CVC2 value of the card.
expiration	Required , See referenced schema Expiry .
pan	Required , string , The primary account number (PAN) of the card.

PaymentInstrumentUpdateRequest

Type: object

Properties

Name	Description
balanceAccountId	string , The unique identifier of the balance account associated with this payment instrument. >You can only change the balance account ID if the payment instrument has inactive status.
card	 See referenced schema CardInfo
status	string , The status of the payment instrument. If a status is not specified when creating a payment instrument, it is set to active by default. However, there can be exceptions for cards based on the card.formFactor and the issuingCountryCode. For example, when issuing physical cards in the US, the default status is inactive . Possible values: * active : The payment instrument is active and can be used to make payments. * inactive : The payment instrument is inactive and cannot be used to make payments. * suspended : The payment instrument is suspended, either because it was stolen or lost. * closed : The payment instrument is permanently closed. This action cannot be undone.

```

{
  "enum": [
    "active",
    "closed",
    "inactive",
    "suspended"
  ],
  "x-enum": [
    {
      "description": "The payment instrument is active and can be used to make payments.",
      "value": "active"
    },
    {
      "description": "The payment instrument is inactive and cannot be used to make payments.",
      "value": "inactive"
    },
    {
      "description": "The payment instrument is suspended. Either because it was stolen or lost.",
      "value": "suspended"
    },
    {
      "description": "The payment instrument is permanently closed. This action cannot be undone.",
      "value": "closed"
    }
  ]
}

```

```
]
}
```

statusComment

string , Comment for the status of the payment instrument. Required if **statusReason** is **other**.

statusReason

string , The reason for updating the status of the payment instrument. Possible values: **lost**, **stolen**, **damaged**, **suspectedFraud**, **expired**, **endOfLife**, **accountClosure**, **other**. If the reason is **other**, you must also send the **statusComment** parameter describing the status change.

```
{
  "enum": [
    "accountClosure",
    "damaged",
    "endOfLife",
    "expired",
    "lost",
    "other",
    "stolen",
    "suspectedFraud"
  ],
  "x-addedInVersion": "2"
}
```

Phone

Type: object

Example:

```
{
  "number": "string",
  "type": "landline"
}
```

Properties

Name	Description
number	Required , string , The full phone number provided as a single string. For example, "0031 6 11 22 33 44" , " +316/1122-3344" , or "(0031) 611223344" .
type	Required , string , Type of phone number. Possible values: Landline , Mobile . <pre>{ "enum": ["landline", "mobile"] }</pre>

PhoneNumber

Type: object

Example:

```
{
  "phoneCountryCode": "string",
  "phoneNumber": "string",
  "phoneType": "Fax"
}
```

Properties

Name	Description
phoneCountryCode	string , The two-character ISO-3166-1 alpha-2 country code of the phone number. For example, US or NL .
phoneNumber	string , The phone number. The inclusion of the phone number country code is not necessary.
phoneType	string , The type of the phone number. Possible values: Landline , Mobile , SIP , Fax . <pre>{ "enum": ["Fax", "Landline", "Mobile", "SIP"] }</pre>

ProcessingTypesRestriction

Type: object

Example:

```
{
  "operation": "string",
  "value": [
    "atmWithdraw"
  ]
}
```

Properties

Name	Description
operation	Required , string , Defines how the condition must be evaluated.
value	array , List of processing types. Possible values: atmWithdraw , balanceInquiry , ecommerce , moto , pos , recurring , token . See referenced schema Items of value

Repayment

Type: object

Properties

Name	Description
basisPoints	Required , integer (format: int32), The repayment that is deducted daily from incoming net volume, in basis points .
term	See referenced schema RepaymentTerm
threshold	See referenced schema ThresholdRepayment

RepaymentTerm

Type: object

Example:

```
{
  "estimatedDays": 0,
  "maximumDays": 0
}
```

Properties

Name	Description
estimatedDays	Required , integer (format: int32), The estimated term for repaying the grant, in days.
maximumDays	integer (format: int32), The maximum term for repaying the grant, in days. Only applies when contractType is loan .

RestServiceError

Type: object

Properties

Name	Description
detail	Required , string , A human-readable explanation specific to this occurrence of the problem.
errorCode	Required , string , A code that identifies the problem type.
instance	string , A unique URI that identifies the specific occurrence of the problem.
invalidFields	array , Detailed explanation of each validation error, when applicable. See referenced schema InvalidField
requestId	string , A unique reference for the request, essentially the same as pspReference.
response	See referenced schema JSONObject
status	Required , integer (format: int32), The HTTP status code.
title	Required , string , A short, human-readable summary of the problem type.
type	Required , string , A URI that identifies the problem type, pointing to human-readable documentation on this problem type.

SELocalAccountIdentification

Type: object

Example:

```
{
  "accountNumber": "strings",
  "clearingNumber": "strin",
  "type": "seLocal"
}
```

Properties

Name	Description
------	-------------

accountNumber	Required , string , The 7- to 10-digit bank account number (Bankkontonummer), without the clearing number, separators, or whitespace. <pre>{ "maxLength": 10, "minLength": 7 }</pre>
clearingNumber	Required , string , The 4- to 5-digit clearing number (Clearingnummer), without separators or whitespace. <pre>{ "maxLength": 5, "minLength": 4 }</pre>
type	Required , string , seLocal <pre>{ "default": "seLocal", "enum": ["seLocal"] }</pre>

SGLocalAccountIdentification

Type: object

Example:

<pre>{ "accountNumber": "string", "bic": "stringst", "type": "sgLocal" }</pre>
--

Properties

Name	Description
accountNumber	Required , string , The 4- to 19-digit bank account number, without separators or whitespace. <pre>{ "maxLength": 19, "minLength": 4 }</pre>
bic	Required , string , The bank's 8- or 11-character BIC or SWIFT code. <pre>{ "maxLength": 11, "minLength": 8 }</pre>
type	string , sgLocal <pre>{ "default": "sgLocal", "enum": ["sgLocal"] }</pre>

StringMatch

Type: object

Example:

<pre>{ "operation": "contains", "value": "string" }</pre>

Properties

Name	Description
operation	string , The type of string matching operation. Possible values: startsWith , endsWith , isEqualTo , contains , <pre>{ "enum": ["contains", "endsWith", "isEqualTo", "startsWith"] }</pre>
value	string , The string to be matched.

SweepConfigurationV2

Type: object

Properties

Name	Description
category	string , The type of transfer that results from the sweep. Possible values: - bank: Sweep to a transfer instrument. - internal: Transfer to another balance account within your platform. Required when setting priorities. <pre>{ "enum": ["bank", "internal", "platformPayment"], "x-addedInVersion": "2" }</pre>
counterparty	Required, See referenced schema SweepCounterparty.
currency	Required, string , The three-character ISO currency code in uppercase. For example, EUR. The sweep currency must match any of the balances currencies.
description	string , The message that will be used in the sweep transfer's description body with a maximum length of 140 characters. If the message is longer after replacing placeholders, the message will be cut off at 140 characters.
id	Required, string , The unique identifier of the sweep. <pre>{ "readOnly": true }</pre>
priorities	array , The list of priorities for the bank transfer. This sets the speed at which the transfer is sent and the fees that you have to pay. You can provide multiple priorities. Adyen will try to pay out using the priority listed first, and if that's not possible, it moves on to the next option in the order of provided priorities. Possible values: * regular: For normal, low-value transactions. * fast: Faster way to transfer funds but has higher fees. Recommended for high-priority, low-value transactions. * wire: Fastest way to transfer funds but has the highest fees. Recommended for high-priority, high-value transactions. * instant: Instant way to transfer funds in SEPA countries. * crossBorder: High-value transfer to a recipient in a different country. * internal: Transfer to an Adyen-issued business bank account (by bank account number/IBAN). Set category to bank. For more details, see optional priorities setup. <pre>{ "items": { "enum": ["crossBorder", "directDebit", "fast", "instant", "internal", "regular", "wire"], "type": "string" }, "x-addedInVersion": "2" }</pre>
reason	See referenced schema Items of priorities string , The reason for disabling the sweep. <pre>{ "enum": ["amountLimitExceeded", "approved", "counterpartyAccountBlocked", "counterpartyAccountClosed", "counterpartyAccountNotFound", "counterpartyAddressRequired", "counterpartyBankTimedOut", "counterpartyBankUnavailable", "error", "notEnoughBalance", "refusedByCounterpartyBank", "routeNotFound", "unknown"], "readOnly": true }</pre>
schedule	Required, undefined , The schedule when the triggerAmount is evaluated. If the balance meets the threshold, funds are pushed out of or pulled in to the balance account. <pre>{ "oneOf": [{ "\$ref": "#/components/schemas/CronSweepSchedule" }, { "\$ref": "#/components/schemas/SweepSchedule" }] }</pre>
status	string , The status of the sweep. If not provided, by default, this is set to active. Possible values: * active: the sweep is enabled and funds will be pulled in or pushed out based on the defined configuration. * inactive: the

sweep is disabled and cannot be triggered.

```
{
  "enum": [
    "active",
    "inactive"
  ],
  "x-enum": [
    {
      "description": "The sweep is enabled and funds will be pulled in or pushed out based on the defined configuration",
      "value": "active"
    },
    {
      "description": "The sweep is disabled and cannot be triggered.",
      "value": "inactive"
    }
  ]
}
```

sweepAmount

See referenced schema [Amount](#)

targetAmount

See referenced schema [Amount](#)

triggerAmount

See referenced schema [Amount](#)

type

string , The direction of sweep, whether pushing out or pulling in funds to the balance account. If not provided, by default, this is set to **push**. Possible values: * **push**: *push out funds* to a destination balance account or transfer instrument. * **pull**: *pull in funds* from a source merchant account, transfer instrument, or balance account.

```
{
  "default": "push",
  "enum": [
    "pull",
    "push"
  ]
}
```

SweepCounterparty

Type: object

Example:

```
{
  "balanceAccountId": "string",
  "merchantAccount": "string",
  "transferInstrumentId": "string"
}
```

Properties

Name	Description
balanceAccountId	string , The unique identifier of the destination or source balance account . You can only use this for periodic sweep schedules such as <code>schedule.type</code> daily or monthly .
merchantAccount	string , The merchant account that will be the source of funds, if you are processing payments with Adyen. You can only use this with sweeps of type pull and <code>schedule.type</code> balance .
transferInstrumentId	string , The unique identifier of the destination or source transfer instrument . You can also use this in combination with a <code>merchantAccount</code> and a type pull to start a direct debit request from the source transfer instrument. To use this feature, reach out to your Adyen contact.

SweepSchedule

Type: object

Example:

```
{
  "type": "daily"
}
```

Properties

Name	Description
type	string , The schedule type. Possible values: * cron : push out funds based on a cron expression. * daily : push out funds daily at 07:00 AM CET. * weekly : push out funds every Monday at 07:00 AM CET. * monthly : push out funds every first of the month at 07:00 AM CET. * balance : pull in funds instantly if the balance is less than or equal to the <code>triggerAmount</code> . You can only use this for sweeps of type pull and when the source is a <code>merchantAccount</code> or <code>transferInstrument</code> .

```
{
  "enum": [
    "daily",
    "weekly",
    "monthly",
    "balance",

```

```
"cron"
  ]
}
```

ThresholdRepayment

Type: object

Properties

Name	Description
amount	Required, See referenced schema Amount

TimeOfDay

Type: object

Example:

```
{
  "endTime": "string",
  "startTime": "string"
}
```

Properties

Name	Description
endTime	string , The end time in a time-only ISO-8601 extended offset format. For example: 08:00:00+02:00, 22:30:00-03:00 .
startTime	string , The start time in a time-only ISO-8601 extended offset format. For example: 08:00:00+02:00, 22:30:00-03:00 .

TimeOfDayRestriction

Type: object

Properties

Name	Description
operation	Required, string , Defines how the condition must be evaluated.
value	 See referenced schema TimeOfDay

TotalAmountRestriction

Type: object

Properties

Name	Description
operation	Required, string , Defines how the condition must be evaluated.
value	 See referenced schema Amount

TransactionRule

Type: object

Properties

Name	Description
aggregationLevel	string , The level at which data must be accumulated, used in rules with type velocity or maxUsage . The level must be the same or lower in hierarchy than the entityKey. If not provided, by default, the rule will accumulate data at the paymentInstrument level. Possible values: paymentInstrument , paymentInstrumentGroup , balanceAccount , accountHolder , balancePlatform . <pre>{ "x-addedInVersion": "2" }</pre>
description	Required, string , Your description for the transaction rule, maximum 300 characters. <pre>{ "maxLength": 300 }</pre>
endDate	

string , The date when the rule will stop being evaluated, in ISO 8601 extended offset date-time format. For example, **2020-12-18T10:15:30+01:00**. If not provided, the rule will be evaluated until the rule status is set to **inactive**.

entityKey

Required,

See referenced schema [TransactionRuleEntityKey](#)

```
{
  "x-addedInVersion": "2"
}
```

id

string , The unique identifier of the transaction rule.

interval

Required,

See referenced schema [TransactionRuleInterval](#)

outcomeType

string , The [outcome](#) that will be applied when a transaction meets the conditions of the rule. If not provided, by default, this is set to **hardBlock**. Possible values: * **hardBlock**: the transaction is declined. * **scoreBased**: the transaction is assigned the `score` you specified. Adyen calculates the total score and if it exceeds 100, the transaction is declined.

```
{
  "enum": [
    "hardBlock",
    "scoreBased"
  ],
  "x-addedInVersion": "2"
}
```

reference

Required, string , Your reference for the transaction rule, maximum 150 characters.

```
{
  "maxLength": 150
}
```

requestType

string , Indicates the type of request to which the rule applies. Possible values: **authorization**, **authentication**, **tokenization**.

```
{
  "enum": [
    "authentication",
    "authorization",
    "tokenization"
  ],
  "x-addedInVersion": "2"
}
```

ruleRestrictions

Required,

See referenced schema [TransactionRuleRestrictions](#)

```
{
  "x-addedInVersion": "2"
}
```

score

integer (format: int32), A positive or negative score applied to the transaction if it meets the conditions of the rule. Required when `outcomeType` is **scoreBased**. The value must be between **-100** and **100**.

```
{
  "format": "int32",
  "x-addedInVersion": "2"
}
```

startDate

string , The date when the rule will start to be evaluated, in ISO 8601 extended offset date-time format. For example, **2020-12-18T10:15:30+01:00**. If not provided when creating a transaction rule, the `startDate` is set to the date when the rule status is set to **active**.

status

string , The status of the transaction rule. If you provide a `startDate` in the request, the rule is automatically created with an **active** status. Possible values: **active**, **inactive**.

```
{
  "enum": [
    "active",
    "inactive"
  ]
}
```

type

Required, string , The [type of rule](#), which defines if a rule blocks transactions based on individual characteristics or accumulates data. Possible values: * **blockList**: decline a transaction when the conditions are met. * **maxUsage**: add the amount or number of transactions for the lifetime of a payment instrument, and then decline a transaction when the specified limits are met. * **velocity**: add the amount or number of transactions based on a specified time interval, and then decline a transaction when the specified limits are met.

```
{
  "enum": [
    "allowList",
    "blockList",
    "maxUsage",
    "velocity"
  ],
  "x-enum": [

```

```
{
  "description": "The rule provides categories (such as country and MCC) where payments must be allowed.",
  "value": "allowList"
},
{
  "description": "The rule provides categories (such as country and MCC) where payments must be blocked.",
  "value": "blockList"
},
{
  "description": "The rule sets limits for the maximum amount or maximum number of transactions for a given time interval.",
  "value": "velocity"
},
{
  "description": "The rule sets limits for the maximum amount or maximum number of transactions for the lifetime of the payment instrument.",
  "value": "maxUsage"
}
]
```

TransactionRuleEntityKey

Type: object

Example:

```
{
  "entityReference": "string",
  "entityType": "string"
}
```

Properties

Name	Description
entityReference	string , The unique identifier of the resource.
entityType	string , The type of resource. Possible values: balancePlatform , paymentInstrumentGroup , accountHolder , balanceAccount , or paymentInstrument .

TransactionRuleInfo

Type: object

Properties

Name	Description
aggregationLevel	string , The level at which data must be accumulated, used in rules with type velocity or maxUsage . The level must be the same or lower in hierarchy than the entityKey . If not provided, by default, the rule will accumulate data at the paymentInstrument level. Possible values: paymentInstrument , paymentInstrumentGroup , balanceAccount , accountHolder , balancePlatform . <pre>{ "x-addedInVersion": "2" }</pre>
description	Required , string , Your description for the transaction rule, maximum 300 characters. <pre>{ "maxLength": 300 }</pre>
endDate	string , The date when the rule will stop being evaluated, in ISO 8601 extended offset date-time format. For example, 2020-12-18T10:15:30+01:00 . If not provided, the rule will be evaluated until the rule status is set to inactive .
entityKey	Required , See referenced schema TransactionRuleEntityKey . <pre>{ "x-addedInVersion": "2" }</pre>
interval	Required , See referenced schema TransactionRuleInterval
outcomeType	string , The outcome that will be applied when a transaction meets the conditions of the rule. If not provided, by default, this is set to hardBlock . Possible values: * hardBlock : the transaction is declined. * scoreBased : the transaction is assigned the score you specified. Adyen calculates the total score and if it exceeds 100, the transaction is declined. <pre>{ "enum": ["hardBlock", "scoreBased"], "x-addedInVersion": "2" }</pre>
reference	Required , string , Your reference for the transaction rule, maximum 150 characters.

```
{
  "maxLength": 150
}
```

requestType

string , Indicates the type of request to which the rule applies. Possible values: **authorization**, **authentication**, **tokenization**.

```
{
  "enum": [
    "authentication",
    "authorization",
    "tokenization"
  ],
  "x-addedInVersion": "2"
}
```

ruleRestrictions

Required,

See referenced schema [TransactionRuleRestrictions](#)

```
{
  "x-addedInVersion": "2"
}
```

score

integer (format: int32), A positive or negative score applied to the transaction if it meets the conditions of the rule. Required when outcomeType is **scoreBased**. The value must be between **-100** and **100**.

```
{
  "format": "int32",
  "x-addedInVersion": "2"
}
```

startDate

string , The date when the rule will start to be evaluated, in ISO 8601 extended offset date-time format. For example, **2020-12-18T10:15:30+01:00**. If not provided when creating a transaction rule, the startDate is set to the date when the rule status is set to **active**.

status

string , The status of the transaction rule. If you provide a startDate in the request, the rule is automatically created with an **active** status. Possible values: **active**, **inactive**.

```
{
  "enum": [
    "active",
    "inactive"
  ]
}
```

type

Required, string , The [type of rule](#), which defines if a rule blocks transactions based on individual characteristics or accumulates data. Possible values: * **blockList**: decline a transaction when the conditions are met. * **maxUsage**: add the amount or number of transactions for the lifetime of a payment instrument, and then decline a transaction when the specified limits are met. * **velocity**: add the amount or number of transactions based on a specified time interval, and then decline a transaction when the specified limits are met.

```
{
  "enum": [
    "allowList",
    "blockList",
    "maxUsage",
    "velocity"
  ],
  "x-enum": [
    {
      "description": "The rule provides categories (such as country and MCC) where payments must be allowed.",
      "value": "allowList"
    },
    {
      "description": "The rule provides categories (such as country and MCC) where payments must be blocked.",
      "value": "blockList"
    },
    {
      "description": "The rule sets limits for the maximum amount or maximum number of transactions for a given time interval.",
      "value": "velocity"
    },
    {
      "description": "The rule sets limits for the maximum amount or maximum number of transactions for the lifetime of the payment instrument.",
      "value": "maxUsage"
    }
  ]
}
```

TransactionRuleInterval

Type: object

Properties

Name	Description
dayOfMonth	integer (format: int32), The day of month, used when the duration.unit is months . If not provided, by default, this is set to 1 , the first day of the month.

```
{
  "format": "int32",
  "x-addedInVersion": "2"
}
```

dayOfWeek	string , The day of week, used when the <code>duration.unit</code> is weeks. If not provided, by default, this is set to monday. Possible values: sunday, monday, tuesday, wednesday, thursday, friday. <pre>{ "enum": ["friday", "monday", "saturday", "sunday", "thursday", "tuesday", "wednesday"], "x-addedInVersion": "2" }</pre>
duration	See referenced schema Duration <pre>{ "x-addedInVersion": "2" }</pre>
timeOfDay	string , The time of day, in hh:mm:ss format, used when the <code>duration.unit</code> is hours. If not provided, by default, this is set to 00:00:00. <pre>{ "x-addedInVersion": "2" }</pre>
timeZone	string , The time zone. For example, Europe/Amsterdam. By default, this is set to UTC. <pre>{ "x-addedInVersion": "2" }</pre>
type	Required, string , The type of interval during which the rule conditions and limits apply, and how often counters are reset. Possible values: * perTransaction: conditions are evaluated and the counters are reset for every transaction. * daily: the counters are reset daily at 00:00:00 UTC. * weekly: the counters are reset every Monday at 00:00:00 UTC. * monthly: the counters reset every first day of the month at 00:00:00 UTC. * lifetime: conditions are applied to the lifetime of the payment instrument. * rolling: conditions are applied and the counters are reset based on a <code>duration</code>. If the reset date and time are not provided, Adyen applies the default reset time similar to fixed intervals. For example, if the duration is every two weeks, the counter resets every third Monday at 00:00:00 UTC. * sliding: conditions are applied and the counters are reset based on the current time and a <code>duration</code> that you specify. <pre>{ "enum": ["daily", "lifetime", "monthly", "perTransaction", "rolling", "sliding", "weekly"] }</pre>

TransactionRuleResponse

Type: object	
Properties	
Name	Description
transactionRule	See referenced schema TransactionRule

TransactionRuleRestrictions

Type: object	
Properties	
Name	Description
activeNetworkTokens	See referenced schema ActiveNetworkTokensRestriction
brandVariants	See referenced schema BrandVariantsRestriction
countries	

	See referenced schema CountriesRestriction
dayOfWeek	
	See referenced schema DayOfWeekRestriction
differentCurrencies	
	See referenced schema DifferentCurrenciesRestriction
entryModes	
	See referenced schema EntryModesRestriction
internationalTransaction	
	See referenced schema InternationalTransactionRestriction
matchingTransactions	
	See referenced schema MatchingTransactionsRestriction
mccs	
	See referenced schema MccsRestriction
merchantNames	
	See referenced schema MerchantNamesRestriction
merchants	
	See referenced schema MerchantsRestriction
processingTypes	
	See referenced schema ProcessingTypesRestriction
timeOfDay	
	See referenced schema TimeOfDayRestriction
totalAmount	
	See referenced schema TotalAmountRestriction

TransactionRulesResponse

Type: object

Properties

Name	Description
transactionRules	array , List of transaction rules. See referenced schema TransactionRule

UKLocalAccountIdentification

Type: object

Example:

```
{
  "accountNumber": "stringst",
  "sortCode": "string",
  "type": "ukLocal"
}
```

Properties

Name	Description
accountNumber	Required , string , The 8-digit bank account number, without separators or whitespace. <pre>{ "maxLength": 8, "minLength": 8 }</pre>
sortCode	Required , string , The 6-digit sort code , without separators or whitespace. <pre>{ "maxLength": 6, "minLength": 6 }</pre>
type	Required , string , ukLocal

```
{
  "default": "ukLocal",
  "enum": [
    "ukLocal"
  ]
}
```

USLocalAccountIdentification

Type: object

Example:

```
{
  "accountNumber": "string",
  "accountType": "checking",
  "routingNumber": "stringstr",
  "type": "usLocal"
}
```

Properties

Name	Description
accountNumber	Required , string , The bank account number, without separators or whitespace. <pre>{ "maxLength": 18, "minLength": 2 }</pre>
accountType	string , The bank account type. Possible values: checking or savings . Defaults to checking . <pre>{ "default": "checking", "enum": ["checking", "savings"] }</pre>
routingNumber	Required , string , The 9-digit routing number , without separators or whitespace. <pre>{ "maxLength": 9, "minLength": 9 }</pre>
type	Required , string , usLocal <pre>{ "default": "usLocal", "enum": ["usLocal"] }</pre>

UpdatePaymentInstrument

Type: object

Properties

Name	Description
balanceAccountId	Required , string , The unique identifier of the balance account associated with the payment instrument.
bankAccount	undefined , Contains the business account details. Returned when you create a payment instrument with type bankAccount . <pre>{ "oneOf": [{ "\$ref": "#/components/schemas/IbanAccountIdentification" }, { "\$ref": "#/components/schemas/USLocalAccountIdentification" }] }</pre>
card	See referenced schema Card
description	string , Your description for the payment instrument, maximum 300 characters. <pre>{ "maxLength": 300 }</pre>
id	Required , string , The unique identifier of the payment instrument.
issuingCountryCode	

Required, string , The two-character [ISO 3166-1 alpha-2](#) country code where the payment instrument is issued. For example, **NL** or **US**.

paymentInstrumentGroupId string , The unique identifier of the [payment instrument group](#) to which the payment instrument belongs.

reference string , Your reference for the payment instrument, maximum 150 characters.

```
{
  "maxLength": 150
}
```

status string , The status of the payment instrument. If a status is not specified when creating a payment instrument, it is set to **active** by default. However, there can be exceptions for cards based on the `card.formFactor` and the `issuingCountryCode`. For example, when issuing physical cards in the US, the default status is **inactive**. Possible values: * **active**: The payment instrument is active and can be used to make payments. * **inactive**: The payment instrument is inactive and cannot be used to make payments. * **suspended**: The payment instrument is suspended, either because it was stolen or lost. * **closed**: The payment instrument is permanently closed. This action cannot be undone.

```
{
  "enum": [
    "active",
    "closed",
    "inactive",
    "suspended"
  ],
  "x-enum": [
    {
      "description": "The payment instrument is active and can be used to make payments.",
      "value": "active"
    },
    {
      "description": "The payment instrument is inactive and cannot be used to make payments.",
      "value": "inactive"
    },
    {
      "description": "The payment instrument is suspended. Either because it was stolen or lost.",
      "value": "suspended"
    },
    {
      "description": "The payment instrument is permanently closed. This action cannot be undone.",
      "value": "closed"
    }
  ]
}
```

statusComment string , Comment for the status of the payment instrument. Required if `statusReason` is **other**.

statusReason string , The reason for updating the status of the payment instrument. Possible values: **lost**, **stolen**, **damaged**, **suspectedFraud**, **expired**, **endOfLife**, **accountClosure**, **other**. If the reason is **other**, you must also send the `statusComment` parameter describing the status change.

```
{
  "enum": [
    "accountClosure",
    "damaged",
    "endOfLife",
    "expired",
    "lost",
    "other",
    "stolen",
    "suspectedFraud"
  ],
  "x-addedInVersion": "2"
}
```

type **Required**, string , Type of payment instrument. Possible value: **card**, **bankAccount**.

```
{
  "enum": [
    "bankAccount",
    "card"
  ]
}
```

VerificationDeadline

Type: object

Example:

```
{
  "capabilities": [
    "acceptExternalFunding"
  ],
  "expiresAt": "2019-08-24T14:15:22Z"
}
```

Properties

Name	Description
capabilities	Required , array , The names of the capabilities to be disallowed.
<pre>{ "items": { "enum": ["acceptExternalFunding", </pre>	

```

    "acceptPspFunding",
    "acceptTransactionInRestrictedCountries",
    "acceptTransactionInRestrictedCountriesCommercial",
    "acceptTransactionInRestrictedCountriesConsumer",
    "acceptTransactionInRestrictedIndustries",
    "acceptTransactionInRestrictedIndustriesCommercial",
    "acceptTransactionInRestrictedIndustriesConsumer",
    "acquiring",
    "atmWithdrawal",
    "atmWithdrawalCommercial",
    "atmWithdrawalConsumer",
    "atmWithdrawalInRestrictedCountries",
    "atmWithdrawalInRestrictedCountriesCommercial",
    "atmWithdrawalInRestrictedCountriesConsumer",
    "authorisedPaymentInstrumentUser",
    "getGrantOffers",
    "issueBankAccount",
    "issueCard",
    "issueCardCommercial",
    "issueCardConsumer",
    "localAcceptance",
    "payout",
    "payoutToTransferInstrument",
    "processing",
    "receiveFromBalanceAccount",
    "receiveFromPlatformPayments",
    "receiveFromThirdParty",
    "receiveFromTransferInstrument",
    "receiveGrants",
    "receivePayments",
    "sendToBalanceAccount",
    "sendToThirdParty",
    "sendToTransferInstrument",
    "thirdPartyFunding",
    "useCard",
    "useCardCommercial",
    "useCardConsumer",
    "useCardInRestrictedCountries",
    "useCardInRestrictedCountriesCommercial",
    "useCardInRestrictedCountriesConsumer",
    "useCardInRestrictedIndustries",
    "useCardInRestrictedIndustriesCommercial",
    "useCardInRestrictedIndustriesConsumer",
    "withdrawFromAtm",
    "withdrawFromAtmCommercial",
    "withdrawFromAtmConsumer",
    "withdrawFromAtmInRestrictedCountries",
    "withdrawFromAtmInRestrictedCountriesCommercial",
    "withdrawFromAtmInRestrictedCountriesConsumer"
  ],
  "type": "string"
},
"readOnly": true
}

```

See referenced schema [Items of capabilities](#)

expiresAt

Required, string (format: date-time), The date that verification is due by before capabilities are disallowed.

```

{
  "format": "date-time",
  "readOnly": true
}

```

Void

Type: object

Example:

```
{}
```

void

Type: object

Example:

```
{}
```

BrandVariantsRestriction_value

Type: string

Example:

```
"string"
```

CountriesRestriction_value

Type: string

Example:

```
"string"
```

DayOfWeekRestriction_value

Type: string

Example:

"friday"

EntryModesRestriction_value

Type: string

Example:

"barcode"

JSONPath_content

Type: string

Example:

"string"

MccsRestriction_value

Type: string

Example:

"string"

ProcessingTypesRestriction_value

Type: string

Example:

"atmWithdraw"

SweepConfigurationV2_priorities

Type: string

Example:

"crossBorder"

VerificationDeadline_capabilities

Type: string

Example:

"acceptExternalFunding"

