

Qooklet Booklet Mode

ivaquero

2026-07-27

By `epigraph()`, you can add a quote or a saying at the beginning of the book.

Preface

By `preface()`, you can add some information about the book.

This template is inspired by [haobook](#). The main difference is that `qooklet` does not provide side-note features like the ones that `haobook` builds with [marginalia](#).

This document serves both as a test document and a tutorial for the template. You can find the source code in `examples/example-book.typ`. The template is designed to be easy to customize for notes, short books, and scientific booklets.

ivaquero

Contents

1. FEATURES	1
1.1. Builtin Styles	1
1.2. Two Modes	2
1.3. Tweakable Config	2
1.4. Theorems	2
2. USAGE OF THE TEMPLATE	3
2.1. Importing the Template	3
2.2. Suggested Document Structure	4
3. SOME EXAMPLES	7
3.1. Bellman Equation	7
3.2. Bellman Optimal Equation	7
3.3. Case: Shortest Path of Islands	8
A. BIBLIOGRAPHY	11

Specifications

Features | 1

In this chapter, I will show you the features of this template.

1.1. Builtin Styles

The public structure helpers are:

- Styles:
 - `chapter(title: title, info: info)[body]`: Add a styled chapter.
 - `appendix(title: title, info: info)[body]`: Add a styled appendix.
 - `front-matter-style(body)`: Style for front matter pages.
- Pages:
 - `cover(info, date: datetime.today())`: Add a cover page to the document.
 - `epigraph(info: info)[body]`: Add an epigraph page to the document.
 - `preface(info: info)[body]`: Add a preface page to the document.
 - `part-page(title, info: info)`: Add a part divider page to the document.
 - `contents(depth: depth, info: info)`: Add a table of contents to the document.

1.2. Two Modes

The default mode is note mode, when `cover()` is called the booklet mode will be activated.

1.3. Tweakable Config

The `info` argument in `cover()`, `preface()`, `contents()`, `part-page()`, `chapter()`, and `appendix()` lets you customize document metadata through a TOML file. If you leave it unspecified, Qooklet uses the empty default metadata from `config/info.toml`.

Read your info file like this:

```
1 #let info = toml("your path").key-you-like
```

The toml file should look like this

```
1 [key-you-like]
2   title = "Your Booklet Name"
3   author = "Your Name"
4   footer = "Some Info You Want to Show"
5   header = "Some Info You Want to Show"
6   lang = "en" # or "zh"
```

1.4. Theorems

The theorem environment is implemented by [theorion](#).

Usage of the Template | 2

The template is designed to be easy to use. You can use it to create a booklet or a note with a beautiful layout.

2.1. Importing the Template

To use the published template, import it from Typst Universe:

```
1 #import "@preview/qooklet:0.6.2": *
```

For local development, clone the repository to your @local workspace:

- Linux:
 - \$XDG_DATA_HOME/typst/packages/local
 - ~/.local/share/typst/packages/local
- macOS: ~/Library/Application\ Support/typst/packages/local
- Windows: %APPDATA%/typst/packages/local

```
1 #import "@local/qooklet:0.1.0": *
```

2.2. Suggested Document Structure

Overall, your document should be structured like this:

```
1  #import "@local/qooklet:0.1.0": *
2
3  #let info = toml("../0.1.0/src/config/info.toml").example
4
5  // add a cover
6  #cover(info, date: datetime.today())
7
8  #epigraph(info: info)[
9    // Add an epigraph to the document.
10 ]
11
12 #preface(info: info)[
13   // Add a preface to the document.
14 ]
15
16 #contents(depth: 2, info: info)
17
18 #part-page("Main Text", info: info)
19
20 // body
21 #chapter(
22   title: "Chapter Title 1",
23   info: info,
24 )[
25   ...
26 ]
27
28 #chapter(
29   title: "Chapter Title 2",
30   info: info,
31 )[
32   ...
33 ]
34
35 // appendix
36 #part-page("Appendix", info: info)
37
```

```
38 #appendix(  
39   title: "Appendix Title 1",  
40   info: info,  
41 ) [  
42   ...  
43 ]  
44  
45 #appendix(  
46   title: "Appendix Title 2",  
47   info: info,  
48 ) [  
49   ...  
50 ]
```


Some Examples | 3

3.1. Bellman Equation

Definition 1 (Bellman Equation).

...

$$\begin{aligned} v_{\pi}(s) &= \mathbb{E}[R_{t+1}|S_t = s] + \gamma \mathbb{E}[G_{t+1}|S_t = s], \\ &= \sum_{a \in \mathcal{A}} \pi(a|s) \sum_{r \in \mathcal{R}} p(r|s, a) + \gamma \sum_{a \in \mathcal{A}} \pi(a|s) \sum_{s' \in \mathcal{S}} p(s'|s, a) v_{\pi}(s') \\ &= \sum_{a \in \mathcal{A}} \pi(a|s) \left[\sum_{r \in \mathcal{R}} p(r|s, a) r + \gamma \sum_{s' \in \mathcal{S}} p(s'|s, a) v_{\pi}(s') \right], \forall s \in \mathcal{S} \end{aligned} \tag{3.2}$$

3.2. Bellman Optimal Equation

By Eq. Eq. (3.2),...

$$\begin{aligned}
v(s) &= \max_{\pi(s) \in \Pi(s)} \sum_{a \in \mathcal{A}} \pi(a|s) \left(\sum_{r \in \mathcal{R}} p(r|s, a) r + \gamma \sum_{s' \in \mathcal{S}} p(s'|s, a) v(s') \right), \quad \forall s \in \mathcal{S} \\
&= \max_{\pi(s) \in \Pi(s)} \sum_{a \in \mathcal{A}} \pi(a|s) q(s, a), \quad \forall s \in \mathcal{S}
\end{aligned} \tag{3.2}$$

3.3. Case: Shortest Path of Islands

```

1 #let csv1 = csv("islands.csv")
2 #figure(
3   tableq(csv1, 9, inset: 0.31em),
4   caption: "Geographic Info of Islands",
5   supplement: "Table",
6   kind: table,
7 )

```

Table 1 Geographic Info of Islands

culture	population	contact	total_tools	mean_TU	lat	lon	lon2	logpop
Malekula	1100	low	13	3.2	-16.3	167.5	-12.5	7.00
Tikopia	1500	low	22	4.7	-12.3	168.8	-11.2	7.31
Santa Cruz	3600	low	24	4	-10.7	166	-14	8.19
Yap	4791	high	43	5	9.5	138.1	-41.9	8.47
Lau Fiji	7400	high	33	5	-17.7	178.1	-1.9	8.91
Trobriand	8000	high	19	4	-8.7	150.9	-29.1	8.99
Chuuk	9200	high	40	3.8	7.4	151.6	-28.4	9.13
Manus	13000	low	28	6.6	-2.1	146.9	-33.1	9.47
Tonga	17500	high	55	5.4	-21.2	-175.2	4.8	9.77
Hawaii	275000	low	71	6.6	19.9	-155.6	24.4	12.52

Appendix

Bibliography | **A**